conda

Release 24.3.1.dev75

Anaconda, Inc.

Apr 25, 2024

CONTENTS

1	Install	3
2	New to conda?	5
3	Other useful resources	7
4	Contributors welcome	9
Python Module Index		733
Index		737

Welcome to conda's documentation! Conda provides package, dependency, and environment management for any language. Here, you will find everything you need to get started using conda in your own projects.

ONE

INSTALL

We recommend the following methods to install conda:

Windows

Miniconda installer for:

Windows x86 64-bit

macOS

Miniconda installer for: macOS x86 64-bit macOS M1 64-bit

Linux

Miniconda installer for:

Linux x86 64-bit

Homebrew

Run the following Homebrew command:

brew install miniconda

NEW TO CONDA?

If you are new to conda, we first recommend the following articles:

Getting started guide Learn the basics of using conda such as creating and adding packages to environments

Managing environments Learn more about environments and best practices for using them in your projects

See also:

Want to get even more in-depth training on how to use conda for free? Check out Anaconda's free course on conda basics.

THREE

OTHER USEFUL RESOURCES

Command reference Full reference for all standard commands and options Cheatsheets Get the latest cheatsheet for commonly used commands Configuring conda Learn about the various ways conda's behavior can be configured Glossary Important vocabulary to know when working with conda

CONTRIBUTORS WELCOME

Conda is an open source project and always welcomes new contributions. Please read the following guides to get started developing conda and making your own contributions.

Contributing 101 Learn more about how the conda project is managed and how to contribute

Development environment Follow this guide to get your own development environment set up

4.1 User guide

4.1.1 Getting started with conda

Conda is a powerful command line tool for package and environment management that runs on Windows, macOS, and Linux.

This guide to getting started with conda goes over the basics of starting up and using conda to create environments and install packages.

Tip: Anaconda Navigator is a graphical desktop application that enables you to use conda without having to run commands at the command line.

See Getting started with Anaconda Navigator to learn more.

Before you start

You should have already installed conda before beginning this getting started guide. Conda can be found in many distributions, like Anaconda Distribution, Miniconda or Miniforge.

Starting conda

Conda is available on Windows, macOS, or Linux and can be used with any terminal application (or shell).

Windows

1. Open either the Command Prompt (cmd.exe) or PowerShell.

macOS

- 1. Open Launchpad.
- 2. Open the Other application folder.
- 3. Open the Terminal application.

Linux

Open a terminal window.

Creating environments

Conda allows you to create separate environments, each containing their own files, packages, and package dependencies. The contents of each environment do not interact with each other.

The most basic way to create a new environment is with the following command:

conda create -n <env-name>

To add packages while creating an environment, specify them after the environment name:

```
conda create -n myenvironment python numpy pandas
```

For more information on working with environments, see Managing environments.

Listing environments

To see a list of all your environments:

conda info --envs

A list of environments appears, similar to the following:

```
conda environments:
base /home/username/Anaconda3
myenvironment * /home/username/Anaconda3/envs/myenvironment
```

Tip: The active environment is the one with an asterisk (*).

To change your current environment back to the default base:

conda activate

Tip: When the environment is deactivated, its name is no longer shown in your prompt, and the asterisk (*) returns to base. To verify, you can repeat the conda info --envs command.

Installing packages

You can also install packages into a previously created environment. To do this, you can either activate the environment you want to modify or specify the environment name on the command line:

```
# via environment activation
conda activate myenvironment
conda install matplotlib
# via command line option
conda install --name myenvironment matplotlib
```

For more information on searching for and installing packages, see Managing packages.

Specifying channels

Channels are locations (on your own computer or elsewhere on the Internet) where packages are stored. By default, conda searches for packages in its *default channels*.

If a package you want is located in another channel, such as conda-forge, you can manually specify the channel when installing the package:

conda install conda-forge::numpy

You can also override the default channels in your *.condarc* file. For a direct example, see *Channel locations* (*channels*) or read the entire *Using the .condarc conda configuration file*.

Tip: Find more packages and channels by searching Anaconda.org.

Updating conda

To see your conda version, use the following command:

conda --version

No matter which environment you run this command in, conda displays its current version:

conda 23.10.0

Note: If you get an error message command not found: conda, close and reopen your terminal window and verify that you are logged into the same user account that you used to install conda.

To update conda to the latest version:

conda update conda

Conda compares your version to the latest available version and then displays what is available to install.

Tip: We recommend that you always keep conda updated to the latest version. For conda's official version support policy, see CEP 10.

More information

- Conda cheat sheet
- Full documentation
- Free community support

4.1.2 Installing conda

To install conda, you must first pick the right installer for you. The following are the most popular installers currently available:

Miniconda

Miniconda is a minimal installer provided by Anaconda. Use this installer if you want to install most packages yourself.

Anaconda Distribution

Anaconda Distribution is a full featured installer that comes with a suite of packages for data science, as well as Anaconda Navigator, a GUI application for working with conda environments.

Miniforge

Miniforge is an installer maintained by the conda-forge community that comes preconfigured for use with the conda-forge channel. To learn more about conda-forge, visit their website.

Tip

If you are just starting out, we recommend installing conda via the Miniconda installer.

System requirements

- A supported operating systems: Windows, macOS, or Linux
- For Miniconda or Miniforge: 400 MB disk space
- For Anaconda: Minimum 3 GB disk space to download and install
- For Windows: Windows 8.1 or newer for Python 3.9, or Windows Vista or newer for Python 3.8

Tip

You do not need administrative or root permissions to install conda if you select a user-writable install location (e.g. /Users/my-username/conda or C:\Users\my-username\conda).

Regular installation

Follow the instructions for your operating system:

- Windows
- *macOS*
- Linux

Installing in silent mode

You can use *silent installation* of Miniconda, Anaconda, or Miniforge for deployment or testing or building services, such as GitHub Actions.

Follow the silent-mode instructions for your operating system:

- Windows
- macOS
- Linux

Cryptographic hash verification

SHA-256 checksums are available for Miniconda and Anaconda Distribution. We do not recommend using MD5 verification as SHA-256 is more secure.

Download the installer file and, before installing, verify it as follows:

- Windows:
 - If you have PowerShell V4 or later:

Open a PowerShell console and verify the file as follows:

Get-FileHash filename -Algorithm SHA256

- If you don't have PowerShell V4 or later:

Use the free online verifier tool on the Microsoft website.

- 1. Download the file and extract it.
- 2. Open a Command Prompt window.
- 3. Navigate to the file.
- 4. Run the following command:

Start-PsFCIV -Path C:\path\to\file.ext -HashAlgorithm SHA256 -Online

- macOS: In iTerm or a terminal window enter shasum -a 256 filename.
- Linux: In a terminal window enter sha256sum filename.

Installing on Windows

- 1. Download the installer:
 - Miniconda installer for Windows
 - Anaconda Distribution installer for Windows
 - Miniforge installer for Windows
- 2. Verify your installer hashes.
- 3. Double-click the .exe file.
- 4. Follow the instructions on the screen.

If you are unsure about any setting, accept the defaults. You can change them later.

When installation is finished, from the Start menu, open either Command Prompt (cmd.exe) or PowerShell

5. Test your installation. In your terminal window, run the command conda list. A list of installed packages appears if it has been installed correctly.

Installing in silent mode

Note: The following instructions are for Miniconda but should also work for the Anaconda Distribution or Miniforge installers.

Note: As of Anaconda Distribution 2022.05 and Miniconda 4.12.0, the option to add Anaconda to the PATH environment variable during an **All Users** installation has been disabled. This was done to address a security exploit. You can still add Anaconda to the PATH environment variable during a **Just Me** installation.

To run the the Windows installer for Miniconda in *silent mode*, use the /S argument. The following optional arguments are supported:

- /InstallationType=[JustMe|AllUsers]---Default is JustMe.
- /AddToPath=[0|1]---Default is 0
- /RegisterPython=[0|1]---Make this the system's default Python. 0 indicates Python won't be registered as the system's default. 1 indicates Python will be registered as the system's default.
- /S---Install in silent mode.
- /D=<installation path>---Destination installation path. Must be the last argument. Do not wrap in quotation marks. Required if you use /S.

All arguments are case-sensitive.

Example: The following command installs Miniconda for the current user without registering Python as the system's default:

start /wait "" Miniconda3-latest-Windows-x86_64.exe /InstallationType=JustMe /
→RegisterPython=0 /S /D=%UserProfile%\Miniconda3

Updating conda

- 1. Open Command Prompt or PowerShell from the start menu.
- 2. Run conda update conda.

Uninstalling conda

- 1. In the Windows Control Panel, click Add or Remove Program.
- 2. Select Python X.X (Miniconda), where X.X is your version of Python.
- 3. Click Remove Program.

Note: Removing a program is different in Windows 10.

Installing on macOS

Caution: If you use the .pkg installer for Miniconda, beware that those installers may skip the "Destination Select" page which will cause the installation to fail. If the installer skips this page, click "Change Install Location..." on the "Installation Type" page, choose a location for your install, and then click Continue.

- 1. Download the installer:
 - Miniconda installer for macOS.
 - Anaconda installer for macOS.
 - Miniforge installer for macOS.
- 2. Verify your installer hashes.
- 3. Install:
 - Miniconda or Miniforge: in your terminal window, run:

bash <conda-installer-name>-latest-MacOSX-x86_64.sh

- Anaconda Distribution: double-click the .pkg file.
- 4. Follow the prompts on the installer screens. If you are unsure about any setting, accept the defaults. You can change them later.
- 5. To make the changes take effect, close and then re-open your terminal window.
- 6. To verify your installation, in your terminal window, run the command conda list. A list of installed packages appears if it has been installed correctly.

Installing in silent mode

Note: The following instructions are for Miniconda but should also work for the Anaconda Distribution or Miniforge installers.

To run the *silent installation* of Miniconda for macOS or Linux, specify the -b and -p arguments of the bash installer. The following arguments are supported:

- -b: Batch mode with no PATH modifications to shell scripts. Assumes that you agree to the license agreement. Does not edit shell scripts such as .bashrc, .bash_profile, .zshrc, etc.
- -p: Installation prefix/path.
- -f: Force installation even if prefix -p already exists.

Example

```
wget https://repo.anaconda.com/miniconda/Miniconda3-latest-MacOSX-x86_64.sh -0 ~/

→miniconda.sh

bash ~/miniconda.sh -b -p $HOME/miniconda
```

Note: In order to initialize after the installation process is done, first run source <path to conda>/bin/activate and then run conda init --all.

Updating Anaconda or Miniconda

- 1. Open a terminal window.
- 2. Run conda update conda.

Uninstalling Anaconda or Miniconda

- 1. Open a terminal window.
- 2. Remove the entire Miniconda install directory with (this may differ depending on your installation location)

```
rm -rf ~/miniconda
```

- 3. Optional: run conda init --reverse --all to undo changes to shell initialization scripts
- 4. Optional: remove the following hidden file and folders that may have been created in the home directory:
 - .condarc file
 - .conda directory
 - .continuum directory

By running:

rm -rf ~/.condarc ~/.continuum

Installing on Linux

- 1. Download the installer:
 - Miniconda installer for Linux.
 - Anaconda Distribution installer for Linux.
 - Miniforge installer for Linux.
- 2. Verify your installer hashes.
- 3. In your terminal window, run:

 $bash <\!conda-installer-name>-latest-Linux-x86_64.sh$

conda-installer-name will be one of "Miniconda3", "Anaconda", or "Miniforge3".

- 4. Follow the prompts on the installer screens. If you are unsure about any setting, accept the defaults. You can change them later.
- 5. To make the changes take effect, close and then re-open your terminal window.
- 6. Test your installation. In your terminal window, run the command conda list. A list of installed packages appears if it has been installed correctly.

Using with fish shell

To use conda with fish shell, run the following in your terminal:

Add conda binary to \$PATH, if not yet added:

fish_add_path <conda-install-location>/condabin

Configure fish-shell:

conda init fish

Installing in silent mode

See the instructions for *installing in silent mode on macOS*.

Updating conda

- 1. Open a terminal window.
- 2. Run conda update conda.

Uninstalling conda

- 1. Open a terminal window.
- 2. Remove the entire conda install directory with (this may differ depending on your installation location)

rm -rf \sim /conda

- 3. Optional: run conda init --reverse --all to undo changes to shell initialization scripts
- 4. Optional: remove the following hidden file and folders that may have been created in the home directory:
 - .condarc file
 - .conda directory
 - .continuum directory

By running:

```
rm -rf ~/.condarc ~/.conda ~/.continuum
```

RPM and Debian Repositories for Miniconda

Conda is available as either a RedHat RPM or as a Debian package. The packages are the equivalent to the Miniconda installer, which only contains conda and its dependencies. You can use yum or apt to install, uninstall, and manage conda on your system. To install conda, follow the instructions for your Linux distribution.

To install the RPM on RedHat, CentOS, Fedora distributions, and other RPM-based distributions, such as openSUSE, download the GPG key and add a repository configuration file for conda.

```
# Import our GPG public key
rpm --import https://repo.anaconda.com/pkgs/misc/gpgkeys/anaconda.asc
# Add the Anaconda repository
cat <<EOF > /etc/yum.repos.d/conda.repo
[conda]
name=Conda
baseurl=https://repo.anaconda.com/pkgs/misc/rpmrepo/conda
enabled=1
gpgcheck=1
gpgcheck=1
gpgkey=https://repo.anaconda.com/pkgs/misc/gpgkeys/anaconda.asc
EOF
```

Conda is ready to install on your RPM-based distribution.

```
# Install it!
yum install conda
Loaded plugins: fastestmirror, ovl
Setting up Install Process
Loading mirror speeds from cached hostfile
 * base: repol.dal.innoscale.net
 * extras: mirrordenver.fdcservers.net
 * updates: mirror.tzulo.com
Resolving Dependencies
--> Running transaction check
```

(continues on next page)

(continued from previous page)

> Package conda.x86_64 0:4.5.11-0 will be installed > Finished Dependency Resolution							
Dependencies Resolved							
		=======================================					
Package	Arch	Version	Repository	Size			
Installing:							
conda	x86_64	4.5.11-0	conda	73 M			
Transaction Summary							
Install 1	Package(s)						
Total download size: 73 M							
Installed size: 210 M Is this ok [v/N]:							
IS CHIS OK LY/NJ.							

To install on Debian-based Linux distributions, such as Ubuntu, download the public GPG key and add the conda repository to the sources list.

```
# Install our public GPG key to trusted store
curl https://repo.anaconda.com/pkgs/misc/gpgkeys/anaconda.asc | gpg --dearmor > conda.gpg
install -o root -g root -m 644 conda.gpg /usr/share/keyrings/conda-archive-keyring.gpg
# Check whether fingerprint is correct (will output an error message otherwise)
gpg --keyring /usr/share/keyrings/conda-archive-keyring.gpg --no-default-keyring --
# Add our Debian repo
echo "deb [arch=amd64 signed-by=/usr/share/keyrings/conda-archive-keyring.gpg] https://
→repo.anaconda.com/pkgs/misc/debrepo/conda stable main" > /etc/apt/sources.list.d/conda.
⊣list
**NB:** If you receive a Permission denied error when trying to run the above command.
→ (because `/etc/apt/sources.list.d/conda.list` is write protected), try using the
\rightarrow following command instead:
echo "deb [arch=amd64 signed-by=/usr/share/keyrings/conda-archive-keyring.gpg] https://
-repo.anaconda.com/pkgs/misc/debrepo/conda stable main" | sudo tee -a /etc/apt/sources.
→list.d/conda.list
```

Conda is ready to install on your Debian-based distribution.

```
# Install it!
apt update
apt install conda
Reading package lists... Done
Building dependency tree
```

(continues on next page)

(continued from previous page)

```
Reading state information... Done
The following NEW packages will be installed:
conda
0 upgraded, 1 newly installed, 0 to remove and 3 not upgraded.
Need to get 76.3 MB of archives.
After this operation, 221 MB of additional disk space will be used.
Get:1 https://repo.anaconda.com/pkgs/misc/debrepo/conda stable/main amd64
conda amd64 4.5.11-0 [76.3 MB]
Fetched 76.3 MB in 10s (7733 kB/s)
debconf: delaying package configuration, since apt-utils is not installed
Selecting previously unselected package conda.
(Reading database ... 4799 files and directories currently installed.)
Preparing to unpack .../conda_4.5.11-0_amd64.deb ...
Unpacking conda (4.5.11-0) ...
Setting up conda (4.5.11-0) ...
```

Check to see if the installation is successful by typing:

source /opt/conda/etc/profile.d/conda.sh
conda -V
conda 4.5.11

Installing conda packages with the system package manager makes it very easy to distribute conda across a cluster of machines running Linux without having to worry about any non-privileged user modifying the installation. Any non-privileged user simply needs to run source /opt/conda/etc/profile.d/conda.sh to use conda.

Administrators can also distribute a .condarc file at /opt/conda/.condarc so that a predefined configuration for channels, package cache directory, and environment locations is pre-seeded to all users in a large organization. A sample configuration could look like:

```
channels:
  - defaults
pkg_dirs:
  - /shared/conda/pkgs
  - $HOME/.conda/pkgs
envs_dirs:
  - /shared/conda/envs
  - $HOME/.conda/envs
```

These RPM and Debian packages also provide another way to set up conda inside a Docker container.

Tip

It is recommended to use this installation method in a read-only manner and upgrade conda using the respective package manager only.

4.1.3 Tasks

Managing conda

Verifying that conda is installed

To verify that conda is installed, in your terminal window, run:

conda --version

Conda responds with the version number that you have installed, such as conda 4.12.0.

If you get an error message, make sure of the following:

- You are logged into the same user account that you used to install Anaconda or Miniconda.
- You are in a directory that Anaconda or Miniconda can find.
- You have closed and re-opened the terminal window after installing conda.

Determining your conda version

In addition to the conda --version command explained above, you can determine what conda version is installed by running one of the following commands in your terminal window:

conda info OR conda -V

Updating conda to the current version

To update conda, in your terminal window, run:

conda update conda

Conda compares versions and reports what is available to install. It also tells you about other packages that will be automatically updated or changed with the update. If conda reports that a newer version is available, type y to update:

Proceed ([y]/n)? y

Suppressing warning message about updating conda

To suppress the following warning message when you do not want to update conda to the latest version:

```
==> WARNING: A newer version of conda exists. <==
current version: 4.6.13
latest version: 4.8.0
```

Update conda by running: conda update -n base conda

Run the following command from your terminal: conda config --set notify_outdated_conda false

Or add the following line in your .condarc file: notify_outdated_conda: false

Managing environments

With conda, you can create, export, list, remove, and update environments that have different versions of Python and/or packages installed in them. Switching or moving between environments is called activating the environment. You can also share an environment file.

There are many options available for the commands described on this page. For a detailed reference on all available commands, see *commands*.

Creating an environment with commands

Use the terminal for the following steps:

1. To create an environment:

conda create --name <my-env>

Replace <my-env> with the name of your environment.

2. When conda asks you to proceed, type y:

proceed ([y]/n)?

This creates the myenv environment in /envs/. No packages will be installed in this environment.

3. To create an environment with a specific version of Python:

conda create -n myenv python=3.9

4. To create an environment with a specific package:

conda create -n myenv scipy

or:

conda create -n myenv python
conda install -n myenv scipy

5. To create an environment with a specific version of a package:

```
conda create -n myenv scipy=0.17.3
```

or:

```
conda create -n myenv python
conda install -n myenv scipy=0.17.3
```

6. To create an environment with a specific version of Python and multiple packages:

```
conda create -n myenv python=3.9 scipy=0.17.3 astroid babel
```

Tip: Install all the programs that you want in this environment at the same time. Installing one program at a time can lead to dependency conflicts.

To automatically install pip or another program every time a new environment is created, add the default programs to the *create_default_packages* section of your .condarc configuration file. The default packages are installed every time you create a new environment. If you do not want the default packages installed in a particular environment, use the --no-default-packages flag:

conda create --no-default-packages -n myenv python

Tip: You can add much more to the conda create command. For details, run conda create --help.

Creating an environment from an environment.yml file

Use the terminal for the following steps:

1. Create the environment from the environment.yml file:

conda env create -f environment.yml

The first line of the yml file sets the new environment's name. For details see *Creating an environment file manually*.

- 2. Activate the new environment: conda activate myenv
- 3. Verify that the new environment was installed correctly:

conda env list

You can also use conda info --envs.

Specifying a location for an environment

You can control where a conda environment lives by providing a path to a target directory when creating the environment. For example, the following command will create a new environment in a subdirectory of the current working directory called **envs**:

conda create --prefix ./envs jupyterlab=3.2 matplotlib=3.5 numpy=1.21

You then activate an environment created with a prefix using the same command used to activate environments created by name:

```
conda activate ./envs
```

Specifying a path to a subdirectory of your project directory when creating an environment has the following benefits:

- It makes it easy to tell if your project uses an isolated environment by including the environment as a subdirectory.
- It makes your project more self-contained as everything, including the required software, is contained in a single project directory.

An additional benefit of creating your project's environment inside a subdirectory is that you can then use the same name for all your environments. If you keep all of your environments in your envs folder, you'll have to give each environment a different name.

There are a few things to be aware of when placing conda environments outside of the default envs folder.

- 1. Conda can no longer find your environment with the --name flag. You'll generally need to pass the --prefix flag along with the environment's full path to find the environment.
- 2. Specifying an install path when creating your conda environments makes it so that your command prompt is now prefixed with the active environment's absolute path rather than the environment's name.

After activating an environment using its prefix, your prompt will look similar to the following:

(/absolute/path/to/envs) \$

This can result in long prefixes:

```
(/Users/USER_NAME/research/data-science/PROJECT_NAME/envs) $
```

To remove this long prefix in your shell prompt, modify the env_prompt setting in your .condarc file:

conda config --set env_prompt '({name})'

This will edit your .condarc file if you already have one or create a .condarc file if you do not.

Now your command prompt will display the active environment's generic name, which is the name of the environment's root folder:

```
$ cd project-directory
$ conda activate ./env
(env) project-directory $
```

Updating an environment

You may need to update your environment for a variety of reasons. For example, it may be the case that:

- one of your core dependencies just released a new version (dependency version number update).
- you need an additional package for data analysis (add a new dependency).
- you have found a better package and no longer need the older package (add new dependency and remove old dependency).

If any of these occur, all you need to do is update the contents of your environment.yml file accordingly and then run the following command:

conda env update --file environment.yml --prune

Note: The --prune option causes conda to remove any dependencies that are no longer required from the environment.

Cloning an environment

Use the terminal for the following steps:

You can make an exact copy of an environment by creating a clone of it:

```
conda create --name myclone --clone myenv
```

Note: Replace myclone with the name of the new environment. Replace myenv with the name of the existing environment that you want to copy.

To verify that the copy was made:

conda info --envs

In the environments list that displays, you should see both the source environment and the new copy.

Building identical conda environments

You can use explicit specification files to build an identical conda environment on the same operating system platform, either on the same machine or on a different machine.

Use the terminal for the following steps:

1. Run conda list --explicit to produce a spec list such as:

```
# This file may be used to create an environment using:
# $ conda create --name <env> --file <this file>
# platform: osx-64
@EXPLICIT
https://repo.anaconda.com/pkgs/free/osx-64/mkl-11.3.3-0.tar.bz2
https://repo.anaconda.com/pkgs/free/osx-64/numpy-1.11.1-py35_0.tar.bz2
https://repo.anaconda.com/pkgs/free/osx-64/openssl-1.0.2h-1.tar.bz2
https://repo.anaconda.com/pkgs/free/osx-64/pip-8.1.2-py35_0.tar.bz2
https://repo.anaconda.com/pkgs/free/osx-64/python-3.5.2-0.tar.bz2
https://repo.anaconda.com/pkgs/free/osx-64/readline-6.2-2.tar.bz2
https://repo.anaconda.com/pkgs/free/osx-64/setuptools-25.1.6-py35_0.tar.bz2
https://repo.anaconda.com/pkgs/free/osx-64/sqlite-3.13.0-0.tar.bz2
https://repo.anaconda.com/pkgs/free/osx-64/tk-8.5.18-0.tar.bz2
https://repo.anaconda.com/pkgs/free/osx-64/wheel-0.29.0-py35_0.tar.bz2
https://repo.anaconda.com/pkgs/free/osx-64/xz-5.2.2-0.tar.bz2
https://repo.anaconda.com/pkgs/free/osx-64/zlib-1.2.8-3.tar.bz2
```

2. To create this spec list as a file in the current working directory, run:

conda list --explicit > spec-file.txt

Note: You can use spec-file.txt as the filename or replace it with a filename of your choice.

An explicit spec file is not usually cross platform, and therefore has a comment at the top such as # platform: osx-64 showing the platform where it was created. This platform is the one where this spec file is known to

work. On other platforms, the packages specified might not be available or dependencies might be missing for some of the key packages already in the spec.

To use the spec file to create an identical environment on the same machine or another machine:

conda create --name myenv --file spec-file.txt

To use the spec file to install its listed packages into an existing environment:

```
conda install --name myenv --file spec-file.txt
```

Conda does not check architecture or dependencies when installing from a spec file. To ensure that the packages work correctly, make sure that the file was created from a working environment, and use it on the same architecture, operating system, and platform, such as linux-64 or osx-64.

Activating an environment

Activating environments is essential to making the software in the environments work well. Activation entails two primary functions: adding entries to PATH for the environment and running any activation scripts that the environment may contain. These activation scripts are how packages can set arbitrary environment variables that may be necessary for their operation. You can also *use the config API to set environment variables*.

Activation prepends to PATH. This only takes effect when you have the environment active so it is local to a terminal session, not global.

Note: When installing Anaconda, you have the option to "Add Anaconda to my PATH environment variable." *This is not recommended* because it *appends* Anaconda to PATH. When the installer appends to PATH, it does not call the activation scripts.

Note: On Windows, PATH is composed of two parts, the *system* PATH and the *user* PATH. The system PATH always comes first. When you install Anaconda for "Just Me", we add it to the *user* PATH. When you install for "All Users", we add it to the *system* PATH. In the former case, you can end up with system PATH values taking precedence over your entries. In the latter case, you do not. *We do not recommend* multi-user installs.

To activate an environment: conda activate myenv

Note: Replace myenv with the environment name or directory path.

Conda prepends the path name myenv onto your system command.

You may receive a warning message if you have not activated your environment:

Warning:

This Python interpreter is in a conda environment, but the environment has not been activated. Libraries may fail to load. To activate this environment please see https://conda.io/activation.

If you receive this warning, you need to activate your environment. To do so on Windows, run: c:\Anaconda3\ Scripts\activate base in a terminal window. Windows is extremely sensitive to proper activation. This is because the Windows library loader does not support the concept of libraries and executables that know where to search for their dependencies (RPATH). Instead, Windows relies on a dynamic-link library search order.

If environments are not active, libraries won't be found and there will be lots of errors. HTTP or SSL errors are common errors when the Python in a child environment can't find the necessary OpenSSL library.

Conda itself includes some special workarounds to add its necessary PATH entries. This makes it so that it can be called without activation or with any child environment active. In general, calling any executable in an environment without first activating that environment will likely not work. For the ability to run executables in activated environments, you may be interested in the conda run command.

If you experience errors with PATH, review our troubleshooting.

Conda init

Earlier versions of conda introduced scripts to make activation behavior uniform across operating systems. Conda 4.4 allowed conda activate myenv. Conda 4.6 added extensive initialization support so that conda works faster and less disruptively on a wide variety of shells (bash, zsh, csh, fish, xonsh, and more). Now these shells can use the conda activate command. Removing the need to modify PATH makes conda less disruptive to other software on your system. For more information, read the output from conda init --help.

One setting may be useful to you when using conda init is:

```
auto_activate_base: bool
```

This setting controls whether or not conda activates your base environment when it first starts up. You'll have the conda command available either way, but without activating the environment, none of the other programs in the environment will be available until the environment is activated with conda activate base. People sometimes choose this setting to speed up the time their shell takes to start up or to keep conda-installed software from automatically hiding their other software.

Nested activation

By default, conda activate will deactivate the current environment before activating the new environment and reactivate it when deactivating the new environment. Sometimes you may want to leave the current environment PATH entries in place so that you can continue to easily access command-line programs from the first environment. This is most commonly encountered when common command-line utilities are installed in the base environment. To retain the current environment in the PATH, you can activate the new environment using:

conda activate --stack myenv

If you wish to always stack when going from the outermost environment, which is typically the base environment, you can set the auto_stack configuration option:

conda config --set auto_stack 1

You may specify a larger number for a deeper level of automatic stacking, but this is not recommended since deeper levels of stacking are more likely to lead to confusion.

Environment variable for DLL loading verification

If you don't want to activate your environment and you want Python to work for DLL loading verification, then follow the *troubleshooting directions*.

Warning: If you choose not to activate your environment, then loading and setting environment variables to activate scripts will not happen. We only support activation.

Deactivating an environment

To deactivate an environment, type: conda deactivate

Conda removes the path name for the currently active environment from your system command.

Note: To simply return to the base environment, it's better to call conda activate with no environment specified, rather than to try to deactivate. If you run conda deactivate from your base environment, you may lose the ability to run conda at all. Don't worry, that's local to this shell - you can start a new one. However, if the environment was activated using --stack (or was automatically stacked) then it is better to use conda deactivate.

Determining your current environment

Use the terminal for the following steps.

By default, the active environment---the one you are currently using---is shown in parentheses () or brackets [] at the beginning of your command prompt:

(myenv) \$

If you do not see this, run:

conda info --envs

In the environments list that displays, your current environment is highlighted with an asterisk (*).

By default, the command prompt is set to show the name of the active environment. To disable this option:

```
conda config --set changeps1 false
```

To re-enable this option:

```
conda config --set changeps1 true
```

Viewing a list of your environments

To see a list of all of your environments, in your terminal window, run:

conda info --envs

OR

conda env list

A list similar to the following is displayed:

conda environments:					
myenv	/home/username/miniconda/envs/myenv				
snowflakes	/home/username/miniconda/envs/snowflakes				
bunnies	/home/username/miniconda/envs/bunnies				

If this command is run by an administrator, a list of all environments belonging to all users will be displayed.

Viewing a list of the packages in an environment

To see a list of all packages installed in a specific environment:

• If the environment is not activated, in your terminal window, run:

conda list -n myenv

• If the environment is activated, in your terminal window, run:

conda list

• To see if a specific package is installed in an environment, in your terminal window, run:

conda list -n myenv scipy

Using pip in an environment

To use pip in your environment, in your terminal window, run:

conda install -n myenv pip conda activate myenv pip <pip_subcommand>

Issues may arise when using pip and conda together. When combining conda and pip, it is best to use an isolated conda environment. Only after conda has been used to install as many packages as possible should pip be used to install any remaining software. If modifications are needed to the environment, it is best to create a new environment rather than running conda after pip. When appropriate, conda and pip requirements should be stored in text files.

We recommend that you:

Use pip only after conda

- Install as many requirements as possible with conda then use pip.
- Pip should be run with --upgrade-strategy only-if-needed (the default).

• Do not use pip with the --user argument, avoid all users installs.

Use conda environments for isolation

- Create a conda environment to isolate any changes pip makes.
- Environments take up little space thanks to hard links.
- Care should be taken to avoid running pip in the root environment.

Recreate the environment if changes are needed

- Once pip has been used, conda will be unaware of the changes.
- To install additional conda packages, it is best to recreate the environment.

Store conda and pip requirements in text files

- Package requirements can be passed to conda via the --file argument.
- Pip accepts a list of Python packages with -r or --requirements.
- Conda env will export or create environments based on a file with conda and pip requirements.

Setting environment variables

If you want to associate environment variables with an environment, you can use the config API. This is recommended as an alternative to using activate and deactivate scripts since those are an execution of arbitrary code that may not be safe.

First, create your environment and activate it:

```
conda create -n test-env
conda activate test-env
```

To list any variables you may have, run conda env config vars list.

To set environment variables, run conda env config vars set my_var=value.

Once you have set an environment variable, you have to reactivate your environment: conda activate test-env.

To check if the environment variable has been set, run echo my_var (echo my_var on Windows) or conda env config vars list.

When you deactivate your environment, you can use those same commands to see that the environment variable goes away.

You can specify the environment you want to affect using the -n and -p flags. The -n flag allows you to name the environment and -p allows you to specify the path to the environment.

To unset the environment variable, run conda env config vars unset my_var -n test-env.

When you deactivate your environment, you can see that environment variable goes away by rerunning echo my_var or conda env config vars list to show that the variable name is no longer present.

Environment variables set using conda env config vars will be retained in the output of conda env export. Further, you can declare environment variables in the environment.yml file as shown here:

(continues on next page)

(continued from previous page)

- python=3.7 - codecov variables: VAR1: valueA VAR2: valueB

Saving environment variables

Conda environments can include saved environment variables.

Suppose you want an environment "analytics" to store both a secret key needed to log in to a server and a path to a configuration file. The sections below explain how to write a script named env_vars to do this on *Windows* and *macOS* or *Linux*.

This type of script file can be part of a conda package, in which case these environment variables become active when an environment containing that package is activated.

You can name these scripts anything you like. However, multiple packages may create script files, so be sure to use descriptive names that are not used by other packages. One popular option is to give the script a name in the form packagename-scriptname.sh, or on Windows, packagename-scriptname.bat.

Windows

- 1. Locate the directory for the conda environment in your terminal window by running in the command shell %CONDA_PREFIX%.
- 2. Enter that directory and create these subdirectories and files:

```
cd %CONDA_PREFIX%
mkdir .\etc\conda\activate.d
mkdir .\etc\conda\deactivate.d
type NUL > .\etc\conda\activate.d\env_vars.bat
type NUL > .\etc\conda\deactivate.d\env_vars.bat
```

3. Edit .\etc\conda\activate.d\env_vars.bat as follows:

```
set MY_KEY='secret-key-value'
set MY_FILE=C:\path\to\my\file
```

4. Edit .\etc\conda\deactivate.d\env_vars.bat as follows:

set MY_KEY=
set MY_FILE=

When you run conda activate analytics, the environment variables MY_KEY and MY_FILE are set to the values you wrote into the file. When you run conda deactivate, those variables are erased.

macOS and Linux

- 1. Locate the directory for the conda environment in your terminal window by running in the terminal echo \$CONDA_PREFIX.
- 2. Enter that directory and create these subdirectories and files:

```
cd $CONDA_PREFIX
mkdir -p ./etc/conda/activate.d
mkdir -p ./etc/conda/deactivate.d
touch ./etc/conda/activate.d/env_vars.sh
touch ./etc/conda/deactivate.d/env_vars.sh
```

3. Edit ./etc/conda/activate.d/env_vars.sh as follows:

```
#!/bin/sh
export MY_KEY='secret-key-value'
export MY_FILE=/path/to/my/file/
```

4. Edit ./etc/conda/deactivate.d/env_vars.sh as follows:

```
#!/bin/sh
```

```
unset MY_KEY
unset MY_FILE
```

When you run conda activate analytics, the environment variables MY_KEY and MY_FILE are set to the values you wrote into the file. When you run conda deactivate, those variables are erased.

Sharing an environment

You may want to share your environment with someone else---for example, so they can re-create a test that you have done. To allow them to quickly reproduce your environment, with all of its packages and versions, give them a copy of your environment.yml file.

Exporting the environment.yml file

Note: If you already have an environment.yml file in your current directory, it will be overwritten during this task.

1. Activate the environment to export: conda activate myenv

Note: Replace myenv with the name of the environment.

2. Export your active environment to a new file:

conda env export > environment.yml

Note: This file handles both the environment's pip packages and conda packages.
3. Email or copy the exported environment.yml file to the other person.

Exporting an environment file across platforms

If you want to make your environment file work across platforms, you can use the conda env export --from-history flag. This will only include packages that you've explicitly asked for, as opposed to including every package in your environment.

For example, if you create an environment and install Python and a package:

conda install python=3.7 codecov

This will download and install numerous additional packages to solve for dependencies. This will introduce packages that may not be compatible across platforms.

If you use conda env export, it will export all of those packages. However, if you use conda env export --from-history, it will only export those you specifically chose:

```
(env-name) ~ conda env export --from-history
name: env-name
channels:
    - conda-forge
    - defaults
dependencies:
    - python=3.7
    - codecov
prefix: /Users/username/anaconda3/envs/env-name
```

Note: If you installed Anaconda 2019.10 on macOS, your prefix may be /Users/username/opt/envs/env-name.

Creating an environment file manually

You can create an environment file (environment.yml) manually to share with others.

EXAMPLE: A simple environment file:

name: stats dependencies: - numpy - pandas

EXAMPLE: A more complex environment file:

(continues on next page)

(continued from previous page)

- flaskpip
- pip - pip:
 - Flask-Testing

Note: Using wildcards

Note the use of the wildcard * when defining a few of the versions in the complex environment file. Keeping the major and minor versions fixed while allowing the patch to be any number allows you to use your environment file to get any bug fixes while still maintaining consistency in your environment. For more information on package installation values, see *Package search and install specifications*.

Specifying channels outside of "channels"

You may occasionally want to specify which channel conda will use to install a specific package. To accomplish this, use the *channel::package* syntax in *dependencies:*, as demonstrated above with *conda-forge::numpy* (version numbers optional). The specified channel does not need to be present in the *channels:* list, which is useful if you want some—but not *all*—packages installed from a community channel such as *conda-forge*.

You can exclude the default channels by adding nodefaults to the channels list.

channels:

- javascript
- nodefaults

This is equivalent to passing the --override-channels option to most conda commands.

Adding nodefaults to the channels list in environment.yml is similar to removing defaults from the *channels list* in the .condarc file. However, changing environment.yml affects only one of your conda environments while changing .condarc affects them all.

For details on creating an environment from this environment.yml file, see *Creating an environment from an environment.yml file*.

Restoring an environment

Conda keeps a history of all the changes made to your environment, so you can easily "roll back" to a previous version. To list the history of each change to the current environment: conda list --revisions

To restore environment to a previous revision: conda install --revision=REVNUM or conda install --rev REVNUM.

Note: Replace REVNUM with the revision number.

Example: If you want to restore your environment to revision 8, run conda install --rev 8.

Removing an environment

To remove an environment, in your terminal window, run:

conda remove --name myenv --all

You may instead use conda env remove --name myenv.

To verify that the environment was removed, in your terminal window, run:

conda info --envs

The environments list that displays should not show the removed environment.

Managing channels

Conda channels are the locations where packages are stored. They serve as the base for hosting and managing packages. Conda packages are downloaded from remote channels, which are URLs to directories containing conda packages. The conda command searches a default set of channels and packages are automatically downloaded and updated from the default channel. Read more about *conda channels* and the various terms of service for their use.

Different channels can have the same package, so conda must handle these channel collisions.

There will be no channel collisions if you use only the defaults channel. There will also be no channel collisions if all of the channels you use only contain packages that do not exist in any of the other channels in your list. The way conda resolves these collisions matters only when you have multiple channels in your channel list that host the same package.

By default, conda prefers packages from a higher priority channel over any version from a lower priority channel. Therefore, you can now safely put channels at the bottom of your channel list to provide additional packages that are not in the default channels and still be confident that these channels will not override the core package set.

Conda collects all of the packages with the same name across all listed channels and processes them as follows:

- 1. Sorts packages from highest to lowest channel priority.
- 2. Sorts tied packages---packages with the same channel priority---from highest to lowest version number. For example, if channelA contains NumPy 1.12.0 and 1.13.1, NumPy 1.13.1 will be sorted higher.
- 3. Sorts still-tied packages---packages with the same channel priority and same version---from highest to lowest build number. For example, if channelA contains both NumPy 1.12.0 build 1 and build 2, build 2 is sorted first. Any packages in channelB would be sorted below those in channelA.
- 4. Installs the first package on the sorted list that satisfies the installation specifications.

 $\label{eq:sentially} \ensuremath{\mathsf{Essentially}}, \ensuremath{\mathsf{the order goes: channelA::numpy-1.13_1 > channelA::numpy-1.12.1_1 > channelA::numpy-1.12.1_0 > channelB::numpy-1.13_1 \\ \ensuremath{\mathsf{channelB::numpy-1.13_1}} \ensuremath{\mathsf{channelA::numpy-1.13_1}} \ensuremath{\mathsf{channelA::num$

Note: If strict channel priority is turned on then channelB::numpy-1.13_1 isn't included in the list at all.

To make conda install the newest version of a package in any listed channel:

• Add channel_priority: disabled to your .condarc file.

OR

• Run the equivalent command:

conda config --set channel_priority disabled

Conda then sorts as follows:

- 1. Sorts the package list from highest to lowest version number.
- 2. Sorts tied packages from highest to lowest channel priority.
- 3. Sorts tied packages from highest to lowest build number.

Because build numbers from different channels are not comparable, build number still comes after channel priority.

The following command adds the channel "new_channel" to the top of the channel list, making it the highest priority:

conda config --add channels new_channel

Conda has an equivalent command:

conda config --prepend channels new_channel

Conda also has a command that adds the new channel to the bottom of the channel list, making it the lowest priority:

conda config --append channels new_channel

Strict channel priority

As of version 4.6.0, Conda has a strict channel priority feature. Strict channel priority can dramatically speed up conda operations and also reduce package incompatibility problems. We recommend setting channel priority to "strict" when possible.

Details about it can be seen by typing conda config --describe channel_priority.

```
channel_priority (ChannelPriority)
Accepts values of 'strict', 'flexible', and 'disabled'. The default
value is 'flexible'. With strict channel priority, packages in lower
priority channels are not considered if a package with the same name
appears in a higher priority channel. With flexible channel priority,
the solver may reach into lower priority channels to fulfill
dependencies, rather than raising an unsatisfiable error. With channel
priority disabled, package version takes precedence, and the
configured priority of channels is used only to break ties. In
previous versions of conda, this parameter was configured as either
True or False. True is now an alias to 'flexible'.
```

channel_priority: flexible

Managing packages

Note: There are many options available for the commands described on this page. For details, see *commands*.

Searching for packages

Use the terminal for the following steps.

To see if a specific package, such as SciPy, is available for installation:

```
conda search scipy
```

To see if a specific package, such as SciPy, is available for installation from Anaconda.org:

conda search --override-channels --channel defaults scipy

To see if a specific package, such as iminuit, exists in a specific channel, such as http://conda.anaconda.org/mutirri, and is available for installation:

conda search --override-channels --channel http://conda.anaconda.org/mutirri iminuit

Installing packages

Use the terminal for the following steps.

To install a specific package such as SciPy into an existing environment "myenv":

conda install --name myenv scipy

If you do not specify the environment name, which in this example is done by --name myenv, the package installs into the current environment:

conda install scipy

To install a specific version of a package such as SciPy:

conda install scipy=0.15.0

To install multiple packages at once, such as SciPy and cURL:

conda install scipy curl

Note: It is best to install all packages at once, so that all of the dependencies are installed at the same time.

To install multiple packages at once and specify the version of the package:

conda install scipy=0.15.0 curl=7.26.0

To install a package for a specific Python version:

conda install scipy=0.15.0 curl=7.26.0 -n py34_env

If you want to use a specific Python version, it is best to use an environment with that version. For more information, see *Troubleshooting*.

Installing similar packages

Installing packages that have similar filenames and serve similar purposes may return unexpected results. The package last installed will likely determine the outcome, which may be undesirable. If the two packages have different names, or if you're building variants of packages and need to line up other software in the stack, we recommend using *Mutex metapackages*.

Installing packages from Anaconda.org

Packages that are not available using conda install can be obtained from Anaconda.org, a package management service for both public and private package repositories. Anaconda.org is an Anaconda product, just like Anaconda and Miniconda.

To install a package from Anaconda.org:

- 1. In a browser, go to http://anaconda.org.
- 2. To find the package named bottleneck, type bottleneck in the top-left box named Search Packages.
- 3. Find the package that you want and click it to go to the detail page.

The detail page displays the name of the channel. In this example it is the "pandas" channel.

4. Now that you know the channel name, use the conda install command to install the package. In your terminal window, run:

conda install -c pandas bottleneck

This command tells conda to install the bottleneck package from the pandas channel on Anaconda.org.

5. To check that the package is installed, in your terminal window, run:

conda list

A list of packages appears, including bottleneck.

Note: For information on installing packages from multiple channels, see Managing channels.

Installing non-conda packages

If a package is not available from conda or Anaconda.org, you may be able to find and install the package via conda-forge or with another package manager like pip.

Pip packages do not have all the features of conda packages and we recommend first trying to install any package with conda. If the package is unavailable through conda, try finding and installing it with conda-forge.

If you still cannot install the package, you can try installing it with pip. The differences between pip and conda packages cause certain unavoidable limits in compatibility but conda works hard to be as compatible with pip as possible.

Note: Both pip and conda are included in Anaconda and Miniconda, so you do not need to install them separately.

Conda environments replace virtualenv, so there is no need to activate a virtualenv before using pip.

It is possible to have pip installed outside a conda environment or inside a conda environment.

To gain the benefits of conda integration, be sure to install pip inside the currently active conda environment and then install packages with that instance of pip. The command conda list shows packages installed this way, with a label showing that they were installed with pip.

You can install pip in the current conda environment with the command conda install pip, as discussed in *Using* pip in an environment.

If there are instances of pip installed both inside and outside the current conda environment, the instance of pip installed inside the current conda environment is used.

To install a non-conda package:

- 1. Activate the environment where you want to put the program:
 - In your terminal window, run conda activate myenv.
- 2. To use pip to install a program such as See, in your terminal window, run:

pip install see

3. To verify the package was installed, in your terminal window, run:

conda list

If the package is not shown, install pip as described in *Using pip in an environment* and try these commands again.

Installing commercial packages

Installing a commercial package such as IOPro is the same as installing any other package. In your terminal window, run:

conda install --name myenv iopro

This command installs a free trial of one of Anaconda's commercial packages called IOPro, which can speed up your Python processing. Except for academic use, this free trial expires after 30 days.

Viewing a list of installed packages

Use the terminal for the following steps.

To list all of the packages in the active environment:

conda list

To list all of the packages in a deactivated environment:

conda list -n myenv

Listing package dependencies

To find what packages are depending on a specific package in your environment, there is not one specific conda command. It requires a series of steps:

- 1. List the dependencies that a specific package requires to run: conda search package_name --info
- 2. Find your installation's package cache directory: conda info
- 3. Find package dependencies. By default, Anaconda/Miniconda stores packages in ~/anaconda/pkgs/ (or ~/opt/pkgs/ on macOS Catalina). Each package has an index.json file which lists the package's dependencies. This file resides in ~anaconda/pkgs/package_name/info/index.json.
- 4. Now you can find what packages depend on a specific package. Use grep to search all index.json files as follows: grep package_name ~/anaconda/pkgs/*/info/index.json

The result will be the full package path and version of anything containing the cpackage_name>.

Example: grep numpy ~/anaconda3/pkgs/*/info/index.json

Output from the above command:

```
/Users/testuser/anaconda3/pkgs/anaconda-4.3.0-np111py36_0/info/index.json: numpy 1.11.3.

→py36_0
/Users/testuser/anaconda3/pkgs/anaconda-4.3.0-np111py36_0/info/index.json: numpydoc 0.6.

→0 py36_0
/Users/testuser/anaconda3/pkgs/anaconda-4.3.0-np111py36_0/info/index.json: numpy 1.11.3.

→py36_0
```

Note this also returned "numpydoc" as it contains the string "numpy". To get a more specific result set you can add < and >.

Updating packages

Use conda update command to check to see if a new update is available. If conda tells you an update is available, you can then choose whether or not to install it.

Use the terminal for the following steps.

• To update a specific package:

conda update biopython

• To update Python:

conda update python

• To update conda itself:

conda update conda

Note: Conda updates to the highest version in its series, so Python 3.8 updates to the highest available in the 3.x series.

To update the Anaconda metapackage:

conda update conda conda update anaconda

Regardless of what package you are updating, conda compares versions and then reports what is available to install. If no updates are available, conda reports "All requested packages are already installed."

If a newer version of your package is available and you wish to update it, type y to update:

Proceed ([y]/n)? y

Preventing packages from updating (pinning)

Pinning a package specification in an environment prevents packages listed in the pinned file from being updated.

In the environment's conda-meta directory, add a file named pinned that includes a list of the packages that you do not want updated.

EXAMPLE: The file below forces NumPy to stay on the 1.7 series, which is any version that starts with 1.7. This also forces SciPy to stay at exactly version 0.14.2:

numpy 1.7.*
scipy ==0.14.2

With this pinned file, conda update numpy keeps NumPy at 1.7.1, and conda install scipy=0.15.0 causes an error.

Use the --no-pin flag to override the update restriction on a package. In the terminal, run:

conda update numpy --no-pin

Because the pinned specs are included with each conda install, subsequent conda update commands without --no-pin will revert NumPy back to the 1.7 series.

Adding default packages to new environments automatically

To automatically add default packages to each new environment that you create:

- 1. Open a terminal window and run: conda config --add create_default_packages PACKAGENAME1 PACKAGENAME2
- 2. Now, you can create new environments and the default packages will be installed in all of them.

You can also edit the .condarc file with a list of packages to create by default.

You can override this option at the command prompt with the --no-default-packages flag.

Removing packages

Use the terminal for the following steps.

• To remove a package such as SciPy in an environment such as myenv:

conda remove -n myenv scipy

• To remove a package such as SciPy in the current environment:

conda remove scipy

• To remove multiple packages at once, such as SciPy and cURL:

conda remove scipy curl

• To confirm that a package has been removed:

conda list

Managing Python

Conda treats Python the same as any other package, so it is easy to manage and update multiple installations. Conda supports Python 3.8, 3.9, 3.10, 3.11 and 3.12.

Viewing a list of available Python versions

To list the versions of Python that are available to install, in your terminal window, run:

conda search python

This lists all packages whose names contain the text python.

To list only the packages whose full name is exactly python, add the --full-name option. In your terminal window, run:

conda search --full-name python

Installing a different version of Python

To install a different version of Python without overwriting the current version, create a new environment and install the second Python version into it:

- 1. Create the new environment:
 - To create the new environment for Python 3.9, in your terminal window run:

conda create -n py39 python=3.9

Note: Replace py39 with the name of the environment you want to create. python=3.9 is the package and version you want to install in this new environment. This could be any package, such as numpy=1.19, or *multiple packages*.

- 2. Activate the new environment.
- 3. Verify that the new environment is your *current environment*.
- 4. To verify that the current environment uses the new Python version, in your terminal window, run:

python --version

Installing PyPy

To use the PyPy builds you can do the following:

```
conda config --add channels conda-forge
conda config --set channel_priority strict
conda create -n pypy pypy
conda activate pypy
```

Using a different version of Python

To switch to an environment that has different version of Python, activate the environment.

Updating Python

To update Python to the latest version in your environment, run:

conda update python

This command will update you to the latest major release (e.g. from python=3.10 to python=3.12).

If you would like to remain on a minor release, use the conda install command instead:

conda install python=3.10

Managing virtual packages

"Virtual" packages are injected into the conda solver to allow real packages to depend on features present on the system that cannot be managed directly by conda, like system driver versions or CPU features. Virtual packages are not real packages and not displayed by conda list. Instead conda runs a small bit of code to detect the presence or absence of the system feature that corresponds to the package. The currently supported list of virtual packages includes:

- __cuda: Maximum version of CUDA supported by the display driver.
- __osx: OSX version if applicable.
- __glibc: Version of glibc supported by the OS.
- __linux: Available when running on Linux.

- __unix: Available when running on OSX or Linux.
- __win: Available when running on Win.
- ___conda: Version of conda that is being used for solving.

Other virtual packages will be added in future conda releases. These are denoted by a leading double-underscore in the package name.

Note: Note that as of version 22.11.0, *virtual packages* are implemented as *conda plugins*.

Listing detected virtual packages

Use the terminal for the following steps.

To see the list of detected virtual packages, run:

conda info

If a package is detected, you will see it listed in the virtual packages section, as shown in this example:

```
active environment : base
   active env location : /Users/demo/dev/conda/devenv
           shell level : 1
      user config file : /Users/demo/.condarc
populated config files : /Users/demo/.condarc
         conda version : 4.6.3.post8+8f640d35a
   conda-build version : 3.17.8
       python version : 3.7.2.final.0
      virtual packages : __cuda=10.0
     base environment : /Users/demo/dev/conda/devenv (writable)
          channel URLs : https://repo.anaconda.com/pkgs/main/osx-64
                         https://repo.anaconda.com/pkgs/main/noarch
                         https://repo.anaconda.com/pkgs/free/osx-64
                         https://repo.anaconda.com/pkgs/free/noarch
                         https://repo.anaconda.com/pkgs/r/osx-64
                         https://repo.anaconda.com/pkgs/r/noarch
         package cache : /Users/demo/dev/conda/devenv/pkgs
                         /Users/demo/.conda/pkgs
      envs directories : /Users/demo/dev/conda/devenv/envs
                         /Users/demo/.conda/envs
              platform : osx-64
            user-agent : conda/4.6.3.post8+8f640d35a requests/2.21.0 CPython/3.7.2
→Darwin/17.7.0 OSX/10.13.6
               UID:GID : 502:20
            netrc file : None
          offline mode : False
```

Overriding detected packages

For troubleshooting, it is possible to override virtual package detection using an environment variable. Supported variables include:

- CONDA_OVERRIDE_CUDA CUDA version number or set to "" for no CUDA detected.
- CONDA_OVERRIDE_OSX OSX version number or set to "" for no OSX detected.
- CONDA_OVERRIDE_GLIBC GLIBC version number or set to "" for no GLIBC. This only applies on Linux.

Creating custom channels

In this tutorial, we walk through how to create your own channel that can either be accessed via the local or network file system or served from a webserver.

To create a custom channel:

1. You will need to install conda-build to complete this tutorial. If you do not already have it, you can install it with the following command:

```
conda install conda-build
```

2. Organize all the packages in subdirectories for the platforms you wish to serve. Below is an example of what this may look like:

```
channel

linux-64

channel

ch
```

3. Run conda index on the channel root directory:

```
conda index channel/
```

The conda index command generates a file repodata.json, saved to each repository directory, which conda uses to get the metadata for the packages in the channel.

Note: Each time you add or modify a package in the channel, you must rerun conda index for conda to see the update.

4. To test custom channels, serve the custom channel using a web server or using a file:// URL to the channel directory. Test by sending a search command to the custom channel.

Example: if you want a file in the custom channel location /opt/channel/linux-64/, search for files in that location:

conda search -c file:///opt/channel/ --override-channels

Note:

• The channel URL does not include the platform, as conda automatically detects and adds the platform.

• The option --override-channels ensures that conda searches only your specified channel and no other channels, such as default channels or any other channels you may have listed in your .condarc file.

If you have set up your private repository correctly, you get the following output:

Fetching package metadata: . . .

This is followed by a list of the conda packages found. This verifies that you have set up and indexed your private repository successfully.

Creating projects

In this tutorial, we will walk through how to set up a new Python project in conda using an environment.yml file. This file will help you keep track of your dependencies and share your project with others. We cover how to create your project, add a simple Python program and update it with new dependencies.

Requirements

To follow along, you will need a working conda installation. Please head over to our *installation guide* for instructions on how to get conda installed if you do not have it.

This tutorial relies heavily on using your computer's terminal (Command Prompt or PowerShell on Windows), so it is also important to have a working familiarity with using basic commands such as cd and 1s.

Creating the project's files

To start off, we will need a directory that will contain the files for our project. This can be created with the following command:

mkdir my-project

In this directory, we will now create a new environment.yaml file, which will hold the dependencies for our Python project. In your text editor (e.g. VSCode, PyCharm, vim, etc.), create this file and add the following:

Let's briefly go over what each part of this file means.

Name

The name of your environment. Here, we have chosen the name "my-project", but this can be anything you want.

Channels

Channels specify where you want conda to search for packages. We have chosen the defaults channel, but others such as conda-forge or bioconda are also possible to list here.

Dependencies

All the dependencies that you need for your project. So far, we have just added python because we know it will be a Python project. We will add more later.

Creating our environment

Now that we have written a basic environment.yml file, we can create and activate an environment from it. To do so, run the following commands:

```
conda env create --file environment.yml
conda activate my-project
```

Creating our Python application

With our new environment with Python installed, we can create a simple Python program. In your project folder, create a main.py file and add the following:

```
def main():
    print("Hello, conda!")

if __name__ == "__main__":
    main()
```

We can run our simple Python program by running the following command:

python main.py
Hello, conda!

Updating our project with new dependencies

If you want your project to do more than the simple example above, you can use one of the thousands of available packages on conda channels. To demonstrate this, we will add a new dependency so that we can pull in some data from the internet and perform a basic analysis.

To perform the data analysis, we will be relying on the Pandas package. To add this to our project, we will need to update our environment.yml file:

```
name: my-project
channels:
    - defaults
dependencies:
    python
    pandas # <-- This is our new dependency</pre>
```

Once we have done that, we can run the conda env update command to install the new package:

```
conda env update --file environment.yml
```

Now that our dependencies are installed, we will download some data to use for our analysis. For this, we will use the U.S. Environmental Protection Agency's Walkability Index dataset available on data.gov. You can download this with the following command:

Tip

If you do not have curl, you can visit the above link with a web browser to download it.

For our analysis, we are interested in knowing what percentage of U.S. residents live in highly walkable areas. This is a question that we can easily answer using the pandas library. Below is an example of how you might go about doing that:

```
import pandas as pd
def main():
    ......
   Answers the question:
   What percentage of U.S. residents live highly walkable neighborhoods?
    "15.26" is the threshold on the index for a highly walkable area.
    .....
   csv_file = "./EPA_SmartLocationDatabase_V3_Jan_2021_Final.csv"
   highly_walkable = 15.26
   df = pd.read_csv(csv_file)
    total_population = df["TotPop"].sum()
   highly_walkable_pop = df[df["NatWalkInd"] >= highly_walkable]["TotPop"].sum()
   percentage = (highly_walkable_pop / total_population) * 100.0
   print(
        f"{percentage:.2f}% of U.S. residents live in highly" "walkable neighborhoods."
    )
if __name__ == "__main__":
   main()
```

Update your main.py file with the code above and run it. You should get the following answer:

```
python main.py
10.69% of Americans live in highly walkable neighborhoods
```

Conclusion

You have just been introduced to creating your own data analysis project by using the environment.yml file in conda. As the project grows, you may wish to add more dependencies and also better organize the Python code into separate files and modules.

For even more information about working with environments and environment.yml files, please see *Managing Environments*.

Viewing command-line help

To see a list of supported conda commands, in your terminal window, run:

conda --help

or

conda -h

To get help for a specific command, type the command name followed by --help.

Example

To see help for the create command, in your terminal window, run:

conda create -h

Note: You can see the same command help in *commands*.

The tasks section is organized into various pages which cover nearly everything you can do with conda.

Common Tasks

Managing conda

Everything necessary to know about managing your installation of conda

Managing environments

Various operations involved with creating, updating, exporting, and removing environments, plus more

Managing channels

Information about channels and how they are searched through when installing packages

Managing packages

Details related to how to find, install, remove, and update packages in a given environment

Managing python

Supported versions of Python and tips for updating and using multiple Python versions

Managing virtual packages

Learn what virtual packages are and conda uses them

View command line help

Get help on the command line for any conda command

Tutorials

Creating custom channels

Tutorial walking you through how to create a custom channel and serve it from your local computer

Creating projects with conda

Learn how to start a new project with conda using a environment.yml file to manage your dependencies

4.1.4 Configuration

Using the .condarc conda configuration file

Overview

The conda configuration file, .condarc, is an optional runtime configuration file that allows advanced users to configure various aspects of conda, such as which channels it searches for packages, proxy settings, and environment directories. For all of the conda configuration options, see the *configuration page*.

Note: A . condarc file can also be used in an administrator-controlled installation to override the users' configuration. See *Administering a multi-user conda installation*.

The .condarc file can change many parameters, including:

- Where conda looks for packages.
- If and how conda uses a proxy server.
- Where conda lists known environments.
- Whether to update the Bash prompt with the currently activated environment name.
- Whether user-built packages should be uploaded to Anaconda.org.
- What default packages or features to include in new environments.

Creating and editing

The .condarc file is not included by default, but it is automatically created in your home directory the first time you run the conda config command. To create or modify a .condarc file, open a terminal and enter the conda config command.

The .condarc configuration file follows simple YAML syntax.

Example:

```
conda config --add channels conda-forge
```

Alternatively, you can open a text editor such as Notepad on Windows, TextEdit on macOS, or VS Code. Name the new file .condarc and save it to your user home directory or root directory. To edit the .condarc file, open it from your home or root directory and make edits in the same way you would with any other text file. If the .condarc file is in the root environment, it will override any in the home directory.

You can find information about your .condarc file by typing conda info in your terminal. This will give you information about your .condarc file, including where it is located.

You can also download a *sample .condarc file* to edit in your editor and save to your user home directory or root directory.

To set configuration options, edit the .condarc file directly or use the conda config --set command.

Example:

To set the auto_update_conda option to False, run:

conda config --set auto_update_conda False

For a complete list of conda config commands, see the *command reference*. The same list is available at the terminal by running conda config --help. You can also see the conda channel configuration for more information.

Conda supports a wide range of configuration options. This page gives a non-exhaustive list of the most frequently used options and their usage. For a complete list of all available options for your version of conda, use the conda config --describe command.

Searching for .condarc

Conda looks in the following locations for a .condarc file:

```
if on_win:
    SEARCH_PATH = (
        "C:/ProgramData/conda/.condarc",
        "C:/ProgramData/conda/condarc",
        "C:/ProgramData/conda/condarc.d",
    )
else:
    SEARCH_PATH = (
        "/etc/conda/.condarc",
        "/etc/conda/condarc",
        "/etc/conda/condarc.d/"
        "/var/lib/conda/.condarc",
        "/var/lib/conda/condarc",
        "/var/lib/conda/condarc.d/",
    )
SEARCH_PATH += (
    "$CONDA_ROOT/.condarc",
    "$CONDA_ROOT/condarc",
    "$CONDA_ROOT/condarc.d/",
    "$XDG_CONFIG_HOME/conda/.condarc",
    "$XDG_CONFIG_HOME/conda/condarc".
    "$XDG_CONFIG_HOME/conda/condarc.d/",
    "~/.config/conda/.condarc",
    "~/.config/conda/condarc",
    "~/.config/conda/condarc.d/",
    "~/.conda/.condarc",
    "~/.conda/condarc",
    "~/.conda/condarc.d/",
    "~/.condarc",
    "$CONDA_PREFIX/.condarc",
    "$CONDA_PREFIX/condarc",
    "$CONDA_PREFIX/condarc.d/",
    "$CONDARC",
)
```

XDG_CONFIG_HOME is the path to where user-specific configuration files should be stored defined following The XDG Base Directory Specification (XDGBDS). Default to \$HOME/.config should be used. CONDA_ROOT is the path for your base conda install. CONDA_PREFIX is the path to the current active environment. CONDARC must be a path to a file named .condarc, condarc, or end with a YAML suffix (.yml or .yaml).

Note: Any condarc files that exist in any of these special search path directories need to end in a valid yaml extension

(".yml" or ".yaml").

Conflict merging strategy

When conflicts between configurations arise, the following strategies are employed:

- · Lists merge
- Dictionaries merge
- Primitive clobber

Precedence

The precedence by which the conda configuration is built out is shown below. Each new arrow takes precedence over the ones before it. For example, config files (by parse order) will be superseded by any of the other configuration options. Configuration environment variables (formatted like CONDA_<CONFIG NAME>) will always take precedence over the other 3.



Obtaining information from the .condarc file

You can use the following commands to get the effective settings for conda. The effective settings are those that have merged settings from all the sources mentioned above.

To get all keys and their values:

```
conda config --get
```

To get the value of a specific key, such as channels:

conda config --get channels

To show all the configuration file sources and their contents:

conda config --show-sources

Saving settings to your .condarc file

The .condarc file can also be modified via conda commands. Below are several examples of how to do this.

To add a new value, such as http://conda.anaconda.org/mutirri, to a specific key, such as channels:

conda config --add channels http://conda.anaconda.org/mutirri

To remove an existing value, such as http://conda.anaconda.org/mutirri from a specific key, such as channels:

conda config --remove channels http://conda.anaconda.org/mutirri

To remove a key, such as channels, and all of its values:

conda config --remove-key channels

To configure channels and their priority for a single environment, make a .condarc file in the *root directory of that* environment.

Sample .condarc file

Because the .condarc file is just a YAML file, it means that it can be edited directly. Below is an example .condarc file:

```
# This is a sample .condarc file.
# It adds the r Anaconda.org channel and enables
# the show_channel_urls option.
# channel locations. These override conda defaults, i.e., conda will
# search *only* the channels listed here, in the order given.
# Use "defaults" to automatically include all default channels.
# Non-url channels will be interpreted as Anaconda.org usernames
# (this can be changed by modifying the channel_alias key; see below).
# The default is just 'defaults'.
channels:
  - r
  - defaults
# Show channel URLs when displaying what is going to be downloaded
# and in 'conda list'. The default is False.
show_channel_urls: True
# For more information about this file see:
# https://conda.io/docs/user-guide/configuration/use-condarc.html
```

Settings

This page contains an overview of many important settings available in conda with examples where possible.

General configuration

channels: Channel locations

Listing channel locations in the .condarc file overrides conda defaults, causing conda to search only the channels listed there in the order given.

Use defaults to automatically include all default channels. Non-URL channels are interpreted as Anaconda.org user or organization names. You can change this by modifying the channel_alias as described in *channel_alias: Set a channel alias*. The default is just defaults.

Example:

- channels:
 - <anaconda_dot_org_username>
 - http://some.custom/channel
 - file:///some/local/directory
 - defaults

To select channels for a single environment, put a .condarc file in the root directory of that environment (or use the --env option when using conda config).

Example: If you have installed Miniconda with Python 3 in your home directory and the environment is named "flowers", the path may be:

```
~/miniconda3/envs/flowers/.condarc
```

default_channels: Default channels

Normally, the defaults channel points to several channels at the repo.anaconda.com repository, but if default_channels is defined, it sets the new list of default channels. This is especially useful for airgapped and enterprise installations.

To ensure that all users only pull packages from an on-premises repository, an administrator can set both *channel alias* and default_channels.

default_channels:

- http://some.custom/channel
- file:///some/local/directory

channel_settings: Extra settings for individual channels

Added in version 23.3.0.

With channel_settings, it is possible to add extra configuration options for individual channels. This is currently used to register additional authentication handlers for conda via the *Auth Handlers* plugin hook, but may also accommodate more use cases in the future.

Here is an example of how it may be defined provided there was an available authentication handler called, "test-authhandler" registered via the aforementioned plugin hook:

```
channel_settings:
    - channel: https://some.custom/channel
    auth: test-auth-handler
    user: my-user-account
    - channel: https://some.base-url-prefix/*
    auth: another-auth-handler
```

Note: Each entry in channel_settings needs to define the channel attribute so that the configuration knows which channel these settings are associated with. The channel attribute may specify a glob-like URL pattern for matching. Note that in this case, the HTTP schema must match exactly to the channel URL, so a pattern like * is not valid.

auto_update_conda: Update conda automatically

When True, conda updates itself any time a user updates or installs a package in the root environment. When False, conda updates itself only if the user manually issues a conda update command. The default is True.

Example:

auto_update_conda: False

always_yes: Always yes

Choose the yes option whenever asked to proceed, such as when installing. Same as using the --yes flag at the command line. The default is False.

Example:

```
always_yes: True
```

show_channel_urls: Show channel URLs

Show channel URLs in conda list and when displaying what is going to be downloaded. The default is False.

Example:

show_channel_urls: True

changeps1: Change command prompt

When using conda activate, change the command prompt from \$PS1 to include the activated environment. The default is True.

Example:

changeps1: False

add_pip_as_python_dependency: Add pip as Python dependency

Add pip, wheel, and setuptools as dependencies of Python. This ensures that pip, wheel, and setuptools are always installed any time Python is installed. The default is True.

Example:

add_pip_as_python_dependency: False

use_pip: Use pip

Use pip when listing packages with conda list. This does not affect any conda command or functionality other than the output of the command conda list. The default is True.

Example:

use_pip: False

proxy_servers: Configure conda for use behind a proxy server

By default, proxy settings are pulled from the HTTP_PROXY and HTTPS_PROXY environment variables or the system. Setting them here overrides that default:

```
proxy_servers:
    http: http://user:pass@corp.com:8080
    https: https://user:pass@corp.com:8080
```

To give a proxy for a specific scheme and host, use the scheme://hostname form for the key. This matches for any request to the given scheme and exact host name:

If you do not include the username and password or if authentication fails, conda prompts for a username and password.

If your password contains special characters, you need to escape them as described in Percent-encoding reserved characters on Wikipedia.

Be careful not to use http when you mean https or https when you mean http.

ssl_verify: SSL verification

If you are behind a proxy that does SSL inspection, such as a Cisco IronPort Web Security Appliance (WSA), you may need to use ssl_verify to override the SSL verification settings.

By default, this variable is True, which means that SSL verification is used and conda verifies certificates for SSL connections. Setting this variable to False disables the connection's normal security and is not recommended:

```
ssl_verify: False
```

You can also set ssl_verify to a string path to a certificate, which can be used to verify SSL connections:

```
ssl_verify: corp.crt
```

offline: Offline mode only

Filters out all channel URLs that do not use the file:// protocol. The default is False.

Example:

offline: True

Advanced configuration

allow_softlinks: Disallow soft-linking

When allow_softlinks is True, conda uses hard links when possible and soft links (symlinks) when hard links are not possible, such as when installing on a different file system than the one that the package cache is on.

When allow_softlinks is False, conda still uses hard links when possible, but when it is not possible, conda copies files. Individual packages can override this option, specifying that certain files should never be soft linked.

The default is True.

Example:

allow_softlinks: False

channel_alias: Set a channel alias

Whenever you use the -c or --channel flag to give conda a channel name that is not a URL, conda prepends the channel_alias to the name that it was given. The default channel_alias is https://conda.anaconda.org.

If channel_alias is set to https://my.anaconda.repo:8080/conda/, then a user who runs the command conda install -c conda-forge some-package will install the package some-package from https://my.anaconda.repo:8080/conda/conda-forge.

For example, the command:

conda install --channel asmeurer <package>

is the same as:

conda install --channel https://conda.anaconda.org/asmeurer <package>

You can set channel_alias to your own repository.

Example: To set channel_alias to your repository at https://your.repo.com:

channel_alias: https://your.repo/

On Windows, you must include a slash ("/") at the end of the URL:

Example: https://your.repo/conda/

When channel_alias set to your repository at https://your.repo.com:

conda install --channel jsmith <package>

is the same as:

conda install --channel https://your.repo.com/jsmith <package>

create_default_packages: Always add packages by default

When creating new environments, add the specified packages by default. The default packages are installed in every environment you create. You can override this option at the command prompt with the --no-default-packages flag. The default is to not include any packages.

Example:

track_features: Track features

Enable certain features to be tracked by default. The default is to not track any features. This is similar to adding MKL to the create_default_packages list.

Example:

track_features:
 - mkl

update_dependencies: Disable updating of dependencies

By default, conda install updates the given package to the latest version and installs any dependencies necessary for that package. However, if dependencies that satisfy the package's requirements are already installed, conda will not update those packages to the latest version.

In this case, if you would prefer that conda update all dependencies to the latest version that is compatible with the environment, set update_dependencies to True.

The default is False.

Example:

update_dependencies: True

Note: Conda still ensures that dependency specifications are satisfied. Thus, some dependencies may still be updated or, conversely, this may prevent packages given at the command line from being updated to their latest versions. You can always specify versions at the command line to force conda to install a given version, such as conda install numpy=1.9.3.

To avoid updating only specific packages in an environment, a better option may be to pin them. For more information, see *Preventing packages from updating (pinning)*.

disallow: Disallow installation of specific packages

Disallow the installation of certain packages. The default is to allow installation of all packages.

Example:

disallow: - anaconda

add_anaconda_token: Add Anaconda.org token to automatically see private packages

When the channel alias is Anaconda.org or an Anaconda Server GUI, you can set the system configuration so that users automatically see private packages. Anaconda.org was formerly known as binstar.org. This uses the Anaconda command-line client, which you can install with conda install anaconda-client, to automatically add the token to the channel URLs.

The default is True.

Example:

add_anaconda_token: False

Note: Even when set to **True**, this setting is enabled only if the Anaconda command-line client is installed and you are logged in with the anaconda login command.

envs_dirs: Specify environment directories

Specify directories in which environments are located. If this key is set, the root prefix envs_dir is not used unless explicitly included. This key also determines where the package caches are located.

For each envs here, envs/pkgs is used as the pkgs cache, except for the standard envs directory in the root directory, for which the normal root_dir/pkgs is used.

Example:

```
envs_dirs:
- ~/my-envs
```

```
- /opt/anaconda/envs
```

The CONDA_ENVS_PATH environment variable overwrites the envs_dirs setting:

- For macOS and Linux: CONDA_ENVS_PATH=~/my-envs:/opt/anaconda/envs
- For Windows: set CONDA_ENVS_PATH=C:\Users\joe\envs;C:\Anaconda\envs

pkgs_dirs: Specify package directories

Specify directories in which packages are located. If this key is set, the root prefix pkgs_dirs is not used unless explicitly included.

If the pkgs_dirs key is not set, then envs/pkgs is used as the pkgs cache, except for the standard envs directory in the root directory, for which the normal root_dir/pkgs is used.

Example:

```
pkgs_dirs:
- /opt/anaconda/pkgs
```

The CONDA_PKGS_DIRS environment variable overwrites the pkgs_dirs setting:

- For macOS and Linux: CONDA_PKGS_DIRS=/opt/anaconda/pkgs
- For Windows: set CONDA_PKGS_DIRS=C:\Anaconda\pkgs

use_only_tar_bz2: Force conda to download only .tar.bz2 packages

Conda 4.7 introduced a new .conda package file format. .conda is a more compact and faster alternative to .tar.bz2 packages. It's thus the preferred file format to use where available.

Nevertheless, it's possible to force conda to only download .tar.bz2 packages by setting the use_only_tar_bz2 boolean to True.

The default is False.

Example:

use_only_tar_bz2: True

Note: This is forced to **True** if conda-build is installed and older than 3.18.3, because older versions of conda break when conda feeds it the new file format.

Conda-build configuration

root-dir: Specify conda-build output root directory

Build output root directory. You can also set this with the CONDA_BLD_PATH environment variable. The default is <CONDA_PREFIX>/conda-bld/. If you do not have write permissions to <CONDA_PREFIX>/conda-bld/, the default is ~/conda-bld/.

Example:

```
conda-build:
    root-dir: ~/conda-builds
```

output_folder: Specify conda-build build folder (conda-build 3.16.3+)

Folder to dump output package to. Packages are moved here if build or test succeeds. If unset, the output folder corresponds to the same directory as root-dir: the root build directory. .. code-block:: yaml

conda-build:

output_folder: conda-bld

pkg_version: Specify conda-build package version

Conda package version to create. Use 2 for . conda packages. If not set, conda-build defaults to .tar.bz2.

conda-build:
 pkg_format: 2

anaconda_upload: Automatically upload conda-build packages to Anaconda.org

Automatically upload packages built with conda-build to Anaconda.org. The default is False.

Example:

anaconda_upload: True

anaconda_token: Token to be used for Anaconda.org uploads (conda-build 3.0+)

Tokens are a means of authenticating with Anaconda.org without logging in. You can pass your token to condabuild with this .condarc setting, or with a CLI argument. This is unset by default. Setting it implicitly enables anaconda_upload.

conda-build: anaconda_token: gobbledygook

quiet: Limit build output verbosity (conda-build 3.0+)

Conda-build's output verbosity can be reduced with the quiet setting. For more verbosity, use the CLI flag --debug.

conda-build: quiet: true

filename_hashing: Disable filename hashing (conda-build 3.0+)

Conda-build 3 adds hashes to filenames to allow greater customization of dependency versions. If you find this disruptive, you can disable the hashing with the following config entry:

conda-build:		
filename	_hashing:	false

Warning: Conda-build does not check when clobbering packages. If you utilize conda-build 3's build matrices with a build configuration that is not reflected in the build string, packages will be missing due to clobbering.

no_verify: Disable recipe and package verification (conda-build 3.0+)

By default, conda-build uses conda-verify to ensure that your recipe and package meet some minimum sanity checks. You can disable these:

conda-build: no_verify: true

set_build_id: Disable per-build folder creation (conda-build 3.0+)

By default, conda-build creates a new folder for each build, named for the package name plus a timestamp. This allows you to do multiple builds at once. If you have issues with long paths, you may need to disable this behavior. You should first try to change the build output root directory with the **root-dir** setting described above, but fall back to this as necessary:

conda-build: set_build_id: false

skip_existing: Skip building packages that already exist (conda-build 3.0+)

By default, conda-build builds all recipes that you specify. You can instead skip recipes that are already built. A recipe is skipped if and only if *all* of its outputs are available on your currently configured channels.

```
conda-build:
    skip_existing: true
```

include_recipe: Omit recipe from package (conda-build 3.0+)

By default, conda-build includes the recipe that was used to build the package. If this contains sensitive or proprietary information, you can omit the recipe.

```
conda-build:
    include_recipe: false
```

Note: If you do not include the recipe, you cannot use conda-build to test the package after the build completes. This means that you cannot split your build and test steps across two distinct CLI commands (conda build --notest recipe and conda build -t recipe). If you need to omit the recipe and split your steps, your only option is to remove the recipe files from the tarball artifacts after your test step. Conda-build does not provide tools for doing that.

activate: Disable activation of environments during build/test (conda-build 3.0+)

By default, conda-build activates the build and test environments prior to executing the build or test scripts. This adds necessary PATH entries, and also runs any activate.d scripts you may have. If you disable activation, the PATH will still be modified, but the activate.d scripts will not run. This is not recommended, but some people prefer this.

```
conda-build:
    activate: false
```

long_test_prefix: Disable long prefix during test (conda-build 3.16.3+)

By default, conda-build uses a long prefix for the test prefix. If you have recipes that fail in long prefixes but would still like to test them in short prefixes, you can disable the long test prefix. This is not recommended.

```
conda-build:
    long_test_prefix: false
```

The default is true.

pypirc: PyPI upload settings (conda-build 3.0+)

Unset by default. If you have wheel outputs in your recipe, conda-build will try to upload them to the PyPI repository specified by the pypi_repository setting using credentials from this file path.

```
conda-build:
    pypirc: ~/.pypirc
```

pypi_repository: PyPI repository to upload to (conda-build 3.0+)

Unset by default. If you have wheel outputs in your recipe, conda-build will try to upload them to this PyPI repository using credentials from the file specified by the pypirc setting.

```
conda-build:
    pypi_repository: pypi
```

Expansion of environment variables

Conda expands environment variables in a subset of configuration settings. These are:

- channel
- channel_alias
- channels
- client_cert_key
- client_cert
- custom_channels
- custom_multichannels

- default_channels
- envs_dirs
- envs_path
- migrated_custom_channels
- pkgs_dirs
- proxy_servers
- verify_ssl
- allowlist_channels

This allows you to store the credentials of a private repository in an environment variable, like so:

channels:

```
- https://${USERNAME}:${PASSWORD}@my.private.conda.channel
```

Configuring number of threads

You can use your .condarc file or environment variables to add configuration to control the number of threads. You may want to do this to tweak conda to better utilize your system. If you have a very fast SSD, you might increase the number of threads to shorten the time it takes for conda to create environments and install/remove packages.

repodata_threads

- Default number of threads: None
- Threads used when downloading, parsing, and creating repodata structures from repodata.json files. Multiple downloads from different channels may occur simultaneously. This speeds up the time it takes to start solving.

verify_threads

- Default number of threads: 1
- Threads used when verifying the integrity of packages and files to be installed in your environment. Defaults to 1, as using multiple threads here can run into problems with slower hard drives.

execute_threads

- Default number of threads: 1
- Threads used to unlink, remove, link, or copy files into your environment. Defaults to 1, as using multiple threads here can run into problems with slower hard drives.

default_threads

- Default number of threads: None
- When set, this value is used for all of the above thread settings. With its default setting (None), it does not affect the other settings.

Setting any of the above can be done in .condarc or with conda config:

At your terminal.	At	your	terminal:
-------------------	----	------	-----------

conda config --set repodata_threads 2

```
In .condarc:
```

verify_threads: 4

Administering a multi-user conda installation

By default, conda and all of the packages it installs are installed locally with a user-specific configuration. Administrative privileges are not required, and no upstream files or other users are affected by the installation.

You can make conda and any number of packages available to a group of one or more users, while preventing these users from installing unwanted packages with conda:

- 1. Install conda and the allowed packages, if any, in a location that is under administrator control and accessible to users.
- 2. Create a *condarc system configuration file* in the root directory of the installation. This system-level configuration file will override any user-level configuration files installed by the user.

Each user accesses the central conda installation, which reads settings from the user .condarc configuration file located in their home directory. The path to the user file is the same as the root environment prefix displayed by conda info, as shown in *User configuration file* below. The user .condarc file is limited by the system .condarc file.

System configuration settings are commonly used in a system . condarc file but may also be used in a user .condarc file. All user configuration settings may also be used in a system .condarc file.

For information about settings in the .condarc file, see Using the .condarc conda configuration file.

Example administrator-controlled installation

The following example describes how to view the system configuration file, review the settings, compare it to a user's configuration file, and determine what happens when the user attempts to access a file from a blocked channel. It then describes how the user must modify their configuration file to access the channels allowed by the administrator.

System configuration file

1. The system configuration file must be in the top-level conda installation directory. Check the path where conda is located:

```
$ which conda
/tmp/miniconda/bin/conda
```

2. View the contents of the .condarc file in the administrator's directory:

```
cat /tmp/miniconda/.condarc
```

The following administrative .condarc file uses the #! final flag to specify the channels, default channels, and channel_alias available to the user.

The #! final flag is very similar to the ! important rule in CSS; any parameter within the . condarc that is trailed by the #! final cannot be overwritten by any other .condarc source. For more information on this flag, see the Anaconda Blog on the subject.

Because the #! final flag has been used and the channel defaults are not explicitly specified, users are disallowed from downloading packages from the default channels. You can check this in the next procedure.

User configuration file

1. Check the location of the user's conda installation:

The conda info command shows that conda is using the user's .condarc file, located at /Users/username/ .condarc and that the default channels such as repo.anaconda.com are listed as channel URLs.

2. View the contents of the administrative .condarc file in the directory that was located in step 1:

```
$ cat ~/.condarc
channels:
    - defaults
```

This user's .condarc file specifies only the default channels, but the administrator config file has blocked default channels by specifying that only admin is allowed. If this user attempts to search for a package in the default channels, they get a message telling them what channels are allowed:

```
$ conda search flask
Fetching package metadata:
Error: URL 'http://repo.anaconda.com/pkgs/pro/osx-64/' not
in allowed channels.
Allowed channels are:
    - https://conda.anaconda.org/admin/osx-64/
```

This error message tells the user to add the admin channel to their configuration file.

3. The user must edit their local .condarc configuration file to access the package through the admin channel:

channels:
 - admin

The user can now search for packages in the allowed admin channel.

Mirroring channels

The conda configuration system has several keys that can be used to set up a mirrored context.

The default setup

By default, conda can serve packages from two main locations:

- repo.anaconda.com: this is where defaults points to by default. This base location is hardcoded in the default value of default_channels:
 - https://repo.anaconda.com/pkgs/main
 - https://repo.anaconda.com/pkgs/r
 - https://repo.anaconda.com/pkgs/msys2
- conda.anaconda.org: this is where conda clients look up community channels like conda-forge or bioconda. This base location can be configured via channel_alias.

So, when it comes to mirroring these channels, you have to account for those two locations.

Mirror defaults

Use default_channels to overwrite the *default configuration*. For example:

```
default_channels:
```

- https://my-mirror.com/pkgs/main
- https://my-mirror.com/pkgs/r
- https://my-mirror.com/pkgs/msys2

Mirror all community channels

Redefine channel_alias to point to your mirror. For example:

channel_alias: https://my-mirror.com

This will make conda look for all community channels at https://my-mirror.com/conda-forge, https://my-mirror.com/bioconda, etc.

Mirror only some community channels

If you want to mirror only some community channels, you must use custom_channels. This takes precedence over channel_alias. For example:

With this configuration, conda-forge will be looked up at https://my-mirror.com/conda-forge. All other community channels will be looked up at https://conda.anaconda.org.

Note: Feel free to explore all the available options in Configuration.

Disabling SSL verification

Using conda with SSL is strongly recommended, but it is possible to disable SSL and it may be necessary to disable SSL in certain cases.

Some corporate environments use proxy services that use Man-In-The-Middle (MITM) attacks to sniff encrypted traffic. These services can interfere with SSL connections such as those used by conda and pip to download packages from repositories such as PyPI.

If you encounter this interference, you should set up the proxy service's certificates so that the **requests** package used by conda can recognize and use the certificates.

For cases where this is not possible, conda-build versions 3.0.31 and higher have an option that disables SSL certificate verification and allows this traffic to continue.

conda skeleton pypi can disable SSL verification when pulling packages from a PyPI server over HTTPS.

Warning: This option causes your computer to download and execute arbitrary code over a connection that it cannot verify as secure. This is not recommended and should only be used if necessary. Use this option at your own risk.

To disable SSL verification when using conda skeleton pypi, set the SSL_NO_VERIFY environment variable to either 1 or True (case insensitive).

On *nix systems:

SSL_NO_VERIFY=1 conda skeleton pypi a_package

And on Windows systems:
```
set SSL_NO_VERIFY=1
conda skeleton pypi a_package
set SSL_NO_VERIFY=
```

We recommend that you unset this environment variable immediately after use. If it is not unset, some other tools may recognize it and incorrectly use unverified SSL connections.

Using this option will cause requests to emit warnings to STDERR about insecure settings. If you know that what you're doing is safe, or have been advised by your IT department that what you're doing is safe, you may ignore these warnings.

Disabling SSL verification via conda settings

In addition to disabling SSL via environment variables, you can disable it by setting *ssl_verify* to *false* in your config files. To do so, run the following commands to disable and enable it:

```
conda config --set ssl_verify False
# Run conda commands with SSL disabled
conda config --set ssl_verify True
```

Using non-standard certificates

Using conda behind a firewall may require using a non-standard set of certificates, which requires custom settings.

If you are using a non-standard set of certificates, then the requests package requires the setting of REQUESTS_CA_BUNDLE. If you receive an error with self-signed certifications, you may consider unsetting REQUESTS_CA_BUNDLE as well as CURL_CA_BUNDLE and disabling SSL verification to create a conda environment over HTTP.

You may need to set the conda environment to use the root certificate provided by your company rather than conda's generic ones.

One workflow to resolve this on macOS is:

- Open Chrome, got to any website, click on the lock icon on the left of the URL. Click on «Certificate» on the dropdown. In the next window you see a stack of certificates. The uppermost (aka top line in window) is the root certificate (e.g. Zscaler Root CA).
- Open macOS keychain, click on «Certificates» and choose among the many certificates the root certificate that you just identified. Export this to any folder of your choosing.
- Convert this certificate with OpenSSL: openssl x509 -inform der -in /path/to/your/certificate. cer -out /path/to/converted/certificate.pem
- For a quick check, set your shell to acknowledge the certificate: export REQUESTS_CA_BUNDLE=/path/to/ converted/certificate.pem
- To set this permanently, open your shell profile (e.g. .bashrc or .zshrc) and add this line: export REQUESTS_CA_BUNDLE=/path/to/converted/certificate.pem. Now exit your terminal/shell and reopen. Check again.

Improving interoperability with pip

The conda 4.6.0 release added improved support for interoperability between conda and pip. This feature is still experimental and is therefore off by default.

With this interoperability, conda can use pip-installed packages to satisfy dependencies, cleanly remove pip-installed software, and replace them with conda packages when appropriate.

If you'd like to try the feature, you can set this .condarc setting:

conda config --set pip_interop_enabled True

Note: Setting pip_interop_enabled to True may slow down conda.

Even without activating this feature, conda now understands pip metadata more intelligently. For example, if we create an environment with conda:

conda create -y -n some_pip_test python=3.7 imagesize=1.0

Then we update imagesize in that environment using pip:

```
conda activate some_pip_test
pip install -U imagesize
```

Prior to conda 4.6.0, the conda list command returned ambiguous results:

imagesize	1.1.0
imagesize	1.0.0 py37_0

Conda 4.6.0 now shows only one entry for imagesize (the newer pip entry):

imagesize	1.1.0 pypi_0	рурі
-----------	--------------	------

Using the free channel

The free channel contains packages created prior to September 26, 2017. Prior to conda 4.7, the free channel was part of the defaults channel. Read more about the *defaults channel*.

Removing the free channel reduced conda's search space and hid old software. That old software could have incompatible constraint information. Read more about why we made this change.

If you still need the content from the **free** channel to reproduce old environments, you can re-add the channel following the directions below.

Adding the free channel to defaults

If you want to add the free channel back into your default list, use the command:

conda config --set restore_free_channel true

The order of the channels is important. Using the above command will restore the free channel in the correct order.

Changing.condarc

You can also add the free channel back into your defaults by changing the .condarc file itself.

Add the following to the conda section of your .condarc file:

restore_free_channel: true

Read more about Using the .condarc conda configuration file.

Package name changes

Some packages that are available in the free channel have different names in the main channel.

Package name in free	Package name in main
dateutil	python-dateutil
gcc	gcc_linux-64 and similar
pil	pillow
ipython-notebook	now installable via notebook, a metapackage could be created
Ipython-qtconsole	now installable via qtconsole, a metapackage could be created
beautiful-soup	beautifulsoup4
pydot-ng	pydot

Troubleshooting

You may encounter some errors, such as UnsatisfiableError or a PackagesNotFoundError.

An example of this error is:

```
$ conda create -n test -c file:///Users/jsmith/anaconda/conda-bld bad_pkg
Collecting package metadata: done
Solving environment: failed
UnsatisfiableError: The following specifications were found to be in conflict:
    - cryptography=2.6.1 -> openssl[version='>=1.1.1b,<1.1.2a']
    - python=3.7.0 -> openssl[version='>=1.0.2o,<1.0.3a']
Use "conda search <package> --info" to see the dependencies for each package.
```

This can occur if:

- you're trying to install a package that is only available in free and not in main.
- you have older environments in files you want to recreate. If those spec files reference packages that are in free, they will not show up.

• a package is dependent upon files found only in the free channel. Conda will not let you install the package if it cannot install the dependency, which the package requires to work.

If you encounter these errors, consider using a newer package than the one in free. If you want those older versions, you can *add the free channel back into your defaults*.

The following pages have information on how conda can be customized further through configuration.

Using the .condarc conda configuration file

Learn how to use a settings file (.condarc) to override defaults and maintain settings across shell sessions

Settings

View a list and definition of all the configuration settings that can be used within conda

Administering a multi-user conda installation

How to set up conda as a system administrator for use by multiple users

Mirroring channels

Explore how to configure your own channel server mirror with conda

Disable SSL Verification

Disabling SSL may be necessary in very limited circumstances; learn how here

Using non-standard certificates

Install and configure non-standard certifications for use with conda

Pip interoperability (experimental)

An experimental feature that makes conda operate better with pip (no longer supported)

Free channel (deprecated)

Explanation of our deprecation of the free channel and how to restore it

4.1.5 Concepts

Commands

The conda command is the primary interface for managing installations of various packages. It can:

- Query and search the Anaconda package index and current Anaconda installation.
- Create new conda environments.
- Install and update packages into existing conda environments.

Tip: You can abbreviate many frequently used command options that are preceded by 2 dashes (--) to just 1 dash and the first letter of the option. So --n and --envs can be written as -n and -e respectively.

For full usage of each command, including abbreviations, see *commands*. You can see the same information at the command line by *viewing the command-line help*.

Packages

What is a package?

A package is a compressed tarball file (.tar.bz2) or .conda file that contains:

- system-level libraries.
- Python or other modules.
- executable programs and other components.
- metadata under the info/ directory.
- a collection of files that are installed directly into an install prefix.

Conda keeps track of the dependencies between packages and platforms. The conda package format is identical across platforms and operating systems.

Only files, including symbolic links, are part of a conda package. Directories are not included. Directories are created and removed as needed, but you cannot create an empty directory from the tar archive directly.

.conda file format

The .conda file format was introduced in conda 4.7 as a more compact, and thus faster, alternative to a tarball.

The .conda file format consists of an outer, uncompressed ZIP-format container, with 2 inner compressed .tar files.

For the .conda format's initial internal compression format support, we chose Zstandard (zstd). The actual compression format used does not matter, as long as the format is supported by libarchive. The compression format may change in the future as more advanced compression algorithms are developed and no change to the .conda format is necessary. Only an updated libarchive would be required to add a new compression format to .conda files.

These compressed files can be significantly smaller than their bzip2 equivalents. In addition, they decompress much more quickly. .conda is the preferred file format to use where available, although we continue to provide .tar.bz2 files in tandem.

Read more about the introduction of the .conda file format.

Note: In conda 4.7 and later, you cannot use package names that end in ".conda" as they conflict with the .conda file format for packages.

Using packages

• You may search for packages

conda search scipy

• You may install a package

conda install scipy

• You may build a package after installing conda-build

conda build my_fun_package

Package structure

```
.

bin

pyflakes

info

LICENSE.txt

files

index.json

paths.json

lib

python3.5
```

- bin contains relevant binaries for the package.
- lib contains the relevant library files (eg. the .py files).
- info contains package metadata.

Metapackages

When a conda package is used for metadata alone and does not contain any files, it is referred to as a metapackage. The metapackage may contain dependencies to several core, low-level libraries and can contain links to software files that are automatically downloaded when executed. Metapackages are used to capture metadata and make complicated package specifications simpler.

An example of a metapackage is "anaconda," which collects together all the packages in the Anaconda installer. The command conda create -n envname anaconda creates an environment that exactly matches what would be created from the Anaconda installer. You can create metapackages with the conda metapackage command. Include the name and version in the command.

Anaconda metapackage

The Anaconda metapackage is used in the creation of the Anaconda Distribution installers so that they have a set of packages associated with them. Each installer release has a version number, which corresponds to a particular collection of packages at specific versions. That collection of packages at specific versions is encapsulated in the Anaconda metapackage.

The Anaconda metapackage contains several core, low-level libraries, including compression, encryption, linear algebra, and some GUI libraries.

Read more about the Anaconda metapackage and Anaconda Distribution.

Mutex metapackages

A mutex metapackage is a very simple package that has a name. It need not have any dependencies or build steps. Mutex metapackages are frequently an "output" in a recipe that builds some variant of another package. Mutex metapackages function as a tool to help achieve mutual exclusivity among packages with different names.

Let's look at some examples for how to use mutex metapackages to build NumPy against different BLAS implementations.

Building NumPy with BLAS variants

If you build NumPy with MKL, you also need to build SciPy, scikit-learn, and anything else using BLAS also with MKL. It is important to ensure that these "variants" (packages built with a particular set of options) are installed together and never with an alternate BLAS implementation. This is to avoid crashes, slowness, or numerical problems. Lining up these libraries is both a build-time and an install-time concern. We'll show how to use metapackages to achieve this need.

Let's start with the metapackage blas=1.0=mkl: https://github.com/AnacondaRecipes/intel_repack-feedstock/blob/ e699b12/recipe/meta.yaml#L108-L112

Note that mkl is a string of blas.

That metapackage is automatically added as a dependency using run_exports when someone uses the mkl-devel package as a build-time dependency: https://github.com/AnacondaRecipes/intel_repack-feedstock/blob/e699b12/recipe/ meta.yaml#L124

By the same token, here's the metapackage for OpenBLAS: https://github.com/AnacondaRecipes/openblas-feedstock/blob/ae5af5e/recipe/meta.yaml#L127-L131

And the run_exports for OpenBLAS, as part of openblas-devel: https://github.com/AnacondaRecipes/ openblas-feedstock/blob/ae5af5e/recipe/meta.yaml#L100

Fundamentally, conda's model of mutual exclusivity relies on the package name. OpenBLAS and MKL are obviously not the same package name, and thus are not mutually exclusive. There's nothing stopping conda from installing both at once. There's nothing stopping conda from installing NumPy with MKL and SciPy with OpenBLAS. The metapackage is what allows us to achieve the mutual exclusivity. It unifies the options on a single package name, but with a different build string. Automating the addition of the metapackage with run_exports helps ensure the library consumers (package builders who depend on libraries) will have correct dependency information to achieve the unified runtime library collection.

Installing NumPy with BLAS variants

To specify which variant of NumPy that you want, you could potentially specify the BLAS library you want:

conda install numpy mkl

However, that doesn't actually preclude OpenBLAS from being chosen. Neither MKL nor its dependencies are mutually exclusive (meaning they do not have similar names and different version/build-string).

This pathway may lead to some ambiguity and solutions with mixed BLAS, so using the metapackage is recommended. To specify MKL-powered NumPy in a non-ambiguous way, you can specify the mutex package (either directly or indirectly):

conda install numpy "blas=*=mkl"

There is a simpler way to address this, however. For example, you may want to try another package that has the desired mutex package as a dependency.

OpenBLAS has this with its "nomkl" package: https://github.com/AnacondaRecipes/openblas-feedstock/blob/ ae5af5e/recipe/meta.yaml#L133-L147

Nothing should use "nomkl" as a dependency. It is strictly a utility for users to facilitate switching from MKL (which is the default) to OpenBLAS.

How did MKL become the default? The solver needs a way to prioritize some packages over others. We achieve that with an older conda feature called track_features that originally served a different purpose.

Track_features

One of conda's optimization goals is to minimize the number of track_features needed to specify the desired specs. By adding track_features to one or more of the options, conda will de-prioritize it or "weigh it down." The lowest priority package is the one that would cause the most track_features to be activated in the environment. The default package among many variants is the one that would cause the least track_features to be activated.

There is a catch, though: any track_features must be unique. No two packages can provide the same track_feature. For this reason, our standard practice is to attach track_features to the metapackage associated with what we want to be non-default.

Take another look at the OpenBLAS recipe: https://github.com/AnacondaRecipes/openblas-feedstock/blob/ae5af5e/ recipe/meta.yaml#L127-L137

This attached track_features entry is why MKL is chosen over OpenBLAS. MKL does not have any track_features associated with it. If there are 3 options, you would attach 0 track_features to the default, then 1 track_features for the next preferred option, and finally 2 for the least preferred option. However, since you generally only care about the one default, it is usually sufficient to add 1 track_feature to all options other than the default option.

More info

For reference, the Visual Studio version alignment on Windows also uses mutex metapackages. https://github.com/ AnacondaRecipes/aggregate/blob/9635228/vs2017/meta.yaml#L24

Noarch packages

Noarch packages are packages that are not architecture specific and therefore only have to be built once. Noarch packages are either generic or Python. Noarch generic packages allow users to distribute docs, datasets, and source code in conda packages. Noarch Python packages are described below.

Declaring these packages as noarch in the build section of the meta.yaml reduces shared CI resources. Therefore, all packages that qualify to be noarch packages should be declared as such.

Noarch Python

The noarch: python directive in the build section makes pure-Python packages that only need to be built once.

Noarch Python packages cut down on the overhead of building multiple different pure Python packages on different architectures and Python versions by sorting out platform and Python version-specific differences at install time.

In order to qualify as a noarch Python package, all of the following criteria must be fulfilled:

- No compiled extensions.
- No post-link, pre-link, or pre-unlink scripts.
- No OS-specific build scripts.
- No Python version-specific requirements.
- No skips except for Python version. If the recipe is py3 only, remove skip statement and add version constraint on Python in host and run section.
- 2to3 is not used.
- Scripts argument in setup.py is not used.
- If console_script entrypoints are in setup.py, they are listed in meta.yaml.
- No activate scripts.
- Not a dependency of conda.

Note: While noarch: python does not work with selectors, it does work with version constraints. skip: True # [py2k] can sometimes be replaced with a constrained Python version in the host and run subsections, for example: python >=3 instead of just python.

Note: Only console_script entry points have to be listed in meta.yaml. Other entry points do not conflict with noarch and therefore do not require extra treatment.

Read more about conda's noarch packages.

Link and unlink scripts

You may optionally execute scripts before and after the link and unlink steps. For more information, see Adding prelink, post-link, and pre-unlink scripts.

More information

For more information, go for a deeper dive in our *managing packages guide*. Learn more about package metadata, repository structure and index, and package match specifications at *Package specifications*.

Package specification

Package metadata

The info/ directory contains all metadata about a package. Files in this location are not installed under the install prefix. Although you are free to add any file to this directory, conda only inspects the content of the files discussed below.

Info

- files
 - a list of all the files in the package (not included in info/)
- index.json
 - metadata about the package including platform, version, dependencies, and build info

```
{
    "arch": "x86_64",
    "build": "py37hfa4b5c9_1",
    "build_number": 1,
    "depends": [
        "depend > 1.1.1"
    ],
    "license": "BSD 3-Clause",
    "name": "fun-packge",
    "platform": "linux",
    "subdir": "linux-64",
    "timestamp": 1535416612069,
    "version": "0.0.0"
}
```

paths.json

a list of files in the package, along with their associated SHA-256, size in bytes, and the type of path (eg. hardlink vs. softlink)

```
"paths": [
    {
        "_path": "lib/python3.7/site-packages/fun-packge/__init__.py",
        "path_type": "hardlink",
        "sha256": "76f3b6e34feeb651aff33ca59e0279c4eadce5a50c6ad93b961c846f7ba717e9",
        "size_in_bytes": 2067
    },
    {
        "_path": "lib/python3.7/site-packages/fun-packge/__config__.py",
        "path_type": "hardlink",
        "sha256": "348e3602616c1fe4c84502b1d8cf97c740d886002c78edab176759610d287f06",
        "size_in_bytes": 87519
    },
    ....
}
```

ł

info/index.json

This file contains basic information about the package, such as name, version, build string, and dependencies. The content of this file is stored in repodata.json, which is the repository index file, hence the name index.json. The JSON object is a dictionary containing the keys shown below. The filename of the conda package is composed of the first 3 values, as in: <name>--<version>--<build>.tar.bz2.

Key	Туре	Description
name	string	The lowercase name of the package. May contain the "-" character.
version	string	The package version. May not contain "-". Conda acknowledges PEP 440.
build	string	 The build string. May not contain "-". Differentiates builds of packages with otherwise identical names and versions, such as: A build with other dependencies, such as Python 3.4 instead of Python 2.7. A bug fix in the build process. Some different optional dependencies, such as MKL versus AT-LAS linkage. Nothing in conda actually inspects the build string. Strings such as np18py34_1 are designed only for human readability and conda never parses them.
build_number	integer	A non-negative integer representing the build number of the package. Unlike the build string, the build_number is inspected by conda. Conda uses it to sort packages that have otherwise identical names and versions to determine the latest one. This is important because new builds that contain bug fixes for the way a package is built may be added to a repos- itory.
depends	list of strings	A list of dependency specifications, where each element is a string, as outlined in <i>Package match specifications</i> .
arch	string	Optional. The architecture the package is built for. EXAMPLE: x86_64 Conda currently does not use this key.
platform	string	Optional. The OS that the package is built for. EXAMPLE: osx Conda currently does not use this key. Packages for a specific architec- ture and platform are usually distinguished by the repository subdirec- tory that contains themsee <i>Repository structure and index</i> .

info/files

Lists all files that are part of the package itself, 1 per line. All of these files need to get linked into the environment. Any files in the package that are not listed in this file are not linked when the package is installed. The directory delimiter for the files in info/files should always be "/", even on Windows. This matches the directory delimiter used in the tarball.

info/has_prefix

Optional file. Lists all files that contain a hard-coded build prefix or placeholder prefix, which needs to be replaced by the install prefix at installation time.

Note: Due to the way the binary replacement works, the placeholder prefix must be longer than the install prefix.

Each line of this file should be either a path, in which case it is considered a text file with the default placeholder /opt/anaconda1anaconda2anaconda3, or a space-separated list of placeholder, mode, and path, where:

- Placeholder is the build or placeholder prefix.
- Mode is either text or binary.
- Path is the relative path of the file to be updated.

```
EXAMPLE: On Windows:
```

```
"Scripts/script1.py"
"C:\Users\username\anaconda\envs\_build" text "Scripts/script2.bat"
"C:/Users/username/anaconda/envs/_build" binary "Scripts/binary"
```

EXAMPLE: On macOS or Linux:

```
bin/script.sh
/Users/username/anaconda/envs/_build binary bin/binary
/Users/username/anaconda/envs/_build text share/text
```

Note: The directory delimiter for the relative path must always be "/", even on Windows. The placeholder may contain either "\" or "/" on Windows, but the replacement prefix will match the delimiter used in the placeholder. The default placeholder /opt/anaconda1anaconda2anaconda3 is an exception, being replaced with the install prefix using the native path delimiter. On Windows, the placeholder and path always appear in quotes to support paths with spaces.

info/license.txt

Optional file. The software license for the package.

info/no_link

Optional file. Lists all files that cannot be linked - either soft-linked or hard-linked - into environments and are copied instead.

info/about.json

Optional file. Contains the entries in the about section of the meta.yaml file. The following keys are added to info/ about.json if present in the build recipe:

- home
- dev_url
- doc_url
- license_url
- license
- summary
- description
- license_family

info/recipe

A directory containing the full contents of the build recipe.

meta.yaml.rendered

The fully rendered build recipe. See conda render.

This directory is present only when the the include_recipe flag is True in the build section.

Repository structure and index

A conda repository - or channel - is a directory tree, usually served over HTTPS, which has platform subdirectories, each of which contain conda packages and a repository index. The index file repodata.json lists all conda packages in the platform subdirectory. Use conda index to create such an index from the conda packages within a directory. It is simple mapping of the full conda package filename to the dictionary object in info/index.json described in link scripts.

In the following example, a repository provides the conda package misc-1.0-np17py27_0.tar.bz2 on 64-bit Linux and 32-bit Windows:

Note: Both conda packages have identical filenames and are distinguished only by the repository subdirectory that contains them.

Package match specifications

This match specification is not the same as the syntax used at the command line with conda install, such as conda install python=3.9. Internally, conda translates the command line syntax to the spec defined in this section.

EXAMPLE: python=3.9 is translated to python 3.9*.

Package dependencies are specified using a match specification. A match specification is a space-separated string of 1, 2, or 3 parts:

- The first part is always the exact name of the package.
- The second part refers to the version and may contain special characters:
 - | means OR.

EXAMPLE: 1.0 | 1.2 matches version 1.0 or 1.2

- * matches 0 or more characters in the version string. In terms of regular expressions, it is the same as r.*```.

EXAMPLE: 1.0|1.4* matches 1.0, 1.4 and 1.4.1b2, but not 1.2.

- <, >, <=, >=, == and != are relational operators on versions, which are compared using PEP-440. For example, <=1.0 matches 0.9, 0.9.1, and 1.0, but not 1.0.1. == and != are exact equality.</p>

Pre-release versioning is also supported such that >1.0b4 will match 1.0b5 and 1.0rc1 but not 1.0b4 or 1.0a5.

EXAMPLE: <=1.0 matches 0.9, 0.9.1, and 1.0, but not 1.0.1.

- , means AND.

EXAMPLE: >=2,<3 matches all packages in the 2 series. 2.0, 2.1 and 2.9 all match, but 3.0 and 1.0 do not.

- , has higher precedence than |, so >=1,<2|>3 means greater than or equal to 1 AND less than 2 or greater than 3, which matches 1, 1.3 and 3.0, but not 2.2.

Conda parses the version by splitting it into parts separated by |. If the part begins with \langle , \rangle , =, or !, it is parsed as a relational operator. Otherwise, it is parsed as a version, possibly containing the "*" operator.

• The third part is always the exact build string. When there are 3 parts, the second part must be the exact version.

Remember that the version specification cannot contain spaces, as spaces are used to delimit the package, version, and build string in the whole match specification. python ≥ 2.7 is an invalid match specification. Furthermore, python ≥ 2.7 is matched as any version of a package named python ≥ 2.7 .

When using the command line, put double quotes around any package version specification that contains the space character or any of the following characters: \langle , \rangle , *, or |.

EXAMPLE:

```
conda install numpy=1.11
conda install numpy=1.11
conda install "numpy>1.11"
conda install "numpy=1.11.1|1.11.3"
conda install "numpy>=1.8,<2"</pre>
```

Examples

The OR constraint "numpy=1.11.1|1.11.3" matches with 1.11.1 or 1.11.3.

The AND constraint "numpy>=1.8,<2" matches with 1.8 and 1.9 but not 2.0.

The fuzzy constraint numpy=1.11 matches 1.11, 1.11.0, 1.11.1, 1.11.2, 1.11.18, and so on.

The exact constraint numpy==1.11 matches 1.11, 1.11.0, 1.11.0.0, and so on.

The build string constraint "numpy=1.11.2=*nomkl*" matches the NumPy 1.11.2 packages without MKL but not the normal MKL NumPy 1.11.2 packages.

The build string constraint "numpy=1.11.1|1.11.3=py36_0" matches NumPy 1.11.1 or 1.11.3 built for Python 3.6 but not any versions of NumPy built for Python 3.5 or Python 2.7.

The following are all valid match specifications for numpy-1.8.1-py27_0:

- numpy
- numpy 1.8*
- numpy 1.8.1
- numpy >=1.8
- numpy ==1.8.1
- numpy 1.8|1.8*
- numpy >=1.8,<2
- numpy >=1.8,<2|1.9
- numpy 1.8.1 py27_0
- numpy=1.8.1=py27_0

Version ordering

The class VersionOrder(object) implements an order relation between version strings.

Version strings can contain the usual alphanumeric characters (A-Za-z0-9), separated into components by dots and underscores. Empty segments (i.e. two consecutive dots, a leading/trailing underscore) are not permitted. An optional epoch number - an integer followed by ! - can precede the actual version string (this is useful to indicate a change in the versioning scheme itself). Version comparison is case-insensitive.

Supported version strings

Conda supports six types of version strings:

- Release versions contain only integers, e.g. 1.0, 2.3.5.
- Pre-release versions use additional letters such as a or rc, for example 1.0a1, 1.2.beta3, 2.3.5rc3.
- Development versions are indicated by the string dev, for example 1.0dev42, 2.3.5.dev12.
- Post-release versions are indicated by the string post, for example 1.0post1, 2.3.5.post2.
- Tagged versions have a suffix that specifies a particular property of interest, e.g. 1.1.parallel. Tags can be added to any of the preceding 4 types. As far as sorting is concerned, tags are treated like strings in pre-release versions.

• An optional local version string separated by + can be appended to the main (upstream) version string. It is only considered in comparisons when the main versions are equal, but otherwise handled in exactly the same manner.

Predictable version ordering

To obtain a predictable version ordering, it is crucial to keep the version number scheme of a given package consistent over time. Conda considers prerelease versions as less than release versions.

- Version strings should always have the same number of components (except for an optional tag suffix or local version string).
- Letters/Strings indicating non-release versions should always occur at the same position.

Before comparison, version strings are parsed as follows:

- They are first split into epoch, version number, and local version number at ! and + respectively. If there is no !, the epoch is set to 0. If there is no +, the local version is empty.
- The version part is then split into components at . and _.
- Each component is split again into runs of numerals and non-numerals
- Subcomponents containing only numerals are converted to integers.
- Strings are converted to lowercase, with special treatment for dev and post.
- When a component starts with a letter, the fillvalue 0 is inserted to keep numbers and strings in phase, resulting in 1.1.a1' == 1.1.0a1'.
- The same is repeated for the local version part.

Examples:

```
1.2g.beta15.rc => [[0], [1], [2, 'g'], [0, 'beta', 15], [0, 'rc']]
1!2.15.1_ALPHA => [[1], [2], [15], [1, '_alpha']]
```

The resulting lists are compared lexicographically, where the following rules are applied to each pair of corresponding subcomponents:

- Integers are compared numerically.
- Strings are compared lexicographically, case-insensitive.
- Strings are smaller than integers, except
 - dev versions are smaller than all corresponding versions of other types.
 - post versions are greater than all corresponding versions of other types.
- If a subcomponent has no correspondent, the missing correspondent is treated as integer 0 to ensure 1.1' = 1.1.0'.

The resulting order is:

0.4 < 0.4.0 < 0.4.1.rc == 0.4.1.RC # case-insensitive comparison < 0.4.1 < 0.5a1 < 0.5b3 < 0.5C1 # case-insensitive comparison

(continues on next page)

(continued from previous page)

```
< 0.5
< 0.9.6
< 0.960923
< 1.0
< 1.1dev1
             # special case ``dev``
< 1.1a1
< 1.1.0dev1 # special case ``dev``
== 1.1.dev1
              # 0 is inserted before string
< 1.1.a1
< 1.1.0rc1
< 1.1.0
== 1.1
< 1.1.0post1 # special case ``post``
== 1.1.post1 # 0 is inserted before string
             # special case ``post`
< 1.1 \text{post1}
< 1996.07.12
< 1!0.4.1
             # epoch increased
< 1!3.1.1.6
< 2!0.4.1
             # epoch increased again
```

Some packages (most notably OpenSSL) have incompatible version conventions. In particular, OpenSSL interprets letters as version counters rather than pre-release identifiers. For OpenSSL, the relation 1.0.1 < 1.0.1a => True # for OpenSSL holds, whereas conda packages use the opposite ordering. You can work around this problem by appending a dash to plain version numbers:

1.0.1a => 1.0.1post.a # ensure correct ordering for OpenSSL

Package search and install specifications

Conda supports the following specifications for conda search and conda install.

Package search

conda search for a specific package or set of packages can be accomplished in several ways. This section includes information on the standard specification and the use of key-value pairs.

Standard specification



channel

(Optional) Can either be a channel name or URL. Channel names may include letters, numbers, dashes, and underscores.

subdir

(Optional) A subdirectory of a channel. Many subdirs are used for architectures, but this is not required. Must have a channel and backslash preceding it. For example: main/noarch

name

(Required) Package name. May include the * wildcard. For example, *py* returns all packages that have "py" in their names, such as "numpy", "pytorch", "python", etc.

version

(Optional) Package version. May include the * wildcard or a version range(s) in single quotes. For example: numpy=1.17.* returns all numpy packages with a version containing "1.17." and numpy>1.17,<1.19.2 returns all numpy packages with versions greater than 1.17 and less than 1.19.2.

build

(Optional) Package build name. May include the * wildcard. For example, numpy 1.17.3 py38* returns all version 1.17.3 numpy packages with a build name that contains the text "py38".

Key-value pairs

Package searches can also be performed using what is called "key-value pair notation", which has different rules than the *Standard specification* example image. The search below will return the same list of packages as the standard specification.

\$ conda search "numpy[channel=conda-forge, subdir=linux-64, version=1.17.*, build=py38*]"

This notation supports the following key-value pairs:

- build	#	validated	via	GlobStrMatch
<pre>- build_number</pre>	#	validated	via	BuildNumberMatch
- channel	#	validated	via	ChannelMatch
- features	#	validated	via	FeatureMatch
- fn	#	validated	via	ExactStrMatch
- license	#	validated	via	CaseInsensitiveStrMatch
 license_family 	#	validated	via	CaseInsensitiveStrMatch
- md5	#	validated	via	ExactStrMatch
- name	#	validated	via	GlobLowerStrMatch
- sha256	#	validated	via	ExactStrMatch
- subdir	#	validated	via	ExactStrMatch
 track_features 	#	validated	via	FeatureMatch
- url	#	validated	via	ExactStrMatch
- version	#	validated	via	VersionSpec

Key-value pair notation can be used at the same time as standard notation.

\$ conda search "conda-forge::numpy=1.17.3[subdir=linux-64, build=py38*]"

Warning: Any search values using the key-value pair notation will override values in the rest of the search string. For example, conda search numpy 1.17.3[version=1.19.2] will return packages with the version 1.19.2.

Package installation

When you're installing packages, conda recommends being as concrete as possible. Using * wildcards and version ranges during an install will most likely cause a conflict.

However, * wildcards can still be helpful in an install command when used sparingly.

Installing with wildcards

Let's say you are working on a project that requires version 2.3 of a package. If you upgrade to 2.4 or 3.0, your project will break. You're also using an environment file to create your environment.

In the version 2.3.1, 2 is the major version, 3 is the minor version, and 1 is the patch. Patches typically contain bug fixes, so if you want to keep version 2.3 in your environment without updating to 2.4 or 3.0, but want to take advantage of any bug fixes, using 2.3.* in your environment file would be helpful to you.

Concrete install example

Let's take the search from the *Package search* section.

\$ conda search "conda-forge/linux-64::numpy 1.17.* py38*"

This returns the following:

Loading channels: do	one		
# Name	Version	Build	Channel
numpy	1.17.3	py38h95a1406_0	conda-forge
numpy	1.17.5	py38h18fd61f_1	conda-forge
numpy	1.17.5	py38h95a1406_0	conda-forge

You can then choose a specific version and build, if necessary, and edit your conda install command accordingly.

\$ conda install "conda-forge/linux-64::numpy 1.17.5 py38h95a1406_0"

Channels

What is a "channel"?

Channels are the locations where packages are stored. They serve as the base for hosting and managing packages. Conda *packages* are downloaded from remote channels, which are URLs to directories containing conda packages. The conda command searches a set of channels. By default, packages are automatically downloaded and updated from the default channel, which may require a paid license, as described in the repository terms of service. The conda-forge channel is free for all to use. You can modify which remote channels are automatically searched; this feature is beneficial when maintaining a private or internal channel. For details, see how to *modify your channel lists*.

We use conda-forge as an example channel. Conda-forge is a community channel made up of thousands of contributors. Conda-forge itself is analogous to PyPI but with a unified, automated build infrastructure and more peer review of recipes.

Specifying channels when installing packages

• From the command line use --channel

\$ conda install scipy --channel conda-forge

You may specify multiple channels by passing the argument multiple times:

\$ conda install scipy --channel conda-forge --channel bioconda

Priority decreases from left to right - the first argument is higher priority than the second.

• From the command line use --*override-channels* to only search the specified channel(s), rather than any channels configured in .condarc. This also ignores conda's default channels.

```
$ conda search scipy --channel file:/<path to>/local-channel --override-channels
```

• In .condarc, use the key channels to see a list of channels for conda to search for packages.

Learn more about managing channels.

Conda clone channel RSS feed

We offer a RSS feed that represents all the things that have been cloned by the channel clone and are now available behind the CDN (content delivery network). The RSS feed shows what has happened on a rolling, two-week time frame and is useful for seeing where packages are or if a sync has been run.

Let's look at the conda-forge channel RSS feed as an example.

In that feed, it will tell you every time that it runs a sync. The feed includes other entries for packages that were added or removed. Each entry is formatted to show the subdirectory the package is from, the action that was taken (addition or removal), and the name of the package. Everything has a publishing date, per standard RSS practice.

```
<rss version="0.91">
 <channel>
   <title>conda-forge updates</title>
   <link>https://anaconda.org</link>
   <description>Updates in the last two weeks</description>
   <language>en</language>
   <copyright>Copyright 2019, Anaconda, Inc.</copyright>
   <pubDate>30 Jul 2019 19:45:47 UTC</pubDate>
      <item>
        <title>running sync</title>
        <pubDate>26 Jul 2019 19:26:36 UTC</pubDate>
      </item>
      <item>
        <title>linux-64:add:jupyterlab-1.0.4-py36_0.tar.bz2</title>
        <pubDate>26 Jul 2019 19:26:36 UTC</pubDate>
      </item>
      <item>
        <title>linux-64:add:jupyterlab-1.0.4-py37_0.tar.bz2</title>
        <pubDate>26 Jul 2019 19:26:36 UTC</pubDate>
      </item>
```

Environments

An environment is a directory that contains a specific collection of packages that you have installed. For example, you may have one environment with NumPy 1.7 and its dependencies, and another environment with NumPy 1.6 for legacy testing. If you change one environment, your other environments are not affected. You can easily activate or deactivate environments, which is how you switch between them. You can also share your environment with someone by giving them a copy of your environment.yaml file. For more information, see *Managing environments*.

Conda directory structure

ROOT_DIR

The directory that Anaconda or Miniconda was installed into.

EXAMPLES:

/opt/Anaconda #Linux C:\Anaconda #Windows

/pkgs

Also referred to as PKGS_DIR. This directory contains decompressed packages, ready to be linked in conda environments. Each package resides in a subdirectory corresponding to its canonical name.

/envs

The system location for additional conda environments to be created.

The following subdirectories comprise the default Anaconda environment:

/bin /include /lib /share

Other conda environments usually contain the same subdirectories as the default environment.

Virtual environments

A virtual environment is a tool that helps to keep dependencies required by different projects separate by creating isolated spaces for them that contain per-project dependencies for them.

Users can create virtual environments using one of several tools such as Pipenv or Poetry, or a conda virtual environment. Pipenv and Poetry are based around Python's built-in venv library, whereas conda has its own notion of virtual environments that is lower-level (Python itself is a dependency provided in conda environments).

Scroll to the right in the table below.

Some other traits are:

	Python virtual environment	Conda virtual environment
Libraries	Statically link, vendor libraries in wheels, or use apt/yum/brew/etc.	Install system-level libraries as conda depen- dencies.
System	Depend on base system install of Python.	Python is independent from system.
Extending environ- ment	Extend environment with pip.	Extended environment with conda or pip.
Non-Python de- pendencies		Manages non-Python dependencies (R, Perl, arbitrary executables).
Tracking depen- dencies		Tracks binary dependencies explicitly.

Why use venv-based virtual environments

- You prefer their workflow or spec formats.
- You prefer to use the system Python and libraries.
- Your project maintainers only publish to PyPI, and you prefer packages that come more directly from the project maintainers, rather than someone else providing builds based on the same code.

Why use conda virtual environments?

- You want control over binary compatibility choices.
- You want to utilize newer language standards, such as C++ 17.
- You need libraries beyond what the system Python offers.
- You want to manage packages from languages other than Python in the same space.

Workflow differentiators

Some questions to consider as you determine your preferred workflow and virtual environment:

- Is your environment shared across multiple code projects?
- Does your environment live alongside your code or in a separate place?
- Do your install steps involve installing any external libraries?
- Do you want to ship your environment as an archive of some sort containing the actual files of the environment?

Package system differentiators

There are potential benefits for choosing PyPI or conda.

PyPI has one global namespace and distributed ownership of that namespace. Because of this, it is easier within PyPI to have single sources for a package directly from package maintainers.

Conda has unlimited namespaces (channels) and distributed ownership of a given channel. As such, it is easier to ensure binary compatibility within a channel using conda.

Installing with conda

Conda packages can be installed by running the following command:

```
conda install <package>
```

When conda installs a package, it is automatically added to your active environment. These packages are collections of files and directories that make up everything you need to use that particular library or software. For Python packages, these are primarily Python files that can be imported into other Python applications, but for compiled software packages, such as **ffmpeg**, these are typically binary executables you use directly on your computer.

Note

If you would like to learn more about how environments are structured, head over to conda environments.

Below is a more precise overview of everything that happens during the installation process for a single package:

- Currently configured channels (e.g. defaults or conda-forge) are read in order of priority
- · Repodata for these configured channels is downloaded and read
- The repodata is searched for the package, starting with the highest priority channel first
- Once the package is found, conda makes a separate download request and then installs it
- This process then repeats for each of the package's dependencies, if there are any

A graphic illustration of this process is shown below:



Conda update versus conda install

conda update updates packages to the latest compatible version. conda install can be used to install any version. Example:

- If Python 2.7.0 is currently installed, and the latest version of Python 2 is 2.7.5, then conda update python installs Python 2.7.5. It does not install Python 3.
- If Python 3.7.0 is currently installed, and the latest version of Python is 3.9.0, then conda install python=3 installs Python 3.9.0.

Conda uses the same rules for other packages. conda update always installs the highest version with the same major version number, whereas conda install always installs the highest version.

Installing conda packages offline

To install conda packages offline, run: conda install /path-to-package/package-filename.tar.bz2/

If you prefer, you can create a /tar/ archive file containing many conda packages and install them all with one command: conda install /packages-path/packages-filename.tar

Note: If an installed package does not work, it may be missing dependencies that need to be resolved manually.

Installing packages directly from the file does not resolve dependencies.

Installing conda packages with a specific build number

If you want to install conda packages with the correct package specification, try pkg_name=version=build_string. Read more about build strings and package naming conventions. Learn more about package specifications and metadata.

For example, if you want to install llvmlite 0.31.0dev0 on Python 3.7.8, you would enter:

conda install -c numba/label/dev llvmlite=0.31.0dev0=py37_8

Performance

Conda's performance can be affected by a variety of things. Unlike many package managers, Anaconda's repositories generally don't filter or remove old packages from the index. This allows old environments to be easily recreated. However, it does mean that the index metadata is always growing, and thus conda becomes slower as the number of packages increases.

How a package is installed

While you are waiting, conda is doing a lot of work installing the packages. At any point along these steps, performance issues may arise.

Conda follows these steps when installing a package:

- 1. Downloading and processing index metadata.
- 2. Reducing the index.
- 3. Expressing the package data and constraints as a SAT problem.
- 4. Running the solver.
- 5. Downloading and extracting packages.
- 6. Verifying package contents.
- 7. Linking packages from package cache into environments.

Therefore, if you're experiencing a slowdown, evaluate the following questions to identify potential causes:

- Are you creating a new environment or installing into an existing one?
- Does your environment have pip-installed dependencies in it?
- What channels are you using?
- What packages are you installing?
- Is the channel metadata sane?
- Are channels interacting in bad ways?

Improving conda performance

To address these challenges, you can move packages to archive channels and follow the methods below to present conda with a smaller, simpler view than all available packages.

To speed up conda, we offer the following recommendations.

Are you:

- Using conda-forge?
 - Use conda-metachannel to reduce conda's problem size.
- Using bioconda?
 - Use conda-metachannel to reduce conda's problem size.
 - Read more about docker images.
- Specifying very broad package specs?
 - Be more specific. Letting conda filter more candidates makes it faster. For example, instead of numpy, we recommend numpy=1.15 or, even better, numpy=1.15.4.
 - If you are using R, instead of specifying only r-essentials, specify r-base=3.5 r-essentials.
- · Feeling frustrated with "verifying transaction" and also feeling lucky?
 - Run conda config --set safety_checks disabled.
- · Getting strange mixtures of defaults and conda-forge?

- Run conda config --set channel_priority strict.
- This also makes things go faster by eliminating possible mixed solutions.
- · Observing that an Anaconda or Miniconda installation is getting slower over time?
 - Create a fresh environment. As environments grow, they become harder and harder to solve. Working with small, dedicated environments can be much faster.

Read more about how we made conda faster.

Set strict channel priority

Setting strict channel priority makes it so that if a package exists on a channel, conda will ignore all packages with the same name on lower priority channels.



This can dramatically reduce package search space and reduces the use of improperly constrained packages.

One thing to consider is that setting strict channel priority may make environments unsatisfiable. Learn more about *Strict channel priority*.

Reduce the index

One option for speeding up conda is to reduce the index. The index is reduced by conda based upon the user's input specs. It's likely that your repodata contains package data that is not used in the solving stage. Filtering out these unnecessary packages before solving can save time.

Making your input specifications more specific improves the effectiveness of the index reduction and, thus, speeds up the process. Listing a version and build string for each of your specs can dramatically reduce the number of packages that are considered when solving so that the SAT doesn't have as much work to do.

Reducing the index:

- Reduces unnecessary input into generating solver clauses.
- Reduces solve complexity.
- Prefers newer packages that apply constraints.

Read more on Understanding and Improving Conda's Performance.

Conda for data scientists

Conda is useful for any packaging process but it stands out from other package and environment management systems through its utility for data science.

Conda's benefits include:

- Providing prebuilt packages which avoid the need to deal with compilers or figuring out how to set up a specific tool.
- Managing one-step installation of tools that are more challenging to install (such as TensorFlow or IRAF).
- Allowing you to provide your environment to other people across different platforms, which supports the reproducibility of research workflows.
- Allowing the use of other package management tools, such as pip, inside conda environments where a library or tools are not already packaged for conda.
- Providing commonly used data science libraries and tools, such as R, NumPy, SciPy, and TensorFlow. These are built using optimized, hardware-specific libraries (such as Intel's MKL or NVIDIA's CUDA) which speed up performance without code changes.

Read more about how conda supports data scientists.

Plugins

In order to enable customization and extra features that are compatible with and discoverable by conda (but do not necessarily ship as a default part of the conda codebase), an official conda plugin mechanism has been implemented as of version 22.11.0.

Implementation

Plugins in conda integrate the "hook + entry point" structure by utilizing the Pluggy Python framework. This implementation can be broken down via the following two steps:

- Define the hook(s) to be registered
- Register the plugin under the conda entrypoint namespace

Hook

Below is an example of a very basic plugin "hook":

Listing 1: my_plugin.py

```
import conda.plugins
```

```
@conda.plugins.hookimpl
def conda_subcommands(): ....
```

Packaging using a pyproject.toml file

Below is an example that configures setuptools using a pyproject.toml file (note that the setup.py file is optional if a pyproject.toml file is defined, and thus will not be discussed here):

```
Listing 2: pyproject.toml
```

```
[build-system]
requires = ["setuptools", "setuptools-scm"]
build-backend = "setuptools.build_meta"
[project]
name = "my-conda-plugin"
version = "1.0.0"
description = "My conda plugin"
requires-python = ">=3.7"
dependencies = ["conda"]
[project.entry-points."conda"]
my-conda-plugin = "my_plugin"
```

Conda plugins use cases

The new conda plugin API ecosystem brings about many possibilities, including but not limited to:

- Custom subcommands
- Support for packaging-related topics (e.g., virtual packages)
- Development environment integrations (e.g., shells)
- · Alternative dependency solver backends

- · Network adapters
- Build system integrations
- Non-Python language support (e.g., C, Rust)
- Experimental features that are not currently covered by conda

Benefits of conda plugins

A conda plugin ecosystem enables contributors across the conda community to develop and share new features, thus bringing about more functionality and focus on the user experience. Though the list below is by no means exhaustive, some of the benefits of conda plugins include:

- Support for a better distribution of maintenance in the conda community
- Enabling third party contributors to use official APIs instead of having to divert to workarounds and wrappers
- The ability to extend conda internals via official APIs
- Lowering the barrier for contributions from other stakeholders in the conda ecosystem
- ... and much more!

In this section, we provide you with detailed information about the fundamental concepts in conda, including information about packages, channels, environments, and plugins, among others.

Commands

Conda commands are your interface for interacting with everything

Packages

Learn about the different forms a package can take

Package specification

Learn about exactly what belongs in a package and what the different metadata files mean

Package search and install

The search specifications for a package (for the conda install and conda search commands)

Channels

Learn about channels and how they host packages

Environments

Learn about how environments work and how they differ from Python's virtual environments

Installing with conda

Take a deep dive into exactly what happens during an installation with conda

Performance

Understand what impacts the performance and speed of conda and how to improve it

Conda for data scientists

See why conda is a such a valuable tool for data scientists

Plugins

The behavior of conda can be extended via plugins; learn more here

4.1.6 Troubleshooting

Using conda in Windows Batch script exits early

In conda 4.6+, the way that you interact with conda goes through a batch script (%PREFIX%\condabin\conda.bat). Unfortunately, this means it's a little complicated to use conda from other batch scripts. When using batch scripts from within batch scripts, you must prefix your command with CALL. If you do not do this, your batch script that calls conda will exit immediately after the conda usage. In other words, if you write this in a .bat file:

conda create myenv python conda activate myenv echo test

Neither the activation, nor the echo will happen. You must write this in your batch script:

CALL conda create myenv python CALL conda activate myenv echo test

This is known behavior with cmd.exe, and we have not found any way to change it. https://stackoverflow.com/questions/ 4798879/how-do-i-run-a-batch-script-from-within-a-batch-script/4798965

NumPy MKL library load failed

Error messages like

Intel MKL FATAL ERROR: Cannot load mkl_intel_thread.dll

or

The ordinal 241 could **not** be located **in** the the dynamic link library

Cause

NumPy is unable to load the correct MKL or Intel OpenMP runtime libraries. This is almost always caused by one of two things:

- 1. The environment with NumPy has not been activated.
- 2. Another software vendor has installed MKL or Intel OpenMP (libiomp5md.dll) files into the C:\Windows\System32 folder. These files are being loaded before Anaconda's and they're not compatible.

Solution

If you are not activating your environments, start with doing that. There's more info at *Activating environments*. If you are still stuck, you may need to consider more drastic measures.

 Remove any MKL-related files from C:\Windows\System32. We recommend renaming them to add .bak to the filename to effectively hide them. Observe if any other software breaks. Try moving the DLL files alongside the .exe of the software that broke. If it works again, you can keep things in the moved state - Anaconda doesn't need MKL in System32, and no other software should need it either. If you identify software that is installing software here, please contact the creators of that software. Inform them that their practice of installing MKL to a global location is fragile and is breaking other people's software and wasting a lot of time. See the list of guilty parties below.

- 2. You may try a special DLL loading mode that Anaconda builds into Python. This changes the DLL search path from System32 first to System32 as another entry on PATH, allowing libraries in your conda environment to be found before the libraries in System32. Control of this feature is done with environment variables. Only Python builds beyond these builds will react to these environment variables:
 - Python 2.7.15 build 14
 - Python 3.6.8 build 7
 - Python 3.7.2 build 8

To update Python from the defaults channel:

conda update -c defaults python

Note: Anaconda has built special patches into its builds of Python to enable this functionality. If you get your Python package from somewhere else (e.g. conda-forge), these flags may not do anything.

Control environment variables:

- CONDA_DLL_SEARCH_MODIFICATION_ENABLE
- CONDA_DLL_SEARCH_MODIFICATION_DEBUG
- CONDA_DLL_SEARCH_MODIFICATION_NEVER_ADD_WINDOWS_DIRECTORY
- CONDA_DLL_SEARCH_MODIFICATION_NEVER_ADD_CWD

To set variables on Windows, you may use either the CLI or a Windows GUI.

- CLI: https://superuser.com/questions/79612/setting-and-getting-windows-environment-variables-from-the-command-79614
- GUI: http://www.dowdandassociates.com/blog/content/howto-set-an-environment-variable-in-windows-gui/

These should be set to a value of 1 to enable them. For example, in a terminal:

set CONDA_DLL_SEARCH_MODIFICATION_ENABLE=1

Note: Only CONDA_DLL_SEARCH_MODIFICATION_ENABLE should be set finally.

List of known software that installs Intel libraries to C:\Windows\System32:

- Amplitube, by IK Multimedia
- ASIO4ALL, by Michael Tippach

If you find others, please let us know. If you're on this list and you want to fix things, let us know. In either case, the conda issue tracker at https://github.com/conda/conda/issues is the best way to reach us.

SSL connection errors

This is a broad umbrella of errors with many causes. Here are some we've seen.

CondaHTTPError: HTTP 000 CONNECTION FAILED

If you're on Windows and you see this error, look a little further down in the error text. Do you see something like this?:

```
SSLError(MaxRetryError('HTTPSConnectionPool(host=\'repo.anaconda.com\', port=443): Max_

→retries exceeded with url: /pkgs/r/win-32/repodata.json.bz2 (Caused by SSLError("Can\

→'t connect to HTTPS URL because the SSL module is not available."))'))
```

The key part there is the last bit:

```
Caused by SSLError("Can\'t connect to HTTPS URL because the SSL module is not available. →")
```

Conda is having problems because it can't find the OpenSSL libraries that it needs.

Cause

You may observe this error cropping up after a conda update. More recent versions of conda and more recent builds of Python are more strict about requiring activation of environments. We're working on better error messages for them, but here's the story for now. Windows relies on the PATH environment variable as the way to locate libraries that are not in the immediate folder, and also not in the C:\Windows\System32 folder. Searching for libraries in the PATH folders goes from left to right. If you choose to put Anaconda's folders on PATH, there are several of them:

- (install root)
- (install root)/Library/mingw-w64/bin
- (install root)/Library/usr/bin
- (install root)/Library/bin
- (install root)/Scripts
- (install root)/bin
- (install root)/condabin

Early installers for Anaconda put these on PATH. That was ultimately fragile because Anaconda isn't the only software on the system. If other software had similarly named executables or libraries, and came earlier on PATH, Anaconda could break. On the flip side, Anaconda could break other software if Anaconda were earlier in the PATH order and shadowed any other executables or libraries. To make this easier, we began recommending "activation" instead of modifying PATH. Activation is a tool where conda sets your PATH, and also runs any custom package scripts which are often used to set additional environment variables that are necessary for software to run (e.g. JAVA_HOME). Because activation runs only in a local terminal session (as opposed to the permanent PATH entry), it is safe to put Anaconda's PATH entries first. That means that Anaconda's libraries get higher priority when you're running Anaconda but Anaconda doesn't interfere with other software when you're not running Anaconda.

Anaconda's Python interpreter included a patch for a long time that added the (install root)/Library/bin folder to that Python's PATH. Unfortunately, this interfered with reasoning about PATH at all when using that Python interpreter. We removed that patch in Python 3.7.0, and we regret that this has caused problems for people who are not activating their environments and who otherwise do not have the proper entries on PATH. We're experimenting with approaches

that will allow our executables to be less dependent on PATH and more self-aware of their needed library load paths. For now, though, the only solutions to this problem are to manage PATH properly.

Our humble opinion is that activation is the easiest way to ensure that things work. See more information on activation in *Activating environments*.

Solution

Use shells opened from Anaconda Navigator. If you use a GUI IDE and you see this error, ask the developers of your IDE to add activation for conda environments.

SSL certificate errors

Cause

Installing packages may produce a "connection failed" error if you do not have the certificates for a secure connection to the package repository.

Solution

Pip can use the --use-feature=truststore option to use the operating system certificate store. This may be of help in typically corporate environments with https traffic inspection, where the corporate CA is installed in the operating system certificate store:

pip install --use-feature=truststore

Conda has a similar option:

conda config --set ssl_verify truststore

Alternatively, pip can use the --trusted-host option to indicate that the URL of the repository is trusted:

```
pip install --trusted-host pypi.org
```

Conda has three similar options.

1. The option --insecure or -k ignores certificate validation errors for all hosts.

Running conda create --help shows:

Networking Options: -k, --insecure Allow conda to perform "insecure" SSL connections and transfers. Equivalent to setting 'ssl_verify' to 'False'.

2. The configuration option ssl_verify can be set to False.

Running conda config --describe ssl_verify shows:

```
# # ssl_verify (bool, str)
# # aliases: verify_ssl
# # conda verifies SSL certificates for HTTPS requests, just like a web
# # browser. By default, SSL verification is enabled and conda operations
(continues on)
```

(continues on next page)

(continued from previous page)

```
# # will fail if a required URL's certificate cannot be verified. Setting
# # ssl_verify to False disables certification verification. The value for
# # ssl_verify can also be (1) a path to a CA bundle file, (2) a path to a
# # directory containing certificates of trusted CA, or (3) 'truststore'
# # to use the operating system certificate store.
# #
# ssl_verify: true
```

Running conda config --set ssl_verify false modifies ~/.condarc and sets the -k flag for all future conda operations performed by that user. Running conda config --help shows other configuration scope options.

When using conda config, the user's conda configuration file at ~/.condarc is used by default. The flag --system will instead write to the system configuration file for all users at <CONDA_BASE_ENV>/.condarc. The flag --env will instead write to the active conda environment's configuration file at <PATH_TO_ACTIVE_CONDA_ENV>/.condarc. If --env is used and no environment is active, the user configuration file is used.

3. The configuration option ssl_verify can be used to install new certificates.

Running conda config --describe ssl_verify shows:

```
# # ssl_verify (bool, str)
# #
     aliases: verify_ssl
# #
     conda verifies SSL certificates for HTTPS requests, just like a web
# #
     browser. By default, SSL verification is enabled, and conda operations
     will fail if a required URL's certificate cannot be verified. Setting
# #
# #
     ssl_verify to False disables certification verification. The value for
     ssl_verify can also be (1) a path to a CA bundle file, (2) a path to a
# #
# #
     directory containing certificates of trusted CA, or (3) 'truststore'
# #
     to use the operating system certificate store.
# #
# ssl_verify: true
```

Your network administrator can give you a certificate bundle for your network's firewall. Then ssl_verify can be set to the path of that certificate authority (CA) bundle and package installation operations will complete without connection errors.

When using conda config, the user's conda configuration file at ~/.condarc is used by default. The flag --system will instead write to the system configuration file for all users at <CONDA_BASE_ENV>/.condarc. The flag --env will instead write to the active conda environment's configuration file at <PATH_TO_ACTIVE_CONDA_ENV>/.condarc. If --env is used and no environment is active, the user configuration file is used.

SSL verification errors

Cause

This error may be caused by lack of activation on Windows or expired certifications:

```
SSL verification error: [SSL: CERTIFICATE_VERIFY_FAILED] certificate verify failed (_ssl.
→c:590)
```

Solution

Make sure your conda is up-to-date: conda --version

If not, run: conda update conda

Try using the operating system certificate store. Set you ssl_verify variable to truststore using the following command:

conda config --set ssl_verify truststore

If using the operating system certificate store does not solve your issue, temporarily set your ssl_verify variable to false, upgrade the requests package, and then set ssl_verify back to true using the following commands:

```
conda config --set ssl_verify false
conda update requests
conda config --set ssl_verify true
```

You can also set ssl_verify to a string path to a certificate, which can be used to verify SSL connections. Modify your .condarc and include the following:

ssl_verify: path-to-cert/chain/filename.ext

If the repository uses a self-signed certificate, use the actual path to the certificate. If the repository is signed by a private certificate authority (CA), the file needs to include the root certificate and any intermediate certificates.

Permission denied errors during installation

Cause

The umask command determines the mask settings that control how file permissions are set for newly created files. If you have a very restrictive umask, such as 077, you get "permission denied" errors.

Solution

Set a less restrictive umask before calling conda commands. Conda was intended as a user space tool, but often users need to use it in a global environment. One place this can go awry is with restrictive file permissions. Conda creates links when you install files that have to be read by others on the system.

To give yourself full permissions for files and directories but prevent the group and other users from having access:

- 1. Before installing, set the umask to 007.
- 2. Install conda.
- 3. Return the umask to the original setting:

```
umask 007
conda install
umask 077
```

For more information on umask, see http://en.wikipedia.org/wiki/Umask.
Permission denied errors after using sudo conda command

Solution

Once you run conda with sudo, you must use sudo forever. We recommend that you NEVER run conda with sudo.

Already installed error message

Cause

If you are trying to fix conda problems without removing the current installation and you try to reinstall Miniconda or Anaconda to fix it, you get an error message that Miniconda or Anaconda is already installed and you cannot continue.

Solution

Install using the --force option.

Download and install the appropriate Miniconda for your operating system from the Miniconda download page using the force option --force or -f:

bash Miniconda3-latest-MacOSX-x86_64.sh -f

Note: Substitute the appropriate filename and version for your operating system.

Note: Be sure that you install to the same location as your existing install so it overwrites the core conda files and does not install a duplicate in a new folder.

Conda reports that a package is installed, but it appears not to be

Sometimes conda claims that a package is already installed but it does not appear to be, for example, a Python package that gives ImportError.

There are several possible causes for this problem, each with its own solution.

Cause

You are not in the same conda environment as your package.

Solution

- 1. Make sure that you are in the same conda environment as your package. The conda info command tells you what environment is currently active under default environment.
- 2. Verify that you are using the Python from the correct environment by running:



Cause

For Python packages, you have set the PYTHONPATH or PYTHONHOME variable. These environment variables cause Python to load files from locations other than the standard ones. Conda works best when these environment variables are not set, as their typical use cases are obviated by conda environments and a common issue is that they cause Python to pick up the wrong or broken versions of a library.

Solution

For Python packages, make sure you have not set the PYTHONPATH or PYTHONHOME variables. The command conda info -a displays the values of these environment variables.

- To unset these environment variables temporarily for the current terminal session, run unset PYTHONPATH.
- To unset them permanently, check for lines in the files:
 - If you use bash----/.bashrc, ~/.bash_profile, ~/.profile.
 - If you use zsh---~/.zshrc.
 - If you use PowerShell on Windows, the file output by \$PROFILE.

Cause

You have site-specific directories or, for Python, you have so-called site-specific files. These are typically located in \sim /.local on macOS and Linux. For a full description of the locations of site-specific packages, see PEP 370. As with PYTHONPATH, Python may try importing packages from this directory, which can cause issues.

Solution

For Python packages, remove site-specific directories and site-specific files.

Cause

For C libraries, the following environment variables have been set:

- macOS---DYLD_LIBRARY_PATH.
- Linux---LD_LIBRARY_PATH.

These act similarly to PYTHONPATH for Python. If they are set, they can cause libraries to be loaded from locations other than the conda environment. Conda environments obviate most use cases for these variables. The command conda info -a shows what these are set to.

Solution

Unset DYLD_LIBRARY_PATH or LD_LIBRARY_PATH.

Cause

Occasionally, an installed package becomes corrupted. Conda works by unpacking the packages in the pkgs directory and then hard-linking them to the environment. Sometimes these get corrupted, breaking all environments that use them. They also break any additional environments since the same files are hard-linked each time.

Solution

Run the command conda install -f to unarchive the package again and relink it. It also does an MD5 verification on the package. Usually if this is different it is because your channels have changed and there is a different package with the same name, version, and build number.

Note: This breaks the links to any other environments that already had this package installed, so you have to reinstall it there, too. It also means that running conda install -f a lot can use up significant disk space if you have many environments.

Note: The -f flag to conda install (--force) implies --no-deps, so conda install -f package does not reinstall any of the dependencies of package.

pkg_resources.DistributionNotFound: conda==3.6.1-6-gb31b0d4-dirty

Cause

The local version of conda needs updating.

Solution

Force reinstall conda. A useful way to work off the development version of conda is to run python setup.py develop on a checkout of the conda GitHub repository. However, if you are not regularly running git pull, it is a good idea to un-develop, as you will otherwise not get any regular updates to conda. The normal way to do this is to run python setup.py develop -u.

However, this command does not replace the conda script itself. With other packages, this is not an issue, as you can just reinstall them with conda, but conda cannot be used if conda is installed.

The fix is to use the ./bin/conda executable in the conda git repository to force reinstall conda. That is, run ./bin/ conda install -f conda. You can then verify with conda info that you have the latest version of conda, and not a git checkout. The version should not include any hashes.

macOS error "ValueError unknown locale: UTF-8"

Cause

This is a bug in the macOS Terminal app that shows up only in certain locales. Locales are country-language combinations.

Solution

- 1. Open Terminal in /Applications/Utilities
- 2. Clear the Set locale environment variables on startup checkbox.

This sets your LANG environment variable to be empty. This may cause Terminal to use incorrect settings for your locale. The locale command in Terminal tells you what settings are used.

To use the correct language, add a line to your bash profile, which is typically ~/.profile:

export LANG=your-lang

Note: Replace your-lang with the correct locale specifier for your language.

The command locale -a displays all the specifiers. For example, the language code for US English is en_US.UTF-8. The locale affects what translations are used when they are available and also how dates, currencies, and decimals are formatted.



AttributeError or missing getproxies

When running a command such as conda update ipython, you may get an AttributeError: 'module' object has no attribute 'getproxies'.

Cause

This can be caused by an old version of requests or by having the PYTHONPATH environment variable set.

Solution

Update requests and be sure PYTHONPATH is not set:

- 1. Run conda info -a to show the requests version and various environment variables such as PYTHONPATH.
- 2. Update the requests version with pip install -U requests.
- 3. Clear PYTHONPATH:
 - On Windows, clear it the environment variable settings.
 - On macOS and Linux, clear it by removing it from the bash profile and restarting the shell.

Shell commands open from the wrong location

When you run a command within a conda environment, conda does not access the correct package executable.

Cause

In both bash and zsh, when you enter a command, the shell searches the paths in PATH one by one until it finds the command. The shell then caches the location, which is called hashing in shell terminology. When you run command again, the shell does not have to search the PATH again.

The problem is that before you installed the program, you ran a command which loaded and hashed another version of that program in some other location on the PATH, such as /usr/bin. Then you installed the program using conda install, but the shell still had the old instance hashed.

Solution

Reactivate the environment or run hash -r (in bash) or rehash (in zsh).

When you run conda activate, conda automatically runs hash -r in bash and rehash in zsh to clear the hashed commands, so conda finds things in the new path on the PATH. But there is no way to do this when conda install is run because the command must be run inside the shell itself, meaning either you have to run the command yourself or used a source file that contains the command.

This is a relatively rare problem, since this happens only in the following circumstances:

- 1. You activate an environment or use the root environment, and then run a command from somewhere else.
- 2. Then you conda install a program, and then try to run the program again without running activate or deactivate.

The command type command_name always tells you exactly what is being run. This is better than which command_name, which ignores hashed commands and searches the PATH directly. The hash is reset by conda activate or by hash -r in bash or rehash in zsh.

Programs fail due to invoking conda Python instead of system Python

Cause

After installing Anaconda or Miniconda, programs that run python switch from invoking the system Python to invoking the Python in the root conda environment. If these programs rely on the system Python to have certain configurations or dependencies that are not in the root conda environment Python, the programs may crash. For example, some users of the Cinnamon desktop environment on Linux Mint have reported these crashes.

Solution

Edit your .bash_profile and .bashrc files so that the conda binary directory, such as ~/miniconda3/bin, is no longer added to the PATH environment variable. You can still run conda activate and conda deactivate by using their full path names, such as ~/miniconda3/bin/conda.

You may also create a folder with symbolic links to conda activate and conda deactivate and then edit your . bash_profile or .bashrc file to add this folder to your PATH. If you do this, running python will invoke the system Python, but running conda commands, conda activate MyEnv, conda activate root, or conda deactivate will work normally.

After running conda activate to activate any environment, including after running conda activate root, running python will invoke the Python in the active conda environment.

UnsatisfiableSpecifications error

Cause

Some conda package installation specifications are impossible to satisfy. For example, conda create -n tmp python=3 wxpython=3 produces an "Unsatisfiable Specifications" error because wxPython 3 depends on Python 2.7, so the specification to install Python 3 conflicts with the specification to install wxPython 3.

When an unsatisfiable request is made to conda, conda shows a message such as this one:

```
The following specifications were found to be in conflict:

- python 3*

- wxpython 3* -> python 2.7*

Use ``conda search <package> --info`` to see the dependencies

for each package.
```

This indicates that the specification to install wxpython 3 depends on installing Python 2.7, which conflicts with the specification to install Python 3.

Solution

Use conda search wxpython --info or conda search 'wxpython=3' --info to show information about this package and its dependencies:

```
wxpython 3.0 py27_0
file name : wxpython-3.0-py27_0.tar.bz2
     : wxpython
name
version
          : 3.0
build number: ◊
build string: py27_0
channel
          : defaults
           : 34.1 MB
size
           : 2014-01-10
date
           : wxpython-3.0-py27_0.tar.bz2
fn
license_family: Other
          : adc6285edfd29a28224c410a39d4bdad
md 5
priority
           : 2
schannel
           : defaults
url
           : https://repo.continuum.io/pkgs/free/osx-64/wxpython-3.0-py27_0.tar.bz2
dependencies:
   python 2.7*
   python.app
```

By examining the dependencies of each package, you should be able to determine why the installation request produced a conflict and modify the request so it can be satisfied without conflicts. In this example, you could install wxPython with Python 2.7:

conda create -n tmp python=2.7 wxpython=3

Package installation fails from a specific channel

Cause

Sometimes it is necessary to install a specific version from a specific channel because that version is not available from the default channel.

Solution

The following example describes the problem in detail and its solution.

Suppose you have a specific need to install the Python cx_freeze module with Python 3.4. A first step is to create a Python 3.4 environment:

conda create -n py34 python=3.4

Using this environment you should first attempt:

conda install -n py34 cx_freeze

However, when you do this you get the following error:

```
Using Anaconda Cloud api site https://api.anaconda.org
Fetching package metadata .........
Solving package specifications: .
Error: Package missing in current osx-64 channels:
- cx_freeze
You can search for packages on anaconda.org with
anaconda search -t conda cx_freeze
```

The message indicates that cx_freeze cannot be found in the default package channels. However, there may be a community-created version available and you can search for it by running the following command:

```
$ anaconda search -t conda cx_freeze
Using Anaconda Cloud api site https://api.anaconda.org
Run 'anaconda show <USER/PACKAGE>' to get more details:
Packages:
    Name
                        | Version | Package Types | Platforms
    ------ | ------ | ------- | -------
    inso/cx_freeze | 4.3.3 | conda | linux-64
pyzo/cx_freeze | 4.3.3 | conda | linux-64, win-32, win-64, ...
nux-32. osx-64
→linux-32, osx-64
                                    : http://cx-freeze.sourceforge.net/
    silg2/cx_freeze | 4.3.4 | conda | linux-64
                                     : create standalone executables from Python
⇔scripts
    takluyver/cx_freeze | 4.3.3 | conda
                                                      | linux-64
Found 4 packages
```

In this example, there are 4 different places that you could try to get the package. None of them are officially supported or endorsed by Anaconda, but members of the conda community have provided many valuable packages. If you want to go with public opinion, then the web interface provides more information:

Notice that the **pyzo** organization has by far the most downloads, so you might choose to use their package. If so, you can add their organization's channel by specifying it on the command line:

🛃 🍝 🛈 🖴 ht	tps://beta.anacond	a.org/search?q=cx_freeze	⊘ [+	C ↓	"å 🛡 🖛 🖬 🗄
	DA CLOUD	III -	Docs	Contact 🗸	🄰 ijstokes 🗸
cx_freeze					Q
▼ Filters Type: All ~		Access: All ~	Platform:	All ~	
♦ Favorites	- Downloads				Platforms
0	1976	pyzo / cx_freeze 4.3.3 http://cx-freeze.sourceforge.net/		conda	linux-32 linux-64 osx-64 win-32 win-64
0	96	pypi / cx_Freeze 4.3.3 create standalone executables from Python scripts		рурі	source
0	14	O inso / cx_freeze 4.3.3		conda	linux-64
0	1	Silg2/cx_freeze 4.3.4 create standalone executables from Python scripts		conda	linux-64
0	0	◯ takluyver / cx_freeze 4.3.3		conda	linux-64
		« Previous showing 1 - 5 of 5 Next »			

```
Total:
                                                          2.3 MB
The following NEW packages will be INSTALLED:
   cx_freeze: 4.3.3-py34_4
   openssl:
               1.0.2h-0
                8.1.1-py34_1
   pip:
   python:
                3.4.4-0
   readline:
                6.2-2
   setuptools: 20.7.0-py34_0
   sqlite:
               3.9.2-0
   tk:
                8.5.18-0
   wheel:
                0.29.0-py34_0
                5.0.5-1
   xz:
    zlib:
                1.2.8-0
```

Now you have a software environment sandbox created with Python 3.4 and cx_freeze.

Conda automatically upgrades to unwanted version

When making a Python package for an app, you create an environment for the app from a file req.txt that sets a certain version, such as python=2.7.9. However, when you conda install your package, it automatically upgrades to a later version, such as 2.7.10.

Cause

If you make a conda package for the app using conda-build, you can set dependencies with specific version numbers. The requirements lines that say – python could be – python ==2.7.9 instead. It is important to have 1 space before the == operator and no space after.

Solution

Exercise caution when coding version requirements.

Conda upgrade error

Cause

Downgrading conda from 4.6.1 to 4.5.x and then trying to conda install conda or conda upgrade conda will produce a solving and upgrade error similar to the following:

```
Solving environment: failed
CondaUpgradeError: This environment has previously been operated on by a conda version_

that's newer than the conda currently being used. A newer version of conda is required.

target environment location: /opt/conda

current conda version: 4.5.9

minimum conda version: 4.6
```

Solution

Change the .condarc file. Set the parameter by editing the .condarc file directly: allow_conda_downgrades: true in conda version 4.5.12. This will then let you upgrade. If you have something older than 4.5.12, install conda 4.6.1 again from the package cache.

EXAMPLE: If my conda info says package cache : /opt/conda/pkgs and my Python version is 3.7, then on the command line, type conda install /opt/conda/pkgs/conda-4.6.1-py37_0.tar.bz2 to resolve the issue.

ValidationError: Invalid value for timestamp

Cause

This happens when certain packages are installed with conda 4.3.28, and then conda is downgraded to 4.3.27 or earlier.

Solution

See https://github.com/conda/conda/issues/6096.

Unicode error after installing Python 2

Example: UnicodeDecodeError: 'ascii' codec can't decode byte 0xd3 in position 1: ordinal not in range(128)

Cause

Python 2 is incapable of handling unicode properly, especially on Windows. In this case, if any character in your PATH env. var contains anything that is not ASCII then you see this exception.

Solution

Remove all non-ASCII from PATH or switch to Python 3.

Windows environment has not been activated

Cause

You may receive a warning message if you have not activated your environment:

Warning:

This Python interpreter is in a conda environment, but the environment has not been activated. Libraries may fail to load. To activate this environment please see https://conda.io/activation

Solution

If you receive this warning, you need to activate your environment. To do so on Windows, on a terminal via PowerShell or the Command Prompt, run: call <your anaconda/miniconda install location>\Scripts\activate base.

The system cannot find the path specified on Windows

Cause

PATH does not contain entries for all of the necessary conda directories. PATH may have too many entries from 3rd party software adding itself to PATH at install time, despite the user not needing to run the software via PATH lookup.

Solution

Strip PATH to have fewer entries and activate your environment.

If there's some software that needs to be found on PATH (you run it via the CLI), we recommend that you create your own batch files to set PATH dynamically within a console session, rather than permanently modifying PATH in the system settings.

For example, a new conda prompt batch file that first strips PATH, then calls the correct activation procedure could look like:

set

```
PATH="%SystemRoot%\system32;%SystemRoot%;%SystemRoot%\System32\Wbem;%SYSTEMROOT%\

→System32\WindowsPowerShell\v1.0\;<3rd-party-entries>"

call "<miniconda/anaconda root>\Scripts\activate"
```

If you need to run 3rd party software (software other than Windows built-ins and Anaconda) from this custom conda prompt, then you should add those entries (and only those strictly necessary) to the set PATH entry above. Note that only the quotes wrapping the entire expression should be there. That is how variables are properly set in batch scripts, and these account for any spaces in any entries in PATH. No additional quotes should be within the value assigned to PATH.

To make 3rd party software take precedence over the same-named programs as supplied by conda, add it to PATH after activating conda:

set

```
"PATH=%SystemRoot%\system32;%SystemRoot%;%SystemRoot%\System32\Wbem;%SYSTEMROOT%\
→System32\WindowsPowerShell\v1.0\"
call "<miniconda/anaconda root>\Scripts\activate"
set "PATH=<3rd-party-entries>;%PATH%"
```

To make conda software take precedence, call the activation script last. Because activation prepends the conda environment PATH entries, they have priority.

set

```
PATH="%SystemRoot%\system32;%SystemRoot%;%SystemRoot%\System32\Wbem;%SYSTEMROOT%\

→System32\WindowsPowerShell\v1.0\;<3rd-party-entries>"

call "<miniconda/anaconda root>\Scripts\activate"
```

4.1.7 Cheat sheet

See the conda cheatsheet PDF (1 MB) for a single-page summary of the most important information about using conda (link always points to the latest version).

Versions

- conda 4.14.x (latest)
- conda 4.12.x
- conda 4.6.x

In this guide, you will learn the about the common tasks involved with using the conda package manager.

4.1.8 First steps

If you are brand new to conda, then these are guides that you will want to start with first:

Installing conda

Follow these instructions to get a working installation of conda on your computer

Getting started

Learn the essential commands you need in your day-to-day usage of conda

Using conda for your project

A tutorial explaining how to use conda in your projects

See also:

Check out Anaconda's free course on conda basics to learn even more.

4.1.9 Learn more

Configuring conda

Reference and explanation for all the ways you can configure conda

Working with packages

Learn how to search for and use conda packages

Working with environments

Learn how to create, update, remove, and export your conda environments

4.1.10 Additional resources

Cheat sheet

Commonly used commands organized into a PDF

Troubleshooting

Various solutions to commonly encountered problems

4.2 Configuration

```
# ##
                Channel Configuration
                                                   ##
# # channels (sequence: primitive)
# #
     aliases: channel
# #
     env var string delimiter: ','
# #
     The list of conda channels to include for relevant operations.
# #
# channels:
#
  - defaults
# # channel_alias (str)
# #
     The prepended url location to associate with channel names.
# #
# channel_alias: https://conda.anaconda.org
# # channel_settings (sequence: map)
     env var string delimiter: ','
# #
# #
     A list of mappings that allows overriding certain settings for a
     single channel. Each list item should include at least the "channel"
# #
# #
     key and the setting you would like to override.
# #
# channel_settings: []
# # default_channels (sequence: primitive)
# #
     env var string delimiter: ','
# #
     The list of channel names and/or urls used for the 'defaults'
# #
     multichannel.
# #
# default_channels:
#
  - https://repo.anaconda.com/pkgs/main
#
   - https://repo.anaconda.com/pkgs/r
# # override_channels_enabled (bool)
# #
     Permit use of the --override-channels command-line flag.
# #
# override_channels_enabled: true
# # allowlist_channels (sequence: primitive)
# #
     aliases: whitelist_channels
     env var string delimiter: ','
# #
# #
     The exclusive list of channels allowed to be used on the system. Use
# #
     of any other channels will result in an error. If conda-build channels
# #
     are to be allowed, along with the --use-local command line flag, be
     sure to include the 'local' channel in the list. If the list is empty
# #
# #
     or left undefined, no channel exclusions will be enforced.
# #
# allowlist_channels: []
```

```
# # custom_channels (map: primitive)
      A map of key-value pairs where the key is a channel name and the value
# #
      is a channel location. Channels defined here override the default
# #
      'channel_alias' value. The channel name (key) is not included in the
# #
      channel location (value). For example, to override the location of
# #
      the 'conda-forge' channel where the url to repodata is
# #
# #
      https://anaconda-repo.dev/packages/conda-forge/linux-64/repodata.json,
# #
      add an entry 'conda-forge: https://anaconda-repo.dev/packages'.
# #
# custom_channels:
   pkgs/pro: https://repo.anaconda.com
#
# # custom_multichannels (map: sequence)
# #
     A multichannel is a metachannel composed of multiple channels. The two
     reserved multichannels are 'defaults' and 'local'. The 'defaults'
# #
     multichannel is customized using the 'default_channels' parameter. The
# #
      'local' multichannel is a list of file:// channel locations where
# #
# #
      conda-build stashes successfully-built packages. Other multichannels
# #
      can be defined with custom_multichannels, where the key is the
      multichannel name and the value is a list of channel names and/or
# #
# #
      channel urls.
# #
# custom_multichannels: {}
# # migrated_channel_aliases (sequence: primitive)
      env var string delimiter: ','
# #
      A list of previously-used channel_alias values. Useful when switching
# #
# #
      between different Anaconda Repository instances.
# #
# migrated_channel_aliases: []
# # migrated_custom_channels (map: primitive)
# #
      A map of key-value pairs where the key is a channel name and the value
# #
     is the previous location of the channel.
# #
# migrated_custom_channels: {}
# # add_anaconda_token (bool)
# #
      aliases: add binstar token
# #
      In conjunction with the anaconda command-line client (installed with
# #
      `conda install anaconda-client`), and following logging into an
# #
      Anaconda Server API site using `anaconda login`, automatically apply a
# #
     matching private token to enable access to private packages and
# #
      channels.
# #
# add_anaconda_token: true
# # allow_non_channel_urls (bool)
      Warn, but do not fail, when conda detects a channel url is not a valid
# #
# #
      channel.
# #
# allow_non_channel_urls: false
```

```
(continued from previous page)
```

```
# # restore_free_channel (bool)
# #
                        Add the "free" channel back into defaults, behind
      "main" in priority. The "free"
                                                     channel was removed
# #
      from the collection of default channels in conda 4.7.0.
# #
# #
# restore free channel: false
# # repodata_fns (sequence: primitive)
# #
      env var string delimiter: ','
# #
     Specify filenames for repodata fetching. The default is
# #
      ('current_repodata.json', 'repodata.json'), which tries a subset of
# #
      the full index containing only the latest version for each package,
      then falls back to repodata.json. You may want to specify something
# #
      else to use an alternate index that has been reduced somehow.
# #
# #
# repodata_fns:
#
    - current_repodata.json
#
    - repodata.json
# # use_only_tar_bz2 (NoneType, bool)
     A boolean indicating that only .tar.bz2 conda packages should be
# #
# #
     downloaded. This is forced to True if conda-build is installed and
# #
     older than 3.18.3, because older versions of conda break when conda
# #
      feeds it the new file format.
# #
# use_only_tar_bz2:
# # repodata_threads (int)
# #
      Threads to use when downloading and reading repodata. When not set,
# #
      defaults to None, which uses the default ThreadPoolExecutor behavior.
# #
# repodata_threads: 0
# # fetch_threads (int)
      Threads to use when downloading packages. When not set, defaults to
# #
      None, which uses the default ThreadPoolExecutor behavior.
# #
# #
# fetch_threads: 0
# # experimental (sequence: primitive)
# #
      env var string delimiter: ','
# #
     List of experimental features to enable.
# #
# experimental: []
# # no_lock (bool)
     Disable index cache lock (defaults to enabled).
# #
# #
# no_lock: false
# # repodata_use_zst (bool)
```

```
(continued from previous page)
     Disable check for `repodata.json.zst`; use `repodata.json` only.
# #
# #
# repodata_use_zst: true
# ##
              Basic Conda Configuration
                                                ##
# # envs_dirs (sequence: primitive)
     aliases: envs_path
# #
     env var string delimiter: ':'
# #
# #
     The list of directories to search for named environments. When
# #
     creating a new named environment, the environment will be placed in
     the first writable location.
# #
# #
# envs_dirs: []
# # pkgs_dirs (sequence: primitive)
     env var string delimiter: ','
# #
# #
     The list of directories where locally-available packages are linked
     from at install time. Packages not locally available are downloaded
# #
# #
     and extracted into the first writable directory.
# #
# pkgs_dirs: []
# # default_threads (int)
# #
     Threads to use by default for parallel operations. Default is None,
# #
     which allows operations to choose themselves. For more specific
# #
     control, see the other *_threads parameters:
                                                 * repodata_threads -
                                   * verify_threads - for verifying
# #
     for fetching/loading repodata
     package contents in transactions
                                      * execute_threads - for carrying
# #
# #
     out the unlinking and linking steps
# #
# default_threads: 0
Network Configuration
# ##
                                                ##
# # client_ssl_cert (NoneType, str)
# #
     aliases: client_cert
# #
     A path to a single file containing a private key and certificate (e.g.
# #
     .pem file). Alternately, use client_ssl_cert_key in conjunction with
     client_ssl_cert for individual files.
# #
# #
# client_ssl_cert:
# # client_ssl_cert_key (NoneType, str)
# #
     aliases: client_cert_key
# #
     Used in conjunction with client_ssl_cert for a matching key file.
                                                                   (continues on next page)
```

```
# #
# client_ssl_cert_key:
# # local_repodata_ttl (bool, int)
      For a value of False or 0, always fetch remote repodata (HTTP 304
# #
# #
     responses respected). For a value of True or 1, respect the HTTP
# #
     Cache-Control max-age header. Any other positive integer values is the
# #
     number of seconds to locally cache repodata before checking the remote
# #
     server for an update.
# #
# local_repodata_ttl: 1
# # offline (bool)
# #
     Restrict conda to cached download content and file:// based urls.
# #
# offline: false
# # proxy_servers (map: primitive)
      A mapping to enable proxy settings. Keys can be either (1) a
# #
      scheme://hostname form, which will match any request to the given
# #
# #
      scheme and exact hostname, or (2) just a scheme, which will match
# #
     requests to that scheme. Values are are the actual proxy server, and
# #
      are of the form 'scheme://[user:password@]host[:port]'. The optional
# #
      'user:password' inclusion enables HTTP Basic Auth with your proxy.
# #
# proxy_servers: {}
# # remote_connect_timeout_secs (float)
# #
      The number seconds conda will wait for your client to establish a
# #
      connection to a remote url resource.
# #
# remote_connect_timeout_secs: 9.15
# # remote_max_retries (int)
     The maximum number of retries each HTTP connection should attempt.
# #
# #
# remote_max_retries: 3
# # remote backoff factor (int)
      The factor determines the time HTTP connection should wait for
# #
# #
      attempt.
# #
# remote backoff factor: 1
# # remote_read_timeout_secs (float)
# #
      Once conda has connected to a remote resource and sent an HTTP
# #
     request, the read timeout is the number of seconds conda will wait for
# #
      the server to send a response.
# #
# remote_read_timeout_secs: 60.0
# # ssl_verify (bool, str)
```

```
# #
     aliases: verify_ssl
# #
     Conda verifies SSL certificates for HTTPS requests, just like a web
     browser. By default, SSL verification is enabled, and conda operations
# #
# #
     will fail if a required url's certificate cannot be verified. Setting
# #
     ssl_verify to False disables certification verification. The value for
# #
     ssl_verify can also be (1) a path to a CA bundle file, (2) a path to a
# #
     directory containing certificates of trusted CA, or (3) 'truststore'
# #
     to use the operating system certificate store.
# #
# ssl_verify: true
# ##
                  Solver Configuration
                                                    ##
# # aggressive_update_packages (sequence: primitive)
# #
     env var string delimiter: ','
# #
     A list of packages that, if installed, are always updated to the
     latest possible version.
# #
# #
# aggressive_update_packages:
#
   - ca-certificates
#
    - certifi
#
    - openssl
# # auto_update_conda (bool)
# #
     aliases: self_update
# #
     Automatically update conda when a newer or higher priority version is
# #
     detected.
# #
# auto_update_conda: true
# # channel_priority (ChannelPriority)
# #
     Accepts values of 'strict', 'flexible', and 'disabled'. The default
# #
     value is 'flexible'. With strict channel priority, packages in lower
# #
     priority channels are not considered if a package with the same name
     appears in a higher priority channel. With flexible channel priority,
# #
# #
     the solver may reach into lower priority channels to fulfill
# #
     dependencies, rather than raising an unsatisfiable error. With channel
# #
     priority disabled, package version takes precedence, and the
# #
     configured priority of channels is used only to break ties. In
# #
     previous versions of conda, this parameter was configured as either
# #
     True or False. True is now an alias to 'flexible'.
# #
# channel_priority: flexible
# # create_default_packages (sequence: primitive)
# #
     env var string delimiter: ','
# #
     Packages that are by default added to a newly created environments.
# #
# create_default_packages: []
```

```
# # disallowed_packages (sequence: primitive)
     aliases: disallow
# #
     env var string delimiter: '&'
# #
     Package specifications to disallow installing. The default is to allow
# #
# #
     all packages.
# #
# disallowed_packages: []
# # force_reinstall (bool)
# #
     Ensure that any user-requested package for the current operation is
# #
     uninstalled and reinstalled, even if that package already exists in
# #
     the environment.
# #
# force_reinstall: false
# # pinned_packages (sequence: primitive)
# #
     env var string delimiter: '&'
# #
     A list of package specs to pin for every environment resolution. This
# #
     parameter is in BETA, and its behavior may change in a future release.
# #
# pinned_packages: []
# # pip_interop_enabled (bool)
# #
     Allow the conda solver to interact with non-conda-installed python
# #
     packages.
# #
# pip_interop_enabled: false
# # track_features (sequence: primitive)
# #
     env var string delimiter: ','
# #
     A list of features that are tracked by default. An entry here is
# #
     similar to adding an entry to the create_default_packages list.
# #
# track_features: []
# # solver (str)
     aliases: experimental_solver
# #
# #
     A string to choose between the different solver logics implemented in
# #
     conda. A solver logic takes care of turning your requested packages
# #
     into a list of specs to add and/or remove from a given environment,
# #
     based on their dependencies and specified constraints.
# #
# solver: libmamba
# ## Package Linking and Install-time Configuration ##
# # allow_softlinks (bool)
# #
     When allow_softlinks is True, conda uses hard-links when possible, and
```

```
(continued from previous page)
# #
      soft-links (symlinks) when hard-links are not possible, such as when
# #
      installing on a different filesystem than the one that the package
      cache is on. When allow_softlinks is False, conda still uses hard-
# #
# #
      links when possible, but when it is not possible, conda copies files.
# #
      Individual packages can override this setting, specifying that certain
# #
      files should never be soft-linked (see the no_link option in the build
# #
      recipe documentation).
# #
# allow_softlinks: false
# # always_copy (bool)
# #
      aliases: copy
# #
      Register a preference that files be copied into a prefix during
# #
      install rather than hard-linked.
# #
# always_copy: false
# # always_softlink (bool)
      aliases: softlink
# #
      Register a preference that files be soft-linked (symlinked) into a
# #
# #
      prefix during install rather than hard-linked. The link source is the
# #
      'pkgs_dir' package cache from where the package is being linked.
# #
      WARNING: Using this option can result in corruption of long-lived
# #
      conda environments. Package caches are *caches*, which means there is
# #
      some churn and invalidation. With this option, the contents of
      environments can be switched out (or erased) via operations on other
# #
# #
      environments.
# #
# always_softlink: false
# # path_conflict (PathConflict)
# #
      The method by which conda handle's conflicting/overlapping paths
# #
      during a create, install, or update operation. The value must be one
# #
      of 'clobber', 'warn', or 'prevent'. The '--clobber' command-line flag
# #
      or clobber configuration parameter overrides path_conflict set to
# #
      'prevent'.
# #
# path_conflict: clobber
# # rollback_enabled (bool)
      Should any error occur during an unlink/link transaction, revert any
# #
# #
      disk mutations made to that point in the transaction.
# #
# rollback_enabled: true
# # safety_checks (SafetyChecks)
      Enforce available safety guarantees during package installation. The
# #
# #
      value must be one of 'enabled', 'warn', or 'disabled'.
# #
# safety_checks: warn
# # extra_safety_checks (bool)
```

```
# #
      Spend extra time validating package contents. Currently, runs sha256
# #
      verification on every file within each package during installation.
# #
# extra_safety_checks: false
# # signing_metadata_url_base (NoneType, str)
# #
      Base URL for obtaining trust metadata updates (i.e., the `*.root.json`
      and `key_mgr.json` files) used to verify metadata and (eventually)
# #
# #
     package signatures.
# #
# signing_metadata_url_base:
# # shortcuts (bool)
# #
     Allow packages to create OS-specific shortcuts (e.g. in the Windows
# #
      Start Menu) at install time.
# #
# shortcuts: true
# # shortcuts_only (sequence: primitive)
      env var string delimiter: ','
# #
# #
     Create shortcuts only for the specified package names.
# #
# shortcuts_only: []
# # non_admin_enabled (bool)
      Allows completion of conda's create, install, update, and remove
# #
# #
      operations, for non-privileged (non-root or non-administrator) users.
# #
# non_admin_enabled: true
# # separate_format_cache (bool)
# #
     Treat .tar.bz2 files as different from .conda packages when filenames
# #
      are otherwise similar. This defaults to False, so that your package
# #
     cache doesn't churn when rolling out the new package format. If you'd
# #
     rather not assume that a .tar.bz2 and .conda from the same place
# #
      represent the same content, set this to True.
# #
# separate_format_cache: false
# # verify_threads (int)
      Threads to use when performing the transaction verification step.
# #
# #
      When not set, defaults to 1.
# #
# verify_threads: 0
# # execute_threads (int)
     Threads to use when performing the unlink/link transaction. When not
# #
# #
      set, defaults to 1. This step is pretty strongly I/O limited, and you
# #
     may not see much benefit here.
# #
# execute_threads: 0
```

```
# ##
             Conda-build Configuration
                                               ##
# # bld_path (str)
# #
     The location where conda-build will put built packages. Same as
     'croot', but 'croot' takes precedence when both are defined. Also used
# #
     in construction of the 'local' multichannel.
# #
# #
# bld_path: ''
# # croot (str)
# #
     The location where conda-build will put built packages. Same as
     'bld_path', but 'croot' takes precedence when both are defined. Also
# #
# #
     used in construction of the 'local' multichannel.
# #
# croot: ''
# # anaconda_upload (NoneType, bool)
# #
     aliases: binstar_upload
     Automatically upload packages built with conda build to anaconda.org.
# #
# #
# anaconda_upload:
# # conda_build (map: primitive)
     aliases: conda-build
# #
# #
     General configuration parameters for conda-build.
# #
# conda_build: {}
# ## Output, Prompt, and Flow Control Configuration ##
# # always_yes (NoneType, bool)
# #
     aliases: yes
# #
     Automatically choose the 'yes' option whenever asked to proceed with a
# #
     conda operation, such as when running `conda install`.
# #
# always_yes:
# # auto_activate_base (bool)
# #
     Automatically activate the base environment during shell
     initialization.
# #
# #
# auto_activate_base: true
# # auto_stack (int)
     Implicitly use --stack when using activate if current level of nesting
# #
# #
     (as indicated by CONDA_SHLVL environment variable) is less than or
```

```
# #
      equal to specified value. 0 or false disables automatic stacking, 1 or
     true enables it for one level.
# #
# #
# auto_stack: 0
# # changeps1 (bool)
# #
      When using activate, change the command prompt ($PS1) to include the
# #
      activated environment.
# #
# changeps1: true
# # env_prompt (str)
# #
      Template for prompt modification based on the active environment.
# #
      Currently supported template variables are '{prefix}', '{name}', and
      '{default_env}'. '{prefix}' is the absolute path to the active
# #
      environment. '{name}' is the basename of the active environment
# #
     prefix. '{default_env}' holds the value of '{name}' if the active
# #
# #
      environment is a conda named environment ('-n' flag), or otherwise
# #
     holds the value of '{prefix}'. Templating uses python's str.format()
# #
     method.
# #
# env_prompt: '({default_env}) '
# # json (bool)
      Ensure all output written to stdout is structured json.
# #
# #
# json: false
# # notify_outdated_conda (bool)
     Notify if a newer version of conda is detected during a create,
# #
# #
     install, update, or remove operation.
# #
# notify_outdated_conda: true
# # quiet (bool)
# #
     Disable progress bar display and other output.
# #
# quiet: false
# # report_errors (NoneType, bool)
     Opt in, or opt out, of automatic error reporting to core maintainers.
# #
# #
      Error reports are anonymous, with only the error stack trace and
# #
      information given by `conda info` being sent.
# #
# report_errors:
# # show_channel_urls (NoneType, bool)
# #
      Show channel URLs when displaying what is going to be downloaded.
# #
# show_channel_urls:
# # verbosity (int)
```

```
(continued from previous page)
```

```
# #
     aliases: verbose
# #
     Sets output log level. 0 is warn. 1 is info. 2 is debug. 3 is trace.
# #
# verbosity: 0
# # unsatisfiable_hints (bool)
# #
     A boolean to determine if conda should find conflicting packages in
     the case of a failed install.
# #
# #
# unsatisfiable_hints: true
# # unsatisfiable_hints_check_depth (int)
# #
     An integer that specifies how many levels deep to search for
     unsatisfiable dependencies. If this number is 1 it will complete the
# #
     unsatisfiable hints fastest (but perhaps not the most complete). The
# #
# #
     higher this number, the longer the generation of the unsat hint will
# #
     take. Defaults to 3.
#
 #
# unsatisfiable_hints_check_depth: 2
# # number_channel_notices (int)
     Sets the number of channel notices to be displayed when running
# #
# #
     commands the "install", "create", "update", "env create", and "env
# #
     update" . Defaults to 5. In order to completely suppress channel
# #
     notices, set this to 0.
# #
# number_channel_notices: 5
# ##
                 Plugin Configuration
                                                  ##
# # no_plugins (bool)
# #
     Disable all currently-registered plugins, except built-in conda
# #
     plugins.
# #
# no_plugins: false
```

4.3 Commands

Conda provides many commands for managing packages and environments. The links on this page provide help for each command. You can also access help from the command line with the --help flag:

conda install --help

The following commands are part of conda:

4.3.1 conda clean

Remove unused packages and caches.

```
usage: conda clean [-h] [-a] [-i] [-p] [-t] [-f] [-c [TEMPFILES ...]] [-1]
[--json] [-v] [-q] [-d] [-y]
```

Removal Targets

-a,all	Remove index cache, lock files, unused cache packages, tarballs, and logfiles.
-i,index-cache	Remove index cache.
-p,packages	Remove unused packages from writable package caches. WARNING: This does not check for packages installed using symlinks back to the package cache.
-t,tarballs	Remove cached package tarballs.
-f,force-pkgs-dirs	Remove <i>all</i> writable package caches. This option is not included with theall flag. WARNING: This will break environments with packages installed using symlinks back to the package cache.
-c,tempfiles	Remove temporary files that could not be deleted earlier due to being in-use. The argument for thetempfiles flag is a path (or list of paths) to the environment(s) where the tempfiles should be found and removed.
-l,logfiles	Remove log files.

Output, Prompt, and Flow Control Options

json	Report all output as json. Suitable for using conda programmatically.
-v,verbose	Can be used multiple times. Once for detailed output, twice for INFO logging, thrice for DEBUG logging, four times for TRACE logging.
-q,quiet	Do not display progress bar.
-d,dry-run	Only display what would have been done.
-y,yes	Sets any confirmation values to 'yes' automatically. Users will not be asked to confirm any adding, deleting, backups, etc.

Examples:

conda clean --tarballs

4.3.2 conda compare

Compare packages between conda environments.

usage: conda compare [-h] [--json] [-v] [-q] [-n ENVIRONMENT | -p PATH] file

Positional Arguments

file	Path to the environment file that is to be compared again
------	---

Output, Prompt, and Flow Control Options

json	Report all output as json. Suitable for using conda programmatically.
-v,verbose	Can be used multiple times. Once for detailed output, twice for INFO logging, thrice for DEBUG logging, four times for TRACE logging.
-q,quiet	Do not display progress bar.

Target Environment Specification

-n,name	Name of environment.
-p,prefix	Full path to environment location (i.e. prefix).

Examples:

Compare packages in the current environment with respect to 'environment.yml' located in the current working directory:

conda compare environment.yml

Compare packages installed into the environment 'myenv' with respect to 'environment.yml' in a different directory:

conda compare -n myenv path/to/file/environment.yml

4.3.3 conda config

Modify configuration values in .condarc.

This is modeled after the git config command. Writes to the user .condarc file (/home/docs/.condarc) by default. Use the --show-sources flag to display all identified configuration locations on your computer.

```
usage: conda config [-h] [--json] [-v] [-q] [--system | --env | --file FILE]
        [--show [SHOW ...] | --show-sources | --validate |
        --describe [DESCRIBE ...] | --write-default]
        [--get [KEY ...] | --append KEY VALUE | --prepend KEY
        VALUE | --set KEY VALUE | --remove KEY VALUE |
        --remove-key KEY | --stdin]
```

Output, Prompt, and Flow Control Options

json	Report all output as json. Suitable for using conda programmatically.
-v,verbose	Can be used multiple times. Once for detailed output, twice for INFO logging, thrice for DEBUG logging, four times for TRACE logging.
-q,quiet	Do not display progress bar.

Config File Location Selection

Without one of these flags, the user config file at '/home/docs/.condarc' is used.

system	Write to the system .condarc file at '/home/docs/checkouts/readthedocs.org/user_builds/continuumio- conda/envs/latest/.condarc'.
env	Write to the active conda environment .condarc file (<no active="" environment="">). If no environment is active, write to the user config file (/home/docs/.condarc).</no>
file	Write to the given file.

Config Subcommands

show	Display configuration values as calculated and compiled. If no arguments given, show information for all configuration values.
show-sources	Display all identified configuration sources.
validate	Validate all configuration sources. Iterates over all .condarc files and checks for parsing errors.
describe	Describe given configuration parameters. If no arguments given, show informa- tion for all configuration parameters.
write-default	Write the default configuration to a file. Equivalent to <i>conda configdescribe</i> > ~/. <i>condarc</i> .

Config Modifiers

get	Get a configuration value.
append	Add one configuration value to the end of a list key.
prepend,add	Add one configuration value to the beginning of a list key.
set	Set a boolean or string key.
remove	Remove a configuration value from a list key. This removes all instances of the value.
remove-key	Remove a configuration key (and all its values).
stdin	Apply configuration information given in yaml format piped through stdin.

See conda config --describe or https://conda.io/docs/config.html for details on all the options that can go in .condarc.

Examples:

Display all configuration values as calculated and compiled:

conda config --show

Display all identified configuration sources:

conda config --show-sources

Print the descriptions of all available configuration options to your command line:

conda config --describe

Print the description for the "channel_priority" configuration option to your command line:

conda config --describe channel_priority

Add the conda-canary channel:

conda config --add channels conda-canary

Set the output verbosity to level 3 (highest) for the current activate environment:

conda config --set verbosity 3 --env

Add the 'conda-forge' channel as a backup to 'defaults':

conda config --append channels conda-forge

4.3.4 conda create

Create a new conda environment from a list of specified packages.

To use the newly-created environment, use 'conda activate envname'. This command requires either the -n NAME or -p PREFIX option.

INNELJ
ock}]
st]
-C]

Positional Arguments

package_spec List of packages to install or update in the conda environment.

Named Arguments

clone	Create a new environment as a copy of an existing local environment.
file	Read package versions from the given file. Repeated file specifications can be passed (e.gfile=file1file=file2).
-m,mkdir	mkdir is pending deprecation and will be removed in 25.3. Redundant argument.
dev	Use <i>sys.executable -m conda</i> in wrapper scripts instead of CONDA_EXE. This is mainly for use during tests where we test new conda sources against old Python versions.

Target Environment Specification

-n,name	Name of environment.
-p,prefix	Full path to environment location (i.e. prefix).

Channel Customization

-c,channel	Additional channel to search for packages. These are URLs searched in the order they are given (including local directories using the 'file://' syntax or simply a path like '/home/conda/mychan' or '/mychan'). Then, the defaults or channels from .condarc are searched (unlessoverride-channels is given). You can use 'defaults' to get the default packages for conda. You can also use any name and the .condarc channel_alias value will be prepended. The default channel_alias is https://conda.anaconda.org/.
use-local	Use locally built packages. Identical to '-c local'.
override-channels	Do not search default or .condarc channels. Requireschannel.
repodata-fn	Specify file name of repodata on the remote server where your channels are con- figured or within local backups. Conda will try whatever you specify, but will ultimately fall back to repodata.json if your specs are not satisfiable with what you specify here. This is used to employ repodata that is smaller and reduced in time scope. You may pass this flag more than once. Leftmost entries are tried first, and the fallback to repodata.json is added for you automatically. For more information, see conda configdescribe repodata_fns.
experimental	Possible choices: jlap, lock
	jlap: Download incremental package index data from repodata.jlap; implies 'lock'. lock: use locking when reading, updating index (repodata.json) cache. Now enabled.
no-lock	Disable locking when reading, updating index (repodata.json) cache.
repodata-use-zst, -	-no-repodata-use-zst Check for/do not check for repodata.json.zst. Enabled by default. (default: Null)

--subdir, --platform Possible choices: emscripten-wasm32, wasi-wasm32, freebsd-64, linux-32, linux-64, linux-armv61, linux-armv71, linux-ppc64, linux-ppc64le, linux-riscv64, linux-s390x, osx-64, osx-arm64, win-32, win-64, win-arm64, zosz

Use packages built for this platform. The new environment will be configured to remember this choice. Should be formatted like 'osx-64', 'linux-32', 'win-64', and so on. Defaults to the current (native) platform.

Solver Mode Modifiers

strict-channel-prio	rity Packages in lower priority channels are not considered if a package with the same name appears in a higher priority channel.			
no-channel-priorit	y Package version takes precedence over channel priority. Overrides the value given by <i>conda configshow channel_priority</i> .			
no-deps	Do not install, update, remove, or change dependencies. This WILL lead to broken environments and inconsistent behavior. Use at your own risk.			
only-deps	Only install dependencies.			
no-pin	Ignore pinned file.			
no-default-packages Ignore create_default_packages in the .condarc file.				
solver	Possible choices: classic			
	Choose which solver backend to use.			

Package Linking and Install-time Options

сору	Install all packages using copies instead of hard- or soft-linking.
no-shortcuts	Don't install start menu shortcuts
shortcuts-only	Install shortcuts only for this package name. Can be used several times

Networking Options

-C,use-index-cache	e Use cache of channel index files, even if it has expired. This is useful if you don't want conda to check whether a new version of the repodata file exists, which will save bandwidth.
-k,insecure	Allow conda to perform "insecure" SSL connections and transfers. Equivalent to setting 'ssl_verify' to 'false'.
offline	Offline mode. Don't connect to the Internet.

Output, Prompt, and Flow Control Options

json	Report all output as json. Suitable for using conda programmatically.			
-v,verbose	Can be used multiple times. Once for detailed output, twice for INFO logging, thrice for DEBUG logging, four times for TRACE logging.			
-q,quiet	Do not display progress bar.			
-d,dry-run	Only display what would have been done.			
-y,yes	Sets any confirmation values to 'yes' automatically. Users will not be asked to confirm any adding, deleting, backups, etc.			
download-only	Solve an environment and ensure package caches are populated, but exit prior to unlinking and linking packages into the prefix.			
show-channel-urls	Show channel urls. Overrides the value given by <i>conda configshow show_channel_urls</i> .			

Examples:

Create an environment containing the package 'sqlite':

conda create -n myenv sqlite

Create an environment (env2) as a clone of an existing environment (env1):

```
conda create -n env2 --clone path/to/file/env1
```

4.3.5 conda doctor

Display a health report for your environment.

|--|

Named Arguments

-v, --verbose Can be used multiple times. Once for detailed output, twice for INFO logging, thrice for DEBUG logging, four times for TRACE logging.

Target Environment Specification

-n,name	Name of environment.
-p,prefix	Full path to environment location (i.e. prefix).

4.3.6 conda env

usage: conda env [-h] command ...

Positional Arguments

command Possible choices: config, create, export, list, remove, update

conda env config

Configure a conda environment.

usage: conda env config [-h] {vars} ...

Examples:

conda env config vars list
conda env config --append channels conda-forge

conda env config vars

Interact with environment variables associated with Conda environments.

usage: conda env config vars [-h] {list,set,unset} ...

Examples:

conda env config vars list -n my_env conda env config vars set MY_VAR=something OTHER_THING=ohhhhya conda env config vars unset MY_VAR

conda env config vars list

List environment variables for a conda environment.

usage:	conda	env	config	vars	list	[-h]	[-n E	ENVIRONMENT	$-\mathbf{p}$	PATH]	[json]	
						[-v]	[-q]					

Target Environment Specification

-n,name	Name of environment.
-p,prefix	Full path to environment location (i.e. prefix).

Output, Prompt, and Flow Control Options

json	Report all output as json. Suitable for using conda programmatically.
-v,verbose	Can be used multiple times. Once for detailed output, twice for INFO logging, thrice for DEBUG logging, four times for TRACE logging.
-q,quiet	Do not display progress bar.

Example:

conda env config vars list -n my_env

conda env config vars set

Set environment variables for a conda environment.

```
usage: conda env config vars set [-h] [-n ENVIRONMENT | -p PATH] [vars ...]
```

Positional Arguments

vars Environment variables to set in the form <KEY>=<VALUE> separated by spaces

Target Environment Specification

-n, --name Name of environment.-p, --prefix Full path to environment location (i.e. prefix).

Example:

conda env config vars set MY_VAR=weee

conda env config vars unset

Unset environment variables for a conda environment.

```
usage: conda env config vars unset [-h] [-n ENVIRONMENT | -p PATH] [vars ...]
```

Positional Arguments

vars Environment variables to unset in the form <KEY> separated by spaces

Target Environment Specification

-n,name	Name of environment.
-p,prefix	Full path to environment location (i.e. prefix).

Example:

conda env config vars unset MY_VAR

conda env create

Create an environment based on an environment definition file.

If using an environment.yml file (the default), you can name the environment in the first line of the file with 'name: envname' or you can specify the environment name in the CLI command using the -n/--name argument. The name specified in the CLI will override the name specified in the environment.yml file.

Unless you are in the directory containing the environment definition file, use -f to specify the file path of the environment definition file you want to use.

usage:	conda	env	create	[-h] [-f FILE] [-n ENVIRONMENT -p PATH] [-C] [-k]
				<pre>[offline] [no-default-packages] [json] [-v] [-q]</pre>
				<pre>[-d] [-y] [solver {classic}] [subdir SUBDIR]</pre>
				[remote_definition]

Positional Arguments

remote_definition Remote environment definition / IPython notebook
Named Arguments

-f,file	Environment definition file (default: environment.yml)
no-default-package	s Ignore create_default_packages in the .condarc file.
solver	Possible choices: classic
	Choose which solver backend to use.
subdir,platform	Possible choices: emscripten-wasm32, wasi-wasm32, freebsd-64, linux-32, linux-64, linux-aarch64, linux-armv6l, linux-armv7l, linux-ppc64, linux-ppc64le, linux-riscv64, linux-s390x, osx-64, osx-arm64, win-32, win-64, win-arm64, zos-z
	Use packages built for this platform. The new environment will be configured to remember this choice. Should be formatted like 'osx-64', 'linux-32', 'win-64', and so on. Defaults to the current (native) platform.

Target Environment Specification

-n,name	Name of environment.
-p,prefix	Full path to environment location (i.e. prefix).

Networking Options

-C,use-index-cache	e Use cache of channel index files, even if it has expired. This is useful if you don't want conda to check whether a new version of the repodata file exists, which will save bandwidth.
-k,insecure	Allow conda to perform "insecure" SSL connections and transfers. Equivalent to setting 'ssl_verify' to 'false'.
offline	Offline mode. Don't connect to the Internet.

Output, Prompt, and Flow Control Options

json	Report all output as json. Suitable for using conda programmatically.	
-v,verbose	Can be used multiple times. Once for detailed output, twice for INFO logging, thrice for DEBUG logging, four times for TRACE logging.	
-q,quiet	Do not display progress bar.	
-d,dry-run	Only display what would have been done.	
-y,yes	Sets any confirmation values to 'yes' automatically. Users will not be asked to confirm any adding, deleting, backups, etc.	

Examples:

```
conda env create
conda env create -n envname
conda env create folder/envname
```

(continues on next page)

(continued from previous page)

```
conda env create -f /path/to/environment.yml
conda env create -f /path/to/requirements.txt -n envname
conda env create -f /path/to/requirements.txt -p /home/user/envname
```

conda env export

Export a given environment

usage:	conda	env	export	[-h] [-c CHANNEL] [override-channels]
				[-n ENVIRONMENT -p PATH] [-f FILE] [no-builds]
				[ignore-channels] [json] [-v] [-q]
				[from-history]

Named Arguments

-c,channel	Additional channel to include in the export	
override-channels	Do not include .condarc channels	
-f,file	File name or path for the exported environment. Note: This will silently overwrite any existing file of the same name in the current directory.	
no-builds	Remove build specification from dependencies	
ignore-channels	Do not include channel names with package names.	
from-history	Build environment spec from explicit specs in history	

Target Environment Specification

-n,name	Name of environment.
-p,prefix	Full path to environment location (i.e. prefix).

Output, Prompt, and Flow Control Options

json	Report all output as json. Suitable for using conda programmatically.	
-v,verbose	Can be used multiple times. Once for detailed output, twice for INFO logging, thrice for DEBUG logging, four times for TRACE logging.	
-q,quiet	Do not display progress bar.	

Examples:

conda export
conda export --file FILE_NAME

conda env list

List the Conda environments.

```
usage: conda env list [-h] [--json] [-v] [-q]
```

Output, Prompt, and Flow Control Options

json	Report all output as json. Suitable for using conda programmatically.
-v,verbose	Can be used multiple times. Once for detailed output, twice for INFO logging, thrice for DEBUG logging, four times for TRACE logging.
-q,quiet	Do not display progress bar.

Examples:

conda env	list
conda env	listjson

conda env remove

Remove an environment.

Removes a provided environment. You must deactivate the existing environment before you can remove it.

```
usage: conda env remove [-h] [-n ENVIRONMENT | -p PATH] [--solver {classic}]
[--json] [-v] [-q] [-d] [-y]
```

Named Arguments

solver	Possible choices:	classic

Choose which solver backend to use.

Target Environment Specification

-n,name	Name of environment.
-p,prefix	Full path to environment location (i.e. prefix).

Output, Prompt, and Flow Control Options

json	Report all output as json. Suitable for using conda programmatically.	
-v,verbose	Can be used multiple times. Once for detailed output, twice for INFO logging, thrice for DEBUG logging, four times for TRACE logging.	
-q,quiet	Do not display progress bar.	
-d,dry-run	Only display what would have been done.	
-y,yes	Sets any confirmation values to 'yes' automatically. Users will not be asked to confirm any adding, deleting, backups, etc.	

Examples:

conda env update

Update the current environment based on environment file.

usage:	conda	env	update	[-h] [[-n ENVIRONMENT -p PATH] [-f FILE] [prune]	
				[jso	on] [-v] [-q] [solver {classic}]	
				[remot	te_definition]	

Positional Arguments

remote_definition	remote environment definition	/ IPython notebook

Named Arguments

-f,file	environment definition (default: environment.yml)
prune	remove installed packages not defined in environment.yml
solver	Possible choices: classic
	Choose which solver backend to use.

Target Environment Specification

-n,name	Name of environment.
-p,prefix	Full path to environment location (i.e. prefix).

Output, Prompt, and Flow Control Options

json	Report all output as json. Suitable for using conda programmatically.	
-v,verbose	Can be used multiple times. Once for detailed output, twice for INFO logging, thrice for DEBUG logging, four times for TRACE logging.	
-q,quiet	Do not display progress bar.	

Examples:

conda	env	update	
conda	env	update	-n=foo
conda	env	update	-f=/path/to/environment.yml
conda	env	update	<pre>name=foofile=environment.yml</pre>
conda	env	update	vader/deathstar

4.3.7 conda info

Display information about current conda install.

```
usage: conda info [-h] [--json] [-v] [-q] [-a] [--base] [-e] [-s]
[--unsafe-channels]
```

Named Arguments

-a,all	all is deprecated and will be removed in 24.9. Useverbose instead
base	Display base environment path.
-e,envs	List all known conda environments.
-s,system	List environment variables.
unsafe-channels	Display list of channels with tokens exposed.

Output, Prompt, and Flow Control Options

json	Report all output as json. Suitable for using conda programmatically.
-v,verbose	Can be used multiple times. Once for detailed output, twice for INFO logging, thrice for DEBUG logging, four times for TRACE logging.
-q,quiet	Do not display progress bar.

4.3.8 conda init

Initialize conda for shell interaction.

```
usage: conda init [-h] [--all] [--user] [--no-user] [--system] [--reverse]
        [--json] [-v] [-q] [-d]
        [SHELLS ...]
```

Positional Arguments

SHELLS	Possible choices: bash, fish, tcsh, xonsh, zsh, powershell		
	One or more shells to be initialized. If not given, the default value is 'bash' on		
	unix and 'cmd.exe' & 'powershell' on Windows. Use the 'all' flag to initialize all		
	shells. Available shells: ['bash', 'fish', 'powershell', 'tcsh', 'xonsh', 'zsh']		

Named Arguments

all	Initialize all currently available shells.
-d,dry-run	Only display what would have been done.

setup type

user	Initialize conda for the current user (default).
no-user	Don't initialize conda for the current user.
system	Initialize conda for all users on the system.
reverse	Undo effects of last conda init.

Output, Prompt, and Flow Control Options

json	Report all output as json. Suitable for using conda programmatically.
-v,verbose	Can be used multiple times. Once for detailed output, twice for INFO logging, thrice for DEBUG logging, four times for TRACE logging.
-q,quiet	Do not display progress bar.

Key parts of conda's functionality require that it interact directly with the shell within which conda is being invoked. The *conda activate* and *conda deactivate* commands specifically are shell-level commands. That is, they affect the state (e.g. environment variables) of the shell context being interacted with. Other core commands, like *conda create* and *conda install*, also necessarily interact with the shell environment. They're therefore implemented in ways specific to each shell. Each shell must be configured to make use of them.

This command makes changes to your system that are specific and customized for each shell. To see the specific files and locations on your system that will be affected before, use the '--dry-run' flag. To see the exact changes that are being or will be made to each location, use the '--verbose' flag.

IMPORTANT: After running conda init, most shells will need to be closed and restarted for changes to take effect.

4.3.9 conda install

Install a list of packages into a specified conda environment.

This command accepts a list of package specifications (e.g, bitarray=0.8) and installs a set of packages consistent with those specifications and compatible with the underlying environment. If full compatibility cannot be assured, an error is reported and the environment is not changed.

Conda attempts to install the newest versions of the requested packages. To accomplish this, it may update some packages that are already installed, or install additional packages. To prevent existing packages from updating, use the --freeze-installed option. This may force conda to install older versions of the requested packages, and it does not prevent additional dependency packages from being installed.

If you wish to skip dependency checking altogether, use the '--no-deps' option. This may result in an environment with incompatible packages, so this option must be used with great caution.

conda can also be called with a list of explicit conda package filenames (e.g. ./lxml-3.2.0-py27_0.tar.bz2). Using conda in this mode implies the --no-deps option, and should likewise be used with great caution. Explicit filenames and package specifications cannot be mixed in a single command.

usage:	conda	install	[-h] [revision REVISION] [-n ENVIRONMENT -p PATH]
			<pre>[-c CHANNEL] [use-local] [override-channels]</pre>
			[repodata-fn REPODATA_FNS] [experimental {jlap,lock}]
			[no-lock] [repodata-use-zst no-repodata-use-zst]
			<pre>[strict-channel-priority] [no-channel-priority]</pre>
			[no-deps only-deps] [no-pin] [copy]
			<pre>[no-shortcuts] [shortcuts-only SHORTCUTS_ONLY] [-C]</pre>
			[-k] [offline] [json] [-v] [-q] [-d] [-y]
			<pre>[download-only] [show-channel-urls] [file FILE]</pre>
			<pre>[solver {classic}] [force-reinstall]</pre>
			[freeze-installed update-deps -S update-all update-
→specs	s]		
			[-m] [clobber] [dev]
			[package_spec]

Positional Arguments

package_spec List of packages to install or update in the conda environment.

Named Arguments

revision	Revert to the specified REVISION.
file	Read package versions from the given file. Repeated file specifications can be passed (e.gfile=file1file=file2).
dev	Use <i>sys.executable -m conda</i> in wrapper scripts instead of CONDA_EXE. This is mainly for use during tests where we test new conda sources against old Python versions.

Target Environment Specification

-n,name	Name of environment.
-p,prefix	Full path to environment location (i.e. prefix).

Channel Customization

-c,channel	Additional channel to search for packages. These are URLs searched in the order they are given (including local directories using the 'file://' syntax or simply a path like '/home/conda/mychan' or '/mychan'). Then, the defaults or channels from .condarc are searched (unlessoverride-channels is given). You can use 'defaults' to get the default packages for conda. You can also use any name and the .condarc channel_alias value will be prepended. The default channel_alias is https://conda.anaconda.org/.
use-local	Use locally built packages. Identical to '-c local'.
override-channels	Do not search default or .condarc channels. Requireschannel.
repodata-fn	Specify file name of repodata on the remote server where your channels are con- figured or within local backups. Conda will try whatever you specify, but will ultimately fall back to repodata.json if your specs are not satisfiable with what you specify here. This is used to employ repodata that is smaller and reduced in time scope. You may pass this flag more than once. Leftmost entries are tried first, and the fallback to repodata.json is added for you automatically. For more information, see conda configdescribe repodata_fns.
experimental	Possible choices: jlap, lock
	jlap: Download incremental package index data from repodata.jlap; implies 'lock'. lock: use locking when reading, updating index (repodata.json) cache. Now enabled.
no-lock	Disable locking when reading, updating index (repodata.json) cache.
repodata-use-zst,	-no-repodata-use-zst Check for/do not check for repodata.json.zst. Enabled by default. (default: Null)

Solver Mode Modifiers

strict-channel-prio	rity Packages in lower priority channels are not considered if a package with the same name appears in a higher priority channel.
no-channel-priority	Package version takes precedence over channel priority. Overrides the value given by <i>conda configshow channel_priority</i> .
no-deps	Do not install, update, remove, or change dependencies. This WILL lead to broken environments and inconsistent behavior. Use at your own risk.
only-deps	Only install dependencies.
no-pin	Ignore pinned file.
solver	Possible choices: classic
	Choose which solver backend to use.
force-reinstall	Ensure that any user-requested package for the current operation is uninstalled and reinstalled, even if that package already exists in the environment.

--freeze-installed, --no-update-deps Do not update or change already-installed dependencies.

--update-deps Update dependencies that have available updates.

-S,satisfied-skip-so	Ive Exit early and do not run the solver if the requested specs are satisfied. Also
	skips aggressive updates as configured by the 'aggressive_update_packages' con-
	fig setting. Use 'conda infodescribe aggressive_update_packages' to view your settingsatisfied-skip-solve is similar to the default behavior of 'pip install'.
update-all,all	Update all installed packages in the environment.

- apaule un, un opeule un instance puerages in the environme
- --update-specs Update based on provided specifications.

Package Linking and Install-time Options

copy	Install all packages using copies instead of hard- or soft-linking.
no-shortcuts	Don't install start menu shortcuts
shortcuts-only	Install shortcuts only for this package name. Can be used several times.
-m,mkdir	<i>mkdir</i> is pending deprecation and will be removed in 25.3. Use <i>conda create</i> instead.
clobber	Allow clobbering (i.e. overwriting) of overlapping file paths within packages and suppress related warnings.

Networking Options

-C,use-index-cache	e Use cache of channel index files, even if it has expired. This is useful if you don't want conda to check whether a new version of the repodata file exists, which will save bandwidth.
-k,insecure	Allow conda to perform "insecure" SSL connections and transfers. Equivalent to setting 'ssl_verify' to 'false'.
offline	Offline mode. Don't connect to the Internet.

Output, Prompt, and Flow Control Options

json	Report all output as json. Suitable for using conda programmatically.
-v,verbose	Can be used multiple times. Once for detailed output, twice for INFO logging, thrice for DEBUG logging, four times for TRACE logging.
-q,quiet	Do not display progress bar.
-d,dry-run	Only display what would have been done.
-y,yes	Sets any confirmation values to 'yes' automatically. Users will not be asked to confirm any adding, deleting, backups, etc.
download-only	Solve an environment and ensure package caches are populated, but exit prior to unlinking and linking packages into the prefix.
show-channel-urls	Show channel urls. Overrides the value given by <i>conda configshow show channel urls.</i>

Examples:

Install the package 'scipy' into the currently-active environment:

conda install scipy

Install a list of packages into an environment, myenv:

```
conda install -n myenv scipy curl wheel
```

Install a specific version of 'python' into an environment, myenv:

```
conda install -p path/to/myenv python=3.11
```

4.3.10 conda list

List installed packages in a conda environment.

```
usage: conda list [-h] [-n ENVIRONMENT | -p PATH] [--json] [-v] [-q]
[--show-channel-urls] [--reverse] [-c] [-f] [--explicit]
[--md5] [-e] [-r] [--no-pip]
[regex]
```

Positional Arguments

regex List only packages matching this regular expression.

Named Arguments

show-channel-urls	Show channel urls. Overrides the value given by <i>conda configshow show_channel_urls</i> .
reverse	List installed packages in reverse order.
-c,canonical	Output canonical names of packages only.
-f,full-name	Only search for full names, i.e., ^ <regex>\$full-name NAME is identical to regex '^NAME\$'.</regex>
explicit	List explicitly all installed conda packages with URL (output may be used by conda createfile).
md5	Add MD5 hashsum when usingexplicit.
-e,export	Output explicit, machine-readable requirement strings instead of human-readable lists of packages. This output may be used by conda createfile.
-r,revisions	List the revision history.
no-pip	Do not include pip-only installed packages.

Target Environment Specification

-n,name	Name of environment.
-p,prefix	Full path to environment location (i.e. prefix).

Output, Prompt, and Flow Control Options

json	Report all output as json. Suitable for using conda programmatically.
-v,verbose	Can be used multiple times. Once for detailed output, twice for INFO logging, thrice for DEBUG logging, four times for TRACE logging.
-q,quiet	Do not display progress bar.

Examples:

List all packages in the current environment:

conda list

List all packages in reverse order:

conda list --reverse

List all packages installed into the environment 'myenv':

conda list -n myenv

List all packages that begin with the letters "py", using regex:

conda list ^py

Save packages for future use:

conda list --export > package-list.txt

Reinstall packages from an export file:

```
conda create -n myenv --file package-list.txt
```

4.3.11 conda notices

Retrieve latest channel notifications.

Conda channel maintainers have the option of setting messages that users will see intermittently. Some of these notices are informational while others are messages concerning the stability of the channel.

usage:	conda	notices	[-h]	[-c	CHANNE	Ľ]	[use	e-loca	al]	[ove	erride-	channels]
			[re	poda	ta-fn	REP	ODATA_	_FNS]	[experi	imental	<pre>{jlap,lock}]</pre>
			[nc	-loc	k] [rep	odata	-use-z	zst	nc	o-repod	ata-use-zst]
			[js	on]	[-v] [-q]						

Channel Customization

-c,channel	Additional channel to search for packages. These are URLs searched in the order they are given (including local directories using the 'file://' syntax or simply a path like '/home/conda/mychan' or '/mychan'). Then, the defaults or channels from .condarc are searched (unlessoverride-channels is given). You can use 'defaults' to get the default packages for conda. You can also use any name and the .condarc channel_alias value will be prepended. The default channel_alias is https://conda.anaconda.org/.
use-local	Use locally built packages. Identical to '-c local'.
override-channels	Do not search default or .condarc channels. Requireschannel.
repodata-fn	Specify file name of repodata on the remote server where your channels are con- figured or within local backups. Conda will try whatever you specify, but will ultimately fall back to repodata.json if your specs are not satisfiable with what you specify here. This is used to employ repodata that is smaller and reduced in time scope. You may pass this flag more than once. Leftmost entries are tried first, and the fallback to repodata.json is added for you automatically. For more information, see conda configdescribe repodata_fns.
experimental	Possible choices: jlap, lock
	jlap: Download incremental package index data from repodata.jlap; implies 'lock'. lock: use locking when reading, updating index (repodata.json) cache. Now enabled.
no-lock	Disable locking when reading, updating index (repodata.json) cache.
repodata-use-zst, -	-no-repodata-use-zst Check for/do not check for repodata.json.zst. Enabled by default. (default: Null)

Output, Prompt, and Flow Control Options

json	Report all output as json. Suitable for using conda programmatically.
-v,verbose	Can be used multiple times. Once for detailed output, twice for INFO logging, thrice for DEBUG logging, four times for TRACE logging.
-q,quiet	Do not display progress bar.

Examples:

conda notices	
conda notices -c defaults	

4.3.12 conda package

Create low-level conda packages. (EXPERIMENTAL)

```
usage: conda package [-h] [-n ENVIRONMENT | -p PATH] [-w PATH [PATH ...]] [-r]
       [-u] [--pkg-name PKG_NAME] [--pkg-version PKG_VERSION]
       [--pkg-build PKG_BUILD]
```

Named Arguments

-w,which	Given some file's PATH, print which conda package the file came from.
-r,reset	Remove all untracked files and exit.
-u,untracked	Display all untracked files and exit.
pkg-name	Designate package name of the package being created.
pkg-version	Designate package version of the package being created.
pkg-build	Designate package build number of the package being created.

Target Environment Specification

-n,name	Name of environment.
-p,prefix	Full path to environment location (i.e. prefix).

4.3.13 conda remove

Remove a list of packages from a specified conda environment.

Use --all flag to remove all packages and the environment itself.

This command will also remove any package that depends on any of the specified packages as well---unless a replacement can be found without that dependency. If you wish to skip this dependency checking and remove just the requested packages, add the '--force' option. Note however that this may result in a broken environment, so use this with caution.

[-h] [-n ENVIRONMENT -p PATH] [-c CHANNEL] [use-local]
<pre>[override-channels] [repodata-fn REPODATA_FNS]</pre>
<pre>[experimental {jlap,lock}] [no-lock]</pre>
[repodata-use-zst no-repodata-use-zst] [features]
[force-remove] [no-pin] [solver {classic}] [-C] [-k]
[offline] [json] [-v] [-q] [-d] [-y] [all]
[keep-env] [dev]
[package_name]

Positional Arguments

package_name	Package names to remove	from the environment.
--------------	-------------------------	-----------------------

Named Arguments

all	Remove all packages, i.e., the entire environment.
keep-env	Used withall, delete all packages but keep the environment.
dev	Use <i>sys.executable -m conda</i> in wrapper scripts instead of CONDA_EXE. This is mainly for use during tests where we test new conda sources against old Python versions.

Target Environment Specification

-n,name	Name of environment.
-p,prefix	Full path to environment location (i.e. prefix)

Channel Customization

-c,channel	Additional channel to search for packages. These are URLs searched in the order they are given (including local directories using the 'file://' syntax or simply a path like '/home/conda/mychan' or '/mychan'). Then, the defaults or channels from .condarc are searched (unlessoverride-channels is given). You can use 'defaults' to get the default packages for conda. You can also use any name and the .condarc channel_alias value will be prepended. The default channel_alias is https://conda.anaconda.org/.
use-local	Use locally built packages. Identical to '-c local'.
override-channels	Do not search default or .condarc channels. Requireschannel.
repodata-fn	Specify file name of repodata on the remote server where your channels are con- figured or within local backups. Conda will try whatever you specify, but will ultimately fall back to repodata.json if your specs are not satisfiable with what you specify here. This is used to employ repodata that is smaller and reduced in time scope. You may pass this flag more than once. Leftmost entries are tried first, and the fallback to repodata.json is added for you automatically. For more information, see conda configdescribe repodata_fns.
experimental	Possible choices: jlap, lock
	jlap: Download incremental package index data from repodata.jlap; implies 'lock'. lock: use locking when reading, updating index (repodata.json) cache. Now enabled.
no-lock	Disable locking when reading, updating index (repodata.json) cache.
repodata-use-zst,	no-repodata-use-zst Check for/do not check for repodata.json.zst. Enabled by default. (default: Null)

features	Remove features (instead of packages).
force-remove,for	ce Forces removal of a package without removing packages that depend on it. Using this option will usually leave your environment in a broken and inconsistent state.
no-pin	Ignore pinned package(s) that apply to the current operation. These pinned packages might come from a .condarc file or a file in <target_environment>/conda-meta/pinned.</target_environment>
solver	Possible choices: classic
	Choose which solver backend to use.

Solver Mode Modifiers

Networking Options

-C,use-index-cache	• Use cache of channel index files, even if it has expired. This is useful if you don't want conda to check whether a new version of the repodata file exists, which will save bandwidth.
-k,insecure	Allow conda to perform "insecure" SSL connections and transfers. Equivalent to setting 'ssl_verify' to 'false'.
offline	Offline mode. Don't connect to the Internet.

Output, Prompt, and Flow Control Options

json	Report all output as json. Suitable for using conda programmatically.
-v,verbose	Can be used multiple times. Once for detailed output, twice for INFO logging, thrice for DEBUG logging, four times for TRACE logging.
-q,quiet	Do not display progress bar.
-d,dry-run	Only display what would have been done.
-y,yes	Sets any confirmation values to 'yes' automatically. Users will not be asked to confirm any adding, deleting, backups, etc.

Examples:

Remove the package 'scipy' from the currently-active environment:

conda remove scipy

Remove a list of packages from an environemnt 'myenv':

conda remove -n myenv scipy curl wheel

Remove all packages from environment myenv and the environment itself:

conda remove -n myenv --all

Remove all packages from the environment *myenv* but retain the environment:

conda remove -n myenv --all --keep-env

4.3.14 conda rename

Rename an existing environment.

This command renames a conda environment via its name (-n/--name) or its prefix (-p/--prefix).

The base environment and the currently-active environment cannot be renamed.

usage:	conda rename	[-h]	[−n ENVIRONMENT	-p PATH]	[force] [-	d] destination
--------	--------------	------	-----------------	----------	------------	----------------

Positional Arguments

destination	New name for the conda environme
destination	New name for the conda environme

Named Arguments

force	Force rename of an environment.
-d,dry-run	Only display what would have been done by the current command, arguments, and other flags.

Target Environment Specification

-n,name	Name of environment.
-p,prefix	Full path to environment location (i.e. prefix).

Examples:

```
conda rename -n test123 test321
conda rename --name test123 test321
conda rename -p path/to/test123 test321
conda rename --prefix path/to/test123 test321
```

4.3.15 conda run

Run an executable in a conda environment.

Positional Arguments

executable_call	Executable name,	with additional	arguments t	o be passe	ed to the	executable on
	invocation.					

Named Arguments

-v,verbose	Can be used multiple times. Once for detailed output, twice for INFO logging, thrice for DEBUG logging, four times for TRACE logging.
dev	Sets <i>CONDA_EXE</i> to <i>python -m conda</i> , assuming the current working directory contains the root of conda development sources. This is mainly for use during tests where we test new conda sources against old Python versions.
debug-wrapper-sci	tipts When this is set, where implemented, the shell wrapper scriptswill use the echo command to print debugging information to stderr (standard error).
cwd	Current working directory for command to run in. Defaults to the user's current working directory if no directory is specified.
no-capture-output,	live-stream Don't capture stdout/stderr (standard out/standard error).

Target Environment Specification

-n,name	Name of environment.
-p,prefix	Full path to environment location (i.e. prefix)

Example:

```
$ conda create -y -n my-python-env python=3
$ conda run -n my-python-env python --version
```

4.3.16 conda search

Search for packages and display associated information using the MatchSpec format.

MatchSpec is a query language for conda packages.

usage:	conda	search	[-h] [envs] [-i] [subdir SUBDIR]
			[skip-flexible-search] [-c CHANNEL] [use-local]
			[override-channels] [repodata-fn REPODATA_FNS]
			[experimental {jlap,lock}] [no-lock]
			[repodata-use-zst no-repodata-use-zst] [-C] [-k]
			[offline] [json] [-v] [-q]

Named Arguments

Search all of the current user's environments. If run as Administrator (on Windows) or UID 0 (on unix), search all known environments on the system.
Provide detailed information about each package.
Search the given subdir. Should be formatted like 'osx-64', 'linux-32', 'win-64', and so on. The default is to search the current platform.

--skip-flexible-search Do not perform flexible search if initial search fails.

Channel Customization

-c,channel	Additional channel to search for packages. These are URLs searched in the order they are given (including local directories using the 'file://' syntax or simply a path like '/home/conda/mychan' or '/mychan'). Then, the defaults or channels from .condarc are searched (unlessoverride-channels is given). You can use 'defaults' to get the default packages for conda. You can also use any name and the .condarc channel_alias value will be prepended. The default channel_alias is https://conda.anaconda.org/.
use-local	Use locally built packages. Identical to '-c local'.
override-channels	Do not search default or .condarc channels. Requireschannel.
repodata-fn	Specify file name of repodata on the remote server where your channels are con- figured or within local backups. Conda will try whatever you specify, but will ultimately fall back to repodata.json if your specs are not satisfiable with what you specify here. This is used to employ repodata that is smaller and reduced in time scope. You may pass this flag more than once. Leftmost entries are tried first, and the fallback to repodata.json is added for you automatically. For more information, see conda configdescribe repodata_fns.
experimental	Possible choices: jlap, lock
	jlap: Download incremental package index data from repodata.jlap; implies 'lock'. lock: use locking when reading, updating index (repodata.json) cache. Now enabled.
no-lock	Disable locking when reading, updating index (repodata.json) cache.
repodata-use-zst,	-no-repodata-use-zst Check for/do not check for repodata.json.zst. Enabled by default. (default: Null)

Networking Options

-C,use-index-cache	e Use cache of channel index files, even if it has expired. This is useful if you don't want conda to check whether a new version of the repodata file exists, which will save bandwidth.
-k,insecure	Allow conda to perform "insecure" SSL connections and transfers. Equivalent to setting 'ssl_verify' to 'false'.
offline	Offline mode. Don't connect to the Internet.

Output, Prompt, and Flow Control Options

json	Report all output as json. Suitable for using conda programmatically.
-v,verbose	Can be used multiple times. Once for detailed output, twice for INFO logging, thrice for DEBUG logging, four times for TRACE logging.
-q,quiet	Do not display progress bar.

Examples:

Search for a specific package named 'scikit-learn':

conda search scikit-learn

Search for packages containing 'scikit' in the package name:

conda search *scikit*

Note that your shell may expand '*' before handing the command over to conda. Therefore, it is sometimes necessary to use single or double quotes around the query:

```
conda search '*scikit'
conda search "*scikit*"
```

Search for packages for 64-bit Linux (by default, packages for your current platform are shown):

```
conda search numpy[subdir=linux-64]
```

Search for a specific version of a package:

conda search 'numpy>=1.12'

Search for a package on a specific channel:

```
conda search conda-forge::numpy
conda search 'numpy[channel=conda-forge, subdir=osx-64]'
```

4.3.17 conda update

Update conda packages to the latest compatible version.

This command accepts a list of package names and updates them to the latest versions that are compatible with all other packages in the environment.

Conda attempts to install the newest versions of the requested packages. To accomplish this, it may update some packages that are already installed, or install additional packages. To prevent existing packages from updating, use the --no-update-deps option. This may force conda to install older versions of the requested packages, and it does not prevent additional dependency packages from being installed.

usage:	conda	update	[-h] [-n ENVIRONMENT -p PATH] [-c CHANNEL] [use-local]
			[override-channels] [repodata-fn REPODATA_FNS]
			[experimental {jlap,lock}] [no-lock]
			[repodata-use-zst no-repodata-use-zst]
			[strict-channel-priority] [no-channel-priority]
			[no-deps only-deps] [no-pin] [copy]
			<pre>[no-shortcuts] [shortcuts-only SHORTCUTS_ONLY] [-C]</pre>
			[-k] [offline] [json] [-v] [-q] [-d] [-y]
			<pre>[download-only] [show-channel-urls] [file FILE]</pre>
			[solver {classic}] [force-reinstall]
			[freeze-installed update-deps -S update-all update-
⇔specs	s]		
			[clobber]
			[package_spec]

Positional Arguments

package_spec List of packages to install or update in the conda environment.

Named Arguments

--file Read package versions from the given file. Repeated file specifications can be passed (e.g. --file=file1 --file=file2).

Target Environment Specification

-n,name	Name of environment.
-p,prefix	Full path to environment location (i.e. prefix).

Channel Customization

-c,channel	Additional channel to search for packages. These are URLs searched in the order they are given (including local directories using the 'file://' syntax or simply a path like '/home/conda/mychan' or '/mychan'). Then, the defaults or channels from .condarc are searched (unlessoverride-channels is given). You can use 'defaults' to get the default packages for conda. You can also use any name and the .condarc channel_alias value will be prepended. The default channel_alias is https://conda.anaconda.org/.
use-local	Use locally built packages. Identical to '-c local'.
override-channels	Do not search default or .condarc channels. Requireschannel.
repodata-fn	Specify file name of repodata on the remote server where your channels are con- figured or within local backups. Conda will try whatever you specify, but will ultimately fall back to repodata.json if your specs are not satisfiable with what you specify here. This is used to employ repodata that is smaller and reduced in time scope. You may pass this flag more than once. Leftmost entries are tried first, and the fallback to repodata.json is added for you automatically. For more information, see conda configdescribe repodata_fns.
experimental	Possible choices: jlap, lock
	jlap: Download incremental package index data from repodata.jlap; implies 'lock'. lock: use locking when reading, updating index (repodata.json) cache. Now enabled.
no-lock	Disable locking when reading, updating index (repodata.json) cache.
repodata-use-zst, -	-no-repodata-use-zst Check for/do not check for repodata.json.zst. Enabled by default. (default: Null)

Solver Mode Modifiers

strict-channel-prio	rity Packages in lower priority channels are not considered if a package with the same name appears in a higher priority channel.
no-channel-priorit	y Package version takes precedence over channel priority. Overrides the value given by <i>conda configshow channel_priority</i> .
no-deps	Do not install, update, remove, or change dependencies. This WILL lead to broken environments and inconsistent behavior. Use at your own risk.
only-deps	Only install dependencies.
no-pin	Ignore pinned file.
solver	Possible choices: classic
	Choose which solver backend to use.
force-reinstall	Ensure that any user-requested package for the current operation is uninstalled and reinstalled, even if that package already exists in the environment.
freeze-installed,r	no-update-deps Do not update or change already-installed dependencies.
update-deps	Update dependencies that have available updates.

-S,satisfied-skip-so	Ive Exit early and do not run the solver if the requested specs are satisfied. Also
	skips aggressive updates as configured by the 'aggressive_update_packages' con-
	fig setting. Use 'conda infodescribe aggressive_update_packages' to view your settingsatisfied-skip-solve is similar to the default behavior of 'pip install'.
update-all,all	Update all installed packages in the environment.
update-specs	Update based on provided specifications.

Package Linking and Install-time Options

сору	Install all packages using copies instead of hard- or soft-linking.
no-shortcuts	Don't install start menu shortcuts
shortcuts-only	Install shortcuts only for this package name. Can be used several times.
clobber	Allow clobbering of overlapping file paths within packages, and suppress related warnings.

Networking Options

-C,use-index-cache	Use cache of channel index files, even if it has expired. This is useful if you don't want conda to check whether a new version of the repodata file exists, which will save bandwidth.
-k,insecure	Allow conda to perform "insecure" SSL connections and transfers. Equivalent to setting 'ssl_verify' to 'false'.
offline	Offline mode. Don't connect to the Internet.

Output, Prompt, and Flow Control Options

json	Report all output as json. Suitable for using conda programmatically.
-v,verbose	Can be used multiple times. Once for detailed output, twice for INFO logging, thrice for DEBUG logging, four times for TRACE logging.
-q,quiet	Do not display progress bar.
-d,dry-run	Only display what would have been done.
-y,yes	Sets any confirmation values to 'yes' automatically. Users will not be asked to confirm any adding, deleting, backups, etc.
download-only	Solve an environment and ensure package caches are populated, but exit prior to unlinking and linking packages into the prefix.
show-channel-urls	Show channel urls. Overrides the value given by <i>conda configshow show_channel_urls</i> .

Examples:

conda update -n myenv scipy

4.3.18 Conda vs. pip vs. virtualenv commands

If you have used pip and virtualenv in the past, you can use conda to perform all of the same operations. Pip is a package manager and virtualenv is an environment manager. conda is both.

Scroll to the right to see the entire table.

Task	Conda package and environ- ment manager command	Pip package manager com- mand	Virtualenv environment man- ager command
Install a package	conda install \$PACKAGE_NAME	pip install \$PACKAGE_NAME	X
Update a package	conda updatename \$ENVIRONMENT_NAME \$PACKAGE_NAME	pip installupgrade \$PACKAGE_NAME	X
Update package manager	conda update conda	Linux/macOS: pip install -U pip Win: python -m pip install -U pip	X
Unin- stall a package	conda removename \$ENVIRONMENT_NAME \$PACKAGE_NAME	pip uninstall \$PACKAGE_NAME	X
Create an envi- ronment	conda createname \$ENVIRONMENT_NAME python	X	<pre>cd \$ENV_BASE_DIR; virtualenv \$ENVIRONMENT_NAME</pre>
Activate an envi- ronment	conda activate \$ENVIRONMENT_NAME*	X	<pre>source \$ENV_BASE_DIR/ \$ENVIRONMENT_NAME/bin/ activate</pre>
Deacti- vate an environ- ment	conda deactivate	X	deactivate
Search avail- able pack- ages	conda search \$SEARCH_TERM	pip search \$SEARCH_TERM	X
Install package from specific source	conda installchannel \$URL \$PACKAGE_NAME	pip installindex-url \$URL \$PACKAGE_NAME	X
List installed pack- ages	conda listname \$ENVIRONMENT_NAME	pip list	X
Create require- ments file	conda listexport	pip freeze	X
List all environ- ments	conda infoenvs	Х	Install virtualenv wrapper, then lsvirtualenv
Install other package manager	conda install pip	pip install conda	X
Install Python	<pre>conda install python=x.x</pre>	Х	Х
Update Python	conda update python*	Х	Х

* conda activate only works on conda 4.6 and later versions. For conda versions prior to 4.6, type:

- Windows: activate
- Linux and macOS: source activate

* conda update python updates to the most recent in the series, so any Python 2.x would update to the latest 2.x and any Python 3.x to the latest 3.x.

4.4 Release notes

This information is drawn from the GitHub conda project changelog: https://github.com/conda/conda/blob/main/ CHANGELOG.md

4.4.1 24.3.0 (2024-03-12)

Enhancements

- Show first few characters of undecodeable response if repodata.json raises JSONDecodeError. (#11804)
- Update conda.gateways.subprocess.subprocess_call to use text=True to avoid manual encoding/decoding. (#13240)
- Add a new plugin hook giving plugin authors the ability to define new settings. (#13554)
- Optimize module imports to speed up conda activate. (#13567 via #13568)
- Move conda env export to conda export and alias the old command to the new command. (#13577)
- Report progress while running conda install --revision <idx>. (#13611)
- Add conda.testing.tmp_channel pytest fixture to create a temporary local channel for testing. (#13634)

Bug fixes

- Print traceback on KeyboardInterrupt instead of raising another AttributeError exception, when conda debugging logs are enabled. (#13531)
- Parse integer channel notice IDs as str instead of raising an exception. (#13543)
- Add direct runtime dependency on zstandard for use when downloading repodata.json.zst. (#13551)
- Fallback to repodata.json if repodata.json.zst cannot be decompressed as zstandard. (#13558)
- conda rename command no longer throws an error when conda is not active. (#13565)
- Fallback to repodata.json from repodata.json.zst on most 4xx error codes. (#13573)
- Fix excess resource usage by log handling when fetching repodata. (#13541 via #13628)
- Re-enable --subdir and --platform flags to be available for conda env create command. (#13632)
- Fix __archspec virtual package on Windows to return microarchitecture instead of the default x86_64. (#13641)

Deprecations

- Discontinue custom docker images. Use images provided by Anaconda Inc. or conda-forge instead. (#13162)
- Mark conda.common.compat.encode_arguments as pending deprecation. (#13240)
- Remove conda.export.handle_proxy_407. (#13629)
- Mark conda.testing.integration.make_temp_channel as pending deprecation. Use conda.testing. tmp_channel fixture instead. (#13634)
- Mark conda.testing.integration.running_a_python_capable_of_unicode_subprocessing as pending deprecation. (#13634)
- Mark conda.testing.integration.set_tmpdir as pending deprecation. Use tmp_path, conda. testing.path_factory, or conda.testing.tmp_env instead. (#13634)
- Mark conda.testing.integration._get_temp_prefix as pending deprecation. Use tmp_path, conda. testing.path_factory, or conda.testing.tmp_env instead. (#13634)
- Mark conda.testing.integration.make_temp_prefix as pending deprecation. Use tmp_path, conda. testing.path_factory, or conda.testing.tmp_env instead. (#13634)
- Mark conda.testing.integration.FORCE_temp_prefix as pending deprecation. Use tmp_path, conda. testing.path_factory, or conda.testing.tmp_env instead. (#13634)
- Mark conda.testing.integration.create_temp_location as pending deprecation. Use tmp_path or conda.testing.path_factory instead. (#13634)
- Mark conda.testing.integration.tempdir as pending deprecation. Use tmp_path or conda.testing. path_factory instead. (#13634)
- Mark conda.testing.integration.reload_config as pending deprecation. Use conda.base.context. reset_context instead. (#13634)
- Postpone conda.base.context.Context.conda_exe deprecation to conda 24.9. (#13634)
- Postpone conda.testing.integration.run_command deprecation to conda 25.3. (#13634)
- Postpone loading subcommands from executables deprecation to conda 25.3. (#13634)
- Remove vendored conda._vendor.boltons. Use boltons package instead. (#12681 via #13634)
- Remove conda.auxlib.packaging. Use a modern build system instead; see https://packaging.python.org/en/latest/tutorials/packaging-projects#creating-pyproject-toml for more details. (#12681 via #13634)
- Remove conda env create --force. Use conda env create --yes instead. (#12681 via #13634)
- Remove conda info PACKAGE. Use conda search PACKAGE --info instead. (#12681 via #13634)
- Remove conda.core.subdir_data.fetch_repodata_remote_request. Use conda.core. subdir_data.SubdirData.repo_fetch.fetch_latest_parsed instead." (#12681 via #13634)
- Remove conda.exports.memoized. Use functools.lru_cache instead. (#12681 via #13634)
- Remove conda.gateways.disk.read._digest_path. Use conda.gateways.disk.read.compute_sum instead. (#12681 via #13634)
- Remove conda.gateways.disk.read.compute_md5sum. Use conda.gateways.disk.read. compute_sum(path, "md5") instead. (#12681 via #13634)
- Remove conda.gateways.disk.read.compute_sha256sum. Use conda.gateways.disk.read. compute_sum(path, "sha256") instead. (#12681 via #13634)
- Remove conda.instructions.PREFIX. (#12681 via #13634)

- Remove conda.instructions.PREFIX_CMD. (#12681 via #13634)
- Remove conda.testing.encode_for_env_var. (#12681 via #13634)
- Remove conda.testing.conda_check_versions_aligned. (#12681 via #13634)
- Remove conda.testing.helpers.run_inprocess_conda_command. Use conda.testing.tmp_env instead. (#12681 via #13634)
- Remove conda.testing.helpers.capture_json_with_argv. (#12681 via #13634)
- Remove conda.testing.integration.get_conda_list_tuple. Use conda.core.prefix_data. PrefixData.get instead. (#12681 via #13634)
- Remove conda.utils.md5_file. Use conda.gateways.disk.read.compute_sum(path, "md5") instead. (#12681 via #13634)
- Remove conda.utils.hashsum_file. Use conda.gateways.disk.read.compute_sum instead. (#12681 via #13634)
- Remove conda.utils.safe_open. Use open instead. (#12681 via #13634)
- Remove python -m conda_env. Use conda env or python -m conda env instead. (#12681 via #13634)
- Remove conda_env.env.load_from_directory. (#12681 via #13634)
- Remove conda_env.pip_util.get_pip_version. (#12681 via #13634)
- Remove conda_env.pip_util.PipPackage. (#12681 via #13634)
- Remove conda_env.pip_util.installed. (#12681 via #13634)
- Remove conda_env.pip_util._canonicalize_name. (#12681 via #13634)
- Remove conda_env.pip_util.add_pip_installed. (#12681 via #13634)

Docs

• Update the navigation links for Miniconda. (#13572)

Other

- Remove dev/* scripts in favor of conda-incubator/setup-miniconda GitHub Action in .github/ workflows/tests.yml. (#13162)
- Stop chaining commands for steps in .github/workflows/tests.yml. (#12418 via #13162)
- Modernize tests. (#13547, #13292)
- Run GitHub tests workflow also on osx-arm64 (aka Apple Silicon) runners. Enable osx-arm64 canary builds. Fix or disable broken tests. (#13617)
- Upload stable release artifacts to GitHub releases during releases. (#13399)

Contributors

- @beeankha
- @conda-bot
- @dbast
- @dholth
- @FFY00
- @isuruf
- @jaimergp
- @jezdez
- @jjhelmus
- @kenodegard
- @zklaus made their first contribution in https://github.com/conda/conda/pull/13579
- @ForgottenProgramme
- @mbargull
- @travishathaway
- @pre-commit-ci[bot]

4.4.2 24.1.2 (2024-02-15)

Bug fixes

• Fix deprecated fetch_repodata_remote_request when repodata_use_zst is enabled. (#13595)

Contributors

• @dholth

4.4.3 24.1.1 (2024-02-12)

Bug fixes

- Fallback to repodata.json if repodata.json.zst cannot be decompressed as zstandard. (#13558)
- Fallback to repodata.json from repodata.json.zst on most 4xx error codes. (#13573)

Contributors

• @dholth

4.4.4 24.1.0 (2024-01-24)

Special announcement

The conda_env.* modules have been merged into the conda package!

To improve the integration of the conda env subcommand (previously standalone), we've moved its code into the conda package, while allowing old conda env commands to still work via Python import redirects. This is a first step of many to improving the user experience of the conda command line interface related to environment management. (#13168)

Enhancements

- Verify signatures on to-be-installed packages instead of on all packages. (#11545, #13053)
- Add new pre-solves and post-solves plugin hooks. (#13053)
- Add support for Python 3.12. (#13072)
- Check repodata.json.zst for faster repodata downloads. (#13256)
- Add --skip-flexible-search option in conda search to skip flexible search. (#13315)
- Provide a more useful warning when attempting to rename a non-existent prefix. (#13387)
- Add a new flag --keep-env to be used with conda remove --all. It allows users to delete all packages in the environment while retaining the environment itself. (#13419)
- Add a Y/N prompt warning users that conda env remove and conda remove --all deletes not only the conda packages but the entirety of the specified environment. (#13440)
- Add --repodata-use-zst/--no-repodata-use-zst flag to control repodata.json.zst check; corresponding repodata_use_zst: true/false for .condarc. Default is to check for repodata.json.zst. Disable if remote returns unparseable repodata.json.zst instead of correct data or 404. (#13504)

Bug fixes

- Create the ~/.conda directory before trying to write to the environments.txt file. (#13338)
- Ensure PackageRecord.timestamp is dumped in milliseconds. (#13483)
- Fix error when setting a non-default repodata filename via CONDA_REPODATA_FNS. (#13490)
- Fix the config file location where the integrated Anaconda client gateway loads user configuration from. This is a regression introduced in conda 23.11.0 when the platformdirs library was adopted. (#13517 via #13520)
- Interpret missing Cache-Control header as max-age=0 instead of exception. (#13522)

Deprecations

- Mark conda_env/cli/common as pending deprecation. Use conda.cli.common instead. (#13168)
- Mark conda_env/cli/main_config as pending deprecation. Use conda.cli.main_env_config instead. (#13168)
- Mark conda_env/cli/main_create as pending deprecation. Use conda.cli.main_env_create instead. (#13168)
- Mark conda_env/cli/main_export as pending deprecation. Use conda.cli.main_env_export instead. (#13168)
- Mark conda_env/cli/main_list as pending deprecation. Use conda.cli.main_env_list instead. (#13168)
- Mark conda_env/cli/main_remove as pending deprecation. Use conda.cli.main_env_remove instead. (#13168)
- Mark conda_env/cli/main_update as pending deprecation. Use conda.cli.main_env_update instead. (#13168)
- Mark conda_env/cli/main_vars as pending deprecation. Use conda.cli.main_env_vars instead. (#13168)
- Mark conda_env/env as pending deprecation. Use conda.env.env instead. (#13168)
- Mark conda_env/installers/base as pending deprecation. Use conda.env.installers.base instead. (#13168)
- Mark conda_env/installers/conda as pending deprecation. Use conda.env.installers.conda instead. (#13168)
- Mark conda_env/installers/pip as pending deprecation. Use conda.env.installers.pip instead. (#13168)
- Mark conda_env/pip_util as pending deprecation. Use conda.env.pip_util instead. (#13168)
- Mark conda_env/specs as pending deprecation. Use conda.env.specs instead. (#13168)
- Mark conda_env/specs/binstar as pending deprecation. Use conda.env.specs.binstar instead. (#13168)
- Mark conda_env/specs/requirements as pending deprecation. Use conda.env.specs.requirements instead. (#13168)
- Mark conda_env/specs/yaml_file as pending deprecation. Use conda.env.specs.yaml_file instead. (#13168)
- Mark conda.testing.integration.make_temp_package_cache as pending deprecation. (#13511)

Docs

- Update Getting Started documentation in User Guide. (#13190)
- Add GoatCounter (https://www.goatcounter.com/) as an analytics tool. (#13384)
- Add type hints and doc strings to conda.cli.main_info. (#13445)
- Add type hints and doc strings to conda.cli.main_search. (#13465)

Other

- Add type hinting for VersionOrder class. (#13380)
- Re-enable and apply pyupgrade via ruff. (#13272, #13433)
- Start tracking performance in continuous integration and automatically report about it in pull requests. (#13460)
- Add tmp_pkgs_dir fixture to replace make_temp_package_cache. (#13511)
- Improve lock API for the repodata cache. (#13455)

Contributors

- @beeankha
- @conda-bot
- @dbast
- @dholth
- @jaimergp
- @jezdez
- @johnnynunez
- @kathatherine
- @kenodegard
- @ForgottenProgramme
- @marcoesters
- @mfansler
- @schuylermartin45 made their first contribution in https://github.com/conda/conda/pull/13385
- @travishathaway
- @pre-commit-ci[bot]
- @samhaese made their first contribution in https://github.com/conda/conda/pull/13465

4.4.5 23.11.0 (2023-11-30)

Special announcement

New menuinst v2 support!

conda has supported Start menu items on Windows for a long time. This is what allows users to open up their Miniconda prompt on CMD (Command Prompt) with an initialized conda session. This menu item (or shortcut) creation logic is provided by the menuinst package.

With the release of 23.11.0, conda now supports menuinst v2, which enables the same experience across Windows, Linux, and macOS. This means package builders will be able to provide desktop icons across all operating systems, which can be especially useful for GUI applications. See the documentation for more details.

If you don't want conda to create shortcuts, you can disable it via:

• shortcuts: false entry in your . condarc configuration

- CONDA_SHORTCUTS=false environment variable
- --no-shortcuts command-line flag

Enhancements

- Add support for menuinst v2, enabling shortcuts across all platforms (Windows, Linux, macOS) using a new JSON schema (see CEP-11). Retain support for old v1-style JSON menus. (#11882)
- Stop using vendored chardet package by requests/pip; explicitly depend on charset_normalizer. (#13171)
- Introduce a new plugin hook, CondaHealthCheck, as part of conda doctor. (#13186)
- Include activate and deactivate in the --help command list. (#13191)
- Prioritize download of larger packages to prevent smaller ones from waiting. (#13248)
- Display the used solver in conda info output for debugging purposes. (#13265)
- Add __conda virtual package. (#13266)
- Switch from appdirs to platformdirs. (#13306)
- Implement resume capability for interrupted package downloads. (#8695)

Bug fixes

- Log expected JLAP range-request errors at info level, occurring when the remote file has rolled over. (#12913)
- Fix a bug causing an error when options like --debug are used without specifying a command. (#13232)
- Improve CTRL-C (cancellation) handling for parallel download threads. (#13234)
- Allow overriding of CONDA_FETCH_THREADS/fetch_threads to set parallel package downloads beyond the default 5. (#13263)
- Require requests >=2.28 for enhanced response.json() exception handling. (#13346)
- Apply callback=reset_context in conda.plan to resolve conda-build + conda-libmamba-solver incompatibilities. (conda-libmamba-solver#393 and conda-libmamba-solver#386 via #13357)

Deprecations

- Deprecate conda.plugins.subcommands.doctor.health_checks.display_health_checks function. (#13186)
- Deprecate conda.plugins.subcommands.doctor.health_checks.display_report_heading function. (#13186)
- Remove ruamel_yaml fallback; use ruamel.yaml exclusively. (#13218)
- Deprecate conda.gateways.anaconda_client.EnvAppDirs in favor of platformdirs. (#13306)
- Mark conda._vendor.cpuinfo for pending deprecation. (#13313)
- Deprecate conda._vendor.distro in favor of the distro package. (#13317)

Docs

- Add the conda-sphinx-theme to the conda documentation. (#13298)
- Update specific pages to remove redundant TOC entries. (#13298)
- Include instructions on updating conda in the main README.md. (#13343)

Other

- Add a lighter weight s3 test; update embedded test package index. (#13085)
- Refactor code to use lazy imports for all relative imports in conda.cli.main_*, and separate argparse configuration functions from conda.cli.conda_argparse to their respective conda.cli.main_* modules. (#13173)
- Move custom argparse.Actions to conda.cli.actions (e.g., NullCountAction), and relocate helper argparse functions to conda.cli.helpers (e.g., add_parser_prefix). (#13173)
- Update upper bound for ruamel.yaml to <0.19 following the release of 0.18. (#13258)
- Replace black with ruff format in pre-commit. (#13272)

Contributors

- @AniketP04 made their first contribution in https://github.com/conda/conda/pull/13224
- @beeankha
- @13rac1 made their first contribution in https://github.com/conda/conda/pull/13191
- @conda-bot
- @dholth
- @eltociear
- @jaimergp
- @jezdez
- @kathatherine
- @kenodegard
- @kennethlaskoski made their first contribution in https://github.com/conda/conda/pull/13322
- @ForgottenProgramme
- @marcoesters
- @opoplawski
- @scruel made their first contribution in https://github.com/conda/conda/pull/13274
- @travishathaway
- @gfggithubleet made their first contribution in https://github.com/conda/conda/pull/13270
- @pre-commit-ci[bot]

4.4.6 23.10.0 (2023-10-30)

Special announcement

This is an announcement about an important change in conda's functionality:

With this 23.10.0 release we are changing the default solver of conda to conda-libmamba-solver!

The previously "classic" solver is based on pycosat/Picosat and will remain part of conda for the foreseeable future, a fallback is possible and available.

Why are we switching the solver?

In short: to make conda faster and more accurate.

A "solver" is the core component of most package managers; it calculates which dependencies (and which version of those dependencies) to install when a user requests to install a package from a package repository. To address growth-related challenges within the conda ecosystem, the conda maintainers, alongside partners Anaconda, Quansight and QuantStack, introduced a new conda dependency solver based on the Mamba project in December 2022.

Since July 2023, the conda-libmamba-solver plugin has been included in all major conda ecosystem installers (miniforge, miniconda, mambaforge and Anaconda Distribution), but was disabled by default. As soon as these installers are updated to contain conda 23.10.0 or later, they will automatically default to using the conda-libmamba-solver plugin.

What can I do if this update doesn't work for me?

If the new solver is not working as you expect:

- Check if the behavior you are observing is a known issue or a deliberate change.
- If that's not the case, please consider submitting a bug report or feature request in the conda-libmamba-solver repository.
- If necessary, you can go back to using the classic solver without modifying your conda installation:
 - When possible, pass the command line option --solver=classic to your conda calls.
 - Otherwise (e.g. for conda build ... or constructor ...), set the environment variable CONDA_SOLVER=classic.
 - For permanent changes, use the conda configuration system: conda config --set solver classic.

Where can I learn more about conda-libmamba-solver?

The documentation of the conda-libmamba-solver plugin can be found on conda.github.io/conda-libmamba-solver. For more information about the conda-libmamba-solver rollout plan, please also see our blog post from earlier this year.

Enhancements

- Provide --platform and --subdir flags to create environments for non-native platforms, remembering that choice in future operations. (#11505 via #11794)
- IMPORTANT: Set solver: libmamba as the new default solver. (#12984)

Bug fixes

- Check name of symlink, not its target against valid configuration file names (condarc, .condarc, or *.yml/ yaml). (#12956)
- Have conda doctor ignore blank lines in ~/.conda/environments.txt. (#12984)

Deprecations

- Mark conda.cli.main.generate_parser as pending deprecation. Use conda.cli.conda_argparse. generate_parser instead. (#13144)
- Mark conda.auxlib.collection.firstitem as pending deprecation. (#13144)
- Mark conda.auxlib.collection.call_each as pending deprecation. (#13144)
- Mark conda.auxlib.compat.NoneType as pending deprecation. (#13144)
- Mark conda.auxlib.compat.primative_types as pending deprecation. (#13144)
- Mark conda.auxlib.compat.utf8_writer as pending deprecation. (#13144)
- Mark conda.auxlib.exceptions.AuthenticationError as pending deprecation. (#13144)
- Mark conda.auxlib.exceptions.NotFoundError as pending deprecation. (#13144)
- Mark conda.auxlib.exceptions.InitializationError as pending deprecation. (#13144)
- Mark conda.auxlib.exceptions.SenderError as pending deprecation. (#13144)
- Mark conda.auxlib.exceptions.AssignmentError as pending deprecation. (#13144)
- Mark conda.auxlib.type_coercion.boolify_truthy_string_ok as pending deprecation. (#13144)
- Mark conda.auxlib.type_coercion.listify as pending deprecation. (#13144)
- Mark conda.models.dist.IndexRecord as pending deprecation for removal in 24.9. (#13193)
- Mark conda.exports.fetch_index as pending deprecation for removal in 24.9. Use conda.core.index. fetch_index instead. (#13194)

Other

• Constrain minimum conda-build version to >=3.27. (#13177)

Contributors

- @conda-bot
- @dholth
- @jaimergp
- @jezdez
- @kenodegard
- @timhoffm
- @pre-commit-ci[bot]

4.4.7 23.9.0 (2023-09-27)

Special announcement

This is an announcement about an important and positive future change in conda's functionality:

We will change the default solver of conda to conda-libmamba-solver in a **special 23.10.0 release** in the near future!

You can already benefit from it *today* by configuring your conda installation to use it (e.g. by running conda config --set solver libmamba).

The current "classic" solver is based on pycosat/Picosat and will remain part of conda for the foreseeable future, a fallback is possible and available (see below).

Plan to change the default solver

Here is our updated plan to change the default solver, to better follow CEP 8 and reduce the potential impact on conda users:

- The upcoming, special 23.10.0 release will be dedicated to the switch of the default solver to libmamba.
- Users will be able to opt out of the libmamba solver and use the classic solver instead, by using one of these options:
 - the --solver=classic command line option,
 - the CONDA_SOLVER=classic environment variable or
 - running conda config --set solver classic.
- All development of conda-libmamba-solver plugin happens in the conda-libmamba-solver repo, including issue tracking.
- The documentation of the conda-libmamba-solver plugin can be found on conda.github.io/conda-libmamba-solver.

For more information about the conda-libmamba-solver rollout plan, please also see our blog post from earlier this year.
Context

A "solver" is the core component of most package managers; it calculates which dependencies (and which version of those dependencies) to install when a user requests to install a package from a package repository. To address growth-related challenges within the conda ecosystem, the conda maintainers, alongside partners Anaconda, Quansight and QuantStack, introduced a new conda dependency solver based on the Mamba project in December 2022.

Since July 2023, that conda-libmamba-solver plugin has been included in and automatically installed with all major conda ecosystem installers (miniforge, miniconda, mambaforge and Anaconda Distribution), with the default solver configuration unchanged.

Enhancements

- Improve speed of fish shell initialization. (#12811)
- Directly suppress use of binstar (conda) token when fetching trust metadata. (#12889)
- Add a new "auth handler" plugin hook for conda. (#12911)
- Lock index cache metadata by default. Added --no-lock option in case of problems, should not be necessary. Older --experimental=lock no longer has an effect. (#12920)
- Add context.register_envs option to control whether to register environments in ~/.conda/ environments.txt when they are created. Defaults to true. (#12924)
- Inject a new detailed output verbosity level (i.e., the old debug level -vv is now -vvv). (#12985, #12977, #12420, #13036)
- Add support for truststore to the ssl_verify config option, enabling conda to use the operating system certificate store (requires Python 3.10 or later). (#13075 and #13149)
- Add emscripten-wasm32 and wasi-wasm32 platforms to known platforms. (#13095)
- Adds the py.typed marker file to the conda package for compliance with PEP-561. (#13107)
- Import boto3 only when S3 channels are used, saving startup time. (#12914)

Bug fixes

- When using pip dependencies with conda env create, check the directory permissions before writing to disk. (#11610)
- Hide InsecureRequestWarning for JLAP when CONDA_SSL_VERIFY=false, matching non-JLAP behavior. (#12731)
- Disallow ability to create a conda environment with a colon in the prefix. (#13044)
- Fix AttributeError logging response with nonexistent request when using JLAP with file:/// URIs. (#12966)
- Do not show progress bars in non-interactive runs for cleaner logs. (#12982)
- Fix S3 bucket name. (#12989)
- Default -- j son and --debug to NULL so as to not override CONDA_JSON and CONDA_DEBUG environment variables. (#12987)
- XonshActivator now uses source-bash in non-interactive mode to avoid side-effects from interactively loaded RC files. (#13012)
- Fix conda remove --all --json output. (#13019)

- Update test data to stop triggering security scanners' false-positives. (#13034)
- Fix performance regression of basic commands (e.g., conda info) on WSL. (#13035)
- Configure conda to ignore "Retry-After" header to avoid the scenarios when this value is very large and causes conda to hang indefinitely. (#13050)
- Treat JSONDecodeError on repodata.info.json as a warning, equivalent to a missing repodata.info.json. (#13056)
- Fix sorting error for conda config --show-sources --json. (#13076)
- Catch OSError in find_commands to account for incorrect PATH entries on Windows. (#13125)
- Catch a NotWritableError when trying to find the first writable package cache dir. (#9609)
- conda env update --prune uses only the specs coming from environment.yml file and ignores the history specs. (#9614)

Deprecations

- Removed conda.another_unicode(). (#12948)
- Removed conda._vendor.toolz. (#12948, #13141)
- Removed conda._vendor.tqdm. (#12948)
- Removed conda.auxlib.decorators.memoized decorator. (#12948)
- Removed conda.base.context.Context.experimental_solver. (#12948)
- Removed conda.base.context.Context.conda_private.(#12948)
- Removed conda.base.context.Context.cuda_version. (#12948)
- Removed conda.base.context.get_prefix(). (#12948)
- Removed conda.cli.common.ensure_name_or_prefix(). (#12948)
- Removed --experimental-solver command line option. (#12948)
- Removed conda.common.cuda module. (#12948)
- Removed conda.common.path.explode_directories(already_split). (#12948)
- Removed conda.common.url.escape_channel_url(). (#12948)
- Removed conda.core.index.check_whitelist(). (#12948)
- Removed conda.core.solve._get_solver_class(). (#12948)
- Removed conda.core.subdir_data.read_mod_and_etag(). (#12948)
- Removed conda.gateways.repodata.RepodataState.load(). (#12948)
- Removed conda.gateways.repodata.RepodataState.save(). (#12948)
- Removed conda.lock module. (#12948)
- Removed conda_env.cli.common.stdout_json(). (#12948)
- Removed conda_env.cli.common.get_prefix(). (#12948)
- Removed conda_env.cli.common.find_prefix_name(). (#12948)
- Remove import of deprecated cgi module by deprecating ftp STOR support. (#13013)

- Require boto3 for S3 support and drop support for the older boto as it doesn't support our minimum required version of Python. (#13112)
- Reduce startup delay from deprecations module by using sys._getframe() instead of inspect.stack(). (#12919)

Other

- Use Ruff linter in pre-commit configuration (#12279)
- Remove unused cache_path arguments from RepoInterface/JlapRepoInterface; replaced by cache object. (#12927)

- @beenje
- @beeankha
- @chbrandt
- @chenghlee
- @conda-bot
- @dbast
- @dholth
- @duncanmmacleod
- @gforsyth
- @eltociear
- @jaimergp
- @jezdez
- @jmcarpenter2 made their first contribution in https://github.com/conda/conda/pull/13034
- @kenodegard
- @ForgottenProgramme
- @Mon-ius made their first contribution in https://github.com/conda/conda/pull/12811
- @otaithleigh made their first contribution in https://github.com/conda/conda/pull/13035
- @psteyer made their first contribution in https://github.com/conda/conda/pull/11610
- @tarcisioe made their first contribution in https://github.com/conda/conda/pull/9614
- @travishathaway
- @wolfv made their first contribution in https://github.com/conda/conda/pull/13095
- @zeehio made their first contribution in https://github.com/conda/conda/pull/13075
- @pre-commit-ci[bot]

4.4.8 23.7.4 (2023-09-12)

Enhancements

• Use os.scandir() to find conda subcommands without stat() overhead. (#13033, #13067)

Bug fixes

- Fix S3 bucket name in test suite. (#12989)
- Fix performance regression of basic commands (e.g., conda info) on WSL. (#13035)
- Catch PermissionError raised by conda.cli.find_commands.find_commands when user's \$PATH contains restricted paths. (#13062, #13089)
- Fix sorting error for conda config --show-sources --json. (#13076)

Contributors

- @beeankha
- @dholth
- @kenodegard
- @otaithleigh made their first contribution in https://github.com/conda/conda/pull/13035

4.4.9 23.7.3 (2023-08-21)

Bug fixes

• Fix regression for supporting conda executable plugins installed into non-base environments. (#13006)

Contributors

• @kenodegard

4.4.10 23.7.2 (2023-07-27)

Bug fixes

• Fix regression in parsing -- j son and -- debug flags for executable plugins. (#12935, #12936)

Contributors

• @kenodegard

4.4.11 23.7.1 (2023-07-26)

Bug fixes

• Patch parsed args with pre_args to correctly parse -- json and --debug arguments. (#12928, #12929)

Contributors

- @jezdez
- @kenodegard

4.4.12 23.7.0 (2023-07-25)

Enhancements

- Add conda.deprecations.DeprecationHandler.action helper to deprecate argparse.Actions. (#12493)
- Add support for the FreeBSD operating system and register freebsd-64 as a known subdirectory for FreeBSD on x86-64. (#12647)
- Do not mock **\$CONDA_PREFIX** when --name or --prefix is provided. (#12696)
- Add support for sha256 filters in the MatchSpec syntax (e.g. *[sha256=f453db4ffe2271ec492a2913af4e61d4a6c118201f07 (#12654 via #12707)
- Add a new health check to conda doctor detecting altered packages in an environment by comparing expected and computed sha256 checksums. (#12757)
- Add new pre_commands and post_commands plugin hooks allowing plugins to run code before and after conda subcommands. (#12712, #12758, #12864)
- Stop using distutils directly in favor of the vendored version in setuptools 60 and later or standard library equivalents. (#11136)
- Add a CITATION.cff file to the root of the repository to make it easier for users to cite conda. (#12781)
- Add optional CondaSubcommand.configure_parser allowing third-party plugins to hook into conda's argument parser. (#12814)
- Only display third-party subcommands in conda --help and not for every other subcommand. (#12814, #12740)
- Add a new config option, no_plugins, a --no-plugins command line flag, and a CONDA_NO_PLUGINS environment variable that disables external plugins for built-in conda commands. (#12748)
- Register plugins using their canonical/fully-qualified name instead of the easily spoofable entry point name. (#12869)
- De-duplicate plugin and legacy subcommands in conda --help. (#12893)
- Implement a 2-phase parser to better handle plugin disabling (via --no-plugins). (#12910)
- Refactor subcommand parsing to use a greedy parser since argparse.REMAINDER has known issues. (#12910)

Bug fixes

- Use requests.exceptions.JSONDecodeError for ensuring compatibility with different json implementations used by requests. This fixes a bug that caused only the first of multiple given source URLs to be tried. This also raises the minimum required requests version to 2.27.0. (#12683)
- Don't export __osx virtual package when CONDA_OVERRIDE_OSX="". (#12715)
- Fix erroneous conda deactivate behavior of unsetting preexisting environment variables that are identical to those set during conda activate. (#12769)
- Correct third-party subcommands to receive *remaining* arguments instead of a blanket sys.argv[2:] which broke conda_cli testing. (#12814, #12910)

Deprecations

- Mark conda.base.context.context.root_dir as pending deprecation. Use conda.base.context. context.root_prefix instead. (#12701)
- Mark conda.plugins.subcommands.doctor.cli.get_prefix as pending deprecation. Use conda.base. context.context.target_prefix instead. (#12725)
- Mark conda.models.leased_path_entry.LeasedPathEntry as pending deprecation. (#12735)
- Mark conda.models.enums.LeasedPathType as pending deprecation. (#12735)
- Mark conda.common.temporary_content_in_file as pending deprecation. Use tempfile instead. (#12795)
- Mark conda.cli.python_api as pending deprecation. Use conda.testing.conda_cli fixture instead. (#12796)

Docs

- Document how to use the new pre_commands and post_commands plugin hooks. (#12712, #12758)
- Add docstrings to all public modules. (#12792)
- Auto-generate API docs using sphinx-autoapi. (#12798)
- Convert all manual redirects into config using sphinx-reredirects. (#12798)
- Revise the plugins index page to make it easier to understand how to create a conda plugin. (#12802)
- Add missing conda env CLI docs. (#12841)

Other

- Update tests/cli/test_main_rename.py to use latest fixtures. (#12517)
- Update tests/test_activate.py to test the new behavior. (#12769)
- Re-enable all conda_env tests and remove irrelevant tests. (#12813)
- Convert all unittest-style tests to pytest-style. (#12819)
- Convert tests/test-recipes into local noarch packages instead of relying on conda-test channel and local builds. (#12879)

Contributors

- @beeankha
- @conda-bot
- @dariocurr
- @jaimergp
- @jezdez
- @johanneskoester made their first contribution in https://github.com/conda/conda/pull/12683
- @jjhelmus
- @kalawac made their first contribution in https://github.com/conda/conda/pull/12738
- @kenodegard
- @schackartk made their first contribution in https://github.com/conda/conda/pull/12781
- @lesteve made their first contribution in https://github.com/conda/conda/pull/12715
- @ForgottenProgramme
- @marcoesters made their first contribution in https://github.com/conda/conda/pull/12863
- @mpotane made their first contribution in https://github.com/conda/conda/pull/11740
- @mattkram made their first contribution in https://github.com/conda/conda/pull/12730
- @morremeyer made their first contribution in https://github.com/conda/conda/pull/12871
- @mcg1969
- @travishathaway
- @pre-commit-ci[bot]

4.4.13 23.5.2 (2023-07-13)

Bug fixes

• Correct native_path_to_unix failure to handle no paths (e.g., an empty string or an empty iterable). (#12880)

Contributors

• @kenodegard

4.4.14 23.5.1 (2023-07-12)

Bug fixes

• Add (back) the cygpath fallback logic since cygpath is not always available on Windows. (#12873)

Contributors

• @kenodegard

4.4.15 23.5.0 (2023-05-17)

Enhancements

- Add conda doctor subcommand plugin. (#474)
- Add Python 3.11 support. (#12256)
- Add conda list --reverse to return a reversed list of installed packages. (#11954)
- Switch from setup.py to pyproject.toml and use Hatchling for our build system. (#12509)
- Optimize which Python modules get imported during conda activate calls to make it faster. (#12550)
- Add conda_cli fixture to replace conda.testing.helpers.run_inprocess_conda_command and conda. testing.integration.run_command. (#12592)
- Add tmp_env fixture to replace conda.testing.integration.make_temp_env. (#12592)
- Add path_factory fixture to replace custom prefix logic like conda.testing.integration. _get_temp_prefix and conda.testing.integration.make_temp_prefix. (#12592)
- Refactor the way that the Activator classes are defined in conda/activate.py. (#12627)
- Warn about misconfiguration when signature verification is enabled. (#12639)

Bug fixes

- conda clean no longer fails if we failed to get the file stats. (#12536)
- Provide fallback version if conda.deprecations.DeprecationHandler receives a bad version. (#12541)
- Ensure the default value for defaults includes msys2 when context.subdir is win-* on non-Windows platforms. (#12555)
- Avoid TypeError when non-string types are written to the index cache metadata. (#12562)
- conda.core.package_cache_data.UrlsData.get_url no longer fails when package_path has .conda extension. (#12516)
- Stop pre-converting paths to Unix style on Windows in conda.sh, so that they are prefix replaceable upon installation, which got broken by #12509. It also relies on cygpath at runtime, which all msys2/cygwin bash versions on Windows should have available. (#12627)

Deprecations

- Mark conda_env.pip_util.get_pip_version as pending deprecation. (#12492)
- Mark conda_env.pip_util.PipPackage as pending deprecation. (#12492)
- Mark conda_env.pip_util.installed as pending deprecation. (#12492)
- Mark conda_env.pip_util._canonicalize_name as pending deprecation. (#12492)
- Mark conda_env.pip_util.add_pip_installed as pending deprecation. (#12492)
- Mark conda_env.env.load_from_directory as pending deprecation. (#12492)

- Mark python -m conda_env.cli.main as pending deprecation. Use conda env instead. (#12492)
- Mark python -m conda_env as pending deprecation. Use conda env instead. (#12492)
- Mark conda.auxlib.packaging for deprecation in 24.3.0. (#12509)
- Rename index cache metadata file .state.json to .info.json to track draft CEP. (#12669)
- Mark conda.testing.integration.get_conda_list_tuple as pending deprecation. Use conda.core. prefix_data.PrefixData().get() instead. (#12676)
- Mark conda.testing.encode_for_env_var as pending deprecation. (#12677)
- Mark conda.testing.integration.temp_chdir as pending deprecation. Use monkeypatch.chdir instead. (#12678)

Docs

- Change the README example from IPython Notebook and NumPy to PyTorch. (#12579)
- Discuss options available to properly configure mirrored channels. (#12583, #12641)
- Add flake8-docstrings to pre-commit. (#12620)

Other

- Update retry language in flexible solve and repodata logs to be less ominous. (#12612)
- Improve repodata / subdir_data programming interface (#12521). Index cache metadata has changed to . info.json to better align with the draft CEP. Improve cache locking when using jlap. Improve jlap logging. (#12572)
- Format with black and replaced pre-commit's darker hook with black. (#12554)
- Format with isort and add pre-commit isort hook. (#12554)
- Add functional tests around conda's content trust code. (#11805)
- Enable flake8 checks that are now handled by black. (#12620)

- @beeankha
- @chbrandt made their first contribution in https://github.com/conda/conda/pull/12419
- @chenghlee
- @conda-bot
- @dholth
- @THEdavehogue made their first contribution in https://github.com/conda/conda/pull/12612
- @HeavenEvolved made their first contribution in https://github.com/conda/conda/pull/12496
- @eltociear
- @jaimergp
- @jezdez
- @johnnynunez made their first contribution in https://github.com/conda/conda/pull/12256

- @kenodegard
- @ForgottenProgramme
- @pkmooreanaconda
- @tl-hbk made their first contribution in https://github.com/conda/conda/pull/12604
- @vic-ma made their first contribution in https://github.com/conda/conda/pull/12579
- @pre-commit-ci[bot]
- @sausagenoods made their first contribution in https://github.com/conda/conda/pull/12631

4.4.16 23.3.1 (2023-03-28)

Enhancements

• Fix and re-enable binstar tests. Replace custom property caching with functools.cached_property. (#12495)

Bug fixes

- Restore default argument for SubdirData method used by conda-index. (#12513)
- Include conda.gateways.repodata.jlap submodule in package. (#12545)

Other

- Add linux-s390x to multi-arch ci/dev container. (#12498)
- Expose a MINIO_RELEASE environment variable to provide a way to pin minio versions in CI setup scripts. (#12525)
- Add jsonpatch dependency to support --experimental=jlap feature. (#12528)

- @conda-bot
- @dbast
- @dholth
- @jaimergp
- @kenodegard
- @ForgottenProgramme

4.4.17 23.3.0 (2023-03-14)

Enhancements

- Allow the use of environment variables for channel urls in environment.yaml. (#10018)
- Improved error message for conda env create if the environment file is missing. (#11883)
- Stop using toolz.dicttoolz.merge and toolz.dicttoolz.merge_with. (#12039)
- Add support for incremental repodata.json updates with --experimental=jlap on the command line or experimental: ["jlap"] in .condarc (#12090). Note: switching between "use jlap" and "don't use jlap" invalidates the cache.
- Added a new conda. deprecations module for easier & standardized deprecation. Includes decorators to mark functions, modules, classes, and arguments for deprecation and functions to mark modules, constants, and topics for deprecation. (#12125)
- Adds a new channel_settings configuration parameter that will be used to override arbitrary settings on perchannel basis. (#12239)
- Improve speed of repodata.json parsing by deferring creation of individual PackageRecord objects. (#8500)
- Refactor subcommand argument parsing to make it easier to understand. This calls the plugin before invoking the default argument parsing. (#12285)
- Handle I/O errors raised while retrieving channel notices. (#12312)
- Add support for the 64-bit RISC-V architecture on Linux. (#12319)
- Update vendored version of py-cpuinfo to 0.9.0. (#12319)
- Improved code coverage. (#12346, #12457, #12469)
- Add a note about use_only_tar_bz2 being enabled on PackagesNotFoundError exceptions. (#12353)
- Added to conda CLI help that conda remove -n <myenv> --all can be used to delete environments. (#12378)
- Handle Python import errors gracefully when loading conda plugins from entrypoints. (#12460)

Bug fixes

- Fixed errors when renaming without an active environment. (#11915)
- Prevent double solve attempt if PackagesNotFoundError is raised. (#12201)
- Virtual packages follow context.subdir instead of platform.system() to enable cross-platform installations. (#12219)
- Don't export __glibc virtual package when CONDA_OVERRIDE_GLIBC="". (#12267)
- Fix arg_parse pass-through for --version and --help in conda.xsh. (#12344)
- Filter out None path values from pwd.getpwall() on Unix systems, for users without home directories, when running as root. (#12063)
- Catch ChunkedEncodingError exceptions to prevent network error tracebacks hitting the output. (#12196 via #12487)
- Fix race conditions in mkdir_p_sudo_safe. (#12490)

Deprecations

- Drop toolz.itertoolz.unique in favor of custom conda.common.iterators.unique implementation. (#12252)
- Stop using OrderedDict/odict since dict preserves insert order since Python 3.7. (#12254)
- Mark conda._vendor.boltons for deprecation in 23.9.0. (#12272, #12482)
- Mark conda_exe in context.py and a topic in print_package_info cli/main_info.py for official deprecation. (#12398)
- Remove unused chain, methodcaller, mkdtemp, StringIO imports in conda.common.compat; apply other fixes from ruff --fix . in the test suite. (#12294)
- Remove unused optimization for searching packages based on *[track_features=<feature name>]. (#12314)
- Remove Notebook spec support from conda env; this was deprecated already and scheduled to be remove in version 4.5. (#12307)
- Mark conda_exe in context.py and a topic in print_package_info cli/main_info.py for official deprecation. (#12276)
- Marking conda.utils.hashsum_file as pending deprecation. Use conda.gateways.disk.read. compute_sum instead. (#12414)
- Marking conda.utils.md5_file as pending deprecation. Use conda.gateways.disk.read. compute_sum(path, "md5") instead. (#12414)
- Marking conda.gateways.disk.read.compute_md5sum as pending deprecation. Use conda.gateways. disk.read.compute_sum(path, "md5") instead. (#12414)
- Marking conda.gateways.disk.read.compute_sha256sum as pending deprecation. Use conda. gateways.disk.read.compute_sum(path, "sha256") instead. (#12414)
- Drop Python 3.7 support. (#12436)

Docs

- Added docs for conda.deprecations. (#12452)
- Updated some instances of "Anaconda Cloud" to be "Anaconda.org". (#12238)
- Added documentation on the specifications for conda search and conda install. (#12304)
- Mark conda.utils.safe_open for deprecation. Use builtin open instead. (#12415)

Other

- Update <cache key>.json.state repodata.json cache format; check mtime against cached repodata.json. (#12090)
- Skip redundant tar --no-same-owner when running as root on Linux, since newer conda-package-handling avoids setting ownership from the archive. (#12231)
- Add additional extensions to conda.common.path for future use. (#12261)
- Pass --cov in test runner scripts but not in setup.cfg defaults, for easier debugging. (#12268)
- Constrain conda-build to at least >=3.18.3, released 2019-06-20. (#12309)

- Improve start.bat Windows development script. (#12311)
- Provide conda-forge-based Docker images and fix the bundled minio binary. (#12335)
- Add support for conda-forge-based CI runtimes. On Linux (all architectures), unit & integration tests will use Python 3.10. On Windows, Python 3.8. On macOS, only the unit tests are run with conda-forge (*instead* of defaults!), using Python 3.9. (#12350, #12447 via #12448)
- Fix testing data issue where the subdir entry in some files was mismatched. (#12389)
- Initialize conda after installing test requirements during CI. (#12446)
- Speedup pre-commit by a factor of 15 by removing ignored hooks (pylint/bandit). This locally reduces the pre-commit runtime from ~43sec to 2.9sec and thus makes it possible to run pre-commit in a loop during development to constantly provide feedback and style the code. (#12466)

- @AdrianFreundQC made their first contribution in https://github.com/conda/conda/pull/11883
- @sanzoghenzo made their first contribution in https://github.com/conda/conda/pull/12074
- @beeankha
- @conda-bot
- @dbast
- @dholth
- @FelisNivalis made their first contribution in https://github.com/conda/conda/pull/11915
- @gforsyth made their first contribution in https://github.com/conda/conda/pull/12344
- @eltociear made their first contribution in https://github.com/conda/conda/pull/12377
- @jaimergp
- @jezdez
- @jjhelmus
- @kannanjayachandran made their first contribution in https://github.com/conda/conda/pull/12363
- @kathatherine
- @kenodegard
- @ForgottenProgramme
- @ryanskeith made their first contribution in https://github.com/conda/conda/pull/12439
- @31Sanskrati made their first contribution in https://github.com/conda/conda/pull/12371
- @travishathaway
- @pre-commit-ci[bot]

4.4.18 23.1.0 (2023-01-17)

Bug fixes

- Detect CUDA driver version in subprocess. (#11667)
- Fixes the behavior of the --no-user flag in conda init so that a user's .bashrc, etc. remains unaltered, as expected. (#11949)
- Fix several more user facing MatchSpec crashes that were identified by fuzzing efforts. (#12099)
- Lock sys.stdout to avoid corrupted -- json multithreaded download progress. (#12231)

Docs

- Optional Bash completion support has been removed starting in v4.4.0, and not just deprecated. (#11171)
- Documented optional channel::package syntax for specifying dependencies in environment.yml files. (#11890)

Other

- Refactor repodata.json fetching; update on-disk cache format. Based on work by @FFY00. (#11600)
- Environment variable overwriting WARNING is printed only if the env vars are different from those specified in the OS. (#12128)
- Added conda-libmamba-solver run constraint. (#12156)
- Updated ruamel.yaml version. (#12156)
- Added tqdm dependency. (#12191)
- Use itertools.chain.from_iterable instead of equivalent tlz.concat. (#12165)
- Use toolz.unique instead of vendored copy. (#12165)
- Use itertools.islice instead of toolz.take. (#12165)
- Update CI test workflow to only run test suite when code changes occur. (#12180)
- Added Python 3.10 canary builds. (#12184)

- @beeankha
- @dholth
- @dariocurr made their first contribution in https://github.com/conda/conda/pull/12128
- @FFY00 made their first contribution in https://github.com/conda/conda/pull/11600
- @jezdez
- @jay-tau made their first contribution in https://github.com/conda/conda/pull/11738
- @kenodegard
- @pkmooreanaconda
- @sven6002 made their first contribution in https://github.com/conda/conda/pull/12162

- @ReveStobinson made their first contribution in https://github.com/conda/conda/pull/12213
- @travishathaway
- @XuehaiPan made their first contribution in https://github.com/conda/conda/pull/11667
- @xylar made their first contribution in https://github.com/conda/conda/pull/11949
- @pre-commit-ci[bot]

4.4.19 22.11.1 (2022-12-06)

Bug fixes

- Restore default virtual package specs as in 22.9.0 (#12148)
 - re-add __unix/__win packages
 - restore __archspec version/build string composition

Other

• Skip test suite for non-code changes. (#12141)

Contributors

- @LtDan33
- @jezdez
- @kenodegard
- @mbargull
- @travishathaway

4.4.20 22.11.0 (2022-11-23)

Enhancements

- Add LD_PRELOAD to env variable list. (#10665)
- Improve CLI warning about updating conda. (#11300)
- Conda's initialize block in the user's profiles will check whether the conda executable exists before calling the conda hook. (#11374)
- Switch to tqdm as a real dependency. (#12005)
- Add a new plugin mechanism. (#11435)
- Add an informative message if explicit install fails due to requested packages not being in the cache. (#11591)
- Download and extract packages in parallel. Greatly speeds up package downloads when latency is high. Controlled by the new fetch_threads config parameter, defaulting to 5 parallel downloads. Thanks @shuges-uk for reporting. (#11841)
- Add a new plugin hook for virtual packages and convert existing code for virtual packages (from index.py) into plugins. (#11854)

- Require ruamel.yaml. (#11868, #11837)
- Stop using toolz.accumulate. (#12020)
- Stop using toolz.groupby. (#11913)
- Remove vendored six package. (#11979)
- Add the ability to extend the solver backends with the conda_solvers plugin hook. (#11993)
- Stop using toolz.functoolz.excepts. (#12016)
- Stop using toolz.itertoolz.concatv. (#12020)
- Also try UTF16 and UTF32 encodings when replacing the prefix. (#9946)

Bug fixes

- conda env update would ask for user input and hang when working with pip installs of git repos and the repo was previously checked out. Tell pip not to ask for user input for that case. (#11818)
- Fix for conda update and conda install issues related to channel notices. (#11852)
- Signature verification printed None when disabled, changes default metadata_signature_status to an empty string instead. (#11944)
- Fix importlib warnings when importing conda.cli.python_api on python=3.10. (#11975)
- Several user facing MatchSpec crashes were identified by fuzzing efforts. (#11999)
- Apply minimal fixes to deal with these (and similar) crashes. (#12014)
- Prevent conda from using /bin/sh + exec trick for its own entry point, which drops \$P\$1 on some shells (#11885, #11893 via #12043).
- Handle CTRL+C during package downloading more gracefully. (#12056)
- Prefer the outer name when a MatchSpec specifies a package's name twice package-name[name=package-name] (#12062)

Deprecations

- Add a pending deprecation warning for when importing tqdm from conda._vendor. (#12005)
- Drop ruamel_yaml and ruamel_yaml_conda in favor of ruamel.yaml. (#11837)
- context.experimental_solver is now marked for pending deprecation. It is replaced by context. solver. The same applies to the --experimental-solver flag, the CONDA_EXPERIMENTAL_SOLVER environment variable, and the ExperimentalSolverChoice enum, which will be replaced by --solver, EXPERIMENTAL_SOLVER and SolverChoice, respectively. (#11889)
- Mark context.conda_private as pending deprecation. (#12101)

Docs

- Add corresponding documentation for the new plugins mechanism. (#11435)
- Update conda cheatsheet for the 4.14.0 release. The cheatsheet now includes an example for conda rename. (#11768)
- Document conda-build package format v2, also known as the .conda-format. (#11881)
- Remove allow_other_channels config option from documentation, as the option no longer exists. (#11866)
- Fix bad URL to "Introduction to conda for Data Scientists" course in conda docs. (#9782)

Other

- Add a comment to the code that explains why .bashrc is modified on Linux and .bash_profile is modified on Windows/macOS when executing conda init. (#11849)
- Add --mach and --arch options to dev/start. (#11851)
- Remove encoding pragma in file headers, as it's not needed in Python 3 anymore. (#11880)
- Refactor conda init SHELLS as argparse choices. (#11897)
- Drop pragma fixes from pre-commit checks. (#11909)
- Add pyupgrade to pre-commit checks. This change affects many files. Existing pull requests may need to be updated, rebased, or merged to address conflicts. (#11909)
- Add aarch64 and ppc64le as additional CI platforms for smoke testing. (#11911)
- Serve package files needed for testing using local server. (#12024)
- Update canary builds to guarantee builds for the commits that trigger workflow. (#12040)

- @arq0017 made their first contribution in https://github.com/conda/conda/pull/11810
- @beeankha
- @conda-bot
- @dbast
- @dholth
- @erykoff
- @consideRatio made their first contribution in https://github.com/conda/conda/pull/12028
- @jaimergp
- @jezdez
- @kathatherine
- @kenodegard
- @ForgottenProgramme made their first contribution in https://github.com/conda/conda/pull/11926
- @hmaarrfk made their first contribution in https://github.com/conda/conda/pull/9946
- @NikhilRaverkar made their first contribution in https://github.com/conda/conda/pull/11842

- @pavelzw made their first contribution in https://github.com/conda/conda/pull/11849
- @pkmooreanaconda made their first contribution in https://github.com/conda/conda/pull/12014
- @fragmede made their first contribution in https://github.com/conda/conda/pull/11818
- @SatyamVyas04 made their first contribution in https://github.com/conda/conda/pull/11870
- @timhoffm
- @travishathaway
- @dependabot made their first contribution in https://github.com/conda/conda/pull/11965
- @pre-commit-ci[bot]
- @wulmer

4.4.21 22.9.0 (2022-09-14)

Special announcement

If you have been following the conda project previously, you will notice a change in our version number for this release. We have officially switched to the CalVer versioning system as agreed upon in CEP 8 (Conda Enhancement Proposal).

Please read that CEP for more information, but here is a quick synopsis. We hope that this versioning system and our release schedule will help make our releases more predictable and transparent to the community going forward. We are now committed to making at least one release every two months, but keep in mind that we can (and most likely will) be making minor version releases within this window.

Enhancements

- Replace vendored toolz with toolz dependency. (#11589, #11700)
- Update bundled Python launchers for Windows (conda/shell/cli-*.exe) to match the ones found in condabuild. (#11676)
- Add win-arm64 as a known platform (subdir). (#11778)

Bug fixes

- Remove extra prefix injection related to the shell interface breaking conda run. (#11666)
- Better support for shebang instructions in prefixes with spaces. (#11676)
- Fix noarch entry points in Unicode-containing prefixes on Windows. (#11694)
- Ensure that exceptions that are raised show up properly instead of resulting in a blank [y/N] prompt. (#11746)

Deprecations

- Mark conda._vendor.toolz as pending deprecation. (#11704)
- Removes vendored version of urllib3. (#11705)

Docs

• Added conda capitalization standards to CONTRIBUTING file. (#11712)

Other

- Add arm64 support to development script . ./dev/start. (#11752)
- Update canary-release version to resolve canary build issue. (#11761)
- Renamed canary recipe from conda.recipe to recipe. (#11774)

Contributors

- @beeankha
- @chenghlee
- @conda-bot
- @dholth
- @isuruf
- @jaimergp
- @jezdez
- @razzlestorm made their first contribution in https://github.com/conda/conda/pull/11736
- @jakirkham
- @kathatherine
- @kenodegard
- @scdub made their first contribution in https://github.com/conda/conda/pull/11816
- @travishathaway
- @pre-commit-ci[bot]

4.4.22 4.14.0 (2022-08-02)

Enhancements

- Only star activated environment in conda info --envs/conda env list. (#10764)
- Adds new sub-command, conda notices, for retrieving channel notices. (#11462)
- Notices will be intermittently shown after running, install, create, update, env create or env update. New notices will only be shown once. (#11462)
- Implementation of a new rename subcommand. (#11496)

- Split SSLError from HTTPError to help resolve HTTP 000 errors. (#11564)
- Include the invalid package name in the error message. (#11601)
- Bump requests version (>=2.20.1) and drop monkeypatching. (#11643)
- Rename whitelist_channels to allowlist_channels. (#11647)
- Always mention channel when notifying about a new conda update. (#11671)

Bug fixes

- Correct a misleading conda --help error message. (#11625)
- Fix support for CUDA version detection on WSL2. (#11626)
- Fixed the bug when providing empty environment.yml to conda env create command. (#11556, #11630)
- Fix MD5 hash generation for FIPS-enabled systems. (#11658)
- Fixed TypeError encountered when logging is set to DEBUG and the package's JSON cannot be read. (#11679)

Deprecations

- conda.cli.common.ensure_name_or_prefix is pending deprecation in a future release. (#11490)
- Mark conda.lock as pending deprecation. (#11571)
- Remove lgtm.com config. (#11572)
- Remove Python 2.7 conda.common.url.is_ipv6_address_win_py27 implementation. (#11573)
- Remove redundant conda.resolve.dashlist definition. (#11578)
- Mark conda_env.cli.common.get_prefix and conda.base.context.get_prefix as pending deprecation in favor of conda.base.context.determine_target_prefix. (#11594)
- Mark conda_env.cli.common.stdout_json as pending deprecation in favor of conda.cli.common. stdout_json. (#11595)
- Mark conda_env.cli.common.find_prefix_name as pending deprecation. (#11596)
- Mark conda.auxlib.decorators.memoize as pending deprecation in favor of functools.lru_cache. (#11597)
- Mark conda.exports.memoized as pending deprecation in favor of functools.lru_cache. (#11597)
- Mark conda.exports.handle_proxy_407 as pending deprecation. (#11597)
- Refactor conda.activate._Activator.get_export_unset_vars to use **kwargs instead of OrderedDict. (#11649)
- Mark conda.another_to_unicode as pending deprecation. (#11678)

Docs

- Corresponding documentation of notices subcommand. (#11462)
- Corresponding documentation of rename subcommand. (#11496)
- Correct docs URL to https://docs.conda.io. (#11508)
- Updated the list of environment variables that can now expand in the Use Condarc section. (#11514)
- Include notice that the "All Users" installation option in the Anaconda Installer is no longer available due to security concerns. (#11528)
- Update conda-zsh-completeion link. (#11541)
- Missing pip as a dependency when including a pip-installed dependency. (#11543)
- Convert README.rst to README.md. (#11544)
- Updated docs and CLI help to include information on conda init arguments. (#11574)
- Added docs for writing integration tests. (#11604)
- Updated conda env create CLI documentation description and examples to be more helpful. (#11611)

Other

- Display tests summary in CI. (#11558)
- Update Dockerfile and ci-images.yml flow to build multi arch images. (#11560)
- Rename master branch to main. (#11570)

- @drewja made their first contribution in #11614
- @beeankha
- @topherocity made their first contribution in #11658
- @conda-bot
- @dandv made their first contribution in #11636
- @dbast
- @dholth
- @deepyaman made their first contribution in #11598
- @dogukanteber made their first contribution in #11556/#11630
- @jaimergp
- @kathatherine
- @kenodegard
- @nps1ngh made their first contribution in #10764
- @pseudoyim made their first contribution in #11528
- @SamStudio8 made their first contribution in #11679
- @SamuelWN made their first contribution in #11543

- @spencermathews made their first contribution in #11508
- @timgates42
- @timhoffm made their first contribution in #11601
- · @travishathaway
- @esc
- @pre-commit-ci[bot]

4.4.23 4.13.0 (2022-05-19)

Enhancements

- Introducing conda clean --logfiles to remove logfiles generated by conda-libmamba-solver. (#11387)
- Add the solver name and version to the user-agent. (#11415, #11455)
- Attempt parsing HTTP errors as a JSON and extract error details. If present, prefer these details instead of those hard-coded. (#11440)

Bug fixes

- Fix inconsistencies with conda clean --dryrun (#11385)
- Standardize tarball & package finding in conda clean (#11386, #11391)
- Fix escape_channel_url logic on Windows (#11416)
- Use 'Accept' header, not 'Content-Type' in GET header (#11446)
- Allow extended user-agent collection to fail but log the exception (#11455)

Deprecations

- Removing deprecated conda.cli.activate. Originally deprecated in conda 4.6.0 in May 2018. (#11309)
- Removing deprecated conda.compat. Originally deprecated in conda 4.6.0 in May 2018. (#11322)
- Removing deprecated conda.install. Originally deprecated in conda 4.6.0 in May 2018. (#11323)
- Removing deprecated conda.cli.main_help. Originally deprecated in conda 4.6.0 in May 2018. (#11325)
- Removed unused conda.auxlib.configuration. (#11349)
- Removed unused conda.auxlib.crypt. (#11349)
- Removed unused conda.auxlib.deprecation. (#11349)
- Removed unused conda.auxlib.factory. (#11349)
- Removed minimally used conda.auxlib.path. (#11349)
- Removed conda.exports.CrossPlatformStLink, a Windows Python <3.2 fix for os.lstat.st_nlink. (#11351)
- Remove Python 2.7 and other legacy code (#11364)
- conda run --live-stream aliases conda run --no-capture-output. (#11422)
- Removes unused exceptions. (#11424)

- Combines conda_env.exceptions with conda.exceptions. (#11425)
- Drop Python 3.6 support. (#11453)
- Remove outdated test test_init_dev_and_NoBaseEnvironmentError (#11469)

Docs

- Initial implementation of deep dive docs (#11059)
- Correction of RegisterPython description in Windows Installer arguments. (#11312)
- Added autodoc documentation for conda compare. (#11336)
- Remove duplicated instruction in manage-python.rst (#11381)
- Updated conda cheatsheet. (#11443)
- Fix typos throughout the codebase (#11448)
- Fix conda activate example (#11471)
- Updated conda 4.12 cheatsheet with new anaconda distribution version (#11479)

Other

- Add Python 3.10 as a test target. (#10992)
- Replace custom conda._vendor with vendoring (#11290)
- Replace conda.auxlib.collection.frozendict with vendored frozendict (#11398)
- Reorganize and new tests for conda.cli.main_clean (#11360)
- Removing vendored usage of urllib3 and instead implementing our own wrapper around std. lib urllib (#11373)
- Bump vendored py-cpuinfo version $4.0.0 \rightarrow 8.0.0.$ (#11393)
- Add informational Codecov status checks (#11400)

- @beeankha made their first contribution in #11469
- @ChrisPanopoulos made their first contribution in #11312
- @conda-bot
- @dholth
- @jaimergp
- @jezdez
- @kathatherine made their first contribution in #11443
- @kenodegard
- @kianmeng made their first contribution in #11448
- @simon9500 made their first contribution in #11381
- @thomasrockhu-codecov made their first contribution in #11400
- @travishathaway made their first contribution in #11373

• @pre-commit-ci[bot]

4.4.24 4.12.0 (2022-03-08)

Enhancements

• Add support for libmamba integrations. (#11193)

This is a new **experimental and opt-in** feature that allows use of the new conda-libmamba-solver for an improved user experience, based on the libmamba community project - the library version of the mamba package manager.

Please follow these steps to try out the new libmamba solver integration:

- 1. Make sure you have conda-libmamba-solver installed in your conda base environment.
- 2. Try out the solver using the --experimental-solver=libmamba command line option.

E.g. with a dry-run to install the scipy package:

conda create -n demo scipy --dry-run --experimental-solver=libmamba

Or install in an activated conda environment:

```
conda activate my-environment
conda install scipy --experimental-solver=libmamba
```

- Make sure that conda env update -f sets env vars from the referenced yaml file. (#10652)
- Improve command line argument quoting, especially for conda run. (#11189)
- Allow conda run to work in read-only environments. (#11215)
- Add support for prelink_message. (#11123)
- Added conda.CONDA_SOURCE_ROOT. (#11182)

Bug fixes

- Refactored conda.utils.ensure_comspec_set into conda.utils.get_comspec. (#11168)
- Refactored conda.cli.common.is_valid_prefix into conda.cli.common.validate_prefix. (#11172)
- Instantiate separate S3 session for thread-safety. (#11038)
- Change overly verbose info log to debug. (#11260)
- Remove five.py and update metaclass definitions. (#11267)
- Remove unnecessary conditional in setup.py (#11013)

Docs

- Clarify on AIE messaging in download.rst. (#11221)
- Fix conda environment variable echo, update example versions. (#11237)
- Fixed link in docs. (#11268)
- Update profile examples. (#11278)
- Fix typos. (#11070)
- Document conda run command. (#11299)

Other

- Added macOS to continuous integration. (#10875)
- Added ability to build per-pullrequest review builds. (#11135)
- Improved subprocess handling on Windows. (#11179)
- Add CONDA_SOURCE_ROOT env var. (#11182)
- Automatically check copyright/license disclaimer & encoding pragma. (#11183)
- Development environment per Python version. (#11233)
- Add concurrency group to cancel GHA runs on repeated pushes to branch/PR. (#11258)
- Only run GHAs on non-forks. (#11265)

- @opoplawski
- @FaustinCarter
- @jaimergp
- @rhoule-anaconda
- @jezdez
- @hajapy
- @erykoff
- @uwuvalon
- @kenodegard
- @manics
- @NaincyKumariKnoldus
- @autotmp
- @yuvipanda
- @astrojuanlu
- @marcelotrevisani

4.4.25 4.11.0 (2021-11-22)

Enhancements

- Allow channel_alias to interpolate environment variables.
- Support running conda with PyPy on Windows.
- Add ability to add, append and prepend to sequence values when using the conda config subcommand.
- Support Python 3.10 in version parser.
- Add XDG_CONFIG_HOME to the conda search path following the XDG Base Directory Specification (XDGBDS).

Bug fixes

- Fix the PowerShell activator to not show an error when unsetting environment variables.
- Remove superfluous eval statements in fish shell integration.
- Indent the conda fish integration file using fish_indent.
- Fix handling of environment variables containing equal signs (=).
- Handle permission errors when listing all known prefixes.
- Catch Unicode decoding errors when parsing conda-meta files.
- Fix handling write errors when trying to create package cache or env directories.

Docs

- Update path of conda repo in RHEL based systems to /etc/yum.repos.d/conda.repo.
- Fix the advanced pip example to stop using the now invalid file: prefix.
- Minor docs cleanup and adding Code of Conduct.
- Add auto-built architecture documentation for conda based on the C4 Model. See the conda documentation for more information.
- Expand the contributing documentation with a section about static code analysis and code linting.
- Add developer guide section to the documentation, including a conda architecture overview.
- Stop referring to updating anaconda when conda update fails with an error.

Other

- Build Docker images periodically on GitHub Actions for the continuous integration testing on Linux, storing them on GitHub Packages's registry for reduced latency and cost when using Docker Hub.
- Simplify the Linux GitHub actions workflows by combining used shell scripts.
- Add periodic GitHub Actions workflow to review old issues in the conda issue tracker and mark them as stale if no feedback is provided in a sensible amount of time, eventually closing them.
- Add periodic GitHub Actions workflow to lock the comment threads of old issues and pull requests in the conda GitHub repository to surface regressions with new issues instead.
- Refactor test suite to use more GitHub Actions runners in parallel, reducing total run time by 50%.

- Switched the issue tracker to use forms with additional questions for bug reporters to help in ticket triage.
- Add and automatically run pre-commit as part of the CI system to improve the code quality continuously and raise issues in contributed patches early on.

The used code linters are: flake8, pylint and bandit.

The Python code formatter black is used as well but is only enforced on changed code in a commit and not to the whole code base at once.

• Automatically build the conda package upon the successful merge into the master branch and upload it to the conda-canary channel on anaconda.org.

To try conda out simply run:

```
conda install -c conda-canary/label/dev conda
```

- · Automate adding new issues to public GitHub project board to facilitate issue triage.
- Update GitHub issue and pull request labels to be more consistent.
- Start using rever for release management.
- (preview) Enable one-click gitpod and GitHub Codespaces setup for Linux development.

- Benjamin Bertrand
- Chawye Hsu
- Cheng H. Lee
- Dan Meador
- Daniel Bast
- Daniel Holth
- Gregor Kržmanc
- Hsin-Hsiang Peng
- Ilan Cosman
- Isuru Fernando
- Jaime Rodríguez-Guerra
- Jan-Benedikt Jagusch
- Jannis Leidel
- John Flavin
- Jonas Haag
- · Ken Odegard
- Kfir Zvi
- Mervin Fansler
- bfis
- mkincaid

• pre-commit CI

4.4.26 4.10.3 (2021-06-29)

Bug fixes

• Reverts "Don't create an unused S3 client at import time (#10516)" in 4.10.2 that introduced a regression for users using S3 based channels. (#10756)

4.4.27 4.10.2 (2021-06-25)

Enhancements

- Add --dry-run option to conda env create (#10635)
- Print warning about pip-installed dependencies only once (#10638)
- Explicit install now respects --download-only flag (#10688)
- Bump vendored tqdm version (#10721)

Bug fixes

- Fix changeps1 handling for PowerShell (#10624)
- Handle unbound \$PS1 so sh activation does not fail with set -u (#10701)
- Fix sh activation so \$PATH is properly restored on errors (#10631)
- Fix -c option handling so defaults channel is not always re-added (#10735)
- Fix artifact verification-related warnings and errors (#10627, #10677)
- Fix log level used in conda/core/prefix_data.py (#9998)
- Fix log level used when fetching artifact verification metadata (#10621)
- Don't create an unused S3 client at import time (#10516)
- Don't load binstar_client until needed (#10692)
- Reflect dropping of older Python versions in setup.py (#10642)

Docs

- Merge release notes and changelog to reduce maintenance burden (#10745)
- Add mentions to PyPy, Anaconda terms of service (#10329, #10712)
- Update Python versions in examples (#10329, #10744)
- Update install macOS instructions (#10728)

Contributors

- @AlbertDeFusco
- @awwad
- @casperdcl
- @cgranade
- @chenghlee
- @ColemanTom
- @dan-hook
- @dbast
- @ericpre
- @HedgehogCode
- @jamesp
- @jezdez
- @johnhany97
- @lightmare
- @mattip
- @maxerbubba
- @mrakitin
- @stinos
- @thermokarst

4.4.28 4.10.1 (2021-04-12)

Bug fixes

- Fix version detection for __linux virtual package (#10599)
- Fix import from conda_content_trust (#10589)
- Fix how URL for verification metadata files are constructed (#10617)
- Partially fix profile \$PATH setup on MSYS2 (#10459)
- Remove . empty directory even when rsync is not installed (#10331)

Contributors

- @awwad
- @chenghlee
- @codepage949
- @niklasholm

4.4.29 4.10.0 (2021-03-30)

NOTE: This release formally drops support for Python 2.7 and Python < 3.6.

Enhancements

- Add pilot support for metadata signatures and verification (#10578)
- Add __linux virtual package (#10552, #10561)
- Support nested keys when using conda config --get (#10447, #10572)
- Support installing default packages when using conda env create (#10530)
- Support HTTP sources for conda env update -f (#10536)
- Make macOS code signing operations less verbose (#10372)

Bug fixes

- Fix conda search crashing on Python 3.9 (#10542)
- Allow {channel}::pip to satisfy pip requirements (#10550)
- Support {host}: {port} specifications in environment YAML files (#10417)
- Fall back to system . condarc if user . condarc is absent (#10479)
- Try UTF-16 if UTF-8 fails when reading environment YAML files (#10356)
- Properly parse Python version >= 3.10 (#10478)
- Fix zsh initialization when \$ZDOTDIR is defined (#10413)
- Fix path handling for csh (#10410)
- Fix setup.py requirement for vendored ruamel_yaml_conda (#10441)
- Fix errors when pickling vendored auxlib objects (#10386)

Docs

- Document the __unix and __windows virtual packages (#10511)
- Update list of supported and default versions of Python (#10531)
- Favor using pip instead of setup.py when setting up CI (#10308)

Miscellaneous

• CI: drop Python 2.7 and add Python 3.9 (#10548)

Contributors

- @awwad
- @BastianZim
- @beenje
- @bgobbi
- @blubs
- @chenghlee
- @cjmartian
- @ericpre
- @erykoff
- @felker
- @giladmaya
- @jamesmyatt
- @mingwandroid
- @opoplawski
- @saadparwaiz1
- @saucoide

4.4.30 4.9.2 (2020-11-10)

Enhancements

• Use vendored tqdm in conda.resolve for better consistency (#10337)

Bug fixes

• Revert to previous naming scheme for repodata cache files when use_only_tar_bz2 config option is false (#10350)

Docs

- Fix missing release notes (#10342)
- Fix permission errors when configuring deb repositories (#10347)

Contributors

- @chenghlee
- @csoja
- @dylanmorroll
- @sscherfke

4.4.31 4.9.1 (2020-10-26)

Enhancements

• Respect PEP 440 ~= "compatible release" clause (#10313)

Bug fixes

- Remove preload_openssl for Win32 (#10298)
- Add if exist to Windows registry hook (#10305)

Contributors

• @mingwandroid

4.4.32 4.9.0 (2020-10-19)

Enhancements

- Add osx-arm64 as a recognized platform (#10128, #10134, #10137)
- Resign files modified during installation on ARM64 macOS (#10260)
- Add __archspec virtual package to identify CPU microarchitecture (#9930)
- Add __unix and __win virtual packages (#10214)
- Add --no-capture--output option to conda run (#9646)
- Add --live-stream option to conda run (#10270)
- Export and import environment variables set using conda env config (#10169)

- Cache repodata from file:// channels (#9730)
- Do not relink already-installed packages (#10208)
- Speed up JSON formatting in logz module (#10189)

Bug fixes:

- Stop env remove --dry-run from actually removing environments (#10261)
- Virtual package requirements are now considered by the solver (#10057)
- Fix cached filename processing when using only tar.bz2 (#10193)
- Stop showing solver hints about CUDA when it is not a dependency (#10275)
- Ignore virtual packages when checking environment consistency (#10196)
- Fix config -- json output errors in certain circumstances (#10194)
- More consistent error handling by conda shell (#10238)
- Bump vendored version of tqdm to fix various threading and I/O bugs (#10266)

Docs

- Correctly state default /AddToPath option in Windows installer (#10179)
- Fix typos in --repodata-fn help text (#10279)

Miscellaneous

- Update CI infrastructure to use GitHub Actions (#10176, #10186, #10234)
- Update README badge to show GitHub Actions status (#10254)

- @AlbertDeFusco
- @angloyna
- @bbodenmiller
- @casperdcl
- @chenghlee
- @chrisburr
- @cjmartian
- @dhirschfeld
- @ericpre
- @gabrielcnr
- @InfiniteChai
- @isuruf
- @jjhelmus

- @LorcanHamill
- @maresb
- @mingwandroid
- @mlline00
- · @xhochy
- @ydmytryk

4.4.33 4.8.5 (2020-09-14)

Enhancements

• Add osx-arm64 as a recognized platform (#10128, #10134)

Contributors

- @isuruf
- @jjhelmus

4.4.34 4.8.4 (2020-08-06)

Enhancements

- Add linux-ppc64 as a recognized platform (#9797, #9877)
- Add linux-s390x as a recognized platform (#9933, #10051)
- Add spinner to pip installer (#10032)
- Add support for running conda in PyPy (#9764)
- Support creating conda environments using remote specification files (#9835)
- Allow request retries on various HTTP errors (#9919)
- Add compare command for environments against a specification file (#10022)
- Add (preliminary) support for JSON-format activation (#8727)
- Properly handle the CURL_CA_BUNDLE environment variable (#10078)
- More uniformly handle \$CONDA_PREFIX when exporting environments (#10092)
- Enable trailing _ to anchor OpenSSL-like versions (#9859)
- Replace listdir and glob with scandir (#9889)
- Ignore virtual packages when searching for constrained packages (#10117)
- Add virtual packages to be considered in the solver (#10057)

Bug fixes:

- Prevent remove --all from deleting non-environment directories (#10086)
- Prevent create --dry-run --yes from deleting existing environments (#10090)
- Remove extra newline from environment export file (#9649)
- Print help on incomplete conda env config command rather than crashing (#9660)
- Correctly set exit code/errorlevel when conda run exits (#9665)
- Send "inconsistent environment" warnings to stderr to avoid breaking JSON output (#9738)
- Fix output formatting from post-link scripts (#9841)
- Fix URL parsing for channel subdirs (#9844)
- Fix conda env export -f sometimes producing empty output files (#9909)
- Fix handling of Python releases with two-digit minor versions (#9999)
- Do not use gid to determine if user is an admin on *nix platforms (#10002)
- Suppress spurious xonsh activation warnings (#10005)
- Fix crash when running conda update --all on a nonexistent environment (#10028)
- Fix collections import for Python 3.8 (#10093)
- Fix regex-related deprecation warnings (#10093, #10096)
- Fix logic error when running under Python 2.7 on 64-bit platforms (#10108)
- Fix Python 3.8 leaked semaphore issue (#10115)

Docs

- Fix formatting and typos (#9623, #9689, #9898, #10042)
- Correct location for yum repository configuration files (#9988)
- Clarify usage for the --channel option (#10054)
- Clarify Python is not installed by default into new environments (#10089)

Miscellaneous

- Fixes to tests and CI pipelines (#9842, #9863, #9938, #9960, #10010)
- Remove conda-forge dependencies for developing conda (#9857, #9871)
- Audit YAML usage for safe_load vs round_trip_load (#9902)

- @alanhdu
- @angloyna
- @Anthchirp
- @Arrowbox
- @bbodenmiller
- @beenje
- @bernardoduarte
- @birdsarah
- @bnemanich
- @chenghlee
- @ChihweiLHBird
- @cjmartian
- @ericpre
- @error404-beep
- @esc
- @hartb
- @hugobuddel
- @isuruf
- @jjhelmus
- @kalefranz
- @mingwandroid
- @mlline00
- @mparry
- @mrocklin
- @necaris
- @pdnm
- @pradghos
- @ravigumm
- @Reissner
- @scopatz
- @sidhant007
- @songmeixu
- @speleo3
- @tomsaleeba
- @WinstonPais
4.4.35 4.8.3 (2020-03-13)

Docs

- Add release notes for 4.8.2 to docs (#9632)
- Fix typos in docs (#9637, #9643)
- Grammatical and formatting changes (#9647)

Bug fixes:

• Account for channel is specs (#9748)

Contributors

- @bernardoduarte
- @forrestwaters
- @jjhelmus
- @msarahan
- @rrigdon
- @timgates42

4.4.36 4.8.2 (2020-01-24)

Enhancements

• Solver messaging improvements (#9560)

Docs

- Added precedence and conflict info (#9565)
- Added how to set env variables with config API (#9536)
- Updated user guide, deleted Overview, minor clean up (#9581)
- Add code of conduct (#9601, #9602, #9603, #9603, #9604 #9605)

- change fish prompt only if changeps1 is true (#7000)
- make frozendict JSON serializable (#9539)
- Conda env create empty dir (#9543)

- @msarahan
- @jjhelmus
- @rrigdon
- @soapy1
- @teake
- @csoja
- @kfranz

4.4.37 4.8.1 (2019-12-19)

Enhancements

- improve performance for conda run by avoiding Popen.communicate (#9381)
- Put conda keyring in /usr/share/keyrings on Debian (#9424)
- refactor common.logic to fix some bugs and prepare for better modularity (#9427)
- Support nested configuration (#9449)
- Support Object configuration parameters (#9465)
- Use freeze_installed to speed up conda env update (#9511)
- add networking args to conda env create (#9525)

Docs

- fix string concatenation running words together regarding CONDA_EXE (#9411)
- Fix typo ("list" -> "info") (#9433)
- typo in condarc key envs_dirs (#9478)
- Clarify channel priority and package sorting (#9492)
- improve description of DLL loading verification and activating environments (#9453)
- Installing with specific build number (#9534)

- Fix calling python api run_command with list and string arguments (#9331)
- revert init bash completion (#9421)
- set tmp to shortened path that excludes spaces (#9409)
- avoid function redefinition upon resourcing conda.fish (#9444)
- propagate pip error level when creating envs with conda env (#9460)
- fix incorrect chown call (#9464)
- Add subdir to PackageRecord dist_str (#9418)

- Fix running conda activate in multiple processes on windows (#9477)
- Don't check in pkgs for trash (#9472)
- remove setuptools from run_constrained in recipe (#9485)
- Fix __conda_activate function to correctly return exit code (#9532)
- fix overly greedy capture done by subprocess for conda run (#9537)

- @AntoinePrv
- @brettcannon
- @bwildenhain
- @cjmartian
- @felker
- @forrestwaters
- @gilescope
- @isuruf
- @jeremyjliu
- @jjhelmus
- @jhultman
- @marcuscaisey
- @mbargull
- @mingwandroid
- @msarahan
- @okhoma
- @osamoylenko
- @rrigdon
- @rulerofthehuns
- @soapy1
- @tartansandal

4.4.38 4.8.0 (2019-11-04)

Enhancements

- retry downloads if they fail, controlled by remote_max_retries and remote_backoff_factor configuration values (#9318)
- redact authentication information in some URLs (#9341)
- add osx version virtual package , __osx (#9349)
- add glibc virtual package, __glibc (#9358)

Docs

- removeed references to MD5s from docs (#9247)
- Add docs on CONDA_DLL_SEARCH_MODIFICATION_ENABLED (#9286)
- document threads, spec history and configuration (#9327)
- more documentation on channels (#9335)
- document the .condarc search order (#9369)
- various minor documentation fixes (#9238, #9248, #9267, #9334, #9351, #9372, #9378, #9388, #9391, #9393)

Bug fixes

- fix issues with xonsh activation on Windows (#8246)
- remove unsupported --lock argument from conda clean (#8310)
- do not add sys_prefix_path to failed activation or deactivation (#9282)
- fix csh setenv command (#9284)
- do not memorize PackageRecord.combined_depends (#9289)
- use CONDA_INTERNAL_OLDPATH rather than OLDPATH in activation script (#9303)
- fixes xonsh activation and tab completion (#9305)
- fix what channels are queried when context.offline is True (#9385)

- @analog-cbarber
- @andreasg123
- @beckermr
- @bryant1410
- @colinbrislawn
- @felker
- @forrestwaters
- @gabrielcnr
- @isuruf
- @jakirkham
- @jeremyjliu
- @jjhelmus
- @jooh
- @jpigla
- @marcelotrevisani
- @melund

- @mfansler
- @mingwandroid
- @msarahan
- @rrigdon
- @scopatz
- @soapy1
- @WillyChen123
- @xhochy

4.4.39 4.7.12 (2019-09-12)

Enhancements

- add support for env file creation based on explicit specs in history (#9093)
- detect prefix paths when -p nor -n not given (#9135)
- Add config parameter to disable conflict finding (for faster time to errors) (#9190)

Bug fixes

- fix race condition with creation of repodata cache dir (#9073)
- fix ProxyError expected arguments (#9123)
- makedirs to initialize .conda folder when registering env fixes permission errors with .conda folders not existing when package cache gets created (#9215)
- fix list duplicates errors in reading repodata/prefix data (#9132)
- fix neutered specs not being recorded in history, leading to unsatisfiable environments later (#9147)
- Standardize "conda env list" behavior between platforms (#9166)
- add JSON output to conda env create/update (#9204)
- speed up finding conflicting specs (speed regression in 4.7.11) (#9218)

- @beenje
- @Bezier89
- @cjmartian
- @forrestwaters
- @jjhelmus
- @martin-raden
- @msarahan
- @nganani

- @rrigdon
- @soapy1
- @WesRoach
- @zheaton

4.4.40 4.7.11 (2019-08-06)

Enhancements

add config for control of number of threads. These can be set in condarc or using environment variables. Names/default values are: default_threads/None, repodata_threads/None, verify_threads/1, execute_threads/1 (#9044)

Bug fixes

- fix repodata_fns from condarc not being respected (#8998)
- Fix handling of UpdateModifiers other than FREEZE_INSTALLED (#8999)
- Improve conflict finding graph traversal (#9006)
- Fix setuptools being removed due to conda run_constrains (#9014)
- Avoid calling find_conflicts until all retries are spent (#9015)
- refactor _conda_activate.bat in hopes of improving behavior in parallel environments (#9021)
- Add support for local version specs in PYPI installed packages (#9025)
- fix boto3 initialization race condition (#9037)
- Fix return condition in package_cache_data (#9039)
- utilize libarchive_enabled attribute provided by conda-package-handling to fall back to .tar.bz2 files only. (#9041, #9053)
- Fix menu creation on windows having race condition, leading to popups about python.exe not being found (#9044)
- Improve list error when egg-link leads to extra egg-infos (#9045)
- Fix incorrect RemoveError when operating on an env that has one of conda's deps, but is not the env in which the current conda in use resides (#9054)

Docs

- Document new package format better
- Document conda init command
- Document availability of RSS feed for CDN-backed channels that clone

- @Bezier89
- @forrestwaters
- @hajapy
- @ihnorton
- @matthewwardrop
- @msarahan
- @rogererens
- @rrigdon
- @soapy1

4.4.41 4.7.10 (2019-07-19)

Bug fixes

- fix merging of specs
- fix bugs in building of chains in prefix graph

Contributors

• @msarahan

4.4.42 4.7.9 (2019-07-18)

Bug fixes

- fix Non records in comprehension
- fix potential keyerror in depth-first search
- fix PackageNotFound attribute error

- @jjhelmus
- @msarahan

4.4.43 4.7.8 (2019-07-17)

Improvements

- improve unsatisfiable messages try to group and explain output better. Remove lots of extraneous stuff that was showing up in 4.7.7 (#8910)
- preload openssl on windows to avoid library conflicts and missing library issues (#8949)

Bug fixes

- fix handling of channels where more than one channel contains packages with similar name, subdir, version and build_number. This was causing mysterious unsatisfiable errors for some users. (#8938)
- reverse logic check in checking channel equality, because == is not reciprocal to != with py27 (no __ne__) (#8938)
- fix an infinite loop or otherwise large process with building the unsatisfiable info. Improve the depth-first search implementation. (#8941)
- streamline fallback paths to unfrozen solve in case frozen fails. (#8942)
- Environment activation output only shows conda activate envname now, instead of sometimes showing just activate. (#8947)

Contributors

- @forrestwaters
- @jjhelmus
- @katietz
- @msarahan
- @rrigdon
- @soapy1

4.4.44 4.7.7 (2019-07-12)

Improvements

• When an update command doesn't do anything because installed software conflicts with the update, information about the conflict is shown, rather than just saying "all requests are already satisfied" (#8899)

Bug fixes

- fix missing package_type attr in finding virtual packages (#8917)
- fix parallel operations of loading index to preserve channel ordering (#8921, #8922)
- filter PrefixRecords out from PackageRecords when making a graph to show unsatisfiable deps. Fixes comparison error between mismatched types. (#8924)
- install entry points before running post-link scripts, because post link scripts may depend on entry points. (#8925)

Contributors

- @jjhelmus
- @msarahan
- @rrigdon
- @soapy1

4.4.45 4.7.6 (2019-07-11)

Improvements

- Improve cuda virtual package conflict messages to show the __cuda virtual package as part of the conflict (#8834)
- add additional debugging info to Resolve.solve (#8895)

- deduplicate error messages being shown for post-link scripts. Show captured stdout/stderr on failure (#8833)
- fix the checkout step in the Windows dev env setup instructions (#8827)
- bail out early when implicit python pinning renders an explicit spec unsatisfiable (#8834)
- handle edge cases in pinned specs better (#8843)
- extract package again if url is None (#8868)
- update docs regarding indexing and subdirs (#8874)
- remove warning about conda-build needing an update that was bothering people (#8884)
- only add repodata fn into cache key when fn is not repodata.json (#8900)
- allow conda to be downgraded with an explicit spec (#8892)
- add target to specs from historic specs (#8901)
- improve message when solving with a repodata file before repodata.json fails (#8907)
- fix distutils usage for "which" functionality. Fix inability to change python version in envs with noarch packages (#8909)
- fix anaconda metapackage being removed because history matching was too restrictive (#8911)
- make freezing less aggressive; add fallback to non-frozen solve (#8912)

- @forrestwaters
- @jjhelmus
- @mcopes73
- @msarahan
- @richardjgowers
- @rrigdon
- @soapy1
- @twinssbc

4.4.46 4.7.5 (2019-06-24)

Improvements

• improve wording in informational message when a particular *_repodata.json can't be found. No need for alarm. (#8808)

Bug fixes

- restore tests being run on win-32 appveyor (#8801)
- fix Dist class handling of .conda files (#8816)
- fix strict channel priority handling when a package is unsatisfiable and thus not present in the collection (#8819)
- handle JSONDecodeError better when package is corrupted at extract time (#8820)

Contributors

- @dhirschfeld
- @msarahan
- @rrigdon

4.4.47 4.7.4 (2019-06-19)

Improvements

• Revert to and improve the unsatisfiability determination from 4.7.2 that was reverted in 4.7.3. It's faster. (#8783)

Bug fixes

• fix tcsh/csh init scripts (#8792)

Docs improvements

- clean up docs of run_command
- fix broken links
- update docs environment.yaml file to update conda-package-handling
- conda logo favicon
- update strict channel priority info
- noarch package content ported from conda-forge
- add info about conda-forge
- remove references to things as they were before conda 4.1. That was a long time ago. This is not a history book.

Contributors

- @jjhelmus
- @msarahan
- @rrigdon
- @soapy1

4.4.48 4.7.3 (2019-06-14)

Bug fixes

- target prefix overrid applies to entry points in addition to replacements in standard files (#8769)
- Revert to solver-based unsatisfiability determination (#8775)
- fix renaming of existing prompt function in powershell (#8774)

- @jjhelmus
- @msarahan
- @rrigdon
- @ScottEvtuch

4.4.49 4.7.2 (2019-06-10)

Behavior changes

- unsatisfiability is determined in a slightly different way now. It no longer uses the SAT solver, but rather determines whether any specs have no candidates at all after running through get_reduced_index. This has been faster in benchmarks, but we welcome further data from your use cases about whether this was a good change. (#8741)
- when using the --only-deps flag for the install command, conda now explicitly records those specs in your history. This primarily serves to reduce conda accidentally removing packages that you have actually requested. (#8766)

Improvements

- UnsatisfiableError messages are now grouped into categories and explained a bit better. (#8741)
- -repodata-fn argument can be passed multiple times to have more fallback paths. repodata_fns conda config setting does the same thing, but saves you from needing to do it for every command invocation. (#8741)

Bug fixes

- fix channel flip-flopping that was happening when adding a channel other than earlier ones (#8741)
- refactor flow control for multiple repodata files to not use exceptions (#8741)
- force conda to use only old .tar.bz2 files if conda-build <3.18.3 is installed. Conda-build breaks when inspecting file contents, and this is fixed in conda-build 3.18.3 (#8741)
- use --force when using rsync to improve behavior with folders that may exist in the destination somehow. (#8750)
- handle EPERM errors when renaming, because MacOS lets you remove or create files, but not rename them. Thanks Apple. (#8755)
- fix conda removing packages installed via install with --only-deps flag when either update or remove commands are run. See behavior changes above. (#8766)

- @csosborn
- @jjhelmus
- @katietz
- @msarahan
- @rrigdon

4.4.50 4.7.1 (2019-05-30)

Improvements

- Base initial solver specs map on explicitly requested specs (new and historic) (#8689)
- Improve anonymization of automatic error reporting (#8715)
- Add option to keep using .tar.bz2 files, in case new .conda isn't working for whatever reason (#8723)

Bug fixes

- fix parsing hyphenated PyPI specs (change hyphens in versions to .) (#8688)
- fix PrefixRecord creation when file inputs are .conda files (#8689)
- fix PrefixRecord creation for pip-installed packages (#8689)
- fix progress bar stopping at 75% (no extract progress with new libarchive) (#8689)
- preserve pre-4.7 download() interface in conda.exports (#8698)
- virtual packages (such as cuda) are represented by leading double underscores by convention, to avoid confusion with existing single underscore packages that serve other purposes (#8738)

Deprecations/Breaking Changes

• The --prune flag no longer does anything. Pruning is implicitly the standard behavior now as a result of the initial solver specs coming from explicitly requested specs. Conda will remove packages that are not explicitly requested and are not required directly or indirectly by any explicitly installed package.

Docs improvements

- Document removal of the free channel from defaults (#8682)
- Add reference to conda config --describe (#8712)
- Add a tutorial for .condarc modification (#8737)

- @alexhall
- @cjmartian
- @kalefranz
- @martinkou
- @msarahan
- @rrigdon
- @soapy1

4.4.51 4.7.0 (2019-05-17)

Improvements

- Implement support for "virtual" CUDA packages, to make conda consider the system-installed CUDA driver and act accordingly (#8267)
- Support and prefer new .conda file format where available (#8265, #8639)
- Use comma-separated env names in prompt when stacking envs (#8431)
- show valid choices in error messages for enums (#8602)
- freeze already-installed packages when running conda install as a first attempt, to speed up the solve in existing envs. Fall back to full solve as necessary (#8260, #8626)
- add optimization criterion to prefer arch over noarch packages when otherwise equivalent (#8267)
- Remove free channel from defaults collection. Add restore_free_channel config parameter if you want to keep it. (#8579)
- Improve unsatisfiable hints (#8638)
- Add capability to use custom repodata filename, for smaller subsets of repodata (#8670)
- Parallelize SubdirData readup (#8670)
- Parallelize transaction verification and execution (#8670)

- Fix PATH handling with deactivate.d scripts (#8464)
- Fix usage of deprecated collections ABCs (#)
- fix tcsh/csh initialization block (#8591)
- fix missing CWD display in powershell prompt (#8596)
- wrap_subprocess_call: fallback to sh if no bash (#8611)
- move TemporaryDirectory to avoid importing from conda.compat (#8671)
- fix missing conda-package-handling dependency in dev/start (#8624)
- fix path_to_url string index out of range error (#8265)
- fix conda init for xonsh (#8644)
- fix fish activation (#8645)
- improve error handling for read-only filesystems (#8665, #8674)
- break out of minimization when bisection has nowhere to go (#8672)
- Handle None values for link channel name gracefully (#8680)

- @chrisburr
- @EternalPhane
- @jjhelmus
- @kalefranz
- @mbargull
- @msarahan
- @rrigdon
- @scopatz
- @seibert
- @soapy1
- @nehaljwani
- @nh3
- @teake
- @yuvalreches

4.4.52 4.6.14 (2019-04-17)

Bug fixes

• export extra function in powershell Conda.psm1 script (fixes anaconda powershell prompt) (#8570)

Contributors

• @msarahan

4.4.53 4.6.13 (2019-04-16)

- disable test_legacy_repodata on win-32 (missing dependencies) (#8540)
- Fix activation problems on windows with bash, powershell, and batch. Improve tests. (#8550, #8564)
- pass -U flag to for pip dependencies in conda env when running "conda env update" (#8542)
- rename conda.common.os to conda.common._os to avoid shadowing os built-in (#8548)
- raise exception when pip subprocess fails with conda env (#8562)
- fix installing recursive requirements.txt files in conda env specs with python 2.7 (#8562)
- Don't modify powershell prompt when "changeps1" setting in condarc is False (#8465)

- @dennispg
- @jjhelmus
- @jpgill86
- @mingwandroid
- @msarahan
- @noahp

4.4.54 4.6.12 (2019-04-10)

Bug fixes

- Fix compat import warning (#8507)
- Adjust collections import to avoid deprecation warning (#8499)
- Fix bug in CLI tests (#8468)
- Disallow the number sign in environment names (#8521)
- Workaround issues with noarch on certain repositories (#8523)
- Fix activation on Windows when spaces are in path (#8503)
- Fix conda init profile modification for powershell (#8531)
- Point conda.bat to condabin (#8517)
- Fix various bugs in activation (#8520, #8528)

Docs improvements

- Fix links in README (#8482)
- Changelogs for 4.6.10 and 4.6.11 (#8502)

Contributors

@Bezier89 @duncanmmacleod @ivigamberdiev @javabrett @jjhelmus @katietz @mingwandroid @msarahan @ne-haljwani @rrigdon

4.4.55 4.6.11 (2019-04-04)

- Remove sys.prefix from front of PATH in basic_posix (#8491)
- add import to fix conda.core.index.get_index (#8495)

Docs improvements

• Changelogs for 4.6.10

Contributors

- @jjhelmus
- @mingwandroid
- @msarahan

4.4.56 4.6.10 (2019-04-01)

Bug fixes

- Fix python-3 only FileNotFoundError usage in initialize.py (#8470)
- Fix more JSON encode errors for the _Null data type (#8471)
- Fix non-posix-compliant == in conda.sh (#8475, #8476)
- improve detection of pip dependency in environment.yml files to avoid warning message (#8478)
- fix condabin\conda.bat use of dp0, making PATH additions incorrect (#8480)
- init_fish_user: don't assume config file exists (#8481)
- Fix for chcp output ending with . (#8484)

Docs improvements

• Changelogs for 4.6.8, 4.6.9

- @duncanmmacleod
- @nehaljwani
- @ilango100
- @jjhelmus
- @mingwandroid
- @msarahan
- @rrigdon

4.4.57 4.6.9 (2019-03-29)

Improvements

- Improve CI for docs commits (#8387, #8401, #8417)
- Implement conda init --reverse to undo rc file and registry changes (#8400)
- Improve handling of unicode systems (#8342, #8435)
- Force the "COMSPEC" environment variable to always point to cmd.exe on windows. This was an implicit assumption that was not always true. (#8457, #8461)

Bug fixes

- Add central C:/ProgramData/conda as a search path on Windows (#8272)
- remove direct use of ruamel_yaml (prefer internal abstraction, yaml_load) (#8392)
- Fix/improve conda init support for fish shell (#8437)
- Improve solver behavior in the presence of inconsistent environments (such as pip as a conda dependency of python, but also installed via pip itself) (#8444)
- Handle read-only filesystems for environments.txt (#8451, #8453)
- Fix conda env commands involving pip-installed dependencies being installed into incorrect locations (#8435)

Docs improvements

- updated cheatsheet (#8402)
- updated color theme (#8403)

- @blackgear
- @dhirschfeld
- @jakirkham
- @jjhelmus
- @katietz
- @mingwandroid
- @msarahan
- @nehaljwani
- @rrigdon
- @soapy1
- @spamlrot-tic

4.4.58 4.6.8 (2019-03-06)

Bug fixes

- detect when parser fails to parse arguments (#8328)
- separate post-link script running from package linking. Do linking of all packages first, then run any post-link scripts after all packages are present. Ideally, more forgiving in presence of cycles. (#8350)
- quote path to temporary requirements files generated by conda env. Fixes issues with spaces. (#8352)
- improve some exception handling around checking for presence of folders in extraction of tarballs (#8360)
- fix reporting of packages when channel name is None (#8379)
- fix the post-creation helper message from "source activate" to "conda activate" (#8370)
- Add safety checks for directory traversal exploits in tarfiles. These may be disabled using the safety_checks configuration parameter. (#8374)

Docs improvements

- document MKL DLL hell and new Python env vars to control DLL search behavior (#8315)
- add github template for reporting speed issues (#8344)
- add in better use of sphinx admonitions (notes, warnings) for better accentuation in docs (#8348)
- improve skipping CI builds when only docs changes are involved (#8336)

Contributors

- @albertmichaelj
- @jjhelmus
- @matta9001
- @msarahan
- @rrigdon
- @soapy1
- @steffenvan

4.4.59 4.6.7 (2019-02-21)

- skip scanning folders for contents during reversal of transactions. Just ignore folders. A bit messier, but a lot faster. (#8266)
- fix some logic in renaming trash files to fix permission errors (#8300)
- wrap pip subprocess calls in conda-env more cleanly and uniformly (#8307)
- revert conda prepending to PATH in cli main file on windows (#8307)
- simplify conda run code to use activation subprocess wrapper. Fix a few conda tests to use conda run. (#8307)

Docs improvements

- fixed duplicated "to" in managing envs section (#8298)
- flesh out docs on activation (#8314)
- correct git syntax for adding a remote in dev docs (#8316)
- unpin sphinx version in docs requirements (#8317)

Contributors

- @jjhelmus
- @MarckK
- @msarahan
- @rrigdon
- @samgd

4.4.60 4.6.6 (2019-02-18)

Bug fixes

- fix incorrect syntax prepending to PATH for conda CLI functionality (#8295)
- fix rename_tmp.bat operating on folders, leading to hung interactive dialogs. Operate only on files. (#8295)

Contributors

- @mingwandroid
- @msarahan

4.4.61 4.6.5 (2019-02-15)

- Make super in resolve.py python 2 friendly (#8280)
- support unicode paths better in activation scripts on Windows (#)
- set PATH for conda.bat to include Conda's root prefix, so that libraries can be found when using conda when the root env is not activated (#8287, #8292)
- clean up warnings/errors about rsync and trash files (#8290)

- @jjhelmus
- @mingwandroid
- @msarahan
- @rrigdon

4.4.62 4.6.4 (2019-02-13)

Improvements

- allow configuring location of instrumentation records (#7849)
- prepend conda-env pip commands with env activation to fix library loading (#8263)

Bug fixes

- resolve #8176 SAT solver choice error handling (#8248)
- document pip_interop_enabled config parameter (#8250)
- ensure prefix temp files are inside prefix (#8253)
- ensure script_caller is bound before use (#8254)
- fix overzealous removal of folders after cleanup of failed post-link scripts (#8259)
- fix #8264: Allow 'int' datatype for values to non-sequence parameters (#8268)

Deprecations/Breaking Changes

• remove experimental featureless_minimization_disabled feature flag (#8249)

- @davemasino
- @geremih
- @jjhelmus
- @kalefranz
- @msarahan
- @minrk
- @nehaljwani
- @prusse-martin
- @rrigdon
- @soapy1

4.4.63 4.6.3 (2019-02-07)

Improvements

- Implement -stack switch for powershell usage of conda (#8217)
- Enable system-wide initialization for conda shell support (#8219)
- Activate environments prior to running post-link scripts (#8229)
- Instrument more solve calls to prioritize future optimization efforts (#8231)
- print more env info when searching in envs (#8240)

Bug fixes

- resolve #8178, fix conda pip interop assertion error with egg folders (#8184)
- resolve #8157, fix token leakage in errors and config output (#8163)
- resolve #8185, fix conda package filtering with embedded/vendored python metadata (#8198)
- resolve #8199, fix errors on .* in version specs that should have been specific to the ~= operator (#8208)
- fix .bat scripts for handling paths on Windows with spaces (#8215)
- fix powershell scripts for handling paths on Windows with spaces (#8222)
- handle missing rename script more gracefully (especially when updating/installing conda itself) (#8212)

Contributors

- @dhirschfeld
- @jjhelmus
- @kalefranz
- @msarahan
- @murrayreadccdc
- @nehaljwani
- @rrigdon
- @soapy1

4.4.64 4.6.2 (2019-01-29)

Improvements

- Documentation restructuring/improvements (#8139, #8143)
- rewrite rm_rf to use native system utilities and rename trash files (#8134)

Bug fixes

- fix UnavailableInvalidChannel errors when only noarch subdir is present (#8154)
- document, but disable the allow_conda_downgrades flag, pending re-examination of the warning, which was blocking conda operations after an upgrade-downgrade cycle across minor versions. (#8160)
- fix conda env export missing pip entries without use of pip interop enabled setting (#8165)

Contributors

- @jjhelmus
- @msarahan
- @nehaljwani
- @rrigdon

4.4.65 4.5.13 (2019-01-29)

Improvements

- document the allow_conda_downgrades configuration parameter (#8034)
- remove conda upgrade message (#8161)

Contributors

- @msarahan
- @nehaljwani

4.4.66 4.6.1 (2019-01-21)

Improvements

• optimizations in get_reduced_index (#8117, #8121, #8122)

- fix faulty onerror call for rm (#8053)
- fix activate.bat to use more direct call to conda.bat (don't require conda init; fix non-interactive script) (#8113)

- @jjhelmus
- @msarahan
- @pv

4.4.67 4.6.0 (2019-01-15)

New Feature Highlights

- resolve #7053 preview support for conda operability with pip; disabled by default (#7067, #7370, #7710, #8050)
- conda initialize (#6518, #7388, #7629)
- resolve #7194 add '-stack' flag to 'conda activate'; remove max_shlvl config (#7195, #7226, #7233)
- resolve #7087 add non-conda-installed python packages into PrefixData (#7067, #7370)
- resolve #2682 add 'conda run' preview support (#7320, #7625)
- resolve #626 conda wrapper for PowerShell (#7794, #7829)

Deprecations/Breaking Changes

- resolve #6915 remove 'conda env attach' and 'conda env upload' (#6916)
- resolve #7061 remove pkgs/pro from defaults (#7162)
- resolve #7078 add deprecation warnings for 'conda.cli.activate', 'conda.compat', and 'conda.install' (#7079)
- resolve #7194 add '-stack' flag to 'conda activate'; remove max_shlvl config (#7195)
- resolve #6979, #7086 remove Dist from majority of project (#7216, #7252)
- fix #7362 remove --license from conda info and related code paths (#7386)
- resolve #7309 deprecate 'conda info package_name' (#7310)
- remove 'conda clean --source-cache' and defer to conda-build (#7731)
- resolve #7724 move windows package cache and envs dirs back to .conda directory (#7725)
- disallow env names with colons (#7801)

Improvements

- import speedups (#7122)
- -help cleanup (#7120)
- fish autocompletion for conda env (#7101)
- remove reference to 'system' channel (#7163)
- add http error body to debug information (#7160)
- warn creating env name with space is not supported (#7168)
- support complete MatchSpec syntax in environment.yml files (#7178)
- resolve #4274 add option to remove an existing environment with 'conda create' (#7133)

- add ability for conda prompt customization via 'env_prompt' config param (#7047)
- resolve #7063 add license and license_family to MatchSpec for 'conda search' (#7064)
- resolve #7189 progress bar formatting improvement (#7191)
- raise log level for errors to error (#7229)
- add to conda.exports (#7217)
- resolve #6845 add option -S / --satisfied-skip-solve to exit early for satisfied specs (#7291)
- add NoBaseEnvironmentError and DirectoryNotACondaEnvironmentError (#7378)
- replace menuinst subprocessing by ctypes win elevation (4.6.0a3) (#7426)
- bump minimum requests version to stable, unbundled release (#7528)
- resolve #7591 updates and improvements from namespace PR for 4.6 (#7599)
- resolve #7592 compatibility shims (#7606)
- user-agent context refactor (#7630)
- solver performance improvements with benchmarks in common.logic (#7676)
- enable fuzzy-not-equal version constraint for pip interop (#7711)
- add -d short option for --dry-run (#7719)
- add --force-pkgs-dirs option to conda clean (#7719)
- address #7709 ensure --update-deps unlocks specs from previous user requests (#7719)
- add package timestamp information to output of 'conda search --info' (#7722)
- resolve #7336 'conda search' tries "fuzzy match" before showing PackagesNotFound (#7722)
- resolve #7656 strict channel priority via 'channel_priority' config option or --strict-channel-priority CLI flag (#7729)
- performance improvement to cache hash value on PackageRecord (#7715)
- resolve #7764 change name of 'condacmd' dir to 'condabin'; use on all platforms (#7773)
- resolve #7782 implement PEP-440 '~=' compatible release operator (#7783)
- disable timestamp prioritization when not needed (#7894, #8012)
- compile pyc files for noarch packages in batches (#8015)
- disable per-file sha256 safety checks by default; add extra_safety_checks condarc option to enable them (#8017)
- shorten retries for file removal on windows, where in-use files can't be removed (#8024)
- expand env vars in custom_channels, custom_multichannels, default_channels, migrated_custom_channels, and whitelist_channels (#7826)
- encode repodata to utf-8 while caching, to fix unicode characters in repodata (#7873)

Bug Fixes

- fix #7107 verify hangs when a package is corrupted (#7131)
- fix #7145 progress bar uses stderr instead of stdout (#7146)
- fix typo in conda.fish (#7152)
- fix #2154 conda remove should complain if requested removals don't exist (#7135)
- fix #7094 exit early for --dry-run with explicit and clone (#7096)
- fix activation script sort order (#7176)
- fix #7109 incorrect chown with sudo (#7180)
- fix #7210 add suppressed --mkdir back to 'conda create' (fix for 4.6.0a1) (#7211)
- fix #5681 conda env create / update when --file does not exist (#7385)
- resolve #7375 enable conda config --set update_modifier (#7377)
- fix #5885 improve conda env error messages and add extra tests (#7395)
- msys2 path conversion (#7389)
- fix autocompletion in fish (#7575)
- fix #3982 following 4.4 activation refactor (#7607)
- fix #7242 configuration load error message (#7243)
- fix conda env compatibility with pip 18 (#7612)
- fix #7184 remove conflicting specs to find solution to user's active request (#7719)
- fix #7706 add condacmd dir to cmd.exe path on first activation (#7735)
- fix #7761 spec handling errors in 4.6.0b0 (#7780)
- fix #7770 'conda list regex' only applies regex to package name (#7784)
- fix #8076 load metadata from index to resolve inconsistent envs (#8083)

Non-User-Facing Changes

- resolve #6595 use OO inheritance in activate.py (#7049)
- resolve #7220 pep8 project renamed to pycodestyle (#7221)
- proxy test routine (#7308)
- add .mailmap and .cla-signers (#7361)
- add copyright headers (#7367)
- rename common.platform to common.os and split among windows, linux, and unix utils (#7396)
- fix windows test failures when symlink not available (#7369)
- test building conda using conda-build (#7251)
- solver test metadata updates (#7664)
- explicitly add Mapping, Sequence to common.compat (#7677)
- add debug messages to communicate solver stages (#7803)
- add undocumented sat_solver config parameter (#7811)

Preview Releases

- 4.6.0a1 at d5bec21d1f64c3bc66c2999cfc690681e9c46177 on 2018-04-20
- 4.6.0a2 at c467517ca652371ebc4224f0d49315b7ec225108 on 2018-05-01
- 4.6.0b0 at 21a24f02b2687d0895de04664a4ec23ccc75c33a on 2018-09-07
- 4.6.0b1 at 1471f043eed980d62f46944e223f0add6a9a790b on 2018-10-22
- 4.6.0rc1 at 64bde065f8343276f168d2034201115dff7c5753 on 2018-12-31

Contributors

- @cgranade
- @fabioz
- @geremih
- @goanpeca
- @jesse-
- @jjhelmus
- @kalefranz
- @makbigc
- @mandeep
- @mbargull
- @msarahan
- @nehaljwani
- @ohadravid
- @teake

4.4.68 4.5.12 (2018-12-10)

Improvements

- backport 'allow_conda_downgrade' configuration parameter, default is False (#7998)
- speed up verification by disabling per-file sha256 checks (#8017)
- indicate Python 3.7 support in setup.py file (#8018)
- speed up solver by reduce the size of reduced index (#8016)
- speed up solver by skipping timestamp minimization when not needed (#8012)
- compile pyc files more efficiently, will speed up install of noarch packages (#8025)
- avoid waiting for removal of files on Windows when possible (#8024)

Bug Fixes

- update integration tests for removal of 'features' key (#7726)
- fix conda.bat return code (#7944)
- ensure channel name is not NoneType (#8021)

Contributors

- @debionne
- @jjhelmus
- @kalefranz
- @msarahan
- @nehaljwani

4.4.69 4.5.11 (2018-08-21)

Improvements

• resolve #7672 compatibility with ruamel.yaml 0.15.54 (#7675)

Contributors

- @CJ-Wright
- @mbargull

4.4.70 4.5.10 (2018-08-13)

Bug Fixes

- fix conda env compatibility with pip 18 (#7627)
- fix py37 compat 4.5.x (#7641)
- fix #7451 don't print name, version, and size if unknown (#7648)
- replace glob with fnmatch in PrefixData (#7645)

- @jesse-
- @nehaljwani

4.4.71 4.5.9 (2018-07-30)

Improvements

- resolve #7522 prevent conda from scheduling downgrades (#7598)
- allow skipping feature maximization in resolver (#7601)

Bug Fixes

- fix #7559 symlink stat in localfs adapter (#7561)
- fix #7486 activate with no PATH set (#7562)
- resolve #7522 prevent conda from scheduling downgrades (#7598)

Contributors

- @kalefranz
- @loriab

4.4.72 4.5.8 (2018-07-10)

Bug Fixes

• fix #7524 should_bypass_proxies for requests 2.13.0 and earlier (#7525)

Contributors

• @kalefranz

4.4.73 4.5.7 (2018-07-09)

Improvements

- resolve #7423 add upgrade error for unsupported repodata_version (#7415)
- raise CondaUpgradeError for conda version downgrades on environments (#7517)

- fix #7505 temp directory for UnlinkLinkTransaction should be in target prefix (#7516)
- fix #7506 requests monkeypatch fallback for old requests versions (#7515)

- @kalefranz
- @nehaljwani

4.4.74 4.5.6 (2018-07-06)

Bug Fixes

- resolve #7473 py37 support (#7499)
- fix #7494 History spec parsing edge cases (#7500)
- fix requests 2.19 incompatibility with NO_PROXY env var (#7498)
- resolve #7372 disable http error uploads and CI cleanup (#7498, #7501)

Contributors

• @kalefranz

4.4.75 4.5.5 (2018-06-29)

Bug Fixes

- fix #7165 conda version check should be restricted to channel conda is from (#7289, #7303)
- fix #7341 ValueError n cannot be negative (#7360)
- fix #6691 fix history file parsing containing comma-joined version specs (#7418)
- fix msys2 path conversion (#7471)

Contributors

- @goanpeca
- @kalefranz
- @mingwandroid
- @mbargull

4.4.76 4.5.4 (2018-05-14)

Improvements

• resolve #7189 progress bar improvement (#7191 via #7274)

Bug Fixes

- fix twofold tarball extraction, improve progress update (#7275)
- fix #7253 always respect copy LinkType (#7269)

Contributors

- @jakirkham
- @kalefranz
- @mbargull

4.4.77 4.5.3 (2018-05-07)

Bug Fixes

• fix #7240 conda's configuration context is not initialized in conda.exports (#7244)

4.4.78 4.5.2 (2018-04-27)

Bug Fixes

- fix #7107 verify hangs when a package is corrupted (#7223)
- fix #7094 exit early for --dry-run with explicit and clone (#7224)
- fix activation/deactivation script sort order (#7225)

4.4.79 4.5.1 (2018-04-13)

Improvements

- resolve #7075 add anaconda.org search message to PackagesNotFoundError (#7076)
- add CondaError details to auto-upload reports (#7060)

- fix #6703,#6981 index out of bound when running deactivate on fish shell (#6993)
- properly close over \$_CONDA_EXE variable (#7004)
- fix condarc map parsing with comments (#7021)
- fix #6919 csh prompt (#7041)
- add _file_created attribute (#7054)
- fix handling of non-ascii characters in custom_multichannels (#7050)
- fix #6877 handle non-zero return in CSH (#7042)
- fix #7040 update tqdm to version 4.22.0 (#7157)

4.4.80 4.5.0 (2018-03-20)

New Feature Highlights

• A new flag, '-envs', has been added to 'conda search'. In this mode, 'conda search' will look for the package query in existing conda environments on your system. If ran as UID 0 (i.e. root) on unix systems or as an Administrator user on Windows, all known conda environments for all users on the system will be searched. For example, 'conda search --envs openssl' will show the openssl version and environment location for all conda-installed openssl packages.

Deprecations/Breaking Changes

- resolve #6886 transition defaults from repo.continuum.io to repo.anaconda.com (#6887)
- resolve #6192 deprecate 'conda help' in favor of --help CLI flag (#6918)
- resolve #6894 add http errors to auto-uploaded error reports (#6895)

Improvements

- resolve #6791 conda search --envs (#6794)
- preserve exit status in fish shell (#6760)
- resolve #6810 add CONDA_EXE environment variable to activate (#6923)
- resolve #6695 outdated conda warning respects --quiet flag (#6935)
- add instructions to activate default environment (#6944)

API

• resolve #5610 add PrefixData, SubdirData, and PackageCacheData to conda/api.py (#6922)

- channel matchspec fixes (#6893)
- fix #6930 add missing return statement to S3Adapter (#6931)
- fix #5802, #6736 enforce disallowed_packages configuration parameter (#6932)
- fix #6860 infinite recursion in resolve.py for empty track_features (#6928)
- set encoding for PY2 stdout/stderr (#6951)
- fix #6821 non-deterministic behavior from MatchSpec merge clobbering (#6956)
- fix #6904 logic errors in prefix graph data structure (#6929)

Non-User-Facing Changes

- fix several lgtm.com flags (#6757, #6883)
- cleanups and refactors for conda 4.5 (#6889)
- unify location of record types in conda/models/records.py (#6924)
- resolve #6952 memoize url search in package cache loading (#6957)

4.4.81 4.4.11 (2018-02-23)

Improvements

- resolve #6582 swallow_broken_pipe context manager and Spinner refactor (#6616)
- resolve #6882 document max_shlvl (#6892)
- resolve #6733 make empty env vars sequence-safe for sequence parameters (#6741)
- resolve #6900 don't record conda skeleton environments in environments.txt (#6908)

Bug Fixes

- fix potential error in ensure_pad(); add more tests (#6817)
- fix #6840 handle error return values in conda.sh (#6850)
- use conda.gateways.disk for misc.py imports (#6870)
- fix #6672 don't update conda during conda-env operations (#6773)
- fix #6811 don't attempt copy/remove fallback for rename failures (#6867)
- fix #6667 aliased posix commands (#6669)
- fix #6816 fish environment autocomplete (#6885)
- fix #6880 build_number comparison not functional in match_spec (#6881)
- fix #6910 sort key prioritizes build string over build number (#6911)
- fix #6914, #6691 conda can fail to update packages even though newer versions exist (#6921)
- fix #6899 handle Unicode output in activate commands (#6909)

4.4.82 4.4.10 (2018-02-09)

- fix #6837 require at least futures 3.0.0 (#6855)
- fix #6852 ensure temporary path is writable (#6856)
- fix #6833 improve feature mismatch metric (via 4.3.34 #6853)

4.4.83 4.4.9 (2018-02-06)

Improvements

• resolve #6632 display package removal plan when deleting an env (#6801)

Bug Fixes

- fix #6531 don't drop credentials for conda-build workaround (#6798)
- fix external command execution issue (#6789)
- fix #5792 conda env export error common in path (#6795)
- fix #6390 add CorruptedEnvironmentError (#6778)
- fix #5884 allow --insecure CLI flag without contradicting meaning of ssl_verify (#6782)
- fix MatchSpec.match() accepting dict (#6808)
- fix broken Anaconda Prompt for users with spaces in paths (#6825)
- JSONDecodeError was added in Python 3.5 (#6848)
- fix #6796 update PATH/prompt on reactivate (#6828)
- fix #6401 non-ascii characters on windows using expanduser (#6847)
- fix #6824 import installers before invoking any (#6849)

4.4.84 4.4.8 (2018-01-25)

Improvements

- allow falsey values for default_python to avoid pinning python (#6682)
- resolve #6700 add message for no space left on device (#6709)
- make variable 'sourced' local for posix shells (#6726)
- add column headers to conda list results (#5726)

- fix #6713 allow parenthesis in prefix path for conda.bat (#6722)
- fix #6684 --force message (#6723)
- fix #6693 KeyError with '-update-deps' (#6694)
- fix aggressive_update_packages availability (#6727)
- fix #6745 don't truncate channel priority map in conda installer (#6746)
- add workaround for system Python usage by lsb_release (#6769)
- fix #6624 can't start new thread (#6653)
- fix #6628 'conda install --rev' in conda 4.4 (#6724)
- fix #6707 FileNotFoundError when extracting tarball (#6708)

- fix #6704 unexpected token in conda.bat (#6710)
- fix #6208 return for no pip in environment (#6784)
- fix #6457 env var cleanup (#6790)
- fix #6645 escape paths for argparse help (#6779)
- fix #6739 handle unicode in environment variables for py2 activate (#6777)
- fix #6618 RepresenterError with 'conda config --set' (#6619)
- fix #6699 suppress memory error upload reports (#6776)
- fix #6770 CRLF for cmd.exe (#6775)
- fix #6514 add message for case-insensitive filesystem errors (#6764)
- fix #6537 AttributeError value for url not set (#6754)
- fix #6748 only warn if unable to register environment due to EACCES (#6752)

4.4.85 4.4.7 (2018-01-08)

Improvements

• resolve #6650 add upgrade message for unicode errors in python 2 (#6651)

Bug Fixes

- fix #6643 difference between '==' and 'exact_match_' (#6647)
- fix #6620 KeyError(u'CONDA_PREFIX',) (#6652)
- fix #6661 remove env from environments.txt (#6662)
- fix #6629 'conda update --name' AssertionError (#6656)
- fix #6630 repodata AssertionError (#6657)
- fix #6626 add setuptools as constrained dependency (#6654)
- fix #6659 conda list explicit should be dependency sorted (#6671)
- fix #6665 KeyError for channel '' (#6668, #6673)
- fix #6627 AttributeError on 'conda activate' (#6655)

4.4.86 4.4.6 (2017-12-31)

- fix #6612 do not assume Anaconda Python on Windows nor Library\bin hack (#6615)
- recipe test improvements and associated bug fixes (#6614)

4.4.87 4.4.5 (2017-12-29)

Bug Fixes

- fix #6577, #6580 single quote in PS1 (#6585)
- fix #6584 os.getcwd() FileNotFound (#6589)
- fix #6592 deactivate command order (#6602)
- fix #6579 python not recognized as command (#6588)
- fix #6572 cached repodata PermissionsError (#6573)
- change instances of 'root' to 'base' (#6598)
- fix #6607 use subprocess rather than execv for conda command extensions (#6609)
- fix #6581 git-bash activation (#6587)
- fix #6599 space in path to base prefix (#6608)

4.4.88 4.4.4 (2017-12-24)

Improvements

- add SUDO_ env vars to info reports (#6563)
- add additional information to the #6546 exception (#6551)

Bug Fixes

- fix #6548 'conda update' installs packages not in prefix #6550
- fix #6546 update after creating an empty env (#6568)
- fix #6557 conda list FileNotFoundError (#6558)
- fix #6554 package cache FileNotFoundError (#6555)
- fix #6529 yaml parse error (#6560)
- fix #6562 repodata_record.json permissions error stack trace (#6564)
- fix #6520 --use-local flag (#6526)

4.4.89 4.4.3 (2017-12-22)

Improvements

• adjust error report message (#6534)
- fix #6530 package cache JsonDecodeError / ValueError (#6533)
- fix #6538 BrokenPipeError (#6540)
- fix #6532 remove anaconda metapackage hack (#6539)
- fix #6536 'conda env export' for old versions of pip (#6535)
- fix #6541 py2 and unicode in environments.txt (#6542)

Non-User-Facing Changes

• regression tests for #6512 (#6515)

4.4.90 4.4.2 (2017-12-22)

Deprecations/Breaking Changes

• resolve #6523 don't prune with --update-all (#6524)

Bug Fixes

- fix #6508 environments.txt permissions error stack trace (#6511)
- fix #6522 error message formatted incorrectly (#6525)
- fix #6516 hold channels over from get_index to install_actions (#6517)

4.4.91 4.4.1 (2017-12-21)

Bug Fixes

• fix #6512 reactivate does not accept arguments (#6513)

4.4.92 4.4.0 (2017-12-20)

Recommended change to enable conda in your shell

With the release of conda 4.4, we recommend a change to how the conda command is made available to your shell environment. All the old methods still work as before, but you'll need the new method to enable the new conda activate and conda deactivate commands.

For the "Anaconda Prompt" on Windows, there is no change.

For Bourne shell derivatives (bash, zsh, dash, etc.), you likely currently have a line similar to

export PATH="/opt/conda/bin:\$PATH"

in your ~/.bashrc file (or ~/.bash_profile file on macOS). The effect of this line is that your base environment is put on PATH, but without actually *activating* that environment. (In 4.4 we've renamed the 'root' environment to the 'base' environment.) With conda 4.4, we recommend removing the line where the PATH environment variable is modified, and replacing it with

```
. /opt/conda/etc/profile.d/conda.sh conda activate base
```

In the above, it's assumed that /opt/conda is the location where you installed miniconda or Anaconda. It may also be something like ~/Anaconda3 or ~/miniconda2.

For system-wide conda installs, to make the conda command available to all users, rather than manipulating individual ~/.bashrc (or ~/.bash_profile) files for each user, just execute once

\$ sudo ln -s /opt/conda/etc/profile.d/conda.sh /etc/profile.d/conda.sh

This will make the conda command itself available to all users, but conda's base (root) environment will *not* be activated by default. Users will still need to run conda activate base to put the base environment on PATH and gain access to the executables in the base environment.

After updating to conda 4.4, we also recommend pinning conda to a specific channel. For example, executing the command

\$ conda config --system --add pinned_packages conda-canary::conda

will make sure that whenever conda is installed or changed in an environment, the source of the package is always being pulled from the conda-canary channel. This will be useful for people who use conda-forge, to prevent conda from flipping back and forth between 4.3 and 4.4.

New Feature Highlights

- **conda activate**: The logic and mechanisms underlying environment activation have been reworked. With conda 4.4, conda activate and conda deactivate are now the preferred commands for activating and deactivating environments. You'll find they are much more snappy than the source activate and source deactivate commands from previous conda versions. The conda activate command also has advantages of (1) being universal across all OSes, shells, and platforms, and (2) not having path collisions with scripts from other packages like python virtualenv's activate script.
- **constrained, optional dependencies**: Conda now allows a package to constrain versions of other packages installed alongside it, even if those constrained packages are not themselves hard dependencies for that package. In other words, it lets a package specify that, if another package ends up being installed into an environment, it must at least conform to a certain version specification. In effect, constrained dependencies are a type of "reverse" dependency. It gives a tool to a parent package to exclude other packages from an environment that might otherwise want to depend on it.

Constrained optional dependencies are supported starting with conda-build 3.0 (via [conda/conda-build#2001[(https://github.com/conda/conda-build/pull/2001])). A new run_constrained keyword, which takes a list of package specs similar to the run keyword, is recognized under the requirements section of meta.yaml. For backward compatibility with versions of conda older than 4.4, a requirement may be listed in both the run and the run_constrained section. In that case older versions of conda will see the package as a hard dependency, while conda 4.4 will understand that the package is meant to be optional.

Optional, constrained dependencies end up in repodata.json under a constrains keyword, parallel to the depends keyword for a package's hard dependencies.

• enhanced package query language: Conda has a built-in query language for searching for and matching packages, what we often refer to as MatchSpec. The MatchSpec is what users input on the command line when they specify packages for create, install, update, and remove operations. With this release, MatchSpec (rather than a regex) becomes the default input for conda search. We have also substantially enhanced our MatchSpec query language.

For example,

conda install conda-forge::python

is now a valid command, which specifies that regardless of the active list of channel priorities, the python package itself should come from the conda-forge channel. As before, the difference between python=3.5 and python==3.5 is that the first contains a "*fuzzy*" version while the second contains an *exact* version. The fuzzy spec will match all python packages with versions >=3.5 and <3.6. The exact spec will match only python packages with version 3.5, 3.5.0, 3.5.0.0, etc. The canonical string form for a MatchSpec is thus

(channel::)name(version(build_string))

which should feel natural to experienced conda users. Specifications however are often necessarily more complicated than this simple form can support, and for these situations we've extended the specification to include an optional square bracket [] component containing comma-separated key-value pairs to allow matching on most any field contained in a package's metadata. Take, for example,

conda search 'conda-forge/linux-64::*[md5=e42a03f799131d5af4196ce31a1084a7]' --info

which results in information for the single package

```
cytoolz 0.8.2 py35_0
file name
          : cytoolz-0.8.2-py35_0.tar.bz2
            : cytoolz
name
version
            : 0.8.2
build string: py35_0
build number: 0
size
            : 1.1 MB
arch
            : x86_64
            : Platform.linux
platform
license
            : BSD 3-Clause
subdir
            : linux-64
url
            : https://conda.anaconda.org/conda-forge/linux-64/cytoolz-0.8.2-py35_0.
\rightarrowtar.bz2
md5
            : e42a03f799131d5af4196ce31a1084a7
dependencies:
  - python 3.5*
  - toolz \geq 0.8.0
```

The square bracket notation can also be used for any field that we match on outside the package name, and will override information given in the "simple form" position. To give a contrived example, python==3. 5[version='>=2.7,<2.8'] will match 2.7.* versions and not 3.5.

• environments track user-requested state: Building on our enhanced MatchSpec query language, conda environments now also track and differentiate (a) packages added to an environment because of an explicit user request from (b) packages brought into an environment to satisfy dependencies. For example, executing

conda install conda-forge::scikit-learn

will confine all future changes to the scikit-learn package in the environment to the conda-forge channel, until the spec is changed again. A subsequent command conda install scikit-learn=0.18 would drop the conda-forge channel restriction from the package. And in this case, scikit-learn is the only user-defined spec, so the solver chooses dependencies from all configured channels and all available versions.

• errors posted to core maintainers: In previous versions of conda, unexpected errors resulted in a request for users to consider posting the error as a new issue on conda's github issue tracker. In conda 4.4, we've implemented

a system for users to opt-in to sending that same error report via an HTTP POST request directly to the core maintainers.

When an unexpected error is encountered, users are prompted with the error report followed by a [y/N] input. Users can elect to send the report, with 'no' being the default response. Users can also permanently opt-in or opt-out, thereby skipping the prompt altogether, using the boolean report_errors configuration parameter.

- various UI improvements: To push through some of the big leaps with transactions in conda 4.3, we accepted some regressions on progress bars and other user interface features. All of those indicators of progress, and more, have been brought back and further improved.
- aggressive updates: Conda now supports an aggressive_update_packages configuration parameter that holds a sequence of MatchSpec strings, in addition to the pinned_packages configuration parameter. Currently, the default value contains the packages ca-certificates, certifi, and openssl. When manipulating configuration with the conda config command, use of the --system and --env flags will be especially helpful here. For example,

conda config --add aggressive_update_packages defaults::pyopenssl --system

would ensure that, system-wide, solves on all environments enforce using the latest version of pyopenssl from the defaults channel.

conda config --add pinned_packages python=2.7 --env

would lock all solves for the current active environment to python versions matching 2.7.*.

• other configuration improvements: In addition to conda config --describe, which shows detailed descriptions and default values for all available configuration parameters, we have a new conda config --write-default command. This new command simply writes the contents of conda config --describe to a condarc file, which is a great starter template. Without additional arguments, the command will write to the .condarc file in the user's home directory. The command also works with the --system, --env, and --file flags to write the contents to alternate locations.

Conda exposes a tremendous amount of flexibility via configuration. For more information, The Conda Configuration Engine for Power Users blog post is a good resource.

Deprecations/Breaking Changes

- the conda 'root' environment is now generally referred to as the 'base' environment
- Conda 4.4 now warns when available information about per-path sha256 sums and file sizes do not match the recorded information. The warning is scheduled to be an error in conda 4.5. Behavior is configurable via the safety_checks configuration parameter.
- remove support for with_features_depends (#5191)
- resolve #5468 remove --alt-hint from CLI API (#5469)
- resolve #5834 change default value of 'allow_softlinks' from True to False (#5835)
- resolve #5842 add deprecation warnings for 'conda env upload' and 'conda env attach' (#5843)

API

• Add Solver from conda.core.solver with three methods to conda.api (4.4.0rc1) (#5838)

- constrained, optional dependencies (#4982)
- conda shell function (#5044, #5141, #5162, #5169, #5182, #5210, #5482)
- resolve #5160 conda xontrib plugin (#5157)
- resolve #1543 add support and tests for --no-deps and --only-deps (#5265)
- resolve #988 allow channel name to be part of the package name spec (#5365, #5791)
- resolve #5530 add ability for users to choose to post unexpected errors to core maintainers (#5531, #5571, #5585)
- Solver, UI, History, and Other (#5546, #5583, #5740)
- improve 'conda search' to leverage new MatchSpec query language (#5597)
- filter out unwritable package caches from conda clean command (#4620)
- envs_manager, requested spec history, declarative solve, and private env tests (#4676, #5114, #5094, #5145, #5492)
- make python entry point format match pip entry points (#5010)
- resolve #5113 clean up CLI imports to improve process startup time (#4799)
- resolve #5121 add features/track_features support for MatchSpec (#5054)
- resolve #4671 hold verify backoff count in transaction context (#5122)
- resolve #5078 record package metadata after tarball extraction (#5148)
- resolve #3580 support stacking environments (#5159)
- resolve #3763, #4378 allow pip requirements.txt syntax in environment files (#3969)
- resolve #5147 add 'config files' to conda info (#5269)
- use --format=json to parse list of pip packages (#5205)
- resolve #1427 remove starts with '.' environment name constraint (#5284)
- link packages from extracted tarballs when tarball is gone (#5289)
- resolve #2511 accept config information from stdin (#5309)
- resolve #4302 add ability to set map parameters with conda config (#5310)
- resolve #5256 enable conda config --get for all primitive parameters (#5312)
- resolve #1992 add short flag -C for --use-index-cache (#5314)
- resolve #2173 add --quiet option to conda clean (#5313)
- resolve #5358 conda should exec to subcommands, not subprocess (#5359)
- resolve #5411 add 'conda config --write-default' (#5412)
- resolve #5081 make pinned packages optional dependencies (#5414)
- resolve #5430 eliminate current deprecation warnings (#5422)
- resolve #5470 make stdout/stderr capture in python_api customizable (#5471)

- logging simplifications/improvements (#5547, #5578)
- update license information (#5568)
- enable threadpool use for repodata collection by default (#5546, #5587)
- conda info now raises PackagesNotFoundError (#5655)
- index building optimizations (#5776)
- fix #5811 change safety_checks default to 'warn' for conda 4.4 (4.4.0rc1) (#5824)
- add constrained dependencies to conda's own recipe (4.4.0rc1) (#5823)
- clean up parser imports (4.4.0rc2) (#5844)
- resolve #5983 add --download-only flag to create, install, and update (4.4.0rc2) (#5988)
- add ca-certificates and certifi to aggressive_update_packages default (4.4.0rc2) (#5994)
- use environments.txt to list all known environments (4.4.0rc2) (#6313)
- resolve #5417 ensure unlink order is correctly sorted (4.4.0) (#6364)
- resolve #5370 index is only prefix and cache in --offline mode (4.4.0) (#6371)
- reduce redundant sys call during file copying (4.4.0rc3) (#6421)
- enable aggressive_update_packages (4.4.0rc3) (#6392)
- default conda.sh to dash if otherwise can't detect (4.4.0rc3) (#6414)
- canonicalize package names when comparing with pip (4.4.0rc3) (#6438)
- add target prefix override configuration parameter (4.4.0rc3) (#6413)
- resolve #6194 warn when conda is outdated (4.4.0rc3) (#6370)
- add information to displayed error report (4.4.0rc3) (#6437)
- csh wrapper (4.4.0) (#6463)
- resolve #5158 --override-channels (4.4.0) (#6467)
- fish update for conda 4.4 (4.4.0) (#6475, #6502)
- skip an unnecessary environments.txt rewrite (4.4.0) (#6495)

- fix some conda-build compatibility issues (#5089)
- resolve #5123 export toposort (#5124)
- fix #5132 signal handler can only be used in main thread (#5133)
- fix orphaned --clobber parser arg (#5188)
- fix #3814 don't remove directory that's not a conda environment (#5204)
- fix #4468 _license stack trace (#5206)
- fix #4987 conda update --all no longer displays full list of packages (#5228)
- fix #3489 don't error on remove --all if environment doesn't exist (#5231)
- fix #1509 bash doesn't need full path for pre/post link/unlink scripts on unix (#5252)
- fix #462 add regression test (#5286)

- fix #5288 confirmation prompt doesn't accept no (#5291)
- fix #1713 'conda package -w' is case dependent on Windows (#5308)
- fix #5371 try falling back to pip's vendored requests if no requests available (#5372)
- fix #5356 skip root logger configuration (#5380)
- fix #5466 scrambled URL of non-alias channel with token (#5467)
- fix #5444 environment.yml file not found (#5475)
- fix #3200 use proper unbound checks in bash code and test (#5476)
- invalidate PrefixData cache on rm_rf for conda-build (#5491, #5499)
- fix exception when generating JSON output (#5628)
- fix target prefix determination (#5642)
- use proxy to avoid segfaults (#5716)
- fix #5790 incorrect activation message (4.4.0rc1) (#5820)
- fix #5808 assertion error when loading package cache (4.4.0rc1) (#5815)
- fix #5809 _pip_install_via_requirements got an unexpected keyword argument 'prune' (4.4.0rc1) (#5814)
- fix #5811 change safety_checks default to 'warn' for conda 4.4 (4.4.0rc1) (#5824)
- fix #5825 -- json output format (4.4.0rc1) (#5831)
- fix force_reinstall for case when packages aren't actually installed (4.4.0rc1) (#5836)
- fix #5680 empty pip subsection error in environment.yml (4.4.0rc2) (#6275)
- fix #5852 bad tokens from history crash conda installs (4.4.0rc2) (#6076)
- fix #5827 no error message on invalid command (4.4.0rc2) (#6352)
- fix exception handler for 'conda activate' (4.4.0rc2) (#6365)
- fix #6173 double prompt immediately after conda 4.4 upgrade (4.4.0rc2) (#6351)
- fix #6181 keep existing pythons pinned to minor version (4.4.0rc2) (#6363)
- fix #6201 incorrect subdir shown for conda search when package not found (4.4.0rc2) (#6367)
- fix #6045 help message and zsh shift (4.4.0rc3) (#6368)
- fix noarch python package resintall (4.4.0rc3) (#6394)
- fix #6366 shell activation message (4.4.0rc3) (#6369)
- fix #6429 AttributeError on 'conda remove' (4.4.0rc3) (#6434)
- fix #6449 problems with 'conda info --envs' (#6451)
- add debug exception for #6430 (4.4.0rc3) (#6435)
- fix #6441 NotImplementedError on 'conda list' (4.4.0rc3) (#6442)
- fix #6445 scale back directory activation in PWD (4.4.0rc3) (#6447)
- fix #6283 no-deps for conda update case (4.4.0rc3) (#6448)
- fix #6419 set PS1 in python code (4.4.0rc3) (#6446)
- fix #6466 sp_dir doesn't exist (#6470)
- fix #6350 --update-all removes too many packages (4.4.0) (#6491)

• fix #6057 unlink-link order for python noarch packages on windows 4.4.x (4.4.0) (#6494)

Non-User-Facing Changes

- eliminate index modification in Resolve init (#4333)
- new MatchSpec implementation (#4158, #5517)
- update conda.recipe for 4.4 (#5086)
- resolve #5118 organization and cleanup for 4.4 release (#5115)
- remove unused disk space check instructions (#5167)
- localfs adapter tests (#5181)
- extra config command tests (#5185)
- add coverage for confirm (#5203)
- clean up FileNotFoundError and DirectoryNotFoundError (#5237)
- add assertion that a path only has a single hard link before rewriting prefixes (#5305)
- remove pycrypto as requirement on windows (#5326)
- import cleanup, dead code removal, coverage improvements, and other housekeeping (#5472, #5474, #5480)
- rename CondaFileNotFoundError to PathNotFoundError (#5521)
- work toward repodata API (#5267)
- rename PackageNotFoundError to PackagesNotFoundError and fix message formatting (#5602)
- update conda 4.4 bld.bat windows recipe (#5573)
- remove last remnant of CondaEnvRuntimeError (#5643)
- fix typo (4.4.0rc2) (#6043)
- replace Travis-CI with CircleCI (4.4.0rc2) (#6345)
- key-value features (#5645); reverted in 4.4.0rc2 (#6347, #6492)
- resolve #6431 always add env_vars to info_dict (4.4.0rc3) (#6436)
- move shell inside conda directory (4.4.0) (#6479)
- remove dead code (4.4.0) (#6489)

4.4.93 4.3.34 (2018-02-09)

Bug Fixes

• fix #6833 improve feature mismatch metric (#6853)

4.4.94 4.3.33 (2018-01-24)

Bug Fixes

- fix #6718 broken 'conda install --rev' (#6719)
- fix #6765 adjust the feature score assigned to packages not installed (#6766)

4.4.95 4.3.32 (2018-01-10)

Improvements

• resolve #6711 fall back to copy/unlink for EINVAL, EXDEV rename failures (#6712)

Bug Fixes

- fix #6057 unlink-link order for python noarch packages on windows (#6277)
- fix #6509 custom_channels incorrect in 'conda config --show' (#6510)

4.4.96 4.3.31 (2017-12-15)

Improvements

• add delete_trash to conda_env create (#6299)

Bug Fixes

- fix #6023 assertion error for temp file (#6154)
- fix #6220 --no-builds flag for 'conda env export' (#6221)
- fix #6271 timestamp prioritization results in undesirable race-condition (#6279)

Non-User-Facing Changes

- fix two failing integration tests after anaconda.org API change (#6182)
- resolve #6243 mark root as not writable when sys.prefix is not a conda environment (#6274)
- add timing instrumentation (#6458)

4.4.97 4.3.30 (2017-10-17)

Improvements

• address #6056 add additional proxy variables to 'conda info --all' (#6083)

- address #6164 move add_defaults_to_specs after augment_specs (#6172)
- fix #6057 add additional detail for message 'cannot link source that does not exist' (#6082)
- fix #6084 setting default_channels from CLI raises NotImplementedError (#6085)

4.4.98 4.3.29 (2017-10-09)

Bug Fixes

• fix #6096 coerce to millisecond timestamps (#6131)

4.4.99 4.3.28 (2017-10-06)

Bug Fixes

- fix #5854 remove imports of pkg_resources (#5991)
- fix millisecond timestamps (#6001)

4.4.100 4.3.27 (2017-09-18)

Bug Fixes

• fix #5980 always delete_prefix_from_linked_data in rm_rf (#5982)

4.4.101 4.3.26 (2017-09-15)

Deprecations/Breaking Changes

- resolve #5922 prioritize channels within multi-channels (#5923)
- add https://repo.continuum.io/pkgs/main to defaults multi-channel (#5931)

- add a channel priority minimization pass to solver logic (#5859)
- invoke cmd.exe with /D for pre/post link/unlink scripts (#5926)
- add boto3 use to s3 adapter (#5949)

- always remove linked prefix entry with rm_rf (#5846)
- resolve #5920 bump repodata pickle version (#5921)
- fix msys2 activate and deactivate (#5950)

4.4.102 4.3.25 (2017-08-16)

Deprecations/Breaking Changes

• resolve #5834 change default value of 'allow_softlinks' from True to False (#5839)

Improvements

- add non-admin check to optionally disable non-privileged operation (#5724)
- add extra warning message to always_softlink configuration option (#5826)

Bug Fixes

- fix #5763 channel url string splitting error (#5764)
- fix regex for repodata _mod and _etag (#5795)
- fix uncaught OSError for missing device (#5830)

4.4.103 4.3.24 (2017-07-31)

Bug Fixes

• fix #5708 package priority sort order (#5733)

4.4.104 4.3.23 (2017-07-21)

Improvements

• resolve #5391 PackageNotFound and NoPackagesFoundError clean up (#5506)

- fix #5525 too many Nones in CondaHttpError (#5526)
- fix #5508 assertion failure after test file not cleaned up (#5533)
- fix #5523 catch OSError when home directory doesn't exist (#5549)
- fix #5574 traceback formatting (#5580)
- fix #5554 logger configuration levels (#5555)
- fix #5649 create_default_packages configuration (#5703)

4.4.105 4.3.22 (2017-06-12)

Improvements

- resolve #5428 clean up cli import in conda 4.3.x (#5429)
- resolve #5302 add warning when creating environment with space in path (#5477)
- for ftp connections, ignore host IP from PASV as it is often wrong (#5489)
- expose common race condition exceptions in exports for conda-build (#5498)

Bug Fixes

- fix #5451 conda clean --json bug (#5452)
- fix #5400 confusing deactivate message (#5473)
- fix #5459 custom subdir channel parsing (#5478)
- fix #5483 problem with setuptools / pkg_resources import (#5496)

4.4.106 4.3.21 (2017-05-25)

Bug Fixes

- fix #5420 conda-env update error (#5421)
- fix #5425 is admin on win int not callable (#5426)

4.4.107 4.3.20 (2017-05-23)

Improvements

• resolve #5217 skip user confirm in python_api, force always_yes (#5404)

- fix #5367 conda info always shows 'unknown' for admin indicator on Windows (#5368)
- fix #5248 drop plan description information that might not always be accurate (#5373)
- fix #5378 duplicate log messages (#5379)
- fix #5298 record has 'build', not 'build_string' (#5382)
- fix #5384 silence logging info to avoid interfering with JSON output (#5393)
- fix #5356 skip root/conda logger init for cli.python_api (#5405)

Non-User-Facing Changes

- avoid persistent state after channel priority test (#5392)
- resolve #5402 add regression test for #5384 (#5403)
- clean up inner function definition inside for loop (#5406)

4.4.108 4.3.19 (2017-05-18)

Improvements

- resolve #3689 better error messaging for missing anaconda-client (#5276)
- resolve #4795 conda env export lacks -p flag (#5275)
- resolve #5315 add alias verify_ssl for ssl_verify (#5316)
- resolve #3399 add netrc existence/location to 'conda info' (#5333)
- resolve #3810 add --prefix to conda env update (#5335)

Bug Fixes

- fix #5272 conda env export ugliness under python2 (#5273)
- fix #4596 warning message from pip on conda env export (#5274)
- fix #4986 --yes not functioning for conda clean (#5311)
- fix #5329 unicode errors on Windows (#5328, #5357)
- fix sys_prefix_unfollowed for Python 3 (#5334)
- fix #5341 -- json flag with conda-env (#5342)
- fix 5321 ensure variable PROMPT is set in activate.bat (#5351)

Non-User-Facing Changes

- test conda 4.3 with requests 2.14.2 (#5281)
- remove pycrypto as requirement on windows (#5325)
- fix typo avaiable -> available (#5345)
- fix test failures related to menuinst update (#5344, #5362)

4.4.109 4.3.18 (2017-05-09)

- resolve #4224 warn when pysocks isn't installed (#5226)
- resolve #5229 add --insecure flag to skip ssl verification (#5230)
- resolve #4151 add admin indicator to conda info on windows (#5241)

- fix #5152 conda info spacing (#5166)
- fix --use-index-cache actually hitting the index cache (#5134)
- backport LinkPathAction verify from 4.4 (#5171)
- fix #5184 stack trace on invalid map configuration parameter (#5186)
- fix #5189 stack trace on invalid sequence config param (#5192)
- add support for the linux-aarch64 platform (#5190)
- fix repodata fetch with the --offline flag (#5146)
- fix #1773 conda remove spell checking (#5176)
- fix #3470 reduce excessive error messages (#5195)
- fix #1597 make extra sure --dry-run doesn't take any actions (#5201)
- fix #3470 extra newlines around exceptions (#5200)
- fix #5214 install messages for 'nothing_to_do' case (#5216)
- fix #598 stack trace for condarc write permission denied (#5232)
- fix #4960 extra information when exception can't be displayed (#5236)
- fix #4974 no matching dist in linked data for prefix (#5239)
- fix #5258 give correct element types for conda config --describe (#5259)
- fix #4911 separate shutil.copy2 into copy and copystat (#5261)

Non-User-Facing Changes

- resolve #5138 add test of rm_rf of symlinked files (#4373)
- resolve #4516 add extra trace-level logging (#5249, #5250)
- add tests for --update-deps flag (#5264)

4.4.110 4.3.17 (2017-04-24)

- fall back to copy if hardlink fails (#5002)
- add timestamp metadata for tiebreaking conda-build 3 hashed packages (#5018)
- resolve #5034 add subdirs configuration parameter (#5030)
- resolve #5081 make pinned packages optional/constrained dependencies (#5088)
- resolve #5108 improve behavior and add tests for spaces in paths (#4786)

- quote prefix paths for locations with spaces (#5009)
- remove binstar logger configuration overrides (#4989)
- fix #4969 error in DirectoryNotFoundError (#4990)
- fix #4998 pinned string format (#5011)
- fix #5039 collecting main_info shouldn't fail on requests import (#5090)
- fix #5055 improve bad token message for anaconda.org (#5091)
- fix #5033 only re-register valid signal handlers (#5092)
- fix #5028 imports in main_list (#5093)
- fix #5073 allow client_ssl_cert{_key} to be of type None (#5096)
- fix #4671 backoff for package validate race condition (#5098)
- fix #5022 gnu_get_libc_version => linux_get_libc_version (#5099)
- fix #4849 package name match bug (#5103)
- fixes #5102 allow proxy_servers to be of type None (#5107)
- fix #5111 incorrect typify for str + NoneType (#5112)

Non-User-Facing Changes

- resolve #5012 remove CondaRuntimeError and RuntimeError (#4818)
- full audit ensuring relative import paths within project (#5090)
- resolve #5116 refactor conda/cli/activate.py to help menuinst (#4406)

4.4.111 4.3.16 (2017-03-30)

Improvements

- additions to configuration SEARCH_PATH to improve consistency (#4966)
- add 'conda config --describe' and extra config documentation (#4913)
- enable packaging pinning in condarc using pinned_packages config parameter as beta feature (#4921, #4964)

- fix #4914 handle directory creation on top of file paths (#4922)
- fix #3982 issue with CONDA_ENV and using powerline (#4925)
- fix #2611 update instructions on how to source conda.fish (#4924)
- fix #4860 missing information on package not found error (#4935)
- fix #4944 command not found error error (#4963)

4.4.112 4.3.15 (2017-03-20)

Improvements

• allow pkgs_dirs to be configured using conda config (#4895)

Bug Fixes

- remove incorrect elision of delete_prefix_from_linked_data() (#4814)
- fix envs_dirs order for read-only root prefix (#4821)
- fix break-point in conda clean (#4801)
- fix long shebangs when creating entry points (#4828)
- fix spelling and typos (#4868, #4869)
- fix #4840 TypeError reduce() of empty sequence with no initial value (#4843)
- fix zos subdir (#4875)
- fix exceptions triggered during activate (#4873)

4.4.113 4.3.14 (2017-03-03)

Improvements

- use cPickle in place of pickle for repodata (#4717)
- ignore pyc compile failure (#4719)
- use conda.exe for windows entry point executable (#4716, #4720)
- localize use of conda_signal_handler (#4730)
- add skip_safety_checks configuration parameter (#4767)
- never symlink executables using ORIGIN (#4625)
- set activate.bat codepage to CP_ACP (#4558)

- fix #4777 package cache initialization speed (#4778)
- fix #4703 menuinst PathNotFoundException (#4709)
- ignore permissions error if user_site can't be read (#4710)
- fix #4694 don't import requests directly in models (#4711)
- fix #4715 include resources directory in recipe (#4716)
- fix CondaHttpError for URLs that contain '%' (#4769)
- bug fixes for preferred envs (#4678)
- fix #4745 check for info/index.json with package is_extracted (#4776)
- make sure url gets included in CondaHTTPError (#4779)

- fix #4757 map-type configs set to None (#4774)
- fix #4788 partial package extraction (#4789)

Non-User-Facing Changes

- test coverage improvement (#4607)
- CI configuration improvements (#4713, #4773, #4775)
- allow sha256 to be None (#4759)
- add cache_fn_url to exports (#4729)
- add unicode paths for PY3 integration tests (#4760)
- additional unit tests (#4728, #4783)
- fix conda-build compatibility and tests (#4785)

4.4.114 4.3.13 (2017-02-17)

Improvements

- resolve #4636 environment variable expansion for pkgs_dirs (#4637)
- link, symlink, islink, and readlink for Windows (#4652, #4661)
- add extra information to CondaHTTPError (#4638, #4672)

Bug Fixes

- maximize requested builds after feature determination (#4647)
- fix #4649 incorrect assert statement concerning package cache directory (#4651)
- multi-user mode bug fixes (#4663)

Non-User-Facing Changes

- path_actions unit tests (#4654)
- remove dead code (#4369, #4655, #4660)
- separate repodata logic from index into a new core/repodata.py module (#4669)

4.4.115 4.3.12 (2017-02-14)

- prepare conda for uploading to pypi (#4619)
- better general http error message (#4627)
- disable old python noarch warning (#4576)

- fix UnicodeDecodeError for ensure_text_type (#4585)
- fix determination of if file path is writable (#4604)
- fix #4592 BufferError cannot close exported pointers exist (#4628)
- fix run_script current working directory (#4629)
- fix pkgs_dirs permissions regression (#4626)

Non-User-Facing Changes

- fixes for tests when conda-bld directory doesn't exist (#4606)
- use requirements.txt and Makefile for travis-ci setup (#4600, #4633)
- remove hasattr use from compat functions (#4634)

4.4.116 4.3.11 (2017-02-09)

Bug Fixes

• fix attribute error in add_defaults_to_specs (#4577)

4.4.117 4.3.10 (2017-02-07)

Improvements

- remove .json from pickle path (#4498)
- improve empty repodata noarch warning and error messages (#4499)
- don't add python and lua as default specs for private envs (#4529, #4533)
- let default_python be None (#4547, #4550)

- fix #4513 null pointer exception for channel without noarch (#4518)
- fix ssl_verify set type (#4517)
- fix bug for windows multiuser (#4524)
- fix clone with noarch python packages (#4535)
- fix ipv6 for python 2.7 on Windows (#4554)

Non-User-Facing Changes

• separate integration tests with a marker (#4532)

4.4.118 4.3.9 (2017-01-31)

Improvements

- improve repodata caching for performance (#4478, #4488)
- expand scope of packages included by bad_installed (#4402)
- silence pre-link warning for old noarch (#4451)
- add configuration to optionally require noarch repodata (#4450)
- improve conda subprocessing (#4447)
- respect info/link.json (#4482)

Bug Fixes

- fix #4398 'hard' was used for link type at one point (#4409)
- fixed "No matches for wildcard '\$activate_d/*.fish" warning (#4415)
- print correct activate/deactivate message for fish shell (#4423)
- fix 'Dist' object has no attribute 'fn' (#4424)
- fix noarch generic and add additional integration test (#4431)
- fix #4425 unknown encoding (#4433)

Non-User-Facing Changes

- fail CI on conda-build fail (#4405)
- run doctests (#4414)
- make index record mutable again (#4461)
- additional test for conda list -- json (#4480)

4.4.119 4.3.8 (2017-01-23)

- fix #4309 ignore EXDEV error for directory renames (#4392)
- fix #4393 by force-renaming certain backup files if the path already exists (#4397)

4.4.120 4.3.7 (2017-01-20)

Bug Fixes

- actually revert json output for leaky plan (#4383)
- fix not raising on pre/post-link error (#4382)
- fix find_commands and find_executable for symlinks (#4387)

4.4.121 4.3.6 (2017-01-18)

Bug Fixes

- fix 'Uncaught backoff with errno 41' warning on windows (#4366)
- revert json output for leaky plan (#4349)
- audit os.environ setting (#4360)
- fix #4324 using old dist string instead of dist object (#4361)
- fix #4351 infinite recursion via code in #4120 (#4370)
- fix #4368 conda -h (#4367)
- workaround for symlink race conditions on activate (#4346)

4.4.122 4.3.5 (2017-01-17)

Improvements

• add exception message for corrupt repodata (#4315)

- fix package not being found in cache after download (#4297)
- fix logic for Content-Length mismatch (#4311, #4326)
- use unicode_escape after etag regex instead of utf-8 (#4325)
- fix #4323 central condarc file being ignored (#4327)
- fix #4316 a bug in deactivate (#4316)
- pass target_prefix as env_prefix regardless of is_unlink (#4332)
- pass positional argument 'context' to BasicClobberError (#4335)

Non-User-Facing Changes

• additional package pinning tests (#4317)

4.4.123 4.3.4 (2017-01-13)

Improvements

• vendor url parsing from urllib3 (#4289)

Bug Fixes

- fix some bugs in windows multi-user support (#4277)
- fix problems with channels of type (#4290)
- include aliases for first command-line argument (#4279)
- fix for multi-line FTP status codes (#4276)

Non-User-Facing Changes

- make arch in IndexRecord a StringField instead of EnumField
- improve conda-build compatibility (#4266)

4.4.124 4.3.3 (2017-01-10)

Improvements

- respect Cache-Control max-age header for repodata (#4220)
- add 'local_repodata_ttl' configurability (#4240)
- remove questionable "nothing to install" logic (#4237)
- relax channel noarch requirement for 4.3; warn now, raise in future feature release (#4238)
- add additional info to setup.py warning message (#4258)

- remove features properly (#4236)
- do not use IFS to find activate/deactivate scripts to source (#4239)
- fix #4235 print message to stderr (#4241)
- fix relative path to python in activate.bat (#4242)
- fix args.channel references (#4245, #4246)
- ensure cache_fn_url right pad (#4255)
- fix #4256 subprocess calls must have env wrapped in str (#4259)

4.4.125 4.3.2 (2017-01-06)

Deprecations/Breaking Changes

• Further refine conda channels specification. To verify if the url of a channel represents a valid conda channel, we check that noarch/repodata.json and/or noarch/repodata.json.bz2 exist, even if empty. (#3739)

Improvements

- add new 'path_conflict' and 'clobber' configuration options (#4119)
- separate fetch/extract pass for explicit URLs (#4125)
- update conda homepage to conda.io (#4180)

Bug Fixes

- fix pre/post unlink/link scripts (#4113)
- fix package version regex and bug in create_link (#4132)
- fix history tracking (#4143)
- fix index creation order (#4131)
- fix #4152 conda env export failure (#4175)
- fix #3779 channel UNC path encoding errors on windows (#4190)
- fix progress bar (#4191)
- use context.channels instead of args.channel (#4199)
- don't use local cached repodata for file:// urls (#4209)

Non-User-Facing Changes

- xfail anaconda token test if local token is found (#4124)
- fix open-ended test failures relating to python 3.6 release (#4145)
- extend timebomb for test_multi_channel_export (#4169)
- don't unlink dists that aren't in the index (#4130)
- add python 3.6 and new conda-build test targets (#4194)

4.4.126 4.3.1 (2016-12-19)

- additional pre-transaction validation (#4090)
- export FileMode enum for conda-build (#4080)
- memoize disk permissions tests (#4091)
- local caching of repodata without remote server calls; new 'repodata_timeout_secs' configuration parameter (#4094)

- performance tuning (#4104)
- add additional fields to dist object serialization (#4102)

- fix a noarch install bug on windows (#4071)
- fix a spec mismatch that resulted in python versions getting mixed during packaging (#4079)
- fix rollback linked record (#4092)
- fix #4097 keep split in PREFIX_PLACEHOLDER (#4100)

4.4.127 4.3.0 (2016-12-14) Safety

New Features

- Unlink and Link Packages in a Single Transaction: In the past, conda hasn't always been safe and defensive with its disk-mutating actions. It has gleefully clobbered existing files, and mid-operation failures leave environments completely broken. In some of the most severe examples, conda can appear to "uninstall itself." With this release, the unlinking and linking of packages for an executed command is done in a single transaction. If a failure occurs for any reason while conda is mutating files on disk, the environment will be returned its previous state. While we've implemented some pre-transaction checks (verifying package integrity for example), it's impossible to anticipate every failure mechanism. In some circumstances, OS file permissions cannot be fully known until an operation is attempted and fails. And conda itself is not without bugs. Moving forward, unforeseeable failures won't be catastrophic. (#3833, #4030)
- **Progressive Fetch and Extract Transactions**: Like package unlinking and linking, the download and extract phases of package handling have also been given transaction-like behavior. The distinction is the rollback on error is limited to a single package. Rather than rolling back the download and extract operation for all packages, the single-package rollback prevents the need for having to re-download every package if an error is encountered. (#4021, #4030)
- Generic- and Python-Type Noarch/Universal Packages: Along with conda-build 2.1.0, a noarch/universal type for python packages is officially supported. These are much like universal python wheels. Files in a python noarch package are linked into a prefix just like any other conda package, with the following additional features
 - 1. conda maps the site-packages directory to the correct location for the python version in the environment,
 - 2. conda maps the python-scripts directory to either *PREFIX/binor***PREFIX/Scripts** depending on platform,
 - 3. conda creates the python entry points specified in the conda-build recipe, and
 - 4. conda compiles pyc files at install time when prefix write permissions are guaranteed.

Python noarch packages must be "fully universal." They cannot have OS- or python version-specific dependencies. They cannot have OS- or python version-specific "scripts" files. If these features are needed, traditional conda packages must be used. (#3712)

- **Multi-User Package Caches**: While the on-disk package cache structure has been preserved, the core logic implementing package cache handling has had a complete overhaul. Writable and read-only package caches are fully supported. (#4021)
- **Python API Module**: An oft requested feature is the ability to use conda as a python library, obviating the need to "shell out" to another python process. Conda 4.3 includes a conda.cli.python_api module that facilitates this use case. While we maintain the user-facing command-line interface, conda commands can be executed in-process. There is also a conda.exports module to facilitate longer-term usage of conda as a library across

conda conda releases. However, conda's python code *is* considered internal and private, subject to change at any time across releases. At the moment, conda will not install itself into environments other than its original install environment. (#4028)

• **Remove All Locks**: Locking has never been fully effective in conda, and it often created a false sense of security. In this release, multi-user package cache support has been implemented for improved safety by hard-linking packages in read-only caches to the user's primary user package cache. Still, users are cautioned that undefined behavior can result when conda is running in multiple process and operating on the same package caches and/or environments. (#3862)

Deprecations/Breaking Changes

- Conda will refuse to clobber existing files that are not within the unlink instructions of the transaction. At the risk of being user-hostile, it's a step forward for conda. We do anticipate some growing pains. For example, conda will not clobber packages that have been installed with pip (or any other package manager). In other instances, conda packages that contain overlapping file paths but are from different package families will not install at the same time. The --force command line flag is the escape hatch. Using --force will let your operation proceed, but also makes clear that you want conda to do something it considers unsafe.
- Conda signed packages have been removed in 4.3. Vulnerabilities existed. An illusion of security is worse than not having the feature at all. We will be incorporating The Update Framework into conda in a future feature release. (#4064)
- Conda 4.4 will drop support for older versions of conda-build.

- create a new "trace" log level enabled by -v -v or -vvv (#3833)
- allow conda to be installed with pip, but only when used as a library/dependency (#4028)
- the 'r' channel is now part of defaults (#3677)
- private environment support for conda (#3988)
- support v1 info/paths.json file (#3927, #3943)
- support v1 info/package_metadata.json (#4030)
- improved solver hint detection, simplified filtering (#3597)
- cache VersionOrder objects to improve performance (#3596)
- fix documentation and typos (#3526, #3572, #3627)
- add multikey configuration validation (#3432)
- some Fish autocompletions (#2519)
- reduce priority for packages removed from the index (#3703)
- add user-agent, uid, gid to conda info (#3671)
- add conda.exports module (#3429)
- make http timeouts configurable (#3832)
- add a pkgs_dirs config parameter (#3691)
- add an 'always_softlink' option (#3870, #3876)
- pre-checks for diskspace, etc for fetch and extract #(4007)

- address #3879 don't print activate message when quiet config is enabled (#3886)
- add zos-z subdir (#4060)
- add elapsed time to HTTP errors (#3942)

- account for the Windows Python 2.7 os.environ unicode aversion (#3363)
- fix link field in record object (#3424)
- anaconda api token bug fix; additional tests (#3673)
- fix #3667 unicode literals and unicode decode (#3682)
- add conda-env entrypoint (#3743)
- fix #3807 json dump on conda config --show --json (#3811)
- fix #3801 location of temporary hard links of index.json (#3813)
- fix invalid yml example (#3849)
- add arm platforms back to subdirs (#3852)
- fix #3771 better error message for assertion errors (#3802)
- fix #3999 spaces in shebang replacement (#4008)
- config --show-sources shouldn't show force by default (#3891)
- fix #3881 don't install conda-env in clones of root (#3899)
- conda-build dist compatibility (#3909)

- remove unnecessary eval (#3428)
- remove dead install_tar function (#3641)
- apply PEP-8 to conda-env (#3653)
- refactor dist into an object (#3616)
- vendor appdirs; remove conda's dependency on anaconda-client import (#3675)
- revert boto patch from #2380 (#3676)
- move and update ROOT_NO_RM (#3697)
- integration tests for conda clean (#3695, #3699)
- disable coverage on s3 and ftp requests adapters (#3696, #3701)
- github repo hygiene (#3705, #3706)
- major install refactor (#3712)
- remove test timebombs (#4012)
- LinkType refactor (#3882)
- move CrossPlatformStLink and make available as export (#3887)
- make Record immutable (#3965)

- project housekeeping (#3994, #4065)
- context-dependent setup.py files (#4057)

4.4.128 4.2.17 (unreleased)

Improvements

• silence pre-link warning for old noarch 4.2.x backport (#4453)

Bug Fixes

- remove incorrect elision of delete_prefix_from_linked_data() (#4813)
- fix CB #1825 context clobbering (#4867)
- fix #5101 api->conda regex substitution for Anaconda API channels (#5100)

Non-User-Facing Changes

• build 4.2.x against conda-build 2.1.2 and enforce passing (#4462)

4.4.129 4.2.16 (2017-01-20)

Improvements

- vendor url parsing from urllib3 (#4289)
- workaround for symlink race conditions on activate (#4346)

Bug Fixes

- do not replace \ with / in file:// URLs on Windows (#4269)
- include aliases for first command-line argument (#4279)
- fix for multi-line FTP status codes (#4276)
- fix errors with unknown type channels (#4291)
- change sys.exit to raise UpgradeError when info/files not found (#4388)

- start using doctests in test runs and coverage (#4304)
- additional package pinning tests (#4312)

4.4.130 4.2.15 (2017-01-10)

Improvements

- use 'post' instead of 'dev' for commits according to PEP-440 (#4234)
- do not use IFS to find activate/deactivate scripts to source (#4243)
- fix relative path to python in activate.bat (#4244)

Bug Fixes

• replace sed with python for activate and deactivate #4257

4.4.131 4.2.14 (2017-01-07)

Improvements

- use install.rm_rf for TemporaryDirectory cleanup (#3425)
- improve handling of local dependency information (#2107)
- add default channels to exports for Windows and Unix (#4103)
- make subdir configurable (#4178)

Bug Fixes

- fix conda/install.py single-file behavior (#3854)
- fix the api->conda substitution (#3456)
- fix silent directory removal (#3730)
- fix location of temporary hard links of index.json (#3975)
- fix potential errors in multi-channel export and offline clone (#3995)
- fix auxlib/packaging, git hashes are not limited to 7 characters (#4189)
- fix compatibility with requests >=2.12, add pyopenssl as dependency (#4059)
- fix #3287 activate in 4.1-4.2.3 clobbers non-conda PATH changes (#4211)

- fix open-ended test failures relating to python 3.6 release (#4166)
- allow args passed to cli.main() (#4193, #4200, #4201)
- test against python 3.6 (#4197)

4.4.132 4.2.13 (2016-11-22)

Deprecations/Breaking Changes

- show warning message for pre-link scripts (#3727)
- error and exit for install of packages that require conda minimum version 4.3 (#3726)

Improvements

- double/extend http timeouts (#3831)
- let descriptive http errors cover more http exceptions (#3834)
- backport some conda-build configuration (#3875)

Bug Fixes

- fix conda/install.py single-file behavior (#3854)
- fix the api->conda substitution (#3456)
- fix silent directory removal (#3730)
- fix #3910 null check for is_url (#3931)

Non-User-Facing Changes

• flake8 E116, E121, & E123 enabled (#3883)

4.4.133 4.2.12 (2016-11-02)

Bug Fixes

- fix #3732, #3471, #3744 CONDA_BLD_PATH (#3747)
- fix #3717 allow no-name channels (#3748)
- fix #3738 move conda-env to ruamel_yaml (#3740)
- fix conda-env entry point (#3745 via #3743)
- fix again #3664 trash emptying (#3746)

4.4.134 4.2.11 (2016-10-23)

Improvements

• only try once for windows trash removal (#3698)

- fix anaconda api token bug (#3674)
- fix #3646 FileMode enum comparison (#3683)
- fix #3517 conda install --mkdir (#3684)
- fix #3560 hack anaconda token coverup on conda info (#3686)
- fix #3469 alias envs_path to envs_dirs (#3685)

4.4.135 4.2.10 (2016-10-18)

Improvements

- add json output for conda info -s (#3588)
- ignore certain binary prefixes on windows (#3539)
- allow conda config files to have .yaml extensions or 'condarc' anywhere in filename (#3633)

Bug Fixes

- fix conda-build's handle_proxy_407 import (#3666)
- fix #3442, #3459, #3481, #3531, #3548 multiple networking and auth issues (#3550)
- add back linux-ppc64le subdir support (#3584)
- fix #3600 ensure links are removed when unlinking (#3625)
- fix #3602 search channels by platform (#3629)
- fix duplicated packages when updating environment (#3563)
- fix #3590 exception when parsing invalid yaml (#3593 via #3634)
- fix #3655 a string decoding error (#3656)

Non-User-Facing Changes

- backport conda.exports module to 4.2.x (#3654)
- travis-ci OSX fix (#3615 via #3657)

4.4.136 4.2.9 (2016-09-27)

- fix #3536 conda-env messaging to stdout with --json flag (#3537)
- fix #3525 writing to sys.stdout with --json flag for post-link scripts (#3538)
- fix #3492 make NULL falsey with python 3 (#3524)

4.4.137 4.2.8 (2016-09-26)

Improvements

• add "error" key back to json error output (#3523)

Bug Fixes

- fix #3453 conda fails with create_default_packages (#3454)
- fix #3455 --dry-run fails (#3457)
- dial down error messages for rm_rf (#3522)
- fix #3467 AttributeError encountered for map config parameter validation (#3521)

4.4.138 4.2.7 (2016-09-16)

Deprecations/Breaking Changes

• revert to 4.1.x behavior of conda list --export (#3450, #3451)

Bug Fixes

- don't add binstar token if it's given in the channel spec (#3427, #3440, #3444)
- fix #3433 failure to remove broken symlinks (#3436)

Non-User-Facing Changes

• use install.rm_rf for TemporaryDirectory cleanup (#3425)

4.4.139 4.2.6 (2016-09-14)

Improvements

- add support for client TLS certificates (#3419)
- address #3267 allow migration of channel_alias (#3410)
- conda-env version matches conda version (#3422)

- fix #3409 unsatisfiable dependency error message (#3412)
- fix #3408 quiet rm_rf (#3413)
- fix #3407 padding error messaging (#3416)
- account for the Windows Python 2.7 os.environ unicode aversion (#3363 via #3420)

4.4.140 4.2.5 (2016-09-08)

Deprecations/Breaking Changes

- partially revert #3041 giving conda config --add previous --prepend behavior (#3364 via #3370)
- partially revert #2760 adding back conda package command (#3398)

Improvements

- order output of conda config --show; make --json friendly (#3384 via #3386)
- clean the pid based lock on exception (#3325)
- improve file removal on all platforms (#3280 via #3396)

Bug Fixes

- fix #3332 allow download urls with :: in them (#3335)
- fix always_yes and not-set argparse args overriding other sources (#3374)
- fix ftp fetch timeout (#3392)
- fix #3307 add try/except block for touch lock (#3326)
- fix CONDA_CHANNELS environment variable splitting (#3390)
- fix #3378 CONDA_FORCE_32BIT environment variable (#3391)
- make conda info channel urls actually give urls (#3397)
- fix cio_test compatibility (#3395 via #3400)

4.4.141 4.2.4 (2016-08-18)

- fix #3277 conda list package order (#3278)
- fix channel priority issue with duplicated channels (#3283)
- fix local channel channels; add full conda-build unit tests (#3281)
- fix conda install with no package specified (#3284)
- fix #3253 exporting and importing conda environments (#3286)
- fix priority messaging on conda config --get (#3304)
- fix conda list --export; additional integration tests (#3291)
- fix conda update --all idempotence; add integration tests for channel priority (#3306)

Non-User-Facing Changes

• additional conda-env integration tests (#3288)

4.4.142 4.2.3 (2016-08-11)

Improvements

• added zsh and zsh.exe to Windows shells (#3257)

Bug Fixes

- allow conda to downgrade itself (#3273)
- fix breaking changes to conda-build from 4.2.2 (#3265)
- fix empty environment issues with conda and conda-env (#3269)

Non-User-Facing Changes

- add integration tests for conda-env (#3270)
- add more conda-build smoke tests (#3274)

4.4.143 4.2.2 (2016-08-09)

Improvements

- enable binary prefix replacement on windows (#3262)
- add --verbose command line flag (#3237)
- improve logging and exception detail (#3237, #3252)
- do not remove empty environment without asking; raise an error when a named environment can't be found (#3222)

- fix #3226 user condarc not available on Windows (#3228)
- fix some bugs in conda config --show* (#3212)
- fix conda-build local channel bug (#3202)
- remove subprocess exiting message (#3245)
- fix comment parsing and channels in conda-env environment.yml (#3258, #3259)
- fix context error with conda-env (#3232)
- fix #3182 conda install silently skipping failed linking (#3184)

4.4.144 4.2.1 (2016-08-01)

Improvements

- improve an error message that can happen during conda install --revision (#3181)
- use clean sys.exit with user choice 'No' (#3196)

Bug Fixes

- critical fix for 4.2.0 error when no git is on PATH (#3193)
- revert #3171 lock cleaning on exit pending further refinement
- patches for conda-build compatibility with 4.2 (#3187)
- fix a bug in --show-sources output that ignored aliased parameter names (#3189)

Non-User-Facing Changes

• move scripts in bin to shell directory (#3186)

4.4.145 4.2.0 (2016-07-28) Configuration

New Features

- New Configuration Engine: Configuration and "operating context" are the foundation of conda's functionality. Conda now has the ability to pull configuration information from a multitude of on-disk locations, including .d directories and a .condarc file *within* a conda environment), along with full CONDA_ environment variable support. Helpful validation errors are given for improperly-specified configuration. Full documentation updates pending. (#2537, #3160, #3178)
- New Exception Handling Engine: Previous releases followed a pattern of premature exiting (with hard calls to sys.exit() when exceptional circumstances were encountered. This release replaces over 100 sys.exit calls with python exceptions. For conda developers, this will result in tests that are easier to write. For developers using conda, this is a first step on a long path toward conda being directly importable. For conda users, this will eventually result in more helpful and descriptive errors messages. (#2899, #2993, #3016, #3152, #3045)
- Empty Environments: Conda can now create "empty" environments when no initial packages are specified, alleviating a common source of confusion. (#3072, #3174)
- **Conda in Private Env**: Conda can now be configured to live within its own private environment. While it's not yet default behavior, this represents a first step toward separating the root environment into a "conda private" environment and a "user default" environment. (#3068)
- Regex Version Specification: Regular expressions are now valid version specifiers. For example, ^1\.[5-8]\.1\$|2.2. (#2933)

Deprecations/Breaking Changes

- remove conda init (#2759)
- remove conda package and conda bundle (#2760)
- deprecate conda-env repo; pull into conda proper (#2950, #2952, #2954, #3157, #3163, #3170)
- force use of ruamel_yaml (#2762)
- implement conda config --prepend; change behavior of --add to --append (#3041)
- exit on link error instead of logging it (#2639)

Improvements

- improve locking (#2962, #2989, #3048, #3075)
- clean up requests usage for fetching packages (#2755)
- remove excess output from conda --help (#2872)
- remove os.remove in update_prefix (#3006)
- better error behavior if conda is spec'd for a non-root environment (#2956)
- scale back try_write function on unix (#3076)

Bug Fixes

- remove psutil requirement, fixes annoying error message (#3135, #3183)
- fix #3124 add threading lock to memoize (#3134)
- fix a failure with multi-threaded repodata downloads (#3078)
- fix windows file url (#3139)
- address #2800, error with environment.yml and non-default channels (#3164)

- project structure enhancement (#2929, #3132, #3133, #3136)
- clean up channel handling with new channel model (#3130, #3151)
- add Anaconda Cloud / Binstar auth handler (#3142)
- remove dead code (#2761, #2969)
- code refactoring and additional tests (#3052, #3020)
- remove auxlib from project root (#2931)
- vendor auxlib 0.0.40 (#2932, #2943, #3131)
- vendor toolz 0.8.0 (#2994)
- move progressbar to vendor directory (#2951)
- fix conda.recipe for new quirks with conda-build (#2959)
- move captured function to common module (#3083)

• rename CHANGELOG to md (#3087)

4.4.146 4.1.13 (unreleased)

- improve handling of local dependency information, #2107
- show warning message for pre-link scripts, #3727
- error and exit for install of packages that require conda minimum version 4.3, #3726
- fix conda/install.py single-file behavior, #3854
- fix open-ended test failures relating to python 3.6 release, #4167
- fix #3287 activate in 4.1-4.2.3 clobbers non-conda PATH changes, #4211
- fix relative path to python in activate.bat, #4244

4.4.147 4.1.12 (2016-09-08)

- fix #2837 "File exists" in symlinked path with parallel activations, #3210
- fix prune option when installing packages, #3354
- change check for placeholder to be more friendly to long PATH, #3349

4.4.148 4.1.11 (2016-07-26)

- fix PS1 backup in activate script, #3135 via #3155
- correct resolution for 'handle failures in binstar_client more generally', #3156

4.4.149 4.1.10 (2016-07-25)

- ignore symlink failure because of read-only file system, #3055
- backport shortcut tests, #3064
- fix #2979 redefinition of \$SHELL variable, #3081
- fix #3060 --clone root --copy exception, #3080

4.4.150 4.1.9 (2016-07-20)

- fix #3104, add global BINSTAR_TOKEN_PAT
- · handle failures in binstar_client more generally

4.4.151 4.1.8 (2016-07-12)

- fix #3004 UNAUTHORIZED for url (null binstar token), #3008
- fix overwrite existing redirect shortcuts when symlinking envs, #3025
- partially revert no default shortcuts, #3032, #3047

4.4.152 4.0.11 2016-07-09

• allow auto_update_conda from sysrc, #3015 via #3021

4.4.153 4.1.7 (2016-07-07)

- add msys2 channel to defaults on Windows, #2999
- fix #2939 channel_alias issues; improve offline enforcement, #2964
- fix #2970, #2974 improve handling of file:// URLs inside channel, #2976

4.4.154 4.1.6 (2016-07-01)

- slow down exp backoff from 1 ms to 100 ms factor, #2944
- set max time on exp_backoff to ~6.5 sec,#2955
- fix #2914 add/subtract from PATH; kill folder output text, #2917
- normalize use of get_index behavior across clone/explicit, #2937
- wrap root prefix check with normcase, #2938

4.4.155 4.1.5 (2016-06-29)

- more conservative auto updates of conda #2900
- fix some permissions errors with more aggressive use of move_path_to_trash, #2882
- fix #2891 error if allow_other_channels setting is used, #2896
- fix #2886, #2907 installing a tarball directly from the package cache, #2908
- fix #2681, #2778 reverting #2320 lock behavior changes, #2915

4.4.156 4.0.10 (2016-06-29)

- fix #2846 revert the use of UNC paths; shorten trash filenames, #2859 via #2878
- fix some permissions errors with more aggressive use of move_path_to_trash, #2882 via #2894
4.4.157 4.1.4 (2016-06-27)

- fix #2846 revert the use of UNC paths; shorten trash filenames, #2859
- fix exp backoff on Windows, #2860
- fix #2845 URL for local file repos, #2862
- fix #2764 restore full path var on win; create to CONDA_PREFIX env var, #2848
- fix #2754 improve listing pip installed packages, #2873
- change root prefix detection to avoid clobbering root activate scripts, #2880
- address #2841 add lowest and highest priority indication to channel config output, #2875
- add SYMLINK_CONDA to planned instructions, #2861
- use CONDA_PREFIX, not CONDA_DEFAULT_ENV for activate.d, #2856
- call scripts with redirect on win; more error checking to activate, #2852

4.4.158 4.1.3 (2016-06-23)

- ensure conda-env auto update, along with conda, #2772
- make yaml booleans behave how everyone expects them to, #2784
- use accept-encoding for repodata; prefer repodata.json to repodata.json.bz2, #2821
- additional integration and regression tests, #2757, #2774, #2787
- add offline mode to printed info; use offline flag when grabbing channels, #2813
- show conda-env version in conda info, #2819
- adjust channel priority superseded list, #2820
- support epoch ! characters in command line specs, #2832
- accept old default names and new ones when canonicalizing channel URLs #2839
- push PATH, PS1 manipulation into shell scripts, #2796
- fix #2765 broken source activate without arguments, #2806
- fix standalone execution of install.py, #2756
- fix #2810 activating conda environment broken with git bash on Windows, #2795
- fix #2805, #2781 handle both file-based channels and explicit file-based URLs, #2812
- fix #2746 conda create --clone of root, #2838
- fix #2668, #2699 shell recursion with activate #2831

4.4.159 4.1.2 (2016-06-17)

- improve messaging for "downgrades" due to channel priority, #2718
- support conda config channel append/prepend, handle duplicates, #2730
- remove --shortcuts option to internal CLI code, #2723
- fix an issue concerning space characters in paths in activate.bat, #2740
- fix #2732 restore yes/no/on/off for booleans on the command line, #2734
- fix #2642 tarball install on Windows, #2729
- fix #2687, #2697 WindowsError when creating environments on Windows, #2717
- fix #2710 link instruction in conda create causes TypeError, #2715
- revert #2514, #2695, disabling of .netrc files, #2736
- revert #2281 printing progress bar to terminal, #2707

4.4.160 4.1.1 (2016-06-16)

- add auto_update_conda config parameter, #2686
- fix #2669 conda config --add channels can leave out defaults, #2670
- fix #2703 ignore activate symlink error if links already exist, #2705
- fix #2693 install duplicate packages with older version of Anaconda, #2701
- fix #2677 respect HTTP_PROXY, #2695
- fix #2680 broken fish integration, #2685, #2694
- fix an issue with conda never exiting, #2689
- fix #2688 explicit file installs, #2708
- fix #2700 conda list UnicodeDecodeError, #2706

4.4.161 4.0.9 (2016-06-15)

• add auto_update_conda config parameter, #2686

4.4.162 4.1.0 (2016-06-14) Channel Priority

- clean up activate and deactivate scripts, moving back to conda repo, #1727, #2265, #2291, #2473, #2501, #2484
- replace pyyaml with ruamel_yaml, #2283, #2321
- better handling of channel collisions, #2323, #2369 #2402, #2428
- improve listing of pip packages with conda list, #2275
- re-license progressbar under BSD 3-clause, #2334
- reduce the amount of extraneous info in hints, #2261
- add --shortcuts option to install shortcuts on windows, #2623
- skip binary replacement on windows, #2630

- don't show channel urls by default in conda list, #2282
- package resolution and solver tweaks, #2443, #2475, #2480
- improved version & build matching, #2442, #2488
- print progress to the terminal rather than stdout, #2281
- verify version specs given on command line are valid, #2246
- fix for try_write function in case of odd permissions, #2301
- fix a conda search --spec error, #2343
- update User-Agent for conda connections, #2347
- remove some dead code paths, #2338, #2374
- fixes a thread safety issue with http requests, #2377, #2383
- manage BeeGFS hard-links non-POSIX configuration, #2355
- prevent version downgrades during removes, #2394
- fix conda info -- json, #2445
- truncate shebangs over 127 characters using /usr/bin/env, #2479
- extract packages to a temporary directory then rename, #2425, #2483
- fix help in install, #2460
- fix re-install bug when sha1 differs, #2507
- fix a bug with file deletion, #2499
- disable .netrc files, #2514
- dont fetch index on remove --all, #2553
- allow track_features to be a string or a list in .condarc, #2541
- fix #2415 infinite recursion in invalid_chains, #2566
- allow channel_alias to be different than binstar, #2564

4.4.163 4.0.8 (2016-06-03)

• fix a potential problem with moving files to trash, #2587

4.4.164 4.0.7 (2016-05-26)

• workaround for boto bug, #2380

4.4.165 4.0.6 (2016-05-11)

- log "custom" versions as updates rather than downgrades, #2290
- fixes a TypeError exception that can occur on install/update, #2331
- fixes an error on Windows removing files with long path names, #2452

4.4.166 4.0.5 (2016-03-16)

- improved help documentation for install, update, and remove, #2262
- fixes #2229 and #2250 related to conda update errors on Windows, #2251
- fixes #2258 conda list for pip packages on Windows, #2264

4.4.167 4.0.4 (2016-03-10)

• revert #2217 closing request sessions, #2233

4.4.168 4.0.3 (2016-03-10)

- adds a conda clean --all feature, #2211
- solver performance improvements, #2209
- fixes conda list for pip packages on windows, #2216
- quiets some logging for package downloads under python 3, #2217
- more urls for conda list --explicit, #1855
- prefer more "latest builds" for more packages, #2227
- fixes a bug with dependency resolution and features, #2226

4.4.169 4.0.2 (2016-03-08)

- fixes track_features in ~/.condarc being a list, see also #2203
- fixes incorrect path in lock file error #2195
- fixes issues with cloning environments, #2193, #2194
- fixes a strange interaction between features and versions, #2206
- fixes a bug in low-level SAT clause generation creating a preference for older versions, #2199

4.4.170 4.0.1 (2016-03-07)

- fixes an install issue caused by md5 checksum mismatches, #2183
- remove auxlib build dependency, #2188

4.4.171 4.0.0 (2016-03-04) Solver

- The solver has been retooled significantly. Performance should be improved in most circumstances, and a number of issues involving feature conflicts should be resolved.
- conda update <package> now handles dependencies properly according to the setting of the "update_deps" configuration: -update-deps: conda will also update any dependencies as needed to install the latest version of the requested packages. The minimal set of changes required to achieve this is sought. -no-update-deps: conda will update the packages *only* to the extent that no updates to the dependencies are required The previous behavior, which would update the packages without regard to their dependencies, could result in a broken configuration, and has been removed.
- Conda finally has an official logo.
- Fix conda clean --packages on Windows, #1944
- Conda sub-commands now support dashes in names, #1840

4.4.172 3.19.4 (unreleased)

- improve handling of local dependency information, #2107
- use install.rm_rf for TemporaryDirectory cleanup, #3425
- fix the api->conda substitution, #3456
- error and exit for install of packages that require conda minimum version 4.3, #3726
- show warning message for pre-link scripts, #3727
- fix silent directory removal, #3730
- fix conda/install.py single-file behavior, #3854

4.4.173 3.19.3 (2016-02-19)

• fix critical issue, see #2106

4.4.174 3.19.2 (2016-02-19)

- add basic activate/deactivate, conda activate/deactivate/ls for fish, see #545
- remove error when CONDA_FORCE_32BIT is set on 32-bit systems, #1985
- suppress help text for --unknown option, #2051
- fix issue with conda create --clone post-link scripts, #2007
- fix a permissions issue on windows, #2083

4.4.175 3.19.1 (2016-02-01)

- resolve.py: properly escape periods in version numbers, #1926
- support for pinning Lua by default, #1934
- · remove hard-coded test URLs, a module cio_test is now expected when CIO_TEST is set

4.4.176 3.19.0 (2015-12-17)

- OpenBSD 5.x support, #1891
- improve install CLI to make Miniconda -f work, #1905

4.4.177 3.18.9 (2015-12-10)

- allow chaining default_channels (only applies to "system" condarc), from from CLI, #1886
- improve default for --show-channel-urls in conda list, #1900

4.4.178 3.18.8 (2015-12-03)

• always attempt to delete files in rm_rf, #1864

4.4.179 3.18.7 (2015-12-02)

- simplify call to menuinst.install()
- add menuinst as dependency on Windows
- add ROOT_PREFIX to post-link (and pre_unlink) environment

4.4.180 3.18.6 (2015-11-19)

- improve conda clean when user lacks permissions, #1807
- make show_channel_urls default to True, #1771
- cleaner write tests, #1735
- fix documentation, #1709
- improve conda clean when directories don't exist, #1808

4.4.181 3.18.5 (2015-11-11)

- fix bad menuinst exception handling, #1798
- · add workaround for unresolved dependencies on Windows

4.4.182 3.18.4 (2015-11-09)

- allow explicit file to contain MD5 hashsums
- add --md5 option to "conda list --explicit"
- stop infinite recursion during certain resolve operations, #1749
- add dependencies even if strictness == 3, #1766

4.4.183 3.18.3 (2015-10-15)

- added a pruning step for more efficient solves, #1702
- · disallow conda-env to be installed into non-root environment
- improve error output for bad command input, #1706
- pass env name and setup cmd to menuinst, #1699

4.4.184 3.18.2 (2015-10-12)

- add "conda list --explicit" which contains the URLs of all conda packages to be installed, and can used with the install/create --file option, #1688
- fix a potential issue in conda clean
- avoid issues with LookupErrors when updating Python in the root environment on Windows
- don't fetch the index from the network with conda remove
- when installing conda packages directly, "conda install .tar.bz2", unlink any installed package with that name (not just the installed one)
- allow menu items to be installed in non-root env, #1692

4.4.185 3.18.1 (2015-09-28)

• fix: removed reference to win_ignore_root in plan module

4.4.186 3.18.0 (2015-09-28)

- allow Python to be updated in root environment on Windows, #1657
- add defaults to specs after getting pinned specs (allows to pin a different version of Python than what is installed)
- show what older versions are in the solutions in the resolve debug log
- fix some issues with Python 3.5
- respect --no-deps when installing from .tar or .tar.bz2
- avoid infinite recursion with NoPackagesFound and conda update --all --file
- fix conda update --file
- toposort: Added special case to remove 'pip' dependency from 'python'
- · show dotlog messages during hint generation with --debug

- disable the max_only heuristic during hint generation
- new version comparison algorithm, which consistently compares any version string, and better handles version strings using things like alpha, beta, rc, post, and dev. This should remove any inconsistent version comparison that would lead to conda installing an incorrect version.
- use the trash in rm_rf, meaning more things will get the benefit of the trash system on Windows
- · add the ability to pass the --file argument multiple times
- · add conda upgrade alias for conda update
- add update_dependencies condarc option and --update-deps/-no-update-deps command line flags
- allow specs with conda update --all
- · add --show-channel-urls and --no-show-channel-urls command line options
- · add always_copy condarc option
- conda clean properly handles multiple envs directories. This breaks backwards compatibility with some of the --json output. Some of the old –json keys are kept for backwards compatibility.

4.4.187 3.17.0 (2015-09-11)

- add windows_forward_slashes option to walk_prefix(), see #1513
- add ability to set CONDA_FORCE_32BIT environment variable, it should only be used when running conda-build, #1555
- add config option to makes the python dependency on pip optional, #1577
- fix an UnboundLocalError
- · print note about pinned specs in no packages found error
- · allow wildcards in AND-connected version specs
- print pinned specs to the debug log
- fix conda create --clone with create_default_packages
- give a better error when a proxy isn't found for a given scheme
- enable running 'conda run' in offline mode
- · fix issue where hardlinked cache contents were being overwritten
- · correctly skip packages whose dependencies can't be found with conda update --all
- use clearer terminology in -m help text.
- use splitlines to break up multiple lines throughout the codebase
- fix AttributeError with SSLError

4.4.188 3.16.0 (2015-08-10)

- rename binstar -> anaconda, see #1458
- fix --use-local when the conda-bld directory doesn't exist
- fixed --offline option when using "conda create --clone", see #1487
- don't mask recursion depth errors
- · add conda search --reverse-dependency
- check whether hardlinking is available before linking when using "python install.py --link" directly, see #1490
- · don't exit nonzero when installing a package with no dependencies
- check which features are installed in an environment via track_features, not features
- set the verify flag directly on CondaSession (fixes conda skeleton not respecting the ssl_verify option)

4.4.189 3.15.1 (2015-07-23)

- fix conda with older versions of argcomplete
- restore the --force-pscheck option as a no-op for backwards compatibility

4.4.190 3.15.0 (2015-07-22)

- sort the output of conda info package correctly
- enable tab completion of conda command extensions using argcomplete. Command extensions that import conda should use conda.cli.conda_argparse.ArgumentParser instead of argparse.ArgumentParser. Otherwise, they should enable argcomplete completion manually.
- allow psutil and pycosat to be updated in the root environment on Windows
- remove all mentions of pscheck. The --force-pscheck flag has been removed.
- added support for S3 channels
- fix color issues from pip in conda list on Windows
- add support for other machine types on Linux, in particular ppc64le
- add non_x86_linux_machines set to config module
- allow ssl_verify to accept strings in addition to boolean values in condarc
- enable --set to work with both boolean and string values

4.4.191 3.14.1 (2015-06-29)

- make use of Crypto.Signature.PKCS1_PSS module, see #1388
- note when features are being used in the unsatisfiable hint

4.4.192 3.14.0 (2015-06-16)

- add ability to verify signed packages, see #1343 (and conda-build #430)
- fix issue when trying to add 'pip' dependency to old python packages
- provide option "conda info --unsafe-channels" for getting unobscured channel list, #1374

4.4.193 3.13.0 (2015-06-04)

- avoid the Windows file lock by moving files to a trash directory, #1133
- handle env dirs not existing in the Environments completer
- rename binstar.org -> anaconda.org, see #1348
- speed up 'source activate' by $\sim 40\%$

4.4.194 3.12.0 (2015-05-05)

- · correctly allow conda to update itself
- print which file leads to the "unable to remove file" error on Windows
- add support for the no_proxy environment variable, #1171
- add a much faster hint generation for unsatisfiable packages, which is now always enabled (previously it would not run if there were more than ten specs). The new hint only gives one set of conflicting packages, rather than all sets, so multiple passes may be necessary to fix such issues
- conda extensions that import conda should use conda.cli.conda_argparser.ArgumentParser instead of argparse.ArgumentParser to conform to the conda help guidelines (e.g., all help messages should be capitalized with periods, and the options should be preceded by "Options:" for the sake of help2man).
- add confirmation dialog to conda remove. Fixes conda remove --dry-run.

4.4.195 3.11.0 (2015-04-22)

- fix issue where forced update on Windows could cause a package to break
- remove detection of running processes that might conflict
- deprecate --force-pscheck (now a no-op argument)
- make conda search --outdated --names-only work, fixes #1252
- handle the history file not having read or write permissions better
- · make multiple package resolutions warning easier to read
- add --full-name to conda list
- · improvements to command help

4.4.196 3.10.1 (2015-04-06)

- fix logic in @memoized for unhashable args
- restored json cache of repodata, see #1249
- hide binstar tokens in conda info -- json
- handle CIO_TEST='2 '
- always find the solution with minimal number of packages, even if there are many solutions
- allow comments at the end of the line in requirement files
- don't update the progressbar until after the item is finished running
- add conda/ to HTTP header User-Agent string

4.4.197 3.10.0 (2015-03-12)

- change default repo urls to be https
- add --offline to conda search
- · add --names-only and --full-name to conda search
- · add tab completion for packages to conda search

4.4.198 3.9.1 (2015-02-24)

- pscheck: check for processes in the current environment, see #1157
- don't write to the history file if nothing has changed, see #1148
- conda update --all installs packages without version restrictions (except for Python), see #1138
- conda update --all ignores the anaconda metapackage, see #1138
- use forward slashes for file urls on Windows
- don't symlink conda in the root environment from activate
- use the correct package name in the progress bar info
- use json progress bars for unsatisfiable dependencies hints
- don't let requests decode gz files when downloaded

4.4.199 3.9.0 (2015-02-16)

- remove (de)activation scripts from conda, those are now in conda-env
- pip is now always added as a Python dependency
- allow conda to be installed into environments which start with _
- add argcomplete tab completion for environments with the -n flag, and for package names with install, update, create, and remove

4.4.200 3.8.4 (2015-02-03)

- copy (de)activate scripts from conda-env
- Add noarch (sub) directory support

4.4.201 3.8.3 (2015-01-28)

• simplified how ROOT_PREFIX is obtained in (de)activate

4.4.202 3.8.2 (2015-01-27)

- add conda clean --source-cache to clean the conda build source caches
- add missing quotes in (de)activate.bat, fixes problem in Windows when conda is installed into a directory with spaces
- fix conda install --copy

4.4.203 3.8.1 (2015-01-23)

• add missing utf-8 decoding, fixes Python 3 bug when icondata to json file

4.4.204 3.8.0 (2015-01-22)

- move active script into conda-env, which is now a new dependency
- load the channel urls in the correct order when using concurrent.futures
- add optional 'icondata' key to json files in conda-meta directory, which contain the base64 encoded png file or the icon
- remove a debug print statement

4.4.205 3.7.4 (2014-12-18)

- add --offline option to install, create, update and remove commands, and also add ability to set "offline: True" in condarc file
- · add conda uninstall as alias for conda remove
- add conda info --root
- add conda.pip module
- fix CONDARC pointing to non-existing file, closes issue #961
- make update -f work if the package is already up-to-date
- fix possible TypeError when printing an error message
- link packages in topologically sorted order (so that pre-link scripts can assume that the dependencies are installed)
- add --copy flag to install
- prevent the progressbar from crashing conda when fetching in some situations

4.4.206 3.7.3 (2014-11-05)

- conda install from a local conda package (or a tar fill which contains conda packages), will now also install the dependencies listed by the installed packages.
- add SOURCE_DIR environment variable in pre-link subprocess
- record all created environments in ~/.conda/environments.txt

4.4.207 3.7.2 (2014-10-31)

- only show the binstar install message once
- print the fetching repodata dot after the repodata is fetched
- write the install and remove specs to the history file
- add '-y' as an alias to '-yes'
- the --file option to conda config now defaults to os.environ.get('CONDARC')
- some improvements to documentation (-help output)
- add user_rc_path and sys_rc_path to conda info --json
- · cache the proxy username and password
- avoid warning about conda in pscheck
- make ~/.conda/envs the first user envs dir

4.4.208 3.7.1 (2014-10-07)

- improve error message for forgetting to use source with activate and deactivate, see issue #601
- don't allow to remove the current environment, see issue #639
- don't fail if binstar_client can't be imported for other reasons, see issue #925
- · allow spaces to be contained in conda run
- only show the conda install binstar hint if binstar is not installed
- conda info package_spec now gives detailed info on packages. conda info path has been removed, as it is duplicated by conda package -w path.

4.4.209 3.7.0 (2014-09-19)

- faster algorithm for --alt-hint
- don't allow channel_alias with allow_other_channels: false if it is set in the system .condarc
- · don't show long "no packages found" error with update --all
- automatically add the Binstar token to urls when the binstar client is installed and logged in
- carefully avoid showing the binstar token or writing it to a file
- be more careful in conda config about keys that are the wrong type
- don't expect directories starting with conda- to be commands

- no longer recommend to run conda init after pip installing conda. A pip installed conda will now work without being initialized to create and manage other environments
- · the rm function on Windows now works around access denied errors
- fix channel urls now showing with conda list with show_channel_urls set to true

4.4.210 3.6.4 (2014-09-08)

- fix removing packages that aren't in the channels any more
- · Pretties output for --alt-hint

4.4.211 3.6.3 (2014-09-04)

- skip packages that can't be found with update --all
- · add --use-local to search and remove
- allow --use-local to be used along with -c (-channels) and -override-channels. --override-channels now requires either -c or -use-local
- allow paths in has_prefix to be quoted, to allow for spaces in paths on Windows
- retain Unix style path separators for prefixes in has_prefix on Windows (if the placeholder path uses /, replace it with a path that uses /, not)
- fix bug in --use-local due to API changes in conda-build
- include user site directories in conda info -s
- make binary has_prefix replacement work with spaces after the prefix
- make binary has_prefix replacement replace multiple occurrences of the placeholder in the same null-terminated string
- don't show packages from other platforms as installed or cached in conda search
- be more careful about not warning about conda itself in pscheck
- Use a progress bar for the unsatisfiable packages hint generation
- Don't use TemporaryFile in try_write, as it is too slow when it fails
- Ignore InsecureRequestWarning when ssl_verify is False
- · conda remove removes features tracked by removed packages in track_features

4.4.212 3.6.2 (2014-08-20)

- add --use-index-cache to conda remove
- fix a bug where features (like mkl) would be selected incorrectly
- use concurrent.future.ThreadPool to fetch package metadata asynchronously in Python 3.
- do the retries in rm_rf on every platform
- use a higher cutoff for package name misspellings
- allow changing default channels in "system" .condarc

4.4.213 3.6.1 (2014-08-13)

- add retries to download in fetch module
- · improved error messages for missing packages
- more robust rm_rf on Windows
- print multiline help for subcommands correctly

4.4.214 3.6.0 (2014-08-11)

- correctly check if a package can be hard-linked if it isn't extracted yet
- change how the package plan is printed to better show what is new, updated, and downgraded
- use suggest_normalized_version in the resolve module. Now versions like 1.0alpha that are not directly recognized by verlib's NormalizedVersion are supported better
- conda run command, to run apps and commands from packages
- more complete -- json API. Every conda command should fully support -- json output now.
- · show the conda_build and requests versions in conda info
- include packages from setup.py develop in conda list (with use_pip)
- raise a warning instead of dying when the history file is invalid
- use urllib.quote on the proxy password
- make conda search --outdated --canonical work
- pin the Python version during conda init
- fix some metadata that is written for Python during conda init
- allow comments in a pinned file
- allow installing and updating menuinst on Windows
- · allow conda create with both --file and listed packages
- · better handling of some nonexistent packages
- fix command line flags in conda package
- fix a bug in the ftp adapter

4.4.215 3.5.5 (2014-06-10)

• remove another instance pycosat version detection, which fails on Windows, see issue #761

4.4.216 3.5.4 (2014-06-10)

• remove pycosat version detection, which fails on Windows, see issue #761

4.4.217 3.5.3 (2014-06-09)

- fix conda update to correctly not install packages that are already up-to-date
- · always fail with connection error in download
- the package resolution is now much faster and uses less memory
- add ssl_verify option in condarc to allow ignoring SSL certificate verification, see issue #737

4.4.218 3.5.2 (2014-05-27)

· fix bug in activate.bat and deactivate.bat on Windows

4.4.219 3.5.1 (2014-05-26)

- fix proxy support conda now prompts for proxy username and password again
- fix activate.bat on Windows with spaces in the path
- update optional psutil dependency was updated to psutil 2.0 or higher

4.4.220 3.5.0 (2014-05-15)

- replace use of urllib2 with requests. requests is now a hard dependency of conda.
- add ability to only allow system-wise specified channels
- hide binstar from output of conda info

4.4.221 3.4.3 (2014-05-05)

- allow prefix replacement in binary files, see issue #710
- check if creating hard link is possible and otherwise copy, during install
- allow circular dependencies

4.4.222 3.4.2 (2014-04-21)

- conda clean --lock: skip directories that don't exist, fixes #648
- fixed empty history file causing crash, issue #644
- remove timezone information from history file, fixes issue #651
- fix PackagesNotFound error for missing recursive dependencies
- change the default for adding cache from the local package cache known is now the default and the option to use index metadata from the local package cache is --unknown
- add --alt-hint as a method to get an alternate form of a hint for unsatisfiable packages

- add conda package --ls-files to list files in a package
- add ability to pin specs in an environment. To pin a spec, add a file called pinned to the environment's conda-meta directory with the specs to pin. Pinned specs are always kept installed, unless the --no-pin flag is used.
- fix keyboard interrupting of external commands. Now keyboard interrupting conda build correctly removes the lock file
- add no_link ability to conda, see issue #678

4.4.223 3.4.1 (2014-04-07)

- always use a pkgs cache directory associated with an envs directory, even when using -p option with an arbitrary a prefix which is not inside an envs dir
- add setting of PYTHONHOME to conda info --system
- skip packages with bad metadata

4.4.224 3.4.0 (2014-04-02)

- added revision history to each environment:
 - conda list --revisions
 - conda install --revision
 - log is stored in conda-meta/history
- allow parsing pip-style requirement files with --file option and in command line arguments, e.g. conda install 'numpy>=1.7', issue #624
- fix error message for --file option when file does not exist
- allow DEFAULTS in CONDA_ENVS_PATH, which expands to the defaults settings, including the condarc file
- don't install a package with a feature (like mkl) unless it is specifically requested (i.e., that feature is already enabled in that environment)
- add ability to show channel URLs when displaying what is going to be downloaded by setting "show_channel_urls: True" in condarc
- fix the --quiet option
- skip packages that have dependencies that can't be found

4.4.225 3.3.2 (2014-03-24)

- fix the --file option
- · check install arguments before fetching metadata
- fix a printing glitch with the progress bars
- give a better error message for conda clean with no arguments
- don't include unknown packages when searching another platform

4.4.226 3.3.1 (2014-03-19)

- Fix setting of PS1 in activate.
- Add conda update --all.
- Allow setting CONDARC=' ' to use no condarc.
- Add conda clean --packages.
- Don't include bin/conda, bin/activate, or bin/deactivate in conda package.

4.4.227 3.3.0 (2014-03-18)

- allow new package specification, i.e. ==, >=, >, <=, <, != separated by ',' for example: >=2.3,<3.0
- add ability to disable self update of conda, by setting "self_update: False" in .condarc
- Try installing packages using the old way of just installing the maximum versions of things first. This provides a major speedup of solving the package specifications in the cases where this scheme works.
- Don't include python=3.3 in the specs automatically for the Python 3 version of conda. This allows you to do "conda create -n env package" for a package that only has a Python 2 version without specifying "python=2". This change has no effect in Python 2.
- Automatically put symlinks to conda, activate, and deactivate in each environment on Unix.
- On Unix, activate and deactivate now remove the root environment from the PATH. This should prevent "bleed through" issues with commands not installed in the activated environment but that are installed in the root environment. If you have "setup.py develop" installed conda on Unix, you should run this command again, as the activate and deactivate scripts have changed.
- Begin work to support Python 3.4.
- Fix a bug in version comparison
- Fix usage of sys.stdout and sys.stderr in environments like pythonw on Windows where they are nonstandard file descriptors.

4.4.228 3.2.1 (2014-03-12)

- fix installing packages with irrational versions
- fix installation in the api
- use a logging handler to print the dots

4.4.229 3.2.0 (2014-03-11)

- print dots to the screen for progress
- move logic functions from resolve to logic module

4.4.230 3.2.0a1 (2014-03-07)

- conda now uses pseudo-boolean constraints in the SAT solver. This allows it to search for all versions at once, rather than only the latest (issue #491).
- Conda contains a brand new logic submodule for converting pseudo-boolean constraints into SAT clauses.

4.4.231 3.1.1 (2014-03-07)

• check if directory exists, fixed issue #591

4.4.232 3.1.0 (2014-03-07)

- local packages in cache are now added to the index, this may be disabled by using the --known option, which only makes conda use index metadata from the known remote channels
- · add --use-index-cache option to enable using cache of channel index files
- · fix ownership of files when installing as root on Linux
- conda search: add '.' symbol for extracted (cached) packages

4.4.233 3.0.6 (2014-02-20)

• fix 'conda update' taking build number into account

4.4.234 3.0.5 (2014-02-17)

- allow packages from create_default_packages to be overridden from the command line
- fixed typo install.py, issue #566
- try to prevent accidentally installing into a non-root conda environment

4.4.235 3.0.4 (2014-02-14)

• conda update: don't try to update packages that are already up-to-date

4.4.236 3.0.3 (2014-02-06)

- improve the speed of clean --lock
- some fixes to conda config
- more tests added
- choose the first solution rather than the last when there are more than one, since this is more likely to be the one you want.

4.4.237 3.0.2 (2014-02-03)

• fix detection of prefix being writable

4.4.238 3.0.1 (2014-01-31)

- bug: not having track_features in condarc now uses default again
- improved test suite
- · remove numpy version being treated special in plan module
- if the post-link.(bat|sh) fails, don't treat it as though it installed, i.e. it is not added to conda-meta
- fix activate if CONDA_DEFAULT_ENV is invalid
- fix conda config --get to work with list keys again
- print the total download size
- fix a bug that was preventing conda from working in Python 3
- add ability to run pre-link script, issue #548

4.4.239 3.0.0 (2014-01-24)

- removed build, convert, index, and skeleton commands, which are now part of the conda-build project: https://github.com/conda/conda-build
- limited pip integration to conda list, that means conda install no longer calls pip install # !!!
- add ability to call sub-commands named 'conda-x'
- The -c flag to conda search is now shorthand for --channel, not -canonical (this is to be consistent with other conda commands)
- allow changing location of .condarc file using the CONDARC environment variable
- conda search now shows the channel that the package comes from
- conda search has a new --platform flag for searching for packages in other platforms.
- remove condarc warnings: issue #526#issuecomment-33195012

4.4.240 2.3.1 (2014-01-17)

- add ability create info/no_softlink
- add conda convert command to convert non-platform-dependent packages from one platform to another (experimental)
- unify create, install, and update code. This adds many features to create and update that were previously only available to install. A backwards incompatible change is that conda create -f now means --force, not --file.

4.4.241 2.3.0 (2014-01-16)

- automatically prepend http://conda.binstar.org/ (or the value of channel_alias in the .condarc file) to channels whenever the channel is not a URL or the word 'defaults or 'system'
- · recipes made with the skeleton pypi command will use setuptools instead of distribute
- re-work the setuptools dependency and entry_point logic so that non console_script entry_points for packages with a dependency on setuptools will get correct build script with conda skeleton pypi
- add -m, --mkdir option to conda install
- add ability to disable soft-linking

4.4.242 2.2.8 (2014-01-06)

- add check for chrpath (on Linux) before build is started, see issue #469
- conda build: fixed ELF headers not being recognized on Python 3
- fixed issues: #467, #476

4.4.243 2.2.7 (2014-01-02)

• fixed bug in conda build related to lchmod not being available on all platforms

4.4.244 2.2.6 (2013-12-31)

- fix test section for automatic recipe creation from pypi using --build-recipe
- minor Py3k fixes for conda build on Linux
- copy symlinks as symlinks, issue #437
- fix explicit install (e.g. from output of conda list -e) in root env
- · add pyyaml to the list of packages which can not be removed from root environment
- fixed minor issues: #365, #453

4.4.245 2.2.5 (2013-12-17)

- conda build: move broken packages to conda-bld/broken
- conda config: automatically add the 'defaults' channel
- conda build: improve error handling for invalid recipe directory
- add ability to set build string, issue #425
- fix LD_RUN_PATH not being set on Linux under Python 3, see issue #427, thanks peter1000

4.4.246 2.2.4 (2013-12-10)

- add support for execution with the -m switch (issue #398), i.e. you can execute conda also as: python -m conda
- add a deactivate script for windows
- conda build adds .pth-file when it encounters an egg (TODO)
- add ability to preserve egg directory when building using build/preserve_egg_dir: True
- allow track_features in ~/.condarc
- Allow arbitrary source, issue #405
- fixed minor issues: #393, #402, #409, #413

4.4.247 2.2.3 (2013-12-03)

- add "foreign mode", i.e. disallow install of certain packages when using a "foreign" Python, such as the system Python
- remove activate/deactivate from source tarball created by sdist.sh, in order to not overwrite activate script from virtualenvwrapper

4.4.248 2.2.2 (2013-11-27)

- remove ARCH environment variable for being able to change architecture
- add PKG_NAME, PKG_VERSION to environment when running build.sh, .-post-link.sh and .-pre-unlink.sh

4.4.249 2.2.1 (2013-11-15)

- minor fixes related to make conda pip installable
- generated conda meta-data missing 'files' key, fixed issue #357

4.4.250 2.2.0 (2013-11-14)

- add conda init command, to allow installing conda via pip
- fix prefix being replaced by placeholder after conda build on Unix
- add 'use_pip' to condarc configuration file
- fixed activate on Windows to set CONDA_DEFAULT_ENV
- allow setting "always_yes: True" in condarc file, which implies always using the --yes option whenever asked to proceed

4.4.251 2.1.0 (2013-11-07)

- fix rm_egg_dirs so that the .egg_info file can be a zip file
- improve integration with pip
 - conda list now shows pip installed packages
 - conda install will try to install via "pip install" if no conda package is available (unless --no-pip is provided)
 - conda build has a new --build-recipe option which will create a recipe (stored in /conda-recipes) from pypi then build a conda package (and install it)
 - pip list and pip install only happen if pip is installed
- enhance the locking mechanism so that conda can call itself in the same process.

4.4.252 2.0.4 (2013-11-04)

- ensure lowercase name when generating package info, fixed issue #329
- on Windows, handle the .nonadmin files

4.4.253 2.0.3 (2013-10-28)

- update bundle format
- fix bug when displaying packages to be downloaded (thanks Crystal)

4.4.254 2.0.2 (2013-10-27)

- add --index-cache option to clean command, see issue #321
- use RPATH (instead of RUNPATH) when building packages on Linux

4.4.255 2.0.1 (2013-10-23)

- add --no-prompt option to conda skeleton pypi
- add create_default_packages to condarc (and --no-default-packages option to create command)

4.4.256 2.0.0 (2013-10-01)

- added user/root mode and ability to soft-link across filesystems
- added create --clone option for copying local environments
- fixed behavior when installing into an environment which does not exist yet, i.e. an error occurs
- fixed install --no-deps option
- added --export option to list command
- allow building of packages in "user mode"
- · regular environment locations now used for build and test
- · add ability to disallow specification names

- add ability to read help messages from a file when install location is RO
- · restore backwards compatibility of share/clone for conda-api
- · add new conda bundle command and format
- · pass ARCH environment variable to build scripts
- added progress bar to source download for conda build, issue #230
- added ability to use url instead of local file to conda install --file and conda create --file options

4.4.257 1.9.1 (2013-09-06)

· fix bug in new caching of repodata index

4.4.258 1.9.0 (2013-09-05)

- · add caching of repodata index
- · add activate command on Windows
- add conda package --which option, closes issue 163
- add ability to install file which contains multiple packages, issue 256
- · move conda share functionality to conda package --share
- update documentation
- improve error messages when external dependencies are unavailable
- add implementation for issue 194: post-link or pre-unlink may append to a special file \${PREFIX}/.messages.txt for messages, which is display to the user's console after conda completes all actions
- add conda search --outdated option, which lists only installed packages for which newer versions are available
- fixed numerous Py3k issues, in particular with the build command

4.4.259 1.8.2 (2013-08-16)

- · add conda build --check option
- add conda clean --lock option
- fixed error in recipe causing conda traceback, issue 158
- fixes conda build error in Python 3, issue 238
- improve error message when test command fails, as well as issue 229
- · disable Python (and other packages which are used by conda itself) to be updated in root environment on Windows
- simplified locking, in particular locking should never crash conda when files cannot be created due to permission problems

4.4.260 1.8.1 (2013-08-07)

- fixed conda update for no arguments, issue 237
- fix setting prefix before calling should_do_win_subprocess() part of issue 235
- add basic subversion support when building
- add --output option to conda build

4.4.261 1.8.0 (2013-07-31)

- add Python 3 support (thanks almarklein)
- add Mercurial support when building from source (thanks delicb)
- allow Python (and other packages which are used by conda itself) to be updated in root environment on Windows
- add conda config command
- add conda clean command
- removed the conda pip command
- · improve locking to be finer grained
- made activate/deactivate work with zsh (thanks to mika-fischer)
- allow conda build to take tarballs containing a recipe as arguments
- add PKG_CONFIG_PATH to build environment variables
- fix entry point scripts pointing to wrong python when building Python 3 packages
- allow source/sha1 in meta.yaml, issue 196
- · more informative message when there are unsatisfiable package specifications
- ability to set the proxy urls in condarc
- conda build asks to upload to binstar. This can also be configured by changing binstar_upload in condarc.
- basic tab completion if the argcomplete package is installed and eval "\$(register-python-argcomplete conda)" is added to the bash profile.

4.4.262 1.7.2 (2013-07-02)

- fixed conda update when packages include a post-link step which was caused by subprocess being lazily imported, fixed by 0d0b860
- · improve error message when 'chrpath' or 'patch' is not installed and needed by build framework
- fixed sharing/cloning being broken (issue 179)
- add the string LOCKERROR to the conda lock error message

4.4.263 1.7.1 (2013-06-21)

- fix "executable" not being found on Windows when ending with .bat when launching application
- give a better error message from when a repository does not exist

4.4.264 1.7.0 (2013-06-20)

- allow \${PREFIX} in app_entry
- add binstar upload information after conda build finishes

4.4.265 1.7.0a2 (2013-06-20)

- add global conda lock file for only allowing one instance of conda to run at the same time
- · add conda skeleton command to create recipes from PyPI
- · add ability to run post-link and pre-unlink script

4.4.266 1.7.0a1 (2013-06-13)

- add ability to build conda packages from "recipes", using the conda build command, for some examples, see: https://github.com/ContinuumIO/conda-recipes
- fixed bug in conda install --force
- conda update command no longer uses anaconda as default package name
- · add proxy support
- added application API to conda.api module
- add -c/-channel and --override-channels flags (issue 121).
- add default and system meta-channels, for use in .condarc and with -c (issue 122).
- fixed ability to install ipython=0.13.0 (issue 130)

4.4.267 1.6.0 (2013-06-05)

- update package command to reflect changes in repodata
- fixed refactoring bugs in share/clone
- warn when anaconda processes are running on install in Windows (should fix most permissions errors on Windows)

4.4.268 1.6.0rc2 (2013-05-31)

- conda with no arguments now prints help text (issue 111)
- don't allow removing conda from root environment
- conda update python does no longer update to Python 3, also ensure that conda itself is always installed into the root environment (issue 110)

4.4.269 1.6.0rc1 (2013-05-30)

- major internal refactoring
- use new "depends" key in repodata
- uses pycosat to solve constraints more efficiently
- · add hard-linking on Windows
- fixed linking across filesystems (issue 103)
- add conda remove --features option
- added more tests, in particular for new dependency resolver
- add internal DSL to perform install actions
- · add package size to download preview
- add conda install --force and --no-deps options
- fixed conda help command
- add conda remove --all option for removing entire environment
- fixed source activate on systems where sourcing a gives "bash" as \$0
- · add information about installed versions to conda search command
- removed known "locations"
- · add output about installed packages when update and install do nothing
- changed default when prompted for y/n in CLI to yes

4.4.270 1.5.2 (2013-04-29)

• fixed issue 59: bad error message when pkgs dir is not writable

4.4.271 1.5.1 (2013-04-19)

- fixed issue 71 and (73 duplicate): not being able to install packages starting with conda (such as 'conda-api')
- fixed issue 69 (not being able to update Python / NumPy)
- fixed issue 76 (cannot install mkl on OSX)

4.4.272 1.5.0 (2013-03-22)

- add conda share and clone commands
- add (hidden) --output-json option to clone, share and info commands to support the conda-api package
- add repo sub-directory type 'linux-armv6l'

4.4.273 1.4.6 (2013-03-12)

• fixed channel selection (issue #56)

4.4.274 1.4.5 (2013-03-11)

- fix issue #53 with install for meta packages
- add -q/–quiet option to update command

4.4.275 1.4.4 (2013-03-09)

• use numpy 1.7 as default on all platforms

4.4.276 1.4.3 (2013-03-09)

• fixed bug in conda.builder.share.clone_bundle()

4.4.277 1.4.2 (2013-03-08)

- feature selection fix for update
- Windows: don't allow linking or unlinking python from the root environment because the file lock, see issue #42

4.4.278 1.4.1 (2013-03-07)

- fix some feature selection bugs
- never exit in activate and deactivate
- improve help and error messages

4.4.279 1.4.0 (2013-03-05)

- fixed conda pip NAME==VERSION
- added conda info --license option
- · add source activate and deactivate commands
- · rename the old activate and deactivate to link and unlink
- · add ability for environments to track "features"

- add ability to distinguish conda build packages from Anaconda packages by adding a "file_hash" meta-data field in info/index.json
- add conda.builder.share module

4.4.280 1.3.5 (2013-02-05)

- fixed detecting untracked files on Windows
- removed backwards compatibility to conda 1.0 version

4.4.281 1.3.4 (2013-01-28)

- fixed conda installing itself into environments (issue #10)
- fixed non-existing channels being silently ignored (issue #12)
- fixed trailing slash in ~/.condarc file cause crash (issue #13)
- fixed conda list not working when ~/.condarc is missing (issue #14)
- fixed conda install not working for Python 2.6 environment (issue #17)
- added simple first cut implementation of remove command (issue #11)
- pip, build commands: only package up new untracked files
- allow a system-wide <sys.prefix>/.condarc (~/.condarc takes precedence)
- only add pro channel is no condarc file exists (and license is valid)

4.4.282 1.3.3 (2013-01-23)

- fix conda create not filtering channels correctly
- remove (hidden) --test and --testgui options

4.4.283 1.3.2 (2013-01-23)

• fix deactivation of packages with same build number note that conda upgrade did not suffer from this problem, as was using separate logic

4.4.284 1.3.1 (2013-01-22)

• fix bug in conda update not installing new dependencies

4.4.285 1.3.0 (2013-01-22)

- added conda package command
- added conda index command
- added -c, --canonical option to list and search commands
- fixed conda --version on Windows
- add this changelog

4.4.286 1.2.1 (2012-11-21)

· remove ambiguity from conda update command

4.4.287 1.2.0 (2012-11-20)

- "conda upgrade" now updates from AnacondaCE to Anaconda (removed upgrade2pro
- add versioneer

4.4.288 1.1.0 (2012-11-13)

• Many new features implemented by Bryan

4.4.289 1.0.0 (2012-09-06)

• initial release

4.5 Glossary

4.5.1 .condarc

The Conda Runtime Configuration file, an optional .yaml file that allows you to configure many aspects of conda, such as which channels it searches for packages, proxy settings, and environment directories. A .condarc file is not included by default, but it is automatically created in your home directory when you use the conda config command. The .condarc file can also be located in a root environment, in which case it overrides any .condarc in the home directory. For more information, see *Using the .condarc conda configuration file* and *Administering a multi-user conda installation*. Pronounced "conda r-c".

4.5.2 Activate/Deactivate environment

Conda commands used to switch or move between installed environments. The conda activate command prepends the path of your current environment to the PATH environment variable so that you do not need to type it each time. deactivate removes it. Even when an environment is deactivated, you can still execute programs in that environment by specifying their paths directly, as in ~/anaconda/envs/envname/bin/program_name. When an environment is activated, you can execute the program in that environment with just program_name.

Note: Replace envname with the name of the environment and replace program_name with the name of the program.

4.5.3 Anaconda

A downloadable, free, open-source, high-performance, and optimized Python and R distribution. Anaconda includes *conda*, conda-build, Python, and 250+ automatically installed, open-source scientific packages and their dependencies that have been tested to work well together, including SciPy, NumPy, and many others. Use the conda install command to easily install 7,500+ popular open-source packages for data science--including advanced and scientific analytics--from the Anaconda repository. Use the conda command to install thousands more open-source packages.

Because Anaconda is a Python distribution, it can make installing Python quick and easy even for new users.

Available for Windows, macOS, and Linux, all versions of Anaconda are supported by the community.

See also *Miniconda* and *conda*.

4.5.4 Anaconda.org

A web-based, repository hosting service in the cloud. Packages created locally can be published to the cloud to be shared with others. Anaconda.org is a public version of Anaconda Repository and was formerly known as Anaconda Cloud.

4.5.5 Anaconda Navigator

A desktop graphical user interface (GUI) included in all versions of Anaconda that allows you to easily manage conda packages, environments, channels, and notebooks without a command line interface (CLI). See more about Navigator.

4.5.6 Channels

The locations of the repositories where conda looks for packages. Channels may point to a Cloud repository or a private location on a remote or local repository that you or your organization created. The conda channel command has a default set of channels to search, beginning with https://repo.anaconda.com/pkgs/, which you may override, for example, to maintain a private or internal channel. These default channels are referred to in conda commands and in the .condarc file by the channel name "defaults."

4.5.7 conda

The package and environment manager program bundled with Anaconda that installs and updates conda packages and their dependencies. Conda also lets you easily switch between conda environments on your local computer.

4.5.8 conda environment

A folder or directory that contains a specific collection of conda packages and their dependencies, so they can be maintained and run separately without interference from each other. For example, you may use a conda environment for only Python 2 and Python 2 packages, maintain another conda environment with only Python 3 and Python 3 packages, and maintain another for R language packages. Environments can be created from:

- The Navigator GUI
- The command line
- An environment specification file with the name your-environment-name.yml

4.5.9 conda package

A compressed file that contains everything that a software program needs in order to be installed and run, so that you do not have to manually find and install each dependency separately. A conda package includes system-level libraries, Python or R language modules, executable programs, and other components. You manage conda packages with conda.

4.5.10 conda repository

A cloud-based repository that contains 7,500+ open-source certified packages that are easily installed locally with the conda install command. Anyone can access the repository from:

- The Navigator GUI
- A terminal using conda commands
- https://repo.anaconda.com/pkgs/

4.5.11 Metapackage

A metapackage is a very simple package that has at least a name and a version. It need not have any dependencies or build steps. *Metapackages* may list dependencies to several core, low-level libraries and may contain links to software files that are automatically downloaded when executed.

4.5.12 Miniconda

A free minimal installer for conda. Miniconda is a small, bootstrap version of Anaconda that includes only conda, Python, the packages they depend on, and a small number of other useful packages, including pip, zlib, and a few others. Use the conda install command to install 7,500+ additional conda packages from the Anaconda repository.

Miniconda is a Python distribution that can make installing Python quick and easy even for new users.

See also Anaconda and conda.

4.5.13 Noarch package

A conda package that contains nothing specific to any system architecture, so it may be installed from any system. When conda searches for packages on any system in a channel, conda checks both the system-specific subdirectory, such as linux-64, and the noarch directory. Noarch is a contraction of "no architecture".

4.5.14 Package manager

A collection of software tools that automates the process of installing, updating, configuring, and removing computer programs for a computer's operating system. Also known as a package management system. Conda is a package manager.

4.5.15 Packages

Software files and information about the software, such as its name, the specific version, and a description, bundled into a file that can be installed and managed by a package manager.

4.5.16 Plugins

Plugins, sometimes referred to as add-ons or extensions, are software or modules that add new functions to a host program (*e.g.*, conda) without directly altering the host program itself. Amongst other uses, plugins support is utilized to enable third-party developers to extend an application, support easily adding new features, and to reduce the size of an application by not loading unused features.

4.5.17 Repository

Any storage location from which software assets may be retrieved and installed on a local computer. See also *Anaconda.org* and *conda repository*.

4.5.18 Silent mode installation

When installing Miniconda or Anaconda in silent mode, screen prompts are not shown on screen and default settings are automatically accepted.

4.6 Developer guide

4.6.1 Architecture

Conda is a complex system of many components and can be hard to understand for users and developers alike. The following C4 model based architecture diagrams should help in that regard. As a refresher, the C4 model tries to visualize complex software systems at different levels of detail, and explaining the functionality to different types of audience.

Note: These diagrams represent the state of conda at the time when the documentation was automatically build as part of the development process for conda 24.3.1.dev75 (Apr 25, 2024).

C4 stands for the for levels:

- 1. Context
- 2. Container
- 3. Component
- 4. Code

Level 1: Context

This is the overview, 30,000 feet view on conda, to better understand how conda in the center of the diagram interacts with other systems and how users relate to it.

More information about how to interpret this diagram can be found in the C4 model documentation about the System Context diagram.



Level 2: Container

This level is zooming in to conda on a system level, which was in the center of the Level 1 diagram, to show the highlevel shape of the software architecture of and the various responsibilities in conda, including major technology choices and communication patterns between the various containers.

More information about how to interpret the following diagrams can be found in the C4 model documentation about the Container diagram.

Channels

The following diagram focuses on the channels container from the level 1 diagram.


Conda

The following diagram focuses on the conda container from the level 1 diagram.



Level 3: Component

Yet another zoom-in, in which individual containers from Level 2 are decomposed to show major building blocks in conda and their interactions. Those building blocks are called components in the sense that they each have a higher function and relate to an identifiable responsibility and implementation details.



More information about how to interpret this diagram can be found in the C4 model documentation about the Component diagram.

Level 4: Code

This part is auto-generated based on the current code and shows how the code is structured and how it interacts. For brevity this ignores a number of subsystems like the public API and exports modules, utility and vendor packages.

More information about how to interpret this diagram can be found in the C4 model documentation about the Code diagram.



4.6.2 Contributing to conda

Thank you for your interest in improving conda! Below, we describe how our development process works and how you can be a part of it.

Already know how to contribute and need help setting up your development environment? Read the development environment guide here

Hosted on GitHub

All development currently takes place on GitHub. This means we make extensive use of the project management tools they provide such as issues and projects.

Code of Conduct

When you decide to contribute to this project, it is important to adhere to our code of conduct, which is currently the NumFOCUS Code of Conduct. Please read it carefully.

Conda Contributor License Agreement

To begin contributing to this repository, you need to sign the Conda Contributor License Agreement (CLA). In case you're new to CLAs, this is a rather standard procedure for larger projects. Django and Python for example both use similar agreements.

Click here to sign the Conda Contributor License Agreement.

A record of prior signatories is kept in a separate repo in conda's GitHub organization.

Ways to contribute

Below are all the ways you can get involved in with conda.

Bug reports and feature requests

Bug reports and feature requests are always welcome. To file a new issue, head to the issue form.

It should be noted that conda-build issues need to be filed separately at its issue tracker.

For all other types of issues, please head to Anaconda.org's "Report a Bug" page. For even more information and documentation on everything related to Anaconda, head to the Support Center at Anaconda Nucleus.

Before submitting an issue via any of these channels, make sure to document it as well as possible and follow the submission guidelines (this makes everyone's job a lot easier!).

Contributing your changes to conda

Here are the steps you need to take to contribute to conda:

- 1. Signup for a GitHub account (if you haven't already) and install Git on your system.
- 2. Sign the Conda Contributor License Agreement.
- 3. Fork the conda repository to your personal GitHub account by clicking the "Fork" button on https://github.com/ conda/conda and follow GitHub's instructions.
- 4. Work on your proposed solution. Visit this page if you need help getting your development environment setup
- 5. When you are ready to submit a change, create a new pull request so that we can merge your changes to our repository.

Issue sorting

Issue sorting is how we filter incoming issues and get them ready for active development. To see how this process works for this project, read "The Issue Sorting Process at conda".

The project maintainers are currently not seeking help with issue sorting, but this may change in the future

Conda capitalization standards

- 1. Conda should be written in lowercase, whether in reference to the tool, ecosystem, packages, or organization.
- 2. References to the conda command should use code formatting (i.e. conda).
- 3. If the use of conda is not a command and if conda is at the beginning of a sentence, conda should be uppercase.

Examples

In sentences

Beginning a sentence:

- Conda is an open-source package and environment management system.
- conda install can be used to install packages.

Conda in the middle of a sentence:

- If a newer version of conda is available, you can use conda update conda to update to that version.
- You can find conda packages within conda channels. The conda command can search these channels.

In titles and headers

Titles and headers should use the same capitalization and formatting standards as sentences.

In links

Links should use the same capitalization conventions as sentences. Because the conda docs currently use reStructured-Text (RST) as a markup language, and RST does not support nested inline markup, documentation writers should avoid using code backtick formatting inside links.

4.6.3 Development Environment

1. Clone the repo you just forked on GitHub to your local machine. Configure your repo to point to both "upstream" (the main conda repo) and your fork ("origin"). For detailed directions, see below:

Bash (macOS, Linux, Windows)

```
# choose the repository location
# warning: not the location of an existing conda installation!
$ CONDA_PROJECT_ROOT="$HOME/conda"
# clone the project
# replace `your-username` with your actual GitHub username
$ git clone git@github.com:your-username/conda "$CONDA_PROJECT_ROOT"
$ cd "$CONDA_PROJECT_ROOT"
# set the `upstream` as the the main repository
$ git remote add upstream git@github.com:conda/conda
```

cmd.exe (Windows)

```
# choose the repository location
# warning: not the location of an existing conda installation!
> set "CONDA_PROJECT_ROOT=%HOMEPATH%\conda"
# clone the project
# replace `your-username` with your actual GitHub username
> git clone git@github.com:your-username/conda "%CONDA_PROJECT_ROOT%"
> cd "%CONDA_PROJECT_ROOT%"
# set the `upstream` as the main repository
> git remote add upstream git@github.com:conda/conda
```

2. One option is to create a local development environment and activate that environment

Bash (macOS, Linux, Windows)

\$ source ./dev/start

cmd.exe (Windows)

> .\dev\start.bat

This command will create a project-specific base environment (see **devenv** in your repo directory after running this command). If the base environment already exists this command will simply activate the already-created **devenv** environment.

To be sure that the conda code being interpreted is the code in the project directory, look at the value of conda location: in the output of conda info --all.

- 3. Alternatively, for Linux development only, you can use the same Docker image the CI pipelines use. Note that you can run this from all three operating systems! We are using docker compose, which provides three actions for you:
 - unit-tests: Run all unit tests.
 - integration-tests: Run all integration tests.
 - interactive: You are dropped in a pre-initialized Bash session, where you can run all your pytest commands as required.

Use them with docker compose run <action>. For example:

Any shell (macOS, Linux, Windows)

\$ docker compose run unit-tests

This builds the same Docker image as used in continuous integration from the Github Container Registry and starts bash with the conda development mode already enabled.

By default, it will use Miniconda-based, Python 3.9 installation configured for the defaults channel. You can customize this with two environment variables:

- CONDA_DOCKER_PYTHON: major.minor value; e.g. 3.11.
- CONDA_DOCKER_DEFAULT_CHANNEL: either defaults or conda-forge

For example, if you need a conda-forge based 3.12 image:

Bash (macOS, Linux, Windows)

cmd.exe (Windows)

```
> set CONDA_DOCKER_PYTHON=3.12
> set CONDA_DOCKER_DEFAULT_CHANNEL=conda-forge
> docker compose build --no-cache
> docker compose run interactive
> set "CONDA_DOCKER_PYTHON="
> set "CONDA_DOCKER_DEFAULT_CHANNEL="
```

The conda repository will be mounted to /opt/conda-src, so all changes done in your editor will be reflected live while the Docker container is running.

Static Code Analysis

This project is configured with pre-commit to automatically run linting and other static code analysis on every commit. Running these tools prior to the PR/code review process helps in two ways:

- 1. it helps you by automating the nitpicky process of identifying and correcting code style/quality issues
- 2. it helps us where during code review we can focus on the substance of your contribution

Feel free to read up on everything pre-commit related in their docs but we've included the gist of what you need to get started below:

Bash (macOS, Linux, Windows)

```
# reuse the development environment created above
$ source ./dev/start
# or start the Docker image in interactive mode
# $ docker compose run interactive
# install pre-commit hooks for conda
$ cd "$CONDA_PROJECT_ROOT"
$ pre-commit install
# manually running pre-commit on current changes
# note: by default pre-commit only runs on staged files
$ pre-commit run
# automatically running pre-commit during commit
$ git commit
```

cmd.exe (Windows)

```
:: reuse the development environment created above
> .\dev\start.bat
:: or start the Docker image in interactive mode
:: > docker compose run interactive
:: install pre-commit hooks for conda
> cd "%CONDA_PROJECT_ROOT%"
> pre-commit install
:: manually running pre-commit on current changes
:: note: by default pre-commit only runs on staged files
> pre-commit run
:: automatically running pre-commit during commit
> git commit
```

Beware that some of the tools run by pre-commit can potentially modify the code (see black, blacken-docs, and darker). If pre-commit detects that any files were modified it will terminate the commit giving you the opportunity to review the code before committing again.

Strictly speaking using pre-commit on your local machine for commits is optional (if you don't install pre-commit you will still be able to commit normally). But once you open a PR to contribue your changes, pre-commit will be automatically run at which point any errors that occur will need to be addressed prior to proceeding.

Testing

We use pytest to run our test suite. Please consult pytest's docs for detailed instructions but generally speaking all you need is the following:

Bash (macOS, Linux, Windows)

```
# reuse the development environment created above
$ source ./dev/start
# or start the Docker image in interactive mode
# $ docker compose run interactive
# run conda's unit tests using GNU make
$ make unit
# or alternately with pytest
$ pytest --cov -m "not integration" conda tests
# or you can use pytest to focus on one specific test
$ pytest --cov tests/test_create.py -k create_install_update_remove_smoketest
```

cmd.exe (Windows)

```
:: reuse the development environment created above
> .\dev\start.bat
:: or start the Docker image in interactive mode
:: > docker compose run interactive
:: run conda's unit tests with pytest
> pytest --cov -m "not integration" conda tests
:: or you can use pytest to focus on one specific test
> pytest --cov tests\test_create.py -k create_install_update_remove_smoketest
```

If you are not measuring code coverage, pytest can be run without the --cov option. The docker compose tests pass --cov.

Note: Some integration tests require you build a package with conda-build beforehand. This is taking care of if you run docker compose run integration-tests, but you need to do it manually in other modes:

Bash (macOS, Linux, Windows)

Check dev/linux/integration.sh and dev\windows\integration.bat for more details.

4.6.4 Deep dives

This section contains a series of deep dives into particularly complex parts of conda.

conda install

In this document we will explore what happens in Conda from the moment a user types their installation command until the process is finished successfully. For the sake of completeness, we will consider the following situation:

- The user is running commands on a Linux x64 machine with a working installation of Miniconda.
- This means we have a base environment with conda, python, and their dependencies.
- The base environment is already preactivated for Bash. For more details on activation, check *conda init and conda activate*.

Ok, so... what happens when you run conda install numpy? Roughly, these steps:

- 1. Command line interface
 - argparse parsers
 - Environment variables
 - Configuration files
 - Context initialization
 - Delegation of the task
- 2. Fetching the index
 - Retrieving all the channels and platforms
 - A note on channel priorities
- 3. Solving the install request
 - Requested packages + prefix state = list of specs
 - Index reduction (sometimes)
 - Running the solver
 - · Post-processing the list of packages
- 4. Generating the transaction and the corresponding actions
- 5. Download and extraction
- 6. Integrity verification
- 7. Linking and unlinking files
- 8. Post-linking and post-activation tasks

What happens when you type conda install ... ?



Fig. 1: This figure shows the different processes and objects involved in handling a simple conda install command.

Command line interface

First, a quick note on an implementation detail that might be not obvious.

When you type conda install numpy in your terminal, Bash takes those three words and looks for a conda command to pass a list of arguments ['conda', 'install', 'numpy']. Before finding the conda executable located at CONDA_HOME/condabin, it probably finds the shell function defined here. This shell function runs the activation/deactivation logic on the shell if requested, or delegates over to the actual Python entry-points otherwise. This part of the logic can be found in conda.shell.

Once we are running the Python entry-point, we are in the conda.cli realm. The function called by the entry point is conda.cli.main:main(). Here, another check is done for shell.* subcommands, which generate the shell initializers you see in ~/.bashrc and others. If you are curious where this happens, it's conda.activate.

Since our command is conda install ..., we still need to arrive somewhere else. You will notice that the rest of the logic is delegated to conda.cli.main:_main(), which will invoke the parser generators, initialize the context and loggers, and, eventually, pass the argument list over to the corresponding command function. These four steps are implemented in four functions/classes:

- conda.cli.conda_argparse:generate_parser(): This uses argparse to generate the CLI. Each subcommand is initialized in separate functions. Note that the command line options are not generated dynamically from the Context object, but annotated manually. If this is needed (e.g. --repodata-fn is exposed in Context. repodata_fn), the dest variable of each CLI option should match the target attribute in the context object.
- 2. conda.base.context.Context: This object stores the configuration options in conda and will be initialized taking into account, among other things, the arguments parsed in the step above. This is covered in more detail in a separate deep dive: *conda config and context*.
- 3. conda.gateways.logging:initialize_logging(): Not too exciting and easy to follow. This part of the code base is more or less self-explanatory.
- 4. conda.cli.conda_argparse:do_call(): The argument parsing will populate a func value that contains the import path to the function responsible for that subcommand. For example, conda install is taken care of by conda.cli.main_install. By design, all the modules reported by func must contain an execute() function that implements the command logic. execute() takes the parsed arguments and the parser itself as arguments. For example, in the case of conda install, execute() only redirects to a certain mode in conda. cli.install:install().

Let's go take a look at that module now. conda.cli.install:install() implements the logic behind conda create, conda install, conda update and conda remove. In essence, they all deal with the same task: changing which packages are present in an environment. If you go and read that function, you will see there are several lines of code handling diverse situations (new environments, clones, etc.) before we arrive to the next section. We will not discuss them here, but feel free to explore that section. It's mostly ensuring that the destination prefix exists, whether we are creating a new environment and massaging some command line flags that would allow us to skip the solver (e.g. --clone).

More information on environments

Check the concepts for *Environments*.

Fetching the index

At this point, we are ready to start doing some work! All of the previous code was telling us what to do, and now we know. We want conda to *install* numpy on our base environment. The first thing we need to know is where we can find packages with the name numpy. The answer is... the channels!

Users download packages from conda channels. These are normally hosted at anaconda.org. A channel is essentially a directory structure with these elements:



More info on Channels

You can find some more user-oriented notes on Channels at *What is a "channel"*? and *Repository structure and index*. If you are interested in more technical details, check the corresponding documentation pages at conda-build.

The important bits are:

- A channel contains one or more platform-specific directories (linux-64, osx-64, etc.), plus a platform-agnostic directory called noarch. In conda jargon, these are also referred to as channel *subdirs*. Officially, the noarch subdirectory is enough to make it a conda channel; e.g. no platform subdirectory is necessary.
- Each *subdir* contains at least a **repodata**. **json** file: a gigantic dictionary with *all* the metadata for each package available on that platform.
- In most cases, the same subdirs also contain the *.tar.bz2 files for each of the published packages. This is what conda downloads and extracts once solving is complete. The anatomy of these files is well defined, both in content and naming structure. See *What is a package?*, *Package metadata* and/or Package naming conventions for more details.

Additionally, the channel's main directory might contain a channeldata.json file, with channel-wide metadata (this is not specific per platform). Not all channels include this, and in general it is not currently something that is commonly utilized.

Since conda's philosophy is to keep all packages ever published around for reproducibility, repodata.json is always growing, which presents a problem both for the download itself and the solver engine. To reduce download times and bandwidth usage, repodata.json is also served as a BZIP2 compressed file, repodata.json.bz2. This is what most conda clients end up downloading.

Note on 'current_repodata.json'

More *repodatas* variations can be found in some channels, but they are always reduced versions of the main one for the sake of performance. For example, current_repodata.json only contains the most recent version of each package, plus their dependencies. The rationale behind this optimization trick can be found here.

So, in essence, fetching the channel information means it can be expressed in pseudo-code like this:

```
platform = {}
noarch = {}
for channel in reversed(context.channels):
    platform_repodata = fetch_extract_and_read(
        channel.full_url / context.subdir / "repodata.json.bz2"
    )
    platform.update(platform_repodata)
    noarch_repodata = fetch_extract_and_read(
        channel.full_url / "noarch" / "repodata.json.bz2"
    )
    noarch.update(noarch_repodata)
```

Note that these dictionaries are keyed by *filename*, so higher priority channels will overwrite entries with the exact same filename (e.g. numpy-1.19-py36h87ha43_0.tar.bz2). If they don't have the same *filename* (e.g., same version and build number but different hash), this ambiguity will be resolved later in the solver, taking into account the channel priority mode.

In this example, context.channels has been populated through different, cascading mechanisms:

- The default settings as found in ~/.condarc or equivalent.
- The CONDA_CHANNELS environment variable (rare usage).
- The command-line flags, such as -c <channel>, --use-local or --override-channels.
- The channels present in a command-line *spec*. Remember that users can say channel::numpy instead of simply numpy to require that numpy comes from that specific channel. That means that the repodata for such channel needs to be fetched, too!

The items in context.channels are supposed to be conda.models.channels.Channel objects, but the Solver API also allows strings that refer to their name, alias or full URL. In that case, you can use Channel objects to parse and retrieve the full URL for each subdir using the Channel.urls() method. Several helper functions can be found in conda.core.index, if needed.

Sadly, fetch_extract_and_read() does not exist as such, but as a combination of objects. The main driving function is actually get_index(), which passes the channel URLs to fetch_index, a wrapper that delegates directly to conda.core.subdir_data.SubdirData objects. This object implements caching, authentication, proxies and other things that complicate the simple idea of "just download the file, please". Most of the logic is in SubdirData. _load(), which ends up calling conda.core.subdir_data.fetch_repodata_remote_request() to process the request. Finally, SubdirData._process_raw_repodata_str() does the parsing and loading.

Internally, the SubdirData stores all the package metadata as a list of PackageRecord objects. Its main usage is via .query() (one result at a time) or .query_all() (all possible matches). These .query* methods accept spec strings (e.g. numpy =1.14), MatchSpec and PackageRecord instances. Alternatively, if you want *all* records with no queries, use SubdirData.iter_records().

Tricks to reduce the size of the index

conda supports the notion of trying with different versions of the index in an effort to minimize the solution space. A smaller index means a faster search, after all! The default logic starts with current_repodata.json files in the channel, which contain only the latest versions of each package plus their dependencies. If that fails, then the full repodata.json is used. This happens *before* the Solver is even invoked.

The second trick is done within the classic solver logic (pycosat): an informed index reduction. In essence, the index (whether it's current_repodata.json or full repodata.json) is pruned by the solver, trying to keep only the parts that it anticipates will be needed. More details can be found on the get_reduced_index function. Interestingly, this optimization step also takes longer the bigger the index gets.

Channel priorities

context.channels returns an IndexedSet of Channel objects; essentially a list of unique items. The different channels in this list can have overlapping or even conflicting information for the same package name. For example, defaults and conda-forge will for sure contain packages that fullfil the conda install numpy request. Which one is chosen by conda in this case? It depends on the context.channel_priority setting: From the help message:

Accepts values of 'strict', 'flexible', and 'disabled'. The default value is 'flexible'. With strict channel priority, packages in lower priority channels are not considered if a package with the same name appears in a higher priority channel. With flexible channel priority, the solver may reach into lower priority channels to fulfill dependencies, rather than raising an unsatisfiable error. With channel priority disabled, package version takes precedence, and the configured priority of channels is used only to break ties.

In practice, channel_priority=strict is often the recommended setting for most users. It's faster to solve and causes fewer problems down the line. Check more details *here*.

Solving the install request

At this point, we can start asking the solver things. After all, we have loaded the channels into our index, building the catalog of available packages and versions we can install. We also have the command line instructions and configurations needed to customize the solver request. So, let's just do it: "Solver, please install numpy on this prefix using these channels as package sources".

The details are complicated, but in essence, the Solver will:

- 1. Express the requested packages, command line options and prefix state as MatchSpec objects
- 2. Query the index for the best possible match that satisfy those constraints
- 3. Return a list of PackageRecord objects

The full details are covered in *Solvers* if you are curious. Just keep in mind that point (1) is conda-specific, while (2) can be tackled, in principle, by any SAT solver.

Generating the transaction and the corresponding actions

The Solver API defines three public methods:

- .solve_final_state(): this is the core function, described in the section above. Given some input state, it returns an IndexedSet of PackageRecord objects that reflect what the final state of the environment should look like. This is the largest method, and its details are fully covered *here*.
- .solve_for_diff(): this method takes the final state and diffs it with the current state of the environment, discovering which old records need to be removed, and which ones need to be added.

• .solve_for_transaction(): this method takes the diff and creates a Transaction object for this operation. This is what the main CLI logic expects back from the solver.

So what is a Transaction object and why is it needed? Transactional actions were introduced in conda 4.3. They seem to be the last iteration of a set of changes designed to check whether conda would be able to download and link the needed packages (e.g. check that there is enough space on disk, whether the user has enough permissions for the target paths, etc.). For more info, refer to PRs #3571, #3301, and #3034.

The transaction is essentially a set of action objects. Each action is allowed to run some checks to determine whether it can be executed successfully. If that's not the case, the failed checks will signal the parent transaction that the whole operation needs to be aborted and rolled back to leave things in the state they were before running that conda command. It is also responsible for some of the messages you will see in the CLI output, like the reports of what will be installed, updated or removed.

Transactions and parallelism

Since the transaction object knows about all the actions that need to happen, it also enables parallelism for verifying, downloading and (un)linking tasks. The level of parallelism can be changed through the following context settings:

- default_threads
- verify_threads
- execute_threads
- repodata_threads
- fetch_threads

There's only one class of transaction in conda: LinkUnlinkTransaction. It only accepts one input parameter: a list of PrefixSetup objects, which are just namedtuple objects with the following fields. These are populated by Solver.solve_for_transaction after running Solver.solve_for_diff:

- target_prefix: the environment path the command is running on.
- unlink_precs: PackageRecord objects that need to be unlinked (removed).
- link_precs: PackageRecord objects that need to be linked (added).
- remove_specs: MatchSpec objects that need to be marked as removed in the history (the user asked for these packages to be uninstalled).
- update_specs: MatchSpec objects that need to be marked as added in the history (the user asked for these packages to be installed or updated).
- neutered_specs: MatchSpec objects that were already in history but had to be relaxed in order to avoid solving conflicts.

Whatever happens after instantiation depends on the content of these PrefixSetup objects. Sometimes, the transaction results in no actions (see the nothing_to_do property) because the request asked by the user is already fulfilled by the current state of the environment.

However, most of the time the transaction will involve a number of actions. This is done via two public methods:

- download_and_extract(): essentially a forwarder to instantiate and call ProgressiveFetchExtract, responsible for deciding which PackageRecords need to be downloaded and extracted to the packages cache.
- execute(): the core logic is layed out here. It involves preparing, verifying and performing the rest of the actions. Among others:
 - Unlinking packages (removing a package from the environment)
 - Linking (adding a package to the environment)

- Compiling bytecode (generating the pyc counterpart for each py module)
- Adding entry points (generate command line executables for the configured functions)
- Adding the JSON records (for each package, a JSON file is added to conda-meta/)
- Make menu items (create shortcuts for packages featuring a JSON file under Menu/)
- Remove menu items (remove the shortcuts created by that package)

It's important to notice that download and extraction happen separately from all the other actions. This separation is important and core to the idea of what a conda environment is. Essentially, when you create a new conda environment, you are not necessarily *copying* files over to the target prefix location. Instead, conda maintains a cache of every package ever downloaded to disk (both the tarball and the extracted contents). To save space and speed up environment creation and deletion, files are not copied over, but instead they are linked (usually via a hardlink). That's why these two tasks are separated in the transaction logic: you don't need to download and extract packages that are already in the cache; you only need to link them!

Transactions also drive reports

{

The type and number of actions can also be calculated by _make_legacy_action_groups(), which returns a list of *action groups* (one per PrefixSetup). Each action group is a just a dictionary following this specification:

```
"FETCH": Iterable[PackageRecord], # estimated by `ProgressiveFetchExtract`
"PREFIX": str,
"UNLINK": Iterable[PackageRecord],
"LINK: Iterable[PackageRecord],
}
```

These simpler action groups are only used for reporting, either via a processed text report (via print_transaction_summary) or just the raw JSON (via stdout_json_success). As you can see, they do not know anything about other types of tasks.

Download and extraction

conda maintains a cache of downloaded tarballs and their extracted contents to save disk space and improve the performance of environment modifications. This requires some code to check whether a given PackageRecord is already present in the cache, and, if it's not, how to download the tarball and extract its contents in a performant way. This is all handled by the ProgressiveFetchExtract class, which can instantiate up to two Action objects for each passed PackageRecord:

- CacheUrlAction: downloads (if remote) or copies (if local) a tarball to the cache location.
- ExtractPackageAction: extracts the contents of the tarball.

These two actions only take place *if* the package is not in cache yet and if it has already been extracted, respectively. They can also revert the changes if the transaction is aborted (either due to an error or because the user pressed Ctrl+C).

Populating the prefix

When all the necessary packages have been downloaded and extracted to the cache, it is time to start populating the prefix with the needed files. This means we need to:

- 1. For each package that needs to be unlinked, run the pre-unlink logic (deactivate and pre-unlink scripts, as well as shortcut removal, if needed) and then unlink the package files.
- 2. For each package that needs to be linked, create the links and run the post-link logic (post-link and activate scripts, as well as creating the shortcuts, if needed).

Note that when you are updating a package version, you are actually removing the installed version entirely and then adding the new one. In other words, an update is just unlink+link.

How is this implemented? For each PrefixSetup object passed to UnlinkLinkTransaction, a number of ActionGroup namedtuples (one per task *category*) will be instantiated and grouped together in a PrefixActionGroup namedtuple. These are then passed to .verify(). This method will take each action, run its checks and, if all of them passed, will allow us to perform the actual execution in .execute(). If one of them fails, the transaction can be aborted and rolled back.

For all this to work, each action object follows the PathAction API contract:

```
class PathAction:
  _verified = False
  def verify(self):
    "Run checks to assess if the action can proceed"
  def execute(self):
    "Perform the action"
  def reverse(self):
    "Undo execute"
  def cleanup(self):
    "Remove artifacts from verification, execution or reversal"
  @property
  def verified(self):
    "True if verification was run and successful"
  }
}
```

Additional PathAction subclasses will add more methods and properties, but this is what the transaction execution logic expects. To support all the different actions involved in populating the prefix, the PathAction class tree holds quite the graph:

PathAction PrefixPathAction CreateInPrefixPathAction LinkPathAction PrefixReplaceLinkAction MakeMenuAction CreateNonadminAction CreatePythonEntryPointAction CreatePrefixRecordAction UpdateHistoryAction RemoveFromPrefixPathAction

(continues on next page)

(continued from previous page)

UnlinkPathAction RemoveLinkedPackageRecordAction RemoveMenuAction RegisterEnvironmentLocationAction UnregisterEnvironmentLocationAction CacheUrlAction ExtractPackageAction

MultiPathAction CompileMultiPycAction AggregateCompileMultiPycAction

You are welcome to read on the docstring for each of those classes to understand which each one is doing; all of them are listed under conda.core.path_actions. In the following sections, we will only comment on the most important ones.

Linking the files in the environment

When conda *links* a file from the cache location to the prefix location, it can actually mean three different actions:

- 1. Creating a soft link
- 2. Creating a hard link
- 3. Copying the file

The difference between soft links and hard links is subtle, but important. You can find more info on the differences elsewhere (e.g. here), but for our purposes it means that:

- Hard links are cheaper to resolve, behave like a real file, but can only link files in the same mount point.
- Soft links can link files across mount points, but they don't behave exactly like files (more like forwarders), so it's possible that they break assumptions made in certain pieces of code.

Most of the time, conda will try to hard link files and, if that fails, it will copy them over. Copying a file is an expensive disk operation, both in terms of time and space, so it should be the last option. However, sometimes it's the only way. Especially, when the file needs to be modified to be used in the target prefix.

Ummm... what? Why would conda modify a file to install it? This has to do with relocatability. When a conda package is created, conda-build creates up to three temporary environments:

- Build environment: where compilers and other build tools are installed, separate from the host environment to support cross-compilation.
- Host environment: where build-time dependencies are installed, together with the package you are building.
- Test environment: where run-time dependencies are installed, together with the package you just built. It simulates what will happen when a user installs the package so you can run arbitrary checks on your package.

When you are building a package, references to the build-time paths can leak into the content of some files, both text and binary. This is not a problem for users who build their own packages from source, since they can choose this path and leave the files there. However, this is almost never true for conda packages. They are created in one machine and installed in another. To avoid "path not found" issues and other problems, conda-build marks those packages that hold references to the build-time paths by replacing them with placeholders. At install-time, conda will replace those placeholders with the target prefix and everything works! But there's a problem: we can't modify the files on the cache location because they might be used across environments (with obviously different paths). In these cases, files are not linked, but copied; the path replacement only happens on the target copy, of course!

How does conda know how to link a given package or, more precisely, its extracted files? All of this is determined in the preparation routines contained in UnlinkLinkTransaction._prepare() (more specifically, through determine_link_type()), as well as LinkPathAction.create_file_link_actions().

Note that the (un)linking actions also include the execution of pre-(un)link and post-(un)link scripts, if listed.

Action groups and actions, in detail

Once the old packages have been removed and the new ones have been linked through the appropriate means, we are done, right? Not yet! There's one step left: the post-linking logic.

It turns out that there's a number of smaller tasks that need to happen to make conda as convenient as it is. You can find all of them listed a few paragraphs above, but we'll cover them here, too. The execution order is determined in UnlinLinkTransaction._execute. All the possible groups are listed under PrefixActionGroup. Their order is roughly how they happen in practice:

- 1. remove_menu_action_groups, composed of RemoveMenuAction actions.
- 2. unlink_action_groups, includes UnlinkPathAction, RemoveLinkedPackageRecordAction, as well as the logic to run the pre- and post-unlink scripts.
- 3. unregister_action_groups, basically a single UnregisterEnvironmentLocationAction action.
- 4. link_action_groups, includes LinkPathAction, PrefixReplaceLinkAction, as well as the logic to run pre- and post-link scripts.
- 5. entry_point_action_groups, a collection of CreatePythonEntryPointAction actions.
- 6. register_action_groups, a single RegisterEnvironmentLocationAction action.
- 7. compile_action_groups, several CompileMultiPycAction that end up aggregated as a AggregateCompileMultiPycAction for performance.
- 8. make_menu_action_groups, composed of MakeMenuAction actions.
- 9. prefix_record_groups, records installed packages in the environment via CreatePrefixRecordAction actions.

Let's discuss these actions groups for the command we are describing in this guide: conda install numpy. The solution given by the solver says we need to:

- unlink Python 3.9.6
- link Python 3.9.9
- link numpy 1.19

This is what would happen:

- 1. No menu items are removed because Python 3.9.6 didn't create any.
- 2. Pre-unlink scripts for Python 3.9.6 would run, but in this case there are none.
- 3. Python 3.9.6 files are removed from the environment. This can be parallelized.
- 4. Post-unlink scripts are run, if any.
- 5. Pre-link scripts are run for Python 3.9.9 and numpy 1.19, if any.
- 6. Files in the Python 3.9.9 and numpy 1.19 packages are linked and/or copied to the prefix. This can be parallelized.

- 7. Entry points are created for the new packages, if any.
- 8. Post-link scripts are run.
- 9. pyc files are generated for the new packages.
- 10. The new packages are registered under conda-meta/.
- 11. The menu shortcuts are created for the new packages, if any.

Any of these steps can fail with a given exception. If that's the case, the first of those exceptions is printed to STDOUT. Additionally, if rollback_enabled is properly configured in the context, the transaction will be rolled back by calling the .reverse() method in each action, from last to first.

If no exceptions are reported, then the actions can run their cleanup routines.

And that's it! If this command had resulted in a new environment being created, you would get a message telling you how to activate the newly created environment.

Conclusion

This is what happens when you type conda install. It might be a bit more involved than you initially thought, but it all boils down to only some steps. TL;DR:

- 1. Parse arguments and initialize the context
- 2. Download and build the index
- 3. Tell the solver what we want
- 4. Convert the solution into a transaction
- 5. Verify and run each action contained in the transaction

conda init and conda activate

conda ships *virtual environments* by design. When you install Anaconda or Miniconda, you obtain a base environment that is essentially a regular environment with some extra checks. These checks have to do with what the conda command really is and how it is installed in your system.

Base prefix vs target prefix

Originally, the base installation for conda was called the *root* environment. Every other environment lived under envs/ in that root environment. The root environment was later renamed to *base*, but the code still distinguishes between base and target using the old terminology:

- context.root_prefix: the path where the base conda installation is located.
- context.target_prefix: the environment conda is running a command on. Usually defaults to the activated environment, unless -n (name) or -p (prefix) is specified in the command line. Note that if you are operating on the base environment, the target prefix will have the same value as the root prefix.

When you type conda in your terminal, your shell will try to find either:

- a shell function named conda
- an executable file named conda in your PATH directories

If your conda installation has been properly initialized, it will find the shell function. If not, it might find the conda executable if it *happens* to be in PATH, but this is most often not the case. That's why initialization is there to begin with!

Conda initialization

Why is initialization needed at all to begin with? There are several reasons:

- Activation requires interacting with the shell context very closely
- It does not pollute PATH unnecessarily
- Improves performance in certain operations

The main idea behind initialization is to provide a conda shell function that allows the Python code to interact with the shell context more intimately. It also allows a cleaner PATH manipulation and snappier responses in some conda commands.

The conda shell function is mainly a forwarder function. It will delegate most of the commands to the real conda executable driven by the Python library. However, it will intercept two very specific subcommands:

- conda activate
- conda deactivate

This interception is needed because activation/deactivation requires exporting (or unsetting) environment variables back to the shell session (and not just temporarily in the Python process). This will be discussed in the next section.

So how is initialization performed? This is the job of the conda init subcommand, driven by the conda.cli. main_init module, which depends directly on the conda.core.initialize module. Let's see how this is implemented.

conda init will initialize a shell permanently by writing some shell code in the relevant startup scripts of your shell (e.g. ~/.bashrc). This is done through different functions defined in conda.core.initialize, namely:

- init_sh_user: initializes a Posix shell (like Bash) for the current user.
- init_sh_system: initializes a Posix shell (like Bash) globally, for all users.
- init_fish_user: initializes the Fish shell for the current user.
- init_xonsh_user: initializes the Xonsh shell for the current user.
- init_cmd_exe_registry: initializes Cmd.exe through the Windows Registry.
- init_powershell_user: initializes Powershell for the current user.
- init_long_path: configures Windows to support longer paths.

What each function does depends on the nature of each shell. In the case of Bash shells, the underlying Activator subclass (more below) can generate the hook code dynamically. In other Posix shells and Powershell, a script is sourced from its location in the base environment. With Cmd, the changes are introduced through the Windows Registry. The end result is the same: they will end up defining a conda shell function with the behavior described above.

Conda activate

All Activator classes can be found under conda.activate. Their job is essentially to write shell-native code programmatically. As of conda 4.11, these are the supported shells and their corresponding activators

- posix, ash, bash, dash, zsh: all driven by PosixActivator.
- csh, tcsh: CshActivator.
- xonsh: XonshActivator.
- cmd.exe: CmdExeActivator.
- fish: FishActivator.
- powershell: PowerShellActivator.

You can add all these classes through the conda shell.<key> command, where key is any of the names in the list above. These CLI interface offers several subcommands, connected directly to methods of the same name:

- activate: writes the shell code to activate a given environment.
- deactivate: writes the shell code to deactivate a given environment.
- hook: writes the shell code to register the initialization code for the conda shell code.
- commands: writes the shell code needed for autocompletion engines.
- reactivate: writes the shell code for deactivation followed by activation.

To be clear, we are saying these functions only *write* shell code. They do *not* execute it! This needs to be done by the shell itself! That's why we need a conda shell function, so these shell strings can be eval'd or source'd in-session.

Let's see what happens when you run conda shell.bash activate:

```
$ conda shell.bash activate
export PATH='/Users/username/.local/anaconda/bin:/opt/homebrew/bin:/opt/homebrew/sbin:/
.usr/local/bin:/usr/bin:/usr/sbin:/Users/username/.local/anaconda/condabin:/
.opt/homebrew/bin:/opt/homebrew/sbin'
unset CONDA_PREFIX_1
PS1='(base) '
export CONDA_PREFIX='/Users/username/.local/anaconda'
export CONDA_SHLVL='1'
export CONDA_DEFAULT_ENV='base'
export CONDA_DEFAULT_ENV='base'
export CONDA_PROMPT_MODIFIER='(base) '
export CONDA_EXE='/Users/username/.local/anaconda/bin/conda'
export _CE_M=''
export _CE_CONDA=''
export CONDA_PYTHON_EXE='/Users/username/.local/anaconda/bin/python'
```

See? It only wrote some shell code to stdout, but it wasn't executed. We would need to do this to actually run it:

\$ eval "\$(conda shell.bash activate)"

And this is essentially what conda activate does: it calls the registered shell activator to obtain the required shell code and then it evals it. In some shells with no eval equivalent, a temporary script is written and sourced or called. The final effect is the same.

Ok, but what is that shell code doing? Mainly setting your PATH correctly so the executables of your base environment can be found (like python). It also sets some extra variables to keep a reference to the path of the currently active environment, the shell prompt modifiers and other information for conda internals.

This command can also generate the code for any other environment you want, not just base. Just pass the name or path:

```
$ conda shell.bash activate mamba-poc
PS1='(mamba-poc) '
export PATH='/Users/username/.local/anaconda/envs/mamba-poc/bin:/opt/homebrew/bin:/opt/
..homebrew/sbin:/usr/local/bin:/usr/bin:/usr/sbin:/Users/username/.local/
..anaconda/condabin:/opt/homebrew/bin:/opt/homebrew/sbin'
export CONDA_PREFIX='/Users/username/.local/anaconda/envs/mamba-poc'
export CONDA_SHLVL='2'
export CONDA_DEFAULT_ENV='mamba-poc'
export CONDA_DEFAULT_ENV='mamba-poc'
export CONDA_PROMPT_MODIFIER='(mamba-poc) '
export CONDA_EXE='/Users/username/.local/anaconda/bin/conda'
export _CE_M=''
export _CE_CONDA=''
export CONDA_PYTHON_EXE='/Users/username/.local/anaconda/bin/python'
export CONDA_PREFIX_1='/Users/username/.local/anaconda'
```

Now the paths are different, as well as some numbers (e.g. CONDA_SHLVL). This is used by conda to keep track of what was activated before, so when you deactivate the last one, you can get back to the previous one seamlessly.

Activation/deactivation scripts

The activation/deactivation code can also include calls to activation/deactivation scripts. If present in the appropriate directories for your shell (e.g. CONDA_PREFIX/etc/conda/activate.d/), they will be called before deactivation or after activation, respectively. For example, compilers usually set up some environment variables to help configure the default flags. This is what happens when you activate an environment that contains Clang and Gfortran:

```
$ conda shell.bash activate compilers
PS1='(compilers) '
export PATH='/Users/username/.local/anaconda/envs/compilers/bin:/opt/homebrew/bin:/opt/
→homebrew/sbin:/usr/local/bin:/usr/bin:/usr/sbin:/usr/sbin:/usr/local/
anaconda/condabin:/opt/homebrew/bin:/opt/homebrew/sbin'
export CONDA_PREFIX='/Users/username/.local/anaconda/envs/compilers'
export CONDA_SHLVL='2'
export CONDA_DEFAULT_ENV='compilers'
export CONDA_PROMPT_MODIFIER='(compilers) '
export CONDA_EXE='/Users/username/.local/anaconda/bin/conda'
export _CE_M=''
export _CE_CONDA=''
export CONDA_PYTHON_EXE='/Users/username/.local/anaconda/bin/python'
export CONDA_PREFIX_1='/Users/username/.local/anaconda'
. "/Users/username/.local/anaconda/envs/compilers/etc/conda/activate.d/activate-gfortran_
→osx-arm64.sh"
. "/Users/username/.local/anaconda/envs/compilers/etc/conda/activate.d/activate_clang_
→osx-arm64.sh"
. "/Users/username/.local/anaconda/envs/compilers/etc/conda/activate.d/activate_clangxx_
\rightarrow osx-arm64.sh"
```

Those three lines are sourcing the relevant scripts. Similarly, for deactivation, notice how the deactivation scripts are executed first this time:

```
$ conda shell.bash deactivate
export PATH='/Users/username/.local/anaconda/bin:/opt/homebrew/bin:/opt/homebrew/sbin:/
usr/local/bin:/usr/bin:/bin:/usr/sbin:/Sbin:/Users/username/.local/anaconda/condabin:/
→opt/homebrew/bin:/opt/homebrew/sbin'
. "/Users/username/.local/anaconda/envs/compilers/etc/conda/deactivate.d/deactivate_

→clangxx_osx-arm64.sh"

. "/Users/username/.local/anaconda/envs/compilers/etc/conda/deactivate.d/deactivate_
\rightarrow clang_osx-arm64.sh"
. "/Users/username/.local/anaconda/envs/compilers/etc/conda/deactivate.d/deactivate-
→gfortran_osx-arm64.sh"
unset CONDA_PREFIX_1
PS1='(base) '
export CONDA_PREFIX='/Users/username/.local/anaconda'
export CONDA_SHLVL='1'
export CONDA_DEFAULT_ENV='base'
export CONDA_PROMPT_MODIFIER='(base) '
export CONDA_EXE='/Users/username/.local/anaconda/bin/conda'
export _CE_M=''
export _CE_CONDA=''
export CONDA_PYTHON_EXE='/Users/username/.local/anaconda/bin/python'
```

conda config and context

The context object is central to many parts of the conda codebase. It serves as a centralized repository of settings. You normally import the singleton and access its (many) attributes directly:

```
from conda.base.context import context
context.quiet
# False
```

This singleton is initialized from a cascade of different possible sources. From lower to higher precedence:

- 1. Default values hardcoded in the Context class. These are defined via class attributes.
- 2. Values defined in the configuration files (.condarc), which have their own precedence.
- 3. Values set by the corresponding command line arguments, if any.
- 4. Values defined by their corresponding CONDA_* environment variables, if present.

The mechanism implementing this behavior is an elaborate object with several types of objects involved.

Anatomy of the Context class

conda.base.context.Context is an conda-specific subclass of the application-agnostic conda.common. configuration.Configuration class. This class implements the precedence order for the instantiation of each defined attribute, as well as the overall validation logic and help message reporting. But that's it, it's merely a storage of ParameterLoader objects which, in turn, instantiate the relevant Parameter subclasses in each attribute. Roughly:

```
class MyConfiguration(Configuration):
    string_field = ParameterLoader(PrimitiveParameter("default", str))
    list_of_int_field = ParameterLoader(SequenceParameter([1, 2, 3], int))
    map_of_foat_values_field = ParameterLoader(MapParameter({"key": 1.0}, float))
```

When MyConfiguration is instantiated, those class attributes are populated by the .raw_data dictionary that has been filled in with the values coming from the precedence chain stated above. The raw_data dictionary contains RawParameter objects, subclassed to deal with the specifics of their origin (YAML file, environment variable, command line flag). Each ParameterLoader object will pass the RawParameter object to the .load() method of its relevant Parameter subclass, which are designed to return their corresponding LoadedParameter object counterpart.

It's a bit confusing, but the delegation happens like this:

- 1. The Configuration subclass parses the raw values of the possible origins and stores them as the relevant RawParameter objects, which can be:
 - EnvRawParameter: for those coming from an environment variable
 - ArgParseRawParameter: for those coming from a command line flag
 - YamlRawParameter: for those coming from a configuration file
 - DefaultValueRawParameter: for those coming from the default value given to ParameterLoader
- 2. Each Configuration attribute is a ParameterLoader, which implements the property protocol via __get__. This means that, upon attribute access (e.g. MyConfiguration.string_field), the ParameterLoader can execute the loading logic. This means finding potential type matches in the raw data, loading them as LoadedParameter objects and merging them with the adequate precedence order.

The merging policy depends on the (Loaded)Parameter subtype. Below is a list of available subtypes:

- PrimitiveParameter: holds a single scalar value of type str, int, float, complex, bool or NoneType.
- SequenceParameter: holds an iterable (list) of other Parameter objects.
- MapParameter: holds a mapping (dict) of other Parameter objects.
- ObjectParameter: holds an object with attributes set to Parameter objects.

The main goal of the Parameter objects is to implement how to typify and turn the raw values into their Loaded counterparts. These implement the validation routines and define how parameters for the same key should be merged:

- PrimitiveLoadedParameter: value with highest precedence replaces the existing one.
- SequenceLoadedParameter: extends with no duplication, keeping precedence.
- MapLoadedParameter: cascading updates, highest precedence kept.
- ObjectLoadedParameter: same as Map.

After all of this, the LoadedParameter objects are *typified*: this is when type validation is performed. If everything goes well, you obtain your values just fine. If not, the validation errors are raised.

Take into account that the result is cached for faster subsequent access. This means that even if you change the value of the environment variables responsible for a given setting, this won't be reflected in the context object until you refresh it with conda.base.context.reset_context().

Do not modify the Context object!

ParameterLoader does not implement the __set__ method of the property protocol, so you can freely override an attribute defined in a Configuration subclass. You might think that this will redefine the value after passing through the validation machinery, but that's not true. You will simply overwrite it entirely with the raw value and that's probably not what you want.

Instead, consider the context object immutable. If you need to change a setting at runtime, it is probably *A Bad Idea*. The only situation where this is acceptable is during testing.

Setting values in the different origins

There's some magic behind the possible origins for the settings values. How these are tied to the final Configuration object might not be obvious at first. This is different for each RawParameter subclass:

- DefaultValueRawParameter: Users will never see this one. It only wraps the default value passed to the ParameterLoader class. Safe to ignore.
- YamlRawParameter: This one takes a YAML file and parses it as a dictionary. The keys in this file must match the attribute names in the Configuration class exactly (or one of their aliases). Matching happens automatically once this is properly set up. How the values are parsed depends on the YAML Loader, set internally by conda.
- EnvRawParameter: Values coming from certain environment variables can make it to the Configuration instance, provided they are formatted as <APP_NAME>_<PARAMETER_NAME>, all uppercase. The app name is defined by the Configuration subclass. The parameter name is defined by the attribute name in the class, transformed to upper case. For example, context.ignore_pinned can be set with CONDA_IGNORE_PINNED. The value of the variable is parsed in different ways depending on the type:
 - PrimitiveParameter is the easy one. The environment variable string is parsed as the expected type. Booleans are a bit different since several strings are recognized as such, and in a case-insensitive way:
 - * True can be set with true, yes, on and y.
 - * False can be set with false, off, n, no, non, none and "" (empty string).
 - SequenceParameter can specify their own delimiter (e.g.,), so the environment variable string is processed into a list.
 - MapParameter and ObjectParameter do not support being set with environment variables.
- ArgParseRawParameter: These are a bit different because there is no automated mechanism that ties a given command line flag to the context object. This means that if you add a new setting to the Context class and you want that available in the CLI as a command line flag, you have to add it yourself. If that's the case, refer to conda.cli.conda_argparse and make sure that the dest value of your argparse.Argument matches the attribute name in Context. This way, Configuration.__init__ can take the argparse.Namespace object, turn it into a dictionary, and make it pass through the loading machinery.

Solvers

The guide *conda install* didn't go into details of the solver black box. It did mention the high-level Solver API and how conda expects a transaction out of it, but we never got to learn what happens *inside* the solver itself. We only covered these three steps:

The details are complicated, but in essence, the solver will:

- 1. Express the requested packages, command line options and prefix state as MatchSpec objects
- 2. Query the index for the best possible match that satisfy those constraints
- 3. Return a list of PackageRecord objects.

How do we transform the prefix state and configurations into a list of MatchSpec objects? How are those turned into a list of PackageRecord objects? Where are those PackageRecord objects coming from? We are going to cover these aspects in detail here.

MatchSpec vs PackageRecord

First, let's define what each object does:

- PackageRecord objects represent a concrete package tarball and its contents. They follow specific naming conventions and expose several fields. Inspect them directly in the class code.
- MatchSpec objects are essentially a query language to find PackageRecord objects. Internally, conda will translate your command line requests, like numpy>=1.19, python=3.* or pytorch=1.8.*=*cuda*, into instances of this class. This query language has its own syntax and rules, detailed here. The most important fields of a MatchSpec object are:
 - name: the name of the package (e.g. pytorch); always expected.
 - version: the version constraints (e.g. 1.8.*); can be empty but if build is set, set it to * to avoid issues with the .conda_build_form() method.
 - build: the build string constraints (e.g. *cuda*); can be empty.

Create a MatchSpec object from a PackageRecord instance

You can create a MatchSpec object from a PackageRecord instance using the .to_match_spec() method. This will create a MatchSpec object with its fields set to exactly match the originating PackageRecord.

Note that there are two PackageRecord subclasses with extra fields, so we need to distinguish between three types, all of them useful:

- PackageRecord: A record as present in the index (channel).
- PackageCacheRecord: A record already extracted in the cache. Contains extra fields for the tarball path in disk and its extracted directory.
- PrefixRecord: A record installed in a prefix. Same as above, plus fields for the files that make the package and how they were linked in the prefix. It can also host information about which MatchSpec string resulted in this record being installed.

Remote state: the index

So the solver takes MatchSpec objects, queries the index for the best match and returns PackageRecord objects. Perfect. What's the index? It's the result of aggregating the requested conda channels in a single entity. For more information, check *Fetching the index*.

Local state: the prefix and context

When you do conda install numpy, do you think the solver will just see something like specs=[MatchSpec("numpy")]? Well, not that quick. The explicit instructions given by the user are only one part of the request we will send to the solver. Other pieces of implicit state are taken into account to build the final request. Namely, the state of your prefix. In total, these are the ingredients of the solver request:

1. Packages already present in your environment, if you are not *creating* a new one. This is exposed through the conda.core.prefix_data.PrefixData class, which provides an iterator method via .iter_records(). As we saw before, this yields conda.models.records.PrefixRecord objects, a PackageRecord subclass for installed records.

- 2. Past actions you have performed in that environment; the *History*. This is a journal of all the conda install|update|remove commands you have run in the past. In other words, the *specs* matched by those previous actions will receive extra protections in the solver.
- 3. Packages included in the *aggressive updates* list. These packages are always included in any requests to make sure they stay up-to-date under all circumstances.
- 4. Packages pinned to a specific version, either via pinned_packages in your .condarc or defined in a \$PREFIX/ conda-meta/pinned file.
- 5. In new environments, packages included in the create_default_packages list. These specs are injected in each conda create command, so the solver will see them as explicitly requested by the user.
- 6. And, finally, the specs the user is asking for. Sometimes this is explicit (e.g. conda install numpy) and sometimes a bit implicit (e.g. conda update --all is telling the solver to add all installed packages to the update list).

All of those sources of information produce a number a of MatchSpec objects, which are then combined and modified in very specific ways depending on the command line flags and their origin (e.g. specs coming from the pinned packages won't be modified, unless the user asks for it explicitly). This logic is intricate and will be covered in the next sections. A more technical description is also available in *Technical specification: solver state*.



Fig. 2: Local variables affect the solving process explicitly and implicitly. As seen in *in the conda install deep dive*, the main actor is the conda.core.solve.Solver class. Before invoking the SAT solver, we can describe nine steps:

- 1. Instantiate the Solver class with the user-requested packages and the active environment (target prefix)
- 2. Call the solve_for_transaction() method on the instance, which calls solve_for_diff().
- 3. Call solve_final_state(), which takes some more arguments from the CLI.
- 4. Under some circumstances, we can return early (e.g. the packages are already installed).
- 5. If we didn't return early, we collect all the local variables into a list of MatchSpec objects.

For steps six to nine, see this figure.

Inside the Solver: formulating the problem



Fig. 3: The remote variables in a solve refer to, essentially, the package index (channels). This figure describes nine steps, focusing on 6-9. For steps 1-5, see *the previous figure*.

- 6. All the channels need to be fetched by now, but they have to be aggregated and reduced so the solver only handles the relevant bits. This step transforms "channels" into a list of available PackageRecord objects.
- 7. This is where the SAT solver will act. It will use the list of MatchSpec objects to pick a number of PackageRecord entries from the index, thus building the "final state of the solved environment". This is detailed later in this deep dive guide, if you need more info.
- 8. solve_for_diff takes the final state and compares it to the initial state, generating the differences between them (e.g. package A was updated to version 1.2, package B was removed).
- 9. solve_for_transaction takes the diff and some more metadata in the instance to generate the Transaction object.

The high-level logic in conda.cli.install

The full solver logic does not start at the conda.core.solve.Solver API, but before that, all the way up in the conda.cli.install module. Here, some important decisions are already made:

- Whether the solver is not needed at all because:
 - The operation is an explicit package install
 - The user requested to roll back to a history checkpoint
 - We are just creating a copy of an existing environment (cloning)
- Which repodata source to use (see *here*). It not only depends on the current configuration (via .condarc or command line flags), but also on the value of use_only_tar_bz2.
- Whether the solver should start by freezing all installed packages (default for conda install and conda remove in existing environments).
- If the solver does not find a solution, whether we need to retry again without freezing the installed packages for the current repodata variant or if we should try with the next one.

So, roughly, the global logic there follows this pseudocode:

```
if operation in (explicit, rollback, clone):
    transaction = handle_without_solver()
else:
   repodatas = from_config or ("current_repodata.json", "repodata.json")
    freeze = (is_install or is_remove) and env_exists and update_modifier not in argv
    for repodata in repodatas:
        try:
            transaction = solve_for_transaction(...)
        except:
            if repodata is last:
                raise
            elif freeze:
                transaction = solve_for_transaction(freeze_installed=False)
            else:
                continue # try next repodata
handle_txn(transaction)
```

Check this other figure for a schematic representation of this pseudocode.

We have, then, two reasons to re-run the full solver logic:

- Freezing the installed packages didn't work, so we try without freezing again.
- Using current_repodata did not work, so we try with full repodata.

These two strategies are stacked so in the end, before eventually failing, we will have tried four things:

- 1. Solve with current_repodata.json and freeze_installed=True
- 2. Solve with current_repodata.json and freeze_installed=False
- 3. Solve with repodata.json and freeze_installed=True
- 4. Solve with repodata.json and freeze_installed=False

Interestingly, those strategies are designed to improve conda's average performance, but they should be seen as a risky bet. Those attempts can get expensive!

How to ask for a simpler approach

If you want to try the full thing without checking whether the optimized solves work, you can override the default behaviour with these flags in your conda install commands:

- --repodata-fn=repodata.json: do not use current_repodata.json
- --update-specs: do not try to freeze installed

Then, the Solver class has its own internal logic, which also features some retry loops. This will be discussed later and summarized.

Early exit tasks

Some tasks do not involve the solver at all. Let's enumerate them:

- Explicit package installs: no index or prefix state needed.
- Cloning an environment: the index might be needed if the cache has been cleared.
- History rollback: currently broken.
- Forced removal: prefix state needed. This happens in the Solver class.
- Skip solve if already satisfied: prefix state needed. This happens in the Solver class.

Explicit package installs

These commands do not need a solver because the requested packages are expressed with a direct URL or path to a specific tarball. Instead of a MatchSpec, we already have a PackageRecord-like entity! For this to work, all the requested packages need to be URLs or paths. They can be typed in the command line or in a text file including a @EXPLICIT line.

Since the solver is not involved, the dependencies of the explicit package(s) are not processed at all. This can leave the environment in an *inconsistent state*, which can be fixed by running conda update --all, for example.

Explicit installs are taken care of by the explicit function.

Cloning an environment

conda create has a --clone flag that allows you to create a fully-working copy of an existing environment. This is needed because you cannot relocate an environment using cp, mv, or your favorite file manager without unintended consequences. Some files in a conda environment might contain hardcoded paths to existing files in the original location, and those references will break if cp or mv is utilized (conda environments *can* be renamed via the conda rename command, however; see the *following section* for more information).

The clone_env function implements this functionality. It essentially takes the source environment, generates the URLs for each installed packages (filtering conda, conda-env and their dependencies) and passes the list of URLs to explicit(). If the source tarballs are not in the cache anymore, it will query the index for the best possible match for the current channels. As such, there's a slim chance that the copy is not exactly a clone of the original environment.

Renaming an environment

When the conda rename command is used to rename an already-existing environment, please keep in mind that the solver is not invoked at all, since the command essentially does a conda create --clone and conda remove --all of the environment.

History rollback

conda install has a --revision flag, which allows you to revert the state of the environment to a previous one. This is done through the History file, but its current implementation can be considered broken. Once fixed, we will cover it in detail.

Forced removals

Similar to explicit installs, you can remove a package without performing a full solve. If conda remove is invoked with --force, the specified package(s) will be removed directly, without analyzing their dependency tree and pruning the orphans. This can only happen after querying the active prefix for the installed packages, so it is handled in the Solver class. This part of the logic returns the list of PackageRecord objects already found in the PrefixData list after filtering out the ones that should be removed.

Skip solve if already satisfied

conda install and update have a rather obscure flag: -S, --satisfied-skip-solve:

Exit early and do not run the solver if the requested specs are satisfied. Also skips aggressive updates as configured by 'aggressive_update_packages'. Similar to the default behavior of 'pip install'.

This is also implemented at the Solver level, because we also need a PrefixData instance. It essentially checks if all of the passed MatchSpec objects can match a PackageRecord already in prefix. If that's the case, we return the installed state as-is. If not, we proceed for the full solve.

Details of Solver.solve_final_state()

Note

From here on, the document only covers the classic solver logic (which uses pycosat). The libmamba solver has a different approach and is not documented here. Please refer to its documentation for more information.

This is where most of the intricacies of the conda logic are defined. In this step, the configuration, command line flags, user-requested specs and prefix state are aggregated to query the current index for the best match.

The aggregation of all those state bits will result in a list of MatchSpec objects. While it's easy to establish which package names will make it to the list, deciding which version and build string constraints the specs carry is a bit more involved.

This is currently implemented in the conda.core.solve.Solver class. Its main goal is to populate the specs_map dictionary, which maps package names (str) to MatchSpec objects. This happens at the beginning of the . solve_final_state() method. The full details of the specs_map population are covered in the *solver state technical specification*, but here's a little map of what submethods are involved:

- 1. Initialization of the SolverStateContainer: Often abbreviated as ssc, it's a helper class to store some state across attempts (remember there are several retry loops). Most importantly, it stores two key attributes (among others):
 - specs_map: same as above. This is where it lives across solver attempts.
 - solution_precs: a list of PackageRecord objects. It stores the solution returned by the SAT solver. It's always initialized to reflect the installed packages in the target prefix.
- 2. Solver._collect_all_metadata(): Initializes the specs_map with the specs found in the history or with the specs corresponding to the installed records. This method delegates to Solver._prepare(). This initializes the index by fetching the channels and reducing it. Then, a conda.resolve.Resolve instance is created with that index. The index is stored in the Solver instance as ._index and the Resolve object as ._r. They are also kept around in the SolverStateContainer, but as public attributes: .index and .r, respectively.
- 3. Solver._remove_specs(): If conda remove was called, it removes the relevant specs from specs_map.
- 4. Solver._add_specs(): For all the other conda commands (create, install, update), it adds (or modifies) the relevant specs to specs_map. This is one of the most complicated pieces of logic in the class!

Check the other parts of the Solver API

You can check the rest of the Solver API here.

At this point, the specs_map is adequately populated and we can call the SAT solver wrapped by the conda.resolve. Resolve class. This is done in Solver._run_sat(), but this method does some other things before actually solving the SAT problem:

- Before calling ._run_sat(), inconsistency analysis is performed via Solver. _find_inconsistent_packages. This will preemptively remove certain PackageRecord objects from ssc.solution_precs if Resolve.bad_installed() determined they were causing inconsistencies. This actually runs a series of small solves to check that the installed records form a satisfiable set of clauses. Those that prevent that solution from being found are annotated as such and ignored during the real solve later.
- Make sure the requested package names are available in the index.
- Anticipate and minimize potentially conflicting specs. This happens in a while loop fed by Resolve. get_conflicting_specs(). If a spec is found to be conflicting, it is *neutered*: a new MatchSpec object is created, but without version and build string constrains (e.g. numpy >=1.19 becomes just numpy). Then, Resolve.get_conflicting_specs() is called again, and the loop continues until convergence: the list of conflicts cannot be reduced further, either because there are no conflicts left or because the existing conflicts cannot be resolved by constraint relaxation.
- Now, the SAT solver is called. This happens via Resolve.solve(). More on this below.
- If the solver failed, then UnsatisfiableError is raised. Depending on which attempt we are on, conda will try again with non-frozen installed packages or a different repodata, or it will give up and analyze the conflict cause core. This will be detailed later.
- If the solver succeeded, some bookkeeping needs to be done:
 - Neutered specs that happened to be in the history are annotated as such.
 - Inconsistent packages are added back to the solution, including potential orphans.
 - Constraint analysis is run via Solver.get_constrained_packages() and Solver. determine_constricting_specs() to help the user understand why some packages were not updated.

We are not done yet, though. After Solver._run_sat(), we still need to run the post-solver logic! After the solve, the final list of PackageRecord objects might still change if certain modifiers are set. This is handled in the Solver._post_sat_handling():

- --no-deps (DepsModifier.NO_DEPS): Remove dependencies of the explicitly requested packages from the final solution.
- --only-deps (DepsModifier.ONLY_DEPS): Remove explicitly requested packages from the final solution but leave their dependencies. This is done via PrefixGraph. remove_youngest_descendant_nodes_with_specs().
- --update-deps (UpdateModifier.UPDATE_DEPS): This is the most interesting one. It actually runs a second solve (!) where the user-requested specs are the originally requested specs plus their (now determined) dependencies.
- --prune: Removes orphan packages from the solution.

The Solver also checks for Conda updates

Interestingly, the Solver API is also responsible of checking if new conda versions are available in the configured channels. This is done here to take advantage of the fact that the index has been already built for the rest of the class.

Details of conda.resolve.Resolve

This is the class that actually wraps the SAT solver. conda.core.solve.Solver is a higher level API that configures the solver *request* and prepares the transaction. The actual solution is computed in this other module we are discussing now.

The Resolve object will mostly receive two arguments:

- The fetched index, as processed by conda.index.get_index().
- The configured channels, so *channel priority* can be sorted out.

It will also hold certain states:

- The index will be grouped by name under a .groups dictionary (str, [PackageRecord]). Each group is later sorted so newer packages are listed first, helping reduce the index better.
- Another dictionary of PackageRecord groups will be created, keyed by their track_features entries, under the .trackers attribute.
- Some other dictionaries are initialized as caches.

The main methods in this class are:

- bad_installed(): This method uses a series of small solves to check if the installed packages are in a consistent state. In other words, if all the PackageRecord entries were expressed as MatchSpec objects, would the environment be solvable?
- get_reduced_index(): This method takes a full index and trims out the parts that are not necessary for the current request, thus reducing the solution space and speeding up the solver.
- gen_clauses(): This instantiates and configures the Clauses object, which is the real SAT solver wrapper. More on this later.
- solve(): The main method in the Resolve class. It will be discussed in the next section.
• find_conflicts(): If the solver didn't succeed, this method performs a conflict analysis to find the most plausible explanation for the current conflicts. It essentially relies on build_conflict_map() to "find the common dependencies that might be the cause of conflicts". conda can spend a lot of time in this method.

Disabling conflict analysis

Conflict analysis can be disabled through the context.unsatisfiable_hints options, but unfortunately that gets in the way of conda's iterative logic. It will shortcut early in the chain of attempts and prevent the solver from trying less constrained specs. This is a part of the logic that should be improved.

Resolve.solve()

As introduced above, this is the main method in the Resolve class. It will perform the following actions:

- 1. Reduce the index via get_reduced_index. If unsuccessful, try to detect if packages are missing or the wrong version was requested. We can raise early to trigger a new attempt in conda.cli.install (remember, unfrozen or next repodata) or, if it's the last attempt, we go straight to find_conflicts() to understand what's wrong.
- 2. Instantiate a new Resolve object with the reduced index to generate the Clauses object via gen_clauses(). This method relies on push_MatchSpec() to turn the MatchSpec object into an SAT clause inside the Clauses object (referred to as C).
- 3. Run Clauses.sat() to solve the SAT problem. If a solution cannot be found, deal with the error in the usual way: raise early to trigger another attempt or call find_conflicts() to try explaining why.
- 4. If no errors are found, then we have one or more solutions available, and we need to post-process them to find the *best* one. This is done in several steps:
 - 1. Minimize the amount of removed packages. The SAT clauses are generated via Resolve. generate_removal_count() and then Clauses.minimize() will use it to optimize the current solution.
 - 2. Maximize how well each record in the solution matches the spec. The SAT clauses are now generated in Resolve.generate_version_metrics(). This returns five sets of clauses: channel, version, build, arch or noarch, and timestamp. At this point, only channels and versions are optimized.
 - 3. Minimize the number of records with track_feature entries. SAT clauses are coming from Resolve. generate_feature_count().
 - 4. Minimize the number of records with features entries. SAT clauses are coming from Resolve. generate_feature_metric().
 - 5. Now, we continue the work started at (2). We will maximize the build number and choose arch-specific packages over noarch variants.
 - 6. We also want to include as many *optional* specs in the solution as possible. Optimize for that thanks to the clauses generated by Resolve.generate_install_count().
 - 7. At the same time, we will minimize the number of necessary updates if keeping the installed versions also satisfies the request. Clauses generated with Resolve.generate_update_count().
 - 8. Steps (2) and (5) are also applied to indirect dependencies.
 - 9. Minimize the number of packages in the solution. This is done by removing unnecessary packages.
 - 10. Finally, maximize timestamps until convergence so the most recent packages are preferred.
- 5. At this point, the SAT solution indices can be translated back to *SAT names*. This is done in the clean() local function you can find in Resolve.sat().

6. There's a chance we can find alternate solutions for the problem, and this is explored now, but eventually only the first one will be returned while translating the *SAT names* to PackageRecord objects.

The Clauses object wraps the SAT solver using several layers

The **Resolve** class exposes the solving logic, but when it comes to interacting with the SAT solver engine, that's done through the **Clauses** object tree. And we say "tree" because the actual engines are wrapped in several layers:

- Resolve generates conda.common.logic.Clauses objects as needed.
- Clauses is a tight wrapper around its private conda.common._logic.Clauses counterpart. Let's call the former _Clauses. It simply wraps the _Clauses API with ._eval() calls and other shortcuts for convenience.
- _Clauses provides an API to process the raw SAT formulas or clauses. It will wrap one of the conda.common. _logic._SatSolver subclasses. *These* are the ones that wrap the SAT solver engines! So far, there are three subclasses, selectable via the context.sat_solver setting:
 - _PycoSatSolver, keyed as pycosat. This is the default one, a Python wrapper around the picosat project.
 - _PySatSolver, keyed as pysat. Uses the Glucose4 solver found in the pysat project.
 - _PyCryptoSatSolver, keyed as pycryptosat. Uses the Python bindings for the CryptoMiniSat project.

In principle, more SAT solvers can be added to conda if a wrapper that subscribes to the _SatSolver API is used. However, if the reason is choosing a better performing engine, consider the following:

- The wrapped SAT solvers are already using compiled languages.
- Generating the clauses is indeed written in pure Python and has a non-trivial overhead.
- Optimization tricks like reducing the index and constraining the solution space have their costs if the "bets" were not successful.

More about SAT solvers in general

This guide did not cover the details of what SAT solvers are or do. If you want to read about them, consider checking the following resources:

- Aaron Meurer's slides about Conda internals. These slides reveal a lot of details of conda back in 2015. Some things have changed, but the core SAT solver behaviour is still well explained there.
- "Understanding and Improving Conda's performance"
- All the talks regarding solvers from Packaging-Con 2021. Check which talks belong to the Solvers track and enjoy!

4.6.5 Writing Tests

This section contains a series of guides and guidelines for writing tests in the conda repository.

	ariables				ocal variables	
user-reques	sted packages	target pref	îx command		Installed packages 🔟	Pinned packages
ehavior varia	ables				History	Aggressive updates
updates	dependencies	pruning	context		Virtual packages	Protected
Remote	e variables					
Cha	annels					
ren	:					
dov	vnload					
	E Fi	ull dex				
			[PackageRecord	1()]	[MatchSp	bec()]
			A			
		-	Full index		Spe	ecs
Solvin	ng environm	ent…	[PackageRecord	±()]	[MatchSr	pec()]
					. ,	CONV
	Pre-solve		Availability	Incor	nsistencies Conflic	ts er
			A Reduced ind	lox		
			Reduced ind	iex conve	CIAUSES()
					pycosat()	
	Solve		CAT		▼ removed packages	▲ channels
			SAT solutions	Ш	• Temoveu packages	
conda.I	resolve.kesolve			Choose best {	▼ features ▲ version	, build ▲ arch > noarch
			;		▲ optional ▼ updates	▼ # pkgs ▲ times
			Best SAT solution		[PackageRecord()]
			Dest SAT Solution		[a on a geneoor at	
			Best SAT Solution		[F donageneoor d(

Fig. 4: Here you can see how the high level Solver API interacts with the low-level Resolve and Clauses objects. The *Collecting metadata* step in the CLI report only compiles the necessary information from the CLI arguments, the prefix state and the chosen channels, presenting the SAT solver adapters with two critical pieces of information:

- The list of MatchSpec objects ("what the user wants in this environment")
- The list of PackageRecord objects ("the packages available in the channels")

So, in essence, the SAT solver takes the MatchSpec objects to select which PackageRecord objects satisfy the user request in the best way. The necessary computations are part of the "Solving environment..." step in the CLI report.

Guides

Integration Tests This guide gives an overview of how to write integration tests using full command invocation. It also covers creating fixtures to use with these types of tests.

Integration Tests

Integration tests in conda test the application from a high level where each test can potentially cover large portions of the code. These tests may also use the local file system and/or perform network calls. In the following sections, we cover several examples of exactly how these tests look. When writing your own integration tests, these should serve as a good starting point.

conda_cli Fixture: Running CLI level tests

CLI level tests are the highest level integration tests you can write. This means that the code in the test is executed as if you were running it from the command line. For example, you may want to write a test to confirm that an environment is created after successfully running conda create. A test like this would look like the following:

Listing 3: Integration test for conda create

```
import json
   from pathlib import Path
2
   from conda.testing import CondaCLIFixture
4
5
6
   def test_conda_create(conda_cli: CondaCLIFixture, tmp_path: Path):
7
       # setup, create environment
8
       out, err, code = conda_cli("create", "--prefix", tmp_path, "--yes")
9
10
       assert f"conda activate {tmp_path}" in out
11
       assert not err # no errors
12
       assert not code # success!
13
14
       # verify everything worked using the `conda env list` command
15
       out, err, code = conda_cli("env", "list", "--json")
16
17
       assert any(
18
           tmp_path.samefile(path)
19
           for path in json.loads(out).get("envs", [])
20
       )
21
       assert not err # no errors
22
       assert not code # success!
23
24
       # cleanup, remove environment
25
       out, err, code = conda_cli("remove", "--all", "--prefix", tmp_path)
26
27
       assert out
28
       assert not err # no errors
29
       assert not code # success!
30
```

Let's break down exactly what is going on in the code snippet above:

First, we rely on a fixture (conda_cli) that allows us to run a command using the current running process. This is much more efficient and quicker than running CLI tests via subprocesses.

In the test itself, we first create a new environment by effectively running conda create. This function returns the standard out, standard error, and the exit code of the command. This allows us to perform our inspections in order to determine whether the command ran successfully.

The second part of the test again uses the conda_cli fixture to call conda env list. This time, we pass the --json flag, which allows capturing JSON that we can better parse and more easily inspect. We then assert whether the environment we just created is actually in the list of environments available.

Finally, we destroy the environment we just created and ensure the standard error and the exit code are what we expect them to be.

Warning: It is preferred to use temporary directories (e.g., tmp_path) whenever possible for automatic cleanup after tests are run. Otherwise, remember to remove anything created during the test since it will be present when other tests are run and may result in unexpected race conditions.

tmp_env Fixture: Creating a temporary environment

The tmp_env fixture is a convenient way to create a temporary environment for use in tests:

Listing 4: Integration test for creating an environment with numpy

```
from conda.testing import CondaCLIFixture, TmpEnvFixture

def test_environment_with_numpy(
   tmp_env: TmpEnvFixture,
   conda_cli: CondaCLIFixture,
):
   with tmp_env("numpy") as prefix:
      out, err, code = conda_cli("list", "--prefix", prefix)
      assert out
      assert out
      assert not err # no error
      assert not code # success!
```

path_factory Fixture: Creating a unique (non-existing) path

The path_factory fixture extends pytest's tmp_path fixture to provide unique, unused paths. This makes it easier to generate new paths in tests:

Listing 5:	Integration	test for	renaming	an	environment
0	0		0		

```
from conda.testing import (
        CondaCLIFixture,
        PathFactoryFixture,
        TmpEnvFixture,
)
```

(continues on next page)

23

4

5

6

7

8

9 10

11

12

13

1

2

3

4

5

(continued from previous page)

```
def test_conda_rename(
8
       path_factory: PathFactoryFixture,
9
        tmp_env: TmpEnvFixture,
10
       conda_cli: CondaCLIFixture,
11
        tmp_path: Path,
12
13
   ):
        # each call to `path_factory` returns a unique path
14
       assert path_factory() != path_factory()
15
16
        # each call to `path_factory` returns a path that is a child of `tmp_path`
17
       assert path_factory().parent == path_factory().parent == tmp_path
18
19
       with tmp_env() as prefix:
20
            out, err, code = conda_cli("rename", "--prefix", prefix, path_factory())
21
22
            assert out
23
            assert not err # no error
24
            assert not code # success!
25
```

Tests with fixtures

Sometimes in integration tests, you may want to re-use the same type of environment more than once. Copying and pasting this setup and teardown code into each individual test can make these tests more difficult to read and harder to maintain.

To overcome this, conda tests make extensive use of pytest fixtures. Below is an example of the previously-shown test, except that we now make the focus of the test the conda env list command and move the creation and removal of the environment into a fixture:

Listing 6: Integration test for conda crea	ite	e	at	cr	conda	for	test	Integration	6:	Listing	
--	-----	---	----	----	-------	-----	------	-------------	----	---------	--

```
import json
1
   from pathlib import Path
2
3
   from conda.testing import CondaCLIFixture
4
5
6
   @pytest.fixture
7
   def env_one(tmp_env: TmpEnvFixture) -> Path:
8
       with tmp_env() as prefix:
0
           yield prefix
10
11
12
   def test_conda_create(env_one: Path, conda_cli: CondaCLIFixture):
13
       # verify everything worked using the `conda env list` command
14
       out, err, code = conda_cli("env", "list", "--json")
15
16
       assert any(
17
           env_one.samefile(path)
18
            for path in json.loads(out).get("envs", [])
19
       )
20
```

(continues on next page)

(continued from previous page)

```
assert not err # no errors
assert not code # success!
```

In the fixture named env_one, we create a new environment using the tmp_env fixture. We yield to mark the end of the setup. Since the tmp_env fixture extends tmp_path no additional teardown is needed.

This fixture will be run using the default scope in pytest, which is function. This means that the setup and teardown will occur before and after each test that requests this fixture. If you need to share an environment or other pieces of data between tests, just remember to set the fixture scope appropriately. Read here for more information on pytest fixture scopes.

General Guidelines

21

22

- Preferred test style (pytest)
- Organizing tests
- The "conda.testing" module
- Adding new fixtures
- The context object

Note: It should be noted that existing tests may deviate from these guidelines, and that is okay. These guidelines are here to inform how we would like all new tests to look and function.

Preferred test style (pytest)

Although our codebase includes class-based unittest tests, our preferred format for all new tests are pytest style tests. These tests are written using functions and handle the setup and teardown of context for tests using fixtures. We recommend familiarizing yourself with pytest first before attempting to write tests for conda. Head over to their Getting Started Guide to learn more.

Organizing tests

Tests should be organized in a way that mirrors the main conda module. For example, if you were writing a test for a function in conda/base/context.py, you would place this test in tests/base/test_context.py.

The "conda.testing" module

This is a module that contains anything that could possibly help with writing tests, including fixtures, functions, and classes. Feel free to make additions to this module as you see fit, but be mindful of organization. For example, if your testing utilities are primarily only for the base module considering storing these in conda.testing.base.

Adding new fixtures

For fixtures that have a very limited scope or purpose, it is okay to define these alongside the tests themselves. However, if these fixtures could be used across multiple tests, then they should be saved in a separate fixtures.py file. The conda.testing module already contains several of these files.

If you want to add new fixtures within a new file, be sure to add a reference to this module in tests/conftest. py::pytest_plugins. This is our preferred way of making fixtures available to our tests. Because of the way these are included in the environment, you should be mindful of naming schemes and choose ones that likely will not collide with each other. Consider using a prefix to achieve this.

The context object

The context object in conda is used as a singleton. This means that everytime the conda command runs, only a single object is instantiated. This makes sense as it holds all the configuration for the program and re-instantiating it or making multiple copies would be inefficient.

Where this causes problems is during tests where you may want to run conda commands potentially hundreds of times within the same process. Therefore, it is important to always reset this object to a fresh state when writing tests.

This can be accomplished by using the reset_context function, which also lives in the conda.base.context module. The following example shows how you would modify the context object and then reset it using the reset_conda_context pytest fixture:

```
import os
import tempfile
from conda.base.context import reset_context, context
from conda.testing.fixtures import reset_conda_context
TEST_CONDARC = """
channels:
 - test-channel
.....
def test_that_uses_context(reset_conda_context):
    # We first created a temporary file to hold our test configuration
   with tempfile.TemporaryDirectory() as tempdir:
        condarc_file = os.path.join(tempdir, "condarc")
        with open(condarc_file, "w") as tmp_file:
            tmp_file.write(TEST_CONDARC)
        # We use the reset_context function to load our new configuration
        reset_context(search_path=(condarc_file,))
        # Run various test assertions, below is an example
        assert "test-channel" in context.channels
```

Using this testing fixture ensures that your context object is returned to the way it was before the test. For this specific test, it means that the channels setting will be returned to its default configuration. If you ever need to manually reset the context during a test, you can do so by manually invoking the reset_context command like in the following example:

```
from conda.base.context import reset_context

def test_updating_context_manually():
    # Load some custom variables into context here like above...
    reset_context()
    # Continue testing with a fresh context...
```

4.6.6 Deprecations

Conda abides by the Deprecation Schedule defined in CEP-9. To help make deprecations as much of a no-brainer as possible we provide several helper decorators and functions to facilitate the correct deprecation process.

Functions, Methods, Properties, and Classes

Warning: To deprecate Enums treat them like constants (see Constants and Enums).

The simplest use case is for deprecating any function, method, or property:

```
Listing 7: Example file, foo.py.
```

```
from conda.deprecations import deprecated
```

```
@deprecated("23.9", "24.3")
def bar():
    ...
```

Listing 8: Example invocation.

As a minimum we must always specify two versions:

- 1. the future deprecation release in which the function, method, or property will be marked as deprecated; prior to that the feature will show up as pending deprecation (which we treat as a commenting period), and
- 2. the subsequent deprecation release in which the function, method, or property will be removed from the code base.

Additionally, you may provide an addendum to inform the user what they should do instead:

Listing 9: Example file, foo.py.

from conda.deprecations import deprecated

(continues on next page)

(continued from previous page)

```
@deprecated("23.9", "24.3", addendum="Use `qux` instead.")
def bar():
    ...
```

Listing 10: Example invocation.

Keyword Arguments

Warning: Deprecating or renaming a positional argument is unnecessarily complicated and is not supported. Instead, it is recommended to either (1) devise a custom way of detecting usage of a deprecated positional argument (e.g., type checking) and use the conda.deprecations.deprecated.topic function (see *Topics*) or (2) deprecate the function/method itself and define a new function/method without the deprecated argument.

Similarly to deprecating a function or method it is common to deprecate a keyword argument:

Listing 11: Example file, foo.py.

```
from conda.deprecations import deprecated
# prior implementation
# def bar(is_true=True):
# ...
@deprecated.argument("23.9", "24.3", "is_true")
def bar():
...
```



Or to rename the keyword argument:

Listing 13: Example file, foo.py.

from conda.deprecations import deprecated

(continues on next page)

(continued from previous page)

```
# prior implementation
# def bar(is_true=True):
# ...
@deprecated.argument("23.9", "24.3", "is_true", rename="enabled")
def bar(enabled=True):
...
```

Listing 14: Example invocation.

argparse.Action

Occasionally, there is a need to deprecate CLI arguments. For this, we provide a helper function to monkeypatch any argparse.Action:

```
Listing 15: Example file, foo.py.
```

```
import argparse
from conda.deprecations import deprecated
parser = argparse.ArgumentParser()
parser.add_argument(
    "--force",
    dest="yes",
    action=deprecated.action(
        "23.9",
        "24.3",
        argparse._StoreTrueAction,
        addendum="Use `--yes` instead.",
    ),
    default=False,
)
parser.parse_args()
```

python foo.py --force foo.py:16: PendingDeprecationWarning: `--force` is pending deprecation and will be →removed in 24.3. Use `--yes` instead.

Constants and Enums

We also offer a way to deprecate global variables or constants:

Listing 16: Example file, foo.py.

from conda.deprecations import deprecated

deprecated.constant("23.9", "24.3", "ULTIMATE_CONSTANT", 42)

Listing 17: Example invocation.

>>> import foo
>>> foo.ULTIMATE_CONSTANT
<stdin>:1: PendingDeprecationWarning: foo.ULTIMATE_CONSTANT is pending deprecation and_
_will be removed in 24.3.

Enums work similarly:

Listing 18: Example file, foo.py.

```
from enum import Enum
from conda.deprecations import deprecated
class Bar(Enum):
    ULTIMATE_CONSTANT = 42
```

```
deprecated.constant("23.9", "24.3", "Bar", Bar)
del Bar
```

Listing 19: Example invocation.

Note: Constants deprecation relies on the module's <u>__getattr__</u> introduced in PEP-562.

Modules

Entire modules can be also be deprecated:

Listing 20: Example file, foo.py.

from conda.deprecations import deprecated

deprecated.module("23.9", "24.3")

Listing 21: Example invocation.

>>> import foo

```
<stdin>:1: PendingDeprecationWarning: foo is pending deprecation and will be removed in _{\rightarrow}24.3.
```

Topics

Finally, there are a multitude of other ways in which code may be run that also needs to be deprecated. To this end we offer a general purpose deprecation function:

Listing 22: Example file, foo.py.

```
from conda.deprecations import deprecated

def bar(...):
    # some logic

if ...:
    deprecated.topic("23.9", "24.3", topic="The <TOPIC>")

# some more logic
```

Listing 23: Example invocation.

4.6.7 Releasing

Conda's releases may be performed via the rever command. Rever is configured to perform the activities for a typical conda release. To cut a release, simply run rever $\langle X.Y.Z \rangle$ where $\langle X.Y.Z \rangle$ is the release number that you want bump to. For example, rever 1.2.3.

However, it is always good idea to make sure that the you have permissions everywhere to actually perform the release. So it is customary to run rever check before the release, just to make sure.

The standard workflow is thus:

```
$ rever check
$ rever 1.2.3
```

If for some reason a release fails partway through, or you want to claw back a release that you have made, rever allows you to undo activities. If you find yourself in this pickle, you can pass the --undo option a comma-separated list of activities you'd like to undo. For example:

\$ rever --undo tag, changelog, authors 1.2.3

Happy releasing!

4.6.8 Plugins

As of version 22.11.0, conda has support for user plugins, enabling extension and/or alterations to some of its functionality.

Quick start

This is an example of a minimal working conda plugin that defines a new subcommand:

```
Listing 24: example_plugin.py
```

```
import conda.plugins
from conda.base.context import context

def command(arguments: list[str]):
    print("Conda subcommand!")

@conda.plugins.hookimpl
def conda_subcommands():
    yield conda.plugins.CondaSubcommand(
        name="example",
        action=command,
        summary="Example of a conda subcommand",
    )
```

Let's break down what's going on here step-by-step:

- 1. First, we create the function command that serves as our subcommand. This function is passed a list of arguments which equal to sys.argv[2:].
- 2. Next, we register this subcommand by using the conda_subcommands plugin hook. We do this by creating a function called conda_subcommands and then decorating it with conda.plugins.hookimpl.
- 3. The object we return from this function is conda.plugins.CondaSubcommand, which does several things:
 - 1. name is what we use to call this subcommand via the command line (i.e. "conda example")
 - 2. action is the function that will be called when we invoke "conda example"
 - 3. summary is the description of the of the subcommand that appears when users call "conda --help"

In order to actually use conda plugins, they must be packaged as Python packages. Furthermore, we also need to take advantage of a feature known as Python package entrypoints. We can define our Python package and the entry points by either using a pyproject.toml file (preferred) or a setup.py (legacy) for our project:

Listing 25: pyproject.toml

```
[build-system]
requires = ["setuptools", "setuptools-scm"]
build-backend = "setuptools.build_meta"
[project]
name = "conda-example-plugin"
version = "1.0.0"
description = "Example conda plugin"
```

(continues on next page)

(continued from previous page)

```
requires-python = ">=3.8"
dependencies = ["conda"]
[project.entry-points."conda"]
conda-example-plugin = "example_plugin"
```

```
Listing 26: setup.py
```

```
from setuptools import setup
setup(
    name="conda-example-plugin",
    install_requires="conda",
    entry_points={"conda": ["conda-example-plugin = example_plugin"]},
    py_modules=["example_plugin"],
)
```

In both examples shown above, we define an entry point for conda. It's important to make sure that the entry point is for "conda" and that it points to the correct module in your plugin package. Our package only consists a single Python module called example_plugin. If you have a large project, be sure to always point the entry point to the module containing the plugin hook declarations (i.e. where conda.plugins.hookimpl is used). We recommend using the *plugin* submodule in these cases, e.g. *large_project.plugin* (in *large_project/plugin.py*).

More examples

To see more examples of conda plugins, please visit the following resources:

• conda-plugins-template: This is a repository with full examples that could be used a starting point for your plugin

Using other plugin hooks

For examples of how to use other plugin hooks, please read their respective documentation pages:

Auth Handlers

The auth handlers plugin hook allows plugin authors to enable new modes of authentication within conda. Registered auth handlers will be available to configure on a per channel basis via the channel_settings configuration option in the .condarc file.

Auth handlers are subclasses of the *ChannelAuthBase* class, which is itself a subclass of requests.auth.AuthBase. The *ChannelAuthBase* class adds an additional channel_name property to the requests.auth.AuthBase class. This is necessary for appropriate handling of channel based authentication in conda.

For more information on how to implement your own auth handlers, please read the requests documentation on Custom Authentication.

class CondaAuthHandler

Return type to use when the defining the conda auth handlers hook.

Parameters

• **name** -- Name (e.g., **basic-auth**). This name should be unique and only one may be registered at a time.

• handler -- Type that will be used as the authentication handler during network requests.

handler

name

conda_auth_handlers()

Register a conda auth handler derived from the requests API.

This plugin hook allows attaching requests auth handler subclasses, e.g. when authenticating requests against individual channels hosted at HTTP/HTTPS services.

Example:

```
import os
from conda import plugins
from requests.auth import AuthBase
class EnvironmentHeaderAuth(AuthBase):
    def __init__(self, *args, **kwargs):
        self.username = os.environ["EXAMPLE_CONDA_AUTH_USERNAME"]
        self.password = os.environ["EXAMPLE_CONDA_AUTH_PASSWORD"]
    def __call__(self, request):
        request.headers["X-Username"] = self.username
        request.headers["X-Password"] = self.password
        return request
@plugins.hookimpl
def conda_auth_handlers():
   yield plugins.CondaAuthHandler(
        name="environment-header-auth",
        auth_handler=EnvironmentHeaderAuth,
    )
```

Health Checks

Conda doctor can be extended with the health_checks plugin hook. Write new health checks using the health_checks plugin hook, install the plugins you wrote and they will run every time conda doctor command is run. The action function is where you specify the code you want to be executed with conda doctor.

class CondaHealthCheck

Return type to use when defining conda health checks plugin hook.

action

name

conda_health_checks()

Register health checks for conda doctor.

This plugin hook allows you to add more "health checks" to conda doctor that you can write to diagnose problems in your conda environment. Check out the health checks already shipped with conda for inspiration.

Example:

```
from conda import plugins

def example_health_check(prefix: str, verbose: bool):
    print("This is an example health check!")

@plugins.hookimpl
def conda_health_checks():
    yield plugins.CondaHealthCheck(
        name="example-health-check",
        action=example_health_check,
    )
```

Post-commands

Conda commands can be extended with the conda_post_commands plugin hook. By specifying the set of commands you would like to use in the run_for configuration option, you can execute code via the action option after these commands are run. The functions are provided a command argument representing the name of the command currently running. If the command fails for any reason, this plugin hook will not be run.

If you would like to target conda env commands, prefix the command name with env_. For example, conda env list would be passed to run_for as env_list.

class CondaPostCommand

Return type to use when defining a conda post-command plugin hook.

For details on how this is used, see conda_post_commands().

Parameters

- **name** -- Post-command name (e.g., custom_plugin_post_commands).
- action -- Callable which contains the code to be run.
- run_for -- Represents the command(s) this will be run on (e.g. install or create).

action

name

run_for

conda_post_commands()

Register post-command functions in conda.

Example:

```
from conda import plugins
```

```
def example_post_command(command):
    print("post-command action")
```

```
@plugins.hookimpl
```

(continues on next page)

(continued from previous page)

```
def conda_post_commands():
    yield plugins.CondaPostCommand(
        name="example-post-command",
        action=example_post_command,
        run_for={"install", "create"},
    )
```

Pre-commands

Conda commands can be extended with the conda_pre_commands plugin hook. By specifying the set of commands you would like to use in the run_for configuration option, you can execute code via the action option before these commands are run. The functions are provided a command argument representing the name of the command currently running.

If you would like to target conda env commands, prefix the command name with env_. For example, conda env list would be passed to run_for as env_list.

class CondaPreCommand

Return type to use when defining a conda pre-command plugin hook.

For details on how this is used, see *conda_pre_commands()*.

Parameters

- **name** -- Pre-command name (e.g., custom_plugin_pre_commands).
- action -- Callable which contains the code to be run.
- **run_for** -- Represents the command(s) this will be run on (e.g. install or create).

action

name

run_for

conda_pre_commands()

Register pre-command functions in conda.

Example:

```
from conda import plugins
```

```
def example_pre_command(command):
    print("pre-command action")

@plugins.hookimpl
def conda_pre_commands():
    yield plugins.CondaPreCommand(
        name="example-pre-command",
        action=example_pre_command,
        run_for={"install", "create"},
    )
```

Settings

The settings plugin hook allows plugin authors to add new settings to conda. Users will be able to use these new parameters either in .condarc files or define them as environment variables. For more information on configuration in conda, see *Configuration*.

The plugin hooks relies on using the various conda.common.configuration.Parameter sub-classes (e.g. conda. common.configuration.PrimitiveParameter or conda.common.configuration.SequenceParameter). For more examples of how these parameter classes are used, please see the conda.base.context.Context class.

class CondaSetting

Return type to use when defining a conda setting plugin hook.

For details on how this is used, see *conda_settings()*.

Parameters

- name -- name of the setting (e.g., config_param)
- description -- description of the setting that should be targeted towards users of the plugin
- parameter -- Parameter instance containing the setting definition
- aliases -- alternative names of the setting

aliases

description

name

parameter

conda_settings()

Register new setting

The example below defines a simple string type parameter

Example:

```
from conda import plugins
from conda.common.configuration import PrimitiveParameter, SequenceParameter
@plugins.hookimpl
def conda_settings():
    yield plugins.CondaSetting(
        name="example_option",
        description="This is an example option",
        parameter=PrimitiveParameter("default_value", element_type=str),
        aliases=("example_option_alias",),
    )
```

Solvers

The conda solvers can be extended with additional backends with the conda_solvers plugin hook. Registered solvers will be available for configuration with the solver configuration and --solver command line option.

class CondaSolver

Return type to use when defining a conda solver plugin hook.

For details on how this is used, see *conda_solvers()*.

Parameters

- **name** -- Solver name (e.g., custom-solver).
- **backend** -- Type that will be instantiated as the solver backend.

backend

name

conda_solvers()

Register solvers in conda.

Example:

```
import logging
from conda import plugins
from conda.core import solve
log = logging.getLogger(__name__)
class VerboseSolver(solve.Solver):
    def solve_final_state(self, *args, **kwargs):
        log.info("My verbose solver!")
        return super().solve_final_state(*args, **kwargs)
@plugins.hookimpl
def conda_solvers():
    yield plugins.CondaSolver(
        name="verbose-classic",
        backend=VerboseSolver,
        )
```

Returns

An iterable of solver entries.

Subcommands

The conda CLI can be extended with the conda_subcommands plugin hook. Registered subcommands will be available under the conda <subcommand> command.

class CondaSubcommand

Return type to use when defining a conda subcommand plugin hook.

For details on how this is used, see conda_subcommands().

Parameters

- name -- Subcommand name (e.g., conda my-subcommand-name).
- summary -- Subcommand summary, will be shown in conda --help.
- action -- Callable that will be run when the subcommand is invoked.
- configure_parser -- Callable that will be run when the subcommand parser is initialized.

action

configure_parser

name

summary

conda_subcommands()

Register external subcommands in conda.

Example:

```
from conda import plugins

def example_command(args):
    print("This is an example command!")

@plugins.hookimpl
def conda_subcommands():
    yield plugins.CondaSubcommand(
        name="example",
        summary="example command",
        action=example_command,
    )
```

Returns

An iterable of subcommand entries.

Virtual Packages

Conda allows for the registering of virtual packages in the index data via the plugin system. This mechanism lets users write plugins that provide version identification for properties only known at runtime (e.g., OS information).

class CondaVirtualPackage

Return type to use when defining a conda virtual package plugin hook.

For details on how this is used, see *conda_virtual_packages()*.

Parameters

- **name** -- Virtual package name (e.g., my_custom_os).
- **version** -- Virtual package version (e.g., 1.2.3).
- **build** -- Virtual package build string (e.g., **x86_64**).

build

name

version

conda_virtual_packages()

Register virtual packages in Conda.

Example:

```
from conda import plugins
```

```
@plugins.hookimpl
def conda_virtual_packages():
    yield plugins.CondaVirtualPackage(
        name="my_custom_os",
        version="1.2.3",
        build="x86_64",
    )
```

Returns

An iterable of virtual package entries.

More information about how plugins work

Plugins in conda are implemented with the use of Pluggy, a Python framework used by other projects, such as pytest, tox, and devpi. pluggy provides the ability to extend and modify the behavior of conda via function hooking, which results in plugin systems that are discoverable with the use of Python package entrypoints.

For more information about how it works, we suggest heading over to their documentation.

API

For even more detailed information about our plugin system, please the see the Plugin API section.

A note on licensing

For more information on which license to use for your custom plugin, please reference the "Choose an Open Source License" site. If you need help figuring out exactly which one to use, we advise communicating with a qualified legal professional.

4.6.9 Specifications

This section contains an incomplete list of conda specifications that may or may not be related to Conda Enhancement Proposals.

Work in progress

This page of the documentation is not yet finished and only contains a draft of the content.

Technical specification: solver state

Note

This document is a technical specification, which might not be the best way to learn about how the solver works. For that, refer to *conda install* and *Solvers*.

The Solver API will pass a collection of MatchSpec objects (from now on, we will refer to them as specs) to the underlying SAT solver. How this list is built from the prefix state and context options is not a straightforward process, but an elaborate logic. This is better understood if we examine the *ingredients* that participate in the construction of specs. We will label them like this:

These groups below will not change during the solver attempts:

- 1. requested: MatchSpec objects the user is *explicitly* asking for.
- 2. installed: Installed packages, expressed as PrefixRecord objects. Empty if the environment did not exist.
- 3. history: Specs asked in the past: the History. Empty if the environment did not exist.
- 4. aggressive_updates: Packages included in the *aggressive updates* list. These packages are always included in any requests to make sure they stay up-to-date under all circumstances.
- 5. pinned: Packages pinned to a specific version, either via pinned_packages in your .condarc or defined in a \$PREFIX/conda-meta/pinned file.
- 6. virtual: System properties exposed as virtual packages (e.g. __glibc=2.17). They can't really be installed or uninstalled, but they do participate in the solver by adding runtime constraints.
- 7. do_not_remove: A fixed list of packages that receive special treatment by the solver due to poor metadata in the early days of conda packaging. A legacy leftover.

This one group *does* change during the solver lifetime:

8. conflicting: Specs that are suspected to be a conflict for the solver.

Also, two more sources that are not obvious at first. These are not labeled as a *source*, but they do participate in the specs collection:

- In new environments, packages included in the contex.create_default_packages list. These MatchSpec objects are injected in each conda create command, so the solver will see them as explicitly requested by the user (requested).
- Specs added by command line modifiers. The specs here present aren't new (they are already in other categories), but they might end up in the specs list only when a flag is added. For example, update --all will add all the installed packages to the specs list, with no version constraint. Without this flag, the installed packages will still end up in the specs list, but with full constraints (--freeze-installed defaults for the first attempt) unless:
 - Frozen attempt failed.
 - --update-specs (or any other UpdateModifier) was passed, overriding --freeze-installed.

See? It gets involved. We will also use this vocabulary to help narrow down the type of change being done:

Types of spec objects:

- specs: map of package name to its currently corresponding MatchSpec instance.
- spec: specific instance of a MatchSpec object.
- Exact or frozen spec: a spec where both the version and build fields are constrained with == operators (exact match).
- Fully constrained or tight spec: a spec where both version and build are populated, but not necessarily with equality operators. It can also be inequalities (>, <, etc.) and fuzzy matches (*something*).
- Version-only spec: a spec where *only* the version field is populated. The build is not.
- Name-only, bare, or unconstrained spec: a spec with no version or build fields. Just the name of the package.
- Targeted spec: a spec with the target field populated. Extracted from the comments in the solver logic:

target is a reference to the package currently existing in the environment. Setting target instructs the solver to not disturb that package if it's not necessary. If the spec.name is being modified by inclusion in specs_to_add, we don't set target, since we *want* the solver to modify/update that package.

TL;DR: when working with MatchSpec objects,

- to minimize the version change, set MatchSpec(name=name, target=prec.dist_str())
- to freeze the package, set all the components of MatchSpec individually
- if the spec object does not have an adjective, it should be assumed it's being added to the specs map unmodified, as it came from its origin.

Pools (collections of PackageRecord objects):

- Installed pool: The installed packages, grouped by name. Each group should only contain one record!
- Explicit pool: The full index, but reduced for the specs in requested.

The following sections will get dry and to the point. They will state what output to expect from a given set of initial conditions. At least we'll try. Take into account that the specs list is kept around across attempts! In other words, the specs list is only really empty in the first attempt; if this fails, the subsequent attempts will only overwrite (update) the existing one. In practice, this should only affect how constrained packages are. The names should be the same.

It will also depend on whether we are adding (conda install|create|update) or removing (conda remove) packages. There's a common initialization part for both, but after that the logic is separate.

Common initialization

Note: This happens in Solver._collect_all_metadata()

This happens regardless of the type of command we are using (install, update, create or remove).

- 1. Add specs from history, if any.
- 2. Add specs from do_not_remove, but only if:
 - There's no spec for that name in specs already, and
 - A package with that name is *not* installed.
- 3. Add virtual packages as unconstrained specs.
- 4. Add all those installed packages, as unconstrained specs, that satisfy any of these conditions:
 - The history is empty (in that case, all installed packages are added)
 - The package name is part of aggresive_updates
 - The package was not installed by conda, but by pip or other PyPI tools instead.

Preparing the index

At this point, the populated **specs** and the **requested** specs are merged together. This temporary collection is used to determine how to reduce the index.

Processing specs for conda install

Preparation

- 1. Generate the explicit pool for the requested specs (via Resolve._get_package_pool()).
- 2. Detect potential conflicts (via (Resolve.get_conflicting_specs()).

Refine specs that match installed records

- 1. Check that each of specs match a single installed package or none! If there are two or more matches, it means that the environment is in bad shape and is basically broken. If the spec matches one installed package (let's call it *installed match*), we will modify the original spec.
- 2. We will turn the spec into an *exact* (frozen) spec if:
 - 1. The installed match is unmanageable (installed by pip, virtual, etc.)
 - 2. There's no history, we are not in --freeze-installed mode, and:
 - The spec is not a potential conflict, and
 - The package name *cannot* be found in the explicit pool index or, if it is, the installed match can be found in that explicit pool (to guarantee it will be found instead of creating one more conflict *just because*).
- 3. We relax the spec to a name-only spec if it's part of the aggressive updates list.
- 4. We turn it into a targeted spec if:
 - 1. The spec is in history. In that case, we take its *historic* spec counterpart and set the target to the installed match version and build.

2. None of the above conditions were met. In other words, we'll try our best to match the installed package if none of the above applies, but if we fail we'll stick to whatever was already present in the specs.

Handle pinned specs

Processing specs for conda remove

4.6.10 API

As of conda 4.4, conda can be installed in any environment, not just environments with names starting with _ (under-score). That change was made, in part, so that conda can be used as a Python library.

As of conda 4.5, we do not support pip install conda. However, we are considering that as a supported bootstrap method in the future.

conda

OS-agnostic, system-level binary package manager.

__main__

Conda as a module entry point.

_vendor

Conda's pure-python dependencies will be vendored until conda 5.0 when conda will be isolated in its own private environment.

Introduction of dependencies for the 4.x series is discussed in https://github.com/conda/conda/issues/2825.

appdirs

Utilities for determining application-specific dirs.

See <http://github.com/ActiveState/appdirs> for details and usage.

Classes

AppDirs

Convenience wrapper for getting application dirs.

Functions

<pre>user_data_dir(appname[, appauthor, version, roam- ing])</pre>	Return full path to the user-specific data dir for this application.
<pre>site_data_dir(appname[, appauthor, version])</pre>	Return full path to the user-shared data dir for this application.
<pre>user_cache_dir(appname[, appauthor, version, opin- ion])</pre>	Return full path to the user-specific cache dir for this application.
<pre>user_log_dir(appname[, appauthor, version, opin- ion])</pre>	Return full path to the user-specific log dir for this appli- cation.
<pre>_get_win_folder_from_registry(csidl_name)</pre>	This is a fallback technique at best. I'm not sure if using the
_get_win_folder_with_pywin32(csidl_name)	
_get_win_folder_with_ctypes(csidl_name)	

Attributes

version_info	
version	
РҮЗ	
unicode	
_get_win_folder	
appname	

__version_info__ = (1, 2, 0)

__version__

РҮЗ

unicode

exception AppDirsError

Bases: Exception

Common base class for all non-exit exceptions.

user_data_dir(appname, appauthor=None, version=None, roaming=False)

Return full path to the user-specific data dir for this application.

"appname" is the name of application. "appauthor" (only required and used on Windows) is the name of the

appauthor or distributing body for this application. Typically it is the owning company name.

"version" is an optional version path element to append to the

path. You might want to use this if you want multiple versions of your app to be able to run independently. If used, this would typically be "<major>.<minor>".

"roaming" (boolean, default False) can be set True to use the Windows

roaming appdata directory. That means that for users on a Windows network setup for roaming profiles, this user data will be sync'd on login. See http://technet.microsoft.com/en-us/library/cc766489(WS.10).aspx> for a discussion of issues.

Typical user data directories are:

Mac OS X: ~/Library/Application Support/<AppName> Unix: ~/.config/<appname> # or in \$XDG_CONFIG_HOME if defined Win XP (not roaming): C:Documents and Settings<username>Application Data<AppAuthor><AppName> Win XP (roaming): C:Documents and Settings<username>Local SettingsApplication Data<AppAuthor><AppName> Win 7 (not roaming): C:Users<username>AppDataLocal<AppAuthor><AppName> Win 7 (roaming): C:Users<username>AppDataRoaming<AppAuthor><AppName> Win 7 (roaming):

For Unix, we follow the XDG spec and support \$XDG_CONFIG_HOME. We don't use \$XDG_DATA_HOME as that data dir is mostly used at the time of installation, instead of the application adding data during runtime. Also, in practice, Linux apps tend to store their data in "~/.config/<appname>" instead of "~/.local/share/<appname>".

site_data_dir(appname, appauthor=None, version=None)

Return full path to the user-shared data dir for this application.

"appname" is the name of application. "appauthor" (only required and used on Windows) is the name of the

appauthor or distributing body for this application. Typically it is the owning company name.

"version" is an optional version path element to append to the

path. You might want to use this if you want multiple versions of your app to be able to run independently. If used, this would typically be "<major>.<minor>".

Typical user data directories are:

Mac OS X: /Library/Application Support/<AppName> Unix: /etc/xdg/<appname> Win XP: C:Documents and SettingsAll UsersApplication Data<AppAuthor><AppName> Vista: (Fail! "C:ProgramData" is a hidden *system* directory on Vista.) Win 7: C:ProgramData<AppAuthor><AppName> # Hidden, but writeable on Win 7.

For Unix, this is using the \$XDG_CONFIG_DIRS[0] default.

WARNING: Do not use this on Windows. See the Vista-Fail note above for why.

user_cache_dir(appname, appauthor=None, version=None, opinion=True)

Return full path to the user-specific cache dir for this application.

"appname" is the name of application. "appauthor" (only required and used on Windows) is the name of the

appauthor or distributing body for this application. Typically it is the owning company name.

"version" is an optional version path element to append to the

path. You might want to use this if you want multiple versions of your app to be able to run independently. If used, this would typically be "<major>.<minor>".

"opinion" (boolean) can be False to disable the appending of

"Cache" to the base app data dir for Windows. See discussion below.

Typical user cache directories are:

Mac OS X: ~/Library/Caches/<AppName> Unix: ~/.cache/<appname> (XDG default) Win XP: C:Documents and Settings<username>Local SettingsApplication Data<AppAuthor><AppName>Cache Vista: C:Users<username>AppDataLocal<AppAuthor><AppName>Cache

On Windows the only suggestion in the MSDN docs is that local settings go in the *CSIDL_LOCAL_APPDATA* directory. This is identical to the non-roaming app data dir (the default returned by *user_data_dir* above). Apps typically put cache data somewhere *under* the given dir here. Some examples:

...MozillaFirefoxProfiles<ProfileName>Cache ...AcmeSuperAppCache1.0

OPINION: This function appends "Cache" to the *CSIDL_LOCAL_APPDATA* value. This can be disabled with the *opinion=False* option.

user_log_dir(appname, appauthor=None, version=None, opinion=True)

Return full path to the user-specific log dir for this application.

"appname" is the name of application. "appauthor" (only required and used on Windows) is the name of the

appauthor or distributing body for this application. Typically it is the owning company name.

"version" is an optional version path element to append to the

path. You might want to use this if you want multiple versions of your app to be able to run independently. If used, this would typically be "<major>.<minor>".

"opinion" (boolean) can be False to disable the appending of

"Logs" to the base app data dir for Windows, and "log" to the base cache dir for Unix. See discussion below.

Typical user cache directories are:

Mac OS X: ~/Library/Logs/<AppName> Unix: ~/.cache/<appname>/log # or defined under \$XDG_CACHE_HOME if Win XP: C:Documents Setand tings<username>Local SettingsApplication Data<AppAuthor><AppName>Logs Vista: C:Users<username>AppDataLocal<AppAuthor><AppName>Logs

On Windows the only suggestion in the MSDN docs is that local settings go in the *CSIDL_LOCAL_APPDATA* directory. (Note: I'm interested in examples of what some windows apps use for a logs dir.)

OPINION: This function appends "Logs" to the *CSIDL_LOCAL_APPDATA* value for Windows and appends "log" to the user cache dir for Unix. This can be disabled with the *opinion=False* option.

class AppDirs(appname, appauthor, version=None, roaming=False)

Bases: object

Convenience wrapper for getting application dirs.

property user_data_dir

property site_data_dir

property user_cache_dir

property user_log_dir

_get_win_folder_from_registry(csidl_name)

This is a fallback technique at best. I'm not sure if using the registry for this guarantees us the correct answer for all CSIDL_* names.

_get_win_folder_with_pywin32(csidl_name)

_get_win_folder_with_ctypes(csidl_name)

_get_win_folder

appname = 'MyApp'

cpuinfo

cpuinfo

Classes

Trace	
DataSource	
ASM	
CPUID	

Functions

_program_paths(program_name)
_run_and_get_stdout(command[, pipe_command])
_read_windows_registry_key(key_name,
field_name)
_check_arch()
_obj_to_b64(thing)
_b64_to_obj(thing)
_uttf_to_str(input)
_ccopy_new_fields(info, new_info)
_get_field_actual(cant_be_number, raw_string,
field_names)
_get_field(cant_be_number, raw_string, convert_to,
...)
_to_decimal_string(ticks)

continues on next page

Table 1 – continued	from previous page
_hz_short_to_full(ticks, scale)	
_hz_friendly_to_full(hz_string)	
<pre>_hz_short_to_friendly(ticks, scale)</pre>	
_to_friendly_bytes(input)	
_friendly_bytes_to_int(friendly_bytes)	
_parse_cpu_brand_string(cpu_string)	
_parse_cpu_brand_string_dx(cpu_string)	
<pre>_parse_dmesg_output(output)</pre>	
_parse_arch(arch_string_raw)	
_is_bit_set(reg, bit)	
_is_selinux_enforcing(trace)	
_filter_dict_keys_with_empty_values(info[,])	
<pre>_get_cpu_info_from_cpuid_actual()</pre>	Warning! This function has the potential to crash the Python runtime.
_get_cpu_info_from_cpuid_subprocess_wrapper(
_get_cpu_info_from_cpuid()	Returns the CPU info gathered by querying the X86 cpuid register in a new process.
_get_cpu_info_from_proc_cpuinfo()	Returns the CPU info gathered from /proc/cpuinfo.
<pre>_get_cpu_info_from_cpufreq_info()</pre>	Returns the CPU info gathered from cpufreq-info.
_get_cpu_info_from_lscpu()	Returns the CPU info gathered from lscpu.
<pre>_get_cpu_info_from_dmesg()</pre>	Returns the CPU info gathered from dmesg.
<pre>_get_cpu_info_from_ibm_pa_features()</pre>	Returns the CPU info gathered from lsprop /proc/device- tree/cpus/*/ibm,pa-features
<pre>_get_cpu_info_from_cat_var_run_dmesg_boot()</pre>	Returns the CPU info gathered from /var/run/dmesg.boot.
_get_cpu_info_from_sysctl()	Returns the CPU info gathered from syscel.
_get_cpu_info_from_sysinfo()	Returns the CPU info gathered from sysinfo.
_get_cpu_info_from_sysinfo_v1()	Returns the CPU info gathered from sysinfo.
_get_cpu_info_from_sysinfo_v2()	Returns the CPU info gathered from sysinfo.
_get_cpu_info_from_wmic()	Returns the CPU info gathered from WMI.
_get_cpu_info_from_registry()	Returns the CPU info gathered from the Windows Reg- istry.
_get_cpu_info_from_kstat()	Returns the CPU info gathered from isainfo and kstat.
_get_cpu_info_from_platform_uname()	
_get_cpu_info_internal()	Returns the CPU info by using the best sources of infor- mation for your OS.
<pre>get_cpu_info_json()</pre>	Returns the CPU info by using the best sources of infor- mation for your OS.

continues on next page

Table	1 - continued	from	previous	page

get_cpu_info()

Returns the CPU info by using the best sources of information for your OS.

main()

Attributes

CPUINFO_VERSION

CPUINFO_VERSION_STRING

CAN_CALL_CPUID_IN_SUBPROCESS

g_trace

g_trace

CPUINFO_VERSION = (9, 0, 0)

CPUINFO_VERSION_STRING

CAN_CALL_CPUID_IN_SUBPROCESS = True

g_trace

class Trace(is_active, is_stored_in_string)

Bases: object

header(msg)

success()

fail(msg)

command_header(msg)

command_output(msg, output)

keys(keys, info, new_info)

write(msg)

to_dict(info, is_fail)

class DataSource

Bases: object

bits

cpu_count

is_windows

```
arch_string_raw
```

- uname_string_raw
- can_cpuid = True
- static has_proc_cpuinfo()
- static has_dmesg()
- static has_var_run_dmesg_boot()
- static has_cpufreq_info()
- static has_sestatus()
- static has_sysctl()
- static has_isainfo()
- static has_kstat()
- static has_sysinfo()
- static has_lscpu()
- static has_ibm_pa_features()
- static has_wmic()
- static cat_proc_cpuinfo()
- static cpufreq_info()
- static sestatus_b()
- static dmesg_a()
- static cat_var_run_dmesg_boot()
- static sysctl_machdep_cpu_hw_cpufrequency()
- static isainfo_vb()
- static kstat_m_cpu_info()
- static sysinfo_cpu()
- static lscpu()
- static ibm_pa_features()
- static wmic_cpu()
- static winreg_processor_brand()
- static winreg_vendor_id_raw()
- static winreg_arch_string_raw()
- static winreg_hz_actual()

```
static winreg_feature_bits()
_program_paths(program_name)
_run_and_get_stdout(command, pipe_command=None)
_read_windows_registry_key(key_name, field_name)
_check_arch()
_obj_to_b64(thing)
_b64_to_obj(thing)
_utf_to_str(input)
_copy_new_fields(info, new_info)
_get_field_actual(cant_be_number, raw_string, field_names)
_get_field(cant_be_number, raw_string, convert_to, default_value, *field_names)
_to_decimal_string(ticks)
_hz_short_to_full(ticks, scale)
_hz_friendly_to_full(hz_string)
_hz_short_to_friendly(ticks, scale)
_to_friendly_bytes(input)
_friendly_bytes_to_int(friendly_bytes)
_parse_cpu_brand_string(cpu_string)
_parse_cpu_brand_string_dx(cpu_string)
_parse_dmesg_output(output)
_parse_arch(arch_string_raw)
_is_bit_set(reg, bit)
_is_selinux_enforcing(trace)
_filter_dict_keys_with_empty_values(info, acceptable_values={})
class ASM(restype=None, argtypes=(), machine_code=[])
     Bases: object
     compile()
     run()
     free()
class CPUID(trace=None)
     Bases: object
     _asm_func(restype=None, argtypes=(), machine_code=[])
```

_run_asm(*machine_code)

get_vendor_id()

get_info()

get_max_extension_support()

get_flags(max_extension_support)

get_processor_brand(max_extension_support)

get_cache(max_extension_support)

get_ticks_func()

get_raw_hz()

_get_cpu_info_from_cpuid_actual()

Warning! This function has the potential to crash the Python runtime. Do not call it directly. Use the _get_cpu_info_from_cpuid function instead. It will safely call this function in another process.

_get_cpu_info_from_cpuid_subprocess_wrapper(queue)

_get_cpu_info_from_cpuid()

Returns the CPU info gathered by querying the X86 cpuid register in a new process. Returns {} on non X86 cpus. Returns {} if SELinux is in enforcing mode.

_get_cpu_info_from_proc_cpuinfo()

Returns the CPU info gathered from /proc/cpuinfo. Returns { } if /proc/cpuinfo is not found.

_get_cpu_info_from_cpufreq_info()

Returns the CPU info gathered from cpufreq-info. Returns {} if cpufreq-info is not found.

_get_cpu_info_from_lscpu()

Returns the CPU info gathered from lscpu. Returns {} if lscpu is not found.

_get_cpu_info_from_dmesg()

Returns the CPU info gathered from dmesg. Returns {} if dmesg is not found or does not have the desired info.

_get_cpu_info_from_ibm_pa_features()

Returns the CPU info gathered from lsprop /proc/device-tree/cpus/*/ibm,pa-features Returns {} if lsprop is not found or ibm,pa-features does not have the desired info.

_get_cpu_info_from_cat_var_run_dmesg_boot()

Returns the CPU info gathered from /var/run/dmesg.boot. Returns {} if dmesg is not found or does not have the desired info.

_get_cpu_info_from_sysctl()

Returns the CPU info gathered from sysctl. Returns {} if sysctl is not found.

_get_cpu_info_from_sysinfo()

Returns the CPU info gathered from sysinfo. Returns {} if sysinfo is not found.

_get_cpu_info_from_sysinfo_v1()

Returns the CPU info gathered from sysinfo. Returns {} if sysinfo is not found.

_get_cpu_info_from_sysinfo_v2()

Returns the CPU info gathered from sysinfo. Returns {} if sysinfo is not found.

_get_cpu_info_from_wmic()

Returns the CPU info gathered from WMI. Returns {} if not on Windows, or wmic is not installed.

_get_cpu_info_from_registry()

Returns the CPU info gathered from the Windows Registry. Returns {} if not on Windows.

_get_cpu_info_from_kstat()

Returns the CPU info gathered from isainfo and kstat. Returns {} if isainfo or kstat are not found.

_get_cpu_info_from_platform_uname()

_get_cpu_info_internal()

Returns the CPU info by using the best sources of information for your OS. Returns {} if nothing is found.

get_cpu_info_json()

Returns the CPU info by using the best sources of information for your OS. Returns the result in a json string

get_cpu_info()

Returns the CPU info by using the best sources of information for your OS. Returns the result in a dict

main()

g_trace

Classes

Trace	
DataSource	
ASM	
CPUID	

Functions

_program_paths(program_name)

_run_and_get_stdout(command[, pipe_command])

```
_read_windows_registry_key(key_name,
field_name)
_check_arch()
```

_obj_to_b64(thing)

_b64_to_obj(thing)

continues on next page
Table $2 - continued from previous page$	Table	2 - continued	from	previous	page
--	-------	---------------	------	----------	------

	· · -
_utf_to_str(input)	
<pre>_copy_new_fields(info, new_info)</pre>	
_get_field_actual(cant_be_number, raw_string, field names)	
_get_field(cant_be_number, raw_string, convert_to,	
)	
_to_decimal_string(ticks)	
_hz_short_to_full(ticks, scale)	
_hz_friendly_to_full(hz_string)	
<pre>_hz_short_to_friendly(ticks, scale)</pre>	
_to_friendly_bytes(input)	
_friendly_bytes_to_int(friendly_bytes)	
_parse_cpu_brand_string(cpu_string)	
_parse_cpu_brand_string_dx(cpu_string)	
_parse_dmesg_output(output)	
_parse_arch(arch_string_raw)	
_is_bit_set(reg, bit)	
_is_selinux_enforcing(trace)	
_filter_dict_keys_with_empty_values(info[,])	
_get_cpu_info_from_cpuid_actual()	Warning! This function has the potential to crash the Python runtime.
_get_cpu_info_from_cpuid_subprocess_wrapper(
_get_cpu_info_from_cpuid()	Returns the CPU info gathered by querying the X86 cpuid register in a new process.
_get_cpu_info_from_proc_cpuinfo()	Returns the CPU info gathered from /proc/cpuinfo.
_get_cpu_info_from_cpufreq_info()	Returns the CPU info gathered from cpufreq-info.
_get_cpu_info_from_lscpu()	Returns the CPU info gathered from lscpu.
_get_cpu_info_from_dmesg()	Returns the CPU info gathered from dmesg.
<pre>_get_cpu_info_from_ibm_pa_features()</pre>	Returns the CPU info gathered from lsprop /proc/device-tree/cpus/*/ibm,pa-features
<pre>_get_cpu_info_from_cat_var_run_dmesg_boot()</pre>	Returns the CPU info gathered from /var/run/dmesg.boot.
_get_cpu_info_from_sysctl()	Returns the CPU info gathered from syscel.
_get_cpu_info_from_sysinfo()	Returns the CPU info gathered from sysinfo.
_get_cpu_info_from_sysinfo_v1()	Returns the CPU info gathered from sysinfo.
_get_cpu_info_from_sysinfo_v2()	Returns the CPU info gathered from sysinfo.

continues on next page

_get_cpu_info_from_wmic()	Returns the CPU info gathered from WMI.
<pre>_get_cpu_info_from_registry()</pre>	Returns the CPU info gathered from the Windows Reg- istry.
_get_cpu_info_from_kstat()	Returns the CPU info gathered from isainfo and kstat.
_get_cpu_info_from_platform_uname()	
_get_cpu_info_internal()	Returns the CPU info by using the best sources of infor- mation for your OS.
get_cpu_info_json()	Returns the CPU info by using the best sources of infor- mation for your OS.
<pre>get_cpu_info()</pre>	Returns the CPU info by using the best sources of infor- mation for your OS.
<pre>main()</pre>	

Table 2 – continued from previous page

Attributes

CPUINFO_VERSION
CPUINFO_VERSION_STRING
CAN_CALL_CPUID_IN_SUBPROCESS
g_trace
deprecated
$CPUINFO_VERSION = (9, 0, 0)$
CPUINFO_VERSION_STRING
CAN_CALL_CPUID_IN_SUBPROCESS = True
g_trace
class Trace(is_active, is_stored_in_string)
Bases: object
header(msg)
success()
<pre>fail(msg)</pre>
<pre>command_header(msg)</pre>
<pre>command_output(msg, output)</pre>
keys(keys, info, new_info)

write(msg)

to_dict(info, is_fail)

class DataSource

Bases: object

bits

cpu_count

is_windows

arch_string_raw

uname_string_raw

can_cpuid = True

static has_proc_cpuinfo()

static has_dmesg()

static has_var_run_dmesg_boot()

static has_cpufreq_info()

static has_sestatus()

static has_sysctl()

```
static has_isainfo()
```

static has_kstat()

static has_sysinfo()

static has_lscpu()

```
static has_ibm_pa_features()
```

```
static has_wmic()
```

```
static cat_proc_cpuinfo()
```

```
static cpufreq_info()
```

```
static sestatus_b()
```

```
static dmesg_a()
```

```
static cat_var_run_dmesg_boot()
```

static sysctl_machdep_cpu_hw_cpufrequency()

```
static isainfo_vb()
```

```
static kstat_m_cpu_info()
```

```
static sysinfo_cpu()
```

```
static lscpu()
```

```
static ibm_pa_features()
     static wmic_cpu()
     static winreg_processor_brand()
     static winreg_vendor_id_raw()
     static winreg_arch_string_raw()
     static winreg_hz_actual()
     static winreg_feature_bits()
_program_paths(program_name)
_run_and_get_stdout(command, pipe_command=None)
_read_windows_registry_key(key_name, field_name)
_check_arch()
_obj_to_b64(thing)
_b64_to_obj(thing)
_utf_to_str(input)
_copy_new_fields(info, new_info)
_get_field_actual(cant_be_number, raw_string, field_names)
_get_field(cant_be_number, raw_string, convert_to, default_value, *field_names)
_to_decimal_string(ticks)
_hz_short_to_full(ticks, scale)
_hz_friendly_to_full(hz_string)
_hz_short_to_friendly(ticks, scale)
_to_friendly_bytes(input)
_friendly_bytes_to_int(friendly_bytes)
_parse_cpu_brand_string(cpu_string)
_parse_cpu_brand_string_dx(cpu_string)
_parse_dmesg_output(output)
_parse_arch(arch_string_raw)
_is_bit_set(reg, bit)
_is_selinux_enforcing(trace)
_filter_dict_keys_with_empty_values(info, acceptable_values={})
```

class ASM(restype=None, argtypes=(), machine_code=[])
Bases: object
compile()

run()

free()

class CPUID(trace=None)

Bases: object

_asm_func(restype=None, argtypes=(), machine_code=[])

_run_asm(*machine_code)

get_vendor_id()

get_info()

get_max_extension_support()

get_flags(max_extension_support)

get_processor_brand(max_extension_support)

get_cache(max_extension_support)

get_ticks_func()

get_raw_hz()

_get_cpu_info_from_cpuid_actual()

Warning! This function has the potential to crash the Python runtime. Do not call it directly. Use the _get_cpu_info_from_cpuid function instead. It will safely call this function in another process.

_get_cpu_info_from_cpuid_subprocess_wrapper(queue)

_get_cpu_info_from_cpuid()

Returns the CPU info gathered by querying the X86 cpuid register in a new process. Returns {} on non X86 cpus. Returns {} if SELinux is in enforcing mode.

_get_cpu_info_from_proc_cpuinfo()

Returns the CPU info gathered from /proc/cpuinfo. Returns { } if /proc/cpuinfo is not found.

_get_cpu_info_from_cpufreq_info()

Returns the CPU info gathered from cpufreq-info. Returns { } if cpufreq-info is not found.

_get_cpu_info_from_lscpu()

Returns the CPU info gathered from lscpu. Returns {} if lscpu is not found.

_get_cpu_info_from_dmesg()

Returns the CPU info gathered from dmesg. Returns {} if dmesg is not found or does not have the desired info.

_get_cpu_info_from_ibm_pa_features()

Returns the CPU info gathered from lsprop /proc/device-tree/cpus/*/ibm,pa-features Returns {} if lsprop is not found or ibm,pa-features does not have the desired info.

_get_cpu_info_from_cat_var_run_dmesg_boot()

Returns the CPU info gathered from /var/run/dmesg.boot. Returns {} if dmesg is not found or does not have the desired info.

_get_cpu_info_from_sysctl()

Returns the CPU info gathered from sysctl. Returns {} if sysctl is not found.

_get_cpu_info_from_sysinfo()

Returns the CPU info gathered from sysinfo. Returns {} if sysinfo is not found.

_get_cpu_info_from_sysinfo_v1()

Returns the CPU info gathered from sysinfo. Returns {} if sysinfo is not found.

_get_cpu_info_from_sysinfo_v2()

Returns the CPU info gathered from sysinfo. Returns {} if sysinfo is not found.

_get_cpu_info_from_wmic()

Returns the CPU info gathered from WMI. Returns {} if not on Windows, or wmic is not installed.

_get_cpu_info_from_registry()

Returns the CPU info gathered from the Windows Registry. Returns {} if not on Windows.

_get_cpu_info_from_kstat()

Returns the CPU info gathered from isainfo and kstat. Returns {} if isainfo or kstat are not found.

_get_cpu_info_from_platform_uname()

_get_cpu_info_internal()

Returns the CPU info by using the best sources of information for your OS. Returns {} if nothing is found.

get_cpu_info_json()

Returns the CPU info by using the best sources of information for your OS. Returns the result in a json string

get_cpu_info()

Returns the CPU info by using the best sources of information for your OS. Returns the result in a dict

main()

deprecated

distro

The distro package (distro stands for Linux Distribution) provides information about the Linux distribution it runs on, such as a reliable machine-readable distro ID, or version information.

It is a renewed alternative implementation for Python's original platform.linux_distribution() function, but it provides much more functionality. An alternative implementation became necessary because Python 3.5 deprecated this function, and Python 3.7 is expected to remove it altogether. Its predecessor function platform.dist() was already deprecated since Python 2.6 and is also expected to be removed in Python 3.7. Still, there are many cases in which access to Linux distribution information is needed. See Python issue 1322 for more information.

Classes

Functions

<pre>linux_distribution([full_distribution_name])</pre>	Return information about the current Linux distribution as a tuple
id()	Return the distro ID of the current Linux distribution, as a
name([pretty])	Return the name of the current Linux distribution, as a human-readable
version([pretty, best])	Return the version of the current Linux distribution, as a human-readable
<pre>version_parts([best])</pre>	Return the version of the current Linux distribution as a tuple
<pre>major_version([best])</pre>	Return the major version of the current Linux distribu- tion, as a string,
<pre>minor_version([best])</pre>	Return the minor version of the current Linux distribu- tion, as a string,
<pre>build_number([best])</pre>	Return the build number of the current Linux distribu- tion, as a string,
like()	Return a space-separated list of distro IDs of distribu- tions that are
codename()	Return the codename for the release of the current Linux distribution,
<pre>info([pretty, best])</pre>	Return certain machine-readable information items about the current Linux
os_release_info()	Return a dictionary containing key-value pairs for the in- formation items
<pre>lsb_release_info()</pre>	Return a dictionary containing key-value pairs for the in- formation items
distro_release_info()	Return a dictionary containing key-value pairs for the in- formation items
os_release_attr(attribute)	Return a single named information item from the os- release file data source
lsb_release_attr(attribute)	Return a single named information item from the lsb_release command output
distro_release_attr(attribute)	Return a single named information item from the distro release file
main()	

Attributes

_UNIXCONFDIR

_OS_RELEASE_BASENAME

NORMALIZED_OS_ID

NORMALIZED_LSB_ID

NORMALIZED_DISTRO_ID

_DISTRO_RELEASE_CONTENT_REVERSED_PATTERN

_DISTRO_RELEASE_BASENAME_PATTERN

_DISTRO_RELEASE_IGNORE_BASENAMES

_distro

_UNIXCONFDIR

_OS_RELEASE_BASENAME = 'os-release'

NORMALIZED_OS_ID

NORMALIZED_LSB_ID

NORMALIZED_DISTRO_ID

_DISTRO_RELEASE_CONTENT_REVERSED_PATTERN

_DISTRO_RELEASE_BASENAME_PATTERN

_DISTRO_RELEASE_IGNORE_BASENAMES = ('debian_version', 'lsb-release', 'oem-release')

linux_distribution(*full_distribution_name=True*)

Return information about the current Linux distribution as a tuple (id_name, version, codename) with items as follows:

- id_name: If *full_distribution_name* is false, the result of distro.id(). Otherwise, the result of distro. name().
- version: The result of distro.version().
- codename: The result of distro.codename().

The interface of this function is compatible with the original platform.linux_distribution() function, supporting a subset of its parameters.

The data it returns may not exactly be the same, because it uses more data sources than the original function, and that may lead to different data if the Linux distribution is not consistent across multiple data sources it provides (there are indeed such distributions ...).

Another reason for differences is the fact that the distro.id() method normalizes the distro ID string to a reliable machine-readable value for a number of popular Linux distributions.

id()

Return the distro ID of the current Linux distribution, as a machine-readable string.

For a number of Linux distributions, the returned distro ID value is *reliable*, in the sense that it is documented and that it does not change across releases of the distribution.

This package maintains the following reliable distro ID values:

Distro ID	Distribution
"ubuntu"	Ubuntu
"debian"	Debian
"rhel"	RedHat Enterprise Linux
"centos"	CentOS
"fedora"	Fedora
"sles"	SUSE Linux Enterprise Server
"opensuse"	openSUSE
"amazon"	Amazon Linux
"arch"	Arch Linux
"cloudlinux"	CloudLinux OS
"exherbo"	Exherbo Linux
"gentoo"	GenToo Linux
"ibm_powerkvm"	IBM PowerKVM
"kvmibm"	KVM for IBM z Systems
"linuxmint"	Linux Mint
"mageia"	Mageia
"mandriva"	Mandriva Linux
"parallels"	Parallels
"pidora"	Pidora
"raspbian"	Raspbian
"oracle"	Oracle Linux (and Oracle Enterprise Linux)
"scientific"	Scientific Linux
"slackware"	Slackware
"xenserver"	XenServer

If you have a need to get distros for reliable IDs added into this set, or if you find that the distro.id() function returns a different distro ID for one of the listed distros, please create an issue in the `distro issue tracker`_.

Lookup hierarchy and transformations:

First, the ID is obtained from the following sources, in the specified order. The first available and non-empty value is used:

- the value of the "ID" attribute of the os-release file,
- the value of the "Distributor ID" attribute returned by the lsb_release command,
- the first part of the file name of the distro release file,

The so determined ID value then passes the following transformations, before it is returned by this method:

- it is translated to lower case,
- blanks (which should not be there anyway) are translated to underscores,
- a normalization of the ID is performed, based upon `normalization tables`_. The purpose of this normalization is to ensure that the ID is as reliable as possible, even across incompatible changes in the Linux distributions. A common reason for an incompatible change is the addition of an os-release file, or the

addition of the lsb_release command, with ID values that differ from what was previously determined from the distro release file name.

name(pretty=False)

Return the name of the current Linux distribution, as a human-readable string.

If *pretty* is false, the name is returned without version or codename. (e.g. "CentOS Linux")

If pretty is true, the version and codename are appended. (e.g. "CentOS Linux 7.1.1503 (Core)")

Lookup hierarchy:

The name is obtained from the following sources, in the specified order. The first available and non-empty value is used:

- If *pretty* is false:
 - the value of the "NAME" attribute of the os-release file,
 - the value of the "Distributor ID" attribute returned by the lsb_release command,
 - the value of the "<name>" field of the distro release file.
- If *pretty* is true:
 - the value of the "PRETTY_NAME" attribute of the os-release file,
 - the value of the "Description" attribute returned by the lsb_release command,
 - the value of the "<name>" field of the distro release file, appended with the value of the pretty version ("<version_id>" and "<codename>" fields) of the distro release file, if available.

version(pretty=False, best=False)

Return the version of the current Linux distribution, as a human-readable string.

If *pretty* is false, the version is returned without codename (e.g. "7.0").

If pretty is true, the codename in parenthesis is appended, if the codename is non-empty (e.g. "7.0 (Maipo)").

Some distributions provide version numbers with different precisions in the different sources of distribution information. Examining the different sources in a fixed priority order does not always yield the most precise version (e.g. for Debian 8.2, or CentOS 7.1).

The *best* parameter can be used to control the approach for the returned version:

If *best* is false, the first non-empty version number in priority order of the examined sources is returned.

If best is true, the most precise version number out of all examined sources is returned.

Lookup hierarchy:

In all cases, the version number is obtained from the following sources. If *best* is false, this order represents the priority order:

- the value of the "VERSION_ID" attribute of the os-release file,
- the value of the "Release" attribute returned by the lsb_release command,
- the version number parsed from the "<version_id>" field of the first line of the distro release file,
- the version number parsed from the "PRETTY_NAME" attribute of the os-release file, if it follows the format of the distro release files.
- the version number parsed from the "Description" attribute returned by the lsb_release command, if it follows the format of the distro release files.

version_parts(best=False)

Return the version of the current Linux distribution as a tuple (major, minor, build_number) with items as follows:

- major: The result of distro.major_version().
- minor: The result of distro.minor_version().
- build_number: The result of distro.build_number().

For a description of the *best* parameter, see the distro.version() method.

major_version(best=False)

Return the major version of the current Linux distribution, as a string, if provided. Otherwise, the empty string is returned. The major version is the first part of the dot-separated version string.

For a description of the *best* parameter, see the distro.version() method.

minor_version(best=False)

Return the minor version of the current Linux distribution, as a string, if provided. Otherwise, the empty string is returned. The minor version is the second part of the dot-separated version string.

For a description of the *best* parameter, see the distro.version() method.

build_number(best=False)

Return the build number of the current Linux distribution, as a string, if provided. Otherwise, the empty string is returned. The build number is the third part of the dot-separated version string.

For a description of the *best* parameter, see the distro.version() method.

like()

Return a space-separated list of distro IDs of distributions that are closely related to the current Linux distribution in regards to packaging and programming interfaces, for example distributions the current distribution is a derivative from.

Lookup hierarchy:

This information item is only provided by the os-release file. For details, see the description of the "ID_LIKE" attribute in the os-release man page.

codename()

Return the codename for the release of the current Linux distribution, as a string.

If the distribution does not have a codename, an empty string is returned.

Note that the returned codename is not always really a codename. For example, openSUSE returns "x86_64". This function does not handle such cases in any special way and just returns the string it finds, if any.

Lookup hierarchy:

- the codename within the "VERSION" attribute of the os-release file, if provided,
- the value of the "Codename" attribute returned by the lsb_release command,
- the value of the "<codename>" field of the distro release file.

info(pretty=False, best=False)

Return certain machine-readable information items about the current Linux distribution in a dictionary, as shown in the following example:

```
{
    'id': 'rhel',
    'version': '7.0',
    'version_parts': {
        'major': '7',
        'minor': '0',
        'build_number': ''
    },
    'like': 'fedora',
    'codename': 'Maipo'
}
```

The dictionary structure and keys are always the same, regardless of which information items are available in the underlying data sources. The values for the various keys are as follows:

- id: The result of distro.id().
- version: The result of distro.version().
- version_parts -> major: The result of distro.major_version().
- version_parts -> minor: The result of distro.minor_version().
- version_parts -> build_number: The result of distro.build_number().
- like: The result of distro.like().
- codename: The result of distro.codename().

For a description of the *pretty* and *best* parameters, see the distro.version() method.

os_release_info()

Return a dictionary containing key-value pairs for the information items from the os-release file data source of the current Linux distribution.

See `os-release file`_ for details about these information items.

lsb_release_info()

Return a dictionary containing key-value pairs for the information items from the lsb_release command data source of the current Linux distribution.

See `lsb_release command output`_ for details about these information items.

distro_release_info()

Return a dictionary containing key-value pairs for the information items from the distro release file data source of the current Linux distribution.

See `distro release file`_ for details about these information items.

os_release_attr(attribute)

Return a single named information item from the os-release file data source of the current Linux distribution.

Parameters:

• attribute (string): Key of the information item.

Returns:

• (string): Value of the information item, if the item exists. The empty string, if the item does not exist.

See `os-release file`_ for details about these information items.

lsb_release_attr(attribute)

Return a single named information item from the lsb_release command output data source of the current Linux distribution.

Parameters:

• attribute (string): Key of the information item.

Returns:

• (string): Value of the information item, if the item exists. The empty string, if the item does not exist.

See `lsb_release command output`_ for details about these information items.

distro_release_attr(attribute)

Return a single named information item from the distro release file data source of the current Linux distribution. Parameters:

didificters.

• attribute (string): Key of the information item.

Returns:

• (string): Value of the information item, if the item exists. The empty string, if the item does not exist.

See `distro release file`_ for details about these information items.

class LinuxDistribution(include_lsb=True, os_release_file=", distro_release_file=")

Bases: object

Provides information about a Linux distribution.

This package creates a private module-global instance of this class with default initialization arguments, that is used by the `consolidated accessor functions`_ and `single source accessor functions`_. By using default initialization arguments, that module-global instance returns data about the current Linux distribution (i.e. the distro this package runs on).

Normally, it is not necessary to create additional instances of this class. However, in situations where control is needed over the exact data sources that are used, instances of this class can be created with a specific distro release file, or a specific os-release file, or without invoking the lsb_release command.

```
__repr__()
```

Return repr of all info

linux_distribution(*full_distribution_name=True*)

Return information about the Linux distribution that is compatible with Python's platform. linux_distribution(), supporting a subset of its parameters.

For details, see distro.linux_distribution().

id()

Return the distro ID of the Linux distribution, as a string.

For details, see distro.id().

name(pretty=False)

Return the name of the Linux distribution, as a string.

For details, see distro.name().

version(pretty=False, best=False)

Return the version of the Linux distribution, as a string.

For details, see distro.version().

version_parts(best=False)

Return the version of the Linux distribution, as a tuple of version numbers.

For details, see distro.version_parts().

major_version(best=False)

Return the major version number of the current distribution.

For details, see distro.major_version().

minor_version(best=False)

Return the minor version number of the Linux distribution.

For details, see distro.minor_version().

build_number(best=False)

Return the build number of the Linux distribution.

For details, see distro.build_number().

like()

Return the IDs of distributions that are like the Linux distribution.

For details, see distro.like().

codename()

Return the codename of the Linux distribution.

For details, see distro.codename().

info(pretty=False, best=False)

Return certain machine-readable information about the Linux distribution.

For details, see distro.info().

os_release_info()

Return a dictionary containing key-value pairs for the information items from the os-release file data source of the Linux distribution.

For details, see distro.os_release_info().

lsb_release_info()

Return a dictionary containing key-value pairs for the information items from the lsb_release command data source of the Linux distribution.

For details, see distro.lsb_release_info().

distro_release_info()

Return a dictionary containing key-value pairs for the information items from the distro release file data source of the Linux distribution.

For details, see distro.distro_release_info().

os_release_attr(attribute)

Return a single named information item from the os-release file data source of the Linux distribution.

For details, see distro.os_release_attr().

lsb_release_attr(attribute)

Return a single named information item from the lsb_release command output data source of the Linux distribution.

For details, see distro.lsb_release_attr().

distro_release_attr(attribute)

Return a single named information item from the distro release file data source of the Linux distribution.

For details, see distro_distro_release_attr().

_get_os_release_info()

Get the information items from the specified os-release file.

Returns

A dictionary containing all information items.

static _parse_os_release_content(lines)

Parse the lines of an os-release file.

Parameters:

• lines: Iterable through the lines in the os-release file.

Each line must be a unicode string or a UTF-8 encoded byte string.

Returns

A dictionary containing all information items.

_get_lsb_release_info()

Get the information items from the lsb_release command output.

Returns

A dictionary containing all information items.

static _parse_lsb_release_content(lines)

Parse the output of the lsb_release command.

Parameters:

• lines: Iterable through the lines of the lsb_release output. Each line must be a unicode string or a UTF-8 encoded byte string.

Returns

A dictionary containing all information items.

_get_distro_release_info()

Get the information items from the specified distro release file.

Returns

A dictionary containing all information items.

_parse_distro_release_file(filepath)

Parse a distro release file.

Parameters:

• filepath: Path name of the distro release file.

Returns

A dictionary containing all information items.

static _parse_distro_release_content(line)

Parse a line from a distro release file.

Parameters: * line: Line from the distro release file. Must be a unicode string

or a UTF-8 encoded byte string.

Returns

A dictionary containing all information items.

_distro

main()

frozendict

Classes

frozendict	An immutable wrapper around dictionaries that imple-
	ments the complete collections.Mapping
FrozenOrderedDict	A frozendict subclass that maintains key order

Attributes

deprecated			
OrderedDict			
iteritems			

deprecated

OrderedDict

iteritems

class frozendict(*args, **kwargs)

Bases: collections.abc.Mapping

An immutable wrapper around dictionaries that implements the complete collections. Mapping interface. It can be used as a drop-in replacement for dictionaries where immutability is desired.

dict_cls

```
__getitem__(key)
```

```
__contains__(key)
```

copy(**add_or_replace)

__iter__()

__len__()

__repr__() Return repr(self). __hash__() Return hash(self). __json__() to_json() class FrozenOrderedDict(*args, **kwargs) Bases: frozendict A frozendict subclass that maintains key order dict_cls _version **TYPE_CHECKING = False** VERSION_TUPLE version: str __version__: str __version_tuple__: VERSION_TUPLE version_tuple: VERSION_TUPLE

activate

Conda activate and deactivate logic.

Implementation for all shell interface logic exposed via *conda shell.*[activate|deactivate|reactivate|hook|commands]*. This includes a custom argument parser, an abstract shell class, and special path handling for Windows.

See conda.cli.main.main_sourced for the entry point into this module.

Classes

_Activator	
PosixActivator	
CshActivator	
XonshActivator	
CmdExeActivator	
FishActivator	
PowerShellActivator	
JSONFormatMixin	Returns the necessary values for activation as JSON, so that tools can use them.

Functions

expand(path)	
ensure_binary(value)	
<pre>ensure_fs_path_encoding(value)</pre>	
<i>native_path_to_unix</i> (→ str tuple[str, Ellipsis] None)	
$path_identity(\rightarrow str tuple[str, Ellipsis] None)$	
$backslash_to_forwardslash(\rightarrow str tuple[str,)$	
_build_activator_cls(shell)	Dynamically construct the activator class.

Attributes

activator_map

formatter_map

class _Activator(arguments=None)

pathsep_join: str

sep: str

```
path_conversion: collections.abc.Callable[[str | collections.abc.Iterable[str] |
None], str | tuple[str, Ellipsis] | None]
```

script_extension: str

tempfile_extension: str | None

command_join: str

unset_var_tmpl: str

export_var_tmpl: str

set_var_tmpl: str

run_script_tmpl: str

hook_source_path: pathlib.Path | None

get_export_unset_vars(export_metavars=True, **kwargs)

Parameters

- **export_metavars** -- whether to export *conda_exe_vars* meta variables.
- **kwargs** -- environment variables to export. .. if you pass and set any other variable to None, then it emits it to the dict with a value of None.

Returns

A dict of env vars to export ordered the same way as kwargs. And a list of env vars to unset.

add_export_unset_vars(export_vars, unset_vars, **kwargs)

```
_finalize(commands, ext)
```

activate()

deactivate()

reactivate()

hook(*auto_activate_base: bool* | *None* = *None*) \rightarrow str

execute()

commands()

Returns a list of possible subcommands that are valid immediately following *conda* at the command line. This method is generally only used by tab-completion.

abstract _hook_preamble() \rightarrow str | None

```
hook_postamble() \rightarrow str | None
```

_parse_and_set_args(arguments)

_yield_commands(cmds_dict)

```
build_activate(env_name_or_prefix)
```

build_stack(env_name_or_prefix)

_build_activate_stack(env_name_or_prefix, stack)

build_deactivate()

build_reactivate()

_get_starting_path_list()

_get_path_dirs(prefix)

_add_prefix_to_path(prefix, starting_path_dirs=None)

_remove_prefix_from_path(prefix, starting_path_dirs=None)

_replace_prefix_in_path(old_prefix, new_prefix, starting_path_dirs=None)

_update_prompt(set_vars, conda_prompt_modifier)

_default_env(prefix)

_prompt_modifier(prefix, conda_default_env)

```
_get_activate_scripts(prefix)
```

_get_deactivate_scripts(prefix)

_get_environment_env_vars(prefix)

expand(path)

```
ensure_binary(value)
```

```
ensure_fs_path_encoding(value)
```

```
native_path_to_unix(paths: str | collections.abc.Iterable[str] | None) \rightarrow str | tuple[str, Ellipsis] | None
```

path_identity(*paths: str* | *collections.abc.Iterable[str*] | *None*) \rightarrow str | tuple[str, Ellipsis] | None

backslash_to_forwardslash(*paths: str* | *collections.abc.Iterable*[*str*] | *None*) \rightarrow str | tuple[str, Ellipsis] | None

```
class PosixActivator(arguments=None)
```

```
Bases: _Activator
pathsep_join
```

```
sep = '/'
```

path_conversion

```
script_extension = '.sh'
tempfile_extension
```

command_join = '\n'

```
unset_var_tmpl = 'unset %s'
```

```
export_var_tmpl = "export %s='%s'"
```

set_var_tmpl = "%s='%s'" run_script_tmpl = '. "%s"' hook_source_path _update_prompt(set_vars, conda_prompt_modifier) $hook_preamble() \rightarrow str$ class CshActivator(arguments=None) Bases: _Activator pathsep_join sep = '/' path_conversion script_extension = '.csh' tempfile_extension command_join = ';\n' unset_var_tmpl = 'unsetenv %s' export_var_tmpl = 'setenv %s "%s"' set_var_tmpl = "set %s='%s'" run_script_tmpl = 'source "%s"' hook_source_path _update_prompt(set_vars, conda_prompt_modifier) $hook_preamble() \rightarrow str$ class XonshActivator(arguments=None) Bases: _Activator pathsep_join sep = '/' path_conversion script_extension tempfile_extension command_join = '\n' unset_var_tmpl = 'del \$%s' export_var_tmpl = "\$%s = '%s'" set_var_tmpl = "\$%s = '%s'" run_script_tmpl

```
hook_source_path
     hook_preamble() \rightarrow str
class CmdExeActivator(arguments=None)
     Bases: _Activator
     pathsep_join
     sep = ' \ '
     path_conversion
     script_extension = '.bat'
     tempfile_extension = '.bat'
     command_join = ' n'
     unset_var_tmpl = '@SET %s='
     export_var_tmpl = '@SET "%s=%s"'
     set_var_tmpl = '@SET "%s=%s"'
     run_script_tmpl = '@CALL "%s"'
     hook_source_path
     hook_preamble() \rightarrow None
class FishActivator(arguments=None)
     Bases: _Activator
     pathsep_join
     sep = '/'
     path_conversion
     script_extension = '.fish'
     tempfile_extension
     command_join = ';\n'
     unset_var_tmpl = 'set -e %s'
     export_var_tmpl = 'set -gx %s "%s"'
     set_var_tmpl = 'set -g %s "%s"'
     run_script_tmpl = 'source "%s"'
     hook_source_path
     hook_preamble() \rightarrow str
class PowerShellActivator(arguments=None)
     Bases: _Activator
```

```
pathsep_join
sep
path_conversion
script_extension = '.ps1'
tempfile_extension
command_join = '\n'
unset_var_tmpl = '$Env:%s = ""'
export_var_tmpl = '$Env:%s = "%s"'
set_var_tmpl = '$Env:%s = "%s"'
run_script_tmpl = '. "%s"'
hook_source_path
_hook_preamble() → str
_hook_postamble() → str
```

```
class JSONFormatMixin(arguments=None)
```

Bases: _Activator

Returns the necessary values for activation as JSON, so that tools can use them.

pathsep_join

tempfile_extension

command_join

```
_hook_preamble()
```

```
get_scripts_export_unset_vars(**kwargs)
```

```
_finalize(commands, ext)
```

_yield_commands(cmds_dict)

activator_map: dict[str, type[_Activator]]

formatter_map

_build_activator_cls(shell)

Dynamically construct the activator class.

Detect the base activator and any number of formatters (appended using '+' to the base name). For example, *posix+json* (as in *conda shell.posix+json activate*) would use the *PosixActivator* base class and add the *JSON-FormatMixin*.

api

Collection of conda's high-level APIs.

Classes

Solver	Beta While in beta, expect both major and minor
	changes across minor releases.
SubdirData	Beta While in beta, expect both major and minor
	changes across minor releases.
PackageCacheData	Beta While in beta, expect both major and minor
	changes across minor releases.
PrefixData	Beta While in beta, expect both major and minor
	changes across minor releases.

Attributes

DepsModifier

UpdateModifier

DepsModifier

UpdateModifier

class Solver(*prefix*, *channels*, *subdirs*=(), *specs_to_add*=(), *specs_to_remove*=())

Beta While in beta, expect both major and minor changes across minor releases.

A high-level API to conda's solving logic. Three public methods are provided to access a solution in various forms.

- solve_final_state()
- solve_for_diff()
- solve_for_transaction()

Beta While in beta, expect both major and minor changes across minor releases.

Gives the final, solved state of the environment.

Parameters

• **deps_modifier** (DepsModifier) -- An optional flag indicating special solver handling for dependencies. The default solver behavior is to be as conservative as possible with dependency updates (in the case the dependency already exists in the environment), while still ensuring all dependencies are satisfied. Options include * NO_DEPS * ONLY_DEPS * UPDATE_DEPS * UPDATE_DEPS_ONLY_DEPS * FREEZE_INSTALLED

- **prune** (*bool*) -- If **True**, the solution will not contain packages that were previously brought into the environment as dependencies but are no longer required as dependencies and are not user-requested.
- **ignore_pinned** (*bool*) -- If True, the solution will ignore pinned package configuration for the prefix.
- **force_remove** (*bool*) -- Forces removal of a package without removing packages that depend on it.

Returns

In sorted dependency order from roots to leaves, the package references for the solved state of the environment.

Return type

tuple[PackageRef]

solve_for_diff(update_modifier=NULL, deps_modifier=NULL, prune=NULL, ignore_pinned=NULL, force_remove=NULL, force_reinstall=False)

Beta While in beta, expect both major and minor changes across minor releases.

Gives the package references to remove from an environment, followed by the package references to add to an environment.

Parameters

- deps_modifier (DepsModifier) -- See solve_final_state().
- prune (bool) -- See solve_final_state().
- **ignore_pinned** (bool) -- See solve_final_state().
- force_remove(bool) -- See solve_final_state().
- **force_reinstall** (*bool*) -- For requested specs_to_add that are already satisfied in the environment, instructs the solver to remove the package and spec from the environment, and then add it back--possibly with the exact package instance modified, depending on the spec exactness.

Returns

A two-tuple of PackageRef sequences. The first is the group of packages to remove from the environment, in sorted dependency order from leaves to roots. The second is the group of packages to add to the environment, in sorted dependency order from roots to leaves.

Return type

tuple[PackageRef], tuple[PackageRef]

Beta While in beta, expect both major and minor changes across minor releases.

Gives an UnlinkLinkTransaction instance that can be used to execute the solution on an environment.

Parameters

- deps_modifier (DepsModifier) -- See solve_final_state().
- prune (bool) -- See solve_final_state().
- **ignore_pinned** (bool) -- See solve_final_state().
- **force_remove** (bool) -- See solve_final_state().
- force_reinstall (bool) -- See solve_for_diff().

Return type

UnlinkLinkTransaction

class SubdirData(channel)

Beta While in beta, expect both major and minor changes across minor releases.

High-level management and usage of repodata.json for subdirs.

query(package_ref_or_match_spec)

Beta While in beta, expect both major and minor changes across minor releases.

Run a query against this specific instance of repodata.

Parameters

package_ref_or_match_spec (PackageRef or MatchSpec or str) -- Either an exact PackageRef to match against, or a MatchSpec query object. A str will be turned into a MatchSpec automatically.

Returns

tuple[PackageRecord]

static query_all(package_ref_or_match_spec, channels=None, subdirs=None)

Beta While in beta, expect both major and minor changes across minor releases.

Run a query against all repodata instances in channel/subdir matrix.

Parameters

- package_ref_or_match_spec (*PackageRef or* MatchSpec *or str*) -- Either an exact PackageRef to match against, or a MatchSpec query object. A str will be turned into a MatchSpec automatically.
- **channels** (*Iterable*[Channel or *str*] or *None*) -- An iterable of urls for channels or Channel objects. If None, will fall back to context.channels.
- subdirs (Iterable[str] or None) -- If None, will fall back to context.subdirs.

Returns

tuple[PackageRecord]

iter_records()

Beta While in beta, expect both major and minor changes across minor releases.

Returns

A generator over all records contained in the repodata.json

instance. Warning: this is a generator that is exhausted on first use.

Return type

Iterable[PackageRecord]

reload()

Beta While in beta, expect both major and minor changes across minor releases.

Update the instance with new information. Backing information (i.e. repodata.json) is lazily down-loaded/loaded on first use by the other methods of this class. You should only use this method if you are *sure* you have outdated data.

Returns

SubdirData

class PackageCacheData(pkgs_dir)

Beta While in beta, expect both major and minor changes across minor releases.

High-level management and usage of package caches.

property is_writable

Beta While in beta, expect both major and minor changes across minor releases.

Indicates if the package cache location is writable or read-only.

Returns bool

get(package_ref, default=NULL)

Beta While in beta, expect both major and minor changes across minor releases.

Parameters

- **package_ref** (*PackageRef*) -- A PackageRef instance representing the key for the PackageCacheRecord being sought.
- **default** -- The default value to return if the record does not exist. If not specified and no record exists, KeyError is raised.

Returns

PackageCacheRecord

query(package_ref_or_match_spec)

Beta While in beta, expect both major and minor changes across minor releases.

Run a query against this specific package cache instance.

Parameters

package_ref_or_match_spec (*PackageRef or* MatchSpec *or str*) -- Either an exact PackageRef to match against, or a MatchSpec query object. A str will be turned into a MatchSpec automatically.

Returns

tuple[PackageCacheRecord]

static query_all(package_ref_or_match_spec, pkgs_dirs=None)

Beta While in beta, expect both major and minor changes across minor releases.

Run a query against all package caches.

Parameters

- package_ref_or_match_spec (*PackageRef or* MatchSpec *or str*) -- Either an exact PackageRef to match against, or a MatchSpec query object. A str will be turned into a MatchSpec automatically.
- pkgs_dirs (Iterable[str] or None) -- If None, will fall back to context.pkgs_dirs.

Returns

tuple[PackageCacheRecord]

iter_records()

Beta While in beta, expect both major and minor changes across minor releases.

Returns

A generator over all records contained in the package

cache instance. Warning: this is a generator that is exhausted on first use.

Return type

Iterable[PackageCacheRecord]

static first_writable(pkgs_dirs=None)

Beta While in beta, expect both major and minor changes across minor releases.

Get an instance object for the first writable package cache.

Parameters

pkgs_dirs (Iterable[str]) -- If None, will fall back to context.pkgs_dirs.

Returns

An instance for the first writable package cache.

Return type

PackageCacheData

reload()

Beta While in beta, expect both major and minor changes across minor releases.

Update the instance with new information. Backing information (i.e. contents of the pkgs_dir) is lazily loaded on first use by the other methods of this class. You should only use this method if you are *sure* you have outdated data.

Returns

PackageCacheData

class PrefixData(prefix_path)

Beta While in beta, expect both major and minor changes across minor releases.

High-level management and usage of conda environment prefixes.

property is_writable

Beta While in beta, expect both major and minor changes across minor releases.

Indicates if the prefix is writable or read-only.

Returns

True if the prefix is writable. False if read-only. None if the prefix does not exist as a conda environment.

Return type

bool or None

get(package_ref, default=NULL)

Beta While in beta, expect both major and minor changes across minor releases.

Parameters

- **package_ref** (*PackageRef*) -- A PackageRef instance representing the key for the PrefixRecord being sought.
- **default** -- The default value to return if the record does not exist. If not specified and no record exists, KeyError is raised.

Returns

PrefixRecord

query(package_ref_or_match_spec)

Beta While in beta, expect both major and minor changes across minor releases.

Run a query against this specific prefix instance.

Parameters

package_ref_or_match_spec (*PackageRef or* MatchSpec *or str*) -- Either an exact PackageRef to match against, or a MatchSpec query object. A str will be turned into a MatchSpec automatically.

Returns

tuple[PrefixRecord]

iter_records()

Beta While in beta, expect both major and minor changes across minor releases.

Returns

A generator over all records contained in the prefix.

Warning: this is a generator that is exhausted on first use.

Return type

Iterable[PrefixRecord]

reload()

Beta While in beta, expect both major and minor changes across minor releases.

Update the instance with new information. Backing information (i.e. contents of the conda-meta directory) is lazily loaded on first use by the other methods of this class. You should only use this method if you are *sure* you have outdated data.

Returns

PrefixData

auxlib

Auxlib is an auxiliary library to the python standard library.

The aim is to provide core generic features for app development in python. Auxlib fills in some python stdlib gaps much like pytoolz has for functional programming, pyrsistent has for data structures, or boltons has generally.

Major areas addressed include:

- packaging: package versioning, with a clean and less invasive alternative to versioneer
- entity: robust base class for type-enforced data models and transfer objects
- type_coercion: intelligent type coercion utilities
- *Configuration*: a map implementation designed specifically to hold application configuration and context information
- factory: factory pattern implementation
- path: file path utilities especially helpful when working with various python package formats
- logz: logging initialization routines to simplify python logging setup
- crypt: simple, but correct, pycrypto wrapper

[2021-11-09] Our version of auxlib has deviated from the upstream project by a significant amount (especially compared with the other vendored packages). Further, the upstream project has low popularity and is no longer actively maintained. Consequently it was decided to absorb, refactor, and replace auxlib. As a first step of this process we moved conda._vendor.auxlib to conda.auxlib.

collection

Common collection classes.

Classes

AttrDict	Sub-classes dict, and further allows attribute-like access to dictionary items.
Functions	
<pre>make_immutable(value)</pre>	
<pre>first(seq[, key, default, apply])</pre>	Give the first value that satisfies the key test.
<pre>firstitem(map[, key, default, apply])</pre>	

last(seq[, key, default, apply])

call_each(seq)

Calls each element of sequence to invoke the side effect.

make_immutable(value)

class AttrDict(*args, **kwargs)

Bases: dict

Sub-classes dict, and further allows attribute-like access to dictionary items.

Examples

```
>>> d = AttrDict({'a': 1})
>>> d.a, d['a'], d.get('a')
(1, 1, 1)
>>> d.b = 2
>>> d.b, d['b']
(2, 2)
```

first(seq, key=bool, default=None, apply=lambda x: ...)

Give the first value that satisfies the key test.

Parameters

- seq(iterable)
- **key** (*callable*) -- test for each element of iterable
- default -- returned when all elements fail test
- apply (callable) -- applied to element before return, but not to default value

Returns: first element in seq that passes key, mutated with optional apply

Examples

```
>>> first([0, False, None, [], (), 42])
42
>>> first([0, False, None, [], ()]) is None
True
>>> first([0, False, None, [], ()], default='ohai')
'ohai'
>>> import re
>>> m = first(re.match(regex, 'abc') for regex in ['b.*', 'a(.*)'])
>>> m.group(1)
'bc'
```

The optional *key* argument specifies a one-argument predicate function like that used for *filter()*. The *key* argument, if supplied, must be in keyword form. For example: >>> first([1, 1, 3, 4, 5], key=lambda x: x % 2 == 0) 4

firstitem(map, key=lambda k, v: ..., default=None, apply=lambda k, v: ...)

last(seq, key=bool, default=None, apply=lambda x: ...)

call_each(seq)

Calls each element of sequence to invoke the side effect.

Parameters seq

Returns: None

compat

Functions

isiterable(obj)

shlex_split_unicode(to_split[, posix])

utf8_writer(fp)

```
Utf8NamedTemporaryFile([mode, buffering, new-
line, ...])
```

isiterable(obj)

shlex_split_unicode(to_split, posix=True)

utf8_writer(fp)

Utf8NamedTemporaryFile(*mode='w+b'*, *buffering=-1*, *newline=None*, *suffix=None*, *prefix=None*, *dir=None*, *delete=True*)

decorators

Classes

classproperty

Functions

<pre>memoizemethod(method)</pre>	Decorator to cause a method to cache it's results in self for each
<pre>clear_memoized_methods(obj, *method_names)</pre>	Clear the memoized method or @memoizedproperty re- sults for the given
<pre>memoizedproperty(func)</pre>	Decorator to cause a method to cache it's results in self for each

memoizemethod(method)

Decorator to cause a method to cache it's results in self for each combination of inputs and return the cached result on subsequent calls. Does not support named arguments or arg values that are not hashable.

```
>>> class Foo (object):
      @memoizemethod
. . .
      def foo(self, x, y=0):
. . .
        print('running method with', x, y)
. . .
        return x + y + 3
. . .
. . .
\rightarrow foo1 = Foo()
\rightarrow foo2 = Foo()
>>> foo1.foo(10)
running method with 10 0
13
>>> foo1.foo(10)
13
>>> foo2.foo(11, y=7)
running method with 11 7
21
>>> foo2.foo(11)
running method with 11 0
14
>>> foo2.foo(11, y=7)
21
>>> class Foo (object):
      def __init__(self, lower):
. . .
        self.lower = lower
. . .
      @memoizemethod
. . .
      def range_tuple(self, upper):
. . .
        print('running function')
. . .
        return tuple(i for i in range(self.lower, upper))
. . .
      @memoizemethod
. . .
```

(continues on next page)

(continued from previous page)

```
def range_iter(self, upper):
. . .
        print('running function')
. . .
        return (i for i in range(self.lower, upper))
. . .
. . .
\rightarrow foo = Foo(3)
>>> foo.range_tuple(6)
running function
(3, 4, 5)
>>> foo.range_tuple(7)
running function
(3, 4, 5, 6)
>>> foo.range_tuple(6)
(3, 4, 5)
>>> foo.range_iter(6)
Traceback (most recent call last):
TypeError: Can't memoize a generator or non-hashable object!
```

clear_memoized_methods(obj, *method_names)

Clear the memoized method or @memoizedproperty results for the given method names from the given object.

```
\gg v = [0]
>>> def inc():
        v[0] += 1
. . .
        return v[0]
. . .
. . .
>>> class Foo(object):
       @memoizemethod
. . .
       def foo(self):
. . .
           return inc()
. . .
       @memoizedproperty
. . . .
       def g(self):
. . .
          return inc()
. . .
. . .
\gg f = Foo()
>>> f.foo(), f.foo()
(1, 1)
>>> clear_memoized_methods(f, 'foo')
>>> (f.foo(), f.foo(), f.g, f.g)
(2, 2, 3, 3)
>>> (f.foo(), f.foo(), f.g, f.g)
(2, 2, 3, 3)
>>> clear_memoized_methods(f, 'g', 'no_problem_if_undefined')
>>> f.g, f.foo(), f.g
(4, 2, 4)
>>> f.foo()
2
```

memoizedproperty(func)

Decorator to cause a method to cache it's results in self for each combination of inputs and return the cached result on subsequent calls. Does not support named arguments or arg values that are not hashable.

>>> class Foo (object):

(continues on next page)

(continued from previous page)

```
x = 1
. . . .
      @memoizedproperty
. . .
      def foo(self):
. . .
        self._x += 1
. . . .
        print('updating and returning {0}'.format(self._x))
. . .
        return self._x
. . .
. . .
>>> foo1 = Foo()
>>> foo2 = Foo()
>>> foo1.foo
updating and returning 2
2
>>> foo1.foo
2
>>> foo2.foo
updating and returning 2
2
>>> foo1.foo
2
```

class classproperty(getter=None, setter=None)

__get__(obj, type_=None)
__set__(obj, value)
setter(setter)

entity

This module provides serializable, validatable, type-enforcing domain objects and data transfer objects. It has many of the same motivations as the python Marshmallow package. It is most similar to Schematics.

Tutorial

Chapter 1: Entity and Field Basics

```
>>> # create a new car object
>>> car = Car(color=Color.blue, weight=4242.46)
>>> car
Car(weight=4242.46, color=0)
```

```
>>> # it has 4 wheels, all by default
>>> car.wheels
4
```

```
>>> # but a car can't have 5 wheels!
>>> # the `validation=` field is a simple callable that returns a
>>> # boolean based on validity
>>> car.wheels = 5
Traceback (most recent call last):
ValidationError: Invalid value 5 for wheels
```

```
>>> # we can call .dump() on car, and just get back a standard
>>> # python dict actually, it's an ordereddict to match attribute
>>> # declaration order
>>> type(car.dump())
<class '...OrderedDict'>
>>> car.dump()
OrderedDict([('weight', 4242.46), ('wheels', 4), ('color', 0)])
```

```
>>> # and json too (note the order!)
>>> car.json()
'{"weight": 4242.46, "wheels": 4, "color": 0}'
```

```
>>> # green cars aren't allowed
>>> car.color = "green"
Traceback (most recent call last):
ValidationError: 'green' is not a valid Color
```

```
>>> # but black cars are!
>>> car.color = "black"
>>> car.color
<Color.black: 1>
```

```
>>> # car.color really is an enum, promise
>>> type(car.color)
<enum 'Color'>
```

```
>>> # enum assignment can be with any of (and preferentially)
>>> # (1) an enum literal,
>>> # (2) a valid enum value, or
>>> # (3) a valid enum name
>>> car.color = Color.blue; car.color.value
0
>>> car.color = 1; car.color.name
'black'
```

```
>>> # actually, they're two different instances
>>> same_car is not car
True
```

>>> # this works too
>>> cloned_car = Car(**car.dump())
>>> cloned_car == car
True

```
>>> # while we're at it, these are all equivalent too
>>> car == Car.from_objects(car)
True
>>> car == Car.from_objects({"weight": 4242.46, "wheels": 4, "color": 1})
True
>>> car == Car.from_json('{"weight": 4242.46, "color": 1}')
True
```

```
>>> # .from_objects() even lets you stack and combine objects
>>> class DumbClass:
... color = 0
... wheels = 3
>>> Car.from_objects(DumbClass(), dict(weight=2222, color=1))
Car(weight=2222, wheels=3, color=0)
>>> # and also pass kwargs that override properties pulled
>>> # off any objects
>>> Car.from_objects(DumbClass(), {'weight': 2222, 'color': 1}, color=2, weight=33)
Car(weight=33, wheels=3, color=2)
```

Chapter 2: Entity and Field Composition

```
>>> # now let's get fancy
>>> # a ComposableField "nests" another valid Entity
>>> # a ListField's first argument is a "generic" type,
>>> # which can be a valid Entity, any python primitive
>>> # type, or a list of Entities/types
>>> class Fleet(Entity):
... boss_car = ComposableField(Car)
... cars = ListField(Car)
```

```
>>> # here's our fleet of company cars
>>> company_fleet = Fleet(boss_car=Car(color='red'), cars=[car, same_car, cloned_car])
>>> company_fleet.pretty_json()
{
    "boss_car": {
        "wheels": 4
        "color": 2,
    },
    "cars": [
        {
        "weight": 4242.46,
```

(continues on next page)
(continued from previous page)

```
"wheels": 4
    "color": 1,
},
{
    "weight": 4242.46,
    "wheels": 4
    "color": 1,
},
{
    "weight": 4242.46,
    "wheels": 4
    "color": 1,
}
]
```

```
>>> # the boss' car is red of course (and it's still an Enum)
>>> company_fleet.boss_car.color.name
'red'
```

```
>>> # and there are three cars left for the employees
>>> len(company_fleet.cars)
3
```

Chapter 3: Immutability

```
>>> class ImmutableCar(ImmutableEntity):
... wheels = IntField(default=4, validation=lambda x: 3 <= x <= 4)
... color = EnumField(Color)
>>> icar = ImmutableCar.from_objects({'wheels': 3, 'color': 'blue'})
>>> icar
ImmutableCar(wheels=3, color=0)
```

```
>>> icar.wheels = 4
Traceback (most recent call last):
AttributeError: Assignment not allowed. ImmutableCar is immutable.
```

```
>>> class FixedWheelCar(Entity):
... wheels = IntField(default=4, immutable=True)
... color = EnumField(Color)
>>> fwcar = FixedWheelCar.from_objects(icar)
>>> fwcar.json()
'{"wheels": 3, "color": 0}'
```

```
>>> # repainting the car is easy
>>> fwcar.color = Color.red
>>> fwcar.color.name
'red'
```

```
>>> # can't really change the number of wheels though
>>> fwcar.wheels = 18
Traceback (most recent call last):
AttributeError: The wheels field is immutable.
```

Chapter X: The del and null Weeds

```
>>> old_date = lambda: isoparse('1982-02-17')
>>> class CarBattery(Entity):
... # NOTE: default value can be a callable!
... first_charge = DateField(required=False) # default=None, nullable=False
... latest_charge = DateField(default=old_date, nullable=True) # required=True
... expiration = DateField(default=old_date, required=False, nullable=False)
```

```
>>> # starting point
>>> battery = CarBattery()
>>> battery
CarBattery()
>>> battery.json()
'{"latest_charge": "1982-02-17T00:00:00", "expiration": "1982-02-17T00:00:00"}'
```

```
>>> # first_charge is not assigned a default value. Once one is assigned, it can be_
__deleted,
>>> # but it can't be made null.
>>> battery.first_charge = isoparse('2016-03-23')
>>> battery
CarBattery(first_charge=datetime.datetime(2016, 3, 23, 0, 0))
>>> battery.first_charge = None
Traceback (most recent call last):
ValidationError: Value for first_charge not given or invalid.
>>> del battery.first_charge
>>> battery
CarBattery()
```

```
>>> # latest_charge can be null, but it can't be deleted. The default value is a callable.
>>> del battery.latest_charge
Traceback (most recent call last):
AttributeError: The latest_charge field is required and cannot be deleted.
>>> battery.latest_charge = None
>>> battery.json()
'{"latest_charge": null, "expiration": "1982-02-17T00:00:00"}'
```

```
>>> # expiration is assigned by default, can't be made null, but can be deleted.
>>> battery.expiration
datetime.datetime(1982, 2, 17, 0, 0)
>>> battery.expiration = None
Traceback (most recent call last):
ValidationError: Value for expiration not given or invalid.
>>> del battery.expiration
```

(continues on next page)

(continued from previous page)

>>>	batter	ry.json()	
'{"1	.atest_	_charge":	null}'

Classes

Field	Fields are doing something very similar to boxing and unboxing
BooleanField	Fields are doing something very similar to boxing and unboxing
IntegerField	Fields are doing something very similar to boxing and unboxing
NumberField	Fields are doing something very similar to boxing and unboxing
StringField	Fields are doing something very similar to boxing and unboxing
DateField	Fields are doing something very similar to boxing and unboxing
EnumField	Fields are doing something very similar to boxing and unboxing
ListField	Fields are doing something very similar to boxing and unboxing
MapField	Fields are doing something very similar to boxing and unboxing
ComposableField	Fields are doing something very similar to boxing and unboxing
Entity	
ImmutableEntity	

Attributes

BoolField		
IntField		

Fields are doing something very similar to boxing and unboxing of c#/java primitives. __set__ should take a "primitive" or "raw" value and create a "boxed" or "programmatically usable" value of it. While __get__ should return the boxed value, dump in turn should unbox the value into a primitive or raw value.

Parameters

- types (primitive literal or type or sequence of types)
- **default** (*any*, *callable*, *optional*) -- If default is callable, it's guaranteed to return a valid value at the time of Entity creation.

- **required** (boolean, optional)
- validation (callable, optional)
- dump (boolean, optional)

property name

property required

property type

property default

property in_dump

property default_in_dump

property nullable

property is_nullable

property immutable

_order_helper = 0

set_name(name)

__get__(instance, instance_type)

__set__(instance, val)

__delete__(instance)

box(*instance*, *instance_type*, *val*)

unbox(instance, instance_type, val)

dump(instance, instance_type, val)

validate(instance, val)

Returns if val is valid

Return type True

Raises

ValidationError ---

class BooleanField(*default=NULL*, *required=True*, *validation=None*, *in_dump=True*, *default_in_dump=True*, *nullable=False*, *immutable=False*, *aliases=()*)

Bases: Field

Fields are doing something very similar to boxing and unboxing of c#/java primitives. __set__ should take a "primitive" or "raw" value and create a "boxed" or "programmatically usable" value of it. While __get__ should return the boxed value, dump in turn should unbox the value into a primitive or raw value.

Parameters

• types (primitive literal or type or sequence of types)

- **default** (*any*, *callable*, *optional*) -- If default is callable, it's guaranteed to return a valid value at the time of Entity creation.
- required (boolean, optional)
- validation (callable, optional)
- dump (boolean, optional)

_type

box(*instance*, *instance_type*, *val*)

BoolField

class IntegerField(*default=NULL*, *required=True*, *validation=None*, *in_dump=True*, *default_in_dump=True*, *nullable=False*, *immutable=False*, *aliases=()*)

Bases: Field

Fields are doing something very similar to boxing and unboxing of c#/java primitives. __set__ should take a "primitive" or "raw" value and create a "boxed" or "programmatically usable" value of it. While __get__ should return the boxed value, dump in turn should unbox the value into a primitive or raw value.

Parameters

- types (primitive literal or type or sequence of types)
- **default** (*any*, *callable*, *optional*) -- If default is callable, it's guaranteed to return a valid value at the time of Entity creation.
- required (boolean, optional)
- validation (callable, optional)
- dump (boolean, optional)

_type

IntField

class NumberField(*default=NULL*, *required=True*, *validation=None*, *in_dump=True*, *default_in_dump=True*, *nullable=False*, *immutable=False*, *aliases=()*)

Bases: Field

Fields are doing something very similar to boxing and unboxing of c#/java primitives. __set__ should take a "primitive" or "raw" value and create a "boxed" or "programmatically usable" value of it. While __get__ should return the boxed value, dump in turn should unbox the value into a primitive or raw value.

Parameters

- types (primitive literal or type or sequence of types)
- **default** (*any*, *callable*, *optional*) -- If default is callable, it's guaranteed to return a valid value at the time of Entity creation.
- required (boolean, optional)
- validation (callable, optional)
- dump (boolean, optional)

_type = ()

class StringField(*default=NULL*, *required=True*, *validation=None*, *in_dump=True*, *default_in_dump=True*, *nullable=False*, *immutable=False*, *aliases=()*)

Bases: Field

Fields are doing something very similar to boxing and unboxing of c#/java primitives. __set__ should take a "primitive" or "raw" value and create a "boxed" or "programmatically usable" value of it. While __get__ should return the boxed value, dump in turn should unbox the value into a primitive or raw value.

Parameters

- types (primitive literal or type or sequence of types)
- **default** (*any*, *callable*, *optional*) -- If default is callable, it's guaranteed to return a valid value at the time of Entity creation.
- required (boolean, optional)
- validation (callable, optional)
- dump (boolean, optional)

_type

box(instance, instance_type, val)

class DateField(*default=NULL*, *required=True*, *validation=None*, *in_dump=True*, *default_in_dump=True*, *nullable=False*, *immutable=False*, *aliases=()*)

Bases: Field

Fields are doing something very similar to boxing and unboxing of c#/java primitives. __set__ should take a "primitive" or "raw" value and create a "boxed" or "programmatically usable" value of it. While __get__ should return the boxed value, dump in turn should unbox the value into a primitive or raw value.

Parameters

- types (primitive literal or type or sequence of types)
- **default** (*any*, *callable*, *optional*) -- If default is callable, it's guaranteed to return a valid value at the time of Entity creation.
- required (boolean, optional)
- validation (callable, optional)
- dump (boolean, optional)

_type

box(instance, instance_type, val)

dump(instance, instance_type, val)

class EnumField(*enum_class*, *default=NULL*, *required=True*, *validation=None*, *in_dump=True*, *default_in_dump=True*, *nullable=False*, *immutable=False*, *aliases=()*)

Bases: Field

Fields are doing something very similar to boxing and unboxing of c#/java primitives. __set__ should take a "primitive" or "raw" value and create a "boxed" or "programmatically usable" value of it. While __get__ should return the boxed value, dump in turn should unbox the value into a primitive or raw value.

Parameters

• types (primitive literal or type or sequence of types)

- **default** (*any*, *callable*, *optional*) -- If default is callable, it's guaranteed to return a valid value at the time of Entity creation.
- required (boolean, optional)
- validation (callable, optional)
- dump (boolean, optional)

box(instance, instance_type, val)

dump(instance, instance_type, val)

class ListField(*element_type*, *default=NULL*, *required=True*, *validation=None*, *in_dump=True*, *default_in_dump=True*, *nullable=False*, *immutable=False*, *aliases=()*)

Bases: Field

Fields are doing something very similar to boxing and unboxing of c#/java primitives. __set__ should take a "primitive" or "raw" value and create a "boxed" or "programmatically usable" value of it. While __get__ should return the boxed value, dump in turn should unbox the value into a primitive or raw value.

Parameters

- types (primitive literal or type or sequence of types)
- **default** (*any*, *callable*, *optional*) -- If default is callable, it's guaranteed to return a valid value at the time of Entity creation.
- required (boolean, optional)
- validation (callable, optional)
- dump (boolean, optional)

_type

box(*instance*, *instance_type*, *val*)

unbox(instance, instance_type, val)

dump(instance, instance_type, val)

validate(instance, val)

Returns

if val is valid

Return type True

Raises

ValidationError ---

Bases: Field

Fields are doing something very similar to boxing and unboxing of c#/java primitives. __set__ should take a "primitive" or "raw" value and create a "boxed" or "programmatically usable" value of it. While __get__ should return the boxed value, dump in turn should unbox the value into a primitive or raw value.

Parameters

• types (primitive literal or type or sequence of types)

- **default** (*any*, *callable*, *optional*) -- If default is callable, it's guaranteed to return a valid value at the time of Entity creation.
- required (boolean, optional)
- validation (callable, optional)
- dump (boolean, optional)

_type

box(*instance*, *instance_type*, *val*)

class ComposableField(*field_class*, *default=NULL*, *required=True*, *validation=None*, *in_dump=True*, *default_in_dump=True*, *nullable=False*, *immutable=False*, *aliases=()*)

Bases: Field

Fields are doing something very similar to boxing and unboxing of c#/java primitives. __set__ should take a "primitive" or "raw" value and create a "boxed" or "programmatically usable" value of it. While __get__ should return the boxed value, dump in turn should unbox the value into a primitive or raw value.

Parameters

- types (primitive literal or type or sequence of types)
- **default** (*any*, *callable*, *optional*) -- If default is callable, it's guaranteed to return a valid value at the time of Entity creation.
- required (boolean, optional)
- validation (callable, optional)
- dump (boolean, optional)

box(*instance*, *instance_type*, *val*)

dump(instance, instance_type, val)

class Entity(**kwargs)

property _initd

___fields___

_lazy_validate = False

classmethod from_objects(*objects, **override_fields)

classmethod from_json(json_str)

classmethod load(data_dict)

validate()

```
__repr__()
```

Return repr(self).

classmethod __register__()

json(indent=None, separators=None, **kwargs)

pretty_json(indent=2, separators=(',', ': '), **kwargs)

dump()

classmethod __dump_fields()

```
___eq__(other)
```

Return self==value.

__hash__()

Return hash(self).

class ImmutableEntity(**kwargs)

Bases: Entity

__setattr__(*attribute*, *value*) Implement setattr(self, name, value).

__delattr__(item)

Implement delattr(self, name).

exceptions

Classes

AuxlibError	Mixin to identify exceptions associated with the auxlib
	package.

Functions

Raise(exception)

Raise(exception)

class AuxlibError

Mixin to identify exceptions associated with the auxlib package.

exception AuthenticationError

Bases: AuxlibError, ValueError

Mixin to identify exceptions associated with the auxlib package.

exception NotFoundError

Bases: AuxlibError, KeyError

Mixin to identify exceptions associated with the auxlib package.

exception InitializationError

Bases: AuxlibError, OSError

Mixin to identify exceptions associated with the auxlib package.

exception SenderError

Bases: AuxlibError, OSError

Mixin to identify exceptions associated with the auxlib package.

exception AssignmentError

Bases: AuxlibError, AttributeError

Mixin to identify exceptions associated with the auxlib package.

exception ValidationError(key, value=None, valid_types=None, msg=None)

Bases: AuxlibError, TypeError

Mixin to identify exceptions associated with the auxlib package.

exception ThisShouldNeverHappenError

Bases: AuxlibError, AttributeError

Mixin to identify exceptions associated with the auxlib package.

ish

Functions

dals(string)			dedent and left-strip
_get_attr(obj, attr_nam	ne[, aliases])		
<pre>find_or_none(key, _map_index])</pre>	search_maps[,	aliases,	Return the value of the first key found in the list of search_maps,
<pre>find_or_raise(key, _map_index])</pre>	search_maps[,	aliases,	

dals(string)

dedent and left-strip

_get_attr(obj, attr_name, aliases=())

find_or_none(key, search_maps, aliases=(), _map_index=0)

Return the value of the first key found in the list of search_maps, otherwise return None.

Examples

```
>>> from .collection import AttrDict
>>> d1 = AttrDict({'a': 1, 'b': 2, 'c': 3, 'e': None})
>>> d2 = AttrDict({'b': 5, 'e': 6, 'f': 7})
>>> find_or_none('c', (d1, d2))
3
>>> find_or_none('f', (d1, d2))
7
>>> find_or_none('b', (d1, d2))
2
>>> print(find_or_none('g', (d1, d2)))
```

(continues on next page)

(continued from previous page)

```
None
>>> find_or_none('e', (d1, d2))
6
```

find_or_raise(key, search_maps, aliases=(), _map_index=0)

logz

Classes

DumpEncoder	Extensible JSON <https: json.org=""> encoder for Python</https:>
	data structures.

Functions

<pre>set_root_level([level])</pre>
attach_stderr([level])
<pre>detach_stderr()</pre>
<pre>initialize_logging([level])</pre>
jsondumps(obj)
fullname(obj)
<pre>request_header_sort_key(item)</pre>
<pre>response_header_sort_key(item)</pre>
<pre>stringify(obj[, content_max_len])</pre>

Attributes

oot_log	
ullHandler	
EBUG_FORMATTER	
NFO_FORMATTER	
DUMPS	
equest_header_sort_dict	
esponse_header_sort_dict	

root_log

NullHandler

DEBUG_FORMATTER

INFO_FORMATTER

set_root_level(level=INFO)

attach_stderr(level=INFO)

detach_stderr()

initialize_logging(level=INFO)

class DumpEncoder(*, *skipkeys=False*, *ensure_ascii=True*, *check_circular=True*, *allow_nan=True*, *sort_keys=False*, *indent=None*, *separators=None*, *default=None*)

Bases: json.JSONEncoder

Extensible JSON <https://json.org> encoder for Python data structures.

Supports the following objects and types by default:

Python	JSON
dict	object
list, tuple	array
str	string
int, float	number
True	true
False	false
None	null

To extend this to recognize other objects, subclass and implement a .default() method with another method that returns a serializable object for o if possible, otherwise it should call the superclass implementation (to raise TypeError).

default(obj)

Implement this method in a subclass such that it returns a serializable object for o, or calls the base implementation (to raise a TypeError).

For example, to support arbitrary iterators, you could implement default like this:

```
def default(self, o):
    try:
        iterable = iter(o)
    except TypeError:
        pass
    else:
        return list(iterable)
    # Let the base class default method raise the TypeError
    return JSONEncoder.default(self, o)
```

_DUMPS

jsondumps(obj)

fullname(obj)

request_header_sort_dict

```
request_header_sort_key(item)
```

response_header_sort_dict

```
response_header_sort_key(item)
```

stringify(obj, content_max_len=0)

type_coercion

Collection of functions to coerce conversion of types with an intelligent guess.

Functions

<pre>numberify(value)</pre>	
	Examples
<pre>boolify(value[, nullable, return_string])</pre>	Convert a number, string, or sequence type into a pure boolean.
<pre>typify(value[, type_hint])</pre>	Take a primitive value, usually a string, and try to make a more relevant type out of it.
<pre>maybecall(value)</pre>	
<pre>listify(val[, return_type])</pre>	
	Examples

numberify(value)

Examples

```
>>> [numberify(x) for x in ('1234', 1234, '0755', 000755, False, 0, '0', True, 1, '1
→')]
[1234, 1234, 755, 493, 0, 0, 0, 1, 1, 1]
>>> [numberify(x) for x in ('12.34', 12.34, 1.2+3.5j, '1.2+3.5j')]
[12.34, 12.34, (1.2+3.5j), (1.2+3.5j)]
```

boolify(value, nullable=False, return_string=False)

Convert a number, string, or sequence type into a pure boolean.

```
Parameters
value (number, string, sequence) -- pretty much anything
Returns
```

boolean representation of the given value

Return type

bool

Examples

```
>>> [boolify(x) for x in ('yes', 'no')]
[True, False]
>>> [boolify(x) for x in (0.1, 0+0j, True, '0', '0.0', '0.1', '2')]
[True, False, True, False, False, True, True]
>>> [boolify(x) for x in ("true", "yes", "on", "y")]
[True, True, True, True]
>>> [boolify(x) for x in ("no", "non", "none", "off", "")]
[False, False, False, False, False]
>>> [boolify(x) for x in ([], set(), dict(), tuple())]
[False, False, False, False]
>>> [boolify(x) for x in ([1], set([False]), dict({'a': 1}), tuple([2]))]
[True, True, True, True]
```

typify(value, type_hint=None)

Take a primitive value, usually a string, and try to make a more relevant type out of it. An optional type_hint will try to coerce the value to that type.

Parameters

- **value** (*Any*) -- Usually a string, not a sequence
- type_hint (type or tuple[type])

Examples

```
>>> typify('32')
32
>>> typify('32', float)
32.0
>>> typify('32.0')
32.0
>>> typify('32.0.0')
'32.0.0'
>>> [typify(x) for x in ('true', 'yes', 'on')]
[True, True, True]
>>> [typify(x) for x in ('no', 'FALSe', 'off')]
[False, False, False]
>>> [typify(x) for x in ('none', 'None', None)]
[None, None, None]
```

maybecall(value)

listify(val, return_type=tuple)

Examples

```
>>> listify('abc', return_type=list)
['abc']
>>> listify(None)
()
>>> listify(False)
(False,)
>>> listify(('a', 'b', 'c'), return_type=list)
['a', 'b', 'c']
```

- __version__ = '0.0.43'
- __author__ = 'Kale Franz'
- __email__ = 'kale@franz.io'
- __url__ = 'https://github.com/kalefranz/auxlib'
- __license__ = 'ISC'
- __copyright__ = '(c) 2015 Kale Franz. All rights reserved.'
- __summary__ = 'auxiliary library to the python standard library'

base

Code in conda.base is the lowest level of the application stack. It is loaded and executed virtually every time the application is executed. Any code within, and any of its imports, must be highly performant.

Conda modules importable from conda.base are

- conda._vendor
- conda.base
- conda.common

Modules prohibited from importing conda.base are:

- conda._vendor
- conda.common

All other conda modules may import from conda.base.

constants

This file should hold most string literals and magic numbers used throughout the code base. The exception is if a literal is specifically meant to be private to and isolated within a module. Think of this as a "more static" source of configuration information.

Another important source of "static" configuration is conda/models/enums.py.

Classes

SafetyChecks	Generic enumeration.
PathConflict	Generic enumeration.
DepsModifier	Flags to enable alternate handling of dependencies.
UpdateModifier	Generic enumeration.
ChannelPriorityMeta	Metaclass for Enum
ValueEnum	Subclass of enum that returns the value of the enum as
	its str representation
ChannelPriority	
SatSolverChoice	Subclass of enum that returns the value of the enum as
	its str representation
NoticeLevel	Subclass of enum that returns the value of the enum as
	its str representation

Attributes

PREFIX_PLACEHOLDER
machine_bits
APP_NAME
SEARCH_PATH
DEFAULT_CHANNEL_ALIAS
CONDA_HOMEPAGE_URL
ERROR_UPLOAD_URL
DEFAULTS_CHANNEL_NAME
RECOGNIZED_URL_SCHEMES
DEFAULT_CHANNELS_UNIX
DEFAULT_CHANNELS_WIN
DEFAULT_CUSTOM_CHANNELS
DEFAULT_CHANNELS
ROOT_ENV_NAME
ROOT_NO_RM
DEFAULT_AGGRESSIVE_UPDATE_PACKAGES
COMPATIBLE_SHELLS
MAX_CHANNEL_PRIORITY
CONDA_PACKAGE_EXTENSION_V1
CONDA_PACKAGE_EXTENSION_V2
CONDA_PACKAGE_EXTENSIONS
CONDA_PACKAGE_PARTS
CONDA_TARBALL_EXTENSION
CONDA_TEMP_EXTENSION
CONDA_TEMP_EXTENSIONS

continues on next page

Table 3 – continued from previous page
CONDA_LOGS_DIR
UNKNOWN_CHANNEL
REPODATA_FN
NOTICES_FN
NOTICES_CACHE_FN
NOTICES_CACHE_SUBDIR
NOTICES_DECORATOR_DISPLAY_INTERVAL
DRY_RUN_PREFIX
PREFIX_NAME_DISALLOWED_CHARS
DEFAULT_SOLVER
CLASSIC_SOLVER
PACKAGE_CACHE_MAGIC_FILE
PREFIX_MAGIC_FILE
PREFIX_STATE_FILE
PACKAGE_ENV_VARS_DIR
CONDA_ENV_VARS_UNSET_VAR
NAMESPACES_MAP
NAMESPACE_PACKAGE_NAMES
NAMESPACES
NO_PLUGINS

-

PREFIX_PLACEHOLDER = '/opt/anaconda1anaconda2anaconda3'

machine_bits

APP_NAME = 'conda'

```
SEARCH_PATH = ('C:/ProgramData/conda/.condarc', 'C:/ProgramData/condarc',
'C:/ProgramData/conda/condarc.d')
```

DEFAULT_CHANNEL_ALIAS = 'https://conda.anaconda.org'

CONDA_HOMEPAGE_URL = 'https://conda.io'

```
ERROR_UPLOAD_URL = 'https://conda.io/conda-post/unexpected-error'
DEFAULTS_CHANNEL_NAME = 'defaults'
RECOGNIZED_URL_SCHEMES = ('http', 'https', 'ftp', 's3', 'file')
DEFAULT_CHANNELS_UNIX = ('https://repo.anaconda.com/pkgs/main',
'https://repo.anaconda.com/pkgs/r')
DEFAULT_CHANNELS_WIN = ('https://repo.anaconda.com/pkgs/main',
'https://repo.anaconda.com/pkgs/r',...
DEFAULT_CUSTOM_CHANNELS
DEFAULT_CHANNELS
ROOT_ENV_NAME = 'base'
ROOT_NO_RM = ('python', 'pycosat', 'ruamel.yaml', 'conda', 'openssl', 'requests')
DEFAULT_AGGRESSIVE_UPDATE_PACKAGES = ('ca-certificates', 'certifi', 'openssl')
COMPATIBLE_SHELLS = ('bash', 'cmd.exe', 'fish', 'tcsh', 'xonsh', 'zsh', 'powershell')
MAX_CHANNEL_PRIORITY = 10000
CONDA_PACKAGE_EXTENSION_V1 = '.tar.bz2'
CONDA_PACKAGE_EXTENSION_V2 = '.conda'
CONDA_PACKAGE_EXTENSIONS = ()
CONDA_PACKAGE_PARTS
CONDA_TARBALL_EXTENSION
CONDA\_TEMP\_EXTENSION = '.c~'
CONDA\_TEMP\_EXTENSIONS = ()
CONDA_LOGS_DIR = '.logs'
UNKNOWN_CHANNEL = '<unknown>'
REPODATA_FN = 'repodata.json'
NOTICES_FN = 'notices.json'
NOTICES_CACHE_FN = 'notices.cache'
NOTICES_CACHE_SUBDIR = 'notices'
NOTICES_DECORATOR_DISPLAY_INTERVAL = 86400
DRY_RUN_PREFIX = 'Dry run action:'
PREFIX_NAME_DISALLOWED_CHARS
```

class SafetyChecks

Bases: enum. Enum

Generic enumeration.

Derive from this class to define new enumerations.

disabled = 'disabled'

warn = 'warn'

enabled = 'enabled'

__str__()

Return str(self).

class PathConflict

Bases: enum. Enum

Generic enumeration.

Derive from this class to define new enumerations.

clobber = 'clobber'

warn = 'warn'

prevent = 'prevent'

__str__()

Return str(self).

class DepsModifier

Bases: enum. Enum

Flags to enable alternate handling of dependencies.

NOT_SET = 'not_set'

NO_DEPS = 'no_deps'

ONLY_DEPS = 'only_deps'

__str__()

Return str(self).

class UpdateModifier

Bases: enum.Enum

Generic enumeration.

Derive from this class to define new enumerations.

SPECS_SATISFIED_SKIP_SOLVE = 'specs_satisfied_skip_solve'

```
FREEZE_INSTALLED = 'freeze_installed'
```

UPDATE_DEPS = 'update_deps'

UPDATE_SPECS = 'update_specs'

UPDATE_ALL = 'update_all'

___str__()

Return str(self).

class ChannelPriorityMeta

Bases: enum.EnumMeta

Metaclass for Enum

__call__(value, *args, **kwargs)

Either returns an existing member, or creates a new enum class.

This method is used both when an enum class is given a value to match to an enumeration member (i.e. Color(3)) and for the functional API (i.e. Color = Enum('Color', names='RED GREEN BLUE')).

When used for the functional API:

value will be the name of the new class.

names should be either a string of white-space/comma delimited names (values will start at *start*), or an iterator/mapping of name, value pairs.

module should be set to the module this class is being created in; if it is not set, an attempt to find that module will be made, but if it fails the class will not be picklable.

qualname should be set to the actual location this class can be found at in its module; by default it is set to the global scope. If this is not correct, unpickling will fail in some circumstances.

type, if set, will be mixed in as the first base class.

class ValueEnum

Bases: enum. Enum

Subclass of enum that returns the value of the enum as its str representation

__str__()

Return str(self).

class ChannelPriority

Bases: six_with_metaclass(ChannelPriorityMeta, ValueEnum)

__name__ = 'ChannelPriority'

STRICT = 'strict'

FLEXIBLE = 'flexible'

DISABLED = 'disabled'

class SatSolverChoice

Bases: ValueEnum

Subclass of enum that returns the value of the enum as its str representation

PYCOSAT = 'pycosat'

```
PYCRYPTOSAT = 'pycryptosat'
```

PYSAT = 'pysat'

DEFAULT_SOLVER = 'libmamba'

```
CLASSIC_SOLVER = 'classic'
```

class NoticeLevel

Bases: ValueEnum

Subclass of enum that returns the value of the enum as its str representation

CRITICAL = 'critical'

WARNING = 'warning'

INFO = 'info'

PACKAGE_CACHE_MAGIC_FILE = 'urls.txt'

PREFIX_MAGIC_FILE

PREFIX_STATE_FILE

PACKAGE_ENV_VARS_DIR

CONDA_ENV_VARS_UNSET_VAR = '***unset***'

NAMESPACES_MAP

NAMESPACE_PACKAGE_NAMES

NAMESPACES

NO_PLUGINS = False

context

Conda's global configuration object.

The context aggregates all configuration files, environment variables, and command line arguments into one global stateful object to be used across all of conda.

Classes

Context	
ContextStackObject	
ContextStack	
PluginConfig	Class used to hold settings for conda plugins.

Functions

```
user_data_dir([appname, appauthor, version, roam-
ing])
mockable_context_envs_dirs(root_writable,
root_prefix, ...)
channel_alias_validation(value)
default_python_default()
default_python_validation(value)
ssl_verify_validation(value)
reset_context([search_path, argparse_args])
fresh_context([env, search_path, argparse_args])
stack_context(pushing[,
                              search_path,
                                               arg-
parse_args])
stack_context_default(pushing[, argparse_args])
replace_context([pushing,
                               search_path,
                                               arg-
parse args])
replace_context_default([pushing,
                                               arg-
parse_args])
_get_cpu_info()
env_name(prefix)
locate_prefix_by_name(name[, envs_dirs])
                                                      Find the location of a prefix given a conda env name. If
                                                      the location does not exist, an
validate_prefix_name(\rightarrow str)
                                                      Run various validations to make sure prefix_name is
                                                      valid
determine_target_prefix(ctx[, args])
                                                      Get the prefix to operate in. The prefix may not yet exist.
_first_writable_envs_dir()
                                                      This is used to move everything under the key "plugins"
get_plugin_config_data(→
                                   dict[pathlib.Path,
dict[str, ...)
                                                      from the provided dictionary
add_plugin_setting(name, parameter[, aliases])
                                                      Adds a setting to the PluginConfig class
remove_all_plugin_settings(→ None)
                                                      Removes all attached settings from the PluginConfig
                                                      class
```

Attributes

_platform_map
non_x86_machines
_arch_names
user_rc_path
sys_rc_path
context_stack
<pre>conda_tests_ctxt_mgmt_def_pol</pre>
context

_platform_map

non_x86_machines

_arch_names

user_rc_path

sys_rc_path

```
user_data_dir(appname: str | None = None, appauthor: str | None | Literal[False] = None, version: str | None =
None, roaming: bool = False)
```

mockable_context_envs_dirs(root_writable, root_prefix, _envs_dirs)

channel_alias_validation(value)

default_python_default()

```
default_python_validation(value)
```

```
ssl_verify_validation(value)
```

class Context(search_path=None, argparse_args=None, **kwargs)
Bases: conda.common.configuration.Configuration

property plugin_manager: conda.plugins.manager.CondaPluginManager

This is the preferred way of accessing the PluginManager object for this application and is located here to avoid problems with cyclical imports elsewhere in the code.

property conda_build_local_paths

property conda_build_local_urls

property croot

This is where source caches and work folders live

property local_build_root

property conda_build

property arch_name

property platform

property default_threads: int | None

property repodata_threads: int | None

property fetch_threads: int | None

If both are not overriden (0), return experimentally-determined value of 5

property verify_threads: int | None

property execute_threads

property subdir

property subdirs

property bits

property root_dir: os.PathLike

property root_writable

property envs_dirs

property pkgs_dirs

property default_prefix

property active_prefix

property shlvl

property aggressive_update_packages

property target_prefix

property conda_prefix

property conda_exe

property av_data_dir

Where critical artifact verification data (e.g., various public keys) can be found.

property signing_metadata_url_base

Base URL for artifact verification signing metadata (*.root.json, key_mgr.json).

property conda_exe_vars_dict

The vars can refer to each other if necessary since the dict is ordered. None means unset it.

property migrated_channel_aliases

property prefix_specified

property channels

property config_files

property use_only_tar_bz2

property binstar_upload

property trace: bool

Alias for context.verbosity >=4.

property debug: bool

Alias for context.verbosity >=3.

property info: bool

Alias for context.verbosity >=2.

property verbose: bool

Alias for context.verbosity >=1.

property verbosity: int

Verbosity level.

For cleaner and readable code it is preferable to use the following alias properties:

context.trace context.debug context.info context.verbose context.log_level

property log_level: int

Map context.verbosity to logging level.

property cpu_flags

property category_map

add_pip_as_python_dependency

allow_conda_downgrades

allow_cycles

allow_softlinks

auto_update_conda

auto_activate_base

auto_stack

notify_outdated_conda

clobber

changeps1

env_prompt

create_default_packages

register_envs

default_python

download_only

enable_private_envs

force_32bit

non_admin_enabled

pip_interop_enabled

_default_threads

_repodata_threads

_fetch_threads

_verify_threads

_execute_threads

_aggressive_update_packages

safety_checks

extra_safety_checks

_signing_metadata_url_base

path_conflict

pinned_packages

disallowed_packages

rollback_enabled

track_features

use_index_cache

separate_format_cache

_root_prefix

_envs_dirs

_pkgs_dirs

_subdir

_subdirs

local_repodata_ttl

ssl_verify

client_ssl_cert

client_ssl_cert_key

proxy_servers

remote_connect_timeout_secs remote_read_timeout_secs remote_max_retries remote_backoff_factor add_anaconda_token _reporters allow_non_channel_urls _channel_alias channel_priority _channels channel_settings _custom_channels _custom_multichannels _default_channels _migrated_channel_aliases migrated_custom_channels override_channels_enabled show_channel_urls use_local allowlist_channels restore_free_channel repodata_fns _use_only_tar_bz2 always_softlink always_copy always_yes _debug _trace dev dry_run error_upload_url

force

json

offline

quiet

ignore_pinned

report_errors

shortcuts

number_channel_notices

shortcuts

shortcuts_only

_verbosity

experimental

no_lock

repodata_use_zst

deps_modifier

update_modifier

sat_solver

solver_ignore_timestamps

solver

force_remove

force_reinstall

target_prefix_override

unsatisfiable_hints

unsatisfiable_hints_check_depth

bld_path

anaconda_upload

_croot

_conda_build

no_plugins

post_build_validation()

plugins() → *PluginConfig*

Preferred way of accessing settings introduced by the settings plugin hook

_native_subdir()

```
known_subdirs()
```

trash_dir()

root_prefix()

channel_alias()

```
default_channels()
```

custom_multichannels()

custom_channels()

solver_user_agent()

user_agent()

_override(key, value)

TODO: This might be broken in some ways. Unsure what happens if the *old* value is a property and gets set to a new value. Or if the new value overrides the validation logic on the underlying ParameterLoader instance.

Investigate and implement in a safer way.

```
requests_version()
```

```
python_implementation_name_version()
```

```
platform_system_release()
```

```
os_distribution_name_version()
```

```
libc_family_version()
```

```
reporters() \rightarrow tuple[Mapping[str, str]]
```

Determine the value of reporters based on other settings and the self._reporters value itself.

get_descriptions()

description_map()

reset_context(search_path=SEARCH_PATH, argparse_args=None)

fresh_context(env=None, search_path=SEARCH_PATH, argparse_args=None, **kwargs)

class ContextStackObject(search_path=SEARCH_PATH, argparse_args=None)

set_value(search_path=SEARCH_PATH, argparse_args=None)

apply()

class ContextStack

push(search_path, argparse_args)

apply()

pop()

replace(*search_path*, *argparse_args*)

context_stack

stack_context(pushing, search_path=SEARCH_PATH, argparse_args=None)

stack_context_default(pushing, argparse_args=None)

replace_context(*pushing=None*, *search_path=SEARCH_PATH*, *argparse_args=None*)

replace_context_default(pushing=None, argparse_args=None)

conda_tests_ctxt_mgmt_def_pol

_get_cpu_info()

env_name(prefix)

locate_prefix_by_name(name, envs_dirs=None)

Find the location of a prefix given a conda env name. If the location does not exist, an error is raised.

validate_prefix_name(prefix_name: str, ctx: Context, allow_base=True) → str

Run various validations to make sure prefix_name is valid

determine_target_prefix(ctx, args=None)

Get the prefix to operate in. The prefix may not yet exist.

Parameters

- **ctx** -- the context of conda
- args -- the argparse args from the command line

Returns: the prefix Raises: CondaEnvironmentNotFoundError if the prefix is invalid

_first_writable_envs_dir()

get_plugin_config_data(*data: dict[pathlib.Path, dict[str,* conda.common.configuration.RawParameter]]) \rightarrow dict[pathlib.Path, dict[str, *conda.common.configuration.RawParameter*]]

This is used to move everything under the key "plugins" from the provided dictionary to the top level of the returned dictionary. The returned dictionary is then passed to *PluginConfig*.

class PluginConfig(data)

Class used to hold settings for conda plugins.

The object created by this class should only be accessed via conda.base.context.Context.plugins.

When this class is updated via the *add_plugin_setting()* function it adds new setting properties which can be accessed later via the context object.

We currently call that function in *conda.plugins.manager.CondaPluginManager.load_settings()*. because CondaPluginManager has access to all registered plugin settings via the settings plugin hook.

add_plugin_setting(name: str, parameter: conda.common.configuration.Parameter, aliases: tuple[str, Ellipsis]

=())

Adds a setting to the *PluginConfig* class

$remove_all_plugin_settings() \rightarrow None$

Removes all attached settings from the *PluginConfig* class

context

exceptions

Base exceptions.

cli

actions

Collection of custom argparse actions.

Classes

NullCountAction	Information about how to convert command line strings to Python objects.
ExtendConstAction	A derivative of _AppendConstAction and Python 3.8's _ExtendAction

class NullCountAction(option_strings, dest, default=None, required=False, help=None)

Bases: argparse._CountAction

Information about how to convert command line strings to Python objects.

Action objects are used by an ArgumentParser to represent the information needed to parse a single argument from one or more strings from the command line. The keyword arguments to the Action constructor are also all attributes of Action instances.

Keyword Arguments

- which (- option_strings -- A list of command-line option strings) -- should be associated with this action.
- object (- dest -- The name of the attribute to hold the created)
- **be** (- nargs -- The number of command-line arguments that should) -- consumed. By default, one argument will be consumed and a single value will be produced. Other values include:
 - N (an integer) consumes N arguments (and produces a list)
 - '?' consumes zero or one arguments
 - '*' consumes zero or more arguments (and produces a list)
 - '+' consumes one or more arguments (and produces a list)

Note that the difference between the default and nargs=1 is that with the default, a single value will be produced, while with nargs=1, a list containing a single value will be produced.

• **the** (- metavar -- The name to be used for the option's argument with) -- option uses an action that takes no values.

- **specified.** (- default -- The value to be produced if the option is not)
- and (- type -- A callable that accepts a single string argument,) -- returns the converted value. The standard Python types str, int, float, and complex are useful examples of such callables. If None, str is used.
- None, (- choices -- A container of values that should be allowed. If not) -- after a command-line argument has been converted to the appropriate type, an exception will be raised if it is not a member of this collection.
- the -- command line. This is only meaningful for optional command-line arguments.
- argument. (- help -- The help string describing the)
- **the** -- help string. If None, the 'dest' value will be used as the name.

static _ensure_value(namespace, name, value)

___call__(*parser*, *namespace*, *values*, *option_string=None*)

class ExtendConstAction(*option_strings*, *dest*, *const*, *default=None*, *type=None*, *choices=None*, *required=False*, *help=None*, *metavar=None*)

Bases: argparse.Action

A derivative of _AppendConstAction and Python 3.8's _ExtendAction

__call__(parser, namespace, values, option_string=None)

common

Common utilities for conda command line tools.

Functions

<pre>confirm([message, choices, default, dry_run])</pre>	
<pre>confirm_yn([message, default, dry_run])</pre>	
$is_active_prefix(\rightarrow bool)$	Determines whether the args we pass in are pointing to the active prefix.
<pre>arg2spec(arg[, json, update])</pre>	
<pre>specs_from_args(args[, json])</pre>	
<pre>strip_comment(line)</pre>	
<pre>spec_from_line(line)</pre>	
<pre>specs_from_url(url[, json])</pre>	
<pre>names_in_specs(names, specs)</pre>	
disp_features(features)	
<pre>stdout_json(d)</pre>	
<pre>stdout_json_success([success])</pre>	
<pre>print_envs_list(known_conda_prefixes[, output])</pre>	
<pre>check_non_admin()</pre>	
<pre>validate_prefix(prefix)</pre>	Verifies the prefix is a valid conda environment.

Attributes

spec_pat

confirm(*message='Proceed'*, *choices=*('yes', 'no'), *default='yes'*, *dry_run=NULL*)

confirm_yn(message='Proceed', default='yes', dry_run=NULL)

```
is_active_prefix(prefix: str) → bool
```

Determines whether the args we pass in are pointing to the active prefix. Can be used a validation step to make sure operations are not being performed on the active prefix.

arg2spec(arg, json=False, update=False)

specs_from_args(args, json=False)

spec_pat

strip_comment(line)

spec_from_line(line)

specs_from_url(url, json=False)

names_in_specs(names, specs)

disp_features(features)

stdout_json(d)

stdout_json_success(success=True, **kwargs)

print_envs_list(known_conda_prefixes, output=True)

check_non_admin()

validate_prefix(prefix)

Verifies the prefix is a valid conda environment.

Raises

- EnvironmentLocationNotFound -- Non-existent path or not a directory.
- DirectoryNotACondaEnvironmentError -- Directory is not a conda environment.

Returns

Valid prefix.

Return type

str

conda_argparse

Conda command line interface parsers.

Classes

ArgumentParser	Object for parsing command line strings into Python objects.
_GreedySubParsersAction	A custom subparser action to conditionally act as a greedy consumer.

Functions

$generate_pre_parser(\rightarrow ArgumentParser)$	
$generate_parser(\rightarrow ArgumentParser)$	
do_call(args, parser)	Serves as the primary entry point for commands referred to in this file and for
<pre>find_builtin_commands(parser)</pre>	
_exec(executable_args, env_vars)	
_exec_win(executable_args, env_vars)	
_exec_unix(executable_args, env_vars)	
$configure_parser_plugins(\rightarrow None)$	For each of the provided plugin-based subcommands, we'll create

Attributes

escaped_user_rc_path

 $escaped_sys_rc_path$

BUILTIN_COMMANDS

escaped_user_rc_path

escaped_sys_rc_path

BUILTIN_COMMANDS

generate_pre_parser(**kwargs) \rightarrow ArgumentParser

generate_parser(**kwargs) \rightarrow ArgumentParser

do_call(args: argparse.Namespace, parser: ArgumentParser)

Serves as the primary entry point for commands referred to in this file and for all registered plugin subcommands.

find_builtin_commands(parser)

class ArgumentParser(*args, add_help=True, **kwargs)

Bases: argparse.ArgumentParser

Object for parsing command line strings into Python objects.

Keyword Arguments

- (default (- usage -- A usage message) -- os.path.basename(sys.argv[0]))
- (**default** -- auto-generated from arguments)
- **does** (- description -- A description of what the program)
- descriptions (- epilog -- Text following the argument)
- one (- parents -- Parsers whose arguments should be copied into this)
- messages (- formatter_class -- HelpFormatter class for printing help)
- arguments (- argument_default -- The default value for all)
- **containing** (- fromfile_prefix_chars -- Characters that prefix files) -- additional arguments
- arguments
- conflicts (- conflict_handler -- String indicating how to handle)
- option (- add_help -- Add a -h/-help)
- unambiguously (- allow_abbrev -- Allow long options to be abbreviated)
- with (- exit_on_error -- Determines whether or not ArgumentParser exits) -- error info when an error occurs

_check_value(action, value)

parse_args(*args, override_args=None, **kwargs)

class _**GreedySubParsersAction**(*option_strings*, *prog*, *parser_class*, *dest=SUPPRESS*, *required=False*, *help=None*, *metavar=None*)

Bases: argparse._SubParsersAction

A custom subparser action to conditionally act as a greedy consumer.

This is a workaround since argparse.REMAINDER does not work as expected, see https://github.com/python/ cpython/issues/61252.

___call__(parser, namespace, values, option_string=None)

_get_subactions()

Sort actions for subcommands to appear alphabetically in help blurb.

_exec(executable_args, env_vars)

_exec_win(executable_args, env_vars)

_exec_unix(executable_args, env_vars)

$configure_parser_plugins(sub_parsers) \rightarrow None$

For each of the provided plugin-based subcommands, we'll create a new subparser for an improved help printout and calling the *configure_parser()* with the newly created subcommand specific argument parser.

find_commands

Utilities for finding executables and conda-* commands.

find_executable(executable[, include_others])

find_commands([include_others])

find_executable(executable, include_others=True)

find_commands(include_others=True)

helpers

Collection of helper functions to standardize reused CLI arguments.

Classes

BooleanOptionalAction	Information about how to convert command line strings
	to Python objects.

<pre>add_parser_create_install_update(p[, fix_required])</pre>	pre-	
$add_parser_pscheck(\rightarrow None)$		
$add_parser_show_channel_urls(\rightarrow None)$		
$add_parser_help(\rightarrow None)$		So we can use consistent capitalization and periods in the help. You must
<i>add_parser_prefix</i> (→ parseMutuallyExclusiveGroup)	arg-	
$add_parser_json(\rightarrow argparseArgumentGroup)$))	
$add_output_and_prompt_options(\rightarrow parseArgumentGroup)$	arg-	
add_parser_channels(→ parseArgumentGroup)	arg-	
add_parser_solver_mode(→ parseArgumentGroup)	arg-	
<pre>add_parser_update_modifiers(solver_mode_</pre>	options	
$add_parser_prune(\rightarrow None)$		
$add_parser_solver(\rightarrow None)$		Add a command-line flag for alternative solver backends.
add_parser_networking(→ parseArgumentGroup)	arg-	
<pre>add_parser_package_install_options()</pre>		
$add_parser_known(\rightarrow None)$		
$add_parser_default_packages(\rightarrow None)$		
<pre>add_parser_platform(parser)</pre>		
$add_parser_verbose(\rightarrow None)$		

class BooleanOptionalAction(*option_strings*, *dest*, *default=None*, *type=None*, *choices=None*, *required=False*, *help=None*, *metavar=None*)

Bases: argparse.Action

Information about how to convert command line strings to Python objects.

Action objects are used by an ArgumentParser to represent the information needed to parse a single argument from one or more strings from the command line. The keyword arguments to the Action constructor are also all attributes of Action instances.

Keyword Arguments

- which (- option_strings -- A list of command-line option strings) -- should be associated with this action.
- object (- dest -- The name of the attribute to hold the created)

- **be** (- nargs -- The number of command-line arguments that should) -- consumed. By default, one argument will be consumed and a single value will be produced. Other values include:
 - N (an integer) consumes N arguments (and produces a list)
 - '?' consumes zero or one arguments
 - '*' consumes zero or more arguments (and produces a list)
 - '+' consumes one or more arguments (and produces a list)

Note that the difference between the default and nargs=1 is that with the default, a single value will be produced, while with nargs=1, a list containing a single value will be produced.

- the (- metavar -- The name to be used for the option's argument with) -- option uses an action that takes no values.
- **specified.** (- default -- The value to be produced if the option is not)
- and (- type -- A callable that accepts a single string argument,) -- returns the converted value. The standard Python types str, int, float, and complex are useful examples of such callables. If None, str is used.
- None, (- choices -- A container of values that should be allowed. If not) -- after a command-line argument has been converted to the appropriate type, an exception will be raised if it is not a member of this collection.
- the -- command line. This is only meaningful for optional command-line arguments.
- argument. (- help -- The help string describing the)
- **the** -- help string. If None, the 'dest' value will be used as the name.

__call__(parser, namespace, values, option_string=None)

```
format_usage()
```

add_parser_create_install_update(p, prefix_required=False)

add_parser_pscheck(p: argparse.ArgumentParser) \rightarrow None

add_parser_show_channel_urls($p: argparse.ArgumentParser | argparse.ArgumentGroup) \rightarrow None$

add_parser_help(p: argparse.ArgumentParser) \rightarrow None

So we can use consistent capitalization and periods in the help. You must use the add_help=False argument to ArgumentParser or add_parser to use this. Add this first to be consistent with the default argparse output.

add_parser_prefix(*p*: argparse.ArgumentParser, prefix_required: bool = False) → argparse._MutuallyExclusiveGroup

add_parser_json(*p: argparse.ArgumentParser*) → argparse._ArgumentGroup

add_parser_channels(p: argparse.ArgumentParser) \rightarrow argparse.ArgumentGroup

add_parser_solver_mode(p: argparse.ArgumentParser) \rightarrow argparse._ArgumentGroup

add_parser_update_modifiers(solver_mode_options: argparse.ArgumentParser)

add_parser_prune(p: argparse.ArgumentParser) \rightarrow None

add_parser_solver(p: argparse.ArgumentParser) \rightarrow None

Add a command-line flag for alternative solver backends.

See context.solver for more info.

add_parser_networking(p: argparse.ArgumentParser) \rightarrow argparse.ArgumentGroup

add_parser_package_install_options(p: argparse.ArgumentParser) \rightarrow argparse.ArgumentGroup

add_parser_known(p: argparse.ArgumentParser) \rightarrow None

add_parser_default_packages(p: argparse.ArgumentParser) \rightarrow None

add_parser_platform(parser)

add_parser_verbose(parser: argparse.ArgumentParser | argparse.ArgumentGroup) \rightarrow None

install

Conda package installation logic.

Core logic for conda [create|install|update|remove] commands.

See conda.cli.main_create, conda.cli.main_install, conda.cli.main_update, and conda.cli.main_remove for the entry points into this module.

Functions

 check_prefix(prefix[, json])

 clone(src_arg, dst_prefix[, json, quiet, index_args])

 print_activate(env_name_or_prefix)

 get_revision(arg[, json])

 install(args, parser[, command])

 handle_txn(unlink_link_transaction, prefix, args, newenv)

Attributes

stderrlog

stderrlog

check_prefix(prefix, json=False)

clone(src_arg, dst_prefix, json=False, quiet=False, index_args=None)

print_activate(env_name_or_prefix)

get_revision(arg, json=False)

install(args, parser, command='install')

Logic for conda install, conda update, and conda create.

handle_txn(unlink_link_transaction, prefix, args, newenv, remove_op=False)

main

Entry point for all conda subcommands.

Functions

<pre>init_loggers()</pre>	
generate_parser(*args, **kwargs)	Some code paths import this function directly from this module instead
<pre>main_subshell(*args[, post_parse_hook])</pre>	Entrypoint for the "subshell" invocation of CLI interface. E.g. <i>conda create</i> .
<pre>main_sourced(shell, *args, **kwargs)</pre>	Entrypoint for the "sourced" invocation of CLI interface. E.g. <i>conda activate</i> .
<pre>main(*args, **kwargs)</pre>	

init_loggers()

generate_parser(*args, **kwargs)

Some code paths import this function directly from this module instead of from conda_argparse. We add the forwarder for backwards compatibility.

main_subshell(*args, post_parse_hook=None, **kwargs)

Entrypoint for the "subshell" invocation of CLI interface. E.g. conda create.

main_sourced(shell, *args, **kwargs)

Entrypoint for the "sourced" invocation of CLI interface. E.g. conda activate.

```
main(*args, **kwargs)
```

main_clean

CLI implementation for conda clean.

Removes cached package tarballs, index files, package metadata, temporary files, and log files.

$configure_parser(\rightarrow argparse.ArgumentParser)$
$_get_size(\rightarrow int)$
$_get_pkgs_dirs(\rightarrow dict[str, tuple[str, Ellipsis]])$
$_get_total_size(\rightarrow int)$
$_rm_rf(\rightarrow None)$
$find_tarballs(\rightarrow dict[str, Any])$
$find_pkgs(\rightarrow dict[str, Any])$
$rm_pkgs(\rightarrow None)$
$find_index_cache(\rightarrow list[str])$
$find_pkgs_dirs(\rightarrow list[str])$
$find_tempfiles(\rightarrow list[str])$
$find_logfiles(\rightarrow list[str])$
$rm_items(\rightarrow None)$
_execute(args, parser)
$execute(\rightarrow int)$

 $configure_parser(sub_parsers: argparse._SubParsersAction, **kwargs) \rightarrow argparse.ArgumentParser$

```
_get_size(*parts: str, warnings: list[str] | None) \rightarrow int
```

```
_get_pkgs_dirs(pkg_sizes: dict[str, dict[str, int]]) → dict[str, tuple[str, Ellipsis]]
```

```
_get_total_size(pkg\_sizes: dict[str, dict[str, int]]) \rightarrow int
```

```
_rm_rf(*parts: str, quiet: bool, verbose: bool) \rightarrow None
```

 $\texttt{find_tarballs()} \rightarrow \texttt{dict[str, Any]}$

 $\texttt{find_pkgs()} \rightarrow dict[str, Any]$

rm_pkgs(*pkgs_dirs: dict[str, tuple[str]], warnings: list[str], total_size: int, pkg_sizes: dict[str, dict[str, int]],* *, *quiet: bool, verbose: bool, dry_run: bool, name: str*) \rightarrow None

 $\texttt{find_index_cache()} \rightarrow list[str]$

 $\texttt{find_pkgs_dirs()} \rightarrow \textit{list[str]}$

find_tempfiles(paths: Iterable[str]) \rightarrow list[str] find_logfiles() \rightarrow list[str]

rm_items(*items: list*[*str*], *, *quiet: bool, verbose: bool, dry_run: bool, name: str*) \rightarrow None

_execute(args, parser)

execute(args: argparse.Namespace, parser: argparse.ArgumentParser) \rightarrow int

main_compare

CLI implementation for conda compare.

Compare the packages in an environment with the packages listed in an environment file.

Functions

```
configure_parser(→ argparse.ArgumentParser)
```

get_packages(prefix)

 $execute(\rightarrow int)$

 $configure_parser(sub_parsers: argparse._SubParsersAction, **kwargs) \rightarrow argparse.ArgumentParser$

get_packages(prefix)

 $compare_packages(active_pkgs, specification_pkgs) \rightarrow tuple[int, list[str]]$

execute(*args: argparse.Namespace, parser: argparse.ArgumentParser*) \rightarrow int

main_config

CLI implementation for conda config.

Allows for programmatically interacting with conda's configuration files (e.g., ~/.condarc).

configure_parser(→ argparse.ArgumentParser)

 $execute(\rightarrow int)$

format_dict(d)

parameter_description_builder(name)

describe_all_parameters()

print_config_item(key, value)

execute_config(args, parser)

configure_parser(*sub_parsers: argparse._SubParsersAction*, ***kwargs*) \rightarrow argparse.ArgumentParser

execute(*args: argparse.Namespace, parser: argparse.ArgumentParser*) \rightarrow int

format_dict(d)

```
parameter_description_builder(name)
```

describe_all_parameters()

print_config_item(key, value)

execute_config(args, parser)

main_create

CLI implementation for *conda create*.

Creates new conda environments with the specified packages.

Functions

configure_parser(→ argparse.ArgumentParser)

 $execute(\rightarrow int)$

 $\label{eq:configure_parser} configure_parser(sub_parsers: argparse._SubParsersAction, **kwargs) \rightarrow argparse.ArgumentParser$

main_env

Entry point for all conda-env subcommands.

Functions

configure_parser(→ argparse.ArgumentParser)

 $execute(\rightarrow int)$

configure_parser(*sub_parsers: argparse._SubParsersAction* | *None*, ***kwargs*) \rightarrow argparse.ArgumentParser **execute**(*args: argparse.Namespace, parser: argparse.ArgumentParser*) \rightarrow int

main_env_config

CLI implementation for conda-env config.

Allows for programmatically interacting with conda-env's configuration files (e.g., ~/.condarc).

Functions

configure_parser(→ argparse.ArgumentParser)

 $execute(\rightarrow int)$

configure_parser(*sub_parsers: argparse._SubParsersAction*, ***kwargs*) \rightarrow argparse.ArgumentParser

execute(args: argparse.Namespace, parser: argparse.ArgumentParser) \rightarrow int

main_env_create

CLI implementation for conda-env create.

Creates new conda environments with the specified packages.

configure_parser(→ argparse.ArgumentParser)

 $\textit{execute}(\rightarrow \textit{int})$

 $configure_parser(sub_parsers: argparse._SubParsersAction, **kwargs) \rightarrow argparse.ArgumentParser$

execute(*args: argparse.Namespace*, *parser: argparse.ArgumentParser*) \rightarrow int

main_env_export

DEPRECATED: Use *conda.cli.main_export* instead. CLI implementation for *conda-env export*. Dumps specified environment package specifications to the screen.

main_env_list

CLI implementation for *conda-env list*. Lists available conda environments.

Functions

configure_parser(→ argparse.ArgumentParser)

execute(args, parser)

configure_parser(*sub_parsers: argparse._SubParsersAction*, ***kwargs*) \rightarrow argparse.ArgumentParser

execute(args: argparse.Namespace, parser: argparse.ArgumentParser)

main_env_remove

CLI implementation for *conda-env remove*. Removes the specified conda environment.

configure_parser(→ argparse.ArgumentParser)

 $\textit{execute}(\rightarrow \textit{int})$

configure_parser(*sub_parsers: argparse._SubParsersAction*, ***kwargs*) \rightarrow argparse.ArgumentParser

execute(*args: argparse.Namespace*, *parser: argparse.ArgumentParser*) \rightarrow int

main_env_update

CLI implementation for conda-env update.

Updates the conda environments with the specified packages.

Functions

configure_parser(→ argparse.ArgumentParser)

 $execute(\rightarrow int)$

```
configure_parser(sub_parsers: argparse._SubParsersAction, **kwargs) \rightarrow argparse.ArgumentParser
execute(args: argparse.Namespace, parser: argparse.ArgumentParser) \rightarrow int
```

main_env_vars

CLI implementation for *conda-env config vars*. Allows for configuring conda-env's vars.

Functions

configure_parser(→ argparse.ArgumentParser)

 $execute_list(\rightarrow int)$

 $execute_set(\rightarrow int)$

 $execute_unset(\rightarrow int)$

configure_parser(*sub_parsers: argparse._SubParsersAction*, ***kwargs*) \rightarrow argparse.ArgumentParser **execute_list**(*args: argparse.Namespace, parser: argparse.ArgumentParser*) \rightarrow int **execute_set**(*args: argparse.Namespace, parser: argparse.ArgumentParser*) \rightarrow int **execute_unset**(*args: argparse.Namespace, parser: argparse.ArgumentParser*) \rightarrow int

main_export

CLI implementation for *conda export*. Dumps specified environment package specifications to the screen.

Functions

configure_parser(→ argparse.ArgumentParser)

 $execute(\rightarrow int)$

configure_parser(*sub_parsers: argparse._SubParsersAction*, ***kwargs*) \rightarrow argparse.ArgumentParser

execute(args: argparse.Namespace, parser: argparse.ArgumentParser) \rightarrow int

main_info

CLI implementation for conda info.

Display information about current conda installation.

Functions

$configure_parser(\rightarrow argparse.ArgumentParser)$	
$get_user_site(\rightarrow list[str])$	Method used to populate site_dirs in conda info.
$dump_record(\rightarrow dict[str, Any])$	Returns a dictionary of key/value pairs from prec. Keys included in IGNORE_FIELDS are not returned.
$pretty_package(\rightarrow None)$	Pretty prints contents of a PackageRecord
$get_info_dict(\rightarrow dict[str, Any])$	Returns a dictionary of contextual information.
$get_env_vars_str(\rightarrow str)$	Returns a printable string representing environment vari- ables from the dictionary returned by get_info_dict.
$get_main_info_str(\rightarrow str)$	Returns a printable string of the contents of info_dict.
$execute(\rightarrow int)$	Implements conda info commands.

Attributes

IGNORE_FIELDS

SKIP_FIELDS

```
configure_parser(sub_parsers: argparse._SubParsersAction, **kwargs) \rightarrow argparse.ArgumentParser
```

get_user_site() \rightarrow list[str]

Method used to populate site_dirs in conda info.

Returns

List of directories.

IGNORE_FIELDS: set[str]

SKIP_FIELDS: set[str]

dump_record(*prec:* conda.models.records.PackageRecord) \rightarrow dict[str, Any]

Returns a dictionary of key/value pairs from prec. Keys included in IGNORE_FIELDS are not returned.

Parameters

prec -- A PackageRecord object.

Returns

A dictionary of elements dumped from prec

pretty_package(*prec:* conda.models.records.PackageRecord) → None

Pretty prints contents of a PackageRecord

Parameters prec -- A PackageRecord

$\texttt{get_info_dict()} \rightarrow \texttt{dict[str, Any]}$

Returns a dictionary of contextual information.

Returns

Dictionary of conda information to be sent to stdout.

get_env_vars_str(*info_dict: dict[str, Any]*) \rightarrow str

Returns a printable string representing environment variables from the dictionary returned by get_info_dict.

Parameters

info_dict -- The returned dictionary from get_info_dict().

Returns

String to print.

get_main_info_str(info_dict: dict[str, Any]) → str

Returns a printable string of the contents of info_dict.

Parameters

info_dict -- The output of get_info_dict().

Returns

String to print.

 $execute(\textit{args: argparse.Namespace, parser: argparse.ArgumentParser}) \rightarrow int$

Implements conda info commands.

- conda info
- conda info --base
- conda info <package_spec> ... (deprecated) (no -- json)
- conda info --unsafe-channels
- conda info --envs (deprecated) (no --json)
- conda info --system (deprecated) (no --json)

main_init

CLI implementation for *conda init*.

Prepares the user's profile for running conda, and sets up the conda shell interface.

Functions

configure_parser(→ argparse.ArgumentParser)

 $execute(\rightarrow int)$

```
\label{eq:configure_parser(sub_parsers: argparse._SubParsersAction, **kwargs) \rightarrow argparse.ArgumentParser
```

execute(args: argparse.Namespace, parser: argparse.ArgumentParser) \rightarrow int

main_install

CLI implementation for conda install.

Installs the specified packages into an existing environment.

Functions

configure_parser(→ argparse.ArgumentParser)

 $execute(\rightarrow int)$

configure_parser(*sub_parsers: argparse._SubParsersAction*, ***kwargs*) \rightarrow argparse.ArgumentParser

main_list

CLI implementation for *conda list*. Lists all packages installed into an environment.

Functions

 $configure_parser(\rightarrow argparse.ArgumentParser)$

print_export_header(subdir)

get_packages(installed, regex)

list_packages(prefix[, regex, format, reverse, ...])

print_packages(prefix[, regex, format, reverse, ...])

print_explicit(prefix[, add_md5])

 $execute(\rightarrow int)$

configure_parser(*sub_parsers: argparse._SubParsersAction*, ***kwargs*) \rightarrow argparse.ArgumentParser

print_export_header(subdir)

get_packages(installed, regex)

list_packages(*prefix*, *regex=None*, *format='human'*, *reverse=False*, *show_channel_urls=None*)

print_explicit(prefix, add_md5=False)

execute(args: argparse.Namespace, parser: argparse.ArgumentParser) \rightarrow int

main_mock_activate

Mock CLI implementation for conda activate.

A mock implementation of the activate shell command for better UX.

configure_parser(sub_parsers)

execute(args, parser)

configure_parser(sub_parsers)

execute(args, parser)

main_mock_deactivate

Mock CLI implementation for *conda deactivate*. A mock implementation of the deactivate shell command for better UX.

Functions

configure_parser(sub_parsers)

execute(args, parser)

configure_parser(sub_parsers)

execute(args, parser)

main_notices

CLI implementation for conda notices.

Manually retrieves channel notifications, caches them and displays them.

Functions

$configure_parser(\rightarrow argparse.ArgumentParser)$	
$execute(\rightarrow int)$	Command that retrieves channel notifications, caches them and displays them.

configure_parser(*sub_parsers: argparse._SubParsersAction*, ***kwargs*) \rightarrow argparse.ArgumentParser

execute(*args: argparse.Namespace, parser: argparse.ArgumentParser*) \rightarrow int

Command that retrieves channel notifications, caches them and displays them.

main_package

CLI implementation for conda package.

Provides some low-level tools for creating conda packages.

Functions

```
configure_parser(→ argparse.ArgumentParser)
remove(prefix, files)
                                                        Remove files for a given prefix.
execute(\rightarrow int)
get_installed_version(prefix, name)
create_info(name, version, build_number,
                                                  re-
quires_py)
fix_shebang(tmp_dir, path)
_add_info_dir(t, tmp_dir, files, has_prefix, info)
create_conda_pkg(prefix, files, info, tar_path[, ...])
                                                       Create a conda package and return a list of warnings.
make_tarbz2(prefix[, name, version, build_number,
files])
which_package(path)
                                                        Return the package containing the path.
which_prefix(path)
                                                        Return the prefix for the provided path.
```

Attributes

shebang_pat

configure_parser (<i>sub_parsers: argparseSubParsersAction</i> , ** <i>kwargs</i>) \rightarrow argparse.ArgumentParser
remove (<i>prefix</i> , <i>files</i>) Remove files for a given prefix.
execute (<i>args: argparse.Namespace, parser: argparse.ArgumentParser</i>) \rightarrow int
<pre>get_installed_version(prefix, name)</pre>
<pre>create_info(name, version, build_number, requires_py)</pre>
shebang_pat
<pre>fix_shebang(tmp_dir, path)</pre>
_add_info_dir(t, tmp_dir, files, has_prefix, info)
create_conda_pkg (<i>prefix</i> , <i>files</i> , <i>info</i> , <i>tar_path</i> , <i>update_info=None</i>) Create a conda package and return a list of warnings.

make_tarbz2(prefix, name='unknown', version='0.0', build_number=0, files=None)

which_package(path)

Return the package containing the path.

Provided the path of a (presumably) conda installed file, iterate over the conda packages the file came from. Usually the iteration yields only one package.

which_prefix(path)

Return the prefix for the provided path.

Provided the path of a (presumably) conda installed file, return the environment prefix in which the file in located.

main_pip

PEP 621 compatible entry point used when *conda init* has not updated the user shell profile.

Functions

pip_installed_post_parse_hook(args, p)

main(*args, **kwargs)

pip_installed_post_parse_hook(args, p)

main(*args, **kwargs)

main_remove

CLI implementation for conda remove.

Removes the specified packages from an existing environment.

Functions

 $configure_parser(\rightarrow argparse.ArgumentParser)$

```
execute(\rightarrow int)
```

configure_parser(*sub_parsers: argparse._SubParsersAction*, ***kwargs*) \rightarrow argparse.ArgumentParser

main_rename

CLI implementation for conda rename.

Renames an existing environment by cloning it and then removing the original environment.

Functions

$configure_parser(\rightarrow argparse.ArgumentParser)$	
$validate_src(\rightarrow str)$	Validate that we are receiving at least one valid value for
	name or
$validate_destination(\rightarrow str)$	Ensure that our destination does not exist
$execute(\rightarrow int)$	Executes the command for renaming an existing environ-
	ment.

configure_parser(*sub_parsers: argparse._SubParsersAction*, ***kwargs*) \rightarrow argparse.ArgumentParser

$validate_src() \rightarrow str$

Validate that we are receiving at least one valid value for --name or --prefix and ensure that the "base" environment is not being renamed

validate_destination(*dest: str*, *force: bool* = *False*) \rightarrow str

Ensure that our destination does not exist

execute(*args: argparse.Namespace, parser: argparse.ArgumentParser*) \rightarrow int

Executes the command for renaming an existing environment.

main_run

CLI implementation for conda run.

Runs the provided command within the specified environment.

Functions

configure_parser(→ argparse.ArgumentParser)

 $\textit{execute}(\rightarrow \textit{int})$

configure_parser(*sub_parsers: argparse._SubParsersAction*, ***kwargs*) \rightarrow argparse.ArgumentParser

main_search

CLI implementation for conda search.

Query channels for packages matching the provided package spec.

Functions

<pre>configure_parser(-</pre>	argparse.ArgumentParser)
-------------------------------	--------------------------

$execute(\rightarrow int)$	Implements conda search commands.
$pretty_record(\rightarrow None)$	Pretty prints a PackageRecord.

configure_parser(*sub_parsers: argparse._SubParsersAction*, ***kwargs*) \rightarrow argparse.ArgumentParser

execute(*args: argparse.Namespace, parser: argparse.ArgumentParser*) \rightarrow int

Implements conda search commands.

conda search <spec> searches channels for packages. *conda search <spec> --envs* searches environments for packages.

pretty_record(*record*: conda.models.records.PackageRecord) \rightarrow None

Pretty prints a PackageRecord.

Parameters record -- The PackageRecord object to print.

main_update

CLI implementation for conda update.

Updates the specified packages in an existing environment.

Functions

configure_parser(→ argparse.ArgumentParser)

 $\textit{execute}(\rightarrow \textit{int})$

configure_parser(*sub_parsers: argparse._SubParsersAction*, ***kwargs*) \rightarrow argparse.ArgumentParser

python_api

Wrapper for running conda CLI commands as a Python API.

Classes

Commands

Functions

<i>run_command</i> (command, *arguments, **kwargs)	Runs a conda command in-process with a given set of
	command-line interface arguments.

Attributes

STRING			
STDOUT			

class Commands

```
CLEAN = 'clean'

CONFIG = 'config'

CREATE = 'create'

INFO = 'info'

INSTALL = 'install'

LIST = 'list'

REMOVE = 'remove'

SEARCH = 'search'

UPDATE = 'update'

RUN = 'run'

NOTICES = 'notices'

STRING

STDOUT
```

run_command(command, *arguments, **kwargs)

Runs a conda command in-process with a given set of command-line interface arguments.

Differences from the command-line interface:

Always uses --yes flag, thus does not ask for confirmation.

Parameters

- command -- one of the Commands.
- ***arguments** -- instructions you would normally pass to the conda command on the command line see below for examples. Be very careful to delimit arguments exactly as you want them to be delivered. No 'combine then split at spaces' or other information destroying processing gets performed on the arguments.
- **kwargs -- special instructions for programmatic overrides

Keyword Arguments

- **use_exception_handler** -- defaults to False. False will let the code calling *run_command* handle all exceptions. True won't raise when an exception has occurred, and instead give a non-zero return code
- **search_path** -- an optional non-standard search path for configuration information that overrides the default SEARCH_PATH
- **stdout** -- Define capture behavior for stream sys.stdout. Defaults to STRING. STRING captures as a string. None leaves stream untouched. Otherwise redirect to file-like object stdout.
- **stderr** -- Define capture behavior for stream sys.stderr. Defaults to STRING. STRING captures as a string. None leaves stream untouched. STDOUT redirects to stdout target and returns None as stderr value. Otherwise redirect to file-like object stderr.

Returns

a tuple of stdout, stderr, and return_code. stdout, stderr are either strings, None or the corresponding file-like function argument.

Examples

Functions

main(*args, **kwargs)

main(*args, **kwargs)

common

Code in conda.common is not conda-specific. Technically, it sits *aside* the application stack and not *within* the stack. It is able to stand independently on its own. The *only* allowed imports of conda code in conda.common modules are imports of other conda.common modules and imports from conda._vendor.

If objects are needed from other parts of conda, they should be passed directly as arguments to functions and methods.

_logic

Classes

_ClauseList	Storage for the CNF clauses, represented as a list of tuples of ints.
_ClauseArray	Storage for the CNF clauses, represented as a flat int array.
_SatSolver	Simple wrapper to call a SAT solver given a _ClauseList/_ClauseArray instance.
_PycoSatSolver	Simple wrapper to call a SAT solver given a _ClauseList/_ClauseArray instance.
_PyCryptoSatSolver	Simple wrapper to call a SAT solver given a _ClauseList/_ClauseArray instance.
_PySatSolver	Simple wrapper to call a SAT solver given a _ClauseList/_ClauseArray instance.
Clauses	

Attributes

TRUE	
FALSE	
_sat_solver_str_to_cls	
_sat_solver_cls_to_str	

TRUE

FALSE

class _ClauseList

Storage for the CNF clauses, represented as a list of tuples of ints.

get_clause_count()

Return number of stored clauses.

save_state()

Get state information to be able to revert temporary additions of supplementary clauses. _ClauseList: state is simply the number of clauses.

restore_state(saved_state)

Restore state saved via *save_state*. Removes clauses that were added after the state has been saved.

as_list()

Return clauses as a list of tuples of ints.

as_array()

Return clauses as a flat int array, each clause being terminated by 0.

class _ClauseArray

Storage for the CNF clauses, represented as a flat int array. Each clause is terminated by int(0).

extend(clauses)

append(clause)

get_clause_count()

Return number of stored clauses. This is an O(n) operation since we don't store the number of clauses explicitly due to performance reasons (Python interpreter overhead in self.append).

save_state()

Get state information to be able to revert temporary additions of supplementary clauses. _ClauseArray: state is the length of the int array, NOT number of clauses.

restore_state(saved_state)

Restore state saved via *save_state*. Removes clauses that were added after the state has been saved.

as_list()

Return clauses as a list of tuples of ints.

as_array()

Return clauses as a flat int array, each clause being terminated by 0.

class _SatSolver(**run_kwargs)

Simple wrapper to call a SAT solver given a _ClauseList/_ClauseArray instance.

get_clause_count()

as_list()

save_state()

```
restore_state(saved_state)
```

run(m, **kwargs)

abstract setup(m, **kwargs)

Create a solver instance, add the clauses to it, and return it.

abstract invoke(solver)

Start the actual SAT solving and return the calculated solution.

abstract process_solution(sat_solution)

Process the solution returned by self.invoke. Returns a list of satisfied variables or None if no solution is found.

class _PycoSatSolver(**run_kwargs)

Bases: _SatSolver

Simple wrapper to call a SAT solver given a _ClauseList/_ClauseArray instance.

setup(m, limit=0, **kwargs)

Create a solver instance, add the clauses to it, and return it.

invoke(iter_sol)

Start the actual SAT solving and return the calculated solution.

process_solution(sat_solution)

Process the solution returned by self.invoke. Returns a list of satisfied variables or None if no solution is found.

class _PyCryptoSatSolver(**run_kwargs)

Bases: _SatSolver

Simple wrapper to call a SAT solver given a _ClauseList/_ClauseArray instance.

setup(m, threads=1, **kwargs)

Create a solver instance, add the clauses to it, and return it.

invoke(solver)

Start the actual SAT solving and return the calculated solution.

process_solution(solution)

Process the solution returned by self.invoke. Returns a list of satisfied variables or None if no solution is found.

class _PySatSolver(**run_kwargs)

Bases: _SatSolver

Simple wrapper to call a SAT solver given a _ClauseList/_ClauseArray instance.

setup(m, **kwargs)

Create a solver instance, add the clauses to it, and return it.

invoke(solver)

Start the actual SAT solving and return the calculated solution.

process_solution(sat_solution)

Process the solution returned by self.invoke. Returns a list of satisfied variables or None if no solution is found.

_sat_solver_str_to_cls

_sat_solver_cls_to_str

class Clauses(*m*=0, *sat_solver_str*=_*sat_solver_cls_to_str*[_*PycoSatSolver*])

```
get_clause_count()
```

as_list()

new_var()

assign(vals)

Combine(args, polarity)

Eval(func, args, polarity)

Prevent(func, *args)

Require(func, *args)

Not(*x*, *polarity=None*, *add_new_clauses=False*)

And(*f*, *g*, *polarity*, *add_new_clauses=False*)

Or(*f*, *g*, *polarity*, *add_new_clauses=False*)

Xor(f, g, polarity, add_new_clauses=False)

ITE(*c*, *t*, *f*, *polarity*, *add_new_clauses=False*)

All(*iter*, *polarity=None*)

Any(*iter*, *polarity*)

AtMostOne_NSQ(vals, polarity)

AtMostOne_BDD(vals, polarity=None)

ExactlyOne_NSQ(vals, polarity)

ExactlyOne_BDD(vals, polarity)

LB_Preprocess(lits, coeffs)

BDD(*lits*, *coeffs*, *nterms*, *lo*, *hi*, *polarity*)

LinearBound(*lits*, *coeffs*, *lo*, *hi*, *preprocess*, *polarity*)

_run_sat(m, limit=0)

sat(additional=None, includeIf=False, limit=0)

Calculate a SAT solution for the current clause set.

Returned is the list of those solutions. When the clauses are unsatisfiable, an empty list is returned.

minimize(lits, coeffs, bestsol=None, trymax=False)

Minimize the objective function given by (coeff, integer) pairs in zip(coeffs, lits). The actual minimization is multiobjective: first, we minimize the largest active coefficient value, then we minimize the sum.

_0S

linux

Functions

$linux_get_libc_version() \rightarrow tuple[str, str] | tuple[None, None]$

If on linux, returns (libc_family, version), otherwise (None, None).

unix

Functions

get_free_space_on_unix(dir_name)

is_admin_on_unix()

get_free_space_on_unix(dir_name)

is_admin_on_unix()

windows

Classes

SW	Enum where members are also (and must be) ints
ERROR	Enum where members are also (and must be) ints

Functions

<pre>get_free_space_on_windows(dir_name)</pre>	
is_admin_on_windows()	
_wait_and_close_handle(process_handle)	Waits until spawned process finishes and closes the han- dle for it.
<pre>run_as_admin(args[, wait])</pre>	Run command line argument list (<i>args</i>) with elevated privileges.

Attributes

PHANDLE

PHANDLE

class SW

Bases: enum.IntEnum

Enum where members are also (and must be) ints

HIDE = 0

MAXIMIZE = 3

MINIMIZE = 6

RESTORE = 9

SHOW = 5

SHOWDEFAULT = 10

SHOWMAXIMIZED = 3

SHOWMINIMIZED = 2

SHOWMINNOACTIVE = 7

SHOWNA = 8

SHOWNOACTIVATE = 4

SHOWNORMAL = 1

class ERROR

Bases: enum.IntEnum

Enum where members are also (and must be) ints

ZERO = 0

 $FILE_NOT_FOUND = 2$

 $PATH_NOT_FOUND = 3$

 $BAD_FORMAT = 11$

 $ACCESS_DENIED = 5$

```
ASSOC_INCOMPLETE = 27
```

```
DDE_BUSY = 30
```

 $DDE_FAIL = 29$

 $DDE_TIMEOUT = 28$

 $DLL_NOT_FOUND = 32$

```
NO_ASSOC = 31
```

OOM = 8

```
SHARE = 26
```

get_free_space_on_windows(dir_name)

```
is_admin_on_windows()
```

_wait_and_close_handle(process_handle)

Waits until spawned process finishes and closes the handle for it.

```
run_as_admin(args, wait=True)
```

Run command line argument list (args) with elevated privileges.

If wait is True, the process will block until completion.

Notes

- no stdin / stdout / stderr pipe support
- does not automatically quote arguments (i.e. for paths that may contain spaces)

See: - http://stackoverflow.com/a/19719292/1170370 on 20160407 MCS. - msdn.microsoft.com/enus/library/windows/desktop/bb762153(v=vs.85).aspx - https://github.com/ContinuumIO/menuinst/ blob/master/menuinst/windows/win_elevate.py - https://github.com/saltstack/salt-windows-install/ blob/master/deps/salt/python/App/Lib/site-packages/win32/Demos/pipes/runproc.py **# NOQA** - https: //github.com/twonds/twisted/blob/master/twisted/internet/_dumbwin32proc.py - https://stackoverflow.com/ a/19982092/2127762 - https://www.codeproject.com/Articles/19165/Vista-UAC-The-Definitive-Guide https://github.com/JustAMan/pyWinClobber/blob/master/win32elevate.py

on_win

compat

Common compatiblity code.

Functions

$encode_for_env_var(\rightarrow str)$	Environment names and values need to be string.
<pre>encode_environment(env)</pre>	
encode_arguments(arguments)	
isiterable(obj)	
<pre>open(file[, mode, buffering, encoding, errors,])</pre>	
<pre>six_with_metaclass(meta, *bases)</pre>	Create a base class with a metaclass.
ensure_binary(value)	
$ensure_text_type(\rightarrow str)$	
ensure_unicode(value)	
<pre>ensure_fs_path_encoding(value)</pre>	
<pre>ensure_utf8_encoding(value)</pre>	

Attributes

on_win
on_mac
on_linux
FILESYSTEM_ENCODING
ENCODE_ENVIRONMENT
NoneType
primitive_types
on_win
on_mac
on_linux
FILESYSTEM_ENCODING
ENCODE_ENVIRONMENT = True
$encode_for_env_var(value) \rightarrow str$
Environment names and values need to be string.
encode_environment(env)
encode_arguments(arguments)
<pre>isiterable(obj)</pre>
open (file, mode='r', buffering=-1, encoding=None, errors=None, newline=None, closefd=True)
six_with_metaclass(<i>meta</i> , *bases) Create a base class with a metaclass.
NoneType
primitive_types = ()
ensure_binary(value)
$ensure_text_type(value) \rightarrow str$
ensure_unicode(value)
<pre>ensure_fs_path_encoding(value)</pre>
ensure_utf8_encoding(value)

configuration

A generalized application configuration utility.

Features include:

- lazy eval
- merges configuration files
- parameter type validation, with custom validation
- parameter aliases

Easily extensible to other source formats, e.g. json and ini

Classes

ParameterFlag	Generic enumeration.
RawParameter	
EnvRawParameter	
ArgParseRawParameter	
YamlRawParameter	
DefaultValueRawParameter	Wraps a default value as a RawParameter, for usage in ParameterLoader.
LoadedParameter	
PrimitiveLoadedParameter	LoadedParameter type that holds a single python primi- tive value.
MapLoadedParameter	LoadedParameter type that holds a map (i.e. dict) of LoadedParameters.
SequenceLoadedParameter	LoadedParameter type that holds a sequence (i.e. list) of LoadedParameters.
ObjectLoadedParameter	LoadedParameter type that holds a mapping (i.e. object) of LoadedParameters.
ConfigurationObject	Dummy class to mark whether a Python object has con- fig parameters within.
Parameter	
PrimitiveParameter	Parameter type for a Configuration class that holds a sin- gle python primitive value.
MapParameter	Parameter type for a Configuration class that holds a map (i.e. dict) of Parameters.
SequenceParameter	Parameter type for a Configuration class that holds a se- quence (i.e. list) of Parameters.
ObjectParameter	Parameter type for a Configuration class that holds an object with Parameter fields.
ParameterLoader	ParameterLoader class contains the top level logic needed to load a parameter from start to
ConfigurationType	metaclass for Configuration
Configuration	

<pre>pretty_list(iterable[, padding])</pre>	
<pre>pretty_map(dictionary[, padding])</pre>	
<pre>expand_environment_variables(unexpanded)</pre>	
raise_errors(errors)	
$load_file_configs(\rightarrow dict[pathlib.Path, dict])$	
$custom_expandvars(\rightarrow str)$	Expand variables in a string.
<pre>unique_sequence_map(*, unique_key)</pre>	Used to validate properties on <i>Configuration</i> sub- classes defined as a

Attributes

EMPTY_MAP

CONDARC_FILENAMES

YAML_EXTENSIONS

_RE_CUSTOM_EXPANDVARS

EMPTY_MAP

pretty_list(iterable, padding=' ')

pretty_map(dictionary, padding=' ')

expand_environment_variables(unexpanded)

exception ConfigurationError(message, caused_by=None, **kwargs)

Bases: conda.CondaError

Common base class for all non-exit exceptions.

exception ConfigurationLoadError(path, message_addition=", **kwargs)

Bases: ConfigurationError

Common base class for all non-exit exceptions.

exception ValidationError(parameter_name, parameter_value, source, msg=None, **kwargs)
Bases: ConfigurationError

Common base class for all non-exit exceptions.

exception MultipleKeysError(source, keys, preferred_key)

Bases: ValidationError

Common base class for all non-exit exceptions.

exception InvalidTypeError(*parameter_name*, *parameter_value*, *source*, *wrong_type*, *valid_types*, *msg=None*) Bases: ValidationError

Common base class for all non-exit exceptions.

exception CustomValidationError(parameter_name, parameter_value, source, custom_message)

Bases: ValidationError

Common base class for all non-exit exceptions.

exception MultiValidationError(errors, *args, **kwargs)

Bases: conda.CondaMultiError, ConfigurationError

Common base class for all non-exit exceptions.

raise_errors(errors)

class ParameterFlag

Bases: enum. Enum

Generic enumeration.

Derive from this class to define new enumerations.

final = 'final'

top = 'top'

bottom = 'bottom'

__str__()

Return str(self).

classmethod from_name(name)

classmethod from_value(value)

classmethod from_string(string)

class RawParameter(source, key, raw_value)

```
__repr__()
```

Return repr(self).

abstract value(parameter_obj)

abstract keyflag()

abstract valueflags(parameter_obj)

classmethod make_raw_parameters(source, from_map)

class EnvRawParameter(source, key, raw_value)

Bases: RawParameter

property __important_split_value

source = 'envvars'

value(parameter_obj)

```
keyflag()
     valueflags(parameter_obj)
     classmethod make_raw_parameters(appname)
class ArgParseRawParameter(source, key, raw_value)
     Bases: RawParameter
     source = 'cmd_line'
     value(parameter_obj)
     keyflag()
     valueflags(parameter_obj)
     classmethod make_raw_parameters(args_from_argparse)
class YamlRawParameter(source, key, raw_value, key_comment)
     Bases: RawParameter
     value(parameter_obj)
     keyflag()
     valueflags(parameter obj)
     static _get_yaml_key_comment(commented_dict, key)
     classmethod _get_yaml_list_comments(value)
     static _get_yaml_list_comment_item(item)
     static _get_yaml_map_comments(value)
     classmethod make_raw_parameters(source, from_map)
     classmethod make_raw_parameters_from_file(filepath)
class DefaultValueRawParameter(source, key, raw_value)
     Bases: RawParameter
     Wraps a default value as a RawParameter, for usage in ParameterLoader.
     value(parameter_obj)
     keyflag()
     valueflags(parameter_obj)
load_file_configs(search_path: Iterable[pathlib.Path | str], **kwargs) \rightarrow dict[pathlib.Path, dict]
class LoadedParameter(name, value, key_flag, value_flags, validation=None)
     _type
     _element_type
```

___eq___(*other*)

Return self==value.
__hash__()

Return hash(self).

```
collect_errors(instance, typed_value, source='<<merged>>')
```

Validate a LoadedParameter typed value.

Parameters

- instance (Configuration) -- the instance object used to create the LoadedParameter.
- typed_value (Any) -- typed value to validate.
- **source** (*str*) -- string description for the source of the typed_value.

expand()

Recursively expands any environment values in the Loaded Parameter.

Returns: LoadedParameter

abstract merge(matches)

Recursively merges matches into one LoadedParameter.

Parameters

matches (List<LoadedParameter>) -- list of matches of this parameter.

Returns: LoadedParameter

typify(source)

Recursively types a LoadedParameter.

Parameters

source (*str*) -- string describing the source of the LoadedParameter.

Returns: a primitive, sequence, or map representing the typed value.

static _typify_data_structure(value, source, type_hint=None)

static _match_key_is_important(loaded_parameter)

```
static _first_important_matches(matches)
```

class PrimitiveLoadedParameter(*name*, *element_type*, *value*, *key_flag*, *value_flags*, *validation=None*)

Bases: LoadedParameter

LoadedParameter type that holds a single python primitive value.

The python primitive types are str, int, float, complex, bool, and NoneType. In addition, python 2 has long and unicode types.

___eq__(*other*)

Return self==value.

__hash__()

Return hash(self).

merge(matches)

Recursively merges matches into one LoadedParameter.

Parameters

matches (List<LoadedParameter>) -- list of matches of this parameter.

Returns: LoadedParameter

class MapLoadedParameter(name, value, element_type, key_flag, value_flags, validation=None) Bases: LoadedParameter

LoadedParameter type that holds a map (i.e. dict) of LoadedParameters.

_type

collect_errors(instance, typed_value, source='<<merged>>')

Validate a LoadedParameter typed value.

Parameters

- instance (Configuration) -- the instance object used to create the LoadedParameter.
- typed_value (Any) -- typed value to validate.
- **source** (*str*) -- string description for the source of the typed_value.

merge(*parameters: Sequence*[MapLoadedParameter]) \rightarrow *MapLoadedParameter*

Recursively merges matches into one LoadedParameter.

Parameters

matches (List<LoadedParameter>) -- list of matches of this parameter.

Returns: LoadedParameter

class SequenceLoadedParameter(name, value, element_type, key_flag, value_flags, validation=None)

Bases: LoadedParameter

LoadedParameter type that holds a sequence (i.e. list) of LoadedParameters.

_type

```
collect_errors(instance, typed_value, source='<<merged>>')
```

Validate a LoadedParameter typed value.

Parameters

- instance (Configuration) -- the instance object used to create the LoadedParameter.
- typed_value (Any) -- typed value to validate.
- **source** (*str*) -- string description for the source of the typed_value.

merge(matches)

Recursively merges matches into one LoadedParameter.

Parameters

matches (*List<LoadedParameter>*) -- list of matches of this parameter.

Returns: LoadedParameter

class ObjectLoadedParameter(name, value, element_type, key_flag, value_flags, validation=None)

Bases: LoadedParameter

LoadedParameter type that holds a mapping (i.e. object) of LoadedParameters.

_type

collect_errors(instance, typed_value, source='<<merged>>')

Validate a LoadedParameter typed value.

Parameters

• instance (Configuration) -- the instance object used to create the LoadedParameter.

- typed_value (Any) -- typed value to validate.
- **source** (*str*) -- string description for the source of the typed_value.

merge(*parameters: Sequence*[ObjectLoadedParameter]) \rightarrow ObjectLoadedParameter

Recursively merges matches into one LoadedParameter.

Parameters

matches (*List<LoadedParameter>*) -- list of matches of this parameter.

Returns: LoadedParameter

class ConfigurationObject

Dummy class to mark whether a Python object has config parameters within.

class Parameter(default, validation=None)

property default

Returns a DefaultValueRawParameter that wraps the actual default value.

_type

_element_type

get_all_matches(name, names, instance)

Finds all matches of a Parameter in a Configuration instance

Parameters

- name (str) -- canonical name of the parameter to search for
- **names** (tuple(str)) -- alternative aliases of the parameter
- instance (Configuration) -- instance of the configuration to search within

Returns (List(RawParameter)): matches of the parameter found in the configuration.

abstract load(name, match)

Loads a Parameter with the value in a RawParameter.

Parameters

- **name** (*str*) -- name of the parameter to pass through
- match (RawParameter) -- the value of the RawParameter match

Returns a LoadedParameter

typify(name, source, value)

class PrimitiveParameter(default, element_type=None, validation=None)

Bases: Parameter

Parameter type for a Configuration class that holds a single python primitive value.

The python primitive types are str, int, float, complex, bool, and NoneType. In addition, python 2 has long and unicode types.

load(name, match)

Loads a Parameter with the value in a RawParameter.

Parameters

• **name** (*str*) -- name of the parameter to pass through

• match (RawParameter) -- the value of the RawParameter match

Returns a LoadedParameter

class MapParameter(element_type, default=frozendict(), validation=None)

Bases: Parameter

Parameter type for a Configuration class that holds a map (i.e. dict) of Parameters.

_type

get_all_matches(name, names, instance)

Finds all matches of a Parameter in a Configuration instance

Parameters

- **name** (*str*) -- canonical name of the parameter to search for
- **names** (tuple(str)) -- alternative aliases of the parameter
- instance (Configuration) -- instance of the configuration to search within

Returns (List(RawParameter)): matches of the parameter found in the configuration.

load(name, match)

Loads a Parameter with the value in a RawParameter.

Parameters

- **name** (*str*) -- name of the parameter to pass through
- match (RawParameter) -- the value of the RawParameter match

Returns a LoadedParameter

class SequenceParameter(*element_type*, *default=(*), *validation=None*, *string_delimiter='*,')

Bases: Parameter

Parameter type for a Configuration class that holds a sequence (i.e. list) of Parameters.

_type

get_all_matches(name, names, instance)

Finds all matches of a Parameter in a Configuration instance

Parameters

- name (str) -- canonical name of the parameter to search for
- **names** (tuple(str)) -- alternative aliases of the parameter
- instance (Configuration) -- instance of the configuration to search within

Returns (List(RawParameter)): matches of the parameter found in the configuration.

load(name, match)

Loads a Parameter with the value in a RawParameter.

Parameters

- name (str) -- name of the parameter to pass through
- match (RawParameter) -- the value of the RawParameter match

Returns a LoadedParameter

class ObjectParameter(element_type, default=ConfigurationObject(), validation=None)
Bases: Parameter

Parameter type for a Configuration class that holds an object with Parameter fields.

_type

get_all_matches(name, names, instance)

Finds all matches of a Parameter in a Configuration instance

Parameters

- **name** (*str*) -- canonical name of the parameter to search for
- **names** (*tuple(str)*) -- alternative aliases of the parameter
- instance (Configuration) -- instance of the configuration to search within

Returns (List(RawParameter)): matches of the parameter found in the configuration.

load(name, match)

Loads a Parameter with the value in a RawParameter.

Parameters

- **name** (*str*) -- name of the parameter to pass through
- match (RawParameter) -- the value of the RawParameter match

Returns a LoadedParameter

class ParameterLoader(parameter_type, aliases=(), expandvars=False)

ParameterLoader class contains the top level logic needed to load a parameter from start to finish.

property name

property names

_set_name(name)

__get__(instance, instance_type)

_raw_parameters_from_single_source(raw_parameters)

static raw_parameters_from_single_source(name, names, raw_parameters)

class ConfigurationType(name, bases, attr)

Bases: type

metaclass for Configuration

CONDARC_FILENAMES = ('.condarc', 'condarc')

YAML_EXTENSIONS = ('.yml', '.yaml')

_RE_CUSTOM_EXPANDVARS

custom_expandvars(*template: str, mapping: collections.abc.Mapping*[*str, Any*] = {}, /, ***kwargs*) \rightarrow str Expand variables in a string.

Inspired by *string.Template* and modified to mirror *os.path.expandvars* functionality allowing custom variables without mutating *os.environ*.

Expands POSIX and Windows CMD environment variables as follows:

- $VARIABLE \rightarrow value of VARIABLE$
- ${VARIABLE} \rightarrow value of VARIABLE$
- %VARIABLE% \rightarrow value of VARIABLE

Invalid substitutions are left as-is:

- $MISSING \rightarrow MISSING$
- ${MISSING} \rightarrow {MISSING}$
- $\% MISSING\% \rightarrow \% MISSING\%$
- $\$\$ \rightarrow \$\$$
- $\bullet \ \% \% \to \% \%$
- $\$ \rightarrow \$$
- $\bullet \hspace{0.2cm} \% \to \%$

class Configuration(search_path=(), app_name=None, argparse_args=None, **kwargs)

static _expand_search_path(search_path: Iterable[pathlib.Path | str], **kwargs) \rightarrow Iterable[pathlib.Path]

classmethod _load_search_path(search_path: Iterable[pathlib.Path]) \rightarrow Iterable[tuple[pathlib.Path, dict]]

```
_set_search_path(search_path: Iterable[pathlib.Path | str], **kwargs)
```

_set_env_vars(app_name=None)

_set_argparse_args(argparse_args)

_set_raw_data(raw_data: collections.abc.Mapping[Hashable, dict])

_reset_cache()

register_reset_callaback(callback)

check_source(source)

validate_all()

static _collect_validation_error(func, *args, **kwargs)

validate_configuration()

post_build_validation()

collect_all()

describe_parameter(parameter_name)

list_parameters()

typify_parameter(parameter_name, value, source)

abstract get_descriptions()

unique_sequence_map(*, unique_key: str)

Used to validate properties on *Configuration* subclasses defined as a SequenceParameter(MapParameter()) where the map contains a single key that should be regarded as unique. This decorator will handle removing duplicates and merging to a single sequence.

constants

Common constants.

NULL

TRACE = 5

decorators

Common decorators.

Functions

env_override(envvar_name[,	con-	Override the return value of the decorated function with
vert_empty_to_none])		an environment variable.

env_override(envvar_name, convert_empty_to_none=False)

Override the return value of the decorated function with an environment variable.

If convert_empty_to_none is true, if the value of the environment variable is the empty string, a None value will be returned.

disk

Common disk utilities.

Functions

temporary_content_in_file(content[, suffix])

temporary_content_in_file(content, suffix=")

io

Common I/O utilities.

Classes

DeltaSecondsFormatter	Logging formatter with additional attributes for run time logging.
ContextDecorator	Base class for a context manager class (implementing() and()) that also
SwallowBrokenPipe	Base class for a context manager class (implementing() and()) that also
CaptureTarget	Constants used for contextmanager captured.
Spinner	
	param message
	A message to prefix the spinner with.
	The string ': ' is automatically ap-
	pended.
ProgressBar	
DummyExecutor	This is an abstract base class for concrete asynchronous
	executors.
ThreadLimitedThreadPoolExecutor	This is an abstract base class for concrete asynchronous
	executors.
time_recorder	Base class for a context manager class (implementing
	enter() andexit()) that also

Functions

<pre>dashlist(iterable[, indent])</pre>	
<pre>env_vars([var_map, callback, stack_callback])</pre>	
<pre>env_var(name, value[, callback, stack_callback])</pre>	
<pre>env_unmodified([callback])</pre>	
<i>captured</i> ([stdout, stderr])	Capture outputs of sys.stdout and sys.stderr.
argv(args_list)	
_logger_lock()	
disable_logger(logger_name)	
<pre>stderr_log_level(level[, logger_name])</pre>	
<pre>attach_stderr_handler([level, logger_name, prop- agate,])</pre>	
<pre>timeout(timeout_secs, func, *args[, default_return])</pre>	Enforce a maximum time for a callable to complete.
<pre>get_instrumentation_record_file()</pre>	
<pre>print_instrumentation_data()</pre>	

Attributes

IS_INTERACTIVE
_FORMATTER
swallow_broken_pipe
as_completed

IS_INTERACTIVE

class DeltaSecondsFormatter(fmt=None, datefmt=None)

Bases: logging.Formatter

Logging formatter with additional attributes for run time logging.

`delta_secs`

Elapsed seconds since last log/format call (or creation of logger).

`relative_created_secs`

Like *relativeCreated*, time relative to the initialization of the *logging* module but conveniently scaled to seconds as a *float* value.

format(record)

Format the specified record as text.

The record's attribute dictionary is used as the operand to a string formatting operation which yields the returned string. Before formatting the dictionary, a couple of preparatory steps are carried out. The message attribute of the record is computed using LogRecord.getMessage(). If the formatting string uses the time (as determined by a call to usesTime(), formatTime() is called to format the event time. If there is exception information, it is formatted using formatException() and appended to the message.

_FORMATTER

dashlist(iterable, indent=2)

class ContextDecorator

Base class for a context manager class (implementing __enter__() and __exit__()) that also makes it a decorator.

___call___(*f*)

class SwallowBrokenPipe

Bases: ContextDecorator

Base class for a context manager class (implementing __enter__() and __exit__()) that also makes it a decorator.

__enter__()

__exit__(exc_type, exc_val, exc_tb)

swallow_broken_pipe

class CaptureTarget

Bases: enum. Enum

Constants used for contextmanager captured.

Used similarly like the constants PIPE, STDOUT for stdlib's subprocess.Popen.

STRING

STDOUT

env_vars(var_map=None, callback=None, stack_callback=None)

env_var(name, value, callback=None, stack_callback=None)

env_unmodified(callback=None)

captured(stdout=CaptureTarget.STRING, stderr=CaptureTarget.STRING)

Capture outputs of sys.stdout and sys.stderr.

If stdout is STRING, capture sys.stdout as a string, if stdout is None, do not capture sys.stdout, leaving it untouched, otherwise redirect sys.stdout to the file-like object given by stdout.

Behave correspondingly for stderr with the exception that if stderr is STDOUT, redirect sys.stderr to stdout target and set stderr attribute of yielded object to None.

```
>>> from conda.common.io import captured
>>> with captured() as c:
... print("hello world!")
...
>>> c.stdout
'hello world!\n'
```

Parameters

- stdout -- capture target for sys.stdout, one of STRING, None, or file-like object
- stderr -- capture target for sys.stderr, one of STRING, STDOUT, None, or file-like object

Yields

CapturedText --

has attributes stdout, stderr which are either strings, None or the corresponding file-like function argument.

argv(args_list)

_logger_lock()

disable_logger(logger_name)

stderr_log_level(level, logger_name=None)

attach_stderr_handler(level=WARN, logger_name=None, propagate=False, formatter=None)

timeout(timeout_secs, func, *args, default_return=None, **kwargs)

Enforce a maximum time for a callable to complete. Not yet implemented on Windows.

class Spinner(message, enabled=True, json=False, fail_message='failed'\n')

Parameters

- **message** (*str*) -- A message to prefix the spinner with. The string ': ' is automatically appended.
- enabled (bool) -- If False, usage is a no-op.
- json (bool) -- If True, will not output non-json to stdout.

```
spinner_cycle
```

```
start()
```

stop()

_start_spinning()

__enter__()

__exit__(exc_type, exc_val, exc_tb)

class ProgressBar(*description*, *enabled=True*, *json=False*, *position=None*, *leave=True*)

classmethod get_lock()

```
update_to(fraction)
```

finish()

refresh()

Force refresh i.e. once 100% has been reached

close()

static _tqdm(*args, **kwargs)

Deferred import so it doesn't hit the conda activate paths.

class DummyExecutor

Bases: concurrent.futures.Executor

This is an abstract base class for concrete asynchronous executors.

submit(fn, *args, **kwargs)

Submits a callable to be executed with the given arguments.

Schedules the callable to be executed as fn(*args, **kwargs) and returns a Future instance representing the execution of the callable.

Returns

A Future representing the given call.

map(func, *iterables)

Returns an iterator equivalent to map(fn, iter).

Parameters

- fn -- A callable that will take as many arguments as there are passed iterables.
- **timeout** -- The maximum number of seconds to wait. If None, then there is no limit on the wait time.
- **chunksize** -- The size of the chunks the iterable will be broken into before being passed to a child process. This argument is only used by ProcessPoolExecutor; it is ignored by ThreadPoolExecutor.

Returns

map(func, *iterables) but the calls may be evaluated out-of-order.

Return type

An iterator equivalent to

Raises

- **TimeoutError** -- If the entire result iterator could not be generated before the given timeout.
- **Exception** -- If fn(*args) raises for any values.

shutdown(wait=True)

Clean-up the resources associated with the Executor.

It is safe to call this method several times. Otherwise, no other methods can be called after this one.

Parameters

- **wait** -- If True then shutdown will not return until all running futures have finished executing and the resources used by the executor have been reclaimed.
- **cancel_futures** -- If True then shutdown will cancel all pending futures. Futures that are completed or running will not be cancelled.

class ThreadLimitedThreadPoolExecutor(max_workers=10)

Bases: concurrent.futures.ThreadPoolExecutor

This is an abstract base class for concrete asynchronous executors.

submit(fn, *args, **kwargs)

This is an exact reimplementation of the *submit()* method on the parent class, except with an added *try/except* around *self._adjust_thread_count()*. So long as there is at least one living thread, this thread pool will not throw an exception if threads cannot be expanded to *max_workers*.

In the implementation, we use "protected" attributes from concurrent.futures (*_base* and *_WorkItem*). Consider vendoring the whole concurrent.futures library as an alternative to these protected imports.

https://github.com/agronholm/pythonfutures/blob/3.2.0/concurrent/futures/thread.py#L121-L131 # NOQA https://github.com/python/cpython/blob/v3.6.4/Lib/concurrent/futures/thread.py#L114-L124

as_completed

get_instrumentation_record_file()

class time_recorder(entry_name=None, module_name=None)

Bases: ContextDecorator

Base class for a context manager class (implementing __enter__() and __exit__()) that also makes it a decorator.

record_file
start_time
total_call_num
total_run_time
_set_entry_name(f)
__call__(f)
__enter__()
__exit__(exc_type, exc_val, exc_tb)
classmethod log_totals()
_ensure_dir()
print_instrumentation_data()

iterators

Replacements for parts of the toolz library.

Functions

<pre>groupby_to_dict(keyfunc, sequence)</pre>	A toolz-style groupby implementation.
$unique(\rightarrow Generator[Any, None, None])$	A toolz inspired unique implementation.

groupby_to_dict(keyfunc, sequence)

A *toolz*-style groupby implementation.

Returns a dictionary of { key: [group] } instead of iterators.

unique(*sequence: Sequence*[Any]) \rightarrow Generator[Any, None, None]

A toolz inspired unique implementation.

Returns a generator of unique elements in the sequence

logic

The basic idea to nest logical expressions is instead of trying to denest things via distribution, we add new variables. So if we have some logical expression expr, we replace it with x and add expr <-> x to the clauses, where x is a new variable, and expr <-> x is recursively evaluated in the same way, so that the final clauses are ORs of atoms.

To use this, create a new Clauses object with the max var, for instance, if you already have [[1, 2, -3]], you would use C = Clause(3). All functions return a new literal, which represents that function, or True or False if the expression can be resolved fully. They may also add new clauses to C.clauses, which will then be delivered to the SAT solver.

All functions take atoms as arguments (an atom is an integer, representing a literal or a negated literal, or boolean constants True or False; that is, it is the callers' responsibility to do the conversion of expressions recursively. This is done because we do not have data structures representing the various logical classes, only atoms.

The polarity argument can be set to True or False if you know that the literal being used will only be used in the positive or the negative, respectively (e.g., you will only use x, not -x). This will generate fewer clauses. It is probably best if you do not take advantage of this directly, but rather through the Require and Prevent functions.

Classes

Clauses

Functions

minimal_unsatisfiable_subset(clauses, sat, ex-
plicit_specs)Given a set of clauses, find a minimal unsatisfiable sub-
set (an

Attributes

TRUE
FALSE
PycoSatSolver
PyCryptoSatSolver
PySatSolver

TRUE

FALSE

PycoSatSolver = 'pycosat'

PyCryptoSatSolver = 'pycryptosat'

PySatSolver = 'pysat'

class Clauses(m=0, sat_solver=PycoSatSolver)

property m

property unsat

get_clause_count()

as_list()

_check_variable(variable)

_check_literal(literal)

add_clause(clause)

add_clauses(clauses)

name_var(m, name)

new_var(name=None)

from_name(name)

from_index(m)

_assign(vals, name=None)

 $_convert(x)$

_eval(func, args, no_literal_args, polarity, name)

Prevent(*what*, **args*)

Returned is the list of those solutions. When the clauses are unsatisfiable, an empty list is returned.
<pre>itersolve(constraints=None, m=None)</pre>
<pre>minimize(objective, bestsol=None, trymax=False)</pre>
mal_unsatisfiable_subset(clauses, sat, explicit_specs) Given a set of clauses, find a minimal unsatisfiable subset (an unsatisfiable core)
A set is a minimal unsatisfiable subset if no proper subset is unsatisfiable. A set of clauses may have many minimal unsatisfiable subsets of different sizes.
sat should be a function that takes a tuple of clauses and returns True if the clauses are satisfiable and False if they are not. The algorithm will work with any order-reversing function (reversing the order of subset and the order False < True), that is, any function where (A <= B) iff ($sat(B) \le sat(A)$), where A <= B means A is a subset of B and False < True).

Not(*x*, *polarity=None*, *name=None*)

And(*f*, *g*, *polarity=None*, *name=None*)

Or(*f*, *g*, *polarity=None*, *name=None*)

Xor(*f*, *g*, *polarity=None*, *name=None*)

ITE(*c*, *t*, *f*, *polarity=None*, *name=None*) If c Then t Else f.

In this function, if any of c, t, or f are True and False the resulting expression is resolved.

All(*iter*, *polarity=None*, *name=None*)

Any(*vals*, *polarity=None*, *name=None*)

AtMostOne_NSQ(vals, polarity=None, name=None)

AtMostOne_BDD(vals, polarity=None, name=None)

AtMostOne(vals, polarity=None, name=None)

ExactlyOne_NSQ(vals, polarity=None, name=None)

ExactlyOne_BDD(vals, polarity=None, name=None)

ExactlyOne(vals, polarity=None, name=None)

LinearBound(equation, lo, hi, preprocess=True, polarity=None, name=None)

sat(additional=None, includeIf=False, names=False, limit=0)

Calculate a SAT solution for the current clause set.

minimal unsatisfiab

516

path

Common path utilities.

Functions

is_path(value)	
expand(path)	
<pre>paths_equal(path1, path2)</pre>	
	Examples
url_to_path(url)	Convert a file:// URL to a path.
<pre>tokenized_startswith(test_iterable, startswith_iterable)</pre>	
$get_all_directories(\rightarrow list[tuple[str]])$	
$get_leaf_directories(\rightarrow Sequence[str])$	
$explode_directories(\rightarrow set[str])$	
<pre>pyc_path(py_path, python_major_minor_version)</pre>	This must not return backslashes on Windows as that will break
<pre>missing_pyc_files(python_major_minor_version, files)</pre>	
<pre>parse_entry_point_def(ep_definition)</pre>	
<pre>get_python_short_path([python_version])</pre>	
<pre>get_python_site_packages_short_path(python_ve</pre>	
<pre>get_major_minor_version(string[, with_dot])</pre>	
<pre>get_bin_directory_short_path()</pre>	
<pre>win_path_ok(path)</pre>	
<pre>win_path_double_escape(path)</pre>	
<pre>win_path_backout(path)</pre>	
ensure_pad(name[, pad])	
	Examples
<pre>is_private_env_name(env_name)</pre>	
	Examples
<pre>is_private_env_path(env_path)</pre>	
	Examples
right_pad_os_sep(path)	
_split_filename(path_or_url)	
518	Chapter 4. Contributors welcome
<pre>get_python_noarch_target_path(source_short_path)</pre>	

win_path_to_unix(path[, root_prefix])

Attributes

PATH_MATCH_REGEX

KNOWN_EXTENSIONS

_VERSION_REGEX

```
PATH_MATCH_REGEX = '\\./|\\.\\.|~|/|[a-zA-Z]:[/\\\\]|\\\\\\|//'
```

KNOWN_EXTENSIONS = ('.conda', '.tar.bz2', '.json', '.jlap', '.json.zst')

is_path(value)

expand(path)

paths_equal(path1, path2)

Examples

```
>>> paths_equal('/a/b/c', '/a/b/c/d/..')
True
```

url_to_path(url)

Convert a file:// URL to a path.

Relative file URLs (i.e. *file:relative/path*) are not supported.

```
tokenized_startswith(test_iterable, startswith_iterable)
```

explode_directories(*child_directories: Iterable[tuple[str, Ellipsis]]*) → set[str]

pyc_path(py_path, python_major_minor_version)

This must not return backslashes on Windows as that will break tests and leads to an eventual need to make url_to_path return backslashes too and that may end up changing files on disc or to the result of comparisons with the contents of them.

missing_pyc_files(python_major_minor_version, files)

```
parse_entry_point_def(ep_definition)
```

get_python_short_path(python_version=None)

get_python_site_packages_short_path(python_version)

_VERSION_REGEX

get_major_minor_version(string, with_dot=True)

```
get_bin_directory_short_path()
```

win_path_ok(path)

win_path_double_escape(path)

win_path_backout(path)

ensure_pad(name, pad='_')

Examples

```
>>> ensure_pad('conda')
'_conda_'
>>> ensure_pad('_conda')
'__conda_'
>>> ensure_pad('')
''
```

is_private_env_name(env_name)

Examples

```
>>> is_private_env_name("_conda")
False
>>> is_private_env_name("_conda_")
True
```

is_private_env_path(env_path)

Examples

```
>>> is_private_env_path('/some/path/to/envs/_conda_')
True
>>> is_private_env_path('/not/an/envs_dir/_conda_')
False
```

right_pad_os_sep(path)

split_filename(path_or_url)

get_python_noarch_target_path(source_short_path, target_site_packages_short_path)

```
win_path_to_unix(path, root_prefix=")
```

which(executable)

Backwards-compatibility wrapper. Use *shutil.which* directly if possible.

```
strip_pkg_extension(path: str)
```

Examples

```
>>> strip_pkg_extension("/path/_license-1.1-py27_1.tar.bz2")
('/path/_license-1.1-py27_1', '.tar.bz2')
>>> strip_pkg_extension("/path/_license-1.1-py27_1.conda")
('/path/_license-1.1-py27_1', '.conda')
>>> strip_pkg_extension("/path/_license-1.1-py27_1")
('/path/_license-1.1-py27_1', None)
```

is_package_file(path)

Examples

```
>>> is_package_file("/path/_license-1.1-py27_1.tar.bz2")
True
>>> is_package_file("/path/_license-1.1-py27_1.conda")
True
>>> is_package_file("/path/_license-1.1-py27_1")
False
```

pkg_formats

python

Common Python package format utilities.

Classes

PythonDistribution	Base object describing a python distribution based on path to anchor file.
PythonInstalledDistribution	Python distribution installed via distutils.
PythonEggInfoDistribution	Python distribution installed via setuptools.
PythonEggLinkDistribution	Python distribution installed via setuptools.
PythonDistributionMetadata	Object representing the metada of a Python Distribution given by anchor
Evaluator	This class is used to evaluate marker expressions.

Functions

<pre>norm_package_name(name)</pre>	
<pre>pypi_name_to_conda_name(pypi_name)</pre>	
<pre>norm_package_version(version)</pre>	Normalize a version by removing extra spaces and paren- theses.
<pre>split_spec(spec, sep)</pre>	Split a spec by separator and return stripped start and end parts.
<pre>parse_specification(spec)</pre>	Parse a requirement from a python distribution metadata and return a
<pre>get_site_packages_anchor_files(site_packages_pa)</pre>	Get all the anchor files for the site packages directory.
<pre>get_dist_file_from_egg_link(egg_link_file, pre- fix_path)</pre>	Return the egg info file path following an egg link.
<pre>parse_marker(marker_string)</pre>	Parse marker string and return a dictionary containing a marker expression.
_is_literal(o)	
<pre>get_default_marker_context()</pre>	Return the default context dictionary to use when parsing markers.
<pre>interpret(marker[, execution_context])</pre>	Interpret a marker and return a result depending on environment.

Attributes

PYPI_TO_CONDA
PYPI_CONDA_DEPS
PARTIAL_PYPI_SPEC_PATTERN
PY_FILE_RE
PySpec
IDENTIFIER
VERSION_IDENTIFIER
COMPARE_OP
MARKER_OP
OR
AND
NON_SPACE
STRING_CHUNK
DEFAULT_MARKER_CONTEXT
evaluator

PYPI_TO_CONDA

PYPI_CONDA_DEPS

PARTIAL_PYPI_SPEC_PATTERN

PY_FILE_RE

PySpec

exception MetadataWarning

Bases: Warning

Base class for warning categories.

class PythonDistribution(anchor_full_path, python_version)

Base object describing a python distribution based on path to anchor file.

property name

property norm_name

```
property conda_name
```

```
property version
```

MANIFEST_FILES = ()

 $REQUIRES_FILES = ()$

 $MANDATORY_FILES = ()$

ENTRY_POINTS_FILES = ('entry_points.txt',)

static init(prefix_path, anchor_file, python_version)

```
_check_files()
```

Check the existence of mandatory files for a given distribution.

```
_check_path_data(path, checksum, size)
```

Normalizes record data content and format.

static _parse_requires_file_data(data, global_section='__global_')

static _parse_entries_file_data(data)

```
_load_requires_provides_file()
```

```
manifest_full_path()
```

get_paths()

Read the list of installed paths from record or source file.

Example

]

```
get_dist_requirements()
```

```
get_python_requirements()
```

```
get_external_requirements()
```

```
get_extra_provides()
```

get_conda_dependencies()

Process metadata fields providing dependency information.

This includes normalizing fields, and evaluating environment markers.

```
abstract get_optional_dependencies()
```

```
get_entry_points()
```

```
class PythonInstalledDistribution(prefix_path, anchor_file, python_version)
```

Bases: PythonDistribution

Python distribution installed via distutils.

Notes

• https://www.python.org/dev/peps/pep-0376/

MANIFEST_FILES = ('RECORD',)

 $REQUIRES_FILES = ()$

MANDATORY_FILES = ('METADATA',)

ENTRY_POINTS_FILES = ()

is_manageable = True

class PythonEggInfoDistribution(*anchor_full_path*, *python_version*, *sp_reference*)

Bases: PythonDistribution

Python distribution installed via setuptools.

Notes

• http://peak.telecommunity.com/DevCenter/EggFormats

property is_manageable

```
MANIFEST_FILES = ('installed-files.txt', 'SOURCES', 'SOURCES.txt')
```

```
REQUIRES_FILES = ('requires.txt', 'depends.txt')
```

 $MANDATORY_FILES = ()$

```
ENTRY_POINTS_FILES = ('entry_points.txt',)
```

class PythonEggLinkDistribution(prefix_path, anchor_file, python_version)

Bases: PythonEggInfoDistribution

Python distribution installed via setuptools.

Notes

• http://peak.telecommunity.com/DevCenter/EggFormats

is_manageable = False

class PythonDistributionMetadata(path)

Object representing the metada of a Python Distribution given by anchor file (or directory) path.

This metadata is extracted from a single file. Python distributions might create additional files that complement this metadata information, but that is handled at the python distribution level.

Notes

- https://packaging.python.org/specifications/core-metadata/
- Metadata 2.1: https://www.python.org/dev/peps/pep-0566/
- Metadata 2.0: https://www.python.org/dev/peps/pep-0426/ (Withdrawn)
- Metadata 1.2: https://www.python.org/dev/peps/pep-0345/
- Metadata 1.1: https://www.python.org/dev/peps/pep-0314/
- Metadata 1.0: https://www.python.org/dev/peps/pep-0241/

property name

property version

FILE_NAMES = ('METADATA', 'PKG-INFO')

SINGLE_USE_KEYS

MULTIPLE_USE_KEYS

static _process_path(path, metadata_filenames)

Find metadata file inside dist-info folder, or check direct file.

classmethod _message_to_dict(message)

Convert the RFC-822 headers data into a dictionary.

message is an email.parser.Message instance.

The canonical method to transform metadata fields into such a data structure is as follows:

- The original key-value format should be read with email.parser.HeaderParser
- All transformed keys should be reduced to lower case. Hyphens should be replaced with underscores, but otherwise should retain all other characters
- The transformed value for any field marked with "(Multiple-use") should be a single list containing all the original values for the given key
- The Keywords field should be converted to a list by splitting the original value on whitespace characters
- The message body, if present, should be set to the value of the description key.
- The result should be stored as a string-keyed dictionary.

classmethod _read_metadata(fpath)

Read the original format which is stored as RFC-822 headers.

_get_multiple_data(keys)

Helper method to get multiple data values by keys.

Keys is an iterable including the preferred key in order, to include values of key that might have been replaced (deprecated), for example keys can be ['requires_dist', 'requires'], where the key 'requires' is deprecated and replaced by 'requires_dist'.

get_dist_requirements()

Changed in version 2.1: The field format specification was relaxed to accept the syntax used by popular publishing tools.

Each entry contains a string naming some other distutils project required by this distribution.

The format of a requirement string contains from one to four parts:

- A project name, in the same format as the Name: field. The only mandatory part.
- A comma-separated list of 'extra' names. These are defined by the required project, referring to specific features which may need extra dependencies.
- A version specifier. Tools parsing the format should accept optional parentheses around this, but tools generating it should not use parentheses.
- An environment marker after a semicolon. This means that the requirement is only needed in the specified conditions.

This field may be followed by an environment marker after a semicolon.

Example

frozenset(['pkginfo', 'PasteDeploy', 'zope.interface (>3.5.0)',

'pywin32 >1.0; sys_platform == "win32"'])

Return 'Requires' if 'Requires-Dist' is empty.

get_python_requirements()

New in version 1.2.

This field specifies the Python version(s) that the distribution is guaranteed to be compatible with. Installation tools may look at this when picking which version of a project to install.

The value must be in the format specified in Version specifiers.

This field may be followed by an environment marker after a semicolon.

Example

frozenset(['>=3', '>2.6,!=3.0.*,!=3.1.*', '~=2.6', '>=3; sys_platform == "win32"'])

get_external_requirements()

Changed in version 2.1: The field format specification was relaxed to accept the syntax used by popular publishing tools.

Each entry contains a string describing some dependency in the system that the distribution is to be used. This field is intended to serve as a hint to downstream project maintainers, and has no semantics which are meaningful to the distutils distribution.

The format of a requirement string is a name of an external dependency, optionally followed by a version declaration within parentheses.

This field may be followed by an environment marker after a semicolon.

Because they refer to non-Python software releases, version numbers for this field are not required to conform to the format specified in PEP 440: they should correspond to the version scheme used by the external dependency.

Notice that there's is no particular rule on the strings to be used!

Example

frozenset(['C', 'libpng (>=1.5)', 'make; sys_platform != "win32"'])

get_extra_provides()

New in version 2.1.

A string containing the name of an optional feature. Must be a valid Python identifier. May be used to make a dependency conditional on hether the optional feature has been requested.

Example

frozenset(['pdf', 'doc', 'test'])

get_dist_provides()

New in version 1.2.

Changed in version 2.1: The field format specification was relaxed to accept the syntax used by popular publishing tools.

Each entry contains a string naming a Distutils project which is contained within this distribution. This field must include the project identified in the Name field, followed by the version : Name (Version).

A distribution may provide additional names, e.g. to indicate that multiple projects have been bundled together. For instance, source distributions of the ZODB project have historically included the transaction project, which is now available as a separate distribution. Installing such a source distribution satisfies requirements for both ZODB and transaction.

A distribution may also provide a "virtual" project name, which does not correspond to any separatelydistributed project: such a name might be used to indicate an abstract capability which could be supplied by one of multiple projects. E.g., multiple projects might supply RDBMS bindings for use by a given ORM: each project might declare that it provides ORM-bindings, allowing other projects to depend only on having at most one of them installed.

A version declaration may be supplied and must follow the rules described in Version specifiers. The distribution's version number will be implied if none is specified.

This field may be followed by an environment marker after a semicolon.

Return Provides in case Provides-Dist is empty.

get_dist_obsolete()

New in version 1.2.

Changed in version 2.1: The field format specification was relaxed to accept the syntax used by popular publishing tools.

Each entry contains a string describing a distutils project's distribution which this distribution renders obsolete, meaning that the two projects should not be installed at the same time.

Version declarations can be supplied. Version numbers must be in the format specified in Version specifiers [1].

The most common use of this field will be in case a project name changes, e.g. Gorgon 2.3 gets subsumed into Torqued Python 1.0. When you install Torqued Python, the Gorgon distribution should be removed.

This field may be followed by an environment marker after a semicolon.

Return Obsoletes in case Obsoletes-Dist is empty.

Example

frozenset(['Gorgon', "OtherProject (<3.0); python_version == '2.7'''])

Notes

• [1] https://packaging.python.org/specifications/version-specifiers/

get_classifiers()

Classifiers are described in PEP 301, and the Python Package Index publishes a dynamic list of currently defined classifiers.

This field may be followed by an environment marker after a semicolon.

Example

frozenset(['Development Status :: 4 - Beta',
 "Environment :: Console (Text Based) ; os_name == "posix"])

norm_package_name(name)

pypi_name_to_conda_name(pypi_name)

norm_package_version(version)

Normalize a version by removing extra spaces and parentheses.

split_spec(spec, sep)

Split a spec by separator and return stripped start and end parts.

parse_specification(spec)

Parse a requirement from a python distribution metadata and return a namedtuple with name, extras, constraints, marker and url components.

This method does not enforce strict specifications but extracts the information which is assumed to be *correct*. As such no errors are raised.

Example

PySpec(name='requests', extras=['security'], constraints='>=3.3.0', marker='foo >= 2.7 or bar == 1', url="])

get_site_packages_anchor_files(site_packages_path, site_packages_dir)

Get all the anchor files for the site packages directory.

get_dist_file_from_egg_link(egg_link_file, prefix_path)

Return the egg info file path following an egg link.

parse_marker(marker_string)

Parse marker string and return a dictionary containing a marker expression.

The dictionary will contain keys "op", "lhs" and "rhs" for non-terminals in the expression grammar, or strings. A string contained in quotes is to be interpreted as a literal string, and a string not contained in quotes is a variable (such as os_name).

IDENTIFIER

VERSION_IDENTIFIER

COMPARE_OP

MARKER_OP

OR

AND

NON_SPACE

STRING_CHUNK

_is_literal(*o*)

class Evaluator

This class is used to evaluate marker expressions.

operations

evaluate(expr, context)

Evaluate a marker expression returned by the parse_requirement() function in the specified context.

get_default_marker_context()

Return the default context dictionary to use when parsing markers.

DEFAULT_MARKER_CONTEXT

evaluator

interpret(marker, execution_context=None)

Interpret a marker and return a result depending on environment.

Parameters

- marker (str) -- The marker to interpret.
- **execution_context** (*mapping*) -- The context used for name lookup.

serialize

YAML and JSON serialization and deserialization functions.

Functions

_yaml_round_trip()	
_yaml_safe()	
<pre>yaml_round_trip_load(string)</pre>	
<pre>yaml_safe_load(string)</pre>	
	Examples
	Examples
yaml_round_trip_dump(object[, stream])	Dump object to string or stream.
<pre>yaml_safe_dump(object[, stream])</pre>	Dump object to string or stream.
json_load(string)	
json_dump(object)	
_yaml_round_trip()	

_yaml_safe()

yaml_round_trip_load(string)

yaml_safe_load(string)

Examples

>>> yaml_safe_load("key: value")
{'key': 'value'}

yaml_round_trip_dump(object, stream=None)
 Dump object to string or stream.

yaml_safe_dump(object, stream=None)

Dump object to string or stream.

json_load(string)

json_dump(object)

signals

Intercept signals and handle them gracefully.

Functions

get_signal_name(signum)

Examples

signal_handler(handler)

Attributes

INTERRUPT_SIGNALS

INTERRUPT_SIGNALS = ('SIGABRT', 'SIGINT', 'SIGTERM', 'SIGQUIT', 'SIGBREAK')

get_signal_name(signum)

Examples

```
>>> from signal import SIGINT
>>> get_signal_name(SIGINT)
'SIGINT'
```

signal_handler(handler)

toposort

Topological sorting implementation.

Functions

_toposort(data)	Dependencies are expressed as a dictionary whose keys are items
pop_key(data)	Pop an item from the graph that has the fewest depen- dencies in the case of a tie
_safe_toposort(data)	Dependencies are expressed as a dictionary whose keys are items
<pre>toposort(data[, safe])</pre>	

_toposort(data)

Dependencies are expressed as a dictionary whose keys are items and whose values are a set of dependent items. Output is a list of sets in topological order. The first set consists of items with no dependences, each subsequent set consists of items that depend upon items in the preceding sets.

pop_key(data)

Pop an item from the graph that has the fewest dependencies in the case of a tie The winners will be sorted alphabetically

_safe_toposort(data)

Dependencies are expressed as a dictionary whose keys are items and whose values are a set of dependent items. Output is a list of sets in topological order. The first set consists of items with no dependencies, each subsequent set consists of items that depend upon items in the preceding sets.

toposort(data, safe=True)

url

Common URL utilities.

Classes

Url	Object used to represent a Url. The string representation
	of this object is a url string.

Functions

<pre>hex_octal_to_int(ho)</pre>	
<pre>percent_decode(path)</pre>	
<pre>path_to_url(path)</pre>	
$urlparse(\rightarrow Url)$	
<pre>url_to_s3_info(url) is url(url)</pre>	Convert an s3 url to a tuple of bucket and key.
	Examples
<pre>is_ipv4_address(string_ip)</pre>	
	Examples
<pre>is_ipv6_address(string_ip)</pre>	
	Examples
<pre>is_ip_address(string_ip)</pre>	
	Examples
join(*args)	
has_scheme(value)	
<pre>strip_scheme(url)</pre>	
	Examples
mask_anaconda_token(url)	
<pre>split_anaconda_token(url)</pre>	
	Examples
<pre>split_platform(known_subdirs, url)</pre>	
	Examples
_split_platform_re(known_subdirs)	
<pre>has_platform(url, known_subdirs)</pre>	
<pre>split_scheme_auth_token(url)</pre>	
	Examples
534 <i>lit_conda_url_easy_parts</i> (known_subdirs, url)	Chapter 4. Contributors welcom
<pre>get_proxy_username_and_pass(scheme)</pre>	

Attributes

file_scheme
url_attrs

def url_to_path(url):

join_url

hex_octal_to_int(ho)

percent_decode(path)

file_scheme = 'file://'

def url_to_path(url): assert url.startswith(file_scheme), "{} is not a file-scheme URL".format(url) decoded = percent_decode(url[len(file_scheme):]) if decoded.startswith('/') and decoded[2] == ':':

A Windows path. decoded.replace('/', '')

return decoded

path_to_url(path)

url_attrs = ('scheme', 'path', 'query', 'fragment', 'username', 'password', 'hostname', 'port')

class Url

Bases: namedtuple('Url', url_attrs)

Object used to represent a Url. The string representation of this object is a url string.

This object was inspired by the urllib3 implementation as it gives you a way to construct URLs from various parts. The motivation behind this object was making something that is interoperable with built the *urllib.parse.urlparse* function and has more features than the built-in *ParseResult* object.

property auth

property netloc

__str__()

Return str(self).

 $\texttt{as_dict()} \rightarrow \texttt{dict}$

Provide a public interface for namedtuple's _asdict

```
replace(**kwargs) \rightarrow Url
```

Provide a public interface for namedtuple's _replace

classmethod from_parse_result(parse_result: urllib.parse.ParseResult) \rightarrow Url

urlparse(*url*: *str*) \rightarrow *Url*

url_to_s3_info(url)

Convert an s3 url to a tuple of bucket and key.

Examples

```
>>> url_to_s3_info("s3://bucket-name.bucket/here/is/the/key")
('bucket-name.bucket', '/here/is/the/key')
```

is_url(url)

Examples

>>> is_url(None)
False
>>> is_url("s3://some/bucket")
True

is_ipv4_address(string_ip)

Examples

```
>>> [is_ipv4_address(ip) for ip in ('8.8.8.8', '192.168.10.10', '255.255.255.255')]
[True, True, True]
>>> [is_ipv4_address(ip) for ip in ('8.8.8', '192.168.10.10.20', '256.255.255',
__'::1')]
[False, False, False, False]
```

is_ipv6_address(string_ip)

Examples

>> [is_ipv6_address(ip) for ip in ('::1', '2001:db8:85a3::370:7334', '1234:'*7+'1234')] [True, True, True] >> [is_ipv6_address(ip) for ip in ('192.168.10.10', '1234:'*8+'1234')] [False, False]

is_ip_address(string_ip)

Examples

>> is_ip_address('192.168.10.10') True >> is_ip_address('::1') True >> is_ip_address('www.google.com') False

join(*args)

join_url

has_scheme(value)

strip_scheme(url)
Examples

```
>>> strip_scheme("https://www.conda.io")
'www.conda.io'
>>> strip_scheme("s3://some.bucket/plus/a/path.ext")
'some.bucket/plus/a/path.ext'
```

mask_anaconda_token(url)

split_anaconda_token(url)

Examples

```
>>> split_anaconda_token("https://1.2.3.4/t/tk-123-456/path")
(u'https://1.2.3.4/path', u'tk-123-456')
>>> split_anaconda_token("https://1.2.3.4/t//path")
(u'https://1.2.3.4/path', u'')
>>> split_anaconda_token("https://some.domain/api/t/tk-123-456/path")
(u'https://some.domain/api/path', u'tk-123-456')
>>> split_anaconda_token("https://1.2.3.4/conda/t/tk-123-456/path")
(u'https://1.2.3.4/conda/path', u'tk-123-456')
>>> split_anaconda_token("https://1.2.3.4/path")
(u'https://1.2.3.4/path', None)
>>> split_anaconda_token("https://10.2.3.4:8080/conda/t/tk-123-45")
(u'https://10.2.3.4:8080/conda', u'tk-123-45')
```

split_platform(known_subdirs, url)

Examples

```
>>> from conda.base.constants import KNOWN_SUBDIRS
>>> split_platform(KNOWN_SUBDIRS, "https://1.2.3.4/t/tk-123/linux-ppc64le/path")
(u'https://1.2.3.4/t/tk-123/path', u'linux-ppc64le')
```

_split_platform_re(known_subdirs)

has_platform(url, known_subdirs)

split_scheme_auth_token(url)

Examples

```
>>> split_scheme_auth_token("https://u:p@conda.io/t/x1029384756/more/path")
('conda.io/more/path', 'https', 'u:p', 'x1029384756')
>>> split_scheme_auth_token(None)
(None, None, None, None)
```

split_conda_url_easy_parts(known_subdirs, url)

```
get_proxy_username_and_pass(scheme)
```

add_username_and_password(url: str, username: str, password: str) \rightarrow str

Inserts username and password into provided url

>>> add_username_and_password('https://anaconda.org', 'TestUser', 'Password')
'https://TestUser:Password@anaconda.org'

maybe_add_auth(*url: str, auth: str, force=False*) \rightarrow str

Add auth if the url doesn't currently have it.

By default, does not replace auth if it already exists. Setting force to True overrides this behavior.

Examples

```
>>> maybe_add_auth("https://www.conda.io", "user:passwd")
'https://user:passwd@www.conda.io'
>>> maybe_add_auth("https://www.conda.io", "")
'https://www.conda.io'
```

maybe_unquote(url)

remove_auth(*url: str*) \rightarrow str

Remove embedded authentication from URL.

```
>>> remove_auth("https://user:password@anaconda.com")
'https://anaconda.com'
```

core

Code in conda.core is the core logic. It is strictly forbidden from having side effects. No printing to stdout or stderr, no disk manipulation, no http requests. All side effects should be implemented through conda.gateways. Objects defined in conda.models should be heavily preferred for conda.core function/method arguments and return values.

Conda modules importable from conda.core are

- conda._vendor
- conda.common
- conda.core
- conda.models
- conda.gateways

Conda modules strictly off limits for import within conda.core are

- conda.api
- conda.cli
- conda.client

envs_manager

Tools for managing conda environments.

Functions

```
get_user_environments_txt_file([userhome])
register_env(location)
unregister_env(location)
list_all_known_prefixes()
query_all_prefixes(spec)
_clean_environments_txt(environments_txt_file[,
...])
_rewrite_environments_txt(environments_txt_file,
prefixes)
```

get_user_environments_txt_file(userhome='~')

register_env(location)

unregister_env(location)

list_all_known_prefixes()

query_all_prefixes(spec)

_clean_environments_txt(environments_txt_file, remove_location=None)

_rewrite_environments_txt(environments_txt_file, prefixes)

index

Tools for fetching the current index.

Functions

$check_allowlist(\rightarrow None)$	Check if the given channel URLs are allowed by the con- text's allowlist.
<pre>get_index(, prepend, platform, use_local, use_cache,)</pre>	Return the index of packages available on the channels
$fetch_index(\rightarrow dict)$	Fetch the package index from the specified channels.
$dist_str_in_index(\rightarrow bool)$	Check if a distribution string matches any package in the index.
$_supplement_index_with_prefix(\rightarrow None)$	Supplement the given index with information from the specified environment prefix.
$_supplement_index_with_cache(\rightarrow None)$	Supplement the given index with packages from the cache.
_make_virtual_package(→ conda.models.records.PackageRecord)	Create a virtual package record.
$_supplement_index_with_features(\rightarrow None)$	Supplement the given index with virtual feature records.
$_supplement_index_with_system(\rightarrow None)$	Loads and populates virtual package records from conda plugins
$get_archspec_name(\rightarrow str \mid None)$	Determine the architecture specification name for the current environment.
<pre>calculate_channel_urls(, prepend, platform, use_local)</pre>	Calculate the full list of channel URLs to use based on the given parameters.
$get_reduced_index(\rightarrow dict)$	Generate a reduced package index based on the given specifications.

Attributes

LAST_CHANNEL_URLS

check_allowlist(*channel_urls: list[str]*) \rightarrow None

Check if the given channel URLs are allowed by the context's allowlist.

Parameters

channel_urls -- A list of channel URLs to check against the allowlist.

Raises

ChannelNotAllowed -- If any URL is not in the allowlist.

LAST_CHANNEL_URLS = []

get_index(channel_urls: tuple[str] = (), prepend: bool = True, platform: str | None = None, use_local: bool =
False, use_cache: bool = False, unknown: bool | None = None, prefix: str | None = None, repodata_fn:
str = context.repodata_fns[-1]) → dict

Return the index of packages available on the channels

If prepend=False, only the channels passed in as arguments are used. If platform=None, then the current platform is used. If prefix is supplied, then the packages installed in that prefix are added.

Parameters

• **channel_urls** -- Channels to include in the index.

- prepend -- If False, only the channels passed in are used.
- platform -- Target platform for the index.
- **use_local** -- Whether to use local channels.
- use_cache -- Whether to use cached index information.
- unknown -- Include unknown packages.
- **prefix** -- Path to environment prefix to include in the index.
- **repodata_fn** -- Filename of the repodata file.

Returns

A dictionary representing the package index.

fetch_index(*channel_urls: list[str]*, *use_cache: bool = False, index: dict | None = None, repodata_fn: str = context.repodata_fns[-1]*) \rightarrow dict

Fetch the package index from the specified channels.

Parameters

- channel_urls -- A list of channel URLs to fetch the index from.
- use_cache -- Whether to use the cached index data.
- **index** -- An optional pre-existing index to update.
- repodata_fn -- The name of the repodata file.

Returns

A dictionary representing the fetched or updated package index.

dist_str_in_index(*index: dict*[Any, Any], dist_str: str) → bool

Check if a distribution string matches any package in the index.

Parameters

- index -- The package index.
- dist_str -- The distribution string to match against the index.

Returns

True if there is a match; False otherwise.

_supplement_index_with_prefix(*index: dict*[Any, Any], prefix: str) \rightarrow None

Supplement the given index with information from the specified environment prefix.

Parameters

- index -- The package index to supplement.
- **prefix** -- The path to the environment prefix.

_supplement_index_with_cache(index: dict[Any, Any]) → None

Supplement the given index with packages from the cache.

Parameters

index -- The package index to supplement.

 $_make_virtual_package(name: str, version: str | None = None, build_string: str | None = None) \rightarrow conda.models.records.PackageRecord$

Create a virtual package record.

Parameters

- name -- The name of the virtual package.
- version -- The version of the virtual package, defaults to "0".
- **build_string** -- The build string of the virtual package, defaults to "0".

Returns

A PackageRecord representing the virtual package.

_supplement_index_with_features(index: dict[conda.models.records.PackageRecord,

```
conda.models.records.PackageRecord], features: list[str] = [] \rightarrow None
```

Supplement the given index with virtual feature records.

Parameters

- index -- The package index to supplement.
- features -- A list of feature names to add to the index.

_supplement_index_with_system(index: dict[conda.models.records.PackageRecord, conda.models.records.PackageRecord]) → None

Loads and populates virtual package records from conda plugins and adds them to the provided index, unless there is a naming conflict.

Parameters

index -- The package index to supplement.

get_archspec_name() \rightarrow str | None

Determine the architecture specification name for the current environment.

Returns

The architecture name if available, otherwise None.

 $calculate_channel_urls(channel_urls: tuple[str] = (), prepend: bool = True, platform: str | None = None, use_local: bool = False) \rightarrow list[str]$

Calculate the full list of channel URLs to use based on the given parameters.

Parameters

- channel_urls -- Initial list of channel URLs.
- prepend -- Whether to prepend default channels to the list.
- platform -- The target platform for the channels.
- **use_local** -- Whether to include the local channel.

Returns

The calculated list of channel URLs.

get_reduced_index(prefix: str | None, channels: list[str], subdirs: list[str], specs:

list[conda.models.match_spec.MatchSpec], repodata_fn: str) \rightarrow dict

Generate a reduced package index based on the given specifications.

This function is useful for optimizing the solver by reducing the amount of data it needs to consider.

Parameters

- **prefix** -- Path to an environment prefix to include installed packages.
- channels -- A list of channel names to include in the index.
- subdirs -- A list of subdirectories to consider for each channel.
- **specs** -- A list of MatchSpec objects to filter the packages.

• **repodata_fn** -- Filename of the repodata file to use.

Returns

A dictionary representing the reduced package index.

initialize

Backend logic for conda init.

Sections in this module are

- 1. top-level functions
- 2. plan creators
- 3. plan runners
- 4. individual operations
- 5. helper functions

The top-level functions compose and execute full plans.

A plan is created by composing various individual operations. The plan data structure is a list of dicts, where each dict represents an individual operation. The dict contains two keys-*function* and *kwargs*--where function is the name of the individual operation function within this module.

Each individual operation must

- a) return a Result (i.e. NEEDS_SUDO, MODIFIED, or NO_CHANGE)
- b) have no side effects if context.dry_run is True
- c) be verbose and descriptive about the changes being made or proposed is context.verbose

The plan runner functions take the plan (list of dicts) as an argument, and then coordinate the execution of each individual operation. The docstring for *run_plan_elevated()* has details on how that strategy is implemented.

Classes

Result

Functions

```
install(conda_prefix)
initialize(conda_prefix, shells, for_user, for_system,
...)
initialize_dev(shell[, dev_env_prefix,
conda_source_root])
__initialize_dev_bash(prefix, env_vars, un-
set_env_vars)
__initialize_dev_cmdexe(prefix, env_vars, un-
set_env_vars)
__initialize_dev_cmdexe(prefix, env_vars, un-
set_env_vars)
```

continues on next page

<pre>make_install_plan(conda_prefix)</pre>		
<pre>make_initialize_plan(conda_prefix, for_user,)</pre>	shells,	Creates a plan for initializing conda in shells.
<i>run_plan</i> (plan)		
<pre>run_plan_elevated(plan)</pre>		The strategy of this function differs between unix and Windows. Both strategies use a
<pre>run_plan_from_stdin()</pre>		
<pre>run_plan_from_temp_file(temp_path)</pre>		
<pre>print_plan_results(plan[, stream])</pre>		
<pre>make_entry_point(target_path, conda_prefix, ule, func)</pre>	, mod-	
<pre>make_entry_point_exe(target_path, conda_pr</pre>	refix)	
<pre>install_anaconda_prompt(target_path, conda_prefix, reverse)</pre>		
_install_file(target_path, file_content)		
<pre>install_conda_sh(target_path, conda_prefix)</pre>		
<pre>install_Scripts_activate_bat(target_path conda_prefix)</pre>	,	
<pre>install_activate_bat(target_path, conda_pr</pre>	efix)	
<pre>install_deactivate_bat(target_path, conda_prefix)</pre>		
install_activate(target_path, conda_prefix)		
<pre>install_deactivate(target_path, conda_prefile)</pre>	x)	
<pre>install_condabin_conda_bat(target_path, conda_prefix)</pre>		
<pre>install_library_bin_conda_bat(target_pat conda prefix)</pre>	ih,	
<pre>install_condabin_conda_activate_bat(ta)</pre>	rget_patl	
<pre>install_condabin_rename_tmp_bat(target_j conda_prefix)</pre>	path,	
<pre>install_condabin_conda_auto_activate)</pre>	bat(targ	
<pre>install_condabin_hook_bat(target_path, conda prefix)</pre>		
install_conda_fish(target_path, conda_prefi	x)	
<pre>install_conda_psm1(target_path, conda_prefi</pre>	x)	
<pre>install_conda_hook_ps1(target_path, conda_prefix)</pre>		
		continues on next page

Table 4 – continued from previous page

Table 4 – continued from previous page
<pre>install_conda_xsh(target_path, conda_prefix)</pre>
<pre>install_conda_csh(target_path, conda_prefix)</pre>
_config_fish_content(conda_prefix)
<pre>init_fish_user(target_path, conda_prefix, reverse)</pre>
_config_xonsh_content(conda_prefix)
<pre>init_xonsh_user(target_path, conda_prefix, reverse)</pre>
_bashrc_content(conda_prefix, shell)
<i>init_sh_user</i> (target_path, conda_prefix, shell[, re-verse])
<pre>init_sh_system(target_path, conda_prefix[, reverse])</pre>
<pre>_read_windows_registry(target_path)</pre>
_write_windows_registry(target_path, value value,)
<pre>init_cmd_exe_registry(target_path, conda_prefix[, reverse])</pre>
<pre>init_long_path(target_path)</pre>
_powershell_profile_content(conda_prefix)
<i>init_powershell_user</i> (target_path, conda_prefix, reverse)
<pre>remove_conda_in_sp_dir(target_path)</pre>
<pre>make_conda_egg_link(target_path, conda source root)</pre>
<pre>modify_easy_install_pth(target_path, conda source root)</pre>
<pre>make_dev_egg_info_file(target_path)</pre>
<pre>make_diff(old, new)</pre>
_get_python_info(prefix)

Table 4 – continued from previous page

Attributes

CONDA_INITIALIZE_RE_BLOCK

CONDA_INITIALIZE_PS_RE_BLOCK

temp_path

CONDA_INITIALIZE_RE_BLOCK = '^# >>> conda initialize >>>(?:\\n|\\r\\n)([\\s\\S]*?)# <<< conda initialize <<<(?:\\n|\\r\\n)?'

CONDA_INITIALIZE_PS_RE_BLOCK = '^#region conda initialize(?:\\n|\\r\\n)([\\s\\S]*?)#endregion(?:\\n|\\r\\n)?'

class Result

NEEDS_SUDO = 'needs sudo'

MODIFIED = 'modified'

NO_CHANGE = 'no change'

install(conda_prefix)

initialize(conda_prefix, shells, for_user, for_system, anaconda_prompt, reverse=False)

initialize_dev(shell, dev_env_prefix=None, conda_source_root=None)

_initialize_dev_bash(prefix, env_vars, unset_env_vars)

_initialize_dev_cmdexe(prefix, env_vars, unset_env_vars)

make_install_plan(conda_prefix)

make_initialize_plan(conda_prefix, shells, for_user, for_system, anaconda_prompt, reverse=False)

Creates a plan for initializing conda in shells.

Bash: On Linux, when opening the terminal, .bashrc is sourced (because it is an interactive shell). On macOS on the other hand, the .bash_profile gets sourced by default when executing it in Terminal.app. Some other programs do the same on macOS so that's why we're initializing conda in .bash_profile. On Windows, there are multiple ways to open bash depending on how it was installed. Git Bash, Cygwin, and MSYS2 all use .bash_profile by default.

PowerShell: There's several places PowerShell can store its path, depending on if it's Windows PowerShell, PowerShell Core on Windows, or PowerShell Core on macOS/Linux. The easiest way to resolve it is to just ask different possible installations of PowerShell where their profiles are.

run_plan(plan)

run_plan_elevated(plan)

The strategy of this function differs between unix and Windows. Both strategies use a subprocess call, where the subprocess is run with elevated privileges. The executable invoked with the subprocess is *python -m conda.core.initialize*, so see the *if* $_name_$ == " $_main_$ " at the bottom of this module.

For unix platforms, we convert the plan list to json, and then call this module with *sudo python -m conda.core.initialize* while piping the plan json to stdin. We collect json from stdout for the results of the plan execution with elevated privileges.

For Windows, we create a temporary file that holds the json content of the plan. The subprocess reads the content of the file, modifies the content of the file with updated execution status, and then closes the file. This process then reads the content of that file for the individual operation execution results, and then deletes the file.

run_plan_from_stdin()

run_plan_from_temp_file(temp_path)

- print_plan_results(plan, stream=None)
- make_entry_point(target_path, conda_prefix, module, func)
- make_entry_point_exe(target_path, conda_prefix)
- install_anaconda_prompt(target_path, conda_prefix, reverse)
- _install_file(target_path, file_content)
- install_conda_sh(target_path, conda_prefix)
- install_Scripts_activate_bat(target_path, conda_prefix)
- install_activate_bat(target_path, conda_prefix)
- install_deactivate_bat(target_path, conda_prefix)
- install_activate(target_path, conda_prefix)
- install_deactivate(target_path, conda_prefix)
- install_condabin_conda_bat(target_path, conda_prefix)
- install_library_bin_conda_bat(target_path, conda_prefix)
- install_condabin_conda_activate_bat(target_path, conda_prefix)
- install_condabin_rename_tmp_bat(target_path, conda_prefix)
- install_condabin_conda_auto_activate_bat(target_path, conda_prefix)
- install_condabin_hook_bat(target_path, conda_prefix)
- install_conda_fish(target_path, conda_prefix)
- install_conda_psm1(target_path, conda_prefix)
- install_conda_hook_ps1(target_path, conda_prefix)
- install_conda_xsh(target_path, conda_prefix)
- install_conda_csh(target_path, conda_prefix)
- _config_fish_content(conda_prefix)
- init_fish_user(target_path, conda_prefix, reverse)
- _config_xonsh_content(conda_prefix)

init_xonsh_user(target_path, conda_prefix, reverse) _bashrc_content(conda_prefix, shell) init_sh_user(target_path, conda_prefix, shell, reverse=False) init_sh_system(target_path, conda_prefix, reverse=False) _read_windows_registry(target_path) _write_windows_registry(target_path, value_value, value_type) init_cmd_exe_registry(target_path, conda_prefix, reverse=False) init_long_path(target_path) _powershell_profile_content(conda_prefix) init_powershell_user(target_path, conda_prefix, reverse) remove_conda_in_sp_dir(target_path) make_conda_egg_link(target_path, conda_source_root) modify_easy_install_pth(target_path, conda_source_root) make_dev_egg_info_file(target_path) make_diff(old, new) _get_python_info(prefix) temp_path

link

Package installation implemented as a series of link/unlink transactions.

Classes

PrefixSetup
ActionGroup
PrefixActionGroup
ChangeReport
UnlinkLinkTransaction

Functions

```
determine_link_type(extracted_package_dir, tar-
get_prefix)
make_unlink_actions(transaction_context, ...)
match_specs_to_dists(packages_info_to_link,
specs)
run_script(→ bool)
```

Call the post-link (or pre-unlink) script, returning True on success,

messages(prefix)

determine_link_type(*extracted_package_dir*, *target_prefix*) make_unlink_actions(transaction_context, target_prefix, prefix_record) match_specs_to_dists(packages_info_to_link, specs) class PrefixSetup Bases: NamedTuple target_prefix: str unlink_precs: tuple[conda.models.records.PackageRecord, Ellipsis] link_precs: tuple[conda.models.records.PackageRecord, Ellipsis] remove_specs: tuple[conda.resolve.MatchSpec, Ellipsis] update_specs: tuple[conda.resolve.MatchSpec, Ellipsis] neutered_specs: tuple[conda.resolve.MatchSpec, Ellipsis] class ActionGroup Bases: NamedTuple type: str pkg_data: conda.models.package_info.PackageInfo | None actions: Iterable[conda.core.path_actions._Action] target_prefix: str class PrefixActionGroup Bases: NamedTuple remove_menu_action_groups: Iterable[ActionGroup] unlink_action_groups: Iterable[ActionGroup] unregister_action_groups: Iterable[ActionGroup] link_action_groups: Iterable[ActionGroup]

register_action_groups: Iterable[ActionGroup]
compile_action_groups: Iterable[ActionGroup]
make_menu_action_groups: Iterable[ActionGroup]
entry_point_action_groups: Iterable[ActionGroup]
prefix_record_groups: Iterable[ActionGroup]
class ChangeReport
Bases: NamedTuple

prefix: str

specs_to_remove: Iterable[conda.resolve.MatchSpec]
specs_to_add: Iterable[conda.resolve.MatchSpec]
removed_precs: Iterable[conda.models.records.PackageRecord]
new_precs: Iterable[conda.models.records.PackageRecord]
updated_precs: Iterable[conda.models.records.PackageRecord]
downgraded_precs: Iterable[conda.models.records.PackageRecord]
superseded_precs: Iterable[conda.models.records.PackageRecord]
fetch_precs: Iterable[conda.models.records.PackageRecord]

class UnlinkLinkTransaction(*setups)

property nothing_to_do

download_and_extract()

prepare()

verify()

_verify_pre_link_message(all_link_groups)

execute()

_get_pfe()

classmethod _prepare(transaction_context, target_prefix, unlink_precs, link_precs, remove_specs, update_specs, neutered_specs)

static _verify_individual_level(prefix_action_group)

static _verify_prefix_level(target_prefix_AND_prefix_action_group_tuple)

static _verify_transaction_level(prefix_setups)

_verify(prefix_setups, prefix_action_groups)

_execute(all_action_groups)

static _execute_actions(axngroup)

static _execute_post_link_actions(axngroup)

static _reverse_actions(axngroup, reverse_from_idx=-1)

static _get_python_version(target_prefix, pcrecs_to_unlink, packages_info_to_link)

_make_legacy_action_groups()

print_transaction_summary()

_change_report_str(change_report)

run_script(*prefix: str, prec, action: str = 'post-link', env_prefix: str = None, activate: bool = False*) \rightarrow bool Call the post-link (or pre-unlink) script, returning True on success, False on failure.

messages(prefix)

package_cache

Backport of conda.core.package_cache_data for conda-build.

ProgressiveFetchExtract

package_cache_data

Tools for managing the package cache (previously downloaded packages).

Classes

PackageCacheType	This metaclass does basic caching of PackageCache in- stance objects.
PackageCacheData	
UrlsData	
ProgressiveFetchExtract	

Functions

<pre>do_cache_action(prec, cache_action,])</pre>	progress_bar[,	This function gets called from <i>ProgressiveFetchEx-tract.execute</i> .
<pre>do_extract_action(prec, progress_bar)</pre>	extract_action,	This function gets called after do_cache_action com- pletes.
do_cleanup(actions)		
do_reverse(actions)		
<pre>done_callback(future, actions, progr tions)</pre>	ess_bar, excep-	
<pre>rm_fetched(dist)</pre>		Checks to see if the requested package is in the cache; and if so, it removes both
download(url, dst_path[, session, md5s	um, urlstxt,])	

Attributes

FileNotFoundError

THREADSAFE_EXTRACT

EXTRACT_THREADS

FileNotFoundError

THREADSAFE_EXTRACT = False

EXTRACT_THREADS

class PackageCacheType

Bases: type

This metaclass does basic caching of PackageCache instance objects.

__call__(pkgs_dir: str | os.PathLike | pathlib.Path)

Call self as a function.

class PackageCacheData(pkgs_dir)

property _package_cache_records

property is_writable

cache: dict[str, PackageCacheData]

insert(package_cache_record)

load()

reload()

get(package_ref, default=NULL)

remove(*package_ref*, *default=NULL*)

query(package_ref_or_match_spec)

iter_records()

classmethod query_all(package_ref_or_match_spec, pkgs_dirs=None)

classmethod first_writable(pkgs_dirs=None)

classmethod writable_caches(pkgs_dirs=None)

classmethod read_only_caches(pkgs_dirs=None)

classmethod all_caches_writable_first(pkgs_dirs=None)

classmethod get_all_extracted_entries()

classmethod get_entry_to_link(package_ref)

classmethod tarball_file_in_cache(tarball_path, md5sum=None, exclude_caches=())

classmethod clear()

tarball_file_in_this_cache(tarball_path, md5sum=None)

_check_writable()

static _clean_tarball_path_and_get_md5sum(tarball_path, md5sum=None)

_scan_for_dist_no_channel(dist_str)

itervalues()

values()

___repr__()

Return repr(self).

_make_single_record(package_filename)

static _dedupe_pkgs_dir_contents(pkgs_dir_contents)

```
class UrlsData(pkgs_dir)
```

__contains__(url)

___iter__()

add_url(url)

get_url(package_path)

class ProgressiveFetchExtract(link_prefs)

```
property cache_actions
```

property extract_actions

```
static make_actions_for_record(pref_or_spec)
```

prepare()

execute()

Run each action in self.paired_actions. Each action in cache_actions runs before its corresponding extract_actions.

static _progress_bar(*prec_or_spec*, *position=None*, *leave=False*) \rightarrow *conda.common.io*.*ProgressBar*

__hash__()

Return hash(self).

```
__eq__(other)
```

Return self==value.

do_cache_action(*prec*, *cache_action*, *progress_bar*, *download_total=1.0*, *, *cancelled*) This function gets called from *ProgressiveFetchExtract.execute*.

```
do_extract_action(prec, extract_action, progress_bar)
```

This function gets called after do_cache_action completes.

do_cleanup(actions)

do_reverse(actions)

rm_fetched(dist)

Checks to see if the requested package is in the cache; and if so, it removes both the package itself and its extracted contents.

download(url, dst_path, session=None, md5sum=None, urlstxt=False, retries=3)

path_actions

Atomic actions that make up a package installation or removal transaction.

Classes

_Action	
PathAction	
MultiPathAction	
PrefixPathAction	
CreateInPrefixPathAction	
LinkPathAction	
PrefixReplaceLinkAction	
MakeMenuAction	
CreateNonadminAction	
CompileMultiPycAction	
AggregateCompileMultiPycAction	Bunch up all of our compile actions, so that they all get carried out at once.
CreatePythonEntryPointAction	
CreatePrefixRecordAction	
UpdateHistoryAction	
RegisterEnvironmentLocationAction	
RemoveFromPrefixPathAction	
UnlinkPathAction	
RemoveMenuAction	
RemoveLinkedPackageRecordAction	
UnregisterEnvironmentLocationAction	
CacheUrlAction	
ExtractPackageAction	

Attributes

FileNotFoundError

_MENU_RE

REPR_IGNORE_KWARGS

FileNotFoundError

_MENU_RE

```
REPR_IGNORE_KWARGS = ('transaction_context', 'package_info', 'hold_path')
```

class _Action

property verified

_verified = False

abstract verify()

abstract execute()

abstract reverse()

abstract cleanup()

__repr__()

Return repr(self).

class PathAction

Bases: _Action

abstract property target_full_path

class MultiPathAction

Bases: _Action

abstract property target_full_paths

class PrefixPathAction(transaction_context, target_prefix, target_short_path)

Bases: PathAction

property target_short_paths

property target_full_path

class CreateInPrefixPathAction(*transaction_context*, *package_info*, *source_prefix*, *source_short_path*, *target_prefix*, *target_short_path*)

Bases: PrefixPathAction

property source_full_path

verify()

```
cleanup()
class LinkPathAction(transaction_context, package_info, extracted_package_dir, source_short_path,
                        target_prefix, target_short_path, link_type, source_path_data)
     Bases: CreateInPrefixPathAction
     classmethod create_file_link_actions(transaction_context, package_info, target_prefix,
                                                 requested_link_type)
     classmethod create_directory_actions(transaction_context, package_info, target_prefix,
                                                 requested_link_type, file_link_actions)
     classmethod create_python_entry_point_windows_exe_action(transaction_context, package_info,
                                                                        target_prefix, requested_link_type,
                                                                        entry_point_def)
     verify()
     execute()
     reverse()
class PrefixReplaceLinkAction(transaction_context, package_info, extracted_package_dir,
                                   source_short_path, target_prefix, target_short_path, link_type,
                                   prefix_placeholder, file_mode, source_path_data)
     Bases: LinkPathAction
     verify()
     execute()
class MakeMenuAction(transaction_context, package_info, target_prefix, target_short_path)
     Bases: CreateInPrefixPathAction
     classmethod create_actions(transaction_context, package_info, target_prefix, requested_link_type)
     execute()
     reverse()
class CreateNonadminAction(transaction_context, package_info, target_prefix)
     Bases: CreateInPrefixPathAction
     classmethod create_actions(transaction_context, package_info, target_prefix, requested_link_type)
     execute()
     reverse()
class CompileMultiPycAction(transaction_context, package_info, target_prefix, source_short_paths,
                                target_short_paths)
     Bases: MultiPathAction
     property target_full_paths
     property source_full_paths
```

classmethod create_actions(*transaction_context*, *package_info*, *target_prefix*, *requested_link_type*, *file_link_actions*)

verify()

cleanup()

execute()

reverse()

class AggregateCompileMultiPycAction(*individuals, **kw)

Bases: CompileMultiPycAction

Bunch up all of our compile actions, so that they all get carried out at once. This avoids clobbering and is faster when we have several individual packages requiring compilation.

class CreatePythonEntryPointAction(*transaction_context*, *package_info*, *target_prefix*, *target_short_path*, *module*, *func*)

Bases: CreateInPrefixPathAction

classmethod create_actions(transaction_context, package_info, target_prefix, requested_link_type)

execute()

reverse()

class CreatePrefixRecordAction(*transaction_context*, *package_info*, *target_prefix*, *target_short_path*, *requested_link_type*, *requested_spec*, *all_link_path_actions*)

Bases: CreateInPrefixPathAction

classmethod create_actions(*transaction_context*, *package_info*, *target_prefix*, *requested_link_type*, *requested_spec*, *all_link_path_actions*)

execute()

reverse()

class UpdateHistoryAction(*transaction_context*, *target_prefix*, *target_short_path*, *remove_specs*, *update_specs*, *neutered_specs*)

Bases: CreateInPrefixPathAction

classmethod create_actions(*transaction_context*, *target_prefix*, *remove_specs*, *update_specs*, *neutered_specs*)

execute()

reverse()

cleanup()

class RegisterEnvironmentLocationAction(transaction_context, target_prefix)

Bases: PathAction

abstract property target_full_path

verify()

execute()

```
reverse()
```

cleanup()

```
class RemoveFromPrefixPathAction(transaction_context, linked_package_data, target_prefix, target_short_path)
```

Bases: PrefixPathAction

verify()

class UnlinkPathAction(*transaction_context*, *linked_package_data*, *target_prefix*, *target_short_path*, *link_type=LinkType.hardlink*)

Bases: RemoveFromPrefixPathAction

execute()

reverse()

cleanup()

class RemoveMenuAction(*transaction_context*, *linked_package_data*, *target_prefix*, *target_short_path*) Bases: RemoveFromPrefixPathAction

classmethod create_actions(transaction_context, linked_package_data, target_prefix)

execute()

reverse()

cleanup()

class RemoveLinkedPackageRecordAction(*transaction_context*, *linked_package_data*, *target_prefix*, *target_short_path*)

Bases: UnlinkPathAction

execute()

reverse()

class UnregisterEnvironmentLocationAction(transaction_context, target_prefix)

Bases: PathAction

abstract property target_full_path

verify()

execute()

reverse()

cleanup()

class CacheUrlAction(url, target_pkgs_dir, target_package_basename, sha256=None, size=None, md5=None)
Bases: PathAction

property target_full_path

verify()

execute(progress_update_callback=None)

_execute_local(*source_path*, *target_package_cache*, *progress_update_callback=None*)

_execute_channel(*target_package_cache*, *progress_update_callback=None*)

reverse()

cleanup()

__str__()

Return str(self).

class ExtractPackageAction(*source_full_path*, *target_pkgs_dir*, *target_extracted_dirname*, *record_or_spec*, *sha256*, *size*, *md5*)

Bases: PathAction

property target_full_path

verify()

execute(progress_update_callback=None)

reverse()

cleanup()

__str__()

Return str(self).

portability

Tools for cross-OS portability.

Functions

 $_subdir_is_win(\rightarrow bool)$ update_prefix(path, new_prefix[, placeholder, mode, ...]) *replace_prefix*(\rightarrow bytes) Replaces *placeholder* text with the *new_prefix* provided. The *mode* provided can $binary_replace(\rightarrow bytes)$ Perform a binary replacement of data, where the placeholder search is has_pyzzer_entry_point(data) replace_pyzzer_entry_point_shebang(all_data, Code adapted from pyzzer. This is meant to deal with entry point exe's created by distlib, ...) replace_long_shebang(mode, data) generate_shebang_for_entry_point(executable[, This function can be used to generate a shebang line for Python entry points. ...])

Attributes

SHEBANG_REGEX

MAX_SHEBANG_LENGTH

POPULAR_ENCODINGS

SHEBANG_REGEX = b'^(#!(?:[]*)(/(?:\\\\ |[^ \\n\\r\\t])*)(.*))\$'

MAX_SHEBANG_LENGTH

POPULAR_ENCODINGS = ('utf-8', 'utf-16-le', 'utf-16-be', 'utf-32-le', 'utf-32-be')

exception _PaddingError

Bases: Exception

Common base class for all non-exit exceptions.

_subdir_is_win(subdir: str) → bool

- replace_prefix(mode: conda.models.enums.FileMode, data: bytes, placeholder: str, new_prefix: str, subdir: str = 'noarch') \rightarrow bytes

Replaces *placeholder* text with the *new_prefix* provided. The *mode* provided can either be text or binary.

We use the *POPULAR_ENCODINGS* module level constant defined above to make several passes at replacing the placeholder. We do this to account for as many encodings as possible. If this causes any performance problems in the future, it could potentially be removed (i.e. just using the most popular "utf-8" encoding").

More information/discussion available here: https://github.com/conda/conda/pull/9946

binary_replace(*data: bytes, search: bytes, replacement: bytes, encoding: str* = '*utf-8*', *subdir: str* = '*noarch*') \rightarrow bytes

Perform a binary replacement of *data*, where the placeholder *search* is replaced with *replacement* and the remaining string is padded with null characters. All input arguments are expected to be bytes objects.

Parameters

- data -- The bytes object that will be searched and replaced
- search -- The bytes object to find
- replacement -- The bytes object that will replace search
- encoding (str) -- The encoding of the expected string in the binary.

has_pyzzer_entry_point(data)

replace_pyzzer_entry_point_shebang(all_data, placeholder, new_prefix)

Code adapted from pyzzer. This is meant to deal with entry point exe's created by distlib, which consist of a launcher, then a shebang, then a zip archive of the entry point code to run. We need to change the shebang. https://bitbucket.org/vinay.sajip/pyzzer/src/5d5740cb04308f067d5844a56fbe91e7a27efccc/pyzzer/___init__.py?at=default&fileviewer=file-view-default#__init__.py-112 # NOQA

replace_long_shebang(mode, data)

generate_shebang_for_entry_point(executable, with_usr_bin_env=False)

This function can be used to generate a shebang line for Python entry points.

Use cases: - At install/link time, to generate the *noarch: python* entry points. - conda init uses it to create its own entry point during conda-build

prefix_data

Tools for managing the packages installed within an environment.

Classes

PrefixDataTypeBasic caching of PrefixData instance objects.PrefixData

Functions

<pre>get_conda_anchor_files_and_records()</pre>	Return the anchor files for the conda records of python packages.
<pre>get_python_version_for_prefix(prefix)</pre>	
$delete_prefix_from_linked_data(\rightarrow bool)$	Here, path may be a complete prefix or a dist inside a prefix

class PrefixDataType

Bases: type

Basic caching of PrefixData instance objects.

```
__call__(prefix_path: str | os.PathLike | pathlib.Path, pip_interop_enabled: bool | None = None)
Call self as a function.
```

class PrefixData(prefix_path: pathlib.Path, pip_interop_enabled: bool | None = None)

```
property _prefix_records
```

property is_writable

property _python_pkg_record

Return the prefix record for the package python.

cache: dict[pathlib.Path, PrefixData]

load()

reload()

_get_json_fn(prefix_record)

insert(prefix_record)

remove(package_name)

get(package_name, default=NULL)

iter_records()

iter_records_sorted()

all_subdir_urls()

query(package_ref_or_match_spec)

_load_single_record(prefix_record_json_path)

_has_python()

_load_site_packages()

Load non-conda-installed python packages in the site-packages of the prefix.

Python packages not handled by conda are installed via other means, like using pip or using python setup.py develop for local development.

Packages found that are not handled by conda are converted into a prefix record and handled in memory.

Packages clobbering conda packages (i.e. the conda-meta record) are removed from the in memory representation.

_get_environment_state_file()

_write_environment_state_file(state)

get_environment_env_vars()

set_environment_env_vars(env_vars)

unset_environment_env_vars(env_vars)

get_conda_anchor_files_and_records(*site_packages_short_path*, *python_records*) Return the anchor files for the conda records of python packages.

get_python_version_for_prefix(prefix)

delete_prefix_from_linked_data(*path: str* | *os.PathLike* | *pathlib.Path*) \rightarrow bool Here, path may be a complete prefix or a dist inside a prefix

solve

The classic solver implementation.

Classes

Solver	A high-level API to conda's solving logic. Three public methods are provided to access a
SolverStateContainer	
Functions	
<pre>get_pinned_specs(prefix)</pre>	Find pinned specs from file and return a tuple of Match- Spec.

diff_for_unlink_link_precs([force_reinstall])

class Solver(prefix: str, channels: Iterable[conda.models.channel.Channel], subdirs: Iterable[str] = (), specs_to_add: Iterable[conda.models.match_spec.MatchSpec] = (), specs_to_remove: Iterable[conda.models.match_spec.MatchSpec] = (), repodata_fn: str = REPODATA_FN, command=NULL)

A high-level API to conda's solving logic. Three public methods are provided to access a solution in various forms.

- solve_final_state()
- solve_for_diff()
- solve_for_transaction()

Gives an UnlinkLinkTransaction instance that can be used to execute the solution on an environment.

Parameters

- **deps_modifier** (DepsModifier) -- See solve_final_state().
- prune (bool) -- See solve_final_state().
- **ignore_pinned** (bool) -- See solve_final_state().
- force_remove(bool) -- See solve_final_state().
- force_reinstall (bool) -- See solve_for_diff().
- should_retry_solve(bool) -- See solve_final_state().

Return type

UnlinkLinkTransaction

Gives the package references to remove from an environment, followed by the package references to add to an environment.

Parameters

- deps_modifier (DepsModifier) -- See solve_final_state().
- prune (bool) -- See solve_final_state().
- **ignore_pinned** (bool) -- See solve_final_state().
- force_remove(bool) -- See solve_final_state().
- force_reinstall (bool) --

For requested specs_to_add that are already satisfied in the environment,

instructs the solver to remove the package and spec from the environment, and then add it back--possibly with the exact package instance modified, depending on the spec exactness.

• should_retry_solve(bool) -- See solve_final_state().

Returns

A two-tuple of PackageRef sequences. The first is the group of packages to remove from the environment, in sorted dependency order from leaves to roots. The second is the group of packages to add to the environment, in sorted dependency order from roots to leaves.

Return type

tuple[PackageRef], tuple[PackageRef]

```
solve_final_state(update_modifier=NULL, deps_modifier=NULL, prune=NULL, ignore_pinned=NULL,
force_remove=NULL, should_retry_solve=False)
```

Gives the final, solved state of the environment.

Parameters

- **update_modifier** (UpdateModifier) -- An optional flag directing how updates are handled regarding packages already existing in the environment.
- **deps_modifier** (DepsModifier) -- An optional flag indicating special solver handling for dependencies. The default solver behavior is to be as conservative as possible with dependency updates (in the case the dependency already exists in the environment), while still ensuring all dependencies are satisfied. Options include * NO_DEPS * ONLY_DEPS * UPDATE_DEPS * UPDATE_DEPS_ONLY_DEPS * FREEZE_INSTALLED
- **prune** (*bool*) -- If **True**, the solution will not contain packages that were previously brought into the environment as dependencies but are no longer required as dependencies and are not user-requested.
- **ignore_pinned** (*bool*) -- If **True**, the solution will ignore pinned package configuration for the prefix.
- **force_remove** (*bool*) -- Forces removal of a package without removing packages that depend on it.
- **should_retry_solve** (*bool*) -- Indicates whether this solve will be retried. This allows us to control whether to call find_conflicts (slow) in ssc.r.solve

Returns

In sorted dependency order from roots to leaves, the package references for the solved state of the environment.

Return type

tuple[PackageRef]

determine_constricting_specs(spec, solution_precs)

get_request_package_in_solution(solution_precs, specs_map)

get_constrained_packages(pre_packages, post_packages, index_keys)

_collect_all_metadata(ssc)

_remove_specs(ssc)

_find_inconsistent_packages(ssc)

_package_has_updates(ssc, spec, installed_pool)

_should_freeze(ssc, target_prec, conflict_specs, explicit_pool, installed_pool)

_add_specs(ssc)

_run_sat(ssc)

_post_sat_handling(ssc)

_notify_conda_outdated(link_precs)

_prepare(prepared_specs)

class SolverStateContainer(*prefix*, *update_modifier*, *deps_modifier*, *prune*, *ignore_pinned*, *force_remove*, *should_retry_solve*)

prefix_data()

specs_from_history_map()

track_features_specs()

pinned_specs()

set_repository_metadata(index, r)

_init_solution_precs()

working_state_reset()

get_pinned_specs(prefix)

Find pinned specs from file and return a tuple of MatchSpec.

diff_for_unlink_link_precs(*prefix, final_precs, specs_to_add=(), force_reinstall=NULL*) → tuple[tuple[conda.models.records.PackageRecord, Ellipsis], tuple[conda.models.records.PackageRecord, Ellipsis]]

subdir_data

Tools for managing a subdir's repodata.json.

Classes

SubdirDataType

PackageRecordList SubdirData Lazily convert dicts to PackageRecord.

Functions

get_cache_control_max_age(→ int)

make_feature_record(feature_name)

Attributes

REPODATA_PICKLE_VERSION

MAX_REPODATA_VERSION

REPODATA_HEADER_RE

REPODATA_PICKLE_VERSION = 30

MAX_REPODATA_VERSION = 2

```
REPODATA_HEADER_RE = b'"(_etag|_mod|_cache_control)":[ ]?"(.*?[^\\\\])"[,}\\s]'
```

class SubdirDataType

Bases: type

__call__(channel, repodata_fn=REPODATA_FN)

Call self as a function.

class PackageRecordList(initlist=None)

Bases: collections.UserList

Lazily convert dicts to PackageRecord.

__getitem__(i)

class SubdirData(channel, repodata_fn=REPODATA_FN, RepoInterface=CondaRepoInterface)

property _repo: conda.gateways.repodata.RepoInterface

Changes as we mutate self.repodata_fn.

property repo_cache: conda.gateways.repodata.RepodataCache

property repo_fetch: conda.gateways.repodata.RepodataFetch Object to get repodata. Not cached since self.repodata_fn is mutable.

Replaces self._repo & self.repo_cache.

property cache_path_base

property url_w_repodata_fn

property cache_path_json

property cache_path_state

Out-of-band etag and other state needed by the RepoInterface.

property cache_path_pickle

cache

classmethod clear_cached_local_channel_data(exclude_file=True)

query(package_ref_or_match_spec)

reload()

load()

iter_records()

```
_iter_records_by_name(name)
```

_load()

Try to load repodata. If e.g. we are downloading *current_repodata.json*, fall back to *repodata.json* when the former is unavailable.

_pickle_me()

_read_local_repodata(state: conda.gateways.repodata.RepodataState)

_pickle_valid_checks(pickled_state, mod, etag)

Throw away the pickle if these don't all match.

_read_pickled(state: conda.gateways.repodata.RepodataState)

_process_raw_repodata_str(*raw_repodata_str*, *state*: conda.gateways.repodata.RepodataState | *None* = *None*)

State contains information that was previously in-band in raw_repodata_str.

_process_raw_repodata(repodata: dict, state: conda.gateways.repodata.RepodataState | None = None)

_get_base_url(*repodata: dict, with_credentials: bool* = True) \rightarrow str

In repodata_version=1, .tar.bz2 and .conda artifacts are assumed to be colocated next to repodata.json, in the same server and directory.

In repodata_version=2, repodata.json files can define a 'base_url' field to override that default assumption. See CEP-15 for more details.

This method deals with both cases and returns the appropriate value.

make_feature_record(feature_name)

deprecations

Tools to aid in deprecating code.

Classes

DeprecationHandler

Attributes

Т

deprecated

Т

exception DeprecatedError

Bases: RuntimeError

Unspecified run-time error.

class DeprecationHandler(version: str)

_version: str | None

_version_tuple: tuple[int, Ellipsis] | None

_version_object: packaging.version.Version | None

static _get_version_tuple(*version: str*) \rightarrow tuple[int, Ellipsis] | None Return version as non-empty tuple of ints if possible, else None.

Parameters

version -- Version string to parse.

_version_less_than(*version: str*) \rightarrow bool

Test whether own version is less than the given version.

Parameters

version -- Version string to compare against.

__call__(*deprecate_in: str, remove_in: str, *, addendum: str* | *None* = *None, stack: int* = 0) \rightarrow Callable[[Callable[P, T]], Callable[P, T]]

Deprecation decorator for functions, methods, & classes.

Parameters

• deprecate_in -- Version in which code will be marked as deprecated.

- **remove_in** -- Version in which code is expected to be removed.
- addendum -- Optional additional messaging. Useful to indicate what to do instead.
- **stack** -- Optional stacklevel increment.

 $argument(deprecate_in: str, remove_in: str, argument: str, *, rename: str | None = None, addendum: str | None = None, stack: int = 0) \rightarrow Callable[[Callable[P, T]], Callable[P, T]]$

Deprecation decorator for keyword arguments.

Parameters

- deprecate_in -- Version in which code will be marked as deprecated.
- **remove_in** -- Version in which code is expected to be removed.
- **argument** -- The argument to deprecate.
- **rename** -- Optional new argument name.
- addendum -- Optional additional messaging. Useful to indicate what to do instead.
- **stack** -- Optional stacklevel increment.
- **action**(*deprecate_in: str, remove_in: str, action: ActionType, *, addendum: str* | *None* = *None, stack: int* = 0) \rightarrow ActionType

Wraps any argparse. Action to issue a deprecation warning.

module(*deprecate_in: str, remove_in: str, *, addendum: str* | *None* = *None, stack: int* = 0) \rightarrow None Deprecation function for modules.

Parameters

- deprecate_in -- Version in which code will be marked as deprecated.
- **remove_in** -- Version in which code is expected to be removed.
- addendum -- Optional additional messaging. Useful to indicate what to do instead.
- **stack** -- Optional stacklevel increment.
- **constant**(*deprecate_in: str, remove_in: str, constant: str, value: Any, *, addendum: str* | *None* = *None*, *stack: int* = 0) \rightarrow None

Deprecation function for module constant/global.

- Parameters
 - **deprecate_in** -- Version in which code will be marked as deprecated.
 - **remove_in** -- Version in which code is expected to be removed.
 - constant
 - value
 - addendum -- Optional additional messaging. Useful to indicate what to do instead.
 - **stack** -- Optional stacklevel increment.

topic(*deprecate_in: str, remove_in: str, *, topic: str, addendum: str* | *None* = *None, stack: int* = 0) \rightarrow None Deprecation function for a topic.

Parameters

- deprecate_in -- Version in which code will be marked as deprecated.
- **remove_in** -- Version in which code is expected to be removed.

- **topic** -- The topic being deprecated.
- addendum -- Optional additional messaging. Useful to indicate what to do instead.
- **stack** -- Optional stacklevel increment.

_get_module(*stack: int*) → tuple[types.ModuleType, str]

Detect the module from which we are being called.

Parameters

stack -- The stacklevel increment.

Returns

The module and module name.

```
_generate_message(deprecate_in: str, remove_in: str, prefix: str, addendum: str | None, *,
```

deprecation_type: type[Warning] = *DeprecationWarning*) → tuple[type[Warning] | None, str]

Generate the standardized deprecation message and determine whether the deprecation is pending, active, or past.

Parameters

- deprecate_in -- Version in which code will be marked as deprecated.
- remove_in -- Version in which code is expected to be removed.
- **prefix** -- The message prefix, usually the function name.
- addendum -- Additional messaging. Useful to indicate what to do instead.
- **deprecation_type** -- The warning type to use for active deprecations.

Returns

The warning category (if applicable) and the message.

deprecated

env

env

Environment object describing the conda environment.yaml file.

Classes

Dependencies	A dict subclass that parses the raw dependencies into a conda and pip list
Environment	A class representing an environment.yaml file

Functions

validate_keys(data, kwargs)	Check for unknown keys, remove them and print a warn- ing
<pre>from_environment(name, prefix[, no_builds,])</pre>	Get Environment object from prefix
<pre>from_yaml(yamlstr, **kwargs)</pre>	Load and return a Environment from a given yaml string
_expand_channels(data)	Expands Environment variables for the channels found in the yaml data
<pre>from_file(filename)</pre>	Load and return an Environment from a given file
<pre>get_filename(filename)</pre>	Expand filename if local path or return the url
<pre>print_result(args, prefix, result)</pre>	Print the result of an install operation

Attributes

VALID_KEYS

VALID_KEYS = ('name', 'dependencies', 'prefix', 'channels', 'variables')

validate_keys(data, kwargs)

Check for unknown keys, remove them and print a warning

from_environment(*name*, *prefix*, *no_builds=False*, *ignore_channels=False*, *from_history=False*)

Get Environment object from prefix

Parameters

- name -- The name of environment
- prefix -- The path of prefix
- no_builds -- Whether has build requirement
- ignore_channels -- whether ignore_channels
- from_history -- Whether environment file should be based on explicit specs in history

Returns: Environment object

from_yaml(yamlstr, **kwargs)

Load and return a ${\tt Environment}$ from a given yaml string

_expand_channels(data)

Expands Environment variables for the channels found in the yaml data

from_file(filename)

Load and return an Environment from a given file

class Dependencies(raw, *args, **kwargs)

Bases: dict

A dict subclass that parses the raw dependencies into a conda and pip list
parse()

Parse the raw dependencies into a conda and pip list

add(package_name)

Add a package to the Environment

A class representing an environment.yaml file

```
add_channels(channels)
```

Add channels to the Environment

remove_channels()

Remove all channels from the Environment

to_dict(stream=None)

Convert information related to the Environment into a dictionary

to_yaml(stream=None)

Convert information related to the Environment into a yaml string

save()

Save the Environment data to a yaml file

get_filename(filename)

Expand filename if local path or return the url

print_result(args, prefix, result)

Print the result of an install operation

installers

base

Dynamic installer loading.

Functions

get_installer(name)

Gets the installer for the given environment.

get_installer(name)

Gets the installer for the given environment. Raises: InvalidInstaller if unable to load installer

conda

Conda-flavored installer.

Functions

_ <i>solve</i> (prefix, specs, args, env, *_, **kwargs)	Solve the environment
<i>dry_run</i> (specs, args, env, *_, **kwargs)	Do a dry run of the environment solve
<pre>install(prefix, specs, args, env, *_, **kwargs)</pre>	Install packages into an environment

solve(prefix, specs, args, env, *, **kwargs) Solve the environment

dry_run(specs, args, env, *_, **kwargs)
Do a dry run of the environment solve

install(prefix, specs, args, env, *_, **kwargs)
Install packages into an environment

pip

Pip-flavored installer.

Functions

```
_pip_install_via_requirements(prefix, specs, Installs the pip dependencies in specs using a temporary pip requirements file.
install(*args, **kwargs)
```

_pip_install_via_requirements(prefix, specs, args, *_, **kwargs)

Installs the pip dependencies in specs using a temporary pip requirements file.

Parameters

- **prefix** (*string*) -- The path to the python and pip executables.
- **specs** (*iterable of strings*) -- Each element should be a valid pip dependency. See: https://pip.pypa.io/en/stable/user_guide/#requirements-files

https://pip.pypa.io/en/stable/reference/pip_install/#requirements-file-format

install(*args, **kwargs)

pip_util

Functions related to core conda functionality that relates to pip

NOTE: This modules used to in conda, as conda/pip.py

Functions

<pre>pip_subprocess(args, prefix, cwd)</pre>	Run pip in a subprocess
<pre>get_pip_installed_packages(stdout)</pre>	Return the list of pip packages installed based on the
	command output

pip_subprocess(args, prefix, cwd)

Run pip in a subprocess

get_pip_installed_packages(stdout)

Return the list of pip packages installed based on the command output

specs

binstar

Define binstar spec.

Classes

BinstarSpec

spec = BinstarSpec('darth/deathstar')

Attributes

ENVIRONMENT_TYPE

ENVIRONMENT_TYPE = 'env'

class BinstarSpec(name=None)

spec = BinstarSpec('darth/deathstar') spec.can_handle() # => True / False spec.environment # => YAML string
spec.msg # => Error messages :raises: EnvironmentFileNotDownloaded

msg

 $can_handle() \rightarrow bool$

Validates loader can process environment definition. :return: True or False

 $valid_name() \rightarrow bool$

Validates name :return: True or False

 $valid_package() \rightarrow bool$

Returns True if package has an environment file :return: True or False

binstar() \rightarrow types.ModuleType

 $\texttt{file_data()} \rightarrow list[dict[str, str]]$

environment() \rightarrow *conda.env.env.Environment*

package()

 $username() \rightarrow str$

 $packagename() \rightarrow str$

requirements

Define requirements.txt spec.

Classes

RequirementsSpec	Reads dependencies from a requirements txt file
neguriemenesspee	Reduces dependencies from a requirements.the me

class RequirementsSpec(filename=None, name=None, **kwargs)

Reads dependencies from a requirements.txt file and returns an Environment object from it.

property environment

msg

extensions

_valid_file()

_valid_name()

can_handle()

yaml_file

Define YAML spec.

Classes

YamlFileSpec

class YamlFileSpec(filename=None, **kwargs)

property environment

_environment

extensions

can_handle()

Classes

BinstarSpec	<pre>spec = BinstarSpec('darth/deathstar')</pre>
RequirementsSpec	Reads dependencies from a requirements.txt file
YamlFileSpec	

Functions

$get_spec_class_from_file(\rightarrow FileSpecTypes)$	Determine spec class to use from the provided filename
$detect (\rightarrow SpecTypes)$	Return the appropriate spec type to use.

Attributes

CONDA_SESSION_SCHEMES
FileSpecTypes
SpecTypes
exception invironmentfileExtensionNotValla(<i>liename</i> , *args, **kwargs)
Bases: CondaEnvException
Common base class for all non-exit exceptions.
<pre>exception EnvironmentFileNotFound(filename, *args, **kwargs)</pre>

Bases: CondaEnvException

Common base class for all non-exit exceptions.

exception SpecNotFound(msg, *args, **kwargs)

Bases: conda.CondaError

Common base class for all non-exit exceptions.

CONDA_SESSION_SCHEMES

class BinstarSpec(name=None)

spec = BinstarSpec('darth/deathstar') spec.can_handle() # => True / False spec.environment # => YAML string
spec.msg # => Error messages :raises: EnvironmentFileNotDownloaded

msg

```
can_handle() \rightarrow bool
```

Validates loader can process environment definition. :return: True or False

 $valid_name() \rightarrow bool$

Validates name :return: True or False

 $valid_package() \rightarrow bool$

Returns True if package has an environment file :return: True or False

binstar() \rightarrow types.ModuleType

file_data() \rightarrow list[dict[str, str]]

 $environment() \rightarrow conda.env.env.Environment$

package()

 $username() \rightarrow str$

 $packagename() \rightarrow str$

```
class RequirementsSpec(filename=None, name=None, **kwargs)
```

Reads dependencies from a requirements.txt file and returns an Environment object from it.

property environment

msg

extensions

_valid_file()

_valid_name()

can_handle()

class YamlFileSpec(filename=None, **kwargs)

property environment

_environment

extensions

can_handle()

FileSpecTypes

 $\texttt{get_spec_class_from_file}(\mathit{filename: str}) \rightarrow \texttt{FileSpecTypes}$

Determine spec class to use from the provided filename

Raises

EnvironmentFileExtensionNotValid | EnvironmentFileNotFound --

SpecTypes

detect(*name:* str = None, filename: str = None, directory: str = None, remote_definition: str = None) \rightarrow SpecTypes

Return the appropriate spec type to use.

Raises

- SpecNotFound -- Raised if no suitable spec class could be found given the input
- EnvironmentFileExtensionNotValid | EnvironmentFileNotFound --

exception_handler

Error handling and error reporting.

Classes

ExceptionHandler

Functions

conda_exception_handler(func, *args, **kwargs)

class ExceptionHandler

property http_timeout

property user_agent

property error_upload_url

property _isatty

__call__(func, *args, **kwargs)

write_out(*content)

handle_exception(exc_val, exc_tb)

handle_application_exception(exc_val, exc_tb)

_print_conda_exception(exc_val, exc_tb)

handle_unexpected_exception(exc_val, exc_tb)

handle_reportable_application_exception(exc_val, exc_tb)

get_error_report(exc_val, exc_tb)

print_unexpected_error_report(error_report)

print_expected_error_report(error_report)

_upload(*error_report*) \rightarrow None

Determine whether or not to upload the error report.

_ask_upload()

_execute_upload(error_report)

_post_upload(do_upload)

conda_exception_handler(func, *args, **kwargs)

exceptions

Conda exceptions.

Functions

maybe_raise(error, context)

print_conda_exception(exc_val[, exc_tb])

_format_exc([exc_val, exc_tb])

exception ResolvePackageNotFound(bad_deps)

Bases: conda.CondaError

Common base class for all non-exit exceptions.

exception LockError(message)

Bases: conda.CondaError

Common base class for all non-exit exceptions.

exception ArgumentError(message, **kwargs)

Bases: conda.CondaError

Common base class for all non-exit exceptions.

return_code = 2

exception Help(message, caused_by=None, **kwargs)

Bases: conda.CondaError

Common base class for all non-exit exceptions.

exception ActivateHelp

Bases: *Help*

exception DeactivateHelp

Bases: *Help*

Common base class for all non-exit exceptions.

exception GenericHelp(command)

Bases: Help

Common base class for all non-exit exceptions.

exception CondaSignalInterrupt(signum)

Bases: conda.CondaError

Common base class for all non-exit exceptions.

exception TooManyArgumentsError(*expected*, *received*, *offending_arguments*, *optional_message=''*, *args)

Bases: ArgumentError

Common base class for all non-exit exceptions.

exception ClobberError(message, path_conflict, **kwargs)

Bases: conda.CondaError

Common base class for all non-exit exceptions.

__repr__()

Return repr(self).

exception BasicClobberError(source_path, target_path, context)

Bases: ClobberError

Common base class for all non-exit exceptions.

exception KnownPackageClobberError(target_path, colliding_dist_being_linked, colliding_linked_dist,

context)

Bases: ClobberError

Common base class for all non-exit exceptions.

exception UnknownPackageClobberError(target_path, colliding_dist_being_linked, context)

Bases: ClobberError

Common base class for all non-exit exceptions.

exception SharedLinkPathClobberError(*target_path*, *incompatible_package_dists*, *context*)

Bases: ClobberError

Common base class for all non-exit exceptions.

exception CommandNotFoundError(command)

Bases: conda.CondaError

Common base class for all non-exit exceptions.

exception PathNotFoundError(path)

Bases: conda.CondaError, OSError

Common base class for all non-exit exceptions.

exception DirectoryNotFoundError(path)

Bases: conda.CondaError

exception EnvironmentLocationNotFound(location)

Bases: conda.CondaError

Common base class for all non-exit exceptions.

exception EnvironmentNameNotFound(environment_name)

Bases: conda.CondaError

Common base class for all non-exit exceptions.

exception NoBaseEnvironmentError

Bases: conda.CondaError

Common base class for all non-exit exceptions.

exception DirectoryNotACondaEnvironmentError(target_directory)

Bases: conda.CondaError

Common base class for all non-exit exceptions.

exception CondaEnvironmentError(message, *args)

Bases: conda.CondaError, OSError

Common base class for all non-exit exceptions.

exception DryRunExit

Bases: conda.CondaExitZero

Common base class for all non-exit exceptions.

exception CondaSystemExit(*args)

Bases: conda.CondaExitZero, SystemExit

Common base class for all non-exit exceptions.

exception PaddingError(dist, placeholder, placeholder_length)

Bases: conda.CondaError

Common base class for all non-exit exceptions.

exception LinkError(message)

Bases: conda.CondaError

Common base class for all non-exit exceptions.

exception CondaOSError(message, **kwargs)

Bases: conda.CondaError, OSError

Common base class for all non-exit exceptions.

exception ProxyError

Bases: conda.CondaError

Common base class for all non-exit exceptions.

exception CondaIOError(message, *args)

Bases: conda.CondaError, OSError

exception CondaFileIOError(filepath, message, *args)

Bases: CondaIOError

Common base class for all non-exit exceptions.

exception CondaKeyError(key, message, *args)

Bases: conda.CondaError, KeyError

Common base class for all non-exit exceptions.

exception ChannelError(message, caused_by=None, **kwargs)

Bases: conda.CondaError

Common base class for all non-exit exceptions.

exception ChannelNotAllowed(channel)

Bases: ChannelError

Common base class for all non-exit exceptions.

Bases: ChannelError

Common base class for all non-exit exceptions.

status_code: str | int

exception OperationNotAllowed(message)

Bases: conda.CondaError

Common base class for all non-exit exceptions.

exception CondaImportError(message)

Bases: conda.CondaError, ImportError

Common base class for all non-exit exceptions.

exception ParseError(message)

Bases: conda.CondaError

Common base class for all non-exit exceptions.

exception CouldntParseError(reason)

Bases: ParseError

Common base class for all non-exit exceptions.

Bases: conda.CondaError

Common base class for all non-exit exceptions.

exception PackageNotInstalledError(prefix, package_name)

Bases: conda.CondaError

exception CondaHTTPError(*message*, *url*, *status_code*, *reason*, *elapsed_time*, *response=None*, *caused_by=None*)

Bases: conda.CondaError

Common base class for all non-exit exceptions.

exception CondaSSLError(message, caused_by=None, **kwargs)

Bases: conda.CondaError

Common base class for all non-exit exceptions.

exception AuthenticationError(message, caused_by=None, **kwargs)

Bases: conda.CondaError

Common base class for all non-exit exceptions.

exception PackagesNotFoundError(packages, channel_urls=())

Bases: conda.CondaError

Common base class for all non-exit exceptions.

exception UnsatisfiableError(bad_deps, chains=True, strict=False)

Bases: conda.CondaError

An exception to report unsatisfiable dependencies.

Parameters

- **bad_deps** -- a list of tuples of objects (likely MatchSpecs).
- **chains** -- (optional) if True, the tuples are interpreted as chains of dependencies, from top level to bottom. If False, the tuples are interpreted as simple lists of conflicting specs.

Returns

Raises an exception with a formatted message detailing the unsatisfiable specifications.

_format_chain_str(bad_deps)

exception RemoveError(message)

Bases: conda.CondaError

Common base class for all non-exit exceptions.

exception DisallowedPackageError(package_ref, **kwargs)

Bases: conda.CondaError

Common base class for all non-exit exceptions.

exception SpecsConfigurationConflictError(requested_specs, pinned_specs, prefix)

Bases: conda.CondaError

Common base class for all non-exit exceptions.

exception CondaIndexError(message)

Bases: conda.CondaError, IndexError

Common base class for all non-exit exceptions.

exception CondaValueError(message, *args, **kwargs)

Bases: conda.CondaError, ValueError

```
exception CyclicalDependencyError(packages_with_cycles, **kwargs)
     Bases: conda.CondaError, ValueError
     Common base class for all non-exit exceptions.
exception CorruptedEnvironmentError(environment location, corrupted file, **kwargs)
     Bases: conda.CondaError
     Common base class for all non-exit exceptions.
exception CondaHistoryError(message)
     Bases: conda.CondaError
     Common base class for all non-exit exceptions.
exception CondaUpgradeError(message)
     Bases: conda.CondaError
     Common base class for all non-exit exceptions.
exception CondaVerificationError(message)
     Bases: conda.CondaError
     Common base class for all non-exit exceptions.
exception SafetyError(message)
     Bases: conda.CondaError
     Common base class for all non-exit exceptions.
exception CondaMemoryError(caused_by, **kwargs)
     Bases: conda.CondaError, MemoryError
     Common base class for all non-exit exceptions.
exception NotWritableError(path, errno, **kwargs)
     Bases: conda.CondaError, OSError
     Common base class for all non-exit exceptions.
exception NoWritableEnvsDirError(envs_dirs, **kwargs)
     Bases: conda.CondaError
     Common base class for all non-exit exceptions.
exception NoWritablePkgsDirError(pkgs_dirs, **kwargs)
     Bases: conda.CondaError
     Common base class for all non-exit exceptions.
exception EnvironmentNotWritableError(environment_location, **kwargs)
     Bases: conda.CondaError
     Common base class for all non-exit exceptions.
exception CondaDependencyError(message)
     Bases: conda.CondaError
```

exception BinaryPrefixReplacementError (<i>path</i> , <i>placeholder</i> , <i>new_prefix</i> , <i>original_data_length</i> , <i>new_data_length</i>)
Bases: conda.CondaError
Common base class for all non-exit exceptions.
<pre>exception InvalidSpec(message: str, **kwargs)</pre>
Bases: conda.CondaError, ValueError
Common base class for all non-exit exceptions.
<pre>exception InvalidVersionSpec(invalid_spec: str, details: str)</pre>
Bases: InvalidSpec
Common base class for all non-exit exceptions.
<pre>exception InvalidMatchSpec(invalid_spec: str, details: str)</pre>
Bases: InvalidSpec
Common base class for all non-exit exceptions.
<pre>exception EncodingError(caused_by, **kwargs)</pre>
Bases: conda.CondaError
Common base class for all non-exit exceptions.
<pre>exception NoSpaceLeftError(caused_by, **kwargs)</pre>
Bases: conda.CondaError
Common base class for all non-exit exceptions.
<pre>exception CondaEnvException(message, *args, **kwargs)</pre>
Bases: conda.CondaError
Common base class for all non-exit exceptions.
<pre>exception EnvironmentFileNotFound(filename, *args, **kwargs)</pre>
Bases: CondaEnvException
Common base class for all non-exit exceptions.
exception EnvironmentFileExtensionNotValid(filename, *args, **kwargs)
Bases: Condenvexception
Common base class for all non-exit exceptions.
exception EnvironmentFileEmpty(filename, *args, **kwargs) ResearcondEnvException
exception EnvironmentFileNotDownloaded (username, packagename, *args, **kwargs) Bases: conda CondaError
Common haso close for all non-avit executions
overantian SpacNatFound(mag. *area. **hugerer)
Bases: conda. CondaError
Common base class for all non-exit exceptions.

exception PluginError(message, caused_by=None, **kwargs)

Bases: conda.CondaError

Common base class for all non-exit exceptions.

maybe_raise(error, context)

print_conda_exception(exc_val, exc_tb=None)

_format_exc(exc_val=None, exc_tb=None)

exception InvalidInstaller(name)

Bases: Exception

Common base class for all non-exit exceptions.

exports

Backported exports for conda-build.

Classes

Completer

InstalledPackages

Functions

<pre>iteritems(d, **kw)</pre>		
<pre>rm_rf(path[, max_retries, trash])</pre>		
hash_file(_)		
verify(_)		
<i>display_actions</i> (actions, show_channel_urls,])	index[,	
<pre>get_index([channel_urls, prepend, platform,</pre>	.])	
<pre>fetch_index(channel_urls[, use_cache, index]</pre>)	
package_cache()		
<pre>symlink_conda(prefix, root_dir[, shell])</pre>		
_ <i>symlink_conda_hlp</i> (prefix, root_dir, where link_fn)	e, sym-	
<pre>win_conda_bat_redirect(src, dst, shell)</pre>		Special function for Windows XP where the <i>CreateSymbolicLink</i>
<pre>linked_data(prefix[, ignore_channels])</pre>		Return a dictionary of the linked packages in prefix.
<pre>linked(prefix[, ignore_channels])</pre>		Return the Dists of linked packages in prefix.
is_linked(prefix, dist)		Return the install metadata for a linked package in a pre- fix, or None
download(url, dst_path[, session, md5sum, urls	txt,])	

Attributes

<pre>non_x86_linux_machines</pre>
get_default_urls
arch_name
binstar_upload
bits
default_prefix
default_python
envs_dirs
pkgs_dirs
platform
root_dir
root_writable
subdir
conda_build
get_rc_urls
get_local_urls
load_condarc
PaddingError
LinkError
CondaOSError
CondaFileNotFoundError
РҮЗ
string_types
text_type
KEYS
KEYS_DIR

non_x86_linux_machines

get_default_urls

arch_name

binstar_upload

bits

default_prefix

default_python

envs_dirs

pkgs_dirs

platform

root_dir

root_writable

subdir

conda_build

get_rc_urls

get_local_urls

load_condarc

PaddingError

LinkError

CondaOSError

CondaFileNotFoundError

PY3 = True

string_types

text_type

iteritems(d, **kw)

class Completer

get_items()

__contains__(item)

__iter__()

class InstalledPackages

```
rm_rf(path, max_retries=5, trash=True)
```

KEYS

KEYS_DIR

hash_file(_)

verify(_)

display_actions(*actions*, *index*, *show_channel_urls=None*, *specs_to_remove=()*, *specs_to_add=()*)

fetch_index(channel_urls, use_cache=False, index=None)

package_cache()

symlink_conda(prefix, root_dir, shell=None)

_symlink_conda_hlp(prefix, root_dir, where, symlink_fn)

win_conda_bat_redirect(src, dst, shell)

Special function for Windows XP where the CreateSymbolicLink function is not available.

Simply creates a .bat file at dst which calls src together with all command line arguments.

Works of course only with callable files, e.g. .bat or .exe files.

linked_data(prefix, ignore_channels=False)

Return a dictionary of the linked packages in prefix.

linked(*prefix*, *ignore_channels=False*)

Return the Dists of linked packages in prefix.

is_linked(prefix, dist)

Return the install metadata for a linked package in a prefix, or None if the package is not linked in the prefix.

download(url, dst_path, session=None, md5sum=None, urlstxt=False, retries=3, sha256=None, size=None)

gateways

Gateways isolate interaction of conda code with the outside world. Disk manipulation, database interaction, and remote requests should all be through various gateways. Functions and methods in conda.gateways must use conda.models for arguments and return values.

Conda modules importable from conda.gateways are

- conda._vendor
- conda.common
- conda.models
- conda.gateways

Conda modules off limits for import within conda.gateways are

- conda.api
- conda.cli
- conda.client

• conda.core

Conda modules strictly prohibited from importing conda.gateways are

- conda.api
- conda.cli
- conda.client

anaconda_client

Anaconda-client (binstar) token management for CondaSession.

Classes

EnvAppDirs

Functions

replace_first_api_with_conda(url)

_get_binstar_token_directory()

read_binstar_tokens()

set_binstar_token(url, token)

remove_binstar_token(url)

replace_first_api_with_conda(url)

class EnvAppDirs(appname, appauthor, root_path)

property user_data_dir

property site_data_dir

property user_cache_dir

property user_log_dir

```
_get_binstar_token_directory()
```

read_binstar_tokens()

set_binstar_token(url, token)

```
remove_binstar_token(url)
```

connection

adapters

ftp

Defines FTP transport adapter for CondaSession (requests.Session).

Taken from requests-ftp (https://github.com/Lukasa/requests-ftp/blob/master/requests_ftp/ftp.py).

Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except in compliance with the License. You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software distributed under the License is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the License for the specific language governing permissions and limitations under the License.

Classes

FTPAdapter	A Requests Transport Adapter that handles FTP urls
I II Adaptei	A Requests transport Adapter that handles I'll uns.

Functions

_new_makepasv(self)	
<pre>data_callback_factory(variable)</pre>	Returns a callback suitable for use by the FTP library. This callback
<pre>build_text_response(request, data, code)</pre>	Build a response for textual data.
build_binary_response(request, data, code)	Build a response for data whose encoding is unknown.
<i>build_response</i> (request, data, code, encoding)	Builds a response object from the data returned by ftplib, using the
<pre>parse_multipart_files(request)</pre>	Given a prepared request, return a file-like object con- taining the
<pre>get_status_code_from_code_response(code)</pre>	Handle complicated code response, even multi-lines.

Attributes

_old_makepasv

_old_makepasv

_new_makepasv(self)

class FTPAdapter

Bases: conda.gateways.connection.BaseAdapter

A Requests Transport Adapter that handles FTP urls.

send(request, **kwargs)

Sends a PreparedRequest object over FTP. Returns a response object.

close()

Dispose of any internal state.

list(*path*, *request*)

Executes the FTP LIST command on the given path.

retr(path, request)

Executes the FTP RETR command on the given path.

stor(path, request)

Executes the FTP STOR command on the given path.

nlst(path, request)

Executes the FTP NLST command on the given path.

get_username_password_from_header(request)

Given a PreparedRequest object, reverse the process of adding HTTP Basic auth to obtain the username and password. Allows the FTP adapter to piggyback on the basic auth notation without changing the control flow.

get_host_and_path_from_url(request)

Given a PreparedRequest object, split the URL in such a manner as to determine the host and the path. This is a separate method to wrap some of urlparse's craziness.

data_callback_factory(variable)

Returns a callback suitable for use by the FTP library. This callback will repeatedly save data into the variable provided to this function. This variable should be a file-like structure.

build_text_response(request, data, code)

Build a response for textual data.

build_binary_response(request, data, code)

Build a response for data whose encoding is unknown.

build_response(request, data, code, encoding)

Builds a response object from the data returned by ftplib, using the specified encoding.

parse_multipart_files(request)

Given a prepared request, return a file-like object containing the original data. This is pretty hacky.

get_status_code_from_code_response(code)

Handle complicated code response, even multi-lines.

We get the status code in two ways: - extracting the code from the last valid line in the response - getting it from the 3 first digits in the code After a comparison between the two values, we can safely set the code or raise a warning. .. rubric:: Examples

- get_status_code_from_code_response('200 Welcome') == 200
- multi_line_code = '226-File successfully transferredn226 0.000 seconds' get_status_code_from_code_response(multi_line_code) == 226

• multi_line_with_code_conflicts = '200-File successfully transferredn226 0.000 seconds' get_status_code_from_code_response(multi_line_with_code_conflicts) == 226

For more detail see RFC 959, page 36, on multi-line responses:

https://www.ietf.org/rfc/rfc959.txt "Thus the format for multi-line replies is that the first line

will begin with the exact required reply code, followed immediately by a Hyphen, "-" (also known as Minus), followed by text. The last line will begin with the same code, followed immediately by Space <SP>, optionally some text, and the Telnet end-of-line code."

http

Defines HTTP transport adapter for CondaSession (requests.Session).

Closely derived from pip:

https://github.com/pypa/pip/blob/8c24fd2a80bad21aa29aec02fb48bd89a1e8f5e1/src/pip/_internal/network/session. py#L254

Under the MIT license:

Copyright (c) 2008-2023 The pip developers (see AUTHORS.txt file on the pip repository)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PAR-TICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFT-WARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Classes

_SSLContextAdapterMixin	Mixin to add the ssl_context constructor argument to HTTP adapters.
HTTPAdapter	Mixin to add the ssl_context constructor argument to HTTP adapters.

class _SSLContextAdapterMixin(*, *ssl_context: ssl.SSLContext* | *None* = *None*, ***kwargs: Any*)

Mixin to add the ssl_context constructor argument to HTTP adapters.

The additional argument is forwarded directly to the pool manager. This allows us to dynamically decide what SSL store to use at runtime, which is used to implement the optional truststore backend.

class HTTPAdapter(*, ssl_context: ssl.SSLContext | None = None, **kwargs: Any)

Bases: _SSLContextAdapterMixin, conda.gateways.connection.HTTPAdapter

Mixin to add the ssl_context constructor argument to HTTP adapters.

The additional argument is forwarded directly to the pool manager. This allows us to dynamically decide what SSL store to use at runtime, which is used to implement the optional truststore backend.

localfs

Defines local filesystem transport adapter for CondaSession (requests.Session).

Classes

LocalFSAdapter

The Base Transport Adapter

class LocalFSAdapter

Bases: conda.gateways.connection.BaseAdapter

The Base Transport Adapter

send(request, stream=None, timeout=None, verify=None, cert=None, proxies=None)

Sends PreparedRequest object. Returns Response object.

Parameters

- request -- The PreparedRequest being sent.
- **stream** -- (optional) Whether to stream the request content.
- **timeout** (*float or tuple*) -- (optional) How long to wait for the server to send data before giving up, as a float, or a (connect timeout, read timeout) tuple.
- **verify** -- (optional) Either a boolean, in which case it controls whether we verify the server's TLS certificate, or a string, in which case it must be a path to a CA bundle to use
- cert -- (optional) Any user-provided SSL certificate to be trusted.
- **proxies** -- (optional) The proxies dictionary to apply to the request.

close()

Cleans up adapter specific items.

s3

Defines S3 transport adapter for CondaSession (requests.Session).

Classes

S3Adapter

The Base Transport Adapter

Attributes

stderrlog

stderrlog

class S3Adapter

Bases: conda.gateways.connection.BaseAdapter

The Base Transport Adapter

send(*request: conda.gateways.connection.PreparedRequest, stream: bool* = *False, timeout: None* | *float* | tuple[float, float] | tuple[float, None] = *None, verify: bool* | str = *True, cert: None* | *bytes* | str | tuple[bytes | str, bytes | str] = *None, proxies: dict[str, str]* | *None* = *None*) \rightarrow conda.gateways.connection.Response

Sends PreparedRequest object. Returns Response object.

Parameters

- request -- The PreparedRequest being sent.
- **stream** -- (optional) Whether to stream the request content.
- **timeout** (*float or tuple*) -- (optional) How long to wait for the server to send data before giving up, as a float, or a (connect timeout, read timeout) tuple.
- **verify** -- (optional) Either a boolean, in which case it controls whether we verify the server's TLS certificate, or a string, in which case it must be a path to a CA bundle to use
- cert -- (optional) Any user-provided SSL certificate to be trusted.
- **proxies** -- (optional) The proxies dictionary to apply to the request.

close()

Cleans up adapter specific items.

 $_$ send_boto3(*resp: conda.gateways.connection.Response, request: conda.gateways.connection.PreparedRequest*) \rightarrow conda.gateways.connection.Response

_write_tempfile(writer_callable)

download

Download logic for conda indices and packages.

Classes

TmpDownload Context manager to handle downloads to a tempfile.

Functions

<pre>disable_ssl_verify_warning()</pre>	
<pre>download(url, target_full_path[, md5, sha256, size,])</pre>	
<pre>download_inner(url, target_full_path, md5, sha256,)</pre>	
<pre>download_partial_file(target_full_path, *, url,)</pre>	Create or open locked partial download file, moving onto target_full_path
<pre>download_http_errors(url)</pre>	Exception translator used inside download()
<pre>download_text(url)</pre>	

Attributes

CHUNK_SIZE

CHUNK_SIZE

disable_ssl_verify_warning()

```
download(url, target_full_path, md5=None, sha256=None, size=None, progress_update_callback=None)
```

download_inner(*url*, *target_full_path*, *md5*, *sha256*, *size*, *progress_update_callback*)

download_partial_file(target_full_path: str | pathlib.Path, *, url: str, sha256: str, md5: str, size: int)

Create or open locked partial download file, moving onto target_full_path when finished. Preserve partial file on exception.

download_http_errors(url: str)

Exception translator used inside download()

```
download_text(url)
```

```
class TmpDownload(url, verbose=True)
```

Context manager to handle downloads to a tempfile.

__enter__()

__exit__(exc_type, exc_value, traceback)

session

Requests session configured with all accepted scheme adapters.

Classes

EnforceUnusedAdapter	The Base Transport Adapter
CondaSessionType	Takes advice from https://github.com/requests/requests/
	issues/1871#issuecomment-33327847
CondaSession	A Requests session.
CondaHttpAuth	Base class that all auth implementations derive from

Functions

$get_channel_name_from_url(\rightarrow str None)$	Given a URL, determine the channel it belongs to and return its name.
<pre>get_session(url)</pre>	Function that determines the correct Session object to be returned
$get_session_storage_key(\rightarrow str)$	Function that determines which storage key to use for our CondaSession object caching

Attributes

RETRIES

CONDA_SESSION_SCHEMES

RETRIES = 3

CONDA_SESSION_SCHEMES

class EnforceUnusedAdapter

Bases: conda.gateways.connection.BaseAdapter

The Base Transport Adapter

send(request, *args, **kwargs)

Sends PreparedRequest object. Returns Response object.

Parameters

• **request** -- The PreparedRequest being sent.

- stream -- (optional) Whether to stream the request content.
- **timeout** (*float or tuple*) -- (optional) How long to wait for the server to send data before giving up, as a float, or a (connect timeout, read timeout) tuple.
- **verify** -- (optional) Either a boolean, in which case it controls whether we verify the server's TLS certificate, or a string, in which case it must be a path to a CA bundle to use
- cert -- (optional) Any user-provided SSL certificate to be trusted.
- proxies -- (optional) The proxies dictionary to apply to the request.

abstract close()

Cleans up adapter specific items.

get_channel_name_from_url(url: str) $\rightarrow str | None$

Given a URL, determine the channel it belongs to and return its name.

get_session(url: str)

Function that determines the correct Session object to be returned based on the URL that is passed in.

get_session_storage_key(auth) \rightarrow str

Function that determines which storage key to use for our CondaSession object caching

class CondaSessionType

Bases: type

Takes advice from https://github.com/requests/requests/issues/1871#issuecomment-33327847 and creates one Session instance per thread.

__call__(**kwargs)

Call self as a function.

class CondaSession(auth: conda.gateways.connection.AuthBase | tuple[str, str] | None = None)

Bases: conda.gateways.connection.Session

A Requests session.

Provides cookie persistence, connection-pooling, and configuration.

Basic Usage:

```
>>> import requests
>>> s = requests.Session()
>>> s.get('https://httpbin.org/get')
<Response [200]>
```

Or as a context manager:

```
>>> with requests.Session() as s:
... s.get('https://httpbin.org/get')
<Response [200]>
```

classmethod cache_clear()

class CondaHttpAuth

Bases: conda.gateways.connection.AuthBase

Base class that all auth implementations derive from

__call__(request)

static _apply_basic_auth(request)

- static add_binstar_token(url)
- static handle_407(response, **kwargs)

Prompts the user for the proxy username and password and modifies the proxy in the session object to include it.

This method is modeled after

- requests.auth.HTTPDigestAuth.handle_401()
- requests.auth.HTTPProxyAuth
- the previous conda.fetch.handle_proxy_407()

It both adds 'username:password' to the proxy URL, as well as adding a 'Proxy-Authorization' header. If any of this is incorrect, please file an issue.

disk

create

Disk utility functions for creating new files or directories.

Classes

TemporaryDirectory

Create and return a temporary directory. This has the same

ProgressFileWrapper

Functions

<pre>write_as_json_to_file(file_path, obj)</pre>	
<pre>create_python_entry_point(target_full_path,)</pre>	
<pre>create_application_entry_point(source_full_path)</pre>	
<pre>extract_tarball(tarball_full_path[,])</pre>	
<pre>make_menu(prefix, file_path[, remove])</pre>	Create cross-platform menu items (e.g. Windows Start Menu)
<pre>create_hard_link_or_copy(src, dst)</pre>	
_is_unix_executable_using_ORIGIN(path)	
_do_softlink(src, dst)	
<pre>create_fake_executable_softlink(src, dst)</pre>	
<i>copy</i> (src, dst)	
_do_copy(src, dst)	
<pre>create_link(src, dst[, link_type, force])</pre>	
<pre>compile_multiple_pyc(python_exe_full_path,)</pre>	
<pre>create_package_cache_directory(pkgs_dir)</pre>	
<pre>create_envs_directory(envs_dir)</pre>	

Attributes

stdoutlog

mkdir_p

python_entry_point_template

application_entry_point_template

class TemporaryDirectory(suffix=", prefix='tmp', dir=None)

Create and return a temporary directory. This has the same behavior as mkdtemp but can be used as a context manager. For .. rubric:: Example

with TemporaryDirectory() as tmpdir:

•••

Upon exiting the context, the directory and everything contained in it are removed.

name _closed = False __repr__() Return repr(self). __enter__() cleanup(_warn=False, _warnings=_warnings) __exit__(exc, value, tb) ___del__() stdoutlog mkdir_p python_entry_point_template application_entry_point_template write_as_json_to_file(file_path, obj) **create_python_entry_point**(*target_full_path*, *python_full_path*, *module*, *func*) create_application_entry_point(source_full_path, target_full_path, python_full_path) class ProgressFileWrapper(fileobj, progress_update_callback)

```
__getattr__(name)
```

__setattr__(*name*, *value*) Implement setattr(self, name, value).

read(*size*=-1)

progress_update()

extract_tarball(tarball_full_path, destination_directory=None, progress_update_callback=None)

```
make_menu(prefix, file_path, remove=False)
```

Create cross-platform menu items (e.g. Windows Start Menu)

Passes all menu config files %PREFIX%/Menu/*.json to menuinst.install. remove=True will remove the menu items.

create_hard_link_or_copy(src, dst)

_is_unix_executable_using_ORIGIN(path)

_do_softlink(src, dst)

create_fake_executable_softlink(src, dst)

copy(*src*, *dst*)

_do_copy(src, dst)

create_link(src, dst, link_type=LinkType.hardlink, force=False)

compile_multiple_pyc(*python_exe_full_path, py_full_paths, pyc_full_paths, prefix, py_ver*)

create_package_cache_directory(pkgs_dir)

create_envs_directory(envs_dir)

delete

Disk utility functions for deleting files and folders.

Functions

<pre>rmtree(path, *args, **kwargs)</pre>		
<pre>unlink_or_rename_to_trash(path)</pre>		If files are in use, especially on windows, we can't re- move them.
<pre>remove_empty_parent_paths(path)</pre>		
<pre>rm_rf(path[, max_retries, clean_empty_parents])</pre>	trash,	Completely delete path
<pre>delete_trash(prefix)</pre>		
<pre>backoff_rmdir(dirpath[, max_tries])</pre>		
<pre>path_is_clean(path)</pre>		Sometimes we can't completely remove a path because files are considered in use

rmtree(path, *args, **kwargs)

unlink_or_rename_to_trash(path)

If files are in use, especially on windows, we can't remove them. The fallback path is to rename them (but keep their folder the same), which maintains the file handle validity. See comments at: https://serverfault.com/a/ 503769

remove_empty_parent_paths(path)

rm_rf(*path*, *max_retries*=5, *trash*=True, *clean_empty_parents*=False, *args, **kw)

Completely delete path max_retries is the number of times to retry on failure. The default is 5. This only applies to deleting a directory. If removing path fails and trash is True, files will be moved to the trash directory.

delete_trash(prefix)

backoff_rmdir(dirpath, max_tries=MAX_TRIES)

path_is_clean(path)

Sometimes we can't completely remove a path because files are considered in use by python (hardlinking confusion). For our tests, it is sufficient that either the folder doesn't exist, or nothing but temporary file copies are left.

link

Disk utility functions for symlinking files and folders.

Portions of the code within this module are taken from https://github.com/jaraco/jaraco.windows which is MIT licensed by Jason R. Coombs.

https://github.com/jaraco/skeleton/issues/1#issuecomment-285448440

lchmod

link

islink

lock

Record locking to manage potential repodata / repodata metadata file contention between conda processes. Try to acquire a lock on a single byte in the metadat file; modify both files; then release the lock.

Functions

_lock_noop(fd)	When locking is not available.
_lock_impl(fd)	
lock(fd)	

Attributes

LOCK_BYTE	
LOCK_ATTEMPTS	
LOCK_SLEEP	

$LOCK_BYTE = 21$

LOCK_ATTEMPTS = 10

 $LOCK_SLEEP = 1$

_lock_noop(fd)

When locking is not available.

_lock_impl(fd)

lock(fd)

permissions

Disk utility functions for modifying file and directory permissions.

Functions

make_writable(path)

make_read_only(path)

```
recursive_make_writable(path[, max_tries])
```

make_executable(path)

is_executable(path)

```
make_writable(path)
```

```
make_read_only(path)
```

recursive_make_writable(path, max_tries=MAX_TRIES)

make_executable(path)

```
is_executable(path)
```

read

Disk utility functions for reading and processing file contents.

Functions

yield_lines(path)	Generator function for lines in file. Empty generator if path does not exist.
$compute_sum(\rightarrow str)$	
<pre>read_package_info(record, package_cache_record)</pre>	
<pre>read_index_json(extracted_package_directory)</pre>	
<pre>read_index_json_from_tarball(package_tarball_ful</pre>	
<pre>read_repodata_json(extracted_package_directory)</pre>	
<pre>read_icondata(extracted_package_directory)</pre>	
<pre>read_package_metadata(extracted_package_directory</pre>	
<pre>read_paths_json(extracted_package_directory)</pre>	
read_has_prefix(path)	Reads <i>has_prefix</i> file and return dict mapping filepaths to tuples(placeholder, FileMode).
<pre>read_no_link(info_dir)</pre>	
<pre>read_soft_links(extracted_package_directory, files)</pre>	
<pre>read_python_record(prefix_path, anchor_file,)</pre>	Convert a python package defined by an anchor file (Metadata information)

Attributes

listdir

listdir

yield_lines(path)

Generator function for lines in file. Empty generator if path does not exist.

Parameters

path (str) -- path to file

Returns

each line in file, not starting with '#'

Return type

iterator

compute_sum(*path: str* | *os.PathLike*, *algo: Literal*[*md5*, *sha256*]) \rightarrow str

read_package_info(record, package_cache_record)

read_index_json(extracted_package_directory)

read_index_json_from_tarball(package_tarball_full_path)

read_repodata_json(extracted_package_directory)

read_icondata(extracted_package_directory)

read_package_metadata(extracted_package_directory)

```
read_paths_json(extracted_package_directory)
```

read_has_prefix(path)

Reads *has_prefix* file and return dict mapping filepaths to tuples(placeholder, FileMode).

A line in *has_prefix* contains one of:

- filepath
- placeholder mode filepath

Mode values are one of:

- text
- binary

```
read_no_link(info_dir)
```

```
read_soft_links(extracted_package_directory, files)
```

read_python_record(prefix_path, anchor_file, python_version)

Convert a python package defined by an anchor file (Metadata information) into a conda prefix record object.

test

Disk utility functions testing path properties (e.g., writable, hardlinks, softlinks, etc.).

Functions

file_path_is_writable(path)

hardlink_supported(source_file, dest_dir)

softlink_supported(source_file, dest_dir)

is_conda_environment(prefix)

file_path_is_writable(path)

hardlink_supported(source_file, dest_dir)

softlink_supported(source_file, dest_dir)

is_conda_environment(prefix)
update

Disk utility functions for modifying existing files or directories.

Functions

<pre>update_file_in_place_as_binary(file_full_path, callback)</pre>	
<pre>rename(source_path, destination_path[, force])</pre>	
<pre>rename_context(source[, destination, dry_run])</pre>	Used for removing a directory when there are dependent actions (i.e. you need to ensure
<pre>backoff_rename(source_path, destination_path[, force])</pre>	
<pre>touch(path[, mkdir, sudo_safe])</pre>	

Attributes

SHEBANG_REGEX

SHEBANG_REGEX

exception CancelOperation

Bases: Exception

Common base class for all non-exit exceptions.

update_file_in_place_as_binary(file_full_path, callback)

rename(*source_path*, *destination_path*, *force=False*)

rename_context(*source: str, destination: str* | *None* = *None, dry_run: bool* = *False*)

Used for removing a directory when there are dependent actions (i.e. you need to ensure other actions succeed before removing it).

Example

```
with rename_context(directory):
    # Do dependent actions here
```

backoff_rename(source_path, destination_path, force=False)

touch(path, mkdir=False, sudo_safe=False)

Functions

<pre>exp_backoff_fn(fn, *args, **kwargs)</pre>	Mostly for retrying file operations that fail on Windows due to virus scanners
<i>mkdir_p</i> (path)	
<pre>mkdir_p_sudo_safe(path)</pre>	

Attributes

on_win		
TRACE		
MAX_TRIES		

on_win

TRACE = 5

MAX_TRIES = 7

```
exp_backoff_fn(fn, *args, **kwargs)
```

Mostly for retrying file operations that fail on Windows due to virus scanners

mkdir_p(path)

mkdir_p_sudo_safe(path)

logging

Configure logging for conda.

Classes

TokenURLFilter	Filter instances are used to perform arbitrary filtering of LogRecords.
StdStreamHandler	Log StreamHandler that always writes to the current sys stream.

Functions

initialize_logging()

initialize_std_loggers()

initialize_root_logger([level])

set_conda_log_level([level])

set_all_logger_level([level])

set_file_logging([logger_name, level, path])

set_verbosity(verbosity)

set_log_level(log_level)

trace(self, message, *args, **kwargs)

Attributes

_VERBOSITY_LEVELS

_VERBOSITY_LEVELS

class TokenURLFilter(name=")

Bases: logging.Filter

Filter instances are used to perform arbitrary filtering of LogRecords.

Loggers and Handlers can optionally use Filter instances to filter records as desired. The base filter class only allows events which are below a certain point in the logger hierarchy. For example, a filter initialized with "A.B" will allow events logged by loggers "A.B", "A.B.C", "A.B.C.D", "A.B.D" etc. but not "A.BB", "B.A.B" etc. If initialized with the empty string, all events are passed.

TOKEN_URL_PATTERN

TOKEN_REPLACE

filter(record)

Since Python 2's getMessage() is incapable of handling any strings that are not unicode when it interpolates the message with the arguments, we fix that here by doing it ourselves.

At the same time we replace tokens in the arguments which was not happening until now.

class StdStreamHandler(sys_stream)

Bases: logging.StreamHandler

Log StreamHandler that always writes to the current sys stream.

terminator = ' n'

__getattr__(attr)

emit(record)

Emit a record.

If a formatter is specified, it is used to format the record. The record is then written to the stream with a trailing newline. If exception information is present, it is formatted using traceback.print_exception and appended to the stream. If the stream has an 'encoding' attribute, it is used to determine how to do the output to the stream.

initialize_logging()

initialize_std_loggers()

initialize_root_logger(level=ERROR)

set_conda_log_level(level=WARN)

set_all_logger_level(level=DEBUG)

set_file_logging(logger_name=None, level=DEBUG, path=None)

set_verbosity(verbosity: int)

set_log_level(log_level: int)

trace(self, message, *args, **kwargs)

repodata

Repodata interface.

jlap

Incremental repodata feature based on .jlap patch files.

core

JLAP reader.

Classes

JLAP	A more or less complete user-defined wrapper around
	list objects.

Functions

keyed_hash(data, key)	Keyed hash.
<i>line_and_pos</i> (\rightarrow Iterator[tuple[int, bytes]])	
	param lines
	iterator over input split by 'n', with 'n'
	removed.

Attributes

DIGEST_SIZE

DEFAULT_IV

DIGEST_SIZE = 32

DEFAULT_IV

keyed_hash(data: bytes, key: bytes)

Keyed hash.

line_and_pos(*lines: Iterable[bytes]*, *pos*=0) \rightarrow Iterator[tuple[int, bytes]]

Parameters

- **lines** -- iterator over input split by 'n', with 'n' removed.
- **pos** -- initial position

class JLAP(initlist=None)

Bases: collections.UserList

A more or less complete user-defined wrapper around list objects.

property body

All lines except the first, and last two.

property penultimate

Next-to-last line. Should contain the footer.

property last

Last line. Should contain the trailing checksum.

classmethod from_lines(lines: Iterable[bytes], iv: bytes, pos=0, verify=True)

Parameters

- lines -- iterator over input split by b'n', with b'n' removed
- pos -- initial position
- iv -- initialization vector (first line of .jlap stream, hex decoded). Ignored if pos==0.

• **verify** -- assert last line equals computed checksum of previous line. Useful for writing new .jlap files if False.

Raises

ValueError -- if trailing and computed checksums do not match

Returns

list of (offset, line, checksum)

classmethod from_path(path: pathlib.Path | str, verify=True)

add(line: str)

Add line to buffer, following checksum rules.

Buffer must not be empty.

(Remember to pop trailing checksum and possibly trailing metadata line, if appending to a complete jlap file)

Less efficient than creating a new buffer from many lines and our last iv, and extending.

Returns self

terminate()

Add trailing checksum to buffer.

Returns self

write(path: pathlib.Path)
Write buffer to path.

fetch

JLAP consumer.

Classes

HashWriter

Base class for raw binary I/O.

Functions

hash()	Ordinary hash.
<pre>process_jlap_response(response[, pos, iv])</pre>	
<pre>fetch_jlap(url[, pos, etag, iv, ignore_etag, session])</pre>	
<pre>request_jlap(url[, pos, etag, ignore_etag, session])</pre>	Return the part of the remote .jlap file we are interested in.
<pre>format_hash(hash)</pre>	Abbreviate hash for formatting.
<pre>find_patches(patches, have, want)</pre>	
<pre>apply_patches(data, apply)</pre>	
withext(url, ext)	
timeme(message)	
build_headers(json_path, state)	Caching headers for a path and state.
<pre>download_and_hash(hasher, url, json_path, session, state)</pre>	Download url if it doesn't exist, passing bytes through hasher.update().
$_is_http_error_most_400_codes(\rightarrow bool)$	Determine whether the <i>HTTPError</i> is an HTTP 400 error code (except for 416).
$request_url_jlap_state(\rightarrow dict None)$	

Attributes

DIGEST_SIZE
JLAP_KEY
HEADERS
NOMINAL_HASH
ON_DISK_HASH
LATEST
STORE_HEADERS

DIGEST_SIZE = 32

JLAP_KEY = 'jlap'

HEADERS = 'headers'

NOMINAL_HASH = 'blake2_256_nominal'

ON_DISK_HASH = 'blake2_256'

LATEST = 'latest'

STORE_HEADERS

hash()

Ordinary hash.

exception Jlap304NotModified

Bases: Exception

Common base class for all non-exit exceptions.

exception JlapSkipZst

Bases: Exception

Common base class for all non-exit exceptions.

exception JlapPatchNotFound

Bases: LookupError

Base class for lookup errors.

process_jlap_response(response: conda.gateways.connection.Response, pos=0, iv=b")

fetch_jlap(url, pos=0, etag=None, iv=b", ignore_etag=True, session=None)

Return the part of the remote .jlap file we are interested in.

format_hash(hash)

Abbreviate hash for formatting.

find_patches(patches, have, want)

apply_patches(data, apply)

withext(url, ext)

timeme(message)

build_headers(*json_path: pathlib.Path, state:* conda.gateways.repodata.RepodataState) Caching headers for a path and state.

class HashWriter(backing, hasher)

Bases: io.RawIOBase

Base class for raw binary I/O.

write(b: bytes)

close()

Flush and close the IO object.

This method has no effect if the file is already closed.

Download url if it doesn't exist, passing bytes through hasher.update().

json_path: Path of old cached data (ignore etag if not exists). dest_path: Path to write new data.

_is_http_error_most_400_codes(e: requests.HTTPError) → bool

Determine whether the HTTPError is an HTTP 400 error code (except for 416).

 $\label{eq:request_url_jlap_state} (url, state: \ conda.gateways.repodata.RepodataState, full_download=False, *, session: conda.gateways.connection.Session, cache: \ conda.gateways.repodata.RepodataCache, temp_path: pathlib.Path) \rightarrow dict | None \\$

interface

JLAP interface for repodata.

Classes

JlapRepoInterface	Helper class that provides a standard way to create an ABC using
RepodataStateSkipFormat	Load/save info file that accompanies cached <i>repo-data.json</i> .
ZstdRepoInterface	Support repodata.json.zst (if available) without checking .jlap

Bases: conda.gateways.repodata.RepoInterface

Helper class that provides a standard way to create an ABC using inheritance.

repodata(*state: dict* | conda.gateways.repodata.RepodataState) \rightarrow str | None

Fetch newest repodata if necessary.

Always writes to cache_path_json.

repodata_parsed(*state: dict* | conda.gateways.repodata.RepodataState) \rightarrow dict | None

JLAP has to parse the JSON anyway.

Use this to avoid a redundant parse when repodata is updated.

When repodata is not updated, it doesn't matter whether this function or the caller reads from a file.

_repodata_state_copy(state: dict | conda.gateways.repodata.RepodataState)

class RepodataStateSkipFormat(*args, skip_formats=set(), **kwargs)

Bases: conda.gateways.repodata.RepodataState

Load/save info file that accompanies cached repodata.json.

skip_formats: set[str]

should_check_format(format)

Return True if named format should be attempted.

class ZstdRepoInterface(*url: str, repodata_fn: str | None, *, cache:* conda.gateways.repodata.RepodataCache, **kwargs)

Bases: JlapRepoInterface

Support repodata.json.zst (if available) without checking .jlap

_repodata_state_copy(state: dict | conda.gateways.repodata.RepodataState)

lock

Backwards compatibility import.

Moved to prevent circular imports.

Classes

PackageCacheData	
Channel	Channel:
RepoInterface	Helper class that provides a standard way to create an ABC using
CondaRepoInterface	Provides an interface for retrieving repodata data from channels.
RepodataState	Load/save info file that accompanies cached <i>repo-data.json</i> .
RepodataCache	Handle caching for a single repodata.json + repo- data.info.json
RepodataFetch	Combine RepodataCache and RepoInterface to provide subdir_data.SubdirData()

Functions

<pre>stringify(obj[, content_max_len])</pre>	
<pre>maybe_unquote(url)</pre>	
get_session(url)	Function that determines the correct Session object to be returned
<pre>mkdir_p_sudo_safe(path)</pre>	
lock(fd)	
$get_repo_interface(\rightarrow type[RepoInterface])$	
_add_http_value_to_dict(resp, http_key, d, dict_key)	
<pre>conda_http_errors(url, repodata_fn)</pre>	Use in a with: statement to translate requests exceptions to conda ones.
_md5_not_for_security(data)	
<pre>cache_fn_url(url[, repodata_fn])</pre>	
<pre>get_cache_control_max_age(cache_control_value)</pre>	
<pre>create_cache_dir()</pre>	

Attributes

CONDA_HOMEPAGE_URL
REPODATA_FN
context
join_url
stderrlog
CHECK_ALTERNATE_FORMAT_INTERVAL
LAST_MODIFIED_KEY
ETAG_KEY
CACHE_CONTROL_KEY
URL_KEY
CACHE_STATE_SUFFIX
ERROR_SNIPPET_LENGTH

```
exception CondaError(message, caused_by=None, **kwargs)
Bases: Exception
Common base class for all non-exit exceptions.
return_code = 1
```

reportable = False

__repr__()

Return repr(self).

```
__str__()
```

Return str(self).

```
dump_map()
```

stringify(obj, content_max_len=0)

```
CONDA_HOMEPAGE_URL = 'https://conda.io'
```

REPODATA_FN = 'repodata.json'

context

join_url

maybe_unquote(url)

```
class PackageCacheData(pkgs_dir)
     property _package_cache_records
     property is_writable
     _cache_: dict[str, PackageCacheData]
     insert(package_cache_record)
     load()
     reload()
     get(package_ref, default=NULL)
     remove(package_ref, default=NULL)
     query(package_ref_or_match_spec)
     iter_records()
     classmethod query_all(package_ref_or_match_spec, pkgs_dirs=None)
     classmethod first_writable(pkgs_dirs=None)
     classmethod writable_caches(pkgs_dirs=None)
     classmethod read_only_caches(pkgs_dirs=None)
     classmethod all_caches_writable_first(pkgs_dirs=None)
     classmethod get_all_extracted_entries()
     classmethod get_entry_to_link(package_ref)
     classmethod tarball_file_in_cache(tarball_path, md5sum=None, exclude_caches=())
     classmethod clear()
     tarball_file_in_this_cache(tarball_path, md5sum=None)
     _check_writable()
     static _clean_tarball_path_and_get_md5sum(tarball_path, md5sum=None)
     _scan_for_dist_no_channel(dist_str)
     itervalues()
     values()
     __repr__()
         Return repr(self).
     _make_single_record(package_filename)
```

```
static _dedupe_pkgs_dir_contents(pkgs_dir_contents)
```

exception CondaDependencyError(message)

Bases: conda.CondaError

Common base class for all non-exit exceptions.

exception CondaHTTPError(*message*, *url*, *status_code*, *reason*, *elapsed_time*, *response=None*,

caused_by=None)

Bases: conda.CondaError

Common base class for all non-exit exceptions.

exception CondaSSLError(message, caused_by=None, **kwargs)

Bases: conda.CondaError

Common base class for all non-exit exceptions.

exception NotWritableError(path, errno, **kwargs)

Bases: conda.CondaError, OSError

Common base class for all non-exit exceptions.

exception ProxyError

Bases: conda.CondaError

Common base class for all non-exit exceptions.

Bases: ChannelError

Common base class for all non-exit exceptions.

status_code: str | int

Channel: scheme <> auth <> location <> token <> channel <> subchannel <> platform <> package_filename

Package Spec: channel <> subchannel <> namespace <> package_name

property channel_location

property channel_name

property subdir

```
property canonical_name
```

```
property base_url
```

```
property base_urls
```

property subdir_url

property url_channel_wtf

cache

static _reset_state()

```
static from_url(url)
```

static from_channel_name(channel_name)

static from_value(value)

static make_simple_channel(channel_alias, channel_url, name=None)

urls(with_credentials=False, subdirs=None)

url(with_credentials=False)

__str__()

Return str(self).

__repr__()

Return repr(self).

__eq__(other)

Return self==value.

__hash__()

Return hash(self).

__nonzero__()

__bool__()

__json__()

dump()

get_session(url: str)

Function that determines the correct Session object to be returned based on the URL that is passed in.

mkdir_p_sudo_safe(path)

lock(fd)

stderrlog

CHECK_ALTERNATE_FORMAT_INTERVAL

LAST_MODIFIED_KEY = 'mod'

ETAG_KEY = 'etag'

CACHE_CONTROL_KEY = 'cache_control'

URL_KEY = 'url'

CACHE_STATE_SUFFIX = '.info.json'

ERROR_SNIPPET_LENGTH = 32

exception RepodatalsEmpty(channel, status_code, response: requests.models.Response | None = None)
Bases: conda.exceptions.UnavailableInvalidChannel

Subclass used to determine when empty repodata should be cached, e.g. for a channel that doesn't provide current_repodata.json

exception RepodataOnDisk

Bases: Exception

Indicate that RepoInterface.repodata() successfully wrote repodata to disk, instead of returning a string.

class RepoInterface

Bases: abc.ABC

Helper class that provides a standard way to create an ABC using inheritance.

repodata(*state: dict*) \rightarrow str

Given a mutable state dictionary with information about the cache, return repodata.json (or current_repodata.json) as a str. This function also updates state, which is expected to be saved by the caller.

exception Response304ContentUnchanged

Bases: Exception

Common base class for all non-exit exceptions.

get_repo_interface() → type[*RepoInterface*]

class CondaRepoInterface(url: str, repodata_fn: str | None, **kwargs)

Bases: RepoInterface

Provides an interface for retrieving repodata data from channels.

_url: str

_repodata_fn: str

repodata(*state*: RepodataState) \rightarrow str | None

Given a mutable state dictionary with information about the cache, return repodata.json (or current_repodata.json) as a str. This function also updates state, which is expected to be saved by the caller.

_add_http_value_to_dict(resp, http_key, d, dict_key)

conda_http_errors(url, repodata_fn)

Use in a with: statement to translate requests exceptions to conda ones.

Bases: collections.UserDict

Load/save info file that accompanies cached repodata.json.

```
property mod: str
```

Last-Modified header or ""

property etag: str

Etag header or ""

```
property cache_control: str
```

Cache-Control header or ""

_aliased

_strings

has_format(*format: str*) → tuple[bool, datetime.datetime | None]

set_has_format(format: str, value: bool)

clear_has_format(format: str)

Remove 'has_{format}' instead of setting to False.

should_check_format(*format: str*) → bool

Return True if named format should be attempted.

______ contains___(*key: str*) \rightarrow bool

__setitem__(*key: str, item: Any*) \rightarrow None

__getitem__(*key: str*) \rightarrow Any

class RepodataCache(base, repodata_fn)

Handle caching for a single repodata.json + repodata.info.json (<hex-string>*.json inside dir)

Avoid race conditions while loading, saving repodata.json and cache state.

property cache_path_json

property cache_path_state

Out-of-band etag and other state needed by the RepoInterface.

 $load(*, state_only=False) \rightarrow str$

load_state()

Update self.state without reading repodata.json.

Return self.state.

save(data: str)

Write data to <repodata>.json cache path, synchronize state.

replace(temp_path: pathlib.Path)

Rename path onto <repodata>.json path, synchronize state.

Relies on path's mtime not changing on move. *temp_path* should be adjacent to *self.cache_path_json* to be on the same filesystem.

refresh(refresh_ns=0)

Update access time in cache info file to indicate a HTTP 304 Not Modified response.

lock(mode='a+')

Lock .info.json file. Hold lock while modifying related files.

mode: "a+" then seek(0) to write/create; "r+" to read.

stale()

Compare state refresh_ns against cache control header and context.local_repodata_ttl.

timeout()

Return number of seconds until cache times out (<= 0 if already timed out).

class RepodataFetch(*cache_path_base: pathlib.Path, channel:* conda.models.channel.Channel, *repodata_fn: str*, *, *repo_interface_cls*)

Combine RepodataCache and RepoInterface to provide subdir_data.SubdirData() with what it needs.

Provide a variety of formats since some RepoInterface have to json.loads(...) anyway, and some clients don't need the Python data structure at all.

```
property url_w_repodata_fn
```

property cache_path_json

```
property cache_path_state
```

Out-of-band etag and other state needed by the RepoInterface.

property repo_cache: RepodataCache

property _repo: RepoInterface

Changes as we mutate self.repodata_fn.

cache_path_base: pathlib.Path

channel: conda.models.channel.Channel

repodata_fn: str

url_w_subdir: str

url_w_credentials: str

repo_interface_cls: Any

fetch_latest_parsed() → tuple[dict, *RepodataState*]

Retrieve parsed latest or latest-cached repodata as a dict; update cache.

Returns

(repodata contents, state including cache headers)

fetch_latest_path() → tuple[pathlib.Path, *RepodataState*]

Retrieve latest or latest-cached repodata; update cache.

Returns

(pathlib.Path to uncompressed repodata contents, RepodataState)

```
fetch_latest() \rightarrow tuple[dict | str, RepodataState]
```

Return up-to-date repodata and cache information. Fetch repodata from remote if cache has expired; return cached data if cache has not expired; return stale cached data or dummy data if in offline mode.

read_cache() \rightarrow tuple[str, *RepodataState*]

Read repodata from disk, without trying to fetch a fresh version.

_md5_not_for_security(data)

cache_fn_url(url, repodata_fn=REPODATA_FN)

get_cache_control_max_age(cache_control_value: str | None)

create_cache_dir()

subprocess

Helpler functions for subprocess.

Functions

```
_format_output(command_str, cwd, rc, stdout,
stderr)
any_subprocess(args, prefix[, env, cwd])
subprocess_call(command[, env, path, stdin, ...])
_subprocess_clean_env(env[, clean_python,
clean_conda])
subprocess_call_with_clean_env(command[,
path, stdin, ...])
```

Attributes

Response

Response

_format_output(command_str, cwd, rc, stdout, stderr)

any_subprocess(args, prefix, env=None, cwd=None)

This utility function should be preferred for all conda subprocessing. It handles multiple tricky details.

```
_subprocess_clean_env(env, clean_python=True, clean_conda=True)
```

history

Tools interfacing with conda's history file.

Classes

History

Functions

write_head(fo)

 $is_diff(content)$

pretty_diff(diff)

pretty_content(content)

Attributes

h

exception CondaHistoryWarning
 Bases: Warning
 Base class for warning categories.
write_head(fo)
is_diff(content)
pretty_diff(diff)
pretty_content(content)
class History(prefix)
 com_pat
 spec_pat
 conda_v_pat
 ___enter___()
 ___exit___(exc_type, exc_value, traceback)
 init_log_file()
 file_is_empty()

$update() \rightarrow None$

Update the history file (creating a new one if necessary).

$parse() \rightarrow list[tuple[str, set[str], list[str]]]$

Parse the history file.

Return a list of tuples(datetime strings, set of distributions/diffs, comments).

static _parse_old_format_specs_string(specs_string)

Parse specifications string that use conda<4.5 syntax.

Examples

- "param >=1.5.1,<2.0""
- "python>=3.5.1, jupyter >=1.0.0, <2.0, matplotlib >=1.5.1, <2.0"

classmethod _parse_comment_line(line)

Parse comment lines in the history file.

These lines can be of command type or action type.

Examples

- "# cmd: /scratch/mc3/bin/conda install -c conda-forge param>=1.5.1,<2.0"
- "# install specs: python>=3.5.1, jupyter >=1.0.0, <2.0, matplotlib >=1.5.1, <2.0"

get_user_requests()

Return a list of user requested items.

Each item is a dict with the following keys: 'date': the date and time running the command 'cmd': a list of argv of the actual command which was run 'action': install/remove/update 'specs': the specs being used

get_requested_specs_map()

construct_states()

Return a list of tuples(datetime strings, set of distributions).

get_state(rev=-1)

Return the state, i.e. the set of distributions, for a given revision.

Defaults to latest (which is the same as the current state when the log file is up-to-date).

Returns a list of dist_strs.

print_log()

object_log()

write_changes(last_state, current_state)

write_specs(remove_specs=(), update_specs=(), neutered_specs=())

h

instructions

Define the instruction set (constants) for conda operations.

Functions

PRINT_CMD(state, arg)

FETCH_CMD(state, package_cache_entry)

EXTRACT_CMD(state, arg)

PROGRESSIVEFETCHEXTRACT_CMD(state, ...)

UNLINKLINKTRANSACTION_CMD(state, arg)

check_files_in_package(source_dir, files)

Attributes

CHECK_FETCH
FETCH
CHECK_EXTRACT
EXTRACT
RM_EXTRACTED
RM_FETCHED
PRINT
PROGRESS
SYMLINK_CONDA
UNLINK
LINK
UNLINKLINKTRANSACTION
PROGRESSIVEFETCHEXTRACT
PROGRESS_COMMANDS
ACTION_CODES
commands
OP_ORDER

CHECK_FETCH = 'CHECK_FETCH'

FETCH = 'FETCH'

```
CHECK_EXTRACT = 'CHECK_EXTRACT'
```

EXTRACT = 'EXTRACT'

RM_EXTRACTED = '**RM_EXTRACTED**'

RM_FETCHED = '**RM_FETCHED**'

PRINT = 'PRINT'

PROGRESS = 'PROGRESS'

```
SYMLINK_CONDA = 'SYMLINK_CONDA'
```

UNLINK = 'UNLINK'

LINK = 'LINK'

UNLINKLINKTRANSACTION = 'UNLINKLINKTRANSACTION'

PROGRESSIVEFETCHEXTRACT = 'PROGRESSIVEFETCHEXTRACT'

PROGRESS_COMMANDS

 $ACTION_CODES = ()$

PRINT_CMD(state, arg)

FETCH_CMD(state, package_cache_entry)

EXTRACT_CMD(*state*, *arg*)

PROGRESSIVEFETCHEXTRACT_CMD(*state*, *progressive_fetch_extract*)

UNLINKLINKTRANSACTION_CMD(state, arg)

check_files_in_package(source_dir, files)

commands

 $OP_ORDER = ()$

misc

Miscellaneous utility functions.

Functions

<pre>conda_installed_files(prefix[, clude_self_build])</pre>	ex-	Return the set of files which have been installed (using conda) into
explicit(specs, prefix[, verbose, force_extract,]	D	
<pre>rel_path(prefix, path[, windows_forward_slashes</pre>	D	
<pre>walk_prefix(prefix[, ignore_predefined_files,])</pre>	1	Return the set of all files in a given prefix directory.
<pre>untracked(prefix[, exclude_self_build])</pre>		Return (the set) of all untracked files for a given prefix.
<pre>touch_nonadmin(prefix)</pre>		Creates \$PREFIX/.nonadmin if sys.prefix/.nonadmin exists (on Windows).
<pre>clone_env(prefix1, prefix2[, verbose, quiet, dex_args])</pre>	in-	Clone existing prefix1 into new prefix2.

Attributes

url_pat

```
conda_installed_files(prefix, exclude_self_build=False)
Return the set of files which have been installed (using conda) into a given prefix.
```

url_pat

explicit(specs, prefix, verbose=False, force_extract=True, index_args=None, index=None)

rel_path(*prefix*, *path*, *windows_forward_slashes=True*)

walk_prefix(prefix, ignore_predefined_files=True, windows_forward_slashes=True)
Return the set of all files in a given prefix directory.

untracked(prefix, exclude_self_build=False)

Return (the set) of all untracked files for a given prefix.

touch_nonadmin(prefix)

Creates \$PREFIX/.nonadmin if sys.prefix/.nonadmin exists (on Windows).

clone_env(prefix1, prefix2, verbose=True, quiet=False, index_args=None)
Clone existing prefix1 into new prefix2.

models

Models are data transfer objects or "light-weight" domain objects with no appreciable logic other than their own validation. Models are used to pass data between layers of the stack. In many ways they are similar to ORM objects. Unlike ORM objects, they are NOT themselves allowed to load data from a remote resource. Thought of another way, they cannot import from conda.gateways, but rather conda.gateways imports from conda.models as appropriate to create model objects from remote resources.

Conda modules importable from conda.models are

- conda._vendor
- conda.common
- conda.models

channel

Defines Channel and MultiChannel objects and other channel-related functions.

Object inheritance:



Classes

ChannelType	This metaclass does basic caching and enables static constructor method usage with a
Channel	Channel:
MultiChannel	Channel:

Functions

```
tokenized_startswith(test iterable,
startswith_iterable)
tokenized_conda_url_startswith(test_url,
startswith_url)
_get_channel_for_name(channel_name)
_read_channel_configuration(scheme, host, port,
path)
parse_conda_channel_url(url)
get_conda_build_local_url()
prioritize_channels(channels[, with_credentials,
subdirs])
all_channel_urls(channels[,
                                          subdirs,
with_credentials])
offline_keep(url)
get_channel_objs(ctx)
                                                    Return current channels as Channel objects
```

class ChannelType

Bases: type

This metaclass does basic caching and enables static constructor method usage with a single arg.

__call__(*args, **kwargs)

Call self as a function.

Channel: scheme <> auth <> location <> token <> channel <> subchannel <> platform <> package_filename

Package Spec: channel <> subchannel <> namespace <> package_name

property channel_location

property channel_name

property subdir

property canonical_name

property base_url

property base_urls

property subdir_url

property url_channel_wtf

cache

static _reset_state()

static from_url(url)

static from_channel_name(channel_name)

static from_value(value)

static make_simple_channel(channel_alias, channel_url, name=None)

urls(with_credentials=False, subdirs=None)

url(with_credentials=False)

__str__()

Return str(self).

```
__repr__()
```

Return repr(self).

```
___eq__(other)
```

Return self==value.

__hash__()

Return hash(self).

```
__nonzero__()
```

__bool__()

__json__()

dump()

class MultiChannel(name, channels, platform=None)

Bases: Channel

Channel: scheme <> auth <> location <> token <> channel <> subchannel <> platform <> package_filename Package Spec: channel <> subchannel <> namespace <> package_name property channel_location

```
property canonical_name
     property base_url
     property base_urls
     urls(with_credentials=False, subdirs=None)
     url(with_credentials=False)
     dump()
tokenized_startswith(test_iterable, startswith_iterable)
tokenized_conda_url_startswith(test_url, startswith_url)
_get_channel_for_name(channel_name)
_read_channel_configuration(scheme, host, port, path)
parse_conda_channel_url(url)
get_conda_build_local_url()
prioritize_channels(channels, with_credentials=True, subdirs=None)
all_channel_urls(channels, subdirs=None, with_credentials=True)
offline_keep(url)
get_channel_objs(ctx: conda.base.context.Context)
```

Return current channels as Channel objects

dist

(Legacy) Low-level implementation of a Channel.

Classes

DistDetails	
DistType	
Dist	

Functions

strip_extension(original_dist)

split_extension(original_dist)

dist_str_to_quad(dist_str)

class DistDetails

Bases: NamedTuple

name: str

version: str

build_string: str

build_number: str

dist_name: str

fmt: str

class DistType(name, bases, attr)

Bases: conda.auxlib.entity.EntityType

__call__(*args, **kwargs) Call self as a function.

strip_extension(original_dist)

```
split_extension(original_dist)
```

Bases: conda.auxlib.entity.Entity

property full_name

property build

property subdir

property pair

property quad

property is_feature_package

property is_channel

property fn

cache

_lazy_validate = True

channel

dist_name

name

fmt

version

build_string

build_number

base_url

platform

to_package_ref()

__str__()

Return str(self).

to_filename(extension=None)

to_matchspec()

to_match_spec()

classmethod from_string(string, channel_override=NULL)

static parse_dist_name(string)

classmethod from_url(url)

to_url()

__key__()

```
__lt__(other)
```

Return self<value.

__gt__(*other*)

Return self>value.

__le__(other)

Return self<=value.

```
__ge__(other)
```

Return self>=value.

__hash__()

Return hash(self).

 $__eq_(other)$

Return self==value.

__ne__(other)

Return self!=value.

split(sep=None, maxsplit=-1)

rsplit(sep=None, maxsplit=-1)

startswith(match)

__contains__(item)

dist_str_to_quad(dist_str)

enums

Collection of enums used throughout conda.

Classes

Arch	Generic enumeration.
Platform	Generic enumeration.
FileMode	Generic enumeration.
LinkType	Generic enumeration.
PathType	Refers to if the file in question is hard linked or soft
	linked. Originally designed to be used
LeasedPathType	Generic enumeration.
PackageType	Generic enumeration.
NoarchType	Generic enumeration.

class Arch

Bases: enum.Enum

Generic enumeration.

Derive from this class to define new enumerations.

x86 = 'x86' x86_64 = 'x86_64'

arm64 = 'arm64'

```
armv61 = 'armv61'
```

```
armv7l = 'armv7l'
```

```
aarch64 = 'aarch64'
```

```
ppc64 = 'ppc64'
```

```
ppc64le = 'ppc64le'
```

```
riscv64 = 'riscv64'
```

s390x = 's390x'

classmethod from_sys()

__json__()

class Platform

Bases: enum.Enum

Generic enumeration.

Derive from this class to define new enumerations.

freebsd = 'freebsd'

linux = 'linux'

win = 'win32'

openbsd = 'openbsd5'

osx = 'darwin'

zos = 'zos'

classmethod from_sys()

__json__()

class FileMode

Bases: enum.Enum

Generic enumeration.

Derive from this class to define new enumerations.

text = 'text'

binary = 'binary'

__str__()

Return str(self).

class LinkType

Bases: enum. Enum

Generic enumeration.

Derive from this class to define new enumerations.

```
hardlink = 1
```

softlink = 2

copy = 3

directory = 4

__int__()

__str__()

Return str(self).

__json__()

class PathType

Bases: enum. Enum

Refers to if the file in question is hard linked or soft linked. Originally designed to be used in paths.json

hardlink = 'hardlink'

softlink = 'softlink'

directory = 'directory'

linked_package_record = 'linked_package_record'

pyc_file = 'pyc_file'

unix_python_entry_point = 'unix_python_entry_point'

windows_python_entry_point_script = 'windows_python_entry_point_script'

windows_python_entry_point_exe = 'windows_python_entry_point_exe'

basic_types()

__str__()

Return str(self).

__json__()

class LeasedPathType

Bases: enum.Enum

Generic enumeration.

Derive from this class to define new enumerations.

```
application_entry_point = 'application_entry_point'
```

application_entry_point_windows_exe = 'application_entry_point_windows_exe'

application_softlink = 'application_softlink'

__str__()

Return str(self).

__json__()

class PackageType

Bases: enum.Enum

Generic enumeration.

Derive from this class to define new enumerations.

NOARCH_GENERIC = 'noarch_generic'

NOARCH_PYTHON = 'noarch_python'

VIRTUAL_PRIVATE_ENV = 'virtual_private_env'

VIRTUAL_PYTHON_WHEEL = 'virtual_python_wheel'

VIRTUAL_PYTHON_EGG_MANAGEABLE = 'virtual_python_egg_manageable'

VIRTUAL_PYTHON_EGG_UNMANAGEABLE = 'virtual_python_egg_unmanageable'

VIRTUAL_PYTHON_EGG_LINK = 'virtual_python_egg_link'

VIRTUAL_SYSTEM = 'virtual_system'

static conda_package_types()

static unmanageable_package_types()

class NoarchType

Bases: enum.Enum

Generic enumeration.

Derive from this class to define new enumerations.

generic = 'generic'

python = 'python'

static coerce(val)

leased_path_entry

Implements object describing a symbolic link from the base environment to a private environment.

Since private environments are an unrealized feature of conda and has been deprecated this data model no longer serves a purpose and has also been deprecated.

Classes

LeasedPathEntry	_path: short path for the leased path, using forward
	slashes

class LeasedPathEntry(**kwargs)

Bases: conda.auxlib.entity.Entity

_path: short path for the leased path, using forward slashes target_path: the full path to the executable in the private env target_prefix: the full path to the private environment leased_path: the full path for the lease in the root prefix package_name: the package holding the lease leased_path_type: application_entry_point

_path

target_path

target_prefix

leased_path

package_name

leased_path_type

match_spec

Implements the query language for conda packages (a.k.a, MatchSpec).

The MatchSpec is the conda package specification (e.g. conda == 23.3, python < 3.7, $cryptography * *_0$) and is used to communicate the desired packages to install.

Classes

MatchSpecType	
MatchSpec	The query language for conda packages.
MatchInterface	
_StrMatchMixin	
ExactStrMatch	
ExactLowerStrMatch	
GlobStrMatch	
GlobLowerStrMatch	
SplitStrMatch	
FeatureMatch	
ChannelMatch	
CaseInsensitiveStrMatch	

Functions

_parse_version_plus_build(v_plus_b)	This should reliably pull the build string out of a version + build string combo.
<pre>_parse_legacy_dist(dist_str)</pre>	
	Examples
_parse_channel(channel_val)	
_parse_spec_str(spec_str)	

Attributes

_PARSE_CACHE

_implementors

class MatchSpecType

Bases: type

__call__(spec_arg=None, **kwargs)

Call self as a function.

class MatchSpec(optional=False, target=None, **kwargs)

The query language for conda packages.

Any of the fields that comprise a PackageRecord can be used to compose a MatchSpec.

MatchSpec can be composed with keyword arguments, where keys are any of the attributes of PackageRecord. Values for keyword arguments are the exact values the attribute should match against. Many fields can also be matched against non-exact values--by including wildcard * and >/< ranges--where supported. Any non-specified field is the equivalent of a full wildcard match.

MatchSpec can also be composed using a single positional argument, with optional keyword arguments. Keyword arguments also override any conflicting information provided in the positional argument. The positional argument can be either an existing MatchSpec instance or a string. Conda has historically had several string representations for equivalent MatchSpec`s. This :class:`MatchSpec should accept any existing valid spec string, and correctly compose a MatchSpec instance.

A series of rules are now followed for creating the canonical string representation of a *MatchSpec* instance. The canonical string representation can generically be represented by

(channel(/subdir):(namespace):)name(version(build))[key1=value1,key2=value2]

where () indicate optional fields. The rules for constructing a canonical string representation are:

- 1. *name* (i.e. "package name") is required, but its value can be '*'. Its position is always outside the key-value brackets.
- If version is an exact version, it goes outside the key-value brackets and is prepended by ==. If version is a "fuzzy" value (e.g. 1.11.*), it goes outside the key-value brackets with the .* left off and is prepended by =. Otherwise version is included inside key-value brackets.
- 3. If *version* is an exact version, and *build* is an exact value, *build* goes outside key-value brackets prepended by a =. Otherwise, *build* goes inside key-value brackets. *build_string* is an alias for *build*.
- 4. The *namespace* position is being held for a future conda feature.
- 5. If *channel* is included and is an exact value, a :: separator is ued between *channel* and *name. channel* can either be a canonical channel name or a channel url. In the canonical string representation, the canonical channel name will always be used.
- 6. If *channel* is an exact value and *subdir* is an exact value, *subdir* is appended to *channel* with a / separator. Otherwise, *subdir* is included in the key-value brackets.
- 7. Key-value brackets can be delimited by comma, space, or comma+space. Value can optionally be wrapped in single or double quotes, but must be wrapped if *value* contains a comma, space, or equal sign. The canonical format uses comma delimiters and single quotes.
8. When constructing a *MatchSpec* instance from a string, any key-value pair given inside the key-value brackets overrides any matching parameter given outside the brackets.

When *MatchSpec* attribute values are simple strings, the are interpreted using the following conventions:

- If the string begins with ^ and ends with \$, it is converted to a regex.
- If the string contains an asterisk (*), it is transformed from a glob to a regex.
- Otherwise, an exact match to the string is sought.

Examples

```
>>> str(MatchSpec(name='foo', build='py2*', channel='conda-forge'))
'conda-forge::foo[build=py2*]'
>>> str(MatchSpec('foo 1.0 py27_0'))
'foo==1.0=py27_0'
>>> str(MatchSpec('foo=1.0=py27_0'))
'foo==1.0=py27_0'
>>> str(MatchSpec('conda-forge::foo[version=1.0.*]'))
'conda-forge::foo=1.0'
>>> str(MatchSpec('conda-forge/linux-64::foo>=1.0'))
"conda-forge/linux-64::foo[version='>=1.0']"
>>> str(MatchSpec('*/linux-64::foo>=1.0')"
```

To fully-specify a package with a full, exact spec, the fields

- channel
- subdir
- name
- version
- build

must be given as exact values. In the future, the namespace field will be added to this list. Alternatively, an exact spec is given by '*[md5=12345678901234567890123456789012]' or '*[sha256=f453db4ffe2271ec492a2913af4e61d4a6c118201f07de757df0eff769b65d2e]'.

property is_name_only_spec

```
property optional
```

property target

```
property original_spec_str
```

property name

property strictness

property spec

property version

property fn

```
FIELD_NAMES = ('channel', 'subdir', 'name', 'version', 'build', 'build_number',
'track_features', 'features',...
```

FIELD_NAMES_SET

_MATCHER_CACHE

classmethod from_dist_str(dist_str)

get_exact_value(field_name)

get_raw_value(field_name)

get(field_name, default=None)

dist_str()

```
match(rec)
```

Accepts a *PackageRecord* or a dict, and matches can pull from any field in that record. Returns True for a match, and False for no match.

_match_individual(record, field_name, match_component)

_is_simple()

_is_single()

_to_filename_do_not_use()

__repr__()

Return repr(self).

__str__()

Return str(self).

__json__()

conda_build_form()

___eq__(*other*)

Return self==value.

__hash__()

Return hash(self).

_hash_key()

```
__contains__(field)
```

_build_components(**kwargs)

static _make_component(field_name, value)

classmethod merge(match_specs, union=False)

classmethod union(match_specs)

```
_merge(other, union=False)
```

_parse_version_plus_build(v_plus_b)

This should reliably pull the build string out of a version + build string combo. .. rubric:: Examples

```
>>> _parse_version_plus_build("=1.2.3 0")
('=1.2.3', '0')
>>> _parse_version_plus_build("1.2.3=0")
('1.2.3', '0')
>>> _parse_version_plus_build(">=1.0 , < 2.0 py34_0")</pre>
('>=1.0,<2.0', 'py34_0')
>>> _parse_version_plus_build(">=1.0 , < 2.0 =py34_0")</pre>
('>=1.0,<2.0', 'py34_0')
>>> _parse_version_plus_build("=1.2.3 ")
('=1.2.3', None)
>>> _parse_version_plus_build(">1.8,<2|==1.7")</pre>
('>1.8,<2|==1.7', None)
>>> _parse_version_plus_build("* openblas_0")
('*', 'openblas_0')
>>> _parse_version_plus_build("* *")
('*', '*')
```

_parse_legacy_dist(dist_str)

Examples

```
>>> _parse_legacy_dist("_license-1.1-py27_1.tar.bz2")
('_license', '1.1', 'py27_1')
>>> _parse_legacy_dist("_license-1.1-py27_1")
('_license', '1.1', 'py27_1')
```

_parse_channel(channel_val)

_PARSE_CACHE

```
_parse_spec_str(spec_str)
```

class MatchInterface(value)

property raw_value

abstract property exact_value

If the match value is an exact specification, returns the value. Otherwise returns None.

abstract match(other)

matches(value)

merge(other)

union(other)

class _StrMatchMixin

property exact_value

__str__()

Return str(self).

__repr__()

Return repr(self).

```
___eq__(other)
```

Return self==value.

__hash__()

Return hash(self).

class ExactStrMatch(value)

Bases: _StrMatchMixin, MatchInterface

__slots__ = ('_raw_value',)

match(other)

class ExactLowerStrMatch(value)

Bases: ExactStrMatch

match(other)

class GlobStrMatch(value)

Bases: _StrMatchMixin, MatchInterface

property exact_value

If the match value is an exact specification, returns the value. Otherwise returns None.

property matches_all

__slots__ = ('_raw_value', '_re_match')

match(other)

class GlobLowerStrMatch(value)

Bases: GlobStrMatch

class SplitStrMatch(value)

Bases: MatchInterface

property exact_value

If the match value is an exact specification, returns the value. Otherwise returns None.

__slots__ = ('_raw_value',)

_convert(value)

match(other)

__repr__()

Return repr(self).

__str__()

Return str(self).

__eq__(other)

Return self==value.

__hash__()

Return hash(self).

class FeatureMatch(value)

Bases: MatchInterface

property exact_value

If the match value is an exact specification, returns the value. Otherwise returns None.

__slots__ = ('_raw_value',)

_convert(value)

match(other)

__repr__()

Return repr(self).

___str__()

Return str(self).

___eq__(*other*)

Return self==value.

__hash__()

Return hash(self).

class ChannelMatch(value)

Bases: GlobStrMatch

match(other)

__str__()

Return str(self).

__**repr__(**) Return repr(self).

class CaseInsensitiveStrMatch(value)

Bases: GlobLowerStrMatch

match(other)

_implementors

package_info

(Legacy) Low-level implementation of a PackageRecord.

Classes

NoarchField	Fields are doing something very similar to boxing and unboxing
Noarch	
PreferredEnv	
PackageMetadata	
PackageInfo	

class NoarchField(*enum_class, default=NULL, required=True, validation=None, in_dump=True, default_in_dump=True, nullable=False, immutable=False, aliases=()*)

Bases: conda.auxlib.entity.EnumField

Fields are doing something very similar to boxing and unboxing of c#/java primitives. __set__ should take a "primitive" or "raw" value and create a "boxed" or "programmatically usable" value of it. While __get__ should return the boxed value, dump in turn should unbox the value into a primitive or raw value.

Parameters

- types (primitive literal or type or sequence of types)
- **default** (*any*, *callable*, *optional*) -- If default is callable, it's guaranteed to return a valid value at the time of Entity creation.
- required (boolean, optional)
- validation (callable, optional)
- dump (boolean, optional)

box(*instance*, *instance_type*, *val*)

class Noarch(**kwargs)

Bases: conda.auxlib.entity.Entity

type

entry_points

class PreferredEnv(**kwargs)

Bases: conda.auxlib.entity.Entity

name

executable_paths

softlink_paths

class PackageMetadata(**kwargs)

Bases: conda.auxlib.entity.Entity

package_metadata_version

noarch

preferred_env class PackageInfo(**kwargs) Bases: conda.auxlib.entity.ImmutableEntity property name property version property build property build_number extracted_package_dir package_tarball_full_path channel repodata_record url icondata package_metadata paths_data dist_str()

prefix_graph

Implements directed graphs to sort and manipulate packages within a prefix. Object inheritance:



Classes

PrefixGraph	A directed graph structure used for sorting packages (prefix_records) in prefixes and
GeneralGraph	Compared with PrefixGraph, this class takes in more than one record of a given name,

class PrefixGraph(records, specs=())

A directed graph structure used for sorting packages (prefix_records) in prefixes and manipulating packages within prefixes (e.g. removing and pruning).

The terminology used for edge direction is "parents" and "children" rather than "successors" and "predecessors". The parent nodes of a record are those records in the graph that match the record's "depends" field. E.g. NodeA depends on NodeB, then NodeA is a child of NodeB, and NodeB is a parent of NodeA. Nodes can have zero parents, or more than two parents.

Most public methods mutate the graph.

property records

remove_spec(spec)

Remove all matching nodes, and any associated child nodes.

Parameters spec (MatchSpec)

Returns

The removed nodes.

Return type

tuple[PrefixRecord]

remove_youngest_descendant_nodes_with_specs()

A specialized method used to determine only dependencies of requested specs.

Returns

The removed nodes.

Return type tuple[*PrefixRecord*]

prune()

Prune back all packages until all child nodes are anchored by a spec.

Returns

The pruned nodes.

Return type

tuple[PrefixRecord]

get_node_by_name(name)

all_descendants(node)

```
all_ancestors(node)
```

_remove_node(node)

Removes this node and all edges referencing it.

_toposort()

classmethod _toposort_raise_on_cycles(graph)

classmethod _topo_sort_handle_cycles(graph)

static _toposort_pop_key(graph)

Pop an item from the graph that has the fewest parents. In the case of a tie, use the node with the alphabetically-first package name.

static _toposort_prepare_graph(graph)

class GeneralGraph(records, specs=())

Bases: PrefixGraph

Compared with PrefixGraph, this class takes in more than one record of a given name, and operates on that graph from the higher view across any matching dependencies. It is not a Prefix thing, but more like a "graph of all possible candidates" thing, and is used for unsatisfiability analysis

breadth_first_search_by_name(root_spec, target_spec)

Return shorted path from root_spec to spec_name

records

Implements the data model for conda packages.

A PackageRecord is the record of a package present in a channel. A PackageCache is the record of a downloaded and cached package. A PrefixRecord is the record of a package installed into a conda environment.

Object inheritance:



Classes

LinkTypeField	Fields are doing something very similar to boxing and unboxing
NoarchField	Fields are doing something very similar to boxing and unboxing
TimestampField	Fields are doing something very similar to boxing and unboxing
Link	
_FeaturesField	Fields are doing something very similar to boxing and unboxing
ChannelField	Fields are doing something very similar to boxing and unboxing
SubdirField	Fields are doing something very similar to boxing and unboxing
FilenameField	Fields are doing something very similar to boxing and unboxing
PackageTypeField	Fields are doing something very similar to boxing and unboxing
PathData	
PathDataV1	
PathsData	
PackageRecord	
Md5Field	Fields are doing something very similar to boxing and unboxing
PackageCacheRecord	
PrefixRecord	

Attributes

EMPTY_LINK		

```
class LinkTypeField(enum_class, default=NULL, required=True, validation=None, in_dump=True, default_in_dump=True, nullable=False, immutable=False, aliases=())
```

Bases: conda.auxlib.entity.EnumField

Fields are doing something very similar to boxing and unboxing of c#/java primitives. __set__ should take a "primitive" or "raw" value and create a "boxed" or "programmatically usable" value of it. While __get__ should return the boxed value, dump in turn should unbox the value into a primitive or raw value.

Parameters

• types (primitive literal or type or sequence of types)

- **default** (*any*, *callable*, *optional*) -- If default is callable, it's guaranteed to return a valid value at the time of Entity creation.
- required (boolean, optional)
- validation (callable, optional)
- dump (boolean, optional)

box(instance, instance_type, val)

class NoarchField(*enum_class, default=NULL, required=True, validation=None, in_dump=True, default_in_dump=True, nullable=False, immutable=False, aliases=()*)

Bases: conda.auxlib.entity.EnumField

Fields are doing something very similar to boxing and unboxing of c#/java primitives. __set__ should take a "primitive" or "raw" value and create a "boxed" or "programmatically usable" value of it. While __get__ should return the boxed value, dump in turn should unbox the value into a primitive or raw value.

Parameters

- types (primitive literal or type or sequence of types)
- **default** (*any*, *callable*, *optional*) -- If default is callable, it's guaranteed to return a valid value at the time of Entity creation.
- required (boolean, optional)
- validation (callable, optional)
- dump (boolean, optional)

box(*instance*, *instance_type*, *val*)

class TimestampField

Bases: conda.auxlib.entity.NumberField

Fields are doing something very similar to boxing and unboxing of c#/java primitives. __set__ should take a "primitive" or "raw" value and create a "boxed" or "programmatically usable" value of it. While __get__ should return the boxed value, dump in turn should unbox the value into a primitive or raw value.

Parameters

- types (primitive literal or type or sequence of types)
- **default** (*any*, *callable*, *optional*) -- If default is callable, it's guaranteed to return a valid value at the time of Entity creation.
- **required** (boolean, optional)
- validation (callable, optional)
- dump (boolean, optional)

static _make_seconds(val)

static _make_milliseconds(val)

box(instance, instance_type, val)

dump(instance, instance_type, val)

```
__get__(instance, instance_type)
```

class Link(**kwargs)

Bases: conda.auxlib.entity.DictSafeMixin, conda.auxlib.entity.Entity

source

type

EMPTY_LINK

class _FeaturesField(**kwargs)

Bases: conda.auxlib.entity.ListField

Fields are doing something very similar to boxing and unboxing of c#/java primitives. __set__ should take a "primitive" or "raw" value and create a "boxed" or "programmatically usable" value of it. While __get__ should return the boxed value, dump in turn should unbox the value into a primitive or raw value.

Parameters

- types (primitive literal or type or sequence of types)
- **default** (*any*, *callable*, *optional*) -- If default is callable, it's guaranteed to return a valid value at the time of Entity creation.
- required (boolean, optional)
- validation (callable, optional)
- dump (boolean, optional)

box(*instance*, *instance_type*, *val*)

dump(instance, instance_type, val)

class ChannelField(aliases=())

Bases: conda.auxlib.entity.ComposableField

Fields are doing something very similar to boxing and unboxing of c#/java primitives. __set__ should take a "primitive" or "raw" value and create a "boxed" or "programmatically usable" value of it. While __get__ should return the boxed value, dump in turn should unbox the value into a primitive or raw value.

Parameters

- types (primitive literal or type or sequence of types)
- **default** (*any*, *callable*, *optional*) -- If default is callable, it's guaranteed to return a valid value at the time of Entity creation.
- required (boolean, optional)
- validation (callable, optional)
- dump (boolean, optional)

dump(instance, instance_type, val)

__get__(instance, instance_type)

class SubdirField

Bases: conda.auxlib.entity.StringField

Fields are doing something very similar to boxing and unboxing of c#/java primitives. __set__ should take a "primitive" or "raw" value and create a "boxed" or "programmatically usable" value of it. While __get__ should return the boxed value, dump in turn should unbox the value into a primitive or raw value.

Parameters

- types (primitive literal or type or sequence of types)
- **default** (*any*, *callable*, *optional*) -- If default is callable, it's guaranteed to return a valid value at the time of Entity creation.
- **required** (boolean, optional)
- validation (callable, optional)
- dump (boolean, optional)

__get__(instance, instance_type)

class FilenameField(aliases=())

Bases: conda.auxlib.entity.StringField

Fields are doing something very similar to boxing and unboxing of c#/java primitives. __set__ should take a "primitive" or "raw" value and create a "boxed" or "programmatically usable" value of it. While __get__ should return the boxed value, dump in turn should unbox the value into a primitive or raw value.

Parameters

- types (primitive literal or type or sequence of types)
- **default** (*any*, *callable*, *optional*) -- If default is callable, it's guaranteed to return a valid value at the time of Entity creation.
- required (boolean, optional)
- validation (callable, optional)
- dump (boolean, optional)

__get__(instance, instance_type)

class PackageTypeField

Bases: conda.auxlib.entity.EnumField

Fields are doing something very similar to boxing and unboxing of c#/java primitives. __set__ should take a "primitive" or "raw" value and create a "boxed" or "programmatically usable" value of it. While __get__ should return the boxed value, dump in turn should unbox the value into a primitive or raw value.

Parameters

- types (primitive literal or type or sequence of types)
- **default** (*any*, *callable*, *optional*) -- If default is callable, it's guaranteed to return a valid value at the time of Entity creation.
- required (boolean, optional)
- validation (callable, optional)
- dump (boolean, optional)

__get__(instance, instance_type)

class PathData(**kwargs)

Bases: conda.auxlib.entity.Entity

property path

_path

prefix_placeholder file_mode no_link path_type class PathDataV1(**kwargs) Bases: PathData sha256 size_in_bytes inode_paths sha256_in_prefix class PathsData(**kwargs) Bases: conda.auxlib.entity.Entity paths_version paths class PackageRecord(*args, **kwargs) Bases: conda.auxlib.entity.DictSafeMixin, conda.auxlib.entity.Entity property schannel property _pkey property is_unmanageable property combined_depends property namekey name version build build_number channel subdir fn md5 legacy_bz2_md5 legacy_bz2_size url

sha256

arch

platform

depends

constrains

track_features

features

noarch

preferred_env

license

license_family

package_type

timestamp

date

size

metadata: set[str]

__hash__()

Return hash(self).

___eq__(*other*)

Return self==value.

dist_str()

dist_fields_dump()

__str__()

Return str(self).

to_match_spec()

to_simple_match_spec()

record_id()

class Md5Field

Bases: conda.auxlib.entity.StringField

Fields are doing something very similar to boxing and unboxing of c#/java primitives. __set__ should take a "primitive" or "raw" value and create a "boxed" or "programmatically usable" value of it. While __get__ should return the boxed value, dump in turn should unbox the value into a primitive or raw value.

Parameters

• types (primitive literal or type or sequence of types)

- **default** (*any*, *callable*, *optional*) -- If default is callable, it's guaranteed to return a valid value at the time of Entity creation.
- required (boolean, optional)
- validation (callable, optional)
- dump (boolean, optional)

```
__get__(instance, instance_type)
```

```
class PackageCacheRecord(*args, **kwargs)
```

Bases: PackageRecord

```
property is_fetched
```

property is_extracted

property tarball_basename

package_tarball_full_path

extracted_package_dir

md5

_calculate_md5sum()

```
class PrefixRecord(*args, **kwargs)
```

Bases: PackageRecord

```
package_tarball_full_path
```

extracted_package_dir

files

paths_data

link

requested_spec

auth

version

Implements the version spec with parsing and comparison logic.

Object inheritance:



Classes

SingleStrArgCachingType	
VersionOrder	Implement an order relation between version strings.
BaseSpec	
VersionSpec	
BuildNumberMatch	

Functions

$normalized_version(\rightarrow VersionOrder)$	Parse a version string and return VersionOrder object.
<pre>ver_eval(vtest, spec)</pre>	
<pre>treeify(spec_str)</pre>	
	Examples
<pre>untreeify(spec[, _inand, depth])</pre>	
	Examples
<pre>compatible_release_operator(x, y)</pre>	

Attributes

version_check_re	version_check_re	ersio
version_split_re	version_split_re	ersid
version_cache	version_cache	ersid
'SPEC_TOKENS	VSPEC_TOKENS	SPEC_
version_relation_re	version_relation_re	ersid
<pre>regex_split_re</pre>	regex_split_re	egex_
)PERATOR_MAP	OPERATOR_MAP	PERAT
PERATOR_START	OPERATOR_START	PERAT
VersionMatch	VersionMatch	ersio

normalized_version(version: str) \rightarrow VersionOrder

Parse a version string and return VersionOrder object.

ver_eval(vtest, spec)

version_check_re

version_split_re

version_cache

class SingleStrArgCachingType

Bases: type

__call__(*arg*)

Call self as a function.

class VersionOrder(vstr: str)

Implement an order relation between version strings.

Version strings can contain the usual alphanumeric characters (A-Za-z0-9), separated into components by dots and underscores. Empty segments (i.e. two consecutive dots, a leading/trailing underscore) are not permitted. An optional epoch number - an integer followed by '!' - can proceed the actual version string (this is useful to indicate a change in the versioning scheme itself). Version comparison is case-insensitive.

Conda supports six types of version strings: * Release versions contain only integers, e.g. '1.0', '2.3.5'. * Prerelease versions use additional letters such as 'a' or 'rc',

for example '1.0a1', '1.2.beta3', '2.3.5rc3'.

- Development versions are indicated by the string 'dev', for example '1.0dev42', '2.3.5.dev12'.
- Post-release versions are indicated by the string 'post', for example '1.0post1', '2.3.5.post2'.

- Tagged versions have a suffix that specifies a particular property of interest, e.g. '1.1.parallel'. Tags can be added to any of the preceding four types. As far as sorting is concerned, tags are treated like strings in pre-release versions.
- An optional local version string separated by '+' can be appended to the main (upstream) version string. It is only considered in comparisons when the main versions are equal, but otherwise handled in exactly the same manner.

To obtain a predictable version ordering, it is crucial to keep the version number scheme of a given package consistent over time. Specifically, * version strings should always have the same number of components

(except for an optional tag suffix or local version string),

· letters/strings indicating non-release versions should always occur at the same position.

Before comparison, version strings are parsed as follows: * They are first split into epoch, version number, and local version

number at '!' and '+' respectively. If there is no '!', the epoch is set to 0. If there is no '+', the local version is empty.

- The version part is then split into components at '.' and '_'.
- Each component is split again into runs of numerals and non-numerals
- Subcomponents containing only numerals are converted to integers.
- Strings are converted to lower case, with special treatment for 'dev' and 'post'.
- When a component starts with a letter, the fillvalue 0 is inserted to keep numbers and strings in phase, resulting in '1.1.a1' == 1.1.0a1'.
- The same is repeated for the local version part.

Examples

1.2g.beta15.rc => [[0], [1], [2, 'g'], [0, 'beta', 15], [0, 'rc']] $1!2.15.1_{ALPHA} => [[1], [2], [15], [1, '_alpha']]$

The resulting lists are compared lexicographically, where the following rules are applied to each pair of corresponding subcomponents: * integers are compared numerically * strings are compared lexicographically, caseinsensitive * strings are smaller than integers, except * 'dev' versions are smaller than all corresponding versions of other types * 'post' versions are greater than all corresponding versions of other types * if a subcomponent has no correspondent, the missing correspondent is

```
treated as integer 0 to ensure '1.1' == '1.1.0'.
```

The resulting order is:

0.4

< 0.4.0 < 0.4.1.rc

== 0.4.1.RC # case-insensitive comparison

< 0.4.1 < 0.5a1 < 0.5b3 < 0.5C1# case-insensitive comparison < 0.5 < 0.9.6 < 0.960923 < 1.0 < 1.1dev1# special case 'dev' $< 1.1_$ # appended underscore is special case for openssl-like versions < 1.1a1 < 1.1.0dev1 # special case 'dev'

== 1.1.dev1 # 0 is inserted before string

< 1.1.a1 < 1.1.0rc1 < 1.1.0

```
== 1.1
```

< 1.1.0post1 # special case 'post'

```
== 1.1.post1 # 0 is inserted before string
```

<1.1 post1 # special case 'post' <1996.07.12<1!0.4.1 # epoch increased <1!3.1.1.6<2!0.4.1 # epoch increased again

Some packages (most notably openssl) have incompatible version conventions. In particular, openssl interprets letters as version counters rather than pre-release identifiers. For openssl, the relation

 $1.0.1 < 1.0.1a \Rightarrow$ False # should be true for openssl

holds, whereas conda packages use the opposite ordering. You can work-around this problem by appending an underscore to plain version numbers:

1.0.1 < 1.0.1a => True # ensure correct ordering for openssl

cache

__str__() → str Return str(self).

Return str(sen).

__repr__() \rightarrow str

Return repr(self).

 $_eq(t1: list[str], t2: list[str]) \rightarrow bool$

 $__eq_(other: object) → bool$ Return self==value.

startswith(*other: object*) \rightarrow bool

```
\__ne\_(other: object) \rightarrow bool
Return self!=value.
```

```
__lt_(other: object) → bool
Return self<value.
```

```
__gt__(other: object) \rightarrow bool
```

Return self>value.

__le__(*other: object*) \rightarrow bool

Return self<=value.

```
__ge__(other: object) \rightarrow bool
```

Return self>=value.

VSPEC_TOKENS = '\\s*\\^[^\$]*[\$]|\\s*[()|,]|[^()|,]+'

treeify(spec_str)

Examples

```
>>> treeify("1.2.3")
'1.2.3'
>>> treeify("1.2.3,>4.5.6")
(',', '1.2.3', '>4.5.6')
>>> treeify("1.2.3,4.5.6|<=7.8.9")
('|', (',', '1.2.3', '4.5.6'), '<=7.8.9')
>>> treeify("(1.2.3|4.5.6),<=7.8.9")
(',', ('|', '1.2.3', '4.5.6'), '<=7.8.9')
>>> treeify("((1.5|((1.6|1.7), 1.8), 1.9 |2.0))|2.1")
('|', '1.5', (',', ('|', '1.6', '1.7'), '1.8', '1.9'), '2.0', '2.1')
>>> treeify("1.5|(1.6|1.7), 1.8,1.9|2.0|2.1")
('|', '1.5', (',', ('|', '1.6', '1.7'), '1.8', '1.9'), '2.0', '2.1')
```

untreeify(spec, _inand=False, depth=0)

Examples

```
>>> untreeify('1.2.3')
'1.2.3'
>>> untreeify((',', '1.2.3', '>4.5.6'))
'1.2.3,>4.5.6'
>>> untreeify(('|', (',', '1.2.3', '4.5.6'), '<=7.8.9'))
'(1.2.3,4.5.6)|<=7.8.9'
>>> untreeify((',', ('|', '1.2.3', '4.5.6'), '<=7.8.9'))
'(1.2.3|4.5.6),<=7.8.9'
>>> untreeify(('|', '1.5', (',', ('|', '1.6', '1.7'), '1.8', '1.9'), '2.0', '2.1'))
'1.5|((1.6|1.7),1.8,1.9)|2.0|2.1'
```

compatible_release_operator(x, y)

version_relation_re

regex_split_re

OPERATOR_MAP

OPERATOR_START

class BaseSpec(spec_str, matcher, is_exact)

property spec

property raw_value

property exact_value

is_exact()

___eq__(*other*)

Return self==value.

__ne__(other)

Return self!=value.

__hash__()

Return hash(self).

__str__()

Return str(self).

__repr__()

Return repr(self).

abstract merge(other)

regex_match(spec_str)

operator_match(spec_str)

any_match(spec_str)

all_match(spec_str)

exact_match(spec_str)

always_true_match(spec_str)

class VersionSpec(vspec)

Bases: BaseSpec

cache

get_matcher(vspec)

merge(other)

union(other)

VersionMatch

class BuildNumberMatch(vspec)

Bases: BaseSpec

property exact_value: int | None

cache

get_matcher(vspec)

merge(other)

union(other)

__str__()

Return str(self).

__repr__()

Return repr(self).

notices

cache

Handles all caching logic including:

• Retrieving from cache

10

- Saving to cache
- Determining whether not certain items have expired and need to be refreshed

Functions

. .

cached_response(func)	
$is_notice_response_cache_expired(\rightarrow bool)$	This checks the contents of the cache response to see if it is expired.
$get_notices_cache_dir(\rightarrow pathlib.Path)$	Returns the location of the notices cache directory as a Path object
$get_notices_cache_file(\rightarrow pathlib.Path)$	Returns the location of the notices cache file as a Path object
<pre>get_notice_response_from_cache()</pre>	Retrieves a notice response object from cache if it exists.
write_notice_response_to_cache(\rightarrow None)	Writes our notice data to our local cache location.
$mark_channel_notices_as_viewed(\rightarrow None)$	Insert channel notice into our database marking it as read.
$get_viewed_channel_notice_ids(\rightarrow set[str])$	Return the ids of the channel notices which have already been seen.

Attributes

logger

logger

```
cached_response(func)
```

```
\label{eq:sponse_cache_expired} is\_notice\_response: \ conda.notices.types.ChannelNoticeResponse) \\ \rightarrow bool
```

This checks the contents of the cache response to see if it is expired.

If for whatever reason we encounter an exception while parsing the individual messages, we assume an invalid cache and return true.

get_notices_cache_dir() \rightarrow pathlib.Path

Returns the location of the notices cache directory as a Path object

$\texttt{get_notices_cache_file()} \rightarrow \texttt{pathlib.Path}$

Returns the location of the notices cache file as a Path object

get_notice_response_from_cache(url: str, name: str, cache_dir: pathlib.Path) \rightarrow conda.notices.types.ChannelNoticeResponse | None

Retrieves a notice response object from cache if it exists.

 $write_notice_response_to_cache(channel_notice_response: conda.notices.types.ChannelNoticeResponse, cache_dir: pathlib.Path) \rightarrow None$

Writes our notice data to our local cache location.

 $\label{eq:mark_channel_notices_as_viewed} (cache_file: pathlib.Path, channel_notices: Sequence[conda.notices.types.ChannelNotice]) \rightarrow \end{tabular} None$

Insert channel notice into our database marking it as read.

Return the ids of the channel notices which have already been seen.

core

Core conda notices logic.

Functions

<pre>retrieve_notices()</pre>	Function used for retrieving notices. This is called by the "notices" decorator as well
$display_notices(\rightarrow None)$	Prints the channel notices to std out.
<pre>notices(func)</pre>	Wrapper for "execute" entry points for subcommands.
get_channel_name_and_urls(\rightarrow	Return a sequence of Channel URL and name tuples.
list[tuple[ChannelUrl,)	
<pre>flatten_notice_responses()</pre>	
<pre>filter_notices()</pre>	Perform filtering actions for the provided sequence of
	ChannelNotice objects.
$is_channel_notices_enabled(\rightarrow bool)$	Determines whether channel notices are enabled and
	therefore displayed when
$is_channel_notices_cache_expired(\rightarrow bool)$	Checks to see if the notices cache file we use to keep track of

Attributes

ChannelName	
ChannelUrl	
logger	

ChannelName

ChannelUrl

logger

```
retrieve_notices(limit: int | None = None, always_show_viewed: bool = True, silent: bool = False) \rightarrow conda.notices.types.ChannelNoticeResultSet
```

Function used for retrieving notices. This is called by the "notices" decorator as well as the sub-command "notices"

Parameters

- limit -- Limit the number of notices to show (defaults to None).
- **always_show_viewed** -- Whether all notices should be shown, not only the unread ones (defaults to True).
- **silent** -- Whether to use a spinner when fetching and caching notices.

display_notices(*channel_notice_set:* conda.notices.types.ChannelNoticeResultSet) \rightarrow None

Prints the channel notices to std out.

notices(func)

Wrapper for "execute" entry points for subcommands.

If channel notices need to be fetched, we do that first and then run the command normally. We then display these notices at the very end of the command output so that the user is more likely to see them.

This ordering was specifically done to address the following bug report:

• https://github.com/conda/conda/issues/11847

Parameters

func -- Function to be decorated

get_channel_name_and_urls(channels: Sequence[conda.models.channel.Channel |

conda.models.channel.MultiChannel/) \rightarrow list[tuple[ChannelUrl, ChannelName]]

Return a sequence of Channel URL and name tuples.

This function handles both Channel and MultiChannel object types.

flatten_notice_responses(channel_notice_responses:

Sequence[conda.notices.types.ChannelNoticeResponse]) → Sequence[conda.notices.types.ChannelNotice]

filter_notices(channel_notices: Sequence[conda.notices.types.ChannelNotice], limit: int | None = None, exclude: set[str] | None = None) → Sequence[conda.notices.types.ChannelNotice]

Perform filtering actions for the provided sequence of ChannelNotice objects.

is_channel_notices_enabled(ctx: conda.base.context.Context) \rightarrow bool

Determines whether channel notices are enabled and therefore displayed when invoking the *notices* command decorator.

This only happens when:

- offline is False
- number_channel_notices is greater than 0

Parameters

ctx -- The conda context object

$\texttt{is_channel_notices_cache_expired()} \rightarrow \texttt{bool}$

Checks to see if the notices cache file we use to keep track of displayed notices is expired. This involves checking the mtime attribute of the file. Anything older than what is specified as the NO-TICES_DECORATOR_DISPLAY_INTERVAL is considered expired.

fetch

Notices network fetch logic.

Functions

<pre>get_notice_responses()</pre>	Provided a list of channel notification url/name tuples, return a sequence of
<pre>get_channel_notice_response()</pre>	Return a channel response object. We use this to wrap the response with

Attributes

logger

logger

get_notice_responses(url_and_names: Sequence[tuple[str, str]], silent: bool = False, max_workers: int = 10) → Sequence[conda.notices.types.ChannelNoticeResponse]

Provided a list of channel notification url/name tuples, return a sequence of ChannelNoticeResponse objects.

Parameters

- url_and_names -- channel url and the channel name
- **silent** -- turn off "loading animation" (defaults to False)
- **max_workers** -- increase worker number in thread executor (defaults to 10)

Returns

Sequence[ChannelNoticeResponse]

get_channel_notice_response(url: str, name: str) \rightarrow conda.notices.types.ChannelNoticeResponse | None

Return a channel response object. We use this to wrap the response with additional channel information to use. If the response was invalid we suppress/log and error message.

types

Implements all conda.notices types.

Classes

ChannelNotice	Represents an individual channel notice.
ChannelNoticeResultSet	Represents a list of a channel notices, plus some accompanying
ChannelNoticeResponse	

Attributes

UNDEFINED_MESSAGE_ID

UNDEFINED_MESSAGE_ID = 'undefined'

class ChannelNotice

Bases: NamedTuple

Represents an individual channel notice.

id: str

channel_name: str | None

message: str | None

level: conda.base.constants.NoticeLevel

created_at: datetime.datetime | None

expired_at: datetime.datetime | None

interval: int | None

to_dict()

class ChannelNoticeResultSet

Bases: NamedTuple

Represents a list of a channel notices, plus some accompanying metadata such as viewed_channel_notices.

channel_notices: Sequence[ChannelNotice]

total_number_channel_notices: int

viewed_channel_notices: int

class ChannelNoticeResponse

Bases: NamedTuple

property notices: Sequence[ChannelNotice]
url: str
name: str
json_data: dict | None
static _parse_notice_level(level: str | None) → conda.base.constants.NoticeLevel
We use this to validate notice levels and provide reasonable defaults if any are invalid.
static _parse_iso_timestamp(iso_timestamp: str | None) → datetime.datetime | None
Parse ISO timestamp and fail over to a default value of none.

classmethod get_cache_key(*url: str, cache_dir: pathlib.Path*) \rightarrow pathlib.Path Returns where this channel response will be cached by hashing the URL.

views

Handles all display/view logic.

Functions

<pre>print_notices(channel_notices)</pre>	Accepts a list of channel notice responses and prints a display.
$print_notice_message(\rightarrow None)$	Prints a single channel notice.
$print_more_notices_message(\rightarrow None)$	Conditionally shows a message informing users how many more message there are.

print_notices(channel_notices: Sequence[conda.notices.types.ChannelNotice])

Accepts a list of channel notice responses and prints a display.

Parameters channel_notices -- A sequence of ChannelNotice objects.

- print_notice_message(*notice:* conda.notices.types.ChannelNotice, *indent:* str = ' ') \rightarrow None Prints a single channel notice.
- print_more_notices_message(total_notices: int, displayed_notices: int, viewed_notices: int) \rightarrow None Conditionally shows a message informing users how many more message there are.

Functions

notices(func)

Wrapper for "execute" entry points for subcommands.

notices(func)

Wrapper for "execute" entry points for subcommands.

If channel notices need to be fetched, we do that first and then run the command normally. We then display these notices at the very end of the command output so that the user is more likely to see them.

This ordering was specifically done to address the following bug report:

• https://github.com/conda/conda/issues/11847

Parameters

func -- Function to be decorated

plan

Handle the planning of installs and their execution.

Note: conda.install uses canonical package names in its interface functions, whereas conda.resolve uses package filenames, as those are used as index keys. We try to keep fixes to this "impedance mismatch" local to this module.

Functions

<pre>print_dists(dists_extras)</pre>	
display_actionsindexshow_channel_urls,])add_unlink(actions, dist)	[,
<pre>add_defaults_to_specs(r, linked, specs[, updat prefix])</pre>	e,
<pre>_get_best_prec_match(precs)</pre>	
<pre>revert_actions(prefix[, revision, index])</pre>	
<pre>execute_actions(actions, index[, verbose])</pre>	
_plan_from_actions(actions, index)	
<pre>_inject_UNLINKLINKTRANSACTION(plan, index, pr fix,)</pre>	е-
<pre>_handle_menuinst(unlink_dists, link_dists)</pre>	
<pre>install_actions(prefix, index, specs[, force,])</pre>	
<pre>get_blank_actions(prefix)</pre>	
<pre>execute_plan(old_plan[, index, verbose])</pre>	Deprecated: This should conda.instructions.execute_instructions instead.
<pre>execute_instructions(plan[, index, verbose, _cor mands])</pre>	n- Execute the instructions in the plan
_update_old_plan(old_plan)	Update an old plan object to work with

print_dists(dists_extras)

display_actions(*actions*, *index*, *show_channel_urls=None*, *specs_to_remove=()*, *specs_to_add=()*)

add_unlink(actions, dist)

add_defaults_to_specs(r, linked, specs, update=False, prefix=None)

_get_best_prec_match(precs)

revert_actions(prefix, revision=-1, index=None)

execute_actions(actions, index, verbose=False)

_plan_from_actions(actions, index)

_inject_UNLINKLINKTRANSACTION(plan, index, prefix, axn, specs)

_handle_menuinst(unlink_dists, link_dists)

get_blank_actions(prefix)

execute_plan(old_plan, index=None, verbose=False)

Deprecated: This should conda.instructions.execute_instructions instead.

execute_instructions(plan, index=None, verbose=False, _commands=None)

Execute the instructions in the plan

Parameters

- plan -- A list of (instruction, arg) tuples
- index -- The meta-data index
- verbose -- verbose output
- _commands -- (For testing only) dict mapping an instruction to executable if None

then the default commands will be used

_update_old_plan(old_plan)

Update an old plan object to work with conda.instructions.execute_instructions

plugins

In this module, you will find everything relevant to conda's plugin system. It contains all of the code that plugin authors will use to write plugins, as well as conda's internal implementations of plugins.

Modules relevant for plugin authors

- *conda.plugins.hookspec*: all available hook specifications are listed here, including examples of how to use them
- conda.plugins.types: important types to use when defining plugin hooks

Modules relevant for internal development

conda.plugins.manager: includes our custom subclass of pluggy's PluginManager class

Modules with internal plugin implementations

• conda.plugins.solvers: implementation of the "classic" solver

- conda.plugins.subcommands.doctor: conda doctor subcommand
- conda.plugins.virtual_packages: registers virtual packages in conda

hookspec

Pluggy hook specifications ("hookspecs") to register conda plugins.

Each hookspec defined in *CondaSpecs* contains an example of how to use it.

Classes

	CondaSpecs	The conda plugin hookspecs, to be used by developers.
--	------------	---

Attributes

spec_name	Name used for organizing conda hook specifications
_hookspec	The conda plugin hook specifications, to be used by de- velopers
hookimpl	Decorator used to mark plugin hook implementations

spec_name = 'conda'

Name used for organizing conda hook specifications

_hookspec

The conda plugin hook specifications, to be used by developers

hookimpl

Decorator used to mark plugin hook implementations

class CondaSpecs

The conda plugin hookspecs, to be used by developers.

```
conda\_solvers() \rightarrow collections.abc.Iterable[conda.plugins.types.CondaSolver]
```

Register solvers in conda.

Example:

```
import logging
from conda import plugins
from conda.core import solve
log = logging.getLogger(__name__)
class VerboseSolver(solve.Solver):
    def solve_final_state(self, *args, **kwargs):
        log.info("My verbose solver!")
        return super().solve_final_state(*args, **kwargs)
```

(continues on next page)

```
@plugins.hookimpl
def conda_solvers():
    yield plugins.CondaSolver(
        name="verbose-classic",
        backend=VerboseSolver,
        )
```

Returns

An iterable of solver entries.

 $conda_subcommands() \rightarrow collections.abc.Iterable[conda.plugins.types.CondaSubcommand]$

Register external subcommands in conda.

Example:

```
from conda import plugins

def example_command(args):
    print("This is an example command!")

@plugins.hookimpl
def conda_subcommands():
    yield plugins.CondaSubcommand(
        name="example",
        summary="example command",
        action=example_command,
    )
```

Returns

An iterable of subcommand entries.

 $\texttt{conda_virtual_packages()} \rightarrow \texttt{collections.abc.Iterable[} \textit{conda.plugins.types.CondaVirtualPackage]}$

Register virtual packages in Conda.

Example:

```
from conda import plugins
@plugins.hookimpl
def conda_virtual_packages():
    yield plugins.CondaVirtualPackage(
        name="my_custom_os",
        version="1.2.3",
        build="x86_64",
        )
```

Returns

An iterable of virtual package entries.

conda_pre_commands() \rightarrow collections.abc.Iterable[*conda.plugins.types.CondaPreCommand*]

Register pre-command functions in conda.

Example:

```
from conda import plugins

def example_pre_command(command):
    print("pre-command action")

@plugins.hookimpl
def conda_pre_commands():
    yield plugins.CondaPreCommand(
        name="example-pre-command,
        action=example_pre_command,
        run_for={"install", "create"},
    )
```

 $conda_post_commands() \rightarrow collections.abc.Iterable[conda.plugins.types.CondaPostCommand]$

Register post-command functions in conda.

Example:

```
from conda import plugins

def example_post_command(command):
    print("post-command action")

@plugins.hookimpl
def conda_post_commands():
    yield plugins.CondaPostCommand(
        name="example-post-command",
        action=example_post_command,
        run_for={"install", "create"},
    )
```

 $conda_auth_handlers() \rightarrow collections.abc.Iterable[conda.plugins.types.CondaAuthHandler]$

Register a conda auth handler derived from the requests API.

This plugin hook allows attaching requests auth handler subclasses, e.g. when authenticating requests against individual channels hosted at HTTP/HTTPS services.

Example:

```
import os
from conda import plugins
from requests.auth import AuthBase
```

(continues on next page)

```
class EnvironmentHeaderAuth(AuthBase):
    def __init__(self, *args, **kwargs):
        self.username = os.environ["EXAMPLE_CONDA_AUTH_USERNAME"]
        self.password = os.environ["EXAMPLE_CONDA_AUTH_PASSWORD"]
    def __call__(self, request):
        request.headers["X-Username"] = self.username
        request.headers["X-Password"] = self.password
        return request
@plugins.hookimpl
def conda_auth_handlers():
    yield plugins.CondaAuthHandler(
        name="environment-header-auth",
        auth_handler=EnvironmentHeaderAuth,
    )
```

 $conda_health_checks() \rightarrow collections.abc.Iterable[conda.plugins.types.CondaHealthCheck]$

Register health checks for conda doctor.

This plugin hook allows you to add more "health checks" to conda doctor that you can write to diagnose problems in your conda environment. Check out the health checks already shipped with conda for inspiration.

Example:

```
from conda import plugins

def example_health_check(prefix: str, verbose: bool):
    print("This is an example health check!")

@plugins.hookimpl
def conda_health_checks():
    yield plugins.CondaHealthCheck(
        name="example-health-check",
        action=example_health_check,
    )
```

conda_pre_solves() → collections.abc.Iterable[*conda.plugins.types.CondaPreSolve*]

Register pre-solve functions in conda that are used in the general solver API, before the solver processes the package specs in search of a solution.

Example:

```
from conda import plugins
from conda.models.match_spec import MatchSpec
def example_pre_solve(
```

(continues on next page)

```
specs_to_add: frozenset[MatchSpec],
    specs_to_remove: frozenset[MatchSpec],
):
    print(f"Adding {len(specs_to_add)} packages")
    print(f"Removing {len(specs_to_remove)} packages")
@plugins.hookimpl
def conda_pre_solves():
    yield plugins.CondaPreSolve(
        name="example-pre-solve",
        action=example_pre_solve,
    )
```

conda_post_solves() → collections.abc.Iterable[*conda.plugins.types.CondaPostSolve*]

Register post-solve functions in conda that are used in the general solver API, after the solver has provided the package records to add or remove from the conda environment.

Example:

```
from conda import plugins
from conda.models.records import PackageRecord

def example_post_solve(
    repodata_fn: str,
    unlink_precs: tuple[PackageRecord, ...],
    link_precs: tuple[PackageRecord, ...],
):
    print(f"Uninstalling {len(unlink_precs)} packages")
    print(f"Installing {len(link_precs)} packages")

@plugins.hookimpl
def conda_post_solves():
    yield plugins.CondaPostSolve(
        name="example-post_solve,
        )
```

conda_settings() → collections.abc.Iterable[*conda.plugins.types.CondaSetting*]

Register new setting

The example below defines a simple string type parameter

Example:

```
yield plugins.CondaSetting(
    name="example_option",
    description="This is an example option",
    parameter=PrimitiveParameter("default_value", element_type=str),
    aliases=("example_option_alias",),
)
```

manager

This module contains a subclass implementation of pluggy's PluginManager.

Additionally, it contains a function we use to construct the PluginManager object and register all plugins during conda's startup process.

Classes

CondaPluginManager	The conda plugin manager to implement behavior addi-
	tional to pluggy's default plugin manager.

Functions

$get_plugin_manager(\rightarrow CondaPluginManager)$	Get a cached version of the CondaPluginManager in-
	stance,

class CondaPluginManager(project_name: str | None = None, *args, **kwargs)

Bases: pluggy.PluginManager

The conda plugin manager to implement behavior additional to pluggy's default plugin manager.

get_cached_solver_backend

```
get_canonical_name(plugin: object) \rightarrow str
```

Return a canonical name for a plugin object.

Note that a plugin may be registered under a different name specified by the caller of *register(plugin, name)*. To obtain the name of a registered plugin use get_name(plugin) instead.

register(*plugin*, *name: str* | *None* = *None*) \rightarrow str | None

Call pluggy.PluginManager.register() and return the result or ignore errors raised, except ValueError, which means the plugin had already been registered.

load_plugins(**plugins*) \rightarrow int

Load the provided list of plugins and fail gracefully on error. The provided list of plugins can either be classes or modules with *hookimpl*.

load_entrypoints(group: str, name: str | None = None) \rightarrow int

Load modules from querying the specified setuptools group.

Parameters
- group (str) -- Entry point group to load plugins.
- **name** (*str*) -- If given, loads only plugins with the given name.

Return type

int

Returns

The number of plugins loaded by this call.

get_hook_results(name: Literal[conda.plugins.subcommands]) \rightarrow list[conda.plugins.types.CondaSubcommand]

get_hook_results(name: Literal[conda.plugins.virtual_packages]) → list[conda.plugins.types.CondaVirtualPackage]

 $get_hook_results(name: Literal[conda.plugins.solvers]) \rightarrow list[conda.plugins.types.CondaSolver]$

 $get_hook_results(name: Literal[pre_commands]) \rightarrow list[conda.plugins.types.CondaPreCommand]$

 $get_hook_results(name: Literal[post_commands]) \rightarrow list[conda.plugins.types.CondaPostCommand]$

 $get_hook_results(name: Literal[auth_handlers]) \rightarrow list[conda.plugins.types.CondaAuthHandler]$

get_hook_results(name: Literal[conda.plugins.subcommands.doctor.health_checks]) \rightarrow list[conda.plugins.types.CondaHealthCheck]

 $get_hook_results(name: Literal[pre_solves]) \rightarrow list[conda.plugins.types.CondaPreSolve]$

- $get_hook_results(name: Literal[conda.plugins.post_solves]) \rightarrow list[conda.plugins.types.CondaPostSolve]$
- $\texttt{get_hook_results}(\textit{name: Literal[settings]}) \rightarrow \texttt{list}[\textit{conda.plugins.types.CondaSetting}]$

Return results of the plugin hooks with the given name and raise an error if there is a conflict.

- get_solvers() \rightarrow dict[str, *conda.plugins.types.CondaSolver*] Return a mapping from solver name to solver class.
- get_solver_backend(name: str | None = None) \rightarrow type[conda.core.solve.Solver]

Get the solver backend with the given name (or fall back to the name provided in the context).

See context.solver for more details.

Please use the cached version of this method called *get_cached_solver_backend()* for high-throughput code paths which is set up as a instance-specific LRU cache.

get_auth_handler(*name: str*) \rightarrow type[requests.auth.AuthBase] | None Get the auth handler with the given name or None

 $get_settings() \rightarrow dict[str, conda.common.configuration.ParameterLoader]$

Return a mapping of plugin setting name to ParameterLoader class

This method intentionally overwrites any duplicates that may be present

```
invoke_pre_commands(command: str) \rightarrow None
```

Invokes CondaPreCommand.action functions registered with conda_pre_commands.

Parameters

command -- name of the command that is currently being invoked

invoke_post_commands(*command: str*) → None

Invokes CondaPostCommand.action functions registered with conda_post_commands.

Parameters

command -- name of the command that is currently being invoked

$\texttt{disable_external_plugins()} \rightarrow None$

Disables all currently registered plugins except built-in conda plugins

 $get_subcommands() \rightarrow dict[str, conda.plugins.types.CondaSubcommand]$

get_virtual_packages() \rightarrow tuple[conda.plugins.types.CondaVirtualPackage, Ellipsis]

invoke_health_checks(*prefix: str, verbose: bool*) \rightarrow None

invoke_pre_solves(*specs_to_add: frozenset*[conda.models.match_spec.MatchSpec], *specs_to_remove: frozenset*[conda.models.match_spec.MatchSpec]) → None

Invokes CondaPreSolve.action functions registered with conda_pre_solves.

Parameters

- specs_to_add
- specs_to_remove

invoke_post_solves(repodata_fn: str, unlink_precs: tuple[conda.models.records.PackageRecord, Ellipsis], link_precs: tuple[conda.models.records.PackageRecord, Ellipsis]) → None

Invokes CondaPostSolve.action functions registered with conda_post_solves.

Parameters

- repodata_fn
- unlink_precs
- link_precs

$\texttt{load_settings()} \rightarrow None$

Iterates through all registered settings and adds them to the conda.common.configuration. PluginConfig class.

$get_plugin_manager() \rightarrow CondaPluginManager$

Get a cached version of the *CondaPluginManager* instance, with the built-in and entrypoints provided by the plugins loaded.

post_solves

Register the built-in post_solves hook implementations.

signature_verification

Register signature verification as a post-solve plugin.

conda_post_solves()

conda_post_solves()

plugins

solvers

Register the classic conda solver.

Functions

conda_solvers()

The classic solver as shipped by default in conda.

conda_solvers()

The classic solver as shipped by default in conda.

subcommands

doctor

Implementation for *conda doctor* subcommand. Adds various environment and package checks to detect issues or possible environment corruption.

health_checks

Backend logic implementation for conda doctor.

$display_report_heading(\rightarrow None)$	Displays our report heading.
$check_envs_txt_file(\rightarrow bool)$	Checks whether the environment is listed in the environ- ments.txt file
<pre>find_packages_with_missing_files(\rightarrow dict[str, list[str]])</pre>	Finds packages listed in conda-meta which have missing files.
$find_altered_packages(\rightarrow dict[str, list[str]])$	Finds altered packages
$display_health_checks(\rightarrow None)$	Prints health report.
$missing_files(\rightarrow None)$	
$altered_files(\rightarrow None)$	
$env_txt_check(\rightarrow None)$	
<pre>conda_health_checks()</pre>	

Attributes

logger		
OK_MARK		
X_MARK		

logger

OK_MARK = ''

X_MARK = ''

display_report_heading(prefix: str) \rightarrow None

Displays our report heading.

- **check_envs_txt_file**(*prefix: str* | *os.PathLike* | *pathlib.Path*) \rightarrow bool Checks whether the environment is listed in the environments.txt file
- **find_packages_with_missing_files**(*prefix: str* | *pathlib.Path*) \rightarrow dict[str, list[str]] Finds packages listed in conda-meta which have missing files.
- **find_altered_packages**(*prefix: str* | *pathlib.Path*) \rightarrow dict[str, list[str]] Finds altered packages
- **display_health_checks**(*prefix: str, verbose: bool* = *False*) \rightarrow None Prints health report.
- **missing_files**(*prefix: str, verbose: bool*) \rightarrow None
- altered_files(prefix: str, verbose: bool) \rightarrow None

env_txt_check(*prefix: str, verbose: bool*) \rightarrow None

conda_health_checks()

Classes

CondaSubcommand	Return type to use when defining a conda subcommand
	plugin hook.

Functions

$add_parser_help(\rightarrow None)$		So we can use consistent capitalization and periods in the help. You must
add_parser_prefix(→ parseMutuallyExclusiveGroup)	arg-	
$add_parser_verbose(\rightarrow None)$		
$get_prefix(\rightarrow str)$		
<pre>configure_parser(parser)</pre>		
$execute(\rightarrow None)$		Run registered health_check plugins.
conda_subcommands()		

Attributes

context	
deprecated	
hookimpl	Decorator used to mark plugin hook implementations

context

add_parser_help(*p*: *argparse*.*ArgumentParser*) → None

So we can use consistent capitalization and periods in the help. You must use the add_help=False argument to ArgumentParser or add_parser to use this. Add this first to be consistent with the default argparse output.

add_parser_prefix(*p*: argparse.ArgumentParser, prefix_required: bool = False) \rightarrow argparse._MutuallyExclusiveGroup

 $add_parser_verbose(parser: argparse.ArgumentParser | argparse.ArgumentGroup) \rightarrow None$

deprecated

class CondaSubcommand

Return type to use when defining a conda subcommand plugin hook.

For details on how this is used, see conda_subcommands().

Parameters

- name -- Subcommand name (e.g., conda my-subcommand-name).
- summary -- Subcommand summary, will be shown in conda --help.
- action -- Callable that will be run when the subcommand is invoked.
- configure_parser -- Callable that will be run when the subcommand parser is initialized.

```
name: str
```

```
summary: str
```

```
action: Callable[[argparse.Namespace | tuple[str]], int | None]
```

configure_parser: Callable[[argparse.ArgumentParser], None] | None

hookimpl

Decorator used to mark plugin hook implementations

```
get_prefix(args: argparse.Namespace) \rightarrow str
```

configure_parser(parser: argparse.ArgumentParser)

execute(*args: argparse.Namespace*) \rightarrow None

Run registered health_check plugins.

 $conda_subcommands()$

plugins

types

Definition of specific return types for use when defining a conda plugin hook.

Each type corresponds to the plugin hook for which it is used.

Classes

CondaSubcommand	Return type to use when defining a conda subcommand plugin hook.
CondaVirtualPackage	Return type to use when defining a conda virtual package plugin hook.
CondaSolver	Return type to use when defining a conda solver plugin hook.
CondaPreCommand	Return type to use when defining a conda pre-command plugin hook.
CondaPostCommand	Return type to use when defining a conda post-command plugin hook.
ChannelNameMixin	Class mixin to make all plugin implementations compat- ible, e.g. when they
ChannelAuthBase	Base class that we require all plugin implementations to use to be compatible.
CondaAuthHandler	Return type to use when the defining the conda auth han- dlers hook.
CondaHealthCheck	Return type to use when defining conda health checks plugin hook.
CondaPreSolve	Return type to use when defining a conda pre-solve plu- gin hook.
CondaPostSolve	Return type to use when defining a conda post-solve plu- gin hook.
CondaSetting	Return type to use when defining a conda setting plugin hook.

class CondaSubcommand

Return type to use when defining a conda subcommand plugin hook.

For details on how this is used, see *conda_subcommands()*.

Parameters

- name -- Subcommand name (e.g., conda my-subcommand-name).
- summary -- Subcommand summary, will be shown in conda --help.
- action -- Callable that will be run when the subcommand is invoked.
- configure_parser -- Callable that will be run when the subcommand parser is initialized.

```
name: str
```

```
summary: str
```

action: Callable[[argparse.Namespace | tuple[str]], int | None]

configure_parser: Callable[[argparse.ArgumentParser], None] | None

class CondaVirtualPackage

Bases: NamedTuple

Return type to use when defining a conda virtual package plugin hook.

For details on how this is used, see *conda_virtual_packages()*.

Parameters

- name -- Virtual package name (e.g., my_custom_os).
- version -- Virtual package version (e.g., 1.2.3).
- **build** -- Virtual package build string (e.g., x86_64).

name: str

version: str | None

build: str | None

class CondaSolver

Bases: NamedTuple

Return type to use when defining a conda solver plugin hook.

For details on how this is used, see *conda_solvers()*.

Parameters

- **name** -- Solver name (e.g., custom-solver).
- **backend** -- Type that will be instantiated as the solver backend.

name: str

backend: type[conda.core.solve.Solver]

class CondaPreCommand

Bases: NamedTuple

Return type to use when defining a conda pre-command plugin hook.

For details on how this is used, see *conda_pre_commands()*.

Parameters

- **name** -- Pre-command name (e.g., custom_plugin_pre_commands).
- action -- Callable which contains the code to be run.
- **run_for** -- Represents the command(s) this will be run on (e.g. install or create).

name: str

action: Callable[[str], None]

run_for: set[str]

class CondaPostCommand

Bases: NamedTuple

Return type to use when defining a conda post-command plugin hook.

For details on how this is used, see conda_post_commands().

Parameters

- name -- Post-command name (e.g., custom_plugin_post_commands).
- action -- Callable which contains the code to be run.
- **run_for** -- Represents the command(s) this will be run on (e.g. install or create).

name: str

action: Callable[[str], None]

run_for: set[str]

class ChannelNameMixin(channel_name: str, *args, **kwargs)

Class mixin to make all plugin implementations compatible, e.g. when they use an existing (e.g. 3rd party) requests authentication handler.

Please use the concrete ChannelAuthBase in case you're creating an own implementation.

class ChannelAuthBase(channel_name: str, *args, **kwargs)

Bases: ChannelNameMixin, requests.auth.AuthBase

Base class that we require all plugin implementations to use to be compatible.

Authentication is tightly coupled with individual channels. Therefore, an additional channel_name property must be set on the requests.auth.AuthBase based class.

class CondaAuthHandler

Bases: NamedTuple

Return type to use when the defining the conda auth handlers hook.

Parameters

- **name** -- Name (e.g., basic-auth). This name should be unique and only one may be registered at a time.
- handler -- Type that will be used as the authentication handler during network requests.

name: str

handler: type[ChannelAuthBase]

class CondaHealthCheck

Bases: NamedTuple

Return type to use when defining conda health checks plugin hook.

name: str

action: Callable[[str, bool], None]

class CondaPreSolve

Return type to use when defining a conda pre-solve plugin hook.

For details on how this is used, see *conda_pre_solves()*.

Parameters

- **name** -- Pre-solve name (e.g., custom_plugin_pre_solve).
- action -- Callable which contains the code to be run.

name: str

action: Callable[[frozenset[conda.models.match_spec.MatchSpec],
frozenset[conda.models.match_spec.MatchSpec]], None]

class CondaPostSolve

Return type to use when defining a conda post-solve plugin hook.

For details on how this is used, see *conda_post_solves()*.

Parameters

- **name** -- Post-solve name (e.g., custom_plugin_post_solve).
- action -- Callable which contains the code to be run.

```
name: str
```

```
action: Callable[[str, tuple[conda.models.records.PackageRecord, Ellipsis],
tuple[conda.models.records.PackageRecord, Ellipsis]], None]
```

class CondaSetting

Return type to use when defining a conda setting plugin hook.

For details on how this is used, see conda_settings().

Parameters

- **name** -- name of the setting (e.g., config_param)
- description -- description of the setting that should be targeted towards users of the plugin
- parameter -- Parameter instance containing the setting definition
- aliases -- alternative names of the setting

name: str

```
description: str
```

parameter: conda.common.configuration.Parameter

```
aliases: tuple[str, Ellipsis]
```

virtual_packages

archspec

Detect archspec name.

Functions

conda_virtual_packages()

conda_virtual_packages()

conda

Expose conda version.

Functions

conda_virtual_packages()

conda_virtual_packages()

cuda

Detect CUDA version.

Functions

<pre>cuda_version()</pre>	Attempt to detect the version of CUDA present in the operating system.
<pre>cached_cuda_version()</pre>	A cached version of the cuda detection system.
<pre>conda_virtual_packages()</pre>	
<pre>_cuda_driver_version_detector_target(queue)</pre>	Attempt to detect the version of CUDA present in the operating system in a

cuda_version()

Attempt to detect the version of CUDA present in the operating system.

On Windows and Linux, the CUDA library is installed by the NVIDIA driver package, and is typically found in the standard library path, rather than with the CUDA SDK (which is optional for running CUDA apps).

On macOS, the CUDA library is only installed with the CUDA SDK, and might not be in the library path.

Returns: version string (e.g., '9.2') or None if CUDA is not found.

cached_cuda_version()

A cached version of the cuda detection system.

conda_virtual_packages()

_cuda_driver_version_detector_target(queue)

Attempt to detect the version of CUDA present in the operating system in a subprocess.

On Windows and Linux, the CUDA library is installed by the NVIDIA driver package, and is typically found in the standard library path, rather than with the CUDA SDK (which is optional for running CUDA apps).

On macOS, the CUDA library is only installed with the CUDA SDK, and might not be in the library path.

Returns: version string (e.g., '9.2') or None if CUDA is not found.

The result is put in the queue rather than a return value.

freebsd

Detect whether this is FeeBSD.

Functions

conda_virtual_packages()

conda_virtual_packages()

linux

Detect whether this is Linux.

Functions

conda_virtual_packages()

conda_virtual_packages()

osx

Detect whether this is macOS.

Functions

conda_virtual_packages()

conda_virtual_packages()

windows

Detect whether this is Windows.

conda_virtual_packages()

conda_virtual_packages()

plugins

Classes

CondaAuthHandler	Return type to use when the defining the conda auth han- dlers hook.
CondaHealthCheck	Return type to use when defining conda health checks plugin hook.
CondaPostCommand	Return type to use when defining a conda post-command plugin hook.
CondaPostSolve	Return type to use when defining a conda post-solve plu- gin hook.
CondaPreCommand	Return type to use when defining a conda pre-command plugin hook.
CondaPreSolve	Return type to use when defining a conda pre-solve plu- gin hook.
CondaSetting	Return type to use when defining a conda setting plugin hook.
CondaSolver	Return type to use when defining a conda solver plugin hook.
CondaSubcommand	Return type to use when defining a conda subcommand plugin hook.
CondaVirtualPackage	Return type to use when defining a conda virtual package plugin hook.

Attributes

hookimpl	Decorator used to mark plugin hook implementations
----------	--

hookimpl

Decorator used to mark plugin hook implementations

class CondaAuthHandler

Bases: NamedTuple

Return type to use when the defining the conda auth handlers hook.

Parameters

• **name** -- Name (e.g., basic-auth). This name should be unique and only one may be registered at a time.

handler -- Type that will be used as the authentication handler during network requests.

name: str

handler: type[ChannelAuthBase]

class CondaHealthCheck

Bases: NamedTuple

Return type to use when defining conda health checks plugin hook.

name: str

action: Callable[[str, bool], None]

class CondaPostCommand

Bases: NamedTuple

Return type to use when defining a conda post-command plugin hook.

For details on how this is used, see conda_post_commands().

Parameters

- name -- Post-command name (e.g., custom_plugin_post_commands).
- action -- Callable which contains the code to be run.
- **run_for** -- Represents the command(s) this will be run on (e.g. install or create).

name: str

action: Callable[[str], None]

run_for: set[str]

class CondaPostSolve

Return type to use when defining a conda post-solve plugin hook.

For details on how this is used, see conda_post_solves().

Parameters

- name -- Post-solve name (e.g., custom_plugin_post_solve).
- action -- Callable which contains the code to be run.

name: str

action: Callable[[str, tuple[conda.models.records.PackageRecord, Ellipsis], tuple[conda.models.records.PackageRecord, Ellipsis]], None]

class CondaPreCommand

Bases: NamedTuple

Return type to use when defining a conda pre-command plugin hook.

For details on how this is used, see conda_pre_commands().

Parameters

- **name** -- Pre-command name (e.g., custom_plugin_pre_commands).
- **action** -- Callable which contains the code to be run.
- run_for -- Represents the command(s) this will be run on (e.g. install or create).

name: str

action: Callable[[str], None]

run_for: set[str]

class CondaPreSolve

Return type to use when defining a conda pre-solve plugin hook.

For details on how this is used, see *conda_pre_solves()*.

Parameters

- **name** -- Pre-solve name (e.g., custom_plugin_pre_solve).
- action -- Callable which contains the code to be run.

name: str

action: Callable[[frozenset[conda.models.match_spec.MatchSpec], frozenset[conda.models.match_spec.MatchSpec]], None]

class CondaSetting

Return type to use when defining a conda setting plugin hook.

For details on how this is used, see *conda_settings()*.

Parameters

- **name** -- name of the setting (e.g., config_param)
- **description** -- description of the setting that should be targeted towards users of the plugin
- parameter -- Parameter instance containing the setting definition
- aliases -- alternative names of the setting

```
name: str
```

description: str

parameter: conda.common.configuration.Parameter

aliases: tuple[str, Ellipsis]

class CondaSolver

Bases: NamedTuple

Return type to use when defining a conda solver plugin hook.

For details on how this is used, see *conda_solvers()*.

Parameters

- **name** -- Solver name (e.g., custom-solver).
- **backend** -- Type that will be instantiated as the solver backend.

name: str

```
backend: type[conda.core.solve.Solver]
```

class CondaSubcommand

Return type to use when defining a conda subcommand plugin hook.

For details on how this is used, see conda_subcommands().

Parameters

- name -- Subcommand name (e.g., conda my-subcommand-name).
- summary -- Subcommand summary, will be shown in conda --help.
- action -- Callable that will be run when the subcommand is invoked.
- configure_parser -- Callable that will be run when the subcommand parser is initialized.

```
name: str
```

```
summary: str
```

```
action: Callable[[argparse.Namespace | tuple[str]], int | None]
```

configure_parser: Callable[[argparse.ArgumentParser], None] | None

class CondaVirtualPackage

Bases: NamedTuple

Return type to use when defining a conda virtual package plugin hook.

For details on how this is used, see *conda_virtual_packages()*.

Parameters

- **name** -- Virtual package name (e.g., my_custom_os).
- **version** -- Virtual package version (e.g., 1.2.3).
- **build** -- Virtual package build string (e.g., x86_64).

name: str

version: str | None

build: str | None

resolve

Low-level SAT solver wrapper/interface for the classic solver.

See conda.core.solver.Solver for the high-level API.

Classes

Resolve

_get_sat_solver_cls([sat_solver_choice])

exactness_and_number_of_deps(resolve_obj, ms) Sorting key to emphasize packages that have more strict

Attributes

stdoutlog

Unsatisfiable

ResolvePackageNotFound

_sat_solvers

stdoutlog

Unsatisfiable

ResolvePackageNotFound

_sat_solvers

```
_get_sat_solver_cls(sat_solver_choice=SatSolverChoice.PYCOSAT)
```

exactness_and_number_of_deps(resolve_obj, ms)

Sorting key to emphasize packages that have more strict requirements. More strict means the reduced index can be reduced more, so we want to consider these more constrained deps earlier in reducing the index.

class Resolve(index, processed=False, channels=())

__hash__()

Return hash(self).

```
default_filter(features=None, filter=None)
```

valid(spec_or_prec, filter, optional=True)

Tests if a package, MatchSpec, or a list of both has satisfiable dependencies, assuming cyclic dependencies are always valid.

Parameters

- **spec_or_prec** -- a package record, a MatchSpec, or an iterable of these.
- **filter** -- a dictionary of (fkey,valid) pairs, used to consider a subset of dependencies, and to eliminate repeated searches.
- **optional** -- if True (default), do not enforce optional specifications when considering validity. If False, enforce them.

Returns

True if the full set of dependencies can be satisfied; False otherwise. If filter is supplied and update is True, it will be updated with the search results.

valid2(spec_or_prec, filter_out, optional=True)

invalid_chains(spec, filter, optional=True)

Constructs a set of 'dependency chains' for invalid specs.

A dependency chain is a tuple of MatchSpec objects, starting with the requested spec, proceeding down the dependency tree, ending at a specification that cannot be satisfied.

Parameters

- spec -- a package key or MatchSpec
- filter -- a dictionary of (prec, valid) pairs to be used when testing for package validity.

Returns

A tuple of tuples, empty if the MatchSpec is valid.

verify_specs(specs)

Perform a quick verification that specs and dependencies are reasonable.

Parameters

specs -- An iterable of strings or MatchSpec objects to be tested.

Returns

Nothing, but if there is a conflict, an error is thrown.

Note that this does not attempt to resolve circular dependencies.

_classify_bad_deps(bad_deps, specs_to_add, history_specs, strict_channel_priority)

find_matches_with_strict(ms, strict_channel_priority)

find_conflicts(specs, specs_to_add=None, history_specs=None)

breadth_first_search_for_dep_graph(root_spec, target_name, dep_graph, num_targets=1)

Return shorted path from root_spec to target_name

build_graph_of_deps(spec)

build_conflict_map(specs, specs_to_add=None, history_specs=None)

Perform a deeper analysis on conflicting specifications, by attempting to find the common dependencies that might be the cause of conflicts.

Parameters

- specs -- An iterable of strings or MatchSpec objects to be tested.
- conflict. (It is assumed that the specs)

Returns

A list of lists of bad deps

Return type

bad_deps

Strategy:

If we're here, we know that the specs conflict. This could be because: - One spec conflicts with another; e.g.

```
['numpy 1.5*', 'numpy >=1.6']
```

• One spec conflicts with a dependency of another; e.g. ['numpy 1.5*', 'scipy 0.12.0b1']

• Each spec depends on *the same package* but in a different way; e.g., ['A', 'B'] where A depends on numpy 1.5, and B on numpy 1.6.

Technically, all three of these cases can be boiled down to the last one if we treat the spec itself as one of the "dependencies". There might be more complex reasons for a conflict, but this code only considers the ones above.

The purpose of this code, then, is to identify packages (like numpy above) that all of the specs depend on *but in different ways*. We then identify the dependency chains that lead to those packages.

```
_get_strict_channel(package_name)
```

```
_broader(ms, specs_by_name)
```

Prevent introduction of matchspecs that broaden our selection of choices.

```
_get_package_pool(specs)
```

```
get_reduced_index(explicit_specs, sort_by_exactness=True, exit_on_conflict=False)
```

match_any(mss, prec)

find_matches(*spec:* conda.models.match_spec.MatchSpec) \rightarrow tuple[*conda.models.records.PackageRecord*]

ms_depends(*prec:* conda.models.records.PackageRecord) \rightarrow list[*conda.models.match_spec.MatchSpec*]

```
version_key(prec, vtype=None)
```

static _make_channel_priorities(channels)

get_pkgs(ms, emptyok=False)

static to_sat_name(val)

static to_feature_metric_id(prec_dist_str, feat)

push_MatchSpec(C, spec)

gen_clauses()

generate_spec_constraints(C, specs)

generate_feature_count(C)

generate_update_count(C, specs)

generate_feature_metric(C)

generate_removal_count(C, specs)

generate_install_count(C, specs)

generate_package_count(C, missing)

generate_version_metrics(C, specs, include0=False)

dependency_sort(*must_have: dict[str*, conda.models.records.PackageRecord]) → list[*conda.models.records.PackageRecord*]

environment_is_consistent(installed)

get_conflicting_specs(specs, explicit_specs)

bad_installed(installed, new_specs)

restore_bad(pkgs, preserve)

install_specs(specs, installed, update_deps=True)

install(specs, installed=None, update_deps=True, returnall=False)

remove_specs(specs, installed)

remove(specs, installed)

solve(*specs: list, returnall: bool* = *False,* _*remove*=*False, specs_to_add*=*None, history_specs=None, should_retry_solve*=*False*) \rightarrow list[*conda.models.records.PackageRecord*]

testing

cases

Extends unittest.TestCase to include select pytest fixtures.

Classes

BaseTestCase

A class whose instances are single test cases.

class BaseTestCase(methodName='runTest')

Bases: unittest.TestCase

A class whose instances are single test cases.

By default, the test code itself should be placed in a method named 'runTest'.

If the fixture may be used for many test cases, create as many test methods as are needed. When instantiating such a TestCase subclass, specify in the constructor arguments the name of the test method that the instance is to execute.

Test authors should subclass TestCase for their own tests. Construction and deconstruction of the test's environment ('fixture') can be implemented by overriding the 'setUp' and 'tearDown' methods respectively.

If it is necessary to override the __init__ method, the base class __init__ method must always be called. It is important that subclasses should not change the signature of their __init__ method, since instances of the classes are instantiated automatically by parts of the framework in order to be run.

When subclassing TestCase, you can set these attributes: * failureException: determines which exception will be raised when

the instance's assertion methods fail; test methods raising this exception will be deemed to have 'failed' rather than 'errored'.

· longMessage: determines whether long messages (including repr of

objects used in assert methods) will be printed on failure in *addition* to any explicit message passed.

```
• maxDiff: sets the maximum length of a diff in failure messages
```

by assert methods using difflib. It is looked up as an instance attribute so can be configured by individual tests if required.

fixture_names = ('tmpdir',)

auto_injector_fixture(request)

fixtures

Collection of pytest fixtures used in conda tests.

Functions

suppress_resource_warning()
tmpdir(tmpdir, request)

Suppress Unclosed Socket Warning

to 0 and then set

(1) libmamba

Fixture that will set "context.number_channel_notices"

Resets the context object after each test function is run.

Used to isolate package or index cache from other tests.

A parameterized fixture that sets the solver backend to

clear_subdir_cache()

disable_channel_notices()

```
reset_conda_context()
temp_package_cache(tmp_path_factory)
parametrized_solver_fixture(...)
```

```
solver\_classic(\rightarrow Iterable[Literal[classic]])
```

solver_libmamba(→ Iterable[Literal[libmamba]])

 $_solver_helper(\rightarrow Iterable[Solver])$

Attributes

Solver

suppress_resource_warning()

Suppress Unclosed Socket Warning

It seems urllib3 keeps a socket open to avoid costly recreation costs.

xref: https://github.com/kennethreitz/requests/issues/1882

tmpdir(tmpdir, request)

clear_subdir_cache()

disable_channel_notices()

Fixture that will set "context.number_channel_notices" to 0 and then set it back to its original value.

This is also a good example of how to override values in the context object.

reset_conda_context()

Resets the context object after each test function is run.

```
temp_package_cache(tmp_path_factory)
```

Used to isolate package or index cache from other tests.

```
parametrized_solver_fixture(request: pytest.FixtureRequest, monkeypatch: pytest.MonkeyPatch) \rightarrow Iterable[Literal[libmamba, classic]]
```

A parameterized fixture that sets the solver backend to (1) libmamba and (2) classic for each test. It's using autouse=True, so only import it in modules that actually need it.

Note that skips and xfails need to be done _inside_ the test body. Decorators can't be used because they are evaluated before the fixture has done its work!

So, instead of:

```
@pytest.mark.skipif(context.solver == "libmamba", reason="...") def test_foo():
```

•••

Do:

def test_foo():

```
if context.solver == ''libmamba'':
    pytest.skip("...")
```

••

solver_classic(*request: pytest.FixtureRequest, monkeypatch: pytest.MonkeyPatch*) \rightarrow Iterable[Literal[classic]]

```
solver_libmamba(request: pytest.FixtureRequest, monkeypatch: pytest.MonkeyPatch) \rightarrow Iterable[Literal[libmamba]]
```

Solver

_solver_helper(*request: pytest.FixtureRequest, monkeypatch: pytest.MonkeyPatch, solver:* Solver) \rightarrow Iterable[Solver]

gateways

fixtures

Collection of pytest fixtures used in conda.gateways tests.

minio_s3_server(xprocess, tmp_path)

Mock a local S3 server using minio

Attributes

MINIO_EXE

MINIO_EXE

minio_s3_server(xprocess, tmp_path)

Mock a local S3 server using minio

This requires: - pytest-xprocess: runs the background process - minio: the executable must be in PATH

Note, the given S3 server will be EMPTY! The test function needs to populate it. You can use *conda.testing.helpers.populate_s3_server* for that.

helpers

Collection of helper functions used in conda tests.

Functions

<pre>strip_expected(stderr)</pre>		
<pre>raises(exception, func[, string])</pre>		
<pre>captured([disallow_stderr])</pre>		
$set_active_prefix(\rightarrow None)$		
<pre>assert_equals(a, b[, output])</pre>		
<pre>assert_not_in(a, b[, output])</pre>		
<pre>assert_in(a, b[, output])</pre>		
add_subdir(dist_string)		
<pre>add_subdir_to_iter(iterable)</pre>		
tempdir()		
<pre>supplement_index_with_repodata(index, data,)</pre>	repo-	
		continues on next page

<pre>add_feature_records_legacy(index</pre>					
_export_subdir_data_to_repodata	(subdir_data)	This function is only wrong / undesirable	temporary and	meant to	patch
_sync_channel_to_disk(subdir_data)	This function is only wrong / undesirable	temporary and	meant to	patch
_alias_canonical_channel_name_c	cache_to_file_	This function is only wrong / undesirable	temporary and	meant to	patch
_patch_for_local_exports(name, s	ubdir_data)	This function is only wrong / undesirable	temporary and	meant to	patch
_get_index_r_base(json_filename_on channel_name)	_packages,				
<pre>get_index_r_1([subdir, add_pip, merg</pre>	e_noarch])				
<pre>get_index_r_2([subdir, add_pip, merg</pre>	ge_noarch])				
<pre>get_index_r_4([subdir, add_pip, merg</pre>	ge_noarch])				
<pre>get_index_r_5([subdir, add_pip, merg</pre>	e_noarch])				
<pre>get_index_must_unfreeze([subdir, merge_noarch])</pre>	add_pip,				
<pre>get_index_cuda([subdir, add_pip, men</pre>	rge_noarch])				
<i>record</i> ([name, version, depends, build,])	build_number,				
_get_solver_base(channel_id, specs_to_add,])	tmpdir[,				
<pre>get_solver(tmpdir[, specs_to_add, sp])</pre>	ecs_to_remove,				
<pre>get_solver_2(tmpdir[, specs_to_remove,])</pre>	specs_to_add,				
<pre>get_solver_4(tmpdir[, specs_to_remove,])</pre>	specs_to_add,				
<pre>get_solver_5(tmpdir[, specs_to_remove,])</pre>	specs_to_add,				
<pre>get_solver_aggregate_1(tmpdir[,])</pre>	specs_to_add,				
<pre>get_solver_aggregate_2(tmpdir[,])</pre>	specs_to_add,				
<pre>get_solver_must_unfreeze(tmpdir[,])</pre>	specs_to_add,				
<pre>get_solver_cuda(tmpdir[, specs_to_a</pre>	dd,])				
<pre>convert_to_dist_str(solution)</pre>					
<pre>solver_class()</pre>					

Table 5 – continued from previous page

Attributes

TEST_DATA_DIR

CHANNEL_DIR_V2

EXPORTED_CHANNELS_DIR

expected_error_prefix

TEST_DATA_DIR

CHANNEL_DIR_V2

EXPORTED_CHANNELS_DIR

expected_error_prefix = 'Using Anaconda Cloud api site https://api.anaconda.org'

```
strip_expected(stderr)
```

raises(exception, func, string=None)

captured(disallow_stderr=True)

set_active_prefix(*prefix: str*) → None

assert_equals(a, b, output=")

assert_not_in(a, b, output=")

assert_in(a, b, output=")

add_subdir(dist_string)

add_subdir_to_iter(iterable)

tempdir()

supplement_index_with_repodata(index, repodata, channel, priority)

add_feature_records_legacy(index)

_export_subdir_data_to_repodata(subdir_data: conda.core.subdir_data.SubdirData)

This function is only temporary and meant to patch wrong / undesirable testing behaviour. It should end up being replaced with the new class-based, backend-agnostic solver tests.

_sync_channel_to_disk(subdir_data: conda.core.subdir_data.SubdirData)

This function is only temporary and meant to patch wrong / undesirable testing behaviour. It should end up being replaced with the new class-based, backend-agnostic solver tests.

_alias_canonical_channel_name_cache_to_file_prefixed(name, subdir_data=None)

This function is only temporary and meant to patch wrong / undesirable testing behaviour. It should end up being replaced with the new class-based, backend-agnostic solver tests.

_patch_for_local_exports(name, subdir_data)

This function is only temporary and meant to patch wrong / undesirable testing behaviour. It should end up being replaced with the new class-based, backend-agnostic solver tests.

- **__get_index_r_base**(json_filename_or_packages, channel_name, subdir=context.subdir, add_pip=False, merge_noarch=False)
- get_index_r_1(subdir=context.subdir, add_pip=True, merge_noarch=False)
- get_index_r_2(subdir=context.subdir, add_pip=True, merge_noarch=False)
- get_index_r_4(subdir=context.subdir, add_pip=True, merge_noarch=False)
- get_index_r_5(subdir=context.subdir, add_pip=False, merge_noarch=False)
- get_index_must_unfreeze(subdir=context.subdir, add_pip=True, merge_noarch=False)
- get_index_cuda(subdir=context.subdir, add_pip=True, merge_noarch=False)
- **record**(*name='a'*, *version='1.0'*, *depends=None*, *build='0'*, *build_number=0*, *timestamp=0*, *channel=None*, **kwargs)
- **__get_solver_base**(channel_id, tmpdir, specs_to_add=(), specs_to_remove=(), prefix_records=(), history_specs=(), add_pip=False, merge_noarch=False)
- get_solver(tmpdir, specs_to_add=(), specs_to_remove=(), prefix_records=(), history_specs=(), add_pip=False, merge_noarch=False)

convert_to_dist_str(solution)

solver_class()

integration

These helpers were originally defined in tests/test_create.py, but were refactored here so downstream projects can benefit from them too.

Classes

Commands

Functions

escape_for_winpath(p)			
<pre>running_a_python_capable_of_unicode_subproce</pre>			
set tmpdir(tmpdir)			
o o o <u>o</u> emplane (unpan)			
act town nuclin([nome use restricted unicode])			
_get_temp_prerrx([name, use_testricted_uncode])			
<pre>make_temp_prefix([name, use_restricted_unicode, \]</pre>	When the env. you are creating will be used to install		
]) F	Python 2.7 on Windows		
<pre>FORCE_temp_prefix([name, use_restricted_unicode])</pre>			
run command(\rightarrow tuple[str str int])			
make temp env() Iterator[str])			
$make_cemp_env(\rightarrow nerator[str])$			
$make_temp_package_cache(\rightarrow Iterator[str])$			
$make_temp_channel(\rightarrow Iterator[str])$			
create temp location(\rightarrow str)			
$tempdir(\rightarrow \text{Iterator[str]})$			
maland and Gra() Name)			
reload_config(~ None)			
package_is_installed()			
<pre>get_shortcut_dir([prefix_for_unix])</pre>			

Attributes

TEST_LOG_LEVEL PYTHON_BINARY BIN_DIRECTORY UNICODE_CHARACTERS CUNICODE_CHARACTERS_RESTRICTED which_or_where cp_or_copy env_or_set SPACER_CHARACTER tmpdir_in_use

TEST_LOG_LEVEL

PYTHON_BINARY

BIN_DIRECTORY

UNICODE_CHARACTERS = 'ōáêñßôç'

UNICODE_CHARACTERS_RESTRICTED = 'abcdef'

which_or_where

cp_or_copy

env_or_set

SPACER_CHARACTER = ' '

```
escape_for_winpath(p)
```

running_a_python_capable_of_unicode_subprocessing()

tmpdir_in_use

set_tmpdir(tmpdir)

_get_temp_prefix(name=None, use_restricted_unicode=False)

make_temp_prefix(name=None, use_restricted_unicode=False, _temp_prefix=None)

When the env. you are creating will be used to install Python 2.7 on Windows only a restricted amount of Unicode will work, and probably only those chars in your current codepage, so the characters in UNI-CODE_CHARACTERS_RESTRICTED should probably be randomly generated from that instead. The problem here is that the current codepage needs to be able to handle 'sys.prefix' otherwise ntpath will fall over.

```
FORCE_temp_prefix(name=None, use_restricted_unicode=False)
```

```
class Commands
```

```
COMPARE = 'compare'

CONFIG = 'config'

CLEAN = 'clean'

CREATE = 'create'

INFO = 'info'

INSTALL = 'install'

LIST = 'list'

REMOVE = 'remove'

SEARCH = 'search'

UPDATE = 'update'

RUN = 'run'

command(command. prefix.
```

```
run_command(command, prefix, *arguments, **kwargs) \rightarrow tuple[str, str, int]
```

```
\texttt{make\_temp\_env}(*packages, **kwargs) \rightarrow \text{Iterator[str]}
```

```
\texttt{make\_temp\_package\_cache()} \rightarrow Iterator[str]
```

 $make_temp_channel(packages) \rightarrow Iterator[str]$

```
\texttt{create\_temp\_location()} \rightarrow \textit{str}
```

```
\texttt{tempdir()} \rightarrow Iterator[str]
```

```
reload_config(prefix) \rightarrow None
```

```
package_is_installed(prefix: str | os.PathLike | pathlib.Path, spec: str | conda.models.match_spec.MatchSpec) → conda.models.records.PrefixRecord | None
```

get_shortcut_dir(prefix_for_unix=sys.prefix)

notices

fixtures

Collection of pytest fixtures used in conda.notices tests.

<i>notices_cache_dir</i> (tmpdir)	Fixture that creates the notices cache dir while also mocking
<pre>notices_mock_fetch_get_session()</pre>	
<pre>conda_notices_args_n_parser()</pre>	

notices_cache_dir(tmpdir)

Fixture that creates the notices cache dir while also mocking out a call to user_cache_dir.

```
notices_mock_fetch_get_session()
```

conda_notices_args_n_parser()

helpers

Collection of helper functions used in conda.notices tests.

Classes

DummyArgs	Dummy object that sets all kwargs as object properties.
MockResponse	

Functions

$get_test_notices(\rightarrow dict)$	
$add_resp_to_mock(\rightarrow None)$	Adds any number of MockResponse to MagicMock object as side_effects
$create_notice_cache_files(\rightarrow None)$	Creates the cache files that we use in tests
$offset_cache_file_mtime(\rightarrow None)$	Allows for offsetting the mtime of the notices cache file. This is often
<pre>notices_decorator_assert_message_in_stdout(c)</pre>	Tests a run of notices decorator where we expect to see the messages
$get_notice_cache_filenames(\rightarrow tuple[str])$	Returns the filenames of the cache files that will be searched for

Attributes

DEFAULT_NOTICE_MESG

DEFAULT_NOTICE_MESG = 'Here is an example message that will be displayed to users'

- $get_test_notices(messages: Sequence[str], level: str | None = 'info', created_at: datetime.datetime | None = None, expired_at: datetime.datetime | None = None) \rightarrow dict$
- add_resp_to_mock(mock_session: unittest.mock.MagicMock, status_code: int, messages_json: dict, raise_exc: $bool = False) \rightarrow None$

Adds any number of MockResponse to MagicMock object as side_effects

create_notice_cache_files(*cache_dir: pathlib.Path, cache_files: Sequence[str], messages_json_seq:* Sequence[dict]) \rightarrow None

Creates the cache files that we use in tests

offset_cache_file_mtime(*mtime_offset*) → None

Allows for offsetting the mtime of the notices cache file. This is often used to mock an older creation time the cache file.

class DummyArgs(**kwargs)

Dummy object that sets all kwargs as object properties.

Tests a run of notices decorator where we expect to see the messages print to stdout.

class MockResponse(status_code, json_data, raise_exc=False)

json()

Returns the filenames of the cache files that will be searched for

solver_helpers

Helpers for testing the solver.

Classes

SimpleEnvironment	Helper environment object.
SolverTests	Tests for conda.core.solve.Solver implementa-
	tions.

<pre>index_packages(num)</pre>	Get the index data of the helpers.get_index_r_* helpers.
<pre>package_string(record)</pre>	-
package_string_set(packages)	Transforms package container in package string set.
package_dict(packages)	Transforms package container into a dictionary.
<pre>empty_prefix()</pre>	1 0 1
$temp_simple_env(\rightarrow SimpleEnvironment)$	
<pre>index_packages(num)</pre>	
Get the index data of the helpers.get_index_r_*	helpers.
<pre>package_string(record)</pre>	
<pre>package_string_set(packages)</pre>	
Transforms package container in package string set.	
<pre>package_dict(packages)</pre>	
Transforms package container into a dictionary.	
<pre>class SimpleEnvironment(path, solver_class, subdirs=</pre>	<pre>=context.subdirs)</pre>
Helper environment object.	
<pre>property _channel_packages</pre>	
Helper that unfolds the repo_packages into a	dictionary.
REPO_DATA_KEYS = ('build', 'build_number 'sha256', 'size', 'subdir',	', 'depends', 'license', 'md5', 'name',
<pre>solver(add, remove)</pre>	
Writes repo_packages to the disk and creates	a solver instance.
<pre>solver_transaction(add=(), remove=(), as_specs=False)</pre>	
<pre>install(*specs, as_specs=False)</pre>	
<pre>remove(*specs, as_specs=False)</pre>	
_package_data(record)	
Turn record into data, to be written in the JSON	l environment/repo files.
_write_installed_packages()	
<pre>_write_repo_packages(channel_name, packages)</pre>)
Write packages to the channel path.	
<pre>empty_prefix()</pre>	
$\texttt{temp_simple_env}(solver_class=Solver) \rightarrow SimpleEnvironeter(Solver_class=Solver) \rightarrow SimpleEnvironeter(Solver_class=Solver) \rightarrow Solver(Solver_class=Solver) \rightarrow Solver(Solver_class=Solver_class=Solver) \rightarrow Solver(Solver_class=Solver) \rightarrow Solver(Solver_class=Solver) \rightarrow Solver(Solver_class=Solver) \rightarrow Solver(Solver_class=Solver) \rightarrow Solver(Solver_class=Solver) \rightarrow Solver(Solver_class=Solver) \rightarrow Solver(Solver_class=Solver_class=Solver) \rightarrow Solver(Solver_class=Solver_class=Solver) \rightarrow Solver(Solver_class=Solver_class=Solver) \rightarrow Solver(Solver_class=Solver_class=Solver) \rightarrow Solver(Solver_class=Solver_class=Solver_class=Solver] \rightarrow Solver_class=So$	onment
class SolverTests	
Tests for conda.core.solve.Solver implementation	ions.

abstract property solver_class: type[conda.core.solve.Solver] Class under test.

property tests_to_skip

skip_tests(request)

env()

find_package_in_list(packages, **kwargs)

find_package(**kwargs)

assert_unsatisfiable(exc_info, entries)

Helper to assert that a *conda.exceptions.UnsatisfiableError* instance as a the specified set of unsatisfiable specifications.

test_empty(env)

test_iopro_mkl(env)

test_iopro_nomkl(env)

test_mkl(env)

test_accelerate(env)

test_scipy_mkl(env)

test_anaconda_nomkl(env)

test_pseudo_boolean(env)

test_unsat_from_r1(env)

test_unsat_simple(env)

test_get_dists(env)

test_unsat_shortest_chain_1(env)

test_unsat_shortest_chain_2(env)

test_unsat_shortest_chain_3(env)

test_unsat_shortest_chain_4(env)

test_unsat_chain(env)

test_unsat_any_two_not_three(env)

test_unsat_expand_single(env)

test_unsat_missing_dep(env)

test_nonexistent(env)

test_timestamps_and_deps(env)

test_nonexistent_deps(env)

test_install_package_with_feature(env)

test_unintentional_feature_downgrade(env)

test_circular_dependencies(env)

test_irrational_version(env)

test_no_features(env)

test_channel_priority_1(monkeypatch, env)

test_unsat_channel_priority(monkeypatch, env)

test_remove(env)

test_surplus_features_1(env)

test_surplus_features_2(env)

test_get_reduced_index_broadening_with_unsatisfiable_early_dep(env)

test_get_reduced_index_broadening_preferred_solution(env)

test_arch_preferred_over_noarch_when_otherwise_equal(env)

test_noarch_preferred_over_arch_when_version_greater(env)

test_noarch_preferred_over_arch_when_version_greater_dep(env)

test_noarch_preferred_over_arch_when_build_greater(env)

test_noarch_preferred_over_arch_when_build_greater_dep(env)

Classes

EntityEncoder	Extensible JSON <https: json.org=""> encoder for Python data structures.</https:>
PackageCacheData	
PackageRecord	
CondaCLIFixture	
PathFactoryFixture	
TmpEnvFixture	
TmpChannelFixture	

<pre>reset_context([search_path, argparse_args])</pre>	
<pre>main_subshell(*args[, post_parse_hook])</pre>	Entrypoint for the "subshell" invocation of CLI interface. E.g. <i>conda create</i> .
<pre>path_to_url(path)</pre>	
<pre>conda_ensure_sys_python_is_base_env_python()</pre>	
<pre>conda_move_to_front_of_PATH()</pre>	
$conda_cli(\rightarrow CondaCLIFixture)$	Fixture returning CondaCLIFixture instance.
$path_factory(\rightarrow PathFactoryFixture)$	Fixture returning PathFactoryFixture instance.
$tmp_env(\rightarrow TmpEnvFixture)$	Fixture returning TmpEnvFixture instance.
$tmp_channel(\rightarrow TmpChannelFixture)$	Fixture returning TmpChannelFixture instance.
$context_aware_monkeypatch(\rightarrow pytest.MonkeyPatch)$	A monkeypatch fixture that resets context after each test
$tmp_pkgs_dir(\rightarrow pathlib.Path)$	

Attributes

PACKAGE_CACHE_MAGIC_FILE

context

on_win

deprecated

class EntityEncoder(*, *skipkeys=False*, *ensure_ascii=True*, *check_circular=True*, *allow_nan=True*, *sort_keys=False*, *indent=None*, *separators=None*, *default=None*)

Bases: json.JSONEncoder

Extensible JSON <https://json.org> encoder for Python data structures.

Supports the following objects and types by default:

Python	JSON
dict	object
list, tuple	array
str	string
int, float	number
True	true
False	false
None	null

To extend this to recognize other objects, subclass and implement a .default() method with another method that returns a serializable object for o if possible, otherwise it should call the superclass implementation (to raise TypeError).

default(obj)

Implement this method in a subclass such that it returns a serializable object for o, or calls the base implementation (to raise a TypeError).

For example, to support arbitrary iterators, you could implement default like this:

```
def default(self, o):
    try:
        iterable = iter(o)
    except TypeError:
        pass
    else:
        return list(iterable)
    # Let the base class default method raise the TypeError
    return JSONEncoder.default(self, o)
```

PACKAGE_CACHE_MAGIC_FILE = 'urls.txt'

context

```
reset_context(search_path=SEARCH_PATH, argparse_args=None)
```

```
main_subshell(*args, post_parse_hook=None, **kwargs)
```

Entrypoint for the "subshell" invocation of CLI interface. E.g. conda create.

```
on_win
```

```
path_to_url(path)
```

```
class PackageCacheData(pkgs_dir)
```

```
property _package_cache_records
```

```
property is_writable
```

```
_cache_: dict[str, PackageCacheData]
```

insert(package_cache_record)

load()

```
reload()
```

get(package_ref, default=NULL)

remove(package_ref, default=NULL)

query(package_ref_or_match_spec)

iter_records()

classmethod query_all(package_ref_or_match_spec, pkgs_dirs=None)

```
classmethod first_writable(pkgs_dirs=None)
```
classmethod writable_caches(pkgs_dirs=None)

classmethod read_only_caches(pkgs_dirs=None)

classmethod all_caches_writable_first(pkgs_dirs=None)

classmethod get_all_extracted_entries()

classmethod get_entry_to_link(package_ref)

classmethod tarball_file_in_cache(tarball_path, md5sum=None, exclude_caches=())

```
classmethod clear()
```

tarball_file_in_this_cache(tarball_path, md5sum=None)

```
_check_writable()
```

static _clean_tarball_path_and_get_md5sum(tarball_path, md5sum=None)

```
_scan_for_dist_no_channel(dist_str)
```

itervalues()

values()

```
__repr__()
```

Return repr(self).

```
_make_single_record(package_filename)
```

```
static _dedupe_pkgs_dir_contents(pkgs_dir_contents)
```

deprecated

exception CondaExitZero(message, caused_by=None, **kwargs)

Bases: CondaError

Common base class for all non-exit exceptions.

return_code = 0

```
class PackageRecord(*args, **kwargs)
```

Bases: conda.auxlib.entity.DictSafeMixin, conda.auxlib.entity.Entity

property schannel

property _pkey

property is_unmanageable

property combined_depends

property namekey

name

version

build

build_number channel subdir fn md5 legacy_bz2_md5 legacy_bz2_size url sha256 arch platform depends constrains track_features features noarch preferred_env license license_family package_type timestamp date size metadata: set[str] __hash__() Return hash(self). __eq__(other) Return self==value. dist_str() dist_fields_dump() __str__() Return str(self).

to_match_spec()

to_simple_match_spec()

record_id()

conda_ensure_sys_python_is_base_env_python()

conda_move_to_front_of_PATH()

class CondaCLIFixture

capsys: pytest.CaptureFixture

__call__(*argv: str | os.PathLike | pathlib.Path, raises: type[Exception] | tuple[type[Exception], Ellipsis]) → tuple[str, str, pytest.ExceptionInfo]

__call__(**argv: str* | *os*.*PathLike* | *pathlib*.*Path*) \rightarrow tuple[str, str, int]

Test conda CLI. Mimic what is done in *conda.cli.main.main*.

 $conda \dots == conda_cli(\dots)$

Parameters

- argv -- Arguments to parse.
- **raises** -- Expected exception to intercept. If provided, the raised exception will be returned instead of exit code (see pytest.raises and pytest.ExceptionInfo).

Returns

Command results (stdout, stderr, exit code or pytest.ExceptionInfo).

conda_cli(*capsys: pytest.CaptureFixture*) \rightarrow *CondaCLIFixture*

Fixture returning CondaCLIFixture instance.

class PathFactoryFixture

tmp_path: pathlib.Path

__call__(*name: str* | *None* = *None*, *prefix: str* | *None* = *None*, *suffix: str* | *None* = *None*) \rightarrow pathlib.Path Unique, non-existent path factory.

Extends pytest's *tmp_path* fixture with a new unique, non-existent path for usage in cases where we need a temporary path that doesn't exist yet.

Parameters

- **name** -- Path name to append to *tmp_path*
- **prefix** -- Prefix to prepend to unique name generated
- **suffix** -- Suffix to append to unique name generated

Returns

A new unique path

path_factory(*tmp_path: pathlib.Path*) → *PathFactoryFixture*

Fixture returning PathFactoryFixture instance.

class TmpEnvFixture

path_factory: PathFactoryFixture

conda_cli: CondaCLIFixture

__call__(**packages: str, prefix: str* | *os.PathLike* | *None* = *None*) \rightarrow Iterator[pathlib.Path] Generate a conda environment with the provided packages.

Parameters

• packages -- The packages to install into environment

• prefix -- The prefix at which to install the conda environment

Returns

The conda environment's prefix

tmp_env(*path_factory*: PathFactoryFixture, *conda_cli*: CondaCLIFixture) \rightarrow *TmpEnvFixture*

Fixture returning TmpEnvFixture instance.

class TmpChannelFixture

path_factory: PathFactoryFixture

conda_cli: CondaCLIFixture

__call__(*packages: str) → Iterator[tuple[pathlib.Path, str]]

- **tmp_channel** (*path_factory*: PathFactoryFixture, *conda_cli*: CondaCLIFixture) \rightarrow *TmpChannelFixture* Fixture returning TmpChannelFixture instance.
- $\verb"context_aware_monkeypatch"(monkeypatch: pytest.MonkeyPatch") \rightarrow pytest.MonkeyPatch") \rightarrow pytest.MonkeyPatch$

A monkeypatch fixture that resets context after each test

tmp_pkgs_dir(*path_factory*: PathFactoryFixture, *mocker: pytest_mock.MockerFixture*) \rightarrow pathlib.Path

trust

constants

Context trust constants.

You could argue that the signatures being here is not necessary; indeed, we are not necessarily going to be able to check them *properly* (based on some prior expectations) as the user, since this is the beginning of trust bootstrapping, the first/backup version of the root of trust metadata. Still, the signatures here are useful for diagnostic purposes, and, more important, to allow self-consistency checks: that helps us avoid breaking the chain of trust if someone accidentally lists the wrong keys down the line. (: The discrepancy can be detected when loading the root data, and we can decline to cache incorrect trust metadata that would make further root updates impossible.

INITIAL_TRUST_ROOT

KEY_MGR_FILE = 'key_mgr.json'

signature_verification

Interface between conda-content-trust and conda.

Classes

_SignatureVerification

Attributes

RE_ROOT_METADATA

signature_verification

exception SignatureError

Bases: Exception

Common base class for all non-exit exceptions.

RE_ROOT_METADATA

class _SignatureVerification

property enabled: bool

property trusted_root: dict

property key_mgr: dict | None

_fetch_channel_signing_data(signing_data_url: str, filename: str, etag=None, mod_stamp=None) \rightarrow dict

verify(repodata_fn: str, record: conda.models.records.PackageRecord)

__call__(*repodata_fn: str, unlink_precs: tuple*[conda.models.records.PackageRecord, *Ellipsis*], *link_precs: tuple*[conda.models.records.PackageRecord, *Ellipsis*]) → None

 $\texttt{classmethod cache_clear()} \rightarrow None$

signature_verification

utils

Utility functions.

Functions

<pre>path_identity(path)</pre>		Used as a dummy path converter where no conversion necessary
<pre>unix_path_to_win(path[, root_prefix])</pre>		Convert a path or :-separated string of paths into a Win- dows representation
<pre>win_path_to_cygwin(path)</pre>		
<pre>cygwin_path_to_win(path)</pre>		
<pre>translate_stream(stream, translator)</pre>		
human_bytes(n)		Return the number of bytes n in more human readable form.
<pre>sys_prefix_unfollowed()</pre>		Since conda is installed into non-root environments as a symlink only
<pre>quote_for_shell(*arguments)</pre>		Properly quote arguments for command line passing.
<pre>massage_arguments(arguments[, errors])</pre>		
<pre>wrap_subprocess_call(root_prefix, dev_mode,)</pre>	prefix,	
<pre>get_comspec()</pre>		Returns COMSPEC from envvars.
<pre>ensure_dir_exists(func)</pre>		Ensures that the directory exists for functions returning

Attributes

unix_shell_base	
msys2_shell_base	
shells	
_RE_UNSAFE	

path_identity(path)

Used as a dummy path converter where no conversion necessary

unix_path_to_win(path, root_prefix=")

Convert a path or :-separated string of paths into a Windows representation

Does not add cygdrive. If you need that, set root_prefix to "/cygdrive"

win_path_to_cygwin(path)

cygwin_path_to_win(path)

translate_stream(stream, translator)

human_bytes(n)

Return the number of bytes n in more human readable form.

Examples

```
>>> human_bytes(42)
'42 B'
>>> human_bytes(1042)
'1 KB'
>>> human_bytes(10004242)
'9.5 MB'
>>> human_bytes(10000004242)
'93.13 GB'
```

unix_shell_base

msys2_shell_base

shells

sys_prefix_unfollowed()

Since conda is installed into non-root environments as a symlink only and because sys.prefix follows symlinks, this function can be used to get the 'unfollowed' sys.prefix.

This value is usually the same as the prefix of the environment into which conda has been symlinked. An example of when this is necessary is when conda looks for external sub-commands in find_commands.py

quote_for_shell(*arguments)

Properly quote arguments for command line passing.

For POSIX uses *shlex.join*, for Windows uses a custom implementation to properly escape metacharacters.

Parameters

arguments (list of str) -- Arguments to quote.

Returns

Quoted arguments.

Return type

str

_RE_UNSAFE

massage_arguments(arguments, errors='assert')

get_comspec()

Returns COMSPEC from envvars.

Ensures COMSPEC envvar is set to cmd.exe, if not attempt to find it.

Raises

KeyError -- COMSPEC is undefined and cannot be found.

Returns

COMSPEC value.

Return type

str

ensure_dir_exists(func)

Ensures that the directory exists for functions returning a Path object containing a directory

Functions

conda_signal_handler(signum, frame)

Attributes

version	
name	
author	
email	
license	
copyright	
summary	
url	
CONDA_PACKAGE_ROOT	

__version__

__name__ = 'conda'
__author__ = 'Anaconda, Inc.'
__email__ = 'conda@continuum.io'
__license__ = 'BSD-3-Clause'
__copyright__ = 'Copyright (c) 2012, Anaconda, Inc.'
__summary__
__url__ = 'https://github.com/conda/conda'

CONDA_PACKAGE_ROOT

```
exception CondaError(message, caused_by=None, **kwargs)
```

Bases: Exception

Common base class for all non-exit exceptions.

return_code = 1

reportable = False

__repr__()

Return repr(self).

__str__()

Return str(self).

dump_map()

exception CondaMultiError(errors)

Bases: CondaError

Common base class for all non-exit exceptions.

__repr__()

Return repr(self).

```
__str__()
```

Return str(self).

dump_map()

contains(exception_class)

exception CondaExitZero(message, caused_by=None, **kwargs)

Bases: CondaError

Common base class for all non-exit exceptions.

return_code = 0

```
conda_signal_handler(signum, frame)
```

conda_env

cli

common

DEPRECATED: Use *conda.env.env* instead.

Common utilities for conda-env command line tools.

main

DEPRECATED: Use *conda.cli.main_env* instead. Entry point for all conda-env subcommands.

Functions

show_help_on_empty_command()

create_parser()

```
do_call(arguments, parser)
```

main()

show_help_on_empty_command()

create_parser()

```
do_call(arguments, parser)
```

main()

main_config

DEPRECATED: Use conda.cli.main_env_config instead.

CLI implementation for conda-env config.

Allows for programmatically interacting with conda-env's configuration files (e.g., ~/.condarc).

config_description = Multiline-String

```
"""
Configure a conda environment
```

config_example = Multiline-String

```
"""
examples:
    conda env config vars list
    conda env config --append channels conda-forge
"""
```

main_create

DEPRECATED: Use conda.cli.main_env_create instead.

CLI implementation for conda-env create.

Creates new conda environments with the specified packages.

description = Multiline-String

```
"""
Create an environment based on an environment definition file.
If using an environment.yml file (the default), you can name the
environment in the first line of the file with 'name: envname' or
you can specify the environment name in the CLI command using the
-n/--name argument. The name specified in the CLI will override
the name specified in the environment.yml file.
Unless you are in the directory containing the environment definition
file, use -f to specify the file path of the environment definition
file you want to use.
```

example = Multiline-String

```
"""
examples:
    conda env create
    conda env create -n envname
    conda env create folder/envname
    conda env create -f /path/to/environment.yml
    conda env create -f /path/to/requirements.txt -n envname
    conda env create -f /path/to/requirements.txt -p /home/user/envname
"""
```

main_export

DEPRECATED: Use conda.cli.main_export instead.

CLI implementation for conda-env export.

Dumps specified environment package specifications to the screen.

description = Multiline-String

```
Export a given environment
```

example = Multiline-String

examples:

(continues on next page)

(continued from previous page)

```
conda env export
conda env export --file SOME_FILE
"""
```

main_list

DEPRECATED: Use *conda.cli.main_env_list* instead.

CLI implementation for conda-env list.

Lists available conda environments.

description = Multiline-String

```
"""
List the Conda environments
"""
```

example = Multiline-String

```
examples:
conda env list
conda env list --json
```

main_remove

DEPRECATED: Use conda.cli.main_env_remove instead.

CLI implementation for conda-env remove.

Removes the specified conda environment.

_help = 'Remove an environment'

_description

```
_example = Multiline-String
```

```
""""
Examples:
conda env remove --name F00
conda env remove -n F00
"""
```

main_update

DEPRECATED: Use *conda.cli.main_env_update* instead.

CLI implementation for conda-env update.

Updates the conda environments with the specified packages.

```
description = Multiline-String
```

```
"""
Update the current environment based on environment file
"""
```

example = Multiline-String

```
"""
examples:
    conda env update
    conda env update -n=foo
    conda env update -f=/path/to/environment.yml
    conda env update --name=foo --file=environment.yml
    conda env update vader/deathstar
"""
```

main_vars

DEPRECATED: Use conda.cli.main_env_vars instead.

CLI implementation for conda-env config vars.

Allows for configuring conda-env's vars.

```
var_description = Multiline-String
```

```
"""
Interact with environment variables associated with Conda environments
"""
```

var_example = Multiline-String

```
examples:
    conda env config vars list -n my_env
    conda env config vars set MY_VAR=something OTHER_THING=ohhhhya
    conda env config vars unset MY_VAR
```

list_description = Multiline-String

```
List environment variables for a conda environment
```

......

list_example = Multiline-String

```
""""
examples:
conda env config vars list -n my_env
"""
```

set_description = Multiline-String

```
Set environment variables for a conda environment
```

set_example = Multiline-String

.....

```
example:
conda env config vars set MY_VAR=weee
```

unset_description = Multiline-String

```
""""
Unset environment variables for a conda environment
```

unset_example = Multiline-String

```
example:
conda env config vars unset MY_VAR
```

env

DEPRECATED: Use conda.env.env instead.

Environment object describing the conda environment.yaml file.

installers

base

DEPRECATED: Use conda.env.installers.base instead.

Dynamic installer loading.

ENTRY_POINT = 'conda_env.installers'

conda

DEPRECATED: Use *conda.env.installers.conda* instead. Conda-flavored installer.

pip

DEPRECATED: Use *conda.env.installers.pip* instead. Pip-flavored installer.

pip_util

DEPRECATED: Use *conda.env.pip_util* instead. Environment object describing the conda environment.yaml file. _canonicalize_regex

specs

DEPRECATED: Use *conda.env.specs* instead. Dynamic installer loading.

binstar

DEPRECATED: Use *conda.env.specs.binstar* instead. Define binstar spec.

requirements

DEPRECATED: Use *conda.env.specs.requirements* instead. Define requirements.txt spec.

yaml_file

DEPRECATED: Use *conda.env.specs.yaml_file* instead. Define YAML spec.

PYTHON MODULE INDEX

С

conda, 382 conda.__main__, 382 conda._vendor, 382 conda._vendor.appdirs, 382 conda._vendor.cpuinfo, 386 conda._vendor.cpuinfo.cpuinfo, 386 conda._vendor.distro, 398 conda._vendor.frozendict, 408 conda._version, 409 conda.activate, 409 conda.api, 416 conda.auxlib, 421 conda.auxlib.collection, 422 conda.auxlib.compat,423 conda.auxlib.decorators, 424 conda.auxlib.entity, 426 conda.auxlib.exceptions, 437 conda.auxlib.ish, 438 conda.auxlib.logz, 439 conda.auxlib.type_coercion, 441 conda.base,444 conda.base.constants, 444 conda.base.context, 450 conda.base.exceptions, 460 conda.cli.460 conda.cli.actions, 460 conda.cli.common, 461 conda.cli.conda_argparse, 463 conda.cli.find_commands, 465 conda.cli.helpers, 466 conda.cli.install, 469 conda.cli.main, 470 conda.cli.main_clean, 470 conda.cli.main_compare, 472 conda.cli.main_config, 472 conda.cli.main_create, 473 conda.cli.main_env, 474 conda.cli.main_env_config, 474 conda.cli.main_env_create, 474 conda.cli.main_env_export,475 conda.cli.main_env_list, 475

conda.cli.main_env_remove, 475 conda.cli.main_env_update, 476 conda.cli.main_env_vars,476 conda.cli.main_export, 477 conda.cli.main_info,477 conda.cli.main_init, 479 conda.cli.main_install, 479 conda.cli.main_list, 480 conda.cli.main_mock_activate, 480 conda.cli.main_mock_deactivate, 481 conda.cli.main_notices, 481 conda.cli.main_package, 482 conda.cli.main_pip, 483 conda.cli.main_remove, 483 conda.cli.main_rename, 484 conda.cli.main_run, 484 conda.cli.main_search, 485 conda.cli.main_update, 485 conda.cli.python_api, 486 conda.common, 488 conda.common._logic, 488 conda.common._os, 491 conda.common._os.linux, 491 conda.common._os.unix,492 conda.common._os.windows, 492 conda.common.compat, 494 conda.common.configuration, 496 conda.common.constants, 507 conda.common.decorators, 507 conda.common.disk.507 conda.common.io, 508 conda.common.iterators, 513 conda.common.logic, 514 conda.common.path, 517 conda.common.pkg_formats, 521 conda.common.pkg_formats.python, 521 conda.common.serialize, 530 conda.common.signals, 531 conda.common.toposort, 532 conda.common.url, 533 conda.core, 538 conda.core.envs_manager, 539

conda.core.index, 539 conda.core.initialize.543 conda.core.link, 548 conda.core.package_cache, 551 conda.core.package_cache_data, 551 conda.core.path_actions, 554 conda.core.portability, 560 conda.core.prefix_data, 562 conda.core.solve.563 conda.core.subdir_data, 566 conda.deprecations, 569 conda.env, 571 conda.env.env, 571 conda.env.installers, 573 conda.env.installers.base, 573 conda.env.installers.conda, 574 conda.env.installers.pip, 574 conda.env.pip_util, 575 conda.env.specs, 575 conda.env.specs.binstar, 575 conda.env.specs.requirements, 576 conda.env.specs.yaml_file, 576 conda.exception_handler, 579 conda.exceptions, 580 conda.exports, 587 conda.gateways, 591 conda.gateways.anaconda_client, 592 conda.gateways.connection, 593 conda.gateways.connection.adapters, 593 conda.gateways.connection.adapters.ftp, 593 conda.gateways.connection.adapters.http, 595 conda.gateways.connection.adapters.localfs, 596 conda.gateways.connection.adapters.s3, 596 conda.gateways.connection.download, 598 conda.gateways.connection.session, 599 conda.gateways.disk, 601 conda.gateways.disk.create, 601 conda.gateways.disk.delete, 604 conda.gateways.disk.link, 605 conda.gateways.disk.lock, 605 conda.gateways.disk.permissions, 606 conda.gateways.disk.read, 606 conda.gateways.disk.test, 608 conda.gateways.disk.update, 609 conda.gateways.logging, 610 conda.gateways.repodata, 612 conda.gateways.repodata.jlap, 612 conda.gateways.repodata.jlap.core, 612 conda.gateways.repodata.jlap.fetch, 614 conda.gateways.repodata.jlap.interface, 617 conda.gateways.repodata.lock, 618 conda.gateways.subprocess, 627 conda.history, 627

conda.instructions, 630 conda.misc. 632 conda.models.633 conda.models.channel, 633 conda.models.dist, 636 conda.models.enums, 639 conda.models.leased_path_entry, 642 conda.models.match_spec, 643 conda.models.package_info, 649 conda.models.prefix_graph, 651 conda.models.records, 653 conda.models.version, 660 conda.notices, 667 conda.notices.cache, 667 conda.notices.core, 668 conda.notices.fetch, 670 conda.notices.types, 671 conda.notices.views, 672 conda.plan, 673 conda.plugins, 674 conda.plugins.hookspec, 675 conda.plugins.manager, 680 conda.plugins.post_solves, 682 conda.plugins.post_solves.signature_verification, 682 conda.plugins.solvers, 683 conda.plugins.subcommands, 683 conda.plugins.subcommands.doctor, 683 conda.plugins.subcommands.doctor.health_checks, 683 conda.plugins.types, 686 conda.plugins.virtual_packages, 690 conda.plugins.virtual_packages.archspec, 690 conda.plugins.virtual_packages.conda, 691 conda.plugins.virtual_packages.cuda, 691 conda.plugins.virtual_packages.freebsd, 692 conda.plugins.virtual_packages.linux, 692 conda.plugins.virtual_packages.osx, 692 conda.plugins.virtual_packages.windows, 692 conda.resolve, 696 conda.testing,700 conda.testing.cases, 700 conda.testing.fixtures, 701 conda.testing.gateways, 702 conda.testing.gateways.fixtures,702 conda.testing.helpers, 703 conda.testing.integration, 707 conda.testing.notices, 709 conda.testing.notices.fixtures, 709 conda.testing.notices.helpers, 710 conda.testing.solver_helpers,711 conda.trust,720 conda.trust.constants,720 conda.trust.signature_verification,721

conda.utils,722 conda_env, 725 conda_env.cli,725 conda_env.cli.common, 725 conda_env.cli.main, 726 conda_env.cli.main_config,726 conda_env.cli.main_create,727 conda_env.cli.main_export,727 conda_env.cli.main_list,728 conda_env.cli.main_remove, 728 conda_env.cli.main_update,729 conda_env.cli.main_vars,729 conda_env.env, 730 conda_env.installers,730 conda_env.installers.base,730 conda_env.installers.conda,731 conda_env.installers.pip,731 conda_env.pip_util, 731 conda_env.specs, 731 conda_env.specs.binstar,731 conda_env.specs.requirements, 731 conda_env.specs.yaml_file,731

INDEX

Symbols

_Action (class in conda.core.path_actions), 556 _Activator (class in conda.activate), 410 _ClauseArray (class in conda.common._logic), 489 _ClauseList (class in conda.common._logic), 488 _DISTRO_RELEASE_BASENAME_PATTERN (in module conda. vendor.distro), 400 _DISTRO_RELEASE_CONTENT_REVERSED_PATTERN (in module conda._vendor.distro), 400 _DISTRO_RELEASE_IGNORE_BASENAMES (in module conda._vendor.distro), 400 _DUMPS (in module conda.auxlib.logz), 441 _FORMATTER (in module conda.common.io), 510 _FeaturesField (class in conda.models.records), 656 _GreedySubParsersAction (class in conda.cli.conda_argparse), 465 _MATCHER_CACHE (MatchSpec attribute), 646 _MENU_RE (in module conda.core.path actions), 556 _OS_RELEASE_BASENAME (in module conda._vendor.distro), 400 _PARSE_CACHE (in module conda.models.match_spec), 647 _PaddingError, 561 _PyCryptoSatSolver (class in conda.common. logic), 490 _PySatSolver (class in conda.common._logic), 490 _PycoSatSolver (class in conda.common._logic), 489 _RE_CUSTOM_EXPANDVARS module (in conda.common.configuration), 505 _RE_UNSAFE (in module conda.utils), 723 _SSLContextAdapterMixin (class in conda.gateways.connection.adapters.http), 595 _SatSolver (class in conda.common._logic), 489 _SignatureVerification (class in conda.trust.signature_verification), 721 _StrMatchMixin (class in conda.models.match_spec), 647 _UNIXCONFDIR (in module conda._vendor.distro), 400 _VERBOSITY_LEVELS (in module conda.gateways.logging), 611 _VERSION_REGEX (in module conda.common.path), 519

__author__ (in module conda), 724 __author__ (in module conda.auxlib), 443 __bool__() (Channel method), 623, 635 __call__() (BooleanOptionalAction method), 468 __call__() (ChannelPriorityMeta method), 449 __call__() (ChannelType method), 634 __call__() (CondaCLIFixture method), 719 __call__() (CondaHttpAuth method), 600 ___call__() (CondaSessionType method), 600 __call__() (ContextDecorator method), 510 __call__() (DeprecationHandler method), 569 __call__() (DistType method), 637 __call__() (ExceptionHandler method), 579 __call__() (ExtendConstAction method), 461 __call__() (MatchSpecType method), 644 __call__() (NullCountAction method), 461 __call__() (PackageCacheType method), 552 __call__() (PathFactoryFixture method), 719 __call__() (PrefixDataType method), 562 __call__() (SingleStrArgCachingType method), 662 __call__() (SubdirDataType method), 567 ___call__() (*TmpChannelFixture method*), 720 __call__() (*TmpEnvFixture method*), 720 ___call___() (_GreedySubParsersAction method), 465 __call__() (_SignatureVerification method), 721 __call__() (time_recorder method), 513 __contains__() (Completer method), 590 __contains__() (Dist method), 639 __contains__() (MatchSpec method), 646 ___contains__() (RepodataState method), 625 ___contains__() (UrlsData method), 553 __contains__() (frozendict method), 408 __copyright__ (in module conda), 724 __copyright__ (in module conda.auxlib), 443 __del__() (TemporaryDirectory method), 603 __delattr__() (ImmutableEntity method), 437 __delete__() (Field method), 432 __dump_fields() (Entity class method), 437 __email__ (in module conda), 724 __email__ (in module conda.auxlib), 443 __enter__() (History method), 628 __enter__() (Spinner method), 511

__enter__() (SwallowBrokenPipe method), 510 __enter__() (TemporaryDirectory method), 603 __enter__() (TmpDownload method), 598 __enter__() (time_recorder method), 513 __eq__() (BaseSpec method), 665 __eq__() (Channel method), 623, 635 __eq__() (Dist method), 638 ___eq__() (*Entity method*), 437 __eq__() (FeatureMatch method), 649 ___eq__() (LoadedParameter method), 500 ___eq__() (MatchSpec method), 646 __eq__() (PackageRecord method), 659, 718 ___eq__() (PrimitiveLoadedParameter method), 501 __eq__() (ProgressiveFetchExtract method), 554 __eq__() (SplitStrMatch method), 648 __eq__() (VersionOrder method), 664 __eq__() (_StrMatchMixin method), 648 __exit__() (History method), 628 __exit__() (Spinner method), 511 __exit__() (SwallowBrokenPipe method), 510 __exit__() (TemporaryDirectory method), 603 __exit__() (TmpDownload method), 599 __exit__() (time_recorder method), 513 ___fields___(Entity attribute), 436 __ge__() (Dist method), 638 __ge__() (VersionOrder method), 664 __get__() (ChannelField method), 656 ___get___() (Field method), 432 __get__() (FilenameField method), 657 __get__() (Md5Field method), 660 __get__() (PackageTypeField method), 657 __get__() (ParameterLoader method), 505 __get__() (SubdirField method), 657 __get__() (TimestampField method), 655 __get__() (classproperty method), 426 __getattr__() (ProgressFileWrapper method), 603 __getattr__() (StdStreamHandler method), 612 __getitem__() (PackageRecordList method), 567 __getitem__() (RepodataState method), 625 __getitem__() (frozendict method), 408 __gt__() (Dist method), 638 __gt__() (VersionOrder method), 664 __hash__() (BaseSpec method), 665 __hash__() (Channel method), 623, 635 __hash__() (Dist method), 638 __hash__() (Entity method), 437 __hash__() (FeatureMatch method), 649 __hash__() (LoadedParameter method), 500 __hash__() (MatchSpec method), 646 __hash__() (PackageRecord method), 659, 718 __hash__() (PrimitiveLoadedParameter method), 501 __hash__() (ProgressiveFetchExtract method), 554 __hash__() (Resolve method), 697 __hash__() (SplitStrMatch method), 648

__hash__() (*StrMatchMixin method*), 648 __hash__() (frozendict method), 409 __important_split_value (EnvRawParameter property), 499 __int__() (LinkType method), 640 __iter__() (Completer method), 590 __iter__() (UrlsData method), 553 __iter__() (frozendict method), 408 __json__() (Arch method), 640 __json__() (Channel method), 623, 635 __json__() (LeasedPathType method), 641 __json__() (LinkType method), 640 __json__() (MatchSpec method), 646 __json__() (PathType method), 641 __json__() (Platform method), 640 __json__() (frozendict method), 409 __key__() (Dist method), 638 $_1e_()$ (Dist method), 638 __le__() (VersionOrder method), 664 __len__() (frozendict method), 408 __license__ (in module conda), 724 __license__ (in module conda.auxlib), 443 ___lt__() (Dist method), 638 __lt__() (VersionOrder method), 664 ___name__ (*ChannelPriority attribute*), 449 __name__ (in module conda), 724 __ne__() (BaseSpec method), 665 __ne__() (Dist method), 638 __ne__() (VersionOrder method), 664 __nonzero__() (Channel method), 623, 635 __register__() (Entity class method), 436 __repr__() (BaseSpec method), 666 __repr__() (BuildNumberMatch method), 666 __repr__() (Channel method), 623, 635 __repr__() (ChannelMatch method), 649 __repr__() (ClobberError method), 581 __repr__() (CondaError method), 620, 725 __repr__() (CondaMultiError method), 725 __repr__() (Entity method), 436 __repr__() (FeatureMatch method), 649 __repr__() (LinuxDistribution method), 405 __repr__() (MatchSpec method), 646 __repr__() (PackageCacheData method), 553, 621, 717 __repr__() (RawParameter method), 499 __repr__() (SplitStrMatch method), 648 __repr__() (TemporaryDirectory method), 603 __repr__() (VersionOrder method), 664 __repr__() (_Action method), 556 __repr__() (_StrMatchMixin method), 648 __repr__() (frozendict method), 408 __set__() (Field method), 432 ___set__() (classproperty method), 426 __setattr__() (ImmutableEntity method), 437

__setitem__() (RepodataState method), 625 __slots__ (ExactStrMatch attribute), 648 __slots__ (*FeatureMatch attribute*), 649 __slots__ (GlobStrMatch attribute), 648 __slots__ (SplitStrMatch attribute), 648 __str__() (BaseSpec method), 666 __str__() (BuildNumberMatch method), 666 __str__() (CacheUrlAction method), 560 __str__() (Channel method), 623, 635 __str__() (ChannelMatch method), 649 __str__() (CondaError method), 620, 725 __str__() (CondaMultiError method), 725 __str__() (DepsModifier method), 448 __str__() (Dist method), 638 ___str__() (ExtractPackageAction method), 560 __str__() (FeatureMatch method), 649 __str__() (FileMode method), 640 __str__() (LeasedPathType method), 641 __str__() (LinkType method), 640 __str__() (MatchSpec method), 646 __str__() (PackageRecord method), 659, 718 __str__() (ParameterFlag method), 499 __str__() (PathConflict method), 448 __str__() (PathType method), 641 __str__() (SafetyChecks method), 448 __str__() (SplitStrMatch method), 648 __str__() (UpdateModifier method), 448 __str__() (Url method), 535 __str__() (ValueEnum method), 449 __str__() (VersionOrder method), 664 __str__() (_StrMatchMixin method), 647 __summary__ (in module conda), 724 __summary__ (in module conda.auxlib), 443 __url__ (in module conda), 724 __url__ (in module conda.auxlib), 443 __version__ (in module conda), 724 __version__ (in module conda._vendor.appdirs), 383 __version__ (in module conda._version), 409 __version__ (in module conda.auxlib), 443 __version_info__ (in module conda._vendor.appdirs), 383 __version_tuple__ (in module conda._version), 409 _add_http_value_to_dict() (in module conda.gateways.repodata), 624 _add_info_dir() (in module conda.cli.main_package), 482 _add_prefix_to_path() (_Activator method), 412 _add_specs() (Solver method), 566 _aggressive_update_packages (Context attribute), 455 _alias_canonical_channel_name_cache_to_file_prefiement()arball_path_and_get_md5sum() (in module conda.testing.helpers), 705 _aliased (RepodataState attribute), 624

_apply_basic_auth() (*CondaHttpAuth static method*), 601 _arch_names (in module conda.base.context), 452 _ask_upload() (ExceptionHandler method), 580 _asm_func() (CPUID method), 390, 397 _assign() (Clauses method), 515 _b64_to_obj() (in module conda. vendor.cpuinfo), 396 _b64_to_obj() (in module conda. vendor.cpuinfo.cpuinfo), 390 _bashrc_content() (in module conda.core.initialize), 548 _broader() (Resolve method), 699 _build_activate_stack() (_Activator method), 412 _build_activator_cls() (in module conda.activate), 415 _build_components() (MatchSpec method), 646 _cache_ (BuildNumberMatch attribute), 666 _cache_(Channel attribute), 622, 635 _cache_ (Dist attribute), 637 _cache_ (PackageCacheData attribute), 552, 621, 716 _cache_ (PrefixData attribute), 562 _cache_ (SubdirData attribute), 568 _cache_(VersionOrder attribute), 664 _cache_ (VersionSpec attribute), 666 _calculate_change_report() (UnlinkLinkTransaction static method), 551 _calculate_md5sum() (PackageCacheRecord method), 660 _canonicalize_regex (in module conda_env.pip_util), 731 _change_report_str() (UnlinkLinkTransaction method), 551 _channel_alias (Context attribute), 456 _channel_packages (SimpleEnvironment property), 712 _channels (Context attribute), 456 _check_arch() (in module conda. vendor.cpuinfo), 396 _check_arch() (in module conda._vendor.cpuinfo.cpuinfo), 390 _check_files() (PythonDistribution method), 524 _check_literal() (Clauses method), 515 _check_path_data() (PythonDistribution method), 524 _check_value() (ArgumentParser method), 465 _check_variable() (Clauses method), 515 _check_writable() (PackageCacheData method), 553, 621,717 _classify_bad_deps() (Resolve method), 698 _clean_environments_txt() (in module conda.core.envs_manager), 539 (PackageCacheData static method), 553, 621, 717

_closed (TemporaryDirectory attribute), 603

_collect_all_metadata() (Solver method), 566 _collect_validation_error() (Configuration static method), 506 _conda_build (Context attribute), 457 _config_fish_content() (in module conda.core.initialize), 547 _config_xonsh_content() module (in conda.core.initialize), 547 _convert() (Clauses method), 515 _convert() (FeatureMatch method), 649 _convert() (SplitStrMatch method), 648 _copy_new_fields() (in module conda._vendor.cpuinfo), 396 _copy_new_fields() (in module conda._vendor.cpuinfo.cpuinfo), 390 _croot (Context attribute), 457 _cuda_driver_version_detector_target() (in module conda.plugins.virtual_packages.cuda), 691 _custom_channels (*Context attribute*), 456 _custom_multichannels (Context attribute), 456 _debug (Context attribute), 456 _dedupe_pkgs_dir_contents() (PackageCacheData static method), 553, 621, 717 _default_channels (*Context attribute*), 456 _default_env() (_Activator method), 412 _default_threads (Context attribute), 455 _description (in module conda_env.cli.main_remove), 728 _distro (in module conda._vendor.distro), 408 _do_copy() (in module conda.gateways.disk.create), 603 _do_softlink() (in module conda.gateways.disk.create), 603 _element_type (LoadedParameter attribute), 500 _element_type (Parameter attribute), 503 _ensure_dir() (time_recorder method), 513 _ensure_value() (*NullCountAction static method*), 461 _environment (YamlFileSpec attribute), 577, 578 _envs_dirs (Context attribute), 455 _eq() (VersionOrder method), 664 _eval() (Clauses method), 515 _example (in module conda env.cli.main remove), 728 _exec() (in module conda.cli.conda_argparse), 465 _exec_unix() (in module conda.cli.conda_argparse), 465 _exec_win() (in module conda.cli.conda_argparse), 465 _execute() (UnlinkLinkTransaction method), 550 _execute() (in module conda.cli.main_clean), 472 _execute_actions() (UnlinkLinkTransaction static method), 550 _execute_channel() (CacheUrlAction method), 560 _execute_local() (CacheUrlAction method), 560

_execute_post_link_actions() (UnlinkLinkTransaction static method), 551 _execute_threads (Context attribute), 455 _execute_upload() (ExceptionHandler method), 580 _expand_channels() (in module conda.env.env), 572 _expand_search_path() (Configuration static method), 506 _export_subdir_data_to_repodata() (in module conda.testing.helpers), 705 _fetch_channel_signing_data() (_SignatureVerification method), 721 _fetch_threads (Context attribute), 455 _filter_dict_keys_with_empty_values() (in module conda._vendor.cpuinfo), 396 _filter_dict_keys_with_empty_values() (in module conda._vendor.cpuinfo.cpuinfo), 390 _finalize() (JSONFormatMixin method), 415 _finalize() (Activator method), 411 _find_inconsistent_packages() (Solver method), 566 _first_important_matches() (LoadedParameter static method), 501 _first_writable_envs_dir() (in module conda.base.context), 459 _format_chain_str() (UnsatisfiableError method), 584 _format_exc() (in module conda.exceptions), 587 _format_output() (in module conda.gateways.subprocess), 627 _friendly_bytes_to_int() module (in conda._vendor.cpuinfo), 396 _friendly_bytes_to_int() (in module conda._vendor.cpuinfo.cpuinfo), 390 _generate_message() (DeprecationHandler method), 571 _get_activate_scripts() (_Activator method), 412 _get_attr() (in module conda.auxlib.ish), 438 _get_base_url() (SubdirData method), 568 _get_best_prec_match() (in module conda.plan), 674 _get_binstar_token_directory() module (in conda.gateways.anaconda client), 592 _get_channel_for_name() (in module conda.models.channel), 636 _get_cpu_info() (in module conda.base.context), 459 _get_cpu_info_from_cat_var_run_dmesg_boot() (in module conda._vendor.cpuinfo), 397 _get_cpu_info_from_cat_var_run_dmesg_boot() (in module conda._vendor.cpuinfo.cpuinfo), 391 _get_cpu_info_from_cpufreq_info() (in module conda._vendor.cpuinfo), 397 _get_cpu_info_from_cpufreq_info() (in module conda._vendor.cpuinfo.cpuinfo), 391

_get_cpu_info_from_cpuid() (in module

_get_cpu_info_from_sysinfo_v2() (in module conda._vendor.cpuinfo.cpuinfo), 391 _get_cpu_info_from_wmic() (in module conda._vendor.cpuinfo), 398 _get_cpu_info_from_wmic() (in module conda._vendor.cpuinfo.cpuinfo), 391 _get_cpu_info_internal() (in module conda._vendor.cpuinfo), 398 _get_cpu_info_internal() (in module conda._vendor.cpuinfo.cpuinfo), 392 _get_deactivate_scripts() (_Activator method), 412 _get_distro_release_info() (LinuxDistribution method), 407 _get_environment_env_vars() (_Activator method), 412 _get_environment_state_file() (PrefixData method), 563 _get_field() (in module conda._vendor.cpuinfo), 396 _get_field() (in module conda._vendor.cpuinfo.cpuinfo), 390 _get_field_actual() module (in conda._vendor.cpuinfo), 396 _get_field_actual() module (in conda._vendor.cpuinfo.cpuinfo), 390 _get_index_r_base() (in module conda.testing.helpers), 706 _get_json_fn() (PrefixData method), 562 _get_lsb_release_info() (LinuxDistribution method), 407 _get_module() (DeprecationHandler method), 571 _get_multiple_data() (PythonDistributionMetadata method), 526 _get_os_release_info() (LinuxDistribution method), 407 _get_package_pool() (Resolve method), 699 _get_path_dirs() (Activator method), 412 _get_pfe() (UnlinkLinkTransaction method), 550 _get_pkgs_dirs() (in module conda.cli.main_clean), 471 _get_python_info() (in module conda.core.initialize), 548 _get_python_version() (UnlinkLinkTransaction static method), 551 _get_sat_solver_cls() (in module conda.resolve), 697 _get_size() (in module conda.cli.main_clean), 471 _get_solver_base() module (in conda.testing.helpers), 706 _get_starting_path_list() (_Activator method), 412 _get_strict_channel() (Resolve method), 699 _get_subactions() (GreedySubParsersAction

method), 465

conda. vendor.cpuinfo), 397 _get_cpu_info_from_cpuid() (in module conda. vendor.cpuinfo.cpuinfo), 391 _get_cpu_info_from_cpuid_actual() (in module conda. vendor.cpuinfo), 397 _get_cpu_info_from_cpuid_actual() (in module conda. vendor.cpuinfo.cpuinfo), 391 _get_cpu_info_from_cpuid_subprocess_wrapper() (in module conda. vendor.cpuinfo), 397 _get_cpu_info_from_cpuid_subprocess_wrapper() (in module conda._vendor.cpuinfo.cpuinfo), 391 _get_cpu_info_from_dmesg() (in module conda._vendor.cpuinfo), 397 _get_cpu_info_from_dmesg() module (in conda._vendor.cpuinfo.cpuinfo), 391 _get_cpu_info_from_ibm_pa_features() (in module conda. vendor.cpuinfo), 397 _get_cpu_info_from_ibm_pa_features() (in module conda. vendor.cpuinfo.cpuinfo), 391 _get_cpu_info_from_kstat() (in module conda. vendor.cpuinfo), 398 _get_cpu_info_from_kstat() module (in conda. vendor.cpuinfo.cpuinfo), 392 _get_cpu_info_from_lscpu() (in module conda. vendor.cpuinfo), 397 _get_cpu_info_from_lscpu() (in moduleconda._vendor.cpuinfo.cpuinfo), 391 _get_cpu_info_from_platform_uname() (in module conda._vendor.cpuinfo), 398 _get_cpu_info_from_platform_uname() (in module conda._vendor.cpuinfo.cpuinfo), 392 _get_cpu_info_from_proc_cpuinfo() (in module conda._vendor.cpuinfo), 397 _get_cpu_info_from_proc_cpuinfo() (in module conda._vendor.cpuinfo.cpuinfo), 391 _get_cpu_info_from_registry() (in module conda._vendor.cpuinfo), 398 _get_cpu_info_from_registry() (in module conda._vendor.cpuinfo.cpuinfo), 392 _get_cpu_info_from_sysctl() module (in conda. vendor.cpuinfo), 398 _get_cpu_info_from_sysctl() (in module conda._vendor.cpuinfo.cpuinfo), 391 _get_cpu_info_from_sysinfo() (in module conda._vendor.cpuinfo), 398 _get_cpu_info_from_sysinfo() (in module conda._vendor.cpuinfo.cpuinfo), 391 _get_cpu_info_from_sysinfo_v1() (in module conda._vendor.cpuinfo), 398 _get_cpu_info_from_sysinfo_v1() (in module conda._vendor.cpuinfo.cpuinfo), 391 _get_cpu_info_from_sysinfo_v2() (in module

conda._vendor.cpuinfo), 398

_gec_cemp_prerrn()	(<i>in</i>		module
conda.testing.integrat	ion), 708		
get total size() (in modu	le conda.c	li.mai	n clean).
471			_ //
aet version tunle() (De	nrecationF	Jandl	er static
method) 569	precution	Iunun	er statte
act win folder (in module	conda y	mdar	ann dire)
_get_win_totder (in module	conaave	enaor.	appairs),
380		<i>.</i> .	1.1
_get_win_folder_from_reg	istry()	(in	module
condavendor.appdir	s), 385		
_get_win_folder_with_cty	pes()	(in	module
condavendor.appdir	s), 386		
_get_win_folder_with_pyw:	in32()	(in	module
condavendor.appdir	s), 385		
_get_yaml_key_comment()(YamlRawP	arame	eter static
method), 500			
get vaml list comment i	tem() (Yar	nlRav	vParame-
ter static method) 500)		
det vaml list comments()) (Yaml	RawF	Parameter
_get_yami_iist_commerces()) (10111	num	arameter
ciuss meinou), 500	(Vam)	Davel	Danamatan
_get_yam1_map_comments()	(1umi	лаwг	arameter
static method), 500	, ,		(74
_handle_menuinst() (in mod	ule conda.	plan),	6/4
_has_python() (<i>PrefixData m</i>	ethod), 56.	3	
_hash_key() (<i>MatchSpec meth</i>	nod), 646		
_help (in module conda_env.cl	i.main_ren	ıove),	728
_hook_postamble() (Power	ShellActiva	ator	method),
415			
413			
_hook_postamble() (_Activat	or method)), 411	
_hook_postamble() (_Activat _hook_preamble() (CmdExeA	or method) Activator m), 411 ethod), 414
_hook_postamble() (_Activat _hook_preamble() (<i>CmdExeA</i> _hook_preamble() (<i>CshActiva</i>	or method) Activator m ator method), 411 <i>ethod</i> d), 41), 414 3
_hook_postamble() (_Activat _hook_preamble() (<i>CmdExeA</i> _hook_preamble() (<i>CshActiva</i> _hook_preamble() (<i>FishActiv</i>	or method) activator m ator metho ator metho), 411 <i>ethod</i> d), 41 d), 41), 414 3 4
_hook_postamble() (_Activat _hook_preamble() (CmdExeA _hook_preamble() (CshActiva _hook_preamble() (FishActiva _hook_preamble() (JSONFor	or method) ctivator m itor method ator metho matMixin i), 411 ethod d), 41 d), 41 netho), 414 3 4 d), 415
_hook_postamble() (_Activat _hook_preamble() (CmdExeA _hook_preamble() (CshActiva _hook_preamble() (FishActiva _hook_preamble() (JSONFor _hook_preamble() (PosivActiva	or method activator m ator metho ator metho matMixin 1 vator meth), 411 ethod d), 41 d), 41 netho), 414 3 4 d), 415
_hook_postamble() (_Activat _hook_preamble() (CmdExeA _hook_preamble() (CshActiva _hook_preamble() (FishActiv _hook_preamble() (JSONFor _hook_preamble() (PosixActiv _hook_preamble() (PosixActiv	or method activator m ator method ator metho matMixin 1 vator metho), 411 ethod d), 41 d), 41 netho od), 4), 414 3 4 d), 415 13 cd) 415
_hook_postamble() (_Activat _hook_preamble() (CmdExeA _hook_preamble() (CshActiva _hook_preamble() (FishActiv _hook_preamble() (JSONFor _hook_preamble() (PosixActi _hook_preamble() (PowerShe	or method activator m ator method ator metho matMixin 1 vator meth illActivator), 411 ethod d), 41 d), 41 metho od), 4 • meth), 414 3 4 d), 415 13 od), 415
_hook_postamble() (_Activat _hook_preamble() (CmdExeA _hook_preamble() (CshActiva _hook_preamble() (FishActiv _hook_preamble() (JSONFor _hook_preamble() (PosixActi _hook_preamble() (PowerShe _hook_preamble() (XonshActi	or method activator m ator method ator metho matMixin 1 vator meth ellActivator ivator meth), 411 ethod d), 41 d), 41 netho od), 4 metho hod), 4), 414 3 4 d), 415 13 od), 415 414
_hook_postamble() (_Activat _hook_preamble() (CmdExeA _hook_preamble() (CshActiva _hook_preamble() (FishActiv _hook_preamble() (JSONFor _hook_preamble() (PowerShe _hook_preamble() (ConshActi _hook_preamble() (_Activato	or method activator m ator method ator metho matMixin i vator meth illActivator ivator meth r method),), 411 ethod d), 41 d), 41 netho od), 4 metho hod), 4 411), 414 3 4 d), 415 13 od), 415 414
_hook_postamble() (_Activat _hook_preamble() (CmdExeA _hook_preamble() (CshActiva _hook_preamble() (FishActiv _hook_preamble() (JSONFor _hook_preamble() (PowerSha _hook_preamble() (PowerSha _hook_preamble() (Activato _hook_preamble() (_Activato _hookspec (in module conda.p	or method activator m ator method ator metho matMixin 1 vator meth illActivator ivator meth r method), lugins.hoo), 411 ethod d), 41 d), 41 netho od), 4 `meth 'hod), 4 411 kspec)), 414 3 4 d), 415 13 od), 415 414), 675
_hook_postamble() (_Activat _hook_preamble() (CmdExeA _hook_preamble() (CshActiva _hook_preamble() (FishActiva _hook_preamble() (JSONFor _hook_preamble() (PowerSha _hook_preamble() (PowerSha _hook_preamble() (_Activato _hookspec (in module conda.p _hz_friendly_to_full()	or method activator m ator method ator metho matMixin 1 vator meth ilActivator ivator meth r method), lugins.hood (in), 411 ethod d), 41 netho od), 4 meth hod), 4 411 kspec)), 414 3 4 d), 415 13 od), 415 414), 675 module
_hook_postamble() (_Activat _hook_preamble() (CmdExeA _hook_preamble() (CshActiva _hook_preamble() (FishActiv _hook_preamble() (JSONFor _hook_preamble() (PowerSha _hook_preamble() (PowerSha _hook_preamble() (Activato _hook_preamble() (_Activato _hookspec (in module conda.p _hz_friendly_to_full() _ condavendor.cpuinfa	or method activator m ator method ator metho matMixin 1 vator meth llActivator ivator meth r method), lugins.hood (in o), 396), 411 ethod d), 41 d), 41 netho od), 4 meth hod), 4 411 kspec), 414 3 4 d), 415 13 od), 415 414), 675 module
_hook_postamble() (_Activat _hook_preamble() (CmdExeA _hook_preamble() (CshActiva _hook_preamble() (FishActiv _hook_preamble() (JSONFor _hook_preamble() (PowerShe _hook_preamble() (PowerShe _hook_preamble() (Activato _hookspec (in module conda.p _hz_friendly_to_full() _hz_friendly_to_full()	or method activator m ator method ator metho matMixin n vator meth illActivator ivator meth r method), lugins.hood (in p), 396 (in), 411 ethod d), 41 d), 41 netho od), 4 · meth hod), 4 411 kspec)), 414 3 4 d), 415 13 od), 415 414), 675 module module
_hook_postamble() (_Activat _hook_preamble() (CmdExeA _hook_preamble() (CshActiva _hook_preamble() (FishActiva _hook_preamble() (JSONFor _hook_preamble() (PosixActi _hook_preamble() (PowerShe _hook_preamble() (Activato _hookspec (in module conda.p _hz_friendly_to_full() _condavendor.cpuinfa _hz_friendly_to_full()	or method activator m ator method ator metho matMixin 1 vator meth llActivator ivator meth r method), lugins.hood (in), 396 (in 0.cpuinfo),), 411 ethod d), 41 d), 41 netho od), 4 meth hod), 4 411 kspec 390), 414 3 4 d), 415 13 od), 415 414), 675 module module
<pre>_hook_postamble() (_Activat _hook_preamble() (CmdExeA _hook_preamble() (CshActivat _hook_preamble() (FishActivat _hook_preamble() (JSONFor _hook_preamble() (PosixActi _hook_preamble() (PowerShet _hook_preamble() (Activato _hookspec (in module conda.p _hz_friendly_to_full() _condavendor.cpuinfat _hz_friendly_to_full() _condavendor.cpuinfat_hz_short_to_friendly()</pre>	or method activator m ator method matMixin 1 vator meth ilActivator ivator meth r method), lugins.hood (in 0), 396 (in 0.cpuinfo), (in), 411 ethod d), 41 d), 41 netho od), 4 meth hod), 4 411 kspec), 414 3 4 d), 415 13 od), 415 414), 675 module module module
<pre>_hook_postamble() (_Activat _hook_preamble() (CmdExeA _hook_preamble() (CshActivat _hook_preamble() (FishActivat _hook_preamble() (FishActivat) _hook_preamble() (PosixActi _hook_preamble() (PowerShat _hook_preamble() (Activato _hook_preamble() (_Activato _hookspec (in module conda.p _hz_friendly_to_full() _condavendor.cpuinfat _hz_short_to_friendly() _condavendor.cpuinfat</pre>	or method activator m ator method matMixin r vator meth ivator meth ivator meth r method), lugins.hood (in 0), 396 (in 0.cpuinfo), (in 0), 396), 411 ethod d), 41 d), 41 netho od), 4 meth hod), 4 411 kspec)), 414 3 4 d), 415 13 od), 415 414), 675 module module module
<pre>_hook_postamble() (_Activat _hook_preamble() (CmdExeA _hook_preamble() (CshActiva _hook_preamble() (FishActiva _hook_preamble() (FishActiva _hook_preamble() (PosixActia _hook_preamble() (PowerShea _hook_preamble() (ConshActaa _hook_preamble() (Activatoaa _hook_preamble() (_Activatoaa _hookspec (in module conda.p _hz_friendly_to_full() _condavendor.cpuinfaa _hz_friendly_to_full() _condavendor.cpuinfaa _hz_short_to_friendly() _condavendor.cpuinfaa _hz_short_to_friendly()</pre>	or method activator m ator method matMixin r vator meth ivator meth ivator meth r method), lugins.hood (in p), 396 (in p), 396 (in p), 396 (in p), 396), 411 ethod d), 41 d), 41 netho od), 4 meth hod), 4 411 kspec)), 414 3 4 d), 415 13 od), 415 414), 675 module module module module
<pre>_hook_postamble() (_Activat _hook_preamble() (CmdExeA _hook_preamble() (CshActiva _hook_preamble() (FishActiva _hook_preamble() (FishActiva _hook_preamble() (PosixActia _hook_preamble() (PowerShea _hook_preamble() (ConshActia _hook_preamble() (Activatoa _hook_preamble() (_Activatoa _hookspec (in module conda.p _hz_friendly_to_full() _conda_vendor.cpuinfa _hz_friendly_to_full() _condavendor.cpuinfa _hz_short_to_friendly() _conda_vendor.cpuinfa _hz_short_to_friendly()</pre>	or method activator m ator metho matMixin r vator meth ivator meth ivator meth r method), lugins.hoo (in), 396 (in o.cpuinfo), (in o), 396 (in o, cpuinfo)), 411 ethod d), 41 d), 41 netho od), 4 meth hod), 4 411 kspec) 390), 414 3 4 d), 415 13 od), 415 414), 675 module module module module
<pre>_hook_postamble() (_Activat _hook_preamble() (CmdExeA _hook_preamble() (CshActiva _hook_preamble() (FishActiv _hook_preamble() (FishActiv _hook_preamble() (PosixActi _hook_preamble() (PowerSha _hook_preamble() (Activato _hook_preamble() (Activato _hookspec (in module conda.p _hz_friendly_to_full() _condavendor.cpuinfa _hz_short_to_friendly() _condavendor.cpuinfa _hz_short_to_friendly() _condavendor.cpuinfa _hz_short_to_friendly() _condavendor.cpuinfa</pre>	or method activator m ator method ator metho matMixin 1 vator meth vator meth vator meth cllActivator ivator meth n method), lugins.hoo (in 0), 396 (in 0), 396 (in 0), 396 (in 0), 396 (in 0), 206), 411 ethod d), 41 d), 41 netho od), 4 meth hod), 4 411 kspec) 390), 414 3 4 d), 415 13 od), 415 414), 675 module module module module
<pre>_hook_postamble() (_Activat _hook_preamble() (CmdExeA _hook_preamble() (CshActiva _hook_preamble() (FishActiv _hook_preamble() (FishActiv _hook_preamble() (PosixActi _hook_preamble() (PowerShe _hook_preamble() (NonshActi _hook_preamble() (Activato _hookspec (in module conda.p _hz_friendly_to_full() _condavendor.cpuinfa _hz_short_to_friendly() _condavendor.cpuinfa _hz_short_to_friendly() _condavendor.cpuinfa _hz_short_to_friendly() _condavendor.cpuinfa _hz_short_to_friendly() _condavendor.cpuinfa _hz_short_to_friendly() _condavendor.cpuinfa</pre>	or method activator m ator method ator metho matMixin 1 vator meth vator meth ivator meth r method), lugins.hood (in p), 396 (in p), 396 (in p), 396 (in p), 396 (in p), 396 (in p), 396 (in p), 396 (in p), 396 (in p), 396), 411 ethod d), 41 netho od), 4 meth hod), 4 411 kspec) 390), 414 3 4 d), 415 13 od), 415 414), 675 module module module module module
<pre>_hook_postamble() (_Activat _hook_preamble() (CmdExeA _hook_preamble() (CshActiva _hook_preamble() (FishActiv _hook_preamble() (FishActiv _hook_preamble() (PosixActi _hook_preamble() (PosixActi _hook_preamble() (NonshAct _hook_preamble() (Activato _hookspec (in module conda.p _hz_friendly_to_full() _condavendor.cpuinfa _hz_friendly_to_full() _condavendor.cpuinfa _hz_short_to_friendly() _condavendor.cpuinfa _hz_short_to_friendly() _condavendor.cpuinfa _hz_short_to_friendly() _condavendor.cpuinfa _hz_short_to_full() _condavendor.cpuinfa _hz_short_to_full() _condavendor.cpuinfa</pre>	or method activator m ator method ator metho matMixin 1 vator meth ivator meth ivator meth r method), lugins.hood (in p), 396 (in p), 396 (in p), 396 (in p), 396 (in p), 396), 411 ethod d), 41 d), 41 netho od), 4 meth hod), 4 411 kspec) 390), 414 3 4 d), 415 13 od), 415 414), 675 module module module module
<pre>_hook_postamble() (_Activat _hook_preamble() (CmdExeA _hook_preamble() (CshActivat _hook_preamble() (FishActiv _hook_preamble() (JSONFor _hook_preamble() (PowerShat _hook_preamble() (PowerShat _hook_preamble() (Activato _hookspec (in module conda.p _hz_friendly_to_full() _condavendor.cpuinfa _hz_short_to_friendly() _condavendor.cpuinfa _hz_short_to_friendly() _condavendor.cpuinfa _hz_short_to_friendly() _condavendor.cpuinfa _hz_short_to_full() _condavendor.cpuinfa _hz_short_to_full() _condavendor.cpuinfa _hz_short_to_full()</pre>	or method activator m ator method ator metho matMixin i vator meth illActivator ivator meth r method), lugins.hoo (in p), 396 (in p), 396 (in p), 396 (in p), 396 (in p), 396), 411 ethod d), 41 netho od), 4 meth hod), 4 411 kspec) 390), 414 3 4 d), 415 13 od), 415 414), 675 module module module module module module
<pre>_hook_postamble() (_Activat _hook_preamble() (CmdExeA _hook_preamble() (CshActivat _hook_preamble() (FishActiv _hook_preamble() (FishActiv _hook_preamble() (PosixActi _hook_preamble() (PowerShe _hook_preamble() (PowerShe _hook_preamble() (Activato _hookspec (in module conda.p _hz_friendly_to_full() _condavendor.cpuinfa _hz_short_to_friendly() _condavendor.cpuinfa _hz_short_to_friendly() _condavendor.cpuinfa _hz_short_to_full() _condavendor.cpuinfa _hz_short_to_full() _condavendor.cpuinfa _hz_short_to_full() _condavendor.cpuinfa _hz_short_to_full() _condavendor.cpuinfa</pre>	or method activator m ator method matMixin i vator metho ivator meth r method), lugins.hood (in p), 396 (in p), 396 (in p), 396 (in p), 396 (in p), 396 (in p), 396 (in p), 396), 411 ethod d), 41 netho od), 4 meth hod), 4 411 kspec) 390), 414 3 4 d), 415 13 od), 415 414), 675 module module module module module
<pre>_hook_postamble() (_Activat _hook_preamble() (CmdExeA _hook_preamble() (CshActivat _hook_preamble() (FishActivat _hook_preamble() (FishActivat) _hook_preamble() (PosixActi _hook_preamble() (PowerShat _hook_preamble() (PowerShat _hook_preamble() (Activato _hookspec (in module conda.p _hz_friendly_to_full() _condavendor.cpuinfat _hz_short_to_friendly() _condavendor.cpuinfat _hz_short_to_friendly() _condavendor.cpuinfat _hz_short_to_full() _condavendor.cpuinfat _hz_short_to_full() _condavendor.cpuinfat _hz_short_to_full() _condavendor.cpuinfat _hz_short_to_full() _condavendor.cpuinfat _hz_short_to_full() _condavendor.cpuinfat _hz_short_to_full() _condavendor.cpuinfat _hz_short_to_full() _condavendor.cpuinfat _hz_short_to_full() _condavendor.cpuinfat _hz_short_to_full() _condavendor.cpuinfat _hz_short_to_full() _condavendor.cpuinfat _hz_short_to_full() _condavendor.cpuinfat _hz_short_to_full()</pre>	or method activator m ator method matMixin i vator metho ivator meth illActivator ivator meth r method), lugins.hood (in p), 396 (in p), 3), 411 ethod d), 41 netho od), 4 meth hod), 4 411 kspec 390 390 s.mat), 414 3 4 d), 415 13 od), 415 414), 675 module module module module module ch_spec),
<pre>_hook_postamble() (_Activat _hook_preamble() (CmdExeA _hook_preamble() (CshActivat _hook_preamble() (FishActivat _hook_preamble() (FishActivat) _hook_preamble() (PosixActi _hook_preamble() (PowerShat _hook_preamble() (ConshActi _hook_preamble() (Activato _hookspec (in module conda.p _hz_friendly_to_full() _condavendor.cpuinfat _hz_short_to_friendly() _condavendor.cpuinfat _hz_short_to_friendly() _condavendor.cpuinfat _hz_short_to_full() _condavendor.cpuinfat _hz_short_to_full() _condavendor.cpuinfat _hz_short_to_full() _condavendor.cpuinfat _hz_short_to_full() _condavendor.cpuinfat _hz_short_to_full() _condavendor.cpuinfat _hz_short_to_full() _condavendor.cpuinfat _hz_short_to_full() _condavendor.cpuinfat _hz_short_to_full() _condavendor.cpuinfat _hz_short_to_full() _condavendor.cpuinfat _hz_short_to_full() _condavendor.cpuinfat _hz_short_to_full() _condavendor.cpuinfat _hz_short_to_full()</pre>	or method activator m ttor method ator method matMixin 1 vator meth illActivator ivator meth r method), lugins.hool (in p), 396 (in p), 39), 411 ethod d), 41 netho od), 4 meth hod), 4 411 kspec 390 390), 414 3 4 d), 415 13 od), 415 414), 675 module module module module module ch_spec),
<pre>_hook_postamble() (_Activat _hook_preamble() (CmdExeA _hook_preamble() (CshActivat _hook_preamble() (FishActivat _hook_preamble() (FishActivat) _hook_preamble() (PosixActi _hook_preamble() (PowerShat _hook_preamble() (Activato _hookspec (in module conda.p _hz_friendly_to_full() _condavendor.cpuinfat _hz_short_to_friendly() _condavendor.cpuinfat _hz_short_to_friendly() _condavendor.cpuinfat _hz_short_to_friendly() _condavendor.cpuinfat _hz_short_to_full() _condavendor.cpuinfat _hz_short_to_full() _condavendor.cpuinfat _hz_short_to_full() _condavendor.cpuinfat _hz_short_to_full() _condavendor.cpuinfat _implementors (in module condation_precs()</pre>	or method activator m ttor method matMixin 1 vator method vator meth ivator meth r method), lugins.hool (in p), 396 (in p), 39), 411 ethod d), 41 netho od), 4 meth hod), 4 411 kspec 390 390 s.mat), 414 3 4 d), 415 13 od), 415 414), 675 module module module module module ch_spec), Container

_initd (Entity property), 43	5	
_initialize_dev_bash()	(in	module
conda.core.initializ	e), 546	
_initialize_dev_cmdexe	() (in	module
conda.core.initializ	e), 546	
_inject_UNLINKLINKTRANS	SACTION()	(in module
conda.plan), 674		
_install_file()(in modul	le conda.core.	initialize), 547
_is_bit_set() (in module of	condavendo	r.cpuinfo), 396
_is_bit_set()	(in	module
condavendor.cpu	nfo.cpuinfo),	390
_is_http_error_most_400	O_codes()	(in module
conda.gateways.rep	odata.jlap.fet	ch), 617
_is_literal()	(in	module
conda.common.pkg	formats.pvth	non), 530
is selinux enforcing() (in	module
conda, vendor.cpu	info). 396	
is selinux enforcing() (in	module
conda vendor com	info couinfo)	390
is simple() (MatchSpec	nethod) 646	570
is single() (Match Spect	method) 646	
is unix executable us	ing OPTCIN((in modula
	k or at a) 603	
conad.guieways.ais	(0.05)	0
_Isally (ExceptionHanaler	property), 57	9
_iter_records_by_name() (SubairData	i metnoa), 568
_lazy_validate (<i>Dist attri</i>	oute), 637	
_lazy_validate (Entity att	<i>ribute</i>), 436	
_load() (SubdirData method	1), 568	
_load_requires_provides	s_file() (P	ythonDistribu-
tion method), 524		
_load_search_path() (Co	onfiguration d	class method),
506		
_load_single_record() (PrefixData me	ethod), 563
_load_site_packages() (PrefixData me	ethod), 563
_lock_impl() (in module	conda.gatew	vays.disk.lock),
605		
<pre>_lock_noop() (in module</pre>	conda.gatew	vays.disk.lock),
605		
<pre>_logger_lock() (in module</pre>	e conda.comm	on.io), 511
_make_channel_prioriti	es() (Res	solve static
<i>method</i>), 699		
_make_compile_actions()) (UnlinkL	inkTransaction
static method), 551	· • • • • • • • • • • • • • • • • • • •	
make component() (Match	hSpec static m	nethod), 646
make entry point action	ons() (Unlin	kLinkTransac-
tion static method)	551	
make legacy action gro	(Un)	linkLinkTrans-
action method) 55	1 1	undenna in ans
make link actions() (I	InlinkI inkTra	nsaction static
	LIIINIIU	nsuchon stull
memou), 331	(Timestam)	Field statio
_mathod) 655	(1 mesiump)	siulle
memou), 055	mnField stati	mathod) 655
_make_seconds() (<i>nimestan</i>	חטר ופוט אומות -1- המי	aacCask a D = 1
_make_single_record()	(Pack	ugeCacheData

method), 553, 621, 717 _make_virtual_package() (in module conda.core.index), 541 _match_individual() (MatchSpec method), 646 _match_key_is_important() (LoadedParameter static method), 501 _md5_not_for_security() (in module conda.gateways.repodata), 626 _merge() (*MatchSpec method*), 646 _message_to_dict() (PythonDistributionMetadata class method), 526 _migrated_channel_aliases (Context attribute), 456 _native_subdir() (Context method), 458 _new_makepasv() (in module conda.gateways.connection.adapters.ftp), 593 _notify_conda_outdated() (Solver method), 566 _obj_to_b64() (in module conda. vendor.cpuinfo), 396 _obj_to_b64() module (in conda. vendor.cpuinfo.cpuinfo), 390 _old_makepasv (in module conda.gateways.connection.adapters.ftp), 593 _order_helper (*Field attribute*), 432 _override() (Context method), 458 _package_cache_records (PackageCacheData property), 552, 621, 716 _package_data() (SimpleEnvironment method), 712 _package_has_updates() (Solver method), 566 _parse_and_set_args() (_Activator method), 411 _parse_arch() (in module conda._vendor.cpuinfo), 396 _parse_arch() (in module conda._vendor.cpuinfo.cpuinfo), 390 _parse_channel() (in module conda.models.match spec), 647 _parse_comment_line() (History class method), 629 _parse_cpu_brand_string() (in module conda._vendor.cpuinfo), 396 _parse_cpu_brand_string() (in module conda._vendor.cpuinfo.cpuinfo), 390 _parse_cpu_brand_string_dx() module (in conda. vendor.cpuinfo), 396 _parse_cpu_brand_string_dx() (in module conda._vendor.cpuinfo.cpuinfo), 390 _parse_distro_release_content() (LinuxDistribution static method), 407 _parse_distro_release_file() (LinuxDistribution method), 407 _parse_dmesg_output() (in module conda._vendor.cpuinfo), 396 _parse_dmesg_output() module (in conda._vendor.cpuinfo.cpuinfo), 390 _parse_entries_file_data() (PythonDistribution static method), 524

_parse_iso_timestamp() (ChannelNoticeResponse static method), 672 _parse_legacy_dist() (in module conda.models.match_spec), 647 _parse_lsb_release_content() (LinuxDistribution static method), 407 _parse_notice_level() (ChannelNoticeResponse static method), 672 _parse_old_format_specs_string() (History static method), 629 _parse_os_release_content() (LinuxDistribution static method), 407 _parse_requires_file_data() (PythonDistribution static method), 524 _parse_spec_str() module (in conda.models.match_spec), 647 _parse_version_plus_build() module (in conda.models.match spec), 646 _patch_for_local_exports() module (in conda.testing.helpers), 705 _path (LeasedPathEntry attribute), 642 _path (PathData attribute), 657 _pickle_me() (SubdirData method), 568 _pickle_valid_checks() (SubdirData method), 568 _pip_install_via_requirements() (in module conda.env.installers.pip), 574 _pkey (PackageRecord property), 658, 717 _pkgs_dirs (Context attribute), 455 _plan_from_actions() (in module conda.plan), 674 _platform_map (in module conda.base.context), 452 _post_sat_handling() (Solver method), 566 _post_upload() (ExceptionHandler method), 580 _powershell_profile_content() (in module conda.core.initialize), 548 _prefix_records (*PrefixData property*), 562 _prepare() (Solver method), 566 _prepare() (UnlinkLinkTransaction class method), 550 _print_conda_exception() (ExceptionHandler method), 579 _process_path() (PythonDistributionMetadata static method), 526 _process_raw_repodata() (SubdirData method), 568 _process_raw_repodata_str() (SubdirData method), 568 _program_paths() (in module conda._vendor.cpuinfo), 396 _program_paths() (in module conda._vendor.cpuinfo.cpuinfo), 390 _progress_bar() (ProgressiveFetchExtract static method), 554 _prompt_modifier() (_Activator method), 412 _python_pkg_record (*PrefixData property*), 562

_raw_parameters_from_single_source() (ParameterLoader method), 505

	(<i>ın</i>	module	
conda.models.channel), 636			
_read_local_repodata() (SubdirDe	ata meth	od), 568	
_read_metadata() (<i>PythonDistribut</i>	onMeta	data class	
method), 526			
_read_pickled() (SubdirData metho	d), 568		
read windows registry()	(in	module	
conda.core.initialize). 548			
read windows registry key()	(in	module	
conda, vendor cpuinfo), 396	(mounte	
read windows registry key()	(in	module	
	(n) 300	mounic	
romous node() (Profix Granh mathe	d) 652		
$remove_node() (I rejuding n method$	i), 052	method)	
	cuvaior	methoa),	
412	66		
_remove_specs() (Solver method), 50			
_replace_prefix_in_path() (_Ad	ctivator	methoa),	
412			
_repo (<i>RepodataFetch property</i>), 626			
_repo (SubdirData property), 567			
_repodata_fn(<i>CondaRepoInterface</i> d	uttribute), 624	
_repodata_state_copy() (IlapRep	oInterface	
<i>method</i>), 617			
_repodata_state_copy() (ZstdRep	oInterface	
<i>method</i>), 618			
_repodata_threads (Context attribut	te), 455		
_reporters (<i>Context attribute</i>), 456			
_reset_cache() (Configuration meth	od), 506		
reset state() (Channel static method), 600			
<pre>_reset_state() (Channel static meth</pre>	nod, 622	2,635	
_reset_state() (Channel static meth _reverse_actions() (UnlinkLinkT	10d), 622 Fransacti	2, 635 on static	
<pre>_reset_state() (Channel static meth _reverse_actions() (UnlinkLinkT</pre>	nod), 622 Fransacti	2,635 on static	
<pre>_reset_state() (Channel static meth _reverse_actions() (UnlinkLinkT</pre>	iod), 622 transacti (in	2, 635 on static module	
<pre>_reset_state() (Channel static meth _reverse_actions() (UnlinkLinkT</pre>	(in	2,635 on static module	
<pre>_reset_state() (Channel static meth _reverse_actions() (UnlinkLinkT</pre>	iod), 622 Fransacti (in (39 Slean) 4	2, 635 on static module	
<pre>_reset_state() (Channel static meth _reverse_actions() (UnlinkLinkT</pre>	iod), 622 Gransacti (in 139 Sclean), 4	2, 635 on static module 71	
<pre>_reset_state() (Channel static meth _reverse_actions() (UnlinkLinkT</pre>	(in (in (39 (clean), 4	2, 635 on static module 71 modula	
<pre>_reset_state() (Channel static meth _reverse_actions() (UnlinkLinkT</pre>	(in (in 39 (lean), 4 5	2, 635 on static module 71 module	
<pre>_reset_state() (Channel static meth _reverse_actions() (UnlinkLinkT</pre>	(in (in (39 (clean), 4 (5)	2, 635 on static module 71 module module	
<pre>_reset_state() (Channel static meth _reverse_actions() (UnlinkLinkT</pre>	(in (in (39 clean), 4 5 n	2, 635 on static module 71 module module	
<pre>_reset_state() (Channel static meth _reverse_actions() (UnlinkLinkT</pre>	(in (in (339 (clean), 4 5 n fo), 390	2, 635 on static module 71 module module	
<pre>_reset_state() (Channel static meth _reverse_actions() (UnlinkLinkT</pre>	(in (in (339 (clean), 4 (5) (n) (6), 390 (0)	2, 635 on static module 71 module module	
<pre>_reset_state() (Channel static meth _reverse_actions() (UnlinkLinkT method), 551 _rewrite_environments_txt() conda.core.envs_manager), 5 _rm_rf() (in module conda.cli.main_c _root_prefix (Context attribute), 453 _run_and_get_stdout() (i condavendor.cpuinfo), 396 _run_and_get_stdout() (i condavendor.cpuinfo.cpuinj _run_asm() (CPUID method), 390, 39 _run_sat() (Clauses method), 491</pre>	nod), 622 fransacti (in 339 clean), 4 5 n n fo), 390	2, 635 on static module 71 module module	
<pre>_reset_state() (Channel static meth _reverse_actions() (UnlinkLinkT</pre>	nod), 622 Gransacti (in (339 Sclean), 4 5 n n fo), 390	2, 635 on static module 71 module module	
<pre>_reset_state() (Channel static meth _reverse_actions() (UnlinkLinkT</pre>	nod), 622 Fransacti (in 339 Elean), 4 5 n n fo), 390	2, 635 on static module 71 module module module	
<pre>_reset_state() (Channel static meth _reverse_actions() (UnlinkLinkT</pre>	aod), 622 fransacti (in (339 clean), 4 5 n fo), 390 97	2, 635 on static module 71 module module module	
<pre>_reset_state() (Channel static meth _reverse_actions() (UnlinkLinkT</pre>	aod), 622 fransacti (in (339 clean), 4 5 n fo), 390 97 3 in	2, 635 on static module 71 module module module module	
<pre>_reset_state() (Channel static meth _reverse_actions() (UnlinkLinkT </pre>	aod), 622 ransacti (in (39 clean), 4 5 n fo), 390 97 3 in	2, 635 on static module 71 module module module module	
<pre>_reset_state() (Channel static meth _reverse_actions() (UnlinkLinkT _method), 551 _rewrite_environments_txt() _ conda.core.envs_manager), 5 _rm_rf() (in module conda.cli.main_oc _root_prefix (Context attribute), 455 _run_and_get_stdout() (i _ condavendor.cpuinfo), 396 _run_and_get_stdout() (i _ condavendor.cpuinfo.cpuinj _run_asm() (CPUID method), 390, 39 _run_sat() (Clauses method), 491 _run_sat() (Solver method), 566 _safe_toposort() (in _ conda.common.toposort), 533 _sat_solver_cls_to_str (in _ conda.commonlogic), 490 _sat_solver_str_to_cls (in</pre>	and), 622 fransacti (in (39 clean), 4 5 n fo), 390 97 3 in	2, 635 on static module 71 module module module module module module	
<pre>_reset_state() (Channel static meth _reverse_actions() (UnlinkLinkT _method), 551 _rewrite_environments_txt() _ conda.core.envs_manager), 5 _rm_rf() (in module conda.cli.main_co _root_prefix (Context attribute), 455 _run_and_get_stdout() (i _ condavendor.cpuinfo), 396 _run_and_get_stdout() (i _ condavendor.cpuinfo.cpuinj _run_asm() (CPUID method), 390, 39 _run_sat() (Clauses method), 491 _run_sat() (Solver method), 566 _safe_toposort() (in _ conda.common.toposort), 533 _sat_solver_cls_to_str (i _ conda.commonlogic), 490 _sat_solver_str_to_cls (i _ conda.commonlogic), 490</pre>	aod), 622 fransacti (in 339 clean), 4 5 n fo), 390 97 3 in	2, 635 on static module 71 module module module module module module	
<pre>_reset_state() (Channel static meth _reverse_actions() (UnlinkLinkT _method), 551 _rewrite_environments_txt() _ conda.core.envs_manager), 5 _rm_rf() (in module conda.cli.main_oc _root_prefix (Context attribute), 453 _run_and_get_stdout() (i _ condavendor.cpuinfo), 396 _run_and_get_stdout() (i _ condavendor.cpuinfo.cpuinj _run_asm() (CPUID method), 390, 39 _run_sat() (Clauses method), 491 _run_sat() (Solver method), 566 _safe_toposort() (in _ conda.common.toposort), 533 _sat_solver_cls_to_str (i _ conda.commonlogic), 490 _sat_solverstr_to_cls (i _ conda.commonlogic), 490</pre>	aod), 622 prod), 622 pransacti (in (339 clean), 4 5 n fo), 390 97 3 in in (ve), 697	2, 635 on static module 71 module module module module module module	
<pre>_reset_state() (Channel static meth _reverse_actions() (UnlinkLinkT _method), 551 _rewrite_environments_txt() _ conda.core.envs_manager), 5 _rm_rf() (in module conda.cli.main_oc _root_prefix (Context attribute), 453 _run_and_get_stdout() (i _ conda.vendor.cpuinfo), 396 _run_and_get_stdout() (i _ conda.vendor.cpuinfo.cpuinj _run_asm() (CPUID method), 390, 39 _run_sat() (Clauses method), 491 _run_sat() (Solver method), 566 _safe_toposort() (in _ conda.common.toposort), 533 _sat_solver_cls_to_str (in _ conda.commonlogic), 490 _sat_solvers(in module conda.resol _scan_for_dist_no_channel() (P</pre>	(in (in (39 (clean), 4 (5) (clean), 4 (5) (clean), 4 (7) (clean), 4 (clean), 3 (clean), 4 (clean), 3 (clean), 4 (clean), 3 (clean),	2, 635 on static module 71 module module module module module SacheData	
<pre>_reset_state() (Channel static meth _reverse_actions() (UnlinkLinkT _method), 551 _rewrite_environments_txt() _ conda.core.envs_manager), 5 _rm_rf() (in module conda.cli.main_co _root_prefix (Context attribute), 453 _run_and_get_stdout() (i. _ condavendor.cpuinfo.goin), 396 _run_and_get_stdout() (i. _ condavendor.cpuinfo.cpuin) _run_asm() (CPUID method), 390, 39 _run_sat() (Clauses method), 491 _run_sat() (Solver method), 566 _safe_toposort() (in _ conda.common.toposort), 533 _sat_solver_cls_to_str (in _ conda.commonlogic), 490 _sat_solvers (in module conda.resol _scan_for_dist_no_channel() (P _ method), 553, 621, 717</pre>	(in (in (39 (lean), 4 (in (in), 390 (in), 390 (in) (in) (ve), 697 (ackageC	2, 635 on static module 71 module module module module module SacheData	
<pre>_reset_state() (Channel static meth _reverse_actions() (UnlinkLinkT _method), 551 _rewrite_environments_txt() _ conda.core.envs_manager), 5 _rm_rf() (in module conda.cli.main_c _root_prefix (Context attribute), 453 _run_and_get_stdout() (i _ condavendor.cpuinfo.goin), 396 _run_and_get_stdout() (i _ condavendor.cpuinfo.cpuin) _run_asm() (CPUID method), 390, 39 _run_sat() (Clauses method), 491 _run_sat() (Solver method), 566 _safe_toposort() (in _ conda.common.toposort), 533 _sat_solver_cls_to_str () _ conda.commonlogic), 490 _sat_solvers(in module conda.resol _scan_for_dist_no_channel() (F _ method), 553, 621, 717 _send_boto3() (S3Adapter method).</pre>	(in (in (39 (lean), 4 (in (in), 390 (in), 390 (in) (in) (ive), 697 (ackageC) (597	2, 635 on static module 71 module module module module module SacheData	
<pre>_reset_state() (Channel static meth _reverse_actions() (UnlinkLinkT </pre>	(in (in (39 (lean), 4 (in (i) (i) (i) (i) (i) (i) (i) (i) (i) (i)	2, 635 on static module 71 module module module module cacheData	
<pre>_reset_state() (Channel static meth _reverse_actions() (UnlinkLinkT </pre>	(in (in (39 (clean), 4 (5 n fo), 390 (07 (5), 390 (07 (5), 390 (07) (3) (in (in) (ve), 697 (ackageC (597 (on method))	2, 635 on static module 71 module module module module cacheData	

_set_env_vars() (Configuration method), 506 _set_name() (ParameterLoader method), 505 _set_raw_data() (Configuration method), 506 _set_search_path() (Configuration method), 506 _should_freeze() (Solver method), 566 _signing_metadata_url_base (Context attribute), 455 _solve() (in module conda.env.installers.conda), 574 _solver_helper() (in module conda.testing.fixtures), 702 _split_platform_re() (in module conda.common.url), 537 _start_spinning() (Spinner method), 511 _strings (RepodataState attribute), 624 _subdir (Context attribute), 455 _subdir_is_win() (in module conda.core.portability), 561 _subdirs (Context attribute), 455 _subprocess_clean_env() (in module conda.gateways.subprocess), 627 _supplement_index_with_cache() (in module conda.core.index), 541 _supplement_index_with_features() (in module conda.core.index), 542 _supplement_index_with_prefix() (in module conda.core.index), 541 _supplement_index_with_system() (in module conda.core.index), 542 _symlink_conda_hlp() (in module conda.exports), 591 _sync_channel_to_disk() module (in conda.testing.helpers), 705 _to_decimal_string() (in module conda._vendor.cpuinfo), 396 _to_decimal_string() (in module conda. vendor.cpuinfo.cpuinfo), 390 _to_filename_do_not_use() (MatchSpec method), 646 _to_friendly_bytes() (in module conda._vendor.cpuinfo), 396 _to_friendly_bytes() module (in conda. vendor.cpuinfo.cpuinfo), 390 _topo_sort_handle_cycles() (PrefixGraph class method), 652 _toposort() (PrefixGraph method), 652 _toposort() (in module conda.common.toposort), 532 _toposort_pop_key() (PrefixGraph static method), 652 _toposort_prepare_graph() (PrefixGraph static method), 652 _toposort_raise_on_cycles() (PrefixGraph class method), 652 _tqdm() (ProgressBar static method), 512 _trace (Context attribute), 456 _type (BooleanField attribute), 433

_type (DateField attribute), 434 _type (IntegerField attribute), 433 _type (*ListField attribute*), 435 _type (LoadedParameter attribute), 500 _type (MapField attribute), 436 _type (*MapLoadedParameter attribute*), 502 _type (*MapParameter attribute*), 504 _type (NumberField attribute), 433 _type (ObjectLoadedParameter attribute), 502 _type (*ObjectParameter attribute*), 505 _type (Parameter attribute), 503 _type (SequenceLoadedParameter attribute), 502 _type (SequenceParameter attribute), 504 _type (*StringField attribute*), 434 _typify_data_structure() (LoadedParameter static method), 501 _update_old_plan() (in module conda.plan), 674 _update_prompt() (CshActivator method), 413 _update_prompt() (PosixActivator method), 413 _update_prompt() (_Activator method), 412 _upload() (*ExceptionHandler method*), 580 _url (CondaRepoInterface attribute), 624 _use_only_tar_bz2 (Context attribute), 456 _utf_to_str() (in module conda. vendor.cpuinfo), 396 _utf_to_str() (in module conda. vendor.cpuinfo.cpuinfo), 390 _valid_file() (RequirementsSpec method), 576, 578 _valid_name() (RequirementsSpec method), 576, 578 _verbosity (Context attribute), 457 _verified (_Action attribute), 556 _verify() (UnlinkLinkTransaction method), 550 _verify_individual_level() (UnlinkLinkTransaction static method), 550 _verify_pre_link_message() (UnlinkLinkTransaction method), 550 _verify_prefix_level() (UnlinkLinkTransaction static method), 550 _verify_threads (Context attribute), 455 _verify_transaction_level() (UnlinkLinkTransaction static method), 550 _version (DeprecationHandler attribute), 569 _version_less_than() (DeprecationHandler method), 569 _version_object (DeprecationHandler attribute), 569 _version_tuple (*DeprecationHandler attribute*), 569 _wait_and_close_handle() module (in conda.common._os.windows), 493 _write_environment_state_file() (PrefixData method), 563 _write_installed_packages() (SimpleEnvironment method), 712 _write_repo_packages() (SimpleEnvironment method), 712 _write_tempfile() (S3Adapter method), 597

- _yield_commands() (*Activator method*), 411

A

aarch64 (Arch attribute), 639 ACCESS_DENIED (ERROR attribute), 493 action (CondaHealthCheck attribute), 372, 689, 694 action (CondaPostCommand attribute), 373, 688, 694 action (CondaPostSolve attribute), 690, 694 action (CondaPreCommand attribute), 374, 688, 695 action (CondaPreSolve attribute), 689, 695 action (CondaSubcommand attribute), 377, 686, 687, 696 action() (DeprecationHandler method), 570 ACTION_CODES (in module conda.instructions), 632 ActionGroup (class in conda.core.link), 549 actions (ActionGroup attribute), 549 activate() (_Activator method), 411 ActivateHelp, 580 activator_map (in module conda.activate), 415 active_prefix (Context property), 453 add() (Dependencies method), 573 add() (JLAP method), 614 add_anaconda_token (Context attribute), 456 add_binstar_token() (CondaHttpAuth static method), 601 add_channels() (Environment method), 573 add_clause() (Clauses method), 515 add_clauses() (Clauses method), 515 add_defaults_to_specs() (in module conda.plan), 674 add_export_unset_vars() (_Activator method), 411 add_feature_records_legacy() (in module conda.testing.helpers), 705 add_output_and_prompt_options() (in module conda.cli.helpers), 468 add_parser_channels() (in module conda.cli.helpers), 468 add_parser_create_install_update() (in module conda.cli.helpers), 468 add_parser_default_packages() (in module conda.cli.helpers), 469 add_parser_help() (in module conda.cli.helpers), 468 add_parser_help() (in module conda.plugins.subcommands.doctor), 685 add_parser_json() (in module conda.cli.helpers), 468

add_parser_networking()	(in	module
add_parser_package_instal	1_options()) (in mod-
add_parser_platform()	409 (in	module
conda.cli.helpers), 469)	
add_parser_prefix() (in mo	odule conda.c	cli.helpers),
add_parser_prefix()	(in mands.doctor	<i>module</i>), 685
add_parser_prune() (in mo	dule conda.c	cli.helpers),
add_parser_pscheck() (in ma 468	odule conda.c	cli.helpers),
add_parser_show_channel_u	rls() (in	module
conda.cli.helpers), 468	3	
add_parser_solver() (in ma 468	odule conda.c	cli.helpers),
add_parser_solver_mode() <i>conda.cli.helpers</i>), 468	(in	module
add_parser_update_modifie <i>conda.cli.helpers</i>), 468	ers() (in	module
add_parser_verbose() (in ma	odule conda.c	cli.helpers),
add_parser_verbose()	(in	module
conda.plugins.subcom add_pip_as_python_depende 454	mands.doctor mcy (Context), 685 attribute),
add_plugin_setting() conda.base.context). 4	(in 59	module
add_resp_to_mock()	(in	module
conda.testing.notices.h	elpers), 711	
add_subdir() (in module cond	a.testing.help	ers), 705
add_subdir_to_iter()	(in	module
conda.testing.helpers),	705	
add_unlink() (in module cond	a.plan), 673	
add_ur1() (UrlsData method),	553	
add_username_and_password	l() (in	module
conda.common.url), 5	3/	
Administering a multi-use	r conda	
Installation, /2	ation (a	lass in
Aggregatecomplientilipyca	(2)	uass in
aggressive_update_package	s (Context	property),
aliases (CondaSetting attribute	e), 375, 690, 6	595
All() (Clauses method), 491, 5	16	
all_ancestors() (<i>PrefixGrap</i>	h method), 65	2
all_caches_writable_first	() (Package	CacheData
class method), 553, 62	1,717	
all_channel_urls()	(in	module
conda.models.channel), 636	
all_descendants() (<i>PrefixGre</i>	aph method),	652
	d) 666	

all_subdir_urls() (*PrefixData method*), 563 allow_conda_downgrades (Context attribute), 454 allow_cycles (*Context attribute*), 454 allow_non_channel_urls (Context attribute), 456 allow_softlinks (Context attribute), 454 allowlist_channels (Context attribute), 456 altered files() module (in conda.plugins.subcommands.doctor.health_checks), 684 always_copy (Context attribute), 456 always_softlink (Context attribute), 456 always_true_match() (BaseSpec method), 666 always_yes (*Context attribute*), 456 Anaconda Distribution, 12 anaconda_upload (Context attribute), 457 AND (in module conda.common.pkg_formats.python), 530 And() (Clauses method), 491, 516 Any() (Clauses method), 491, 516 any_match() (BaseSpec method), 666 any_subprocess() (in module conda.gateways.subprocess), 627 APP_NAME (in module conda.base.constants), 446 AppDirs (class in conda._vendor.appdirs), 385 AppDirsError, 383 append() (_ClauseArray method), 489 application_entry_point (LeasedPathType attribute), 641 application_entry_point_template (in module conda.gateways.disk.create), 603 application_entry_point_windows_exe (Leased-PathType attribute), 641 application_softlink (*LeasedPathType attribute*), 641 apply() (ContextStack method), 458 apply() (ContextStackObject method), 458 apply_patches() module (in conda.gateways.repodata.jlap.fetch), 616 appname (in module conda._vendor.appdirs), 386 Arch (class in conda.models.enums), 639 arch (PackageRecord attribute), 659, 718 arch_name (Context property), 453 arch_name (in module conda.exports), 590 arch_string_raw (DataSource attribute), 388, 395 arg2spec() (in module conda.cli.common), 462 ArgParseRawParameter (class in conda.common.configuration), 500 argument() (DeprecationHandler method), 570 ArgumentError, 580 ArgumentParser (class in conda.cli.conda_argparse), 464 argv() (in module conda.common.io), 511 arm64 (Arch attribute), 639 armv61 (Arch attribute), 639 armv71 (Arch attribute), 639

as_array() (*ClauseArray method*), 489 as_array() (_ClauseList method), 489 as_completed (in module conda.common.io), 513 as_dict() (Url method), 535 as_list() (ClauseArray method), 489 as_list() (ClauseList method), 489 as_list() (SatSolver method), 489 as_list() (Clauses method), 490, 515 ASM (class in conda._vendor.cpuinfo), 396 ASM (class in conda._vendor.cpuinfo.cpuinfo), 390 assert_equals() (in module conda.testing.helpers), 705 assert_in() (in module conda.testing.helpers), 705 assert_not_in() (in module conda.testing.helpers), 705 assert_unsatisfiable() (SolverTests method), 713 assign() (Clauses method), 490 AssignmentError, 438 ASSOC_INCOMPLETE (ERROR attribute), 493 AtMostOne() (Clauses method), 516 AtMostOne_BDD() (Clauses method), 491, 516 AtMostOne_NSQ() (Clauses method), 491, 516 attach_stderr() (in module conda.auxlib.logz), 440 attach stderr handler() (in module conda.common.io), 511 AttrDict (class in conda.auxlib.collection), 422 auth (PrefixRecord attribute), 660 auth (Url property), 535 AuthenticationError, 437, 584 auto_activate_base (Context attribute), 454 auto_injector_fixture() (BaseTestCase method), 701 auto_stack (Context attribute), 454 auto_update_conda (Context attribute), 454 AuxlibError (class in conda.auxlib.exceptions), 437 av_data_dir (Context property), 453

В

backend (CondaSolver attribute), 376, 688, 695 backoff_rename() (in module conda.gateways.disk.update), 609 backoff_rmdir() module (in conda.gateways.disk.delete), 604 modulebackslash_to_forwardslash() (in conda.activate), 412 BAD_FORMAT (ERROR attribute), 493 bad_installed() (Resolve method), 700 base_url (Channel property), 622, 635 base_url (Dist attribute), 638 base_url (MultiChannel property), 636 base_urls (Channel property), 622, 635 base_urls (MultiChannel property), 636 BaseSpec (class in conda.models.version), 665 BaseTestCase (class in conda.testing.cases), 700

basic_types() (PathType method), 641 BasicClobberError. 581 BDD() (Clauses method), 491 BIN_DIRECTORY (in module conda.testing.integration), 708 binary (FileMode attribute), 640 binary_replace() (in module conda.core.portability), 561 BinaryPrefixReplacementError, 585 binstar() (BinstarSpec method), 576, 578 binstar_upload (Context property), 454 binstar_upload (in module conda.exports), 590 BinstarSpec (class in conda.env.specs), 577 BinstarSpec (class in conda.env.specs.binstar), 575 bits (Context property), 453 bits (DataSource attribute), 388, 395 bits (in module conda.exports), 590 bld_path (*Context attribute*), 457 body (JLAP property), 613 BooleanField (*class in conda.auxlib.entity*), 432 BooleanOptionalAction (class in conda.cli.helpers), 467 BoolField (in module conda.auxlib.entity), 433 boolify() (in module conda.auxlib.type coercion), 442 bottom (ParameterFlag attribute), 499 box() (FeaturesField method), 656 box() (BooleanField method), 433 box() (ComposableField method), 436 box() (DateField method), 434 box() (EnumField method), 435 box() (Field method), 432 box() (LinkTypeField method), 655 box() (ListField method), 435 box() (MapField method), 436 box() (NoarchField method), 650, 655 box() (StringField method), 434 box() (TimestampField method), 655 breadth_first_search_by_name() (GeneralGraph method), 653 breadth_first_search_for_dep_graph() (Resolve method), 698 build (CondaVirtualPackage attribute), 378, 688, 696 build (Dist property), 637 build (PackageInfo property), 651 build (PackageRecord attribute), 658, 717 build_activate() (_Activator method), 411 build_binary_response() (in module conda.gateways.connection.adapters.ftp), 594 build_conflict_map() (Resolve method), 698 build_deactivate() (_Activator method), 412 build_graph_of_deps() (Resolve method), 698 build_headers() (in module conda.gateways.repodata.jlap.fetch), 616

build_number (Dist attribute), 638 build_number (DistDetails attribute), 637 build_number (PackageInfo property), 651 build_number (PackageRecord attribute), 658, 717 build_number() (in module conda. vendor.distro), 403 build_number() (LinuxDistribution method), 406 build_reactivate() (Activator method), 412 build_response() (in module conda.gateways.connection.adapters.ftp), 594 build_stack() (_Activator method), 411 build_string (Dist attribute), 638 build_string (DistDetails attribute), 637 build_text_response() (in module conda.gateways.connection.adapters.ftp), 594 BuildNumberMatch (class in conda.models.version), 666 BUILTIN_COMMANDS module (in conda.cli.conda_argparse), 464

С

cache_actions (ProgressiveFetchExtract property), 553 cache_clear() (_SignatureVerification class method), 721 cache_clear() (CondaSession class method), 600 cache_control (RepodataState property), 624 CACHE_CONTROL_KEY module (in conda.gateways.repodata), 623 cache_fn_url() (in module conda.gateways.repodata), 626 cache_path_base (RepodataFetch attribute), 626 cache_path_base (SubdirData property), 568 cache_path_json (*RepodataCache property*), 625 cache_path_j son (RepodataFetch property), 626 cache_path_json (SubdirData property), 568 cache_path_pickle (SubdirData property), 568 cache_path_state (*RepodataCache property*), 625 cache_path_state (*RepodataFetch property*), 626 cache_path_state (SubdirData property), 568 CACHE_STATE_SUFFIX module (in conda.gateways.repodata), 623 cached_cuda_version() module (in conda.plugins.virtual_packages.cuda), 691 cached_response() (in module conda.notices.cache), 667 CacheUrlAction (class in conda.core.path_actions), 559 calculate_channel_urls() (in module conda.core.index), 542 call_each() (in module conda.auxlib.collection), 423 CAN_CALL_CPUID_IN_SUBPROCESS module (in conda._vendor.cpuinfo), 394 CAN_CALL_CPUID_IN_SUBPROCESS module (in conda._vendor.cpuinfo.cpuinfo), 388

can_cpuid (DataSource attribute), 389, 395 can_handle() (BinstarSpec method), 575, 578 can_handle() (*RequirementsSpec method*), 576, 578 can_handle() (YamlFileSpec method), 577, 578 CancelOperation, 609 canonical_name (Channel property), 622, 635 canonical_name (MultiChannel property), 636 capsys (CondaCLIFixture attribute), 719 captured() (in module conda.common.io), 510 captured() (in module conda.testing.helpers), 705 CaptureTarget (class in conda.common.io), 510 CaseInsensitiveStrMatch (class in conda.models.match_spec), 649 cat_proc_cpuinfo() (DataSource static method), 389, 395 cat_var_run_dmesg_boot() (DataSource static method), 389, 395 category_map (*Context property*), 454 changeps1 (Context attribute), 454 ChangeReport (class in conda.core.link), 550 Channel (class in conda.gateways.repodata), 622 Channel (class in conda.models.channel), 634 channel (Dist attribute), 637 channel (PackageInfo attribute), 651 channel (*PackageRecord attribute*), 658, 718 channel (RepodataFetch attribute), 626 channel_alias() (Context method), 458 channel_alias_validation() (in module conda.base.context), 452 CHANNEL_DIR_V2 (in module conda.testing.helpers), 705 channel_location (Channel property), 622, 635 channel_location (MultiChannel property), 635 channel_name (Channel property), 622, 635 channel_name (ChannelNotice attribute), 671 channel_notices (*ChannelNoticeResultSet attribute*), 671 channel_priority (*Context attribute*), 456 channel_settings (Context attribute), 456 ChannelAuthBase (class in conda.plugins.types), 689 ChannelError, 583 ChannelField (class in conda.models.records), 656 ChannelMatch (class in conda.models.match spec), 649 ChannelName (in module conda.notices.core), 668 ChannelNameMixin (class in conda.plugins.types), 689 ChannelNotAllowed, 583 ChannelNotice (class in conda.notices.types), 671 ChannelNoticeResponse (class in conda.notices.types), 671 ChannelNoticeResultSet (class in conda.notices.types), 671 ChannelPriority (class in conda.base.constants), 449 ChannelPriorityMeta (class in conda.base.constants), 449 Channels, **46**, **98**

channels (Context property), 453 ChannelType (class in conda.models.channel), 634 ChannelUrl (in module conda.notices.core), 668 Cheat sheet, 118 check_allowlist() (in module conda.core.index), 540 CHECK_ALTERNATE_FORMAT_INTERVAL (in module conda.gateways.repodata), 623 module check_envs_txt_file() (in conda.plugins.subcommands.doctor.health_checksopdename() (in module conda._vendor.distro), 403 684 CHECK_EXTRACT (in module conda.instructions), 631 CHECK_FETCH (in module conda.instructions), 631 check_files_in_package() (in module conda.instructions), 632 check_non_admin() (in module conda.cli.common), 463 check_prefix() (in module conda.cli.install), 469 check_source() (Configuration method), 506 ChecksumMismatchError, 583 CHUNK SIZE (in module conda.gateways.connection.download), 598 CLASSIC_SOLVER (in module conda.base.constants), 449 classproperty (class in conda.auxlib.decorators), 426 Clauses (class in conda.common. logic), 490 Clauses (class in conda.common.logic), 515 CLEAN (Commands attribute), 486, 709 cleanup() (_Action method), 556 cleanup() (CacheUrlAction method), 560 cleanup() (CompileMultiPycAction method), 558 cleanup() (CreateInPrefixPathAction method), 556 cleanup() (ExtractPackageAction method), 560 cleanup() (RegisterEnvironmentLocationAction method), 559 cleanup() (RemoveMenuAction method), 559 cleanup() (TemporaryDirectory method), 603 cleanup() (UnlinkPathAction method), 559 cleanup() (UnregisterEnvironmentLocationAction method), 559 cleanup() (UpdateHistoryAction method), 558 clear() (PackageCacheData class method), 553, 621, 717 clear_cached_local_channel_data() (SubdirData class method), 568 clear_has_format() (RepodataState method), 625 clear_memoized_methods() module (in conda.auxlib.decorators), 425 clear_subdir_cache() (in module conda.testing.fixtures), 701 client_ssl_cert (Context attribute), 455 client_ssl_cert_key (Context attribute), 455 clobber (Context attribute), 454 clobber (PathConflict attribute), 448 ClobberError. 581 clone() (in module conda.cli.install), 469

clone_env() (in module conda.misc), 633 close() (EnforceUnusedAdapter method), 600 close() (FTPAdapter method), 594 close() (HashWriter method), 616 close() (LocalFSAdapter method), 596 close() (ProgressBar method), 512 close() (S3Adapter method), 597 CmdExeActivator (class in conda.activate), 414 codename() (*LinuxDistribution method*), 406 coerce() (NoarchType static method), 642 collect_all() (Configuration method), 506 collect_errors() (LoadedParameter method), 501 collect_errors() (MapLoadedParameter method), 502 collect_errors() (ObjectLoadedParameter method), 502 collect_errors() (SequenceLoadedParameter method), 502 com_pat (*History attribute*), 628 Combine() (Clauses method), 490 combined_depends (PackageRecord property), 658, 717 command_header() (Trace method), 388, 394 command_join (Activator attribute), 411 command_join (*CmdExeActivator attribute*), 414 command_join (CshActivator attribute), 413 command_join (FishActivator attribute), 414 command_join (JSONFormatMixin attribute), 415 command_join (*PosixActivator attribute*), 412 command_join (*PowerShellActivator attribute*), 415 command_join (XonshActivator attribute), 413 command_output() (Trace method), 388, 394 CommandNotFoundError, 581 Commands, 98 Commands (class in conda.cli.python api), 486 Commands (class in conda.testing.integration), 709 commands (in module conda.instructions), 632 commands() (_Activator method), 411 COMPARE (Commands attribute), 709 COMPARE_OP module (in conda.common.pkg_formats.python), 530 compare_packages() (in module conda.cli.main compare), 472 compatible_release_operator() (in module conda.models.version), 665 COMPATIBLE_SHELLS (in module conda.base.constants), 447 compile() (ASM method), 390, 397 compile_action_groups (PrefixActionGroup attribute), 550 compile_multiple_pyc() (in module conda.gateways.disk.create), 604 CompileMultiPycAction (class in conda.core.path actions), 557

Completer (class in conda.exports), 590 ComposableField (class in conda.auxlib.entity), 436 compute_sum() (in module conda.gateways.disk.read), 607 conda module, 382 Conda for data scientists. 98 conda.___main___ module. 382 conda._vendor module, 382 conda._vendor.appdirs module, 382 conda._vendor.cpuinfo module, 386 conda._vendor.cpuinfo.cpuinfo module, 386 conda._vendor.distro module. 398 conda._vendor.frozendict module, 408 conda._version module, 409 conda.activate module, 409 conda.api module, 416 conda.auxlib module, 421 conda.auxlib.collection module, 422 conda.auxlib.compat module, 423 conda.auxlib.decorators module, 424 conda.auxlib.entity module, 426 conda.auxlib.exceptions module, 437 conda.auxlib.ish module, 438 conda.auxlib.logz module, 439 conda.auxlib.type_coercion module, 441 conda.base module, 444 conda.base.constants module, 444 conda.base.context module, 450 conda.base.exceptions module, 460 conda.cli

module, 460 conda.cli.actions module. 460 conda.cli.common module, 461 conda.cli.conda_argparse module. 463 conda.cli.find_commands module. 465 conda.cli.helpers module, 466 conda.cli.install module. 469 conda.cli.main module, 470 conda.cli.main_clean module, 470 conda.cli.main_compare module, 472 conda.cli.main_config module, 472 conda.cli.main_create module, 473 conda.cli.main env module, 474 conda.cli.main_env_config module, 474 conda.cli.main_env_create module, 474 conda.cli.main_env_export module, 475 conda.cli.main_env_list module, 475 conda.cli.main_env_remove module, 475 conda.cli.main_env_update module, 476 conda.cli.main_env_vars module, 476 conda.cli.main_export module, 477 conda.cli.main_info module.477 conda.cli.main_init module, 479 conda.cli.main_install module, 479 conda.cli.main_list module, 480conda.cli.main_mock_activate module, 480 conda.cli.main_mock_deactivate module. 481 conda.cli.main_notices

module, 481 conda.cli.main_package module, 482 conda.cli.main_pip module, 483 conda.cli.main_remove module. 483 conda.cli.main_rename module. 484 conda.cli.main_run module, 484 conda.cli.main_search module, 485 conda.cli.main_update module, 485 conda.cli.python_api module, 486 conda.common module. 488 conda.common._logic module, 488 conda.common._os module, 491 conda.common._os.linux module, 491 conda.common._os.unix module, 492 conda.common._os.windows module, 492 conda.common.compat module, 494 conda.common.configuration module, 496 conda.common.constants module, 507 conda.common.decorators module. 507 conda.common.disk module. 507 conda.common.io module, 508 conda.common.iterators module. 513 conda.common.logic module, 514 conda.common.path module, 517 conda.common.pkg_formats module, 521 conda.common.pkg_formats.python module, 521 conda.common.serialize module. 530 conda.common.signals

module, 531 conda.common.toposort module. 532 conda.common.url module, 533 conda.core module. 538 conda.core.envs_manager module, 539 conda.core.index module, 539 conda.core.initialize module, 543 conda.core.link module, 548 conda.core.package_cache module, 551 conda.core.package_cache_data module, 551 conda.core.path_actions module, 554 conda.core.portability module, 560 conda.core.prefix_data module, 562 conda.core.solve module, 563 conda.core.subdir_data module, 566 conda.deprecations module, 569 conda.env module, 571 conda.env.env module, 571 conda.env.installers module. 573 conda.env.installers.base module, 573 conda.env.installers.conda module, 574 conda.env.installers.pip module, 574 conda.env.pip_util module, 575 conda.env.specs module, 575 conda.env.specs.binstar module, 575 conda.env.specs.requirements module, 576 conda.env.specs.yaml_file module, 576 conda.exception_handler

module, 579 conda.exceptions module, 580 conda.exports module, 587 conda.gateways module. 591 conda.gateways.anaconda_client module. 592 conda.gateways.connection module, 593 conda.gateways.connection.adapters module, 593 conda.gateways.connection.adapters.ftp module, 593 conda.gateways.connection.adapters.http module, 595 conda.gateways.connection.adapters.localfs module, 596 conda.gateways.connection.adapters.s3 module, 596 conda.gateways.connection.download module, 598 conda.gateways.connection.session module, 599 conda.gateways.disk module, 601 conda.gateways.disk.create module, 601 conda.gateways.disk.delete module, 604conda.gateways.disk.link module, 605 conda.gateways.disk.lock module, 605 conda.gateways.disk.permissions module, 606 conda.gateways.disk.read module, 606 conda.gateways.disk.test module, 608 conda.gateways.disk.update module, 609 conda.gateways.logging module, 610conda.gateways.repodata module, 612 conda.gateways.repodata.jlap module, 612 conda.gateways.repodata.jlap.core module, 612 conda.gateways.repodata.jlap.fetch module, 614 conda.gateways.repodata.jlap.interface

module, 617 conda.gateways.repodata.lock module, 618 conda.gateways.subprocess module, 627 conda.history module. 627 conda.instructions module. 630 conda.misc module, 632 conda.models module. 633 conda.models.channel module. 633 conda.models.dist module, 636 conda.models.enums module, 639 conda.models.leased_path_entry module. 642 conda.models.match_spec module, 643 conda.models.package_info module, 649 conda.models.prefix_graph module, 651 conda.models.records module, 653 conda.models.version module, 660 conda.notices module, 667 conda.notices.cache module, 667 conda.notices.core module. 668 conda.notices.fetch module, 670 conda.notices.types module, 671 conda.notices.views module. 672 conda.plan module, 673 conda.plugins module, 674 conda.plugins.hookspec module, 675 conda.plugins.manager module, 680 conda.plugins.post_solves module, 682 conda.plugins.post_solves.signature_verification
module, 682 conda.plugins.solvers module, 683 conda.plugins.subcommands module, 683 conda.plugins.subcommands.doctor module. 683 conda.plugins.subcommands.doctor.health_checks module. 683 conda.plugins.types module, 686 conda.plugins.virtual_packages module, 690 conda.plugins.virtual_packages.archspec module, 690 conda.plugins.virtual_packages.conda module, 691 conda.plugins.virtual_packages.cuda module, 691 conda.plugins.virtual_packages.freebsd module, 692 conda.plugins.virtual_packages.linux module, 692 conda.plugins.virtual_packages.osx module, 692 conda.plugins.virtual_packages.windows module, 692 conda.resolve module, 696 conda.testing module, 700 conda.testing.cases module, 700 conda.testing.fixtures module, 701 conda.testing.gateways module. 702 conda.testing.gateways.fixtures module, 702 conda.testing.helpers module, 703 conda.testing.integration module.707 conda.testing.notices module, 709 conda.testing.notices.fixtures module, 709 conda.testing.notices.helpers module, 710 conda.testing.solver_helpers module, 711 conda.trust module.720 conda.trust.constants

module, 720 conda.trust.signature_verification module.721 conda.utils module, 722 conda_auth_handlers() (CondaSpecs method), 677 conda_auth_handlers() (in module conda.plugins.hookspec.CondaSpecs), 372 conda_build (Context property), 453 conda_build (in module conda.exports), 590 conda_build_form() (MatchSpec method), 646 conda_build_local_paths (Context property), 452 conda_build_local_urls (Context property), 452 conda_cli (*TmpChannelFixture attribute*), 720 conda_cli (TmpEnvFixture attribute), 719 conda_cli() (in module conda.testing), 719 conda_ensure_sys_python_is_base_env_python() (in module conda.testing), 719 conda env module.725 conda_env.cli module, 725 conda_env.cli.common module, 725 conda_env.cli.main module.726 conda_env.cli.main_config module, 726 conda_env.cli.main_create module.727 conda_env.cli.main_export module, 727 conda_env.cli.main_list module, 728 conda_env.cli.main_remove module.728 conda_env.cli.main_update module, 729 conda_env.cli.main_vars module, 729 conda_env.env module, 730 conda env.installers module, 730 conda_env.installers.base module, 730 conda_env.installers.conda module, 731 conda_env.installers.pip module, 731 conda_env.pip_util module, 731 conda_env.specs module, 731

conda_env.specs.binstar module.731 conda_env.specs.requirements module, 731 conda_env.specs.yaml_file module, 731 CONDA_ENV_VARS_UNSET_VAR module (in conda.base.constants), 450 conda_exception_handler() (in module conda.exception_handler), 580 conda_exe (Context property), 453 conda_exe_vars_dict (Context property), 453 conda_health_checks() (CondaSpecs method), 678 conda_health_checks() module (in conda.plugins.hookspec.CondaSpecs), 372 conda_health_checks() (in module 685 CONDA_HOMEPAGE_URL (in module conda.base.constants), 446 CONDA_HOMEPAGE_URL (in module conda.gateways.repodata), 620 conda_http_errors() (in module conda.gateways.repodata), 624 CONDA_INITIALIZE_PS_RE_BLOCK (in module conda.core.initialize), 546 CONDA_INITIALIZE_RE_BLOCK (in moduleconda.core.initialize), 546 conda_installed_files() (in module conda.misc), 633 CONDA_LOGS_DIR (in module conda.base.constants), 447 conda_move_to_front_of_PATH() (in module conda.testing), 719 conda_name (PythonDistribution property), 523 conda_notices_args_n_parser() (in module conda.testing.notices.fixtures), 710 CONDA_PACKAGE_EXTENSION_V1 (in module conda.base.constants), 447 CONDA_PACKAGE_EXTENSION_V2 (in module conda.base.constants), 447 CONDA_PACKAGE_EXTENSIONS module (in conda.base.constants), 447 CONDA_PACKAGE_PARTS module (in conda.base.constants), 447 CONDA_PACKAGE_ROOT (in module conda), 724 conda_package_types() (PackageType static method), 642 conda_post_commands() (CondaSpecs method), 677 conda_post_commands() (in module conda.plugins.hookspec.CondaSpecs), 373 conda_post_solves() (CondaSpecs method), 679 conda_post_solves() (in module conda.plugins.post_solves.signature_verification), 683

conda_pre_commands() (CondaSpecs method), 677 conda_pre_commands() module (in conda.plugins.hookspec.CondaSpecs), 374 conda_pre_solves() (CondaSpecs method), 678 conda_prefix (Context property), 453 CONDA_SESSION_SCHEMES (in module conda.env.specs), 577 CONDA_SESSION_SCHEMES (in module conda.gateways.connection.session), 599 conda_settings() (CondaSpecs method), 679 conda_settings() (in module conda.plugins.hookspec.CondaSpecs), 375 conda_signal_handler() (in module conda), 725 conda_solvers() (CondaSpecs method), 675 conda_solvers() module (in conda.plugins.hookspec.CondaSpecs), 376 conda.plugins.subcommands.doctor.health_checksgonda_solvers() (in module conda.plugins.solvers), 683 conda_subcommands() (CondaSpecs method), 676 conda_subcommands() (in module conda.plugins.hookspec.CondaSpecs), 377 conda_subcommands() module (in conda.plugins.subcommands.doctor), 686 CONDA TARBALL EXTENSION module (in conda.base.constants), 447 CONDA_TEMP_EXTENSION (in module conda.base.constants), 447 CONDA_TEMP_EXTENSIONS module (in conda.base.constants), 447 conda_tests_ctxt_mgmt_def_pol (in module conda.base.context), 459 conda_v_pat (*History attribute*), 628 conda_virtual_packages() (CondaSpecs method), 676 conda_virtual_packages() (in module conda.plugins.hookspec.CondaSpecs), 378 conda_virtual_packages() (in module conda.plugins.virtual_packages.archspec), 690 conda_virtual_packages() module (in conda.plugins.virtual packages.conda), 691 conda_virtual_packages() (in module conda.plugins.virtual packages.cuda), 691 conda_virtual_packages() module (in conda.plugins.virtual_packages.freebsd), 692 module conda_virtual_packages() (in conda.plugins.virtual_packages.linux), 692 conda_virtual_packages() (in module conda.plugins.virtual_packages.osx), 692 conda_virtual_packages() module (in conda.plugins.virtual packages.windows),

693

CondaAuthHandler (class in conda.plugins), 693

CondaAuthHandler (*class in conda.plugins.types*), 371, 689 CondaCLIFixture (class in conda.testing), 719 CondaDependencyError, 585, 621 CondaEnvException, 586 CondaEnvironmentError, 582 CondaError, 620, 725 CondaExitZero, 717, 725 CondaFileIOError, 582 CondaFileNotFoundError (in module conda.exports), 590 CondaHealthCheck (class in conda.plugins), 694 CondaHealthCheck (class in conda.plugins.types), 372, 689 CondaHistoryError, 585 CondaHistoryWarning, 628 CondaHttpAuth (class in conda.gateways.connection.session), 600 CondaHTTPError, 583, 622 CondaImportError, 583 CondaIndexError, 584 CondaIOError, 582 CondaKeyError, 583 CondaMemorvError. 585 CondaMultiError, 725 CondaOSError, 582 CondaOSError (in module conda.exports), 590 CondaPluginManager (class in conda.plugins.manager), 680 CondaPostCommand (class in conda.plugins), 694 CondaPostCommand (class in conda.plugins.types), 373, 688 CondaPostSolve (class in conda.plugins), 694 CondaPostSolve (class in conda.plugins.types), 689 CondaPreCommand (class in conda.plugins), 694 CondaPreCommand (class in conda.plugins.types), 374, 688 CondaPreSolve (class in conda.plugins), 695 CondaPreSolve (class in conda.plugins.types), 689 CONDARC_FILENAMES module (in conda.common.configuration), 505 CondaRepoInterface (class in conda.gateways.repodata), 624 CondaSession (class in conda.gateways.connection.session), 600 CondaSessionType (class in conda.gateways.connection.session), 600 CondaSetting (class in conda.plugins), 695 CondaSetting (class in conda.plugins.types), 375, 690 CondaSignalInterrupt, 581 CondaSolver (class in conda.plugins), 695 CondaSolver (class in conda.plugins.types), 376, 688 CondaSpecs (class in conda.plugins.hookspec), 675 CondaSSLError, 584, 622

CondaSubcommand	(class in conda.plugins), 6	595
CondaSubcommand	(class	in
conda.plug	gins.subcommands.doctor), 685
CondaSubcommand	(class in conda.plugins.t	ypes), 377,
687		
CondaSystemExit,	582	
CondaUpgradeErro	or, 585	
CondaValueError,	584	
CondaVerificatio	onError, 585	
CondaVirtualPack	age (class in conda.plugi	ins), <mark>696</mark>
CondaVirtualPack	age (class in conda.plu	gins.types),
378, 687		
CONFIG (Commands	attribute), 486, 709	
config_descripti	on (in	module
conda_env	cli.main_config), 726	
config_example	(in	module
conda env	cli.main_config), 726	
config_files (Con	ntext property), 454	
Configuration (cl	ass in conda.common.con	figuration).
506		, 0 , ,
ConfigurationErr	or. 498	
ConfigurationLoa	dError, 498	
ConfigurationObi	iect (class	in
conda con	mon configuration) 503	
ConfigurationTvr	ne (class	in
conda con	mon configuration) 505	in
configure parse	(CondaSubcommand	attribute)
377 686 (587 696	un toure),
configure parser	(in	modula
conda cli i	nain clean) 471	точинс
configure parser	r() (in	modula
conda cli i	main compare) 472	точинс
configure parser	r() (in	modula
conda cli i	nain config) 473	точие
configure parser	r() (in	modula
conda cli i	nain create) 473	точие
configure parser	() (in module conda cli	main env)
474	() (in mounie conducen.	main_env);
configure narse	() (in	modula
conda cli i	nain env config) 474	точие
configure parser	$r() \qquad (in$	modula
conda cli i	nain env create) 475	точие
configure parser	r() (in	modula
conda cli i	nain env list) 475	точие
configure parser	$\frac{1}{2}$	modula
conda di i	() (in main any remova) 176	тоцие
configura parsor	() (in	modula
conda cli i	() (in main any undata) 176	тоцие
configura paraa	nain_env_upaaie), 470	madula
contryure_parser	(III main any yars) 176	moaule
configura paras	$\frac{1}{10}$	madul
contrigure_parsel	(In apport) 477	moaule
configura paras	num_export), 4//	main infa
ATQ	(in moune conta.cll.)	main_inj0),
4/0		

configure_parser() (in mo	dule conda.cl	i.main_init),
configure parser()	(in	module
conda.cli.main insta	(<i>ll</i>), 479	mounie
configure_parser() (in mo 480	dule conda.cl	i.main_list),
configure_parser()	(in activate) 48	module
configure parser()	_uctivate), 10	module
conda cli main mock	deactivate)	481
configure parser()	_ucuciivaic), (in	module
conda cli main notic	(11) (11) (11) (11) (11) (11) (11) (11)	mounie
configure parser()	(in	module
conda cli main pack	19e). 482	mounie
configure parser()	(in	module
conda.cli.main_remo	ve). 483	mounie
configure parser()	(in	module
conda.cli.main_renar	ne). 484	mounie
configure_parser() (in mo	dule conda.cli	i.main_run),
configure parser()	(in	module
conda cli main searc	(h) 485	mounie
configure parser()	(in	module
conda cli main unda	(11)	mounie
configure parser()	(in	module
conda plugins subcor	nmands docto	r) 686
configure parser plugins	() (in	module
conda cli conda ara	(arse) 465	mounie
Configuring conda 118	<i>urse</i>), 405	
confirm() (in module conda (cli common) A	62
confirm $vn()$ (in module conduction	da cli commo	(02)
constant() (DeprecationHan	dler method)	570
constrains (PackageRecord)	attribute) 650	718
construct states () (Histor	m mathod) 62	0
contains() (CondaMultiErro	r method), 02	5
Context (class in conda base	(1) (1) (1) (1) (1) (1) (1) (1) (1) (1) (1)	5
context (in module conda bas	(20 mexi), 452	0
context (in module conda gat	eways repodat	(a) 620
context (in module conda plue	ins subcomm	ands doctor)
685	;ms.subcomme	inus.uocior),
context (in module conda test	ting) 716	
context aware monkeypate	(ing), 710	modula
conda testing) 720	II() (<i>in</i>	тоцие
context stack (in module co	nda hase cont	ext) 459
ContextDecorator (class in a	randa commo	$(x_i), (x_i), (x_i)$
ContextDecorator (class in condo	base context)	1.10), 510
ContextStack(class in conda	in conda b	(, + 50)
458	in condu.ot	<i>ise.context</i>),
convert to dist str()	(in	module
conda testing helpers	706	mounie
copy (LinkType attribute) 640	,,	
copy() (frozendict method) 4()8	
copy() (in module conda gate	ways.disk.crea	te), 603
CorruptedEnvironmentErro	r. 585	,
	-,	

CouldntParseError, 583
cp_or_copy (in module conda.testing.integration), 708
cpu_count (<i>DataSource attribute</i>), 388, 395
cpu_flags (Context property), 454
<pre>cpufreq_info() (DataSource static method), 389, 395</pre>
CPUID (class in condavendor.cpuinfo), 397
CPUID (class in condavendor.cpuinfo.cpuinfo), 390
CPUINFO_VERSION (in module condavendor.cpuinfo),
394
CPUINFO_VERSION (in module
condavendor.cpuinfo.cpuinfo), 388
CPUINFO_VERSION_STRING (in module
condavendor.cpuinfo), 394
CPUINFO_VERSION_STRING (in module
condavendor.cpuinfo.cpuinfo), 388
CREATE (Commands attribute), 486, 709
<pre>create_actions() (CompileMultiPycAction class</pre>
method), 557
<pre>create_actions() (CreateNonadminAction class</pre>
method), 557
create_actions() (CreatePrefixRecordAction class
method), 558
create_actions() (CreatePythonEntryPointAction
class method), 558
create_actions() (MakeMenuAction class method),
557
create_actions() (<i>RemoveMenuAction class method</i>),
559
create_actions() (UpdateHistoryAction class
method), 558
create_application_entry_point() (in module
conda.gateways.disk.create), 603
create_cache_dir() (in module
conaa.gateways.repoaata), 626
create_conda_pkg() (in moaule
conad.cu.main_package), 462
create_default_packages (Context duribute), 434
method) 557
memoa), 557
create_envs_urrectory() (in module
conad.galeways.alsk.creale), 004
conda actavaya disk create) 603
create file link actions() (LinkPathAction class
method) 557
create hard link or conv() (in module
conda gateways disk create) 603
create info() (in module conda climain package)
482
create link() (in module conda gateways disk create)
603
create notice cache files() (in module
conda_testing notices helpers) 711
create package cache directory() (in module

DEFAULT_AGGRESSIVE_UPDATE_PACKAGES (in module

conda.gateways.disk.	<i>create</i>), 604	
<pre>create_parser() (in module</pre>	e conda_env.c	li.main), 726
<pre>create_python_entry_poir</pre>	nt() (in	module
conda.gateways.disk.	.create), 603	
<pre>create_python_entry_poir</pre>	nt_windows_	_exe_action
(LinkPathAction clas	s method), 55	57
<pre>create_temp_location()</pre>	(in	module
conda.testing.integra	tion), 709	
created_at (ChannelNotice a	ttribute), 671	
CreateInPrefixPathAction	n (<i>cla</i>	iss in
conda.core.path_acti	ions), 556	
CreateNonadminAction	(class	in
conda.core.path_acti	ions), 557	
CreatePrefixRecordAction	n (<i>cla</i>	iss in
conda.core.path_acti	ions), 558	
CreatePythonEntryPointAc	ction (class in
conda.core.path_acti	ions), 558	
Creating custom channels	s, 49	
Creating projects with o	conda, 49	
CRITICAL (NoticeLevel attribu	ıte), 450	
croot (Context property), 452		
CshActivator (class in conde	a.activate), 41	.3
<pre>cuda_version()</pre>	(in	module
conda.plugins.virtua	l_packages.cı	ıda), 691
<pre>custom_channels() (Contex</pre>	t method), 45	8
<pre>custom_expandvars()</pre>	(in	module
conda.common.confi	guration), 503	5
<pre>custom_multichannels() (0</pre>	Context metho	od), 458
CustomValidationError, 49)9	
CyclicalDependencyError,	584	
<pre>cygwin_path_to_win() (in r</pre>	nodule conda	utils), 722.

D

```
dals() (in module conda.auxlib.ish), 438
dashlist() (in module conda.common.io), 510
data_callback_factory()
                                   (in
                                             module
         conda.gateways.connection.adapters.ftp),
         594
DataSource (class in conda. vendor.cpuinfo), 395
DataSource (class in conda._vendor.cpuinfo.cpuinfo),
         388
date (PackageRecord attribute), 659, 718
DateField (class in conda.auxlib.entity), 434
DDE_BUSY (ERROR attribute), 493
DDE_FAIL (ERROR attribute), 493
DDE_TIMEOUT (ERROR attribute), 493
deactivate() (_Activator method), 411
DeactivateHelp, 580
debug (Context property), 454
DEBUG_FORMATTER (in module conda.auxlib.logz), 440
default (Field property), 432
default (Parameter property), 503
default() (DumpEncoder method), 440
default() (EntityEncoder method), 716
```

		7	
conaa.base.co	onstants), 44		1.1
DEFAULI_CHANNEL_AL		(in	module
conda.base.co	onstants), 44	.6	
()DEFAULI_CHANNELS (1)	n module c	onda.base	e.constants),
447	(a	1 1 1 1 7	0
<pre>default_channels()</pre>	(Context me	(thod), 45	8
DEFAULT_CHANNELS_U	NIX	(in	module
conda.base.co	onstants), 44	.7	
DEFAULT_CHANNELS_W	IN	(in	module
conda.base.co	onstants), 44	.7	
DEFAULT_CUSTOM_CHA	NNELS	(in	module
conda.base.co	onstants), 44	.7	
<pre>default_filter() (R</pre>	esolve metho	od), 697	
<pre>default_in_dump (Fie</pre>	eld property), 432	
DEFAULT_IV	(in		module
conda.gatewa	ys.repodata.	jlap.core)	, 613
DEFAULT_MARKER_CON	TEXT	(in	module
conda.commo	n.pkg_forma	ats.python), 530
DEFAULT_NOTICE_MES	G	(in	module
conda.testing.	notices.help	ers), 711	
<pre>default_prefix (Con</pre>	text propert	y), 453	
<pre>default_prefix (in m</pre>	odule conda	a.exports)	, 590
default_python (Con	text attribut	e), 454	
default_python (in m	odule condo	a.exports)	, 590
default_python_default_	ault()	(in	module
conda.base.co	ontext), 452		
default_python_val:	idation()	(in	module
conda.base.co	ontext), 452		
DEFAULT_SOLVER (in m	odule condo	a.base.con	stants), 449
default_threads (Co	ntext proper	rty), 453	
DEFAULTS_CHANNEL_N	AME	(in	module
conda.base.co	onstants), 44	7	
DefaultValueRawPara	ameter	(clas	s in
conda.commo	n.configurat	tion), 500	
delete_prefix_from	_linked_da	ata() (in module
conda.core.pr	efix_data), 5	563	
<pre>delete_trash()</pre>	(in		module
conda.gatewa	ys.disk.delet	e), 604	
DeltaSecondsFormat	ter (<i>class i</i>	in conda.c	common.io),
500			
309			
Dependencies, 46			
Dependencies, 46 Dependencies (<i>class in</i>	n conda.env.	.env), 572	
Dependencies, 46 Dependencies (<i>class in</i> dependency_sort() (n conda.env. Resolve meti	.env), 572 hod), 699	
Dependencies, 46 Dependencies (<i>class in</i> dependency_sort() (<i>depends (PackageReco</i>	n conda.env. Resolve met rd attribute)	env), 572 hod), 699 , 659, 718	5
Dependencies, 46 Dependencies (<i>class in</i> dependency_sort() (<i>a</i> depends (<i>PackageReco</i> deprecated (<i>in module</i>)	n conda.env. Resolve met rd attribute) e conda.vei	env), 572 hod), 699), 659, 718 udor.cpuin	s (10), 398
Dependencies, 46 Dependencies (<i>class in</i> dependency_sort() (<i>i</i> depends (<i>PackageReco</i> deprecated (<i>in module</i> deprecated (<i>in module</i>	n conda.env. Resolve meta rd attribute) e condavet e conda. vet	env), 572 hod), 699 , 659, 718 idor.cpuin idor.frozei	s to), 398 ndict), 408
Dependencies, 46 Dependencies (<i>class in</i> dependency_sort() (<i>i</i> depends (<i>PackageReco</i> deprecated (<i>in module</i> deprecated (<i>in module</i> deprecated (<i>in module</i>	n conda.env. Resolve meta rd attribute) e condaver e condaver e conda.dep	env), 572 hod), 699), 659, 718 idor.cpuin idor.frozen recations)	s (fo), 398 (ndict), 408 , 571
Dependencies, 46 Dependencies (<i>class in</i> dependency_sort() (<i>i</i> depends (<i>PackageReco</i> deprecated (<i>in module</i> deprecated (<i>in module</i> deprecated (<i>in module</i> deprecated	n conda.env. Resolve meta rd attribute) e condaver e conda.depa (in	env), 572 hod), 699 , 659, 718 udor.cpuin udor.frozen recations)	s fo), 398 ndict), 408 , 571 module
Dependencies, 46 Dependencies (<i>class in</i> dependency_sort() (<i>d</i> depends (<i>PackageReco</i> deprecated (<i>in module</i> deprecated (<i>in module</i> deprecated (<i>in module</i> deprecated <i>conda.plugins</i>	n conda.env. Resolve meta rd attribute) e condaver e conda.depa (in s.subcomman	env), 572 hod), 699 h, 659, 718 ndor.cpuin ndor.frozen recations) nds.doctor	s nfo), 398 ndict), 408 , 571 module •), 685
Dependencies, 46 Dependencies (<i>class in</i> dependency_sort() (<i>i</i> depends (<i>PackageReco</i> deprecated (<i>in module</i> deprecated (<i>in module</i> deprecated (<i>in module</i> deprecated <i>conda.plugins</i> deprecated (<i>in module</i>	n conda.env. Resolve met rd attribute) e condaver e conda.dep (in s.subcomman e conda.testi	env), 572 hod), 699 , 659, 718 idor.cpuin idor.frozen recations) inds.doctor ing), 717	s hfo), 398 ndict), 408 , 571 module c), 685
Dependencies, 46 Dependencies (class in dependency_sort() (depends (PackageReco deprecated (in module deprecated (in module deprecated conda.plugins deprecated (in module Deprecated Error, 569	n conda.env. Resolve meta rd attribute) e condaver e conda.depa (in (in s.subcomman e conda.testi	env), 572 hod), 699), 659, 718 udor.cpuin ndor.frozei recations) nds.doctor ing), 717	s tfo), 398 ndict), 408 , 571 module •), 685
Dependencies, 46 Dependencies (<i>class in</i> dependency_sort() (<i>i</i> depends (<i>PackageReco</i> deprecated (<i>in module</i> deprecated (<i>in module</i> deprecated (<i>in module</i> deprecated <i>conda.plugins</i> deprecated (<i>in module</i> DeprecatedError, 569 DeprecationHandler	n conda.env. Resolve meta rd attribute) e condaver e conda.depa (in c.subcomman e conda.testi o (class in	env), 572 hod), 699 , 659, 718 udor.cpuin ndor.frozen recations) nds.doctor ing), 717 conda.de	s (fo), 398 (ndict), 408 , 571 <i>module</i> (-), 685 (precations).

deps_modifier (*Context attribute*), 457 DepsModifier (class in conda.base.constants), 448 DepsModifier (in module conda.api), 416 describe_all_parameters() (in module conda.cli.main config), 473 describe_parameter() (Configuration method), 506 description (CondaSetting attribute), 375, 690, 695 description (in module conda_env.cli.main_create), 727 description (in module conda_env.cli.main_export), 727 description (in module conda_env.cli.main_list), 728 description (in module conda_env.cli.main_update), 729 description_map() (Context method), 458 detach_stderr() (in module conda.auxlib.logz), 440 detect() (in module conda.env.specs), 579 determine_constricting_specs() (Solver method), 565 determine_link_type() (in module conda.core.link), 549 determine_target_prefix() (in module conda.base.context), 459 dev (Context attribute), 456 dict_cls (frozendict attribute), 408 dict_cls (FrozenOrderedDict attribute), 409 diff_for_unlink_link_precs() (in module conda.core.solve), 566 DIGEST_SIZE module (in conda.gateways.repodata.jlap.core), 613 DIGEST_SIZE (in module conda.gateways.repodata.jlap.fetch), 615 directory (LinkType attribute), 640 directory (PathType attribute), 641 DirectoryNotACondaEnvironmentError, 582 DirectoryNotFoundError, 581 Disable SSL Verification, 72 disable_channel_notices() (in module conda.testing.fixtures), 701 disable_external_plugins() (CondaPluginManager method), 681 disable_logger() (in module conda.common.io), 511 disable_ssl_verify_warning() (in module conda.gateways.connection.download), 598 DISABLED (ChannelPriority attribute), 449 disabled (SafetyChecks attribute), 448 disallowed_packages (Context attribute), 455 DisallowedPackageError, 584 disp_features() (in module conda.cli.common), 463 display_actions() (in module conda.exports), 591 display_actions() (in module conda.plan), 673 display_health_checks() (in module conda.plugins.subcommands.doctor.health_checks), 684

display_notices() (in module conda.notices.core), 669 display_report_heading() (in module conda.plugins.subcommands.doctor.health_checks), 684 Dist (class in conda.models.dist), 637 dist_fields_dump() (PackageRecord method), 659, 718 dist_name (Dist attribute), 638 dist_name (DistDetails attribute), 637 dist_str() (MatchSpec method), 646 dist_str() (PackageInfo method), 651 dist_str() (PackageRecord method), 659, 718 dist_str_in_index() (in module conda.core.index), 541 dist_str_to_quad() (in module conda.models.dist), 639 DistDetails (class in conda.models.dist), 637 distro_release_attr() (in module conda. vendor.distro), 405 distro_release_attr() (LinuxDistribution method), 406 distro_release_info() (in module conda. vendor.distro), 404 distro_release_info() (*LinuxDistribution method*), 406 DistType (class in conda.models.dist), 637 DLL_NOT_FOUND (ERROR attribute), 493 dmesg_a() (DataSource static method), 389, 395 do_cache_action() (in module conda.core.package_cache_data), 554 do_call() (in module conda.cli.conda_argparse), 464 do_call() (in module conda_env.cli.main), 726 do_cleanup() module (in conda.core.package_cache_data), 554 (in module do_extract_action() conda.core.package cache data), 554 do_reverse() (in module conda.core.package_cache_data), 554 done_callback() module (in conda.core.package cache data), 554 downgraded_precs (ChangeReport attribute), 550 download() module (in conda.core.package_cache_data), 554 download() (in module conda.exports), 591 download() (in module conda.gateways.connection.download), 598 download_and_extract() (UnlinkLinkTransaction method), 550 download_and_hash() (in module conda.gateways.repodata.jlap.fetch), 616 download_http_errors() module (in conda.gateways.connection.download), 598 download_inner() (in module

conda.gateways.connection.download), 598 download_only (Context attribute), 454 download_partial_file() (in module conda.gateways.connection.download), 598 download_text() (in module conda.gateways.connection.download), 598 dry_run (Context attribute), 456 dry_run() (in module conda.env.installers.conda), 574 DRY_RUN_PREFIX (in module conda.base.constants), 447 DryRunExit, 582 DummyArgs (class in conda.testing.notices.helpers), 711 DummyExecutor (class in conda.common.io), 512 dump() (_FeaturesField method), 656 dump() (Channel method), 623, 635 dump() (ChannelField method), 656 dump() (ComposableField method), 436 dump() (DateField method), 434 dump() (Entity method), 436 dump() (EnumField method), 435 dump() (Field method), 432 dump() (ListField method), 435 dump() (MultiChannel method), 636 dump() (TimestampField method), 655 dump_map() (CondaError method), 620, 725 dump_map() (CondaMultiError method), 725 dump_record() (in module conda.cli.main info), 478 DumpEncoder (class in conda.auxlib.logz), 440

Е

emit() (StdStreamHandler method), 612 EMPTY_LINK (in module conda.models.records), 656 EMPTY_MAP (in module conda.common.configuration), 498 empty_prefix() (in module conda.testing.solver_helpers), 712 enable_private_envs (Context attribute), 455 enabled (_SignatureVerification property), 721 enabled (SafetyChecks attribute), 448 encode_arguments() module (in conda.common.compat), 495 ENCODE_ENVIRONMENT module (in conda.common.compat), 495 encode_environment() module (in conda.common.compat), 495 encode_for_env_var() module (in conda.common.compat), 495 EncodingError, 586 EnforceUnusedAdapter in (class conda.gateways.connection.session), 599 ensure_binary() (in module conda.activate), 412 ensure_binary() (in module conda.common.compat), 495 ensure_dir_exists() (in module conda.utils), 724

ensure_fs_path_encoding() (in module conda.activate), 412 ensure_fs_path_encoding() (in module conda.common.compat), 495 ensure_pad() (in module conda.common.path), 520 ensure_text_type() (in module conda.common.compat), 495 ensure_unicode() (in module conda.common.compat), 495 ensure_utf8_encoding() (in module conda.common.compat), 495 Entity (class in conda.auxlib.entity), 436 EntityEncoder (class in conda.testing), 715 ENTRY_POINT (in module conda_env.installers.base), 730 entry_point_action_groups (PrefixActionGroup at*tribute*), 550 entry_points (Noarch attribute), 650 ENTRY_POINTS_FILES (*PythonDistribution attribute*), 524 ENTRY_POINTS_FILES (*PythonEggInfoDistribution at*tribute), 525 ENTRY_POINTS_FILES (PythonInstalledDistribution attribute), 525 EnumField (class in conda.auxlib.entity), 434 env() (SolverTests method), 713 env_name() (in module conda.base.context), 459 env_or_set (in module conda.testing.integration), 708 module env_override() (in conda.common.decorators), 507 env_prompt (Context attribute), 454 env_txt_check() (in module conda.plugins.subcommands.doctor.health_checks), 684 env_unmodified() (in module conda.common.io), 510 env_var() (in module conda.common.io), 510 env_vars() (in module conda.common.io), 510 EnvAppDirs (class in conda.gateways.anaconda client), 592 Environment (class in conda.env.env), 573 environment (RequirementsSpec property), 576, 578 environment (YamlFileSpec property), 576, 578 environment() (BinstarSpec method), 576, 578 environment_is_consistent() (Resolve method), 699 ENVIRONMENT_TYPE (in module conda.env.specs.binstar), 575 EnvironmentFileEmpty, 586 EnvironmentFileExtensionNotValid, 577, 586 EnvironmentFileNotDownloaded, 586 EnvironmentFileNotFound, 577, 586 EnvironmentLocationNotFound, 581 EnvironmentNameNotFound, 582 EnvironmentNotWritableError, 585 Environments, 98

EnvRawParameter	(class	in
conda.common.config	guration), 499	
envs_dirs (Context property)	, 453	
envs_dirs (in module conda.e	exports), 590	
ERROR (class in conda.common	nos.windows), 4	193
ERROR_SNIPPET_LENGTH	(in	module
conda.gateways.repo	data), 623	
error_upload_url(Context)	attribute), 456	
error_upload_url (Exceptio	nHandler proper	rty), 579
ERROR_UPLOAD_URL (in modi	ile conda.base.c	onstants),
446		
escape_for_winpath()	(in	module
conda.testing.integra	tion), 708	
escaped_sys_rc_path	(in	module
conda.cli.conda_arg	parse), 464	
escaped_user_rc_path	(in	module
conda.cli.conda_argj	parse), 464	
etag (<i>RepodataState property</i>)	, 624	
ETAG_KEY (in module conda.go	iteways.repodata	e), 623
<pre>Eval() (Clauses method), 490</pre>		
<pre>evaluate() (Evaluator metho</pre>	<i>d</i>), 530	
Evaluator (class in conda.con	nmon.pkg_forma	ts.python),
530		
evaluator (i	'n	module
conda.common.pkg_j	formats.python),	530
exact_match() (<i>BaseSpec me</i>	ethod), 666	
exact_value (_ <i>StrMatchMixi</i>	n property), 647	
exact_value (BaseSpec prope	erty), 665	
exact_value (<i>BuildNumberM</i>	latch property), 6	566
exact_value (FeatureMatch p	property), 649	
exact_value (GlobStrMatch)	property), 648	
exact_value (<i>MatchInterface</i>	property), 647	
exact_value (<i>SplitStrMatch</i> p	property), 648	
ExactLowerStrMatch	(class	in
conda.models.match_	<i>_spec</i>), 648	
ExactlyOne() (Clauses metho	od), 516	
ExactlyOne_BDD() (Clauses	<i>method</i>), 491, 51	.6
ExactlyOne_NSQ() (Clauses	<i>method</i>), 491, 51	.6
exactness_and_number_of_	_deps() (in	module
conda.resolve), 697		
ExactStrMatch (class in c	onda.models.mai	tch_spec),
648		
example (in module conda_en	v.cli.main_create	e), 727
example (in module conda_en	v.cli.main_expor	<i>t</i>), 727
example (in module conda_en	v.cli.main_list),	/28
example (in module conda_en	v.cli.main_updat	e), 729
ExceptionHandler (<i>class in c</i> 579	conda.exception_	_handler),
executable_paths (<i>Preferred</i>	dEnv attribute), (550
<pre>execute() (_Action method),</pre>	556	
<pre>execute() (_Activator method</pre>	<i>l</i>), 411	
<pre>execute() (CacheUrlAction n</pre>	nethod), 559	
execute() (CompileMultiPyc.	Action method),	558
execute() (CreateNonadminA	Action method), 5	557

execute() (CreatePrefixRecordAction method), 558 execute() (CreatePythonEntryPointAction method), 558 execute() (ExtractPackageAction method), 560 execute() (in module conda.cli.main clean), 472 execute() (in module conda.cli.main compare), 472 execute() (in module conda.cli.main config), 473 execute() (in module conda.cli.main create), 473 execute() (in module conda.cli.main env), 474 execute() (in module conda.cli.main_env_config), 474 execute() (in module conda.cli.main_env_create), 475 execute() (in module conda.cli.main_env_list), 475 execute() (in module conda.cli.main_env_remove), 476 execute() (in module conda.cli.main_env_update), 476 execute() (in module conda.cli.main_export), 477 execute() (in module conda.cli.main_info), 478 execute() (in module conda.cli.main_init), 479 execute() (in module conda.cli.main install), 479 execute() (in module conda.cli.main list), 480 execute() (in module conda.cli.main mock activate), 481 execute() (in module conda.cli.main mock deactivate), 481 execute() (in module conda.cli.main notices), 481 execute() (in module conda.cli.main_package), 482 execute() (in module conda.cli.main remove), 483 execute() (in module conda.cli.main_rename), 484 execute() (in module conda.cli.main_run), 484 execute() (in module conda.cli.main_search), 485 execute() (in module conda.cli.main_update), 485 execute() (in module conda.plugins.subcommands.doctor), 686 execute() (LinkPathAction method), 557 execute() (MakeMenuAction method), 557 execute() (PrefixReplaceLinkAction method), 557 execute() (ProgressiveFetchExtract method), 554 execute() (RegisterEnvironmentLocationAction method), 558 execute() (RemoveLinkedPackageRecordAction method), 559 execute() (RemoveMenuAction method), 559 execute() (UnlinkLinkTransaction method), 550 execute() (UnlinkPathAction method), 559 execute() (UnregisterEnvironmentLocationAction method), 559 execute() (UpdateHistoryAction method), 558 execute_actions() (in module conda.plan), 674 execute_config() (in module conda.cli.main_config), 473 execute_instructions() (in module conda.plan), 674 execute_list() (in module conda.cli.main_env_vars), 477 execute_plan() (in module conda.plan), 674

execute_set() (in module conda.cli.main env vars), FETCH (in module conda.instructions), 631 477 execute_threads (Context property), 453 execute_unset() module (in conda.cli.main_env_vars), 477 exp_backoff_fn() (in module conda.gateways.disk), 610 expand() (in module conda.activate), 412 expand() (*in module conda.common.path*), 519 expand() (LoadedParameter method), 501 expand_environment_variables() (in module conda.common.configuration), 498 (in expected_error_prefix module conda.testing.helpers), 705 experimental (Context attribute), 457 expired_at (ChannelNotice attribute), 671 explicit() (in module conda.misc), 633 explode_directories() module (in conda.common.path), 519 export_var_tmpl (Activator attribute), 411 export_var_tmpl (CmdExeActivator attribute), 414 export_var_tmpl (CshActivator attribute), 413 export_var_tmpl (FishActivator attribute), 414 export_var_tmpl (PosixActivator attribute), 412 export_var_tmpl (PowerShellActivator attribute), 415 export_var_tmpl (XonshActivator attribute), 413 EXPORTED_CHANNELS_DIR (in module conda.testing.helpers), 705 extend() (_ClauseArray method), 489 ExtendConstAction (class in conda.cli.actions), 461 extensions (RequirementsSpec attribute), 576, 578 extensions (YamlFileSpec attribute), 577, 578 extra_safety_checks (Context attribute), 455 EXTRACT (in module conda.instructions), 631 extract_actions (*ProgressiveFetchExtract property*), 553 EXTRACT_CMD() (in module conda.instructions), 632 extract_tarball() module (in conda.gateways.disk.create), 603 EXTRACT_THREADS module (in conda.core.package cache data), 552 (PackageCacheRecord extracted_package_dir attribute), 660 extracted_package_dir (PackageInfo attribute), 651 extracted_package_dir (PrefixRecord attribute), 660 ExtractPackageAction (class in conda.core.path_actions), 560

F

fail() (Trace method), 388, 394 FALSE (in module conda.common._logic), 488 FALSE (in module conda.common.logic), 515 FeatureMatch (class in conda.models.match_spec), 649 features (PackageRecord attribute), 659, 718

FETCH_CMD() (in module conda.instructions), 632 fetch_index() (in module conda.core.index), 541 fetch_index() (in module conda.exports), 591 fetch_jlap() (in module conda.gateways.repodata.jlap.fetch), 616 fetch_latest() (RepodataFetch method), 626 fetch_latest_parsed() (RepodataFetch method), 626 fetch_latest_path() (RepodataFetch method), 626 fetch_precs (ChangeReport attribute), 550 fetch_threads (Context property), 453 Field (class in conda.auxlib.entity), 431 FIELD_NAMES (MatchSpec attribute), 645 FIELD_NAMES_SET (MatchSpec attribute), 646 file_data() (BinstarSpec method), 576, 578 file_is_empty() (History method), 628 file_mode (PathData attribute), 658 FILE_NAMES (*PythonDistributionMetadata attribute*), 526 FILE_NOT_FOUND (ERROR attribute), 493 file_path_is_writable() (in module conda.gateways.disk.test), 608 file_scheme (in module conda.common.url), 535 FileMode (class in conda.models.enums), 640 FilenameField (class in conda.models.records), 657 FileNotFoundError (in module conda.core.package_cache_data), 552 FileNotFoundError module (in conda.core.path_actions), 556 files (PrefixRecord attribute), 660 FileSpecTypes (in module conda.env.specs), 578 FILESYSTEM_ENCODING (in module conda.common.compat), 495 filter() (TokenURLFilter method), 611 filter_notices() (in module conda.notices.core), 669 final (ParameterFlag attribute), 499 find_altered_packages() (in module conda.plugins.subcommands.doctor.health_checks), 684 find_builtin_commands() module (in conda.cli.conda_argparse), 464 find_commands() module (in conda.cli.find_commands), 466 find_conflicts() (Resolve method), 698 find_executable() (in module conda.cli.find_commands), 466 find_index_cache() (in module conda.cli.main_clean), 471 find_logfiles() (in module conda.cli.main_clean), 472 find_matches() (Resolve method), 699 find_matches_with_strict() (Resolve method), 698 find_or_none() (in module conda.auxlib.ish), 438 find_or_raise() (in module conda.auxlib.ish), 439

find_package() (SolverTests method), 713 find_package_in_list() (SolverTests method), 713 find_packages_with_missing_files() (in module conda.plugins.subcommands.doctor.health_checksfprom_lines() (JLAP class method), 613 684 find_patches() module (in conda.gateways.repodata.jlap.fetch), 616 find_pkgs() (in module conda.cli.main clean), 471 find_pkgs_dirs() (in module conda.cli.main_clean), 471 find_tarballs() (in module conda.cli.main_clean), 471 find_tempfiles() (in module conda.cli.main_clean), 471 finish() (ProgressBar method), 511 first() (in module conda.auxlib.collection), 422 first_writable() (PackageCacheData class method), 553, 621, 716 first_writable() (PackageCacheData static method), 420 firstitem() (in module conda.auxlib.collection), 423 FishActivator (class in conda.activate), 414 fix_shebang() (in module conda.cli.main_package), 482 fixture_names (*BaseTestCase attribute*), 701 flatten_notice_responses() (in module conda.notices.core), 669 FLEXIBLE (ChannelPriority attribute), 449 fmt (Dist attribute), 638 fmt (DistDetails attribute), 637 fn (Dist property), 637 fn (MatchSpec property), 645 fn (PackageRecord attribute), 658, 718 force (Context attribute), 456 force_32bit (Context attribute), 455 force_reinstall (Context attribute), 457 force_remove (*Context attribute*), 457 FORCE_temp_prefix() module (in conda.testing.integration), 708 format() (DeltaSecondsFormatter method), 510 format_dict() (in module conda.cli.main config), 473 format_hash() module (in conda.gateways.repodata.jlap.fetch), 616 format_usage() (BooleanOptionalAction method), 468 formatter_map (in module conda.activate), 415 Free channel (deprecated), 72 free() (ASM method), 390, 397 freebsd (Platform attribute), 640 FREEZE_INSTALLED (UpdateModifier attribute), 448 fresh_context() (in module conda.base.context), 458 from_channel_name() (Channel static method), 622, 635 from_dist_str() (MatchSpec class method), 646 from_environment() (in module conda.env.env), 572

from_file() (in module conda.env.env), 572 from_index() (Clauses method), 515 from_json() (Entity class method), 436 from_name() (Clauses method), 515 from_name() (ParameterFlag class method), 499 from_objects() (Entity class method), 436 from_parse_result() (Url class method), 535 from_path() (JLAP class method), 614 from_string() (Dist class method), 638 from_string() (ParameterFlag class method), 499 from_sys() (Arch class method), 639 from_sys() (Platform class method), 640 from_url() (Channel static method), 622, 635 from_url() (Dist class method), 638 from_value() (Channel static method), 623, 635 from_value() (ParameterFlag class method), 499 from_yaml() (in module conda.env.env), 572 frozendict (class in conda._vendor.frozendict), 408 FrozenOrderedDict (class in conda._vendor.frozendict), 409 FTPAdapter (class in conda.gateways.connection.adapters.ftp), 593 full_name (Dist property), 637

fullname() (in module conda.auxlib.logz), 441

G

g_trace (in module conda._vendor.cpuinfo), 394 g_trace (in module conda._vendor.cpuinfo.cpuinfo), 388, 392 gen_clauses() (Resolve method), 699 GeneralGraph (class in conda.models.prefix graph), 653 generate_feature_count() (Resolve method), 699 generate_feature_metric() (Resolve method), 699 generate_install_count() (Resolve method), 699 generate_package_count() (Resolve method), 699 generate_parser() (in module conda.cli.conda_argparse), 464 generate_parser() (in module conda.cli.main), 470 generate_pre_parser() (in module conda.cli.conda_argparse), 464 generate_removal_count() (Resolve method), 699 generate_shebang_for_entry_point() (in module conda.core.portability), 562 generate_spec_constraints() (Resolve method), 699 generate_update_count() (Resolve method), 699 generate_version_metrics() (Resolve method), 699 generic (NoarchType attribute), 642 GenericHelp, 581 get() (MatchSpec method), 646 get() (PackageCacheData method), 419, 553, 621, 716

get() (PrefixData method), 420, 563

- get_all_matches() (MapParameter method), 504
- get_all_matches() (ObjectParameter method), 505
- get_all_matches() (Parameter method), 503
- get_all_matches() (SequenceParameter method), 504
- get_archspec_name() (in module conda.core.index),
 542

- get_blank_actions() (in module conda.plan), 674
- get_cache() (CPUID method), 391, 397

- get_canonical_name() (CondaPluginManager method), 680

- get_classifiers() (PythonDistributionMetadata method), 529
- get_clause_count() (_ClauseArray method), 489
- get_clause_count() (_ClauseList method), 488
- get_clause_count() (_SatSolver method), 489
- get_clause_count() (Clauses method), 490, 515
- get_comspec() (in module conda.utils), 723
- get_conda_anchor_files_and_records() (in module conda.core.prefix_data), 563

- get_conflicting_specs() (Resolve method), 699
- get_constrained_packages() (Solver method), 566

- get_cpu_info_json() (in module

- conda._vendor.cpuinfo), 398

- get_default_urls (in module conda.exports), 590
- get_descriptions() (Configuration method), 506
- get_descriptions() (Context method), 458

- get_dist_requirements() (PythonDistributionMetadata method), 526
- get_entry_points() (PythonDistribution method),
 524

- get_environment_env_vars() (PrefixData method),
 563
- get_error_report() (ExceptionHandler method), 579
 get_exact_value() (MatchSpec method), 646
- get_export_unset_vars() (_Activator method), 411
- get_external_requirements() (PythonDistribution-Metadata method), 527
- get_extra_provides() (PythonDistribution method),
 524
- get_filename() (in module conda.env.env), 573
- get_flags() (CPUID method), 391, 397

- get_host_and_path_from_url() (FTPAdapter method), 594
- get_index() (in module conda.core.index), 540
- get_index() (in module conda.exports), 591
- get_index_cuda() (in module conda.testing.helpers),
 706
- get_index_r_1() (in module conda.testing.helpers),

706 get_index_r_2() (in module conda.testing.helpers), 706 get_index_r_4() (in module conda.testing.helpers), 706 get_index_r_5() (in module conda.testing.helpers), 706 get_info() (CPUID method), 391, 397 get_info_dict() (in module conda.cli.main info), 478 get_installed_version() module (in conda.cli.main_package), 482 get_installer() module (in conda.env.installers.base), 573 get_instrumentation_record_file() (in module conda.common.io), 513 get_items() (Completer method), 590 get_leaf_directories() module (in conda.common.path), 519 get_local_urls (in module conda.exports), 590 get_lock() (ProgressBar class method), 511 get_main_info_str() (in module conda.cli.main info), 478 get_major_minor_version() (in module conda.common.path), 519 get_matcher() (BuildNumberMatch method), 666 get_matcher() (VersionSpec method), 666 get_max_extension_support() (CPUID method), 391, 397 get_node_by_name() (PrefixGraph method), 652 get_notice_cache_filenames() module (in conda.testing.notices.helpers), 711 get_notice_response_from_cache() (in module conda.notices.cache), 667 get_notice_responses() (in module conda.notices.fetch), 670 get_notices_cache_dir() module (in conda.notices.cache), 667 get_notices_cache_file() (in module conda.notices.cache), 667 get_optional_dependencies() (PythonDistribution method), 524 get_packages() (in module conda.cli.main_compare), 472 get_packages() (in module conda.cli.main_list), 480 get_paths() (PythonDistribution method), 524 get_pinned_specs() (in module conda.core.solve), 566 get_pip_installed_packages() (in module conda.env.pip_util), 575 get_pkgs() (Resolve method), 699 get_plugin_config_data() (in module conda.base.context), 459 get_plugin_manager() (in module conda.plugins.manager), 682 get_prefix() (in module get_solver_backend()

conda.plugins.subcommands.doctor), 686 get_processor_brand() (CPUID method), 391, 397 get_proxy_username_and_pass() (in module conda.common.url), 537 get_python_noarch_target_path() (in module conda.common.path), 520 get_python_requirements() (PythonDistribution method), 524 get_python_requirements() (PythonDistribution-Metadata method), 527 get_python_short_path() (in module conda.common.path), 519 get_python_site_packages_short_path() (in module conda.common.path), 519 get_python_version_for_prefix() (in module conda.core.prefix_data), 563 get_raw_hz() (CPUID method), 391, 397 get_raw_value() (MatchSpec method), 646 get_rc_urls (in module conda.exports), 590 get_reduced_index() (in module conda.core.index), 542 get_reduced_index() (Resolve method), 699 get_repo_interface() module (in conda.gateways.repodata), 624 get_request_package_in_solution() (Solver method), 565 get_requested_specs_map() (History method), 629 get_revision() (in module conda.cli.install), 470 get_scripts_export_unset_vars() (_Activator method), 411 get_scripts_export_unset_vars() (JSONFormat-Mixin method), 415 get_session() (in module conda.gateways.connection.session), 600 get_session() (in module conda.gateways.repodata), 623 get_session_storage_key() (in module conda.gateways.connection.session), 600 get_settings() (CondaPluginManager method), 681 get_shortcut_dir() (in module conda.testing.integration), 709 get_signal_name() (in module conda.common.signals), 532 get_site_packages_anchor_files() (in module conda.common.pkg_formats.python), 529 get_solver() (in module conda.testing.helpers), 706 get_solver_2() (in module conda.testing.helpers), 706 get_solver_4() (in module conda.testing.helpers), 706 get_solver_5() (in module conda.testing.helpers), 706 get_solver_aggregate_1() (in module conda.testing.helpers), 706 get_solver_aggregate_2() (in module

conda.testing.helpers), 706

(CondaPluginManager

method), 681

- get_solver_cuda() (in module conda.testing.helpers), 706
- get_solver_must_unfreeze() (in module conda.testing.helpers), 706
- get_solvers() (CondaPluginManager method), 681
- get_state() (History method), 629
- get_status_code_from_code_response() (in module conda.gateways.connection.adapters.ftp), 594
- get_test_notices() (in module conda.testing.notices.helpers), 711
- get_ticks_func() (CPUID method), 391, 397
- get_url() (UrlsData method), 553
- get_user_requests() (History method), 629
- get_user_site() (in module conda.cli.main_info), 478
- get_username_password_from_header() (FT-PAdapter method), 594
- get_vendor_id() (CPUID method), 391, 397

- Getting started, **118**
- GlobLowerStrMatch (class conda.models.match_spec), 648
- GlobStrMatch (class in conda.models.match_spec), 648 groupby_to_dict() (in module conda.common.iterators), 514

Η

h (in module conda.history), 629 handle_407() (CondaHttpAuth static method), 601 handle_application_exception() (ExceptionHandler method), 579 handle_exception() (ExceptionHandler method), 579 handle_reportable_application_exception() (ExceptionHandler method), 579 handle_txn() (in module conda.cli.install), 470 handle_unexpected_exception() (ExceptionHandler method), 579 handler (CondaAuthHandler attribute), 372, 689, 694 hardlink (LinkType attribute), 640 hardlink (PathType attribute), 641 hardlink_supported() module (in conda.gateways.disk.test), 608 has_cpufreq_info() (DataSource static method), 389, 395

- has_dmesg() (DataSource static method), 389, 395
- has_format() (RepodataState method), 624
- has_isainfo() (DataSource static method), 389, 395
- has_kstat() (DataSource static method), 389, 395
- has_lscpu() (DataSource static method), 389, 395
- has_platform() (in module conda.common.url), 537
- has_proc_cpuinfo() (DataSource static method), 389, 395
- has_pyzzer_entry_point() (in module conda.core.portability), 561
- has_scheme() (in module conda.common.url), 536
- has_sestatus() (DataSource static method), 389, 395
- has_sysctl() (DataSource static method), 389, 395
- has_sysinfo() (DataSource static method), 389, 395
- has_wmic() (DataSource static method), 389, 395
- hash() (*in module conda.gateways.repodata.jlap.fetch*), 616
- hash_file() (in module conda.exports), 591
- HashWriter (class in conda.gateways.repodata.jlap.fetch), 616
- header() (Trace method), 388, 394
- HEADERS (in module conda.gateways.repodata.jlap.fetch), 615
- Help, 580
- in HIDE (SW attribute), 492
 - History (class in conda.history), 628
 - hook() (_Activator method), 411
 - hook_source_path (_Activator attribute), 411
 - hook_source_path (CmdExeActivator attribute), 414
 - hook_source_path (CshActivator attribute), 413
 - hook_source_path (FishActivator attribute), 414
 - hook_source_path (PosixActivator attribute), 413
 - hook_source_path (PowerShellActivator attribute), 415
 - hook_source_path (XonshActivator attribute), 413
 - hookimpl (in module conda.plugins), 693
 - hookimpl (in module conda.plugins.hookspec), 675
 - hookimpl (in module conda.plugins.subcommands.doctor), 686
 - http_timeout (ExceptionHandler property), 579HTTPAdapter(classin
 - conda.gateways.connection.adapters.http), 595

human_bytes() (in module conda.utils), 723

id (ChannelNotice attribute), 671 id() (in module conda._vendor.distro), 400 id() (LinuxDistribution method), 405 IDENTIFIER (in module conda.common.pkg_formats.python), 529 IGNORE_FIELDS (in module conda.cli.main info), 478 ignore_pinned (Context attribute), 457 immutable (Field property), 432 ImmutableEntity (class in conda.auxlib.entity), 437 in_dump (Field property), 432 index_packages() (in module conda.testing.solver_helpers), 712 INFO (Commands attribute), 486, 709 info (Context property), 454 INFO (NoticeLevel attribute), 450 info() (in module conda._vendor.distro), 403 info() (LinuxDistribution method), 406 INFO_FORMATTER (in module conda.auxlib.logz), 440 init() (PythonDistribution static method), 524 init_cmd_exe_registry() (in module conda.core.initialize), 548 init_fish_user() (in module conda.core.initialize), 547 init_log_file() (History method), 628 init_loggers() (in module conda.cli.main), 470 init_long_path() (in module conda.core.initialize), 548 (_SSLContextAdapterMixin init_poolmanager() method), 595 init_powershell_user() (in module conda.core.initialize), 548 init_sh_system() (in module conda.core.initialize), 548 init_sh_user() (in module conda.core.initialize), 548 init_xonsh_user() (in module conda.core.initialize), 547 INITIAL_TRUST_ROOT (in module conda.trust.constants), 720 InitializationError, 437 initialize() (in module conda.core.initialize), 546 initialize_dev() (in module conda.core.initialize), 546 initialize_logging() (in module conda.auxlib.logz), 440 initialize_logging() (in module conda.gateways.logging), 612 initialize_root_logger() (in module conda.gateways.logging), 612 initialize_std_loggers() (in module conda.gateways.logging), 612 inode_paths (PathDataV1 attribute), 658 insert() (PackageCacheData method), 552, 621, 716 insert() (PrefixData method), 563 INSTALL (Commands attribute), 486, 709

install() (in module conda.cli.install), 470 install() (in module conda.core.initialize), 546 install() (in module conda.env.installers.conda), 574 install() (in module conda.env.installers.pip), 574 install() (Resolve method), 700 install() (SimpleEnvironment method), 712 install_actions() (in module conda.plan), 674 install_activate() (in module conda.core.initialize), 547 install_activate_bat() (in module conda.core.initialize), 547 install_anaconda_prompt() (in module conda.core.initialize), 547 install_conda_csh() (in module conda.core.initialize), 547 install_conda_fish() (in module conda.core.initialize), 547 install_conda_hook_ps1() module (in conda.core.initialize), 547 install_conda_psm1() (in module conda.core.initialize), 547 install_conda_sh() (in module conda.core.initialize), 547 install_conda_xsh() (in module conda.core.initialize), 547 install_condabin_conda_activate_bat() (in module conda.core.initialize), 547 install_condabin_conda_auto_activate_bat() (in module conda.core.initialize), 547 install_condabin_conda_bat() (in module conda.core.initialize), 547 install_condabin_hook_bat() (in module conda.core.initialize), 547 install_condabin_rename_tmp_bat() (in module conda.core.initialize), 547 install_deactivate() module (in conda.core.initialize), 547 install_deactivate_bat() (in module conda.core.initialize), 547 install_library_bin_conda_bat() (in module conda.core.initialize), 547 install_Scripts_activate_bat() (in module conda.core.initialize), 547 install_specs() (Resolve method), 700 InstalledPackages (class in conda.exports), 590 Installing conda, 118 Installing with conda, 98 IntegerField (class in conda.auxlib.entity), 433 interpret() (in module conda.common.pkg_formats.python), 530 INTERRUPT_SIGNALS module (in conda.common.signals), 532 interval (ChannelNotice attribute), 671 IntField (in module conda.auxlib.entity), 433

invalid_chains() (Resolve met	thod), 698
Invallumstaller, 387	
InvalidMatchSpec, 586	
InvalidSpec, 586	
InvalidTypeError, 499	
<pre>InvalidVersionSpec, 586</pre>	
<pre>invoke() (_PycoSatSolver method</pre>	od), 490
<pre>invoke() (_PyCryptoSatSolver m</pre>	nethod), 490
invoke() (<i>PvSatSolver method</i>)	. 490
invoke() (<i>SatSolver method</i>), 4	189
invoke health checks()	(CondaPluginManager
method) 682	(contain ingininanager
invoko post commands()	(Conda Plugin Managar
mothed 621	(Condul inginimanager
methoa), 681	
invoke_post_solves()	(CondaPluginManager
<i>method</i>), 682	
invoke_pre_commands()	(CondaPluginManager
<i>method</i>), 681	
<pre>invoke_pre_solves()</pre>	(CondaPluginManager
<i>method</i>), 682	
is active prefix() (in modu	ule conda.cli.common).
462	
is admin on unix()	(in module
is_dumin_on_unix()	(<i>in module</i>
contaccommonos.unix	(), 492
is_admin_on_windows()	(in module
conda.commonos.win	dows), 493
is_channel (<i>Dist property</i>), 637	
<pre>is_channel_notices_cache_e</pre>	expired() (in module
conda.notices.core), 669	9
is_channel_notices_enabled	l() (in module
conda.notices.core), 669	9
is_conda_environment()	(in module
conda gateways disk tes	t). 608
is diff() (in module conda his	tory) 628
is exact() (RaseSpac method)	665
is executable()	(in module
IS_executable()	
conaa.gateways.aisk.pe	rmissions), 606
is_extracted (PackageCacheRe	ecord property), 660
<pre>is_feature_package (Dist prop</pre>	perty), 637
<pre>is_fetched (PackageCacheReco</pre>	ord property), 660
IS_INTERACTIVE (in module con	nda.common.io), 509
<pre>is_ip_address() (in module co</pre>	onda.common.url), 536
<pre>is_ipv4_address() (in modu</pre>	le conda.common.url),
536	
is ipv6 address() (in modu	le conda.common.url).
536	
is linked() (in module conda)	ernorte) 501
is managashla (Duthan Eaglife	Distribution muon onto)
is_manageable (PythonEgginjo	Distribution property),
525	· · · · · · · ·
<pre>is_manageable (PythonEggLink</pre>	<i>xDistribution attribute</i>),
525	
<pre>is_manageable (PythonInstalled)</pre>	dDistribution attribute),
525	
<pre>is_name_only_spec (MatchSpe</pre>	c property), 645

<pre>is_notice_response_cache_expired() (in module</pre>			
is nullable (<i>Field property</i>) 432			
is package file() (in module conda common path)			
521			
is_path() (in module conda.common.path), 519			
is_private_env_name() (in module			
conda.common.path), 520			
<pre>is_private_env_path() (in module</pre>			
conda.common.path), 520			
is_unmanageable (<i>PackageRecord property</i>), 658, 717			
<pre>is_url() (in module conda.common.url), 536</pre>			
is_windows (DataSource attribute), 388, 395			
<pre>is_writable (PackageCacheData property), 419, 552,</pre>			
621,716			
<pre>is_writable (PrefixData property), 420, 562</pre>			
<pre>isainfo_vb() (DataSource static method), 389, 395</pre>			
<pre>isiterable() (in module conda.auxlib.compat), 423</pre>			
<pre>isiterable() (in module conda.common.compat), 495</pre>			
islink (in module conda.gateways.disk.link), 605			
ITE() (<i>Clauses method</i>), 491, 516			
<pre>iter_records() (PackageCacheData method), 419,</pre>			
553, 621, 716			
<pre>iter_records() (PrefixData method), 421, 563</pre>			
<pre>iter_records() (SubdirData method), 418, 568</pre>			
<pre>iter_records_sorted() (PrefixData method), 563</pre>			
iteritems (in module condavendor.frozendict), 408			
<pre>iteritems() (in module conda.exports), 590</pre>			
<pre>itersolve() (Clauses method), 516</pre>			
<pre>itervalues() (PackageCacheData method), 553, 621,</pre>			
717			
J			

```
JLAP (class in conda.gateways.repodata.jlap.core), 613
Jlap304NotModified, 616
JLAP_KEY (in module conda.gateways.repodata.jlap.fetch),
         615
JlapPatchNotFound, 616
JlapRepoInterface
                                (class
                                                  in
         conda.gateways.repodata.jlap.interface),
         617
JlapSkipZst, 616
join() (in module conda.common.url), 536
join_url (in module conda.common.url), 536
join_url (in module conda.gateways.repodata), 620
json (Context attribute), 457
json() (Entity method), 436
json() (MockResponse method), 711
json_data (ChannelNoticeResponse attribute), 672
json_dump() (in module conda.common.serialize), 531
json_load() (in module conda.common.serialize), 531
jsondumps() (in module conda.auxlib.logz), 441
JSONFormatMixin (class in conda.activate), 415
```

Κ

key_mgr (_SignatureVerification property), 721 KEY_MGR_FILE (in module conda.trust.constants), 720 keyed_hash() module (in conda.gateways.repodata.jlap.core), 613 keyflag() (ArgParseRawParameter method), 500 keyflag() (DefaultValueRawParameter method), 500 keyflag() (EnvRawParameter method), 499 keyflag() (RawParameter method), 499 keyflag() (YamlRawParameter method), 500 KEYS (in module conda.exports), 590 keys() (*Trace method*), 388, 394 KEYS_DIR (in module conda.exports), 591 KNOWN_EXTENSIONS (in module conda.common.path), 519 known_subdirs() (Context method), 458 KnownPackageClobberError, 581 kstat_m_cpu_info() (DataSource static method), 389, 395 L last (JLAP property), 613 last() (in module conda.auxlib.collection), 423 LAST_CHANNEL_URLS (in module conda.core.index), 540 LAST_MODIFIED_KEY (in module conda.gateways.repodata), 623 LATEST (in module conda.gateways.repodata.jlap.fetch), 616 LB_Preprocess() (Clauses method), 491 1chmod (in module conda.gateways.disk.link), 605 leased_path (LeasedPathEntry attribute), 642 leased_path_type (LeasedPathEntry attribute), 642 LeasedPathEntry (class in conda.models.leased_path_entry), 642 LeasedPathType (class in conda.models.enums), 641 legacy_bz2_md5 (PackageRecord attribute), 658, 718 legacy_bz2_size (*PackageRecord attribute*), 658, 718 level (ChannelNotice attribute), 671 libc_family_version() (Context method), 458 license (PackageRecord attribute), 659, 718 license_family (PackageRecord attribute), 659, 718 like() (in module conda._vendor.distro), 403 like() (LinuxDistribution method), 406 module line_and_pos() (in conda.gateways.repodata.jlap.core), 613 LinearBound() (Clauses method), 491, 516 Link (class in conda.models.records), 655 link (in module conda.gateways.disk.link), 605 LINK (in module conda.instructions), 632

link (PrefixRecord attribute), 660

link_action_groups (PrefixActionGroup attribute),
549

link_precs (PrefixSetup attribute), 549

linked() (in module conda.exports), 591

linked_data() (in module conda.exports), 591 linked_package_record (PathType attribute), 641 LinkError, 582 LinkError (in module conda.exports), 590 LinkPathAction (class in conda.core.path_actions), 557 LinkType (class in conda.models.enums), 640 LinkTypeField (class in conda.models.records), 654 linux (Platform attribute), 640 linux_distribution() (in module conda._vendor.distro), 400 linux_distribution() (LinuxDistribution method), 405 linux_get_libc_version() (in module conda.common._os.linux), 491 LinuxDistribution (class in conda._vendor.distro), 405 LIST (Commands attribute), 486, 709 list() (FTPAdapter method), 594 list_all_known_prefixes() (in module conda.core.envs_manager), 539 list_description module (in conda_env.cli.main_vars), 729 list_example (in module conda env.cli.main vars), 729 list_packages() (in module conda.cli.main_list), 480 list_parameters() (Configuration method), 506 listdir (in module conda.gateways.disk.read), 607 ListField (class in conda.auxlib.entity), 435 listify() (in module conda.auxlib.type_coercion), 443 load() (Entity class method), 436 load() (MapParameter method), 504 load() (ObjectParameter method), 505 load() (PackageCacheData method), 552, 621, 716 load() (Parameter method), 503 load() (PrefixData method), 562 load() (PrimitiveParameter method), 503 load() (RepodataCache method), 625 load() (SequenceParameter method), 504 load() (SubdirData method), 568 load_condarc (in module conda.exports), 590 load_entrypoints() (CondaPluginManager method), 680 load_file_configs() (in module conda.common.configuration), 500 load_plugins() (CondaPluginManager method), 680 load_settings() (CondaPluginManager method), 682 load_state() (RepodataCache method), 625 LoadedParameter (class in conda.common.configuration), 500 local_build_root (Context property), 452 local_repodata_ttl (Context attribute), 455 LocalFSAdapter (class in conda.gateways.connection.adapters.localfs),

596 locate_prefix_by_name() (in module conda.base.context), 459 lock() (in module conda.gateways.disk.lock), 605 lock() (in module conda.gateways.repodata), 623 lock() (RepodataCache method), 625 LOCK_ATTEMPTS (in module conda.gateways.disk.lock), 605 LOCK_BYTE (in module conda.gateways.disk.lock), 605 LOCK_SLEEP (in module conda.gateways.disk.lock), 605 LockError, 580 log_level (*Context property*), 454 log_totals() (time_recorder class method), 513 logger (in module conda.notices.cache), 667 logger (in module conda.notices.core), 669 logger (in module conda.notices.fetch), 670 logger (in module conda.plugins.subcommands.doctor.he 684 lsb_release_attr() (in module conda. vendor.distro), 404 lsb_release_attr() (LinuxDistribution method), 406 lsb_release_info() (in module conda._vendor.distro), 404 lsb_release_info() (LinuxDistribution method), 406 lscpu() (DataSource static method), 389, 395

Μ

m (Clauses property), 515 machine_bits (in module conda.base.constants), 446 main() (in module conda._vendor.cpuinfo), 398 main() (in module conda._vendor.cpuinfo.cpuinfo), 392 main() (in module conda._vendor.distro), 408 main() (in module conda.cli), 487 main() (in module conda.cli.main), 470 main() (in module conda.cli.main_pip), 483 main() (in module conda_env.cli.main), 726 main_sourced() (in module conda.cli.main), 470 main_subshell() (in module conda.cli.main), 470 main_subshell() (in module conda.testing), 716 major_version() (in module conda._vendor.distro), 403 major_version() (LinuxDistribution method), 406 make_actions_for_record() (ProgressiveFetchExtract static method), 554 make_conda_egg_link() module (in conda.core.initialize), 548 make_dev_egg_info_file() (in module conda.core.initialize), 548 make_diff() (in module conda.core.initialize), 548 make_entry_point() (in module conda.core.initialize), 547 make_entry_point_exe() (in module conda.core.initialize), 547

<pre>make_executable() (in modu </pre>	le
make_feature_record() (in modu	le
<pre>conda.core.subdir_data), 569 make_immutable() (in module conda.auxlib.collection</pre>	ı),
422	.1.
conda.core.initialize), 546	ie
make_install_plan() (in modu	le
make_menu() (in module conda.gateways.disk.create 603	?),
<pre>make_menu_action_groups (PrefixActionGrou</pre>	ир
<pre>make_raw_parameters() (ArgParseRawParamet class method), 500</pre>	er
almakership, parameters() (EnvRawParameter cla method) 500	ss
<pre>make_raw_parameters() (RawParameter cla method) 499</pre>	ss
<pre>make_raw_parameters() (YamlRawParameter cla method) 500</pre>	ss
make_raw_parameters_from_file() (YamlRawParameters_from_file())	'a-
make_read_only() (in modu	le
conda.gateways.disk.permissions), 606 make_simple_channel() (Channel static method), 62	3,
make_tarbz2() (in module conda.cli.main_package	?),
make_temp_channel() (in modu	le
make_temp_env() (in module conda.testing.integration	ı),
make_temp_package_cache() (in modu	le
make_temp_prefix() (in modu	le
<pre>conda.testing.integration), 708 make_unlink_actions() (in module conda.core.link</pre>	k),
549 make writable() <i>(in modu</i>	le
conda.gateways.disk.permissions), 606	
MakeMenuAction (class in conda.core.path_actions 557	5),
Managing channels, 49	
Managing conda, 49	
managing environments, 49	
Managing packages, 49	
Managing python, 49	
Managing virtual packages, 49	
MANDATORY_FILES (<i>PythonDistribution attribute</i>), 524	
MANDATORY_FILES (PythonEggInfoDistribution a	ıt-
tribute), 525	
MANDAIURY_FILES (PythonInstalledDistribution a	ıt-

tribute), 525 MANIFEST_FILES (PythonDistribution attribute), 524 MANIFEST_FILES (*PythonEggInfoDistribution attribute*), 525 MANIFEST_FILES (PythonInstalledDistribution attribute), 525 manifest_full_path() (PythonDistribution method), 524 map() (DummyExecutor method), 512 MapField (class in conda.auxlib.entity), 435 MapLoadedParameter (class in conda.common.configuration), 501 MapParameter (class in conda.common.configuration), 504mark_channel_notices_as_viewed() (in module conda.notices.cache), 668 MARKER_OP module (in conda.common.pkg formats.python), 530 mask_anaconda_token() (in module conda.common.url), 537 massage_arguments() (in module conda.utils), 723 match() (CaseInsensitiveStrMatch method), 649 match() (ChannelMatch method), 649 match() (ExactLowerStrMatch method), 648 match() (ExactStrMatch method), 648 match() (FeatureMatch method), 649 match() (GlobStrMatch method), 648 match() (MatchInterface method), 647 match() (MatchSpec method), 646 match() (SplitStrMatch method), 648 match_any() (Resolve method), 699 match_specs_to_dists() (in module conda.core.link), 549 matches() (MatchInterface method), 647 matches_all (GlobStrMatch property), 648 MatchInterface (class in conda.models.match spec), 647 MatchSpec (class in conda.models.match_spec), 644 MatchSpecType (class in conda.models.match_spec), 644 MAX_CHANNEL_PRIORITY module (in conda.base.constants), 447 MAX_REPODATA_VERSION (in module conda.core.subdir_data), 567 MAX_SHEBANG_LENGTH (in module conda.core.portability), 561 MAX_TRIES (in module conda.gateways.disk), 610 MAXIMIZE (SW attribute), 492 maybe_add_auth() (in module conda.common.url), 538 maybe_raise() (in module conda.exceptions), 587 maybe_unquote() (in module conda.common.url), 538 maybe_unquote() (in module conda.gateways.repodata), 620 maybecall() (in module conda.auxlib.type coercion), mod (RepodataState property), 624

443

md5 (PackageCacheRecord attribute), 660 md5 (PackageRecord attribute), 658, 718 Md5Field (class in conda.models.records), 659 memoizedproperty() (in module conda.auxlib.decorators), 425 memoizemethod() (in module conda.auxlib.decorators), 424 merge() (BaseSpec method), 666 merge() (BuildNumberMatch method), 666 merge() (LoadedParameter method), 501 merge() (MapLoadedParameter method), 502 merge() (MatchInterface method), 647 merge() (MatchSpec class method), 646 merge() (ObjectLoadedParameter method), 503 merge() (PrimitiveLoadedParameter method), 501 merge() (SequenceLoadedParameter method), 502 merge() (VersionSpec method), 666 message (ChannelNotice attribute), 671 messages() (in module conda.core.link), 551 metadata (PackageRecord attribute), 659, 718 MetadataWarning, 523 migrated_channel_aliases (Context property), 453 migrated_custom_channels (Context attribute), 456 Miniconda, 12 Miniforge, 12 minimal_unsatisfiable_subset() (in module conda.common.logic), 516 MINIMIZE (SW attribute), 493 minimize() (Clauses method), 491, 516 MINIO_EXE (in module conda.testing.gateways.fixtures), 703 minio_s3_server() (in module conda.testing.gateways.fixtures), 703 minor_version() (in module conda. vendor.distro), 403 minor_version() (*LinuxDistribution method*), 406 Mirroring channels, 72 missing_files() module (in conda.plugins.subcommands.doctor.health_checks), 684 missing_pyc_files() (in module conda.common.path), 519 mkdir_p (in module conda.gateways.disk.create), 603 mkdir_p() (in module conda.gateways.disk), 610 mkdir_p_sudo_safe() (in module conda.gateways.disk), 610 mkdir_p_sudo_safe() module (in conda.gateways.repodata), 623 mockable_context_envs_dirs() (in module conda.base.context), 452 MockResponse (class in conda.testing.notices.helpers), 711

MODIFIED (Result attribute), 546 (in module modify_easy_install_pth() conda.core.initialize), 548 module conda, 382 conda.__main__, 382 conda. vendor. 382 conda._vendor.appdirs, 382 conda._vendor.cpuinfo, 386 conda._vendor.cpuinfo.cpuinfo, 386 conda._vendor.distro, 398 conda._vendor.frozendict, 408 conda._version, 409 conda.activate, 409 conda.api, 416 conda.auxlib, 421 conda.auxlib.collection, 422 conda.auxlib.compat, 423 conda.auxlib.decorators, 424 conda.auxlib.entity, 426 conda.auxlib.exceptions, 437 conda.auxlib.ish, 438 conda.auxlib.logz, 439 conda.auxlib.type_coercion, 441 conda.base, 444 conda.base.constants.444 conda.base.context, 450 conda.base.exceptions, 460 conda.cli, 460 conda.cli.actions, 460 conda.cli.common, 461 conda.cli.conda_argparse, 463 conda.cli.find_commands, 465 conda.cli.helpers,466 conda.cli.install, 469 conda.cli.main, 470 conda.cli.main_clean, 470 conda.cli.main_compare, 472 conda.cli.main_config, 472 conda.cli.main_create, 473 conda.cli.main_env, 474 conda.cli.main_env_config, 474 conda.cli.main_env_create, 474 conda.cli.main_env_export, 475 conda.cli.main_env_list, 475 conda.cli.main_env_remove, 475 conda.cli.main_env_update, 476 conda.cli.main_env_vars, 476 conda.cli.main_export,477 conda.cli.main_info, 477 conda.cli.main_init, 479 conda.cli.main_install, 479 conda.cli.main_list, 480 conda.cli.main_mock_activate, 480

conda.cli.main_mock_deactivate, 481 conda.cli.main_notices, 481 conda.cli.main_package, 482 conda.cli.main_pip, 483 conda.cli.main_remove, 483 conda.cli.main_rename, 484 conda.cli.main run.484 conda.cli.main_search, 485 conda.cli.main_update, 485 conda.cli.python_api, 486 conda.common, 488 conda.common._logic, 488 conda.common._os, 491 conda.common._os.linux, 491 conda.common._os.unix, 492 conda.common._os.windows, 492 conda.common.compat, 494 conda.common.configuration, 496 conda.common.constants.507 conda.common.decorators, 507 conda.common.disk, 507 conda.common.io, 508 conda.common.iterators, 513 conda.common.logic.514 conda.common.path, 517 conda.common.pkg_formats, 521 conda.common.pkg_formats.python, 521 conda.common.serialize, 530 conda.common.signals, 531 conda.common.toposort, 532 conda.common.url, 533 conda.core, 538 conda.core.envs_manager, 539 conda.core.index, 539 conda.core.initialize, 543 conda.core.link, 548 conda.core.package_cache, 551 conda.core.package_cache_data, 551 conda.core.path_actions, 554 conda.core.portability, 560 conda.core.prefix_data, 562 conda.core.solve.563 conda.core.subdir_data, 566 conda.deprecations, 569 conda.env, 571 conda.env.env, 571 conda.env.installers.573 conda.env.installers.base, 573 conda.env.installers.conda, 574 conda.env.installers.pip, 574 conda.env.pip_util, 575 conda.env.specs, 575 conda.env.specs.binstar, 575 conda.env.specs.requirements, 576

conda.env.specs.yaml_file, 576 conda.exception_handler, 579 conda.exceptions, 580 conda.exports, 587 conda.gateways, 591 conda.gateways.anaconda_client, 592 conda.gateways.connection, 593 conda.gateways.connection.adapters, 593 conda.gateways.connection.adapters.ftp, 593 conda.gateways.connection.adapters.http, 595 conda.gateways.connection.adapters.localfs, 596 conda.gateways.connection.adapters.s3, 596 conda.gateways.connection.download, 598 conda.gateways.connection.session, 599 conda.gateways.disk, 601 conda.gateways.disk.create, 601 conda.gateways.disk.delete, 604 conda.gateways.disk.link, 605 conda.gateways.disk.lock, 605 conda.gateways.disk.permissions, 606 conda.gateways.disk.read, 606 conda.gateways.disk.test, 608 conda.gateways.disk.update, 609 conda.gateways.logging, 610 conda.gateways.repodata, 612 conda.gateways.repodata.jlap, 612 conda.gateways.repodata.jlap.core, 612 conda.gateways.repodata.jlap.fetch, 614 conda.gateways.repodata.jlap.interface, 617 conda.gateways.repodata.lock, 618 conda.gateways.subprocess, 627 conda.history, 627 conda.instructions, 630 conda.misc, 632 conda.models, 633 conda.models.channel, 633 conda.models.dist, 636 conda.models.enums.639 conda.models.leased_path_entry, 642 conda.models.match_spec, 643 conda.models.package_info, 649 conda.models.prefix_graph, 651 conda.models.records, 653 conda.models.version, 660 conda.notices, 667 conda.notices.cache,667 conda.notices.core, 668 conda.notices.fetch, 670 conda.notices.types, 671

conda.notices.views, 672 conda.plan, 673 conda.plugins, 674 conda.plugins.hookspec, 675 conda.plugins.manager, 680 conda.plugins.post_solves, 682 conda.plugins.post_solves.signature_verification, 682 conda.plugins.solvers, 683 conda.plugins.subcommands, 683 conda.plugins.subcommands.doctor, 683 conda.plugins.subcommands.doctor.health_checks, 683 conda.plugins.types, 686 conda.plugins.virtual_packages, 690 conda.plugins.virtual_packages.archspec, 690 conda.plugins.virtual_packages.conda, 691 conda.plugins.virtual_packages.cuda, 691 conda.plugins.virtual_packages.freebsd, 692 conda.plugins.virtual_packages.linux, 692 conda.plugins.virtual_packages.osx, 692 conda.plugins.virtual_packages.windows, 692 conda.resolve, 696 conda.testing, 700 conda.testing.cases, 700 conda.testing.fixtures, 701 conda.testing.gateways, 702 conda.testing.gateways.fixtures, 702 conda.testing.helpers, 703 conda.testing.integration, 707 conda.testing.notices, 709 conda.testing.notices.fixtures,709 conda.testing.notices.helpers,710 conda.testing.solver_helpers,711 conda.trust,720 conda.trust.constants,720 conda.trust.signature_verification,721 conda.utils,722 conda_env, 725 conda_env.cli, 725 conda_env.cli.common, 725 conda_env.cli.main, 726 conda_env.cli.main_config, 726 conda_env.cli.main_create, 727 conda_env.cli.main_export,727 conda_env.cli.main_list,728 conda_env.cli.main_remove, 728 conda_env.cli.main_update,729 conda_env.cli.main_vars,729 conda_env.env, 730 conda_env.installers,730

conda_env.installers.base,730 conda_env.installers.conda,731 conda_env.installers.pip, 731 conda_env.pip_util, 731 conda_env.specs, 731 conda_env.specs.binstar,731 conda_env.specs.requirements,731 conda_env.specs.yaml_file,731 module() (DeprecationHandler method), 570 ms_depends() (Resolve method), 699 msg (BinstarSpec attribute), 575, 578 msg (RequirementsSpec attribute), 576, 578 msys2_shell_base (in module conda.utils), 723 MultiChannel (class in conda.models.channel), 635 MultiPathAction (class in conda.core.path_actions), 556 MULTIPLE_USE_KEYS (PythonDistributionMetadata attribute), 526 MultipleKeysError, 498 MultiValidationError, 499

Ν

Name, 46 name (ChannelNoticeResponse attribute), 672 name (CondaAuthHandler attribute), 372, 689, 694 name (CondaHealthCheck attribute), 372, 689, 694 name (CondaPostCommand attribute), 373, 688, 694 name (CondaPostSolve attribute), 690, 694 name (CondaPreCommand attribute), 374, 688, 694 name (CondaPreSolve attribute), 689, 695 name (CondaSetting attribute), 375, 690, 695 name (CondaSolver attribute), 376, 688, 695 name (CondaSubcommand attribute), 377, 686, 687, 696 name (CondaVirtualPackage attribute), 378, 688, 696 name (Dist attribute), 638 name (DistDetails attribute), 637 name (Field property), 432 name (MatchSpec property), 645 name (PackageInfo property), 651 name (PackageRecord attribute), 658, 717 name (ParameterLoader property), 505 name (PreferredEnv attribute), 650 name (PythonDistribution property), 523 name (PythonDistributionMetadata property), 526 name (TemporaryDirectory attribute), 603 name() (in module conda._vendor.distro), 402 name() (LinuxDistribution method), 405 name_var() (Clauses method), 515 namekey (PackageRecord property), 658, 717 names (ParameterLoader property), 505 names in specs() (in module conda.cli.common), 463 NAMESPACE_PACKAGE_NAMES (in module conda.base.constants), 450

NAMESPACES (in module conda.base.constants), 450

NAMESPACES_MAP (in module conda.base.constants), 450 native_path_to_unix() (in module conda.activate), 412 NEEDS_SUDO (Result attribute), 546 netloc (Url property), 535 neutered_specs (PrefixSetup attribute), 549 new_precs (ChangeReport attribute), 550 new_var() (Clauses method), 490, 515 nlst() (FTPAdapter method), 594 NO_ASSOC (ERROR attribute), 493 NO_CHANGE (Result attribute), 546 NO_DEPS (DepsModifier attribute), 448 no_link (PathData attribute), 658 no_lock (Context attribute), 457 no_plugins (Context attribute), 457 NO_PLUGINS (in module conda.base.constants), 450 Noarch (class in conda.models.package_info), 650 noarch (PackageMetadata attribute), 650 noarch (PackageRecord attribute), 659, 718 NOARCH_GENERIC (PackageType attribute), 641 NOARCH_PYTHON (PackageType attribute), 641 NoarchField (class in conda.models.package info), 650 NoarchField (class in conda.models.records), 655 NoarchType (class in conda.models.enums), 642 NoBaseEnvironmentError, 582 NOMINAL HASH (in module conda.gateways.repodata.jlap.fetch), 615 non_admin_enabled (Context attribute), 455 module NON_SPACE (in conda.common.pkg_formats.python), 530 non_x86_linux_machines (in module conda.exports), 590 non_x86_machines (in module conda.base.context), 452 NoneType (in module conda.common.compat), 495 norm_name (PythonDistribution property), 523 module norm_package_name() (in conda.common.pkg formats.python), 529 norm_package_version() (in module conda.common.pkg_formats.python), 529 NORMALIZED_DISTRO_ID (in module conda. vendor.distro), 400 NORMALIZED_LSB_ID (in module conda._vendor.distro), 400 NORMALIZED_OS_ID (in module conda._vendor.distro), 400 normalized_version() (in module conda.models.version), 662 NoSpaceLeftError, 586 Not() (Clauses method), 491, 516 NOT_SET (DepsModifier attribute), 448 NotFoundError, 437 nothing_to_do (UnlinkLinkTransaction property), 550 NoticeLevel (class in conda.base.constants), 449 notices (*ChannelNoticeResponse property*), 671

NOTICES (Commands attribute), 486 notices() (in module conda.notices), 672 notices() (in module conda.notices.core), 669 notices_cache_dir() (in module conda.testing.notices.fixtures), 710 NOTICES_CACHE_FN (in module conda.base.constants), 447 NOTICES_CACHE_SUBDIR (in module conda.base.constants), 447 notices_decorator_assert_message_in_stdout() (in module conda.testing.notices.helpers), 711 NOTICES_DECORATOR_DISPLAY_INTERVAL (in module conda.base.constants), 447 NOTICES_FN (in module conda.base.constants), 447 notices_mock_fetch_get_session() (in module conda.testing.notices.fixtures), 710 notify_outdated_conda (Context attribute), 454 NotWritableError, 585, 622 NoWritableEnvsDirError, 585 NoWritablePkgsDirError, 585 NULL (in module conda.common.constants), 507 nullable (Field property), 432 NullCountAction (class in conda.cli.actions), 460 NullHandler (in module conda.auxlib.logz), 440 number_channel_notices (Context attribute), 457 NumberField (class in conda.auxlib.entity), 433 numberify() (in module conda.auxlib.type_coercion), 441

0

<pre>object_log() (History mage)</pre>	ethod), 62	9	
ObjectLoadedParameter		(class	in
conda.common.co	onfiguratic	on), 502	
ObjectParameter	(cl	ass	in
conda.common.co	onfiguratic	on), 504	
offline (Context attribute), 457		
offline_keep() (in mo 636	dule con	da.model:	s.channel),
offset_cache_file_mti	me()	(in	module
conda.testing.not	ices.helpe	rs), 711	
OK_MARK (in module conda.)	plugins.su	bcomman	ds.doctor.h
684			
ON_DISK_HASH	(in		module
conda.gateways.r	epodata.jl	ap.fetch),	615
on_linux (in module cond	a.common	.compat)	, 495
on_mac (in module conda.c	common.co	ompat), 49	95
on_win (in module conda.c	commone	os), 494	
on_win (in module conda.c	common.co	ompat), 49	95
on_win (in module conda.g	gateways.d	lisk), 610	
on_win (in module conda.te	esting), 71	.6	
ONLY_DEPS (DepsModifier	attribute),	, 448	
OOM (ERROR attribute), 493	3		
OP_ORDER (in module cond	a.instructi	ons), 632	
open() (in module conda.c	common.co	ompat), 49	95

openbsd (*Platform attribute*), 640 OperationNotAllowed, 583 operations (Evaluator attribute), 530 OPERATOR_MAP (in module conda.models.version), 665 operator_match() (BaseSpec method), 666 OPERATOR_START (in module conda.models.version), 665 optional (*MatchSpec property*), 645 OR (in module conda.common.pkg_formats.python), 530 Or() (Clauses method), 491, 516 OrderedDict (in module conda._vendor.frozendict), 408 original_spec_str (MatchSpec property), 645 os_distribution_name_version() (Context method), 458 os_release_attr() (in module conda._vendor.distro), 404 os_release_attr() (LinuxDistribution method), 406 os_release_info() (in module conda._vendor.distro), 404os_release_info() (LinuxDistribution method), 406 osx (Platform attribute), 640 override_channels_enabled (Context attribute), 456

Ρ

PackageCacheData (class conda.core.package_cache_data), 552 PackageCacheData (class in conda.gateways.repodata), 620 PackageCacheData (class in conda.testing), 716 PackageCacheRecord (class in conda.models.records), 660 PackageCacheType (class in conda.core.package_cache_data), 552 PackageInfo (class in conda.models.package_info), 651 PackageMetadata (class in conda.models.package_info), 650 packagename() (BinstarSpec method), 576, 578 PackageNotInstalledError, 583 PackageRecord (class in conda.models.records), 658 PackageRecord (class in conda.testing), 717 PackageRecordList (class in conda.core.subdir_data), 567 Packages, 98 PackagesNotFoundError, 584 PackageType (class in conda.models.enums), 641 PackageTypeField (class in conda.models.records), 657 PaddingError. 582 PaddingError (in module conda.exports), 590 pair (Dist property), 637 Parameter (class in conda.common.configuration), 503 parameter (CondaSetting attribute), 375, 690, 695 parameter_description_builder() (in module conda.cli.main_config), 473 ParameterFlag (class in conda.common.configuration), 499 ParameterLoader (class in conda.common.configuration), 505 parametrized_solver_fixture() module (in conda.testing.fixtures), 702 parse() (Dependencies method), 572 parse() (History method), 629 parse_args() (ArgumentParser method), 465 parse_conda_channel_url() (in module conda.models.channel), 636 parse_dist_name() (Dist static method), 638 parse_entry_point_def() (in module conda.common.path), 519 module parse_marker() (in conda.common.pkg_formats.python), 529 parse_multipart_files() (in module conda.gateways.connection.adapters.ftp), 594 parse_specification() (in module conda.common.pkg_formats.python), 529 ParseError, 583 PARTIAL PYPI SPEC PATTERN (in conda.common.pkg formats.python), 523

in path (*PathData property*), 657 path_conflict (Context attribute), 455 path_conversion (*Activator attribute*), 410 path_conversion (CmdExeActivator attribute), 414 path_conversion (CshActivator attribute), 413 path_conversion (FishActivator attribute), 414 path conversion (*PosixActivator attribute*), 412 path_conversion (*PowerShellActivator attribute*), 415 path_conversion (XonshActivator attribute), 413 path_factory (TmpChannelFixture attribute), 720 path_factory (TmpEnvFixture attribute), 719 path_factory() (in module conda.testing), 719 path_identity() (in module conda.activate), 412 path_identity() (in module conda.utils), 722 path_is_clean() module (in conda.gateways.disk.delete), 604 PATH_MATCH_REGEX (in module conda.common.path), 519 PATH_NOT_FOUND (ERROR attribute), 493 path_to_url() (in module conda.common.url), 535 path_to_url() (in module conda.testing), 716 path_type (PathData attribute), 658 PathAction (class in conda.core.path_actions), 556 PathConflict (class in conda.base.constants), 448 PathData (class in conda.models.records), 657 PathDataV1 (class in conda.models.records), 658 PathFactoryFixture (class in conda.testing), 719 PathNotFoundError, 581 paths (PathsData attribute), 658 paths_data (*PackageInfo attribute*), 651 paths_data (PrefixRecord attribute), 660 paths_equal() (in module conda.common.path), 519 paths_version (PathsData attribute), 658 PathsData (class in conda.models.records), 658 pathsep_join (*Activator attribute*), 410 pathsep_join (CmdExeActivator attribute), 414 pathsep_join (*CshActivator attribute*), 413 pathsep_join (FishActivator attribute), 414 pathsep_join (JSONFormatMixin attribute), 415 pathsep_join (PosixActivator attribute), 412 pathsep_join (PowerShellActivator attribute), 414 pathsep_join (XonshActivator attribute), 413 PathType (class in conda.models.enums), 640 penultimate (JLAP property), 613 percent_decode() (in module conda.common.url), 535 Performance, 98 PHANDLE (in module conda.common._os.windows), 492 pinned_packages (Context attribute), 455 pinned_specs() (SolverStateContainer method), 566 Pip interoperability (experimental), 72 pip_installed_post_parse_hook() (in module conda.cli.main pip), 483 *module* pip_interop_enabled (*Context attribute*), 455 pip_subprocess() (in module conda.env.pip util), 575

pkg_data (ActionGroup attribute), 549 pkgs_dirs (Context property), 453 pkgs_dirs (in module conda.exports), 590 Platform (class in conda.models.enums), 640 platform (Context property), 453 platform (Dist attribute), 638 platform (in module conda.exports), 590 platform (PackageRecord attribute), 659, 718 platform_system_release() (Context method), 458 plugin_manager (Context property), 452 PluginConfig (class in conda.base.context), 459 PluginError, 586 Plugins, 98 plugins (in module conda.plugins.post_solves), 683 plugins (in module conda.plugins.subcommands), 686 plugins (in module conda.plugins.virtual_packages), 693 plugins() (Context method), 457 pop() (ContextStack method), 459 pop_key() (in module conda.common.toposort), 533 POPULAR_ENCODINGS (in module conda.core.portability), 561 PosixActivator (class in conda.activate), 412 post_build_validation() (Configuration method), 506 post_build_validation() (Context method), 457 PowerShellActivator (class in conda.activate), 414 ppc64 (Arch attribute), 639 ppc641e (Arch attribute), 639 preferred_env (PackageMetadata attribute), 650 preferred_env (PackageRecord attribute), 659, 718 **PreferredEnv** (*class in conda.models.package_info*), 650 prefix (ChangeReport attribute), 550 prefix_data() (SolverStateContainer method), 566 PREFIX_MAGIC_FILE (in module conda.base.constants), 450 PREFIX_NAME_DISALLOWED_CHARS (in module conda.base.constants), 447 PREFIX_PLACEHOLDER module (in conda.base.constants), 446 prefix_placeholder (PathData attribute), 657 prefix_record_groups (PrefixActionGroup attribute), 550 prefix_specified (Context property), 453 PREFIX_STATE_FILE (in module conda.base.constants), 450 PrefixActionGroup (class in conda.core.link), 549 PrefixData (class in conda.api), 420 PrefixData (class in conda.core.prefix_data), 562 PrefixDataType (class in conda.core.prefix_data), 562 PrefixGraph (class in conda.models.prefix_graph), 651 PrefixPathAction (class in conda.core.path actions), 556

PrefixRecord (class in conda.models.records), 660 PrefixReplaceLinkAction (class in conda.core.path actions), 557 PrefixSetup (class in conda.core.link), 549 prepare() (ProgressiveFetchExtract method), 554 prepare() (UnlinkLinkTransaction method), 550 pretty_content() (in module conda.history), 628 pretty_diff() (in module conda.history), 628 pretty_json() (Entity method), 436 pretty_list() (in module conda.common.configuration), 498 pretty_map() (in module conda.common.configuration), 498 pretty_package() (in module conda.cli.main_info), 478 pretty_record() (in module conda.cli.main_search), 485 prevent (*PathConflict attribute*), 448 Prevent() (Clauses method), 491, 515 primitive_types (in module conda.common.compat), 495 PrimitiveLoadedParameter (class in conda.common.configuration), 501 PrimitiveParameter (class in conda.common.configuration), 503 PRINT (in module conda.instructions), 631 print_activate() (in module conda.cli.install), 469 PRINT_CMD() (in module conda.instructions), 632 print_conda_exception() module (in conda.exceptions), 587 print_config_item() (in module conda.cli.main_config), 473 print_dists() (in module conda.plan), 673 print_envs_list() (in module conda.cli.common), 463 print_expected_error_report() (ExceptionHandler method), 580 print_explicit() (in module conda.cli.main_list), 480 print_export_header() (in module conda.cli.main_list), 480 print_instrumentation_data() module (in conda.common.io), 513 print_log() (History method), 629 print_more_notices_message() module (in conda.notices.views), 672 print_notice_message() (in module conda.notices.views), 672 print_notices() (in module conda.notices.views), 672 print_packages() (in module conda.cli.main_list), 480 print_plan_results() (in module conda.core.initialize), 547 print_result() (in module conda.env.env), 573 print_transaction_summary() (UnlinkLinkTransaction method), 551

print_unexpected_error_report() (ExceptionHan- PYTHON_BINARY (in module conda.testing.integration). dler method), 579 prioritize_channels() (in module conda.models.channel), 636 process_jlap_response() (in module conda.gateways.repodata.jlap.fetch), 616 process_solution() (PycoSatSolver method), 490 process_solution() (_PyCryptoSatSolver method), 490 process_solution() (_PySatSolver method), 490 process_solution() (_SatSolver method), 489 PROGRESS (in module conda.instructions), 631 PROGRESS_COMMANDS (in module conda.instructions), 632 progress_update() (ProgressFileWrapper method), 603 ProgressBar (class in conda.common.io), 511 in **ProgressFileWrapper** (class conda.gateways.disk.create), 603 ProgressiveFetchExtract (class in conda.core.package_cache_data), 553 ProgressiveFetchExtract module (in conda.core.package_cache), 551 PROGRESSIVEFETCHEXTRACT module (in conda.instructions), 632 PROGRESSIVEFETCHEXTRACT_CMD() (in module conda.instructions), 632 proxy_servers (Context attribute), 455 **ProxyError**, 582, 622 prune() (PrefixGraph method), 652 push() (ContextStack method), 458 push_MatchSpec() (Resolve method), 699 PY3 (in module conda._vendor.appdirs), 383 PY3 (in module conda.exports), 590 PY_FILE_RE (in module conda.common.pkg_formats.python), 523 pyc_file (PathType attribute), 641 pyc_path() (in module conda.common.path), 519 PYCOSAT (SatSolverChoice attribute), 449 PycoSatSolver (in module conda.common.logic), 515 PYCRYPTOSAT (SatSolverChoice attribute), 449 PyCryptoSatSolver (in module conda.common.logic), 515 PYPI_CONDA_DEPS module (in conda.common.pkg_formats.python), 523 pypi_name_to_conda_name() module (in conda.common.pkg_formats.python), 529 PYPI_TO_CONDA (in module conda.common.pkg_formats.python), 523 PYSAT (SatSolverChoice attribute), 449 PySatSolver (in module conda.common.logic), 515 PySpec (in module conda.common.pkg_formats.python), 523 python (NoarchType attribute), 642

	,
708	
<pre>python_entry_point_template (in module</pre>	2
conda.gateways.disk.create), 603	
<pre>python_implementation_name_version() (Contex.</pre>	t
<i>method</i>), 458	
PythonDistribution (class in	ı
conda.common.pkg_formats.python), 523	
PythonDistributionMetadata (class in	ı
conda.common.pkg_formats.python), 525	
PythonEggInfoDistribution (class in	ı
conda.common.pkg_formats.python), 525	
PythonEggLinkDistribution (class in	ı
conda.common.pkg_formats.python), 525	
PythonInstalledDistribution (class in	ı

conda.common.pkg_formats.python), 524

Q

quad (Dist property), 637 query() (PackageCacheData method), 419, 553, 621, 716 query() (PrefixData method), 420, 563 query() (SubdirData method), 418, 568 query_all() (PackageCacheData class method), 553, 621.716 query_all() (PackageCacheData static method), 419 query_all() (SubdirData static method), 418, 568 query_all_prefixes() (in module conda.core.envs manager), 539 quiet (Context attribute), 457 quote_for_shell() (in module conda.utils), 723

R

Raise() (in module conda.auxlib.exceptions), 437 raise_errors() (in module conda.common.configuration), 499 raises() (in module conda.testing.helpers), 705 raw_parameters_from_single_source() (ParameterLoader static method), 505 raw_value (BaseSpec property), 665 raw_value (MatchInterface property), 647 RawParameter (class in conda.common.configuration), 499 **RE_ROOT_METADATA** (in module conda.trust.signature_verification), 721 reactivate() (_Activator method), 411 read() (ProgressFileWrapper method), 603 read_binstar_tokens() module (in conda.gateways.anaconda client), 592 read_cache() (RepodataFetch method), 626 read_has_prefix() module (in conda.gateways.disk.read), 608 read_icondata() module (in conda.gateways.disk.read), 608

<pre>read_index_json()</pre>	(in	module	
conda.gateways.dis	k.read), 607		
<pre>read_index_json_from_ta</pre>	arball() (in	module	
conda.gateways.dis	k.read), 608		
read no link() (in module	conda.gateways.di	sk.read).	
608		,,	
read only caches() (A	PackageCacheData	class	
method) 552 621	717	ciuss	
memod), 555, 621,	(11)		
read_package_info()	(in	moaute	
conaa.gateways.ais	<i>k.reaa</i>), 607		
<pre>read_package_metadata()</pre>) (in	module	
conda.gateways.dis	k.read), 608		
read_paths_json()	(in	module	
conda.gateways.dis	k.read), 608		
<pre>read_python_record()</pre>	(in	module	
conda.gateways.dis	k.read), 608		
read repodata ison()	(in	module	
conda gateways dis	k.read). 608		
read soft links()	(in	module	
conda gataways dis	k read 608	mounie	
DECOCNIZED LIDI SCHEMES	(in	modulo	
RECOGNIZED_URL_SCHEMES	(111	mouute	
conaa.base.constan	<i>ts</i>), 44 /	~	
record() (in module conda.)	testing.helpers), 70	6	
<pre>record_file (time_recorder attribute), 513</pre>			
<pre>record_id() (PackageRecord method), 659, 719</pre>			
records (PrefixGraph prope	rty), 652		
recursive_make_writable	e() (in	module	
conda.gateways.dis	k.permissions), 606)	
refresh() (ProgressBar me	thod), 512		
refresh() (<i>RepodataCache</i>	method), 625		
regex match() (BaseSpec n	nethod), 666		
regex split re (in module conda models version) 665			
register() (CondaPluginManager method) 680			
register action groups	(Profix Action Gr	oun at	
register_action_groups	(FrejixActionGre	mp ai-	
tribute), 549	<i>/</i> ·		
register_env()	(in	module	
conda.core.envs_m	anager), 539		
register_envs (Context attribute), 454			
register_reset_callabac	ck() (Confi	iguration	
<i>method</i>), 506			
RegisterEnvironmentLoca	ationAction (c	lass in	
conda.core.path_ac	ctions), 558		
rel path() (in module cond	la.misc), 633		
reload() (PackageCacheDa	<i>ita method</i>), 420, 5	52, 621,	
716	,,	,	
reload() (Prefix Data metho	d) 421 562		
nolood() (SubdinData metho	$(a), \pm 21, 502$		
reload () (Subair Data metho	9 <i>a</i>), 416, 306		
reload_config() (in module conda.testing.integration),			
/09			
remote_backoii_iactor (<i>Context attribute</i>), 456			
<pre>remote_connect_timeout_secs (Context attribute),</pre>			
455			
<pre>remote_max_retries (Context attribute), 456</pre>			
<pre>remote_read_timeout_sec</pre>	s (Context attribut	te), 456	

REMOVE (Commands attribute), 486, 709 remove() (in module conda.cli.main_package), 482 remove() (PackageCacheData method), 553, 621, 716 remove() (PrefixData method), 563 remove() (Resolve method), 700 remove() (SimpleEnvironment method), 712 remove_all_plugin_settings() module (in conda.base.context), 459 remove_auth() (in module conda.common.url), 538 remove_binstar_token() module (in conda.gateways.anaconda_client), 592 remove_channels() (Environment method), 573 remove_conda_in_sp_dir() (in module conda.core.initialize), 548 remove_empty_parent_paths() (in module conda.gateways.disk.delete), 604 remove_menu_action_groups (PrefixActionGroup attribute), 549 remove_spec() (PrefixGraph method), 652 remove_specs (*PrefixSetup attribute*), 549 remove_specs() (Resolve method), 700 remove_youngest_descendant_nodes_with_specs() (PrefixGraph method), 652 removed_precs (ChangeReport attribute), 550 RemoveError, 584 RemoveFromPrefixPathAction (class in conda.core.path_actions), 559 RemoveLinkedPackageRecordAction (class in conda.core.path_actions), 559 RemoveMenuAction (class in conda.core.path_actions), 559 rename() (in module conda.gateways.disk.update), 609 rename_context() module (in conda.gateways.disk.update), 609 replace() (ContextStack method), 459 replace() (RepodataCache method), 625 replace() (Url method), 535 replace_context() (in module conda.base.context), 459 replace_context_default() (in module conda.base.context), 459 replace_first_api_with_conda() (in module conda.gateways.anaconda client), 592 replace_long_shebang() module (in conda.core.portability), 561 replace_prefix() (in module conda.core.portability), 561 replace_pyzzer_entry_point_shebang() (in module conda.core.portability), 561 repo_cache (*RepodataFetch property*), 626 repo_cache (SubdirData property), 567 **REPO_DATA_KEYS** (SimpleEnvironment attribute), 712 repo_fetch (SubdirData property), 568 repo_interface_cls (RepodataFetch attribute), 626

repodata() (CondaRepoInterface method), 624 repodata() (JlapRepoInterface method), 617 repodata() (RepoInterface method), 624 REPODATA_FN (in module conda.base.constants), 447 REPODATA_FN (in module conda.gateways.repodata), 620 repodata_fn (RepodataFetch attribute), 626 repodata fns (Context attribute), 456 REPODATA_HEADER_RE (in module conda.core.subdir data), 567 repodata_parsed() (JlapRepoInterface method), 617 REPODATA_PICKLE_VERSION (in module conda.core.subdir_data), 567 repodata_record (PackageInfo attribute), 651 repodata_threads (Context property), 453 repodata_use_zst (Context attribute), 457 RepodataCache (class in conda.gateways.repodata), 625 RepodataFetch (class in conda.gateways.repodata), 625 RepodataIsEmpty, 623 RepodataOnDisk, 623 RepodataState (class in conda.gateways.repodata), 624 RepodataStateSkipFormat (class in conda.gateways.repodata.jlap.interface), 617 RepoInterface (class in conda.gateways.repodata), 624 report_errors (Context attribute), 457 reportable (CondaError attribute), 620, 725 reporters() (Context method), 458 REPR_IGNORE_KWARGS (in module conda.core.path_actions), 556 request_header_sort_dict (in module conda.auxlib.logz), 441 request_header_sort_key() (in module conda.auxlib.logz), 441 request_jlap() (in module conda.gateways.repodata.jlap.fetch), 616 request_url_jlap_state() module (in conda.gateways.repodata.jlap.fetch), 617 requested_spec (PrefixRecord attribute), 660 requests_version() (Context method), 458 Require() (Clauses method), 491, 515 required (*Field property*), 432 RequirementsSpec (class in conda.env.specs), 578 RequirementsSpec (class in conda.env.specs.requirements), 576 REQUIRES_FILES (PythonDistribution attribute), 524 REQUIRES_FILES (*PythonEggInfoDistribution attribute*), 525 REQUIRES_FILES (PythonInstalledDistribution attribute), 525 reset_conda_context() (in module conda.testing.fixtures), 702 reset_context() (in module conda.base.context), 458 reset_context() (in module conda.testing), 716 Resolve (class in conda.resolve), 697

ResolvePackageNotFound, 580 ResolvePackageNotFound (in module conda.resolve), 697 Response (in module conda.gateways.subprocess), 627 Response304ContentUnchanged, 624 response_header_sort_dict module (in conda.auxlib.logz), 441 response_header_sort_key() module (in conda.auxlib.logz), 441 RESTORE (SW attribute), 493 restore_bad() (Resolve method), 700 restore_free_channel (Context attribute), 456 restore_state() (_ClauseArray method), 489 restore_state() (_ClauseList method), 489 restore_state() (_SatSolver method), 489 Result (class in conda.core.initialize), 546 retr() (FTPAdapter method), 594 RETRIES (in module conda.gateways.connection.session), 599 retrieve_notices() (in module conda.notices.core), 669 return_code (ArgumentError attribute), 580 return_code (CondaError attribute), 620, 725 return_code (CondaExitZero attribute), 717, 725 reverse() (Action method), 556 reverse() (CacheUrlAction method), 560 reverse() (CompileMultiPycAction method), 558 reverse() (CreateNonadminAction method), 557 reverse() (CreatePrefixRecordAction method), 558 reverse() (*CreatePythonEntryPointAction method*), 558 reverse() (ExtractPackageAction method), 560 reverse() (LinkPathAction method), 557 reverse() (MakeMenuAction method), 557 reverse() (RegisterEnvironmentLocationAction method), 558 reverse() (RemoveLinkedPackageRecordAction method), 559 reverse() (RemoveMenuAction method), 559 reverse() (UnlinkPathAction method), 559 reverse() (UnregisterEnvironmentLocationAction method), 559 reverse() (UpdateHistoryAction method), 558 revert_actions() (in module conda.plan), 674 right_pad_os_sep() (in module conda.common.path), 520 riscv64 (Arch attribute), 639 RM_EXTRACTED (in module conda.instructions), 631 RM_FETCHED (in module conda.instructions), 631 rm_fetched() (in module conda.core.package_cache_data), 554 rm_items() (in module conda.cli.main_clean), 472 rm_pkgs() (in module conda.cli.main clean), 471 rm_rf() (in module conda.exports), 590

rm_rf() (in module conda.gateways.disk.delete), 604 rmtree() (in module conda.gateways.disk.delete), 604 rollback_enabled (Context attribute), 455 root_dir (Context property), 453 root_dir (in module conda.exports), 590 ROOT_ENV_NAME (in module conda.base.constants), 447 root_log (in module conda.auxlib.logz), 440 ROOT_NO_RM (in module conda.base.constants), 447 root_prefix() (Context method), 458 root_writable (Context property), 453 root_writable (in module conda.exports), 590 rsplit() (Dist method), 639 RUN (Commands attribute), 486, 709 run() (_SatSolver method), 489 run() (ASM method), 390, 397 run_as_admin() (in module conda.common._os.windows), 493 run_command() (in module conda.cli.python api), 486 run_command() (in module conda.testing.integration), 709 run_for (CondaPostCommand attribute), 373, 689, 694 run_for (CondaPreCommand attribute), 374, 688, 695 run_plan() (in module conda.core.initialize), 546 run_plan_elevated() module (in conda.core.initialize), 546 run_plan_from_stdin() (in module conda.core.initialize), 547 run_plan_from_temp_file() (in module conda.core.initialize), 547 run_script() (in module conda.core.link), 551 run_script_tmpl (_Activator attribute), 411 run_script_tmpl (CmdExeActivator attribute), 414 run_script_tmpl (CshActivator attribute), 413 run_script_tmpl (FishActivator attribute), 414 run_script_tmpl (PosixActivator attribute), 413 run_script_tmpl (PowerShellActivator attribute), 415 run_script_tmpl (XonshActivator attribute), 413 running_a_python_capable_of_unicode_subprocessing(description (in module conda_env.cli.main_vars), (in module conda.testing.integration), 708

S

s390x (Arch attribute), 639 S3Adapter(class in conda.gateways.connection.adapters.s39,et_file_logging() 597 safety_checks (Context attribute), 455 SafetyChecks (class in conda.base.constants), 447 612 SafetyError, 585 sat() (Clauses method), 491, 516 sat_solver (Context attribute), 457 SatSolverChoice (class in conda.base.constants), 449 save() (Environment method), 573 save() (RepodataCache method), 625 708 save_state() (_ClauseArray method), 489 save_state() (_ClauseList method), 488

save_state() (SatSolver method), 489 schannel (PackageRecord property), 658, 717 script_extension (Activator attribute), 411 script_extension (CmdExeActivator attribute), 414 script_extension (CshActivator attribute), 413 script_extension (FishActivator attribute), 414 script_extension (PosixActivator attribute), 412 script_extension (PowerShellActivator attribute), 415 script_extension (XonshActivator attribute), 413 SEARCH (Commands attribute), 486, 709 SEARCH_PATH (in module conda.base.constants), 446 send() (EnforceUnusedAdapter method), 599 send() (FTPAdapter method), 594 send() (LocalFSAdapter method), 596 send() (S3Adapter method), 597 SenderError, 437 sep (_Activator attribute), 410 sep (*CmdExeActivator attribute*), 414 sep (CshActivator attribute), 413 sep (*FishActivator attribute*), 414 sep (PosixActivator attribute), 412 sep (PowerShellActivator attribute), 415 sep (XonshActivator attribute), 413 separate_format_cache (Context attribute), 455 SequenceLoadedParameter (class in conda.common.configuration), 502 SequenceParameter (class in conda.common.configuration), 504 sestatus_b() (DataSource static method), 389, 395 set_active_prefix() (in module conda.testing.helpers), 705 set_all_logger_level() module (in conda.gateways.logging), 612 set_binstar_token() (in module conda.gateways.anaconda client), 592 set_conda_log_level() (in module conda.gateways.logging), 612 730 set_environment_env_vars() (PrefixData method), 563 set_example (in module conda_env.cli.main_vars), 730 (in module conda.gateways.logging), 612 set_has_format() (RepodataState method), 624 set_log_level() (in module conda.gateways.logging), set_name() (Field method), 432 set_repository_metadata() (SolverStateContainer method), 566 set_root_level() (in module conda.auxlib.logz), 440 set_tmpdir() (in module conda.testing.integration), set_value() (ContextStackObject method), 458

set_var_tmpl (Activator attribute), 411 set_var_tmpl (CmdExeActivator attribute), 414 set_var_tmpl (CshActivator attribute), 413 set_var_tmpl (FishActivator attribute), 414 set_var_tmpl (PosixActivator attribute), 412 set_var_tmpl (PowerShellActivator attribute), 415 set_var_tmpl (XonshActivator attribute), 413 set_verbosity() (in module conda.gateways.logging), 612 setter() (classproperty method), 426 Settings, 72 setup() (_PycoSatSolver method), 490 setup() (_PyCryptoSatSolver method), 490 setup() (_PySatSolver method), 490 setup() (_SatSolver method), 489 sha256 (PackageRecord attribute), 658, 718 sha256 (PathDataV1 attribute), 658 sha256_in_prefix (PathDataV1 attribute), 658 SHARE (ERROR attribute), 493 SharedLinkPathClobberError, 581 shebang_pat (in module conda.cli.main_package), 482 SHEBANG_REGEX (in module conda.core.portability), 561 SHEBANG_REGEX module (in conda.gateways.disk.update), 609 shells (in module conda.utils), 723 shlex_split_unicode() (in module conda.auxlib.compat), 423 shlvl (Context property), 453 shortcuts (Context attribute), 457 shortcuts_only (Context attribute), 457 should_check_format() (RepodataState method), 625 should_check_format() (RepodataStateSkipFormat *method*), 617 SHOW (SW attribute), 493 show_channel_urls (Context attribute), 456 show_help_on_empty_command() module (in conda env.cli.main), 726 SHOWDEFAULT (SW attribute), 493 SHOWMAXIMIZED (SW attribute), 493 SHOWMINIMIZED (SW attribute), 493 SHOWMINNOACTIVE (SW attribute), 493 SHOWNA (SW attribute), 493 SHOWNOACTIVATE (SW attribute), 493 SHOWNORMAL (SW attribute), 493 shutdown() (DummyExecutor method), 512 signal_handler() (in module conda.common.signals), 532 signature_verification (in module conda.trust.signature_verification), 721 SignatureError, 721 signing_metadata_url_base (Context property), 453 SimpleEnvironment (class in conda.testing.solver_helpers), 712

SINGLE_USE_KEYS (*PvthonDistributionMetadata* attribute), 526 SingleStrArgCachingType (class in conda.models.version), 662 site_data_dir (AppDirs property), 385 site_data_dir (EnvAppDirs property), 592 site_data_dir() (in module conda. vendor.appdirs), 384 six_with_metaclass() (in module conda.common.compat), 495 size (PackageRecord attribute), 659, 718 size_in_bytes (PathDataV1 attribute), 658 SKIP_FIELDS (in module conda.cli.main_info), 478 skip_formats (RepodataStateSkipFormat attribute), 617 skip_tests() (SolverTests method), 713 softlink (LinkType attribute), 640 softlink (*PathType attribute*), 641 softlink_paths (PreferredEnv attribute), 650 softlink_supported() (in module conda.gateways.disk.test), 608 solve() (Resolve method), 700 solve_final_state() (Solver method), 416, 565 solve_for_diff() (Solver method), 417, 564 solve_for_transaction() (Solver method), 417, 564 Solver (class in conda.api), 416 Solver (class in conda.core.solve), 564 solver (Context attribute), 457 Solver (in module conda.testing.fixtures), 702 solver() (SimpleEnvironment method), 712 solver_class (SolverTests property), 712 solver_class() (in module conda.testing.helpers), 706 solver_classic() (in module conda.testing.fixtures), 702 solver_ignore_timestamps (Context attribute), 457 solver_libmamba() (in module conda.testing.fixtures), 702 solver_transaction() (SimpleEnvironment method), 712 solver_user_agent() (Context method), 458 SolverStateContainer (class in conda.core.solve), 566 SolverTests (class in conda.testing.solver helpers), 712 source (ArgParseRawParameter attribute), 500 source (EnvRawParameter attribute), 499 source (Link attribute), 656 source_full_path (CreateInPrefixPathAction prop*erty*), 556 source_full_paths (CompileMultiPycAction property), 557 SPACER_CHARACTER (in module conda.testing.integration), 708 spec (BaseSpec property), 665

spec (*MatchSpec property*), 645 spec_from_line() (in module conda.cli.common), 463 spec_name (in module conda.plugins.hookspec), 675 spec_pat (History attribute), 628 spec_pat (in module conda.cli.common), 462 SpecNotFound, 577, 586 specs_from_args() (in module conda.cli.common), 462 specs_from_history_map() (SolverStateContainer method), 566 specs_from_url() (in module conda.cli.common), 463 SPECS_SATISFIED_SKIP_SOLVE (UpdateModifier attribute), 448 specs_to_add (ChangeReport attribute), 550 specs_to_remove (ChangeReport attribute), 550 SpecsConfigurationConflictError, 584 SpecTypes (in module conda.env.specs), 578 Spinner (class in conda.common.io), 511 spinner_cycle (Spinner attribute), 511 split() (Dist method), 638 split_anaconda_token() (in module conda.common.url), 537 split_conda_url_easy_parts() (in module conda.common.url), 537 split_extension() (in module conda.models.dist), 637 split_filename() (in module conda.common.path), 520 split_platform() (in module conda.common.url), 537 split_scheme_auth_token() (in module conda.common.url), 537 split_spec() (in module conda.common.pkg_formats.python), 529 SplitStrMatch (class in conda.models.match_spec), 648 ssl_verify (Context attribute), 455 ssl_verify_validation() (in module conda.base.context), 452 stack_context() (in module conda.base.context), 459 stack_context_default() module (in conda.base.context), 459 stale() (RepodataCache method), 625 start() (Spinner method), 511 start_time (time_recorder attribute), 513 startswith() (Dist method), 639 startswith() (VersionOrder method), 664 status_code (UnavailableInvalidChannel attribute), 583,622 stderr_log_level() (in module conda.common.io), 511 stderrlog (in module conda.cli.install), 469 stderrlog (in module conda.gateways.connection.adapters.s3), 597

stderrlog (in module conda.gateways.repodata), 623 STDOUT (CaptureTarget attribute), 510 STDOUT (in module conda.cli.python api), 486 stdout_json() (in module conda.cli.common), 463 stdout_json_success() (in module conda.cli.common), 463 stdoutlog (in module conda.gateways.disk.create), 603 stdoutlog (in module conda.resolve), 697 StdStreamHandler (class in conda.gateways.logging), 611 stop() (Spinner method), 511 stor() (FTPAdapter method), 594 STORE_HEADERS module (in conda.gateways.repodata.jlap.fetch), 616 STRICT (ChannelPriority attribute), 449 strictness (MatchSpec property), 645 STRING (Capture Target attribute), 510 STRING (in module conda.cli.python api), 486 STRING_CHUNK (in module conda.common.pkg_formats.python), 530 string_types (in module conda.exports), 590 StringField (class in conda.auxlib.entity), 433 stringify() (in module conda.auxlib.logz), 441 stringify() (in module conda.gateways.repodata), 620 strip_comment() (in module conda.cli.common), 462 strip_expected() (in module conda.testing.helpers), 705 strip_extension() (in module conda.models.dist), 637 strip_pkg_extension() (in module conda.common.path), 520 strip_scheme() (in module conda.common.url), 536 subdir (Channel property), 622, 635 subdir (Context property), 453 subdir (Dist property), 637 subdir (in module conda.exports), 590 subdir (PackageRecord attribute), 658, 718 subdir_url (Channel property), 622, 635 SubdirData (class in conda.api), 418 SubdirData (class in conda.core.subdir_data), 567 SubdirDataType (class in conda.core.subdir data), 567 SubdirField (class in conda.models.records), 656 subdirs (Context property), 453 submit() (DummyExecutor method), 512 submit() (ThreadLimitedThreadPoolExecutor method), 513 subprocess_call() (in module conda.gateways.subprocess), 627 subprocess_call_with_clean_env() (in module conda.gateways.subprocess), 627 success() (Trace method), 388, 394 summary (CondaSubcommand attribute), 377, 686, 687, 696

superseded_precs (ChangeReport attribute), 550

- suppress_resource_warning() (in module conda.testing.fixtures), 701
- SW (class in conda.common._os.windows), 492
- swallow_broken_pipe (in module conda.common.io),
 510
- SwallowBrokenPipe (class in conda.common.io), 510
- SYMLINK_CONDA (in module conda.instructions), 631
- symlink_conda() (in module conda.exports), 591
- sys_prefix_unfollowed() (in module conda.utils),
 723
- sys_rc_path (in module conda.base.context), 452
- sysctl_machdep_cpu_hw_cpufrequency() (Data-Source static method), 389, 395
- sysinfo_cpu() (DataSource static method), 389, 395

Т

- T (*in module conda.deprecations*), 569

tarball_file_in_this_cache() (PackageCache-Data method), 553, 621, 717

- target (*MatchSpec property*), 645
- target_full_path (CacheUrlAction property), 559
- target_full_path (PathAction property), 556
- target_full_path (PrefixPathAction property), 556
- target_full_path (RegisterEnvironmentLocationAction property), 558
- target_full_path (UnregisterEnvironmentLocation-Action property), 559
- target_full_paths (CompileMultiPycAction property), 557
- target_full_paths (MultiPathAction property), 556
- target_path (LeasedPathEntry attribute), 642
- target_prefix (ActionGroup attribute), 549
- target_prefix (Context property), 453
- target_prefix (LeasedPathEntry attribute), 642
- target_prefix (PrefixSetup attribute), 549
- target_prefix_override (Context attribute), 457
- target_short_paths (PrefixPathAction property), 556
 temp_package_cache() (in module
- *conda.testing.fixtures*), 702
- temp_path (in module conda.core.initialize), 548
 temp_simple_env() (in module
- temp_simple_env() (in n conda.testing.solver_helpers), 712
- tempdir() (in module conda.testing.helpers), 705
- tempdir() (in module conda.testing.integration), 709
- tempfile_extension (_Activator attribute), 411
- tempfile_extension (*CmdExeActivator attribute*), 414

tempfile_extension (FishActivator attribute), 414 tempfile_extension (JSONFormatMixin attribute), 415 tempfile_extension (PosixActivator attribute), 412 tempfile_extension (*PowerShellActivator attribute*), 415 tempfile_extension (XonshActivator attribute), 413 temporary_content_in_file() (in module conda.common.disk), 507 TemporaryDirectory (class in conda.gateways.disk.create), 602 terminate() (JLAP method), 614 terminator (StdStreamHandler attribute), 611 test_accelerate() (SolverTests method), 713 test_anaconda_nomkl() (SolverTests method), 713 test_arch_preferred_over_noarch_when_otherwise_equal() (SolverTests method), 714

- test_channel_priority_1() (SolverTests method), 714
- TEST_DATA_DIR (in module conda.testing.helpers), 705
- test_empty() (SolverTests method), 713
- test_get_dists() (SolverTests method), 713

- test_iopro_mkl() (SolverTests method), 713
- test_iopro_nomkl() (SolverTests method), 713
- test_irrational_version() (SolverTests method),
 714
- TEST_LOG_LEVEL (in module conda.testing.integration), 708
- test_mkl() (SolverTests method), 713
- test_no_features() (SolverTests method), 714

- test_nonexistent() (SolverTests method), 713
- test_nonexistent_deps() (SolverTests method), 713
- test_pseudo_boolean() (SolverTests method), 713
- test_remove() (SolverTests method), 714
- test_scipy_mkl() (SolverTests method), 713
- test_surplus_features_1() (SolverTests method),
 714

test_surplus_features_2() (SolverTests method), to_filename() (Dist method), 638 714 test_timestamps_and_deps() (SolverTests method), 713 test_unintentional_feature_downgrade() (SolverTests method), 714 test_unsat_any_two_not_three() (SolverTests method), 713 test_unsat_chain() (SolverTests method), 713 test_unsat_channel_priority() (SolverTests method), 714 test_unsat_expand_single() (SolverTests method), 713 test_unsat_from_r1() (SolverTests method), 713 test_unsat_missing_dep() (SolverTests method), 713 test_unsat_shortest_chain_1() (SolverTests method), 713 test_unsat_shortest_chain_2() (SolverTests *method*), 713 test_unsat_shortest_chain_3() (SolverTests *method*), 713 test_unsat_shortest_chain_4() (SolverTests method), 713 test_unsat_simple() (SolverTests method), 713 tests_to_skip (SolverTests property), 713 text (FileMode attribute), 640 text_type (in module conda.exports), 590 ThisShouldNeverHappenError, 438 ThreadLimitedThreadPoolExecutor (class in conda.common.io), 512 THREADSAFE_EXTRACT (in module conda.core.package_cache_data), 552 time_recorder (class in conda.common.io), 513 timeme() (in module conda.gateways.repodata.jlap.fetch), 616 timeout() (in module conda.common.io), 511 timeout() (RepodataCache method), 625 timestamp (PackageRecord attribute), 659, 718 TimestampField (class in conda.models.records), 655 tmp_channel() (in module conda.testing), 720 tmp_env() (in module conda.testing), 720 tmp_path (PathFactoryFixture attribute), 719 tmp_pkgs_dir() (in module conda.testing), 720 TmpChannelFixture (class in conda.testing), 720 tmpdir() (in module conda.testing.fixtures), 701 tmpdir_in_use (in module conda.testing.integration), 708 **TmpDownload** (class in conda.gateways.connection.download), 598 TmpEnvFixture (class in conda.testing), 719 to_dict() (ChannelNotice method), 671 to_dict() (Environment method), 573 to_dict() (Trace method), 388, 394 to_feature_metric_id() (Resolve static method), 699

to_json() (frozendict method), 409 to_match_spec() (*Dist method*), 638 to_match_spec() (PackageRecord method), 659, 718 to_matchspec() (Dist method), 638 to_package_ref() (Dist method), 638 to_sat_name() (Resolve static method), 699 to_simple_match_spec() (PackageRecord method), 659,719 to_url() (Dist method), 638 to_yaml() (Environment method), 573 TOKEN_REPLACE (TokenURLFilter attribute), 611 TOKEN_URL_PATTERN (TokenURLFilter attribute), 611 tokenized_conda_url_startswith() (in module conda.models.channel), 636 tokenized_startswith() (in module conda.common.path), 519 tokenized_startswith() module (in conda.models.channel), 636 TokenURLFilter (class in conda.gateways.logging), 611 TooManyArgumentsError, 581 top (ParameterFlag attribute), 499 topic() (DeprecationHandler method), 570 toposort() (in module conda.common.toposort), 533 total_call_num (time_recorder attribute), 513 total_number_channel_notices (ChannelNoticeResultSet attribute), 671 total_run_time (time_recorder attribute), 513 touch() (in module conda.gateways.disk.update), 609 touch_nonadmin() (in module conda.misc), 633 Trace (class in conda._vendor.cpuinfo), 394 Trace (class in conda._vendor.cpuinfo.cpuinfo), 388 trace (Context property), 454 TRACE (in module conda.common.constants), 507 TRACE (in module conda.gateways.disk), 610 trace() (in module conda.gateways.logging), 612 track_features (Context attribute), 455 track_features (PackageRecord attribute), 659, 718 track_features_specs() (SolverStateContainer method), 566 translate_stream() (in module conda.utils), 723 trash_dir() (Context method), 458 treeify() (in module conda.models.version), 664 Troubleshooting, 118 TRUE (in module conda.common._logic), 488 TRUE (in module conda.common.logic), 515 trusted_root (_SignatureVerification property), 721 type (ActionGroup attribute), 549 type (Field property), 432 type (Link attribute), 656 type (Noarch attribute), 650 TYPE_CHECKING (in module conda._version), 409 typify() (in module conda.auxlib.type_coercion), 442

typify() (LoadedParameter method), 501

typify() (Parameter method), 503
typify_parameter() (Configuration method), 506

U

uname_string_raw (DataSource attribute), 389, 395 UnavailableInvalidChannel, 583, 622 unbox() (Field method), 432 unbox() (ListField method), 435 UNDEFINED_MESSAGE_ID (in module conda.notices.types), 671 unicode (in module conda. vendor.appdirs), 383 UNICODE_CHARACTERS (in module conda.testing.integration), 708 UNICODE_CHARACTERS_RESTRICTED module (in conda.testing.integration), 708 union() (BuildNumberMatch method), 666 union() (*MatchInterface method*), 647 union() (MatchSpec class method), 646 union() (VersionSpec method), 666 unique() (in module conda.common.iterators), 514 module unique_sequence_map() (in conda.common.configuration), 506 unix_path_to_win() (in module conda.utils), 722 unix_python_entry_point (PathType attribute), 641 unix_shell_base (in module conda.utils), 723 UNKNOWN_CHANNEL (in module conda.base.constants), 447 UnknownPackageClobberError, 581 UNLINK (in module conda.instructions), 632 unlink_action_groups (PrefixActionGroup attribute), 549 unlink_or_rename_to_trash() (in module conda.gateways.disk.delete), 604 unlink_precs (PrefixSetup attribute), 549 UnlinkLinkTransaction (class in conda.core.link), 550 UNLINKLINKTRANSACTION (in module conda.instructions), 632 UNLINKLINKTRANSACTION_CMD() (in module conda.instructions), 632 UnlinkPathAction (class in conda.core.path_actions), 559 unmanageable_package_types() (PackageType static method), 642 unregister_action_groups (PrefixActionGroup attribute), 549 unregister_env() module (in conda.core.envs_manager), 539 UnregisterEnvironmentLocationAction (class in conda.core.path actions), 559 unsat (Clauses property), 515 Unsatisfiable (in module conda.resolve), 697 unsatisfiable_hints (Context attribute), 457

unsatisfiable_hints_check_depth (Context attribute). 457 UnsatisfiableError, 584 unset_description (in module conda_env.cli.main_vars), 730 unset_environment_env_vars() (PrefixData method). 563unset_example (in module conda_env.cli.main_vars), 730 unset_var_tmpl (_Activator attribute), 411 unset_var_tmpl (CmdExeActivator attribute), 414 unset_var_tmpl (CshActivator attribute), 413 unset_var_tmpl (FishActivator attribute), 414 unset_var_tmpl (PosixActivator attribute), 412 unset_var_tmpl (PowerShellActivator attribute), 415 unset_var_tmpl (XonshActivator attribute), 413 untracked() (in module conda.misc), 633 untreeify() (in module conda.models.version), 665 UPDATE (Commands attribute), 486, 709 update() (*History method*), 628 UPDATE_ALL (UpdateModifier attribute), 448 UPDATE_DEPS (UpdateModifier attribute), 448 update_file_in_place_as_binary() (in module conda.gateways.disk.update), 609 update_modifier (Context attribute), 457 update_prefix() (in module conda.core.portability), 561 update_specs (PrefixSetup attribute), 549 UPDATE_SPECS (UpdateModifier attribute), 448 update_to() (ProgressBar method), 511 updated_precs (ChangeReport attribute), 550 UpdateHistoryAction (class in conda.core.path_actions), 558 UpdateModifier (class in conda.base.constants), 448 UpdateModifier (in module conda.api), 416 url (ChannelNoticeResponse attribute), 672 Url (class in conda.common.url), 535 url (PackageInfo attribute), 651 url (PackageRecord attribute), 658, 718 url() (Channel method), 623, 635 url() (MultiChannel method), 636 url_attrs (in module conda.common.url), 535 url_channel_wtf (Channel property), 622, 635 URL_KEY (in module conda.gateways.repodata), 623 url_pat (in module conda.misc), 633 url_to_path() (in module conda.common.path), 519 url_to_s3_info() (in module conda.common.url), 535 url_w_credentials (RepodataFetch attribute), 626 url_w_repodata_fn (RepodataFetch property), 625 url_w_repodata_fn (SubdirData property), 568 url_w_subdir (RepodataFetch attribute), 626 urlparse() (in module conda.common.url), 535 urls() (Channel method), 623, 635

UrlsData (class in conda.core.package_cache_data), 553 use_index_cache (Context attribute), 455 use_local (Context attribute), 456 use_only_tar_bz2 (Context property), 454 user_agent (ExceptionHandler property), 579 user_agent() (Context method), 458 user_cache_dir (AppDirs property), 385 user_cache_dir (EnvAppDirs property), 592 user_cache_dir() (in module conda._vendor.appdirs), 384 user_data_dir (AppDirs property), 385 user_data_dir (EnvAppDirs property), 592 user_data_dir() (in module conda._vendor.appdirs), 383 user_data_dir() (in module conda.base.context), 452 user_log_dir (AppDirs property), 385 user_log_dir (*EnvAppDirs property*), 592 user_log_dir() (in module conda._vendor.appdirs), 385 user_rc_path (in module conda.base.context), 452 username() (BinstarSpec method), 576, 578 Using conda for your project, 118 Using non-standard certificates, 72 Using the .condarc conda configuration file, 72 utf8_writer() (in module conda.auxlib.compat), 423 Utf8NamedTemporaryFile() (in module conda.auxlib.compat), 423 V valid() (Resolve method), 697 valid2() (Resolve method), 698 VALID_KEYS (in module conda.env.env), 572 valid_name() (BinstarSpec method), 575, 578 valid_package() (BinstarSpec method), 575, 578 validate() (Entity method), 436 validate() (Field method), 432 validate() (ListField method), 435

- validate_all() (Configuration method), 506

- validate_keys() (in module conda.env.env), 572

- ValidationError, 438, 498
- value() (ArgParseRawParameter method), 500
- value() (DefaultValueRawParameter method), 500

value() (EnvRawParameter method), 499 value() (RawParameter method), 499 value() (YamlRawParameter method), 500 ValueEnum (class in conda.base.constants), 449 valueflags() (ArgParseRawParameter method), 500 valueflags() (DefaultValueRawParameter method), 500 valueflags() (EnvRawParameter method), 500 valueflags() (RawParameter method), 499 valueflags() (YamlRawParameter method), 500 values() (PackageCacheData method), 553, 621, 717 var_description(in module conda_env.cli.main_vars), 729 var_example (in module conda_env.cli.main_vars), 729 ver_eval() (in module conda.models.version), 662 verbose (Context property), 454 verbosity (Context property), 454 verified (Action property), 556 verify() (_Action method), 556 verify() (SignatureVerification method), 721 verify() (CacheUrlAction method), 559 verify() (CompileMultiPycAction method), 558 verify() (CreateInPrefixPathAction method), 556 verify() (ExtractPackageAction method), 560 verify() (in module conda.exports), 591 verify() (LinkPathAction method), 557 verify() (PrefixReplaceLinkAction method), 557 (RegisterEnvironmentLocationAction verify() method), 558 verify() (RemoveFromPrefixPathAction method), 559 verify() (UnlinkLinkTransaction method), 550 verify() (UnregisterEnvironmentLocationAction method), 559 verify_specs() (Resolve method), 698 verify_threads (Context property), 453 version (CondaVirtualPackage attribute), 378, 688, 696 version (Dist attribute), 638 version (DistDetails attribute), 637 version (in module conda._version), 409 version (MatchSpec property), 645 version (PackageInfo property), 651 version (PackageRecord attribute), 658, 717 version (PythonDistribution property), 524 version (PythonDistributionMetadata property), 526 version() (in module conda._vendor.distro), 402 version() (LinuxDistribution method), 405 version_cache (in module conda.models.version), 662 version_check_re (in module conda.models.version), 662 VERSION_IDENTIFIER (in module conda.common.pkg_formats.python), 530 version_key() (Resolve method), 699

- version_parts() (LinuxDistribution method), 405
- version_relation_re (in module conda.models.version), 665
- VERSION_TUPLE (in module conda._version), 409
- version_tuple (in module conda._version), 409
- VersionMatch (in module conda.models.version), 666
- VersionOrder (*class in conda.models.version*), 662
- VersionSpec (class in conda.models.version), 666
- View command line help, 49
- viewed_channel_notices (ChannelNoticeResultSet attribute), 671
- VIRTUAL_PRIVATE_ENV (PackageType attribute), 641
- VIRTUAL_PYTHON_EGG_LINK (*PackageType attribute*), 642
- VIRTUAL_PYTHON_EGG_MANAGEABLE (*PackageType attribute*), 641
- VIRTUAL_PYTHON_EGG_UNMANAGEABLE (PackageType attribute), 641
- VIRTUAL_PYTHON_WHEEL (PackageType attribute), 641
- VIRTUAL_SYSTEM (*PackageType attribute*), 642

VSPEC_TOKENS (in module conda.models.version), 664

W

walk_prefix() (in module conda.misc), 633 warn (PathConflict attribute), 448 warn (SafetyChecks attribute), 448 WARNING (NoticeLevel attribute), 450 which() (in module conda.common.path), 520 which_or_where (in module conda.testing.integration), 708 which_package() (in module conda.cli.main_package), 483 which_prefix() (in module conda.cli.main_package), 483 win (Platform attribute), 640 win_conda_bat_redirect() (in module conda.exports), 591 win_path_backout() (in module conda.common.path), 520 win_path_double_escape() (in module conda.common.path), 520 win_path_ok() (in module conda.common.path), 519 win_path_to_cygwin() (in module conda.utils), 722 win_path_to_unix() (in module conda.common.path), 520 windows_python_entry_point_exe (PathType attribute), 641 windows_python_entry_point_script (PathType at-

- tribute), 641
 winreg_arch_string_raw() (DataSource static
- winreg_arch_string_raw() (DataSource statio method), 389, 396

- winreg_hz_actual() (DataSource static method), 389, 396
- winreg_processor_brand() (DataSource static method), 389, 396
- withext() (in module conda.gateways.repodata.jlap.fetch), 616
- wmic_cpu() (DataSource static method), 389, 396
- Working with environments, 118
- Working with packages, 118
- working_state_reset() (SolverStateContainer method), 566
- wrap_subprocess_call() (in module conda.utils), 723
- writable_caches() (PackageCacheData class method), 553, 621, 716
- write() (HashWriter method), 616
- write() (JLAP method), 614
- write() (Trace method), 388, 394
- write_out() (ExceptionHandler method), 579
- write_specs() (History method), 629

Х

- x86 (Arch attribute), 639
 e), x86_64 (Arch attribute), 639
 X_MARK (in module conda.plugins.subcommands.doctor.health_checks), 684
 - XonshActivator (class in conda.activate), 413
 Xor() (Clauses method), 491, 516

Y

YAML_EXTENSIONS	(in	module	
conda.common.configuration), 505			
<pre>yaml_round_trip_dump()</pre>	(in	module	
conda.common.serialize), 531			
<pre>yaml_round_trip_load()</pre>	(in	module	
conda.common.serialize), 531			
<pre>yaml_safe_dump()</pre>	(in	module	
conda.common.serialize), 531			
<pre>yaml_safe_load()</pre>	(in	module	
conda.common.serialize), 531			
YamlFileSpec (class in conda.env.specs), 578			
<pre>YamlFileSpec (class in conda.env.specs.yaml_file), 576</pre>			
YamlRawParameter	(class	in	
conda.common.configuration), 500			

Ζ

z (Arch attribute), 639 ZERO (ERROR attribute), 493 zos (Platform attribute), 640 ZstdRepoInterface (class in conda.gateways.repodata.jlap.interface), 618